INDEXES TO THE JOURNAL

compiled by the

American Ceramic Society

VOL. 55, NO. 12 **DECEMBER 1972**

AUTHOR INDEX TO THE JOURNAL

Numbers in parentheses refer to *monthly* issue of *The Journal;* numbers following are *page* numbers.

Abdel-Azim, M. S., and Vlajic, M. Method for determining particle size (10) 535.

Abdel-Latif, A. I. A., and Day, D. E. Internal friction of proton-exchanged $Li_2O.Al_2O_3.2SiO_2$ glass (5) 254; Internal friction of ion- exchanged $Li_2O.Al_2O_3.2SiO_2$ glass (6) 279.

Aggarwal, I. D., Moynihan, C. T., Macedo, P. B., Mecholsky, J. J., and Srinivasan, G. R. Glass formation in the pseudobinary metallic selenide systems M_mSe_n-$Ge_{1.5}As_{0.5}Se_3$ (7) 366.

Ajiri, Koichi See Setaka, Nobuo

Aksay, I. A. See Davis, R. F.

Anderson, H. U. See Conger, G. J.

Angers, R. See Hajmrle, K. ; St-Jacques, R. G.

Angers, R., Tremblay, R., and Chaklader, A. C. D. Formation of $CaZrO_3$ by solid-state reaction between CaO and ZrO_2 (8) 425.

Anju, Y. See Kato, A.

Arafa, Salah Titanium centers induced in borate glasses by irradiation (3) 137.

Armstrong, P. E. See Wagner, P.

Ash, B. See Fort, A.

Baes, C. F., Jr. See Bamberger, C. E.

Bamberger, C. E., and Baes, C. F., Jr. Equilibria of SiF_4 with SiO_2, Be_2SiO_4, and BeO in molten Li_2BeF_4 (11) 564.

Bang, O. See Christensen, N. H.

Bannister, M. J. See Woolfrey, J. L.

Bell, H., Krishnamachari, V., and Jones, J. T. Recovery of high- temperature creep-resistant substructure in rutile (1) 6.

Bergeron, C. G. See Eagan, R. J.

Berger, R. L. See Klemm, W. A.

Bilde-Soerensen, J. B. Dislocation structures in creep-deformed polycrystalline MgO (12) 606.

Blachere, J. R., and Young, J. E. Freezing point of water in porous glass (6) 306.

Boesch, L. P. See Provenzano, V.

Bollin, P. L. Glass formation in the system Cs_2O-Al_2O_3-SiO_2 (9) 483.

Bolwijn, P. T. See Schipper, D. J.

Bourque, L. R. See Hastings, I. J.

Brabers, M. J. See De Maayer, P.

Bradt, R. C. See Coppola, J. A.

Breedis, J. F. See Shaw, R. R.

Brizes, W. F., and Brody, H. D. Modification of the Nb-C phase diagram (5) 277.

Brockman, F. G. Nickel-zinc ferrites: IV. Zero anisotropy in stoichiometric 50NiO/50ZnO ferrite containing 0.5 mol % Co O— relation between 60-Hz and 2.5-MHz magnetic losses (1) 28.

Brody, H. D. See Brizes, W. F.

Brook, R. J. Effect of TiO_2 on the initial sintering of Al_2O_3 (2) 114.

Brown, J. J., Jr. Phase equilibria in the system SrO-CdO-V_2O_5 (10) 500. See Fields, J. M., Jr.

Brown, L. M. See Mazdiyasni, K. S.

Brown, L. M., and Mazdiyasni, K. S. Cold pressing and low-temperature sintering of alkoxy-derived PLZT (11) 541.

Buessem, W. R., and Gruver, R. M. Computation of residual stresses in quenched Al_2O_3 (2) 101.

Burns, G. See Scott, B. A.

Burte, A. S., and Nicholson, P. S. Influence of anisotropy and water vapor on the solid-state reaction of CaO and β-quartz (9) 469.

Calderwood, F. W. See Manning, W. R.

Carlson, D. E. See Goldstein, Bernard

Carlson, D. E., Hang, K. W., and Stockdale, G. F. Electrode "polarization" in alkali-containing glasses (7) 337.

Carnall, E., Jr. Hot-pressing of ZnS and CdTe (11) 582.

Carniglia, S. C. Reexamination of experimental srength-vs-grain-size data for ceramics (5) 243; Working model for porosity effects on the uniaxial strength of ceramics (12) 610.

Chaklader, A. C. D. See Angers, R. ; Rao, A. S.

Chang, R. H., and Wagner, J. B., Jr. Direct-current conductivity and iron tracer diffusion in hematite at high temperature (4) 211.

Chase, A. B. See Osmer, J. A.

Chatterji, D., and Vest, R. W. Thermodynamic properties of the system indium-oxygen (11) 575.

Chatterji, S. See Wheeler, J.

Chikalla, T. D., McNeilly, C. E., and Roberts, F. P. Polymorphic modifications of Pm_2O_3 (8) 428.

Childs, B. G., Harvey, P. J., and Hallett, J. B. Optical absorption spectroscopy of ThO_2 (11) 544.

Christensen, N. H., and Bang, O. Diffusion and convection in reactions of slag with porous ceramic bodies (12) 592.

Coble, R. L. See Samanta, S. C. ; Yen, C. F.

Cocks, F. H., and Stormont, R. W. Rutile substructures in barium magnesium titanate (9) 479.

Cohen, J. B. See Hayakawa, M.

Cole, S. S., Jr. Sintering of Ag-Pd in the presence of a reactive glass (6) 296.

Collepardi, M., Marcialis, A., and Turriziani, R. Penetration of chloride ions into cement pastes (10) 534.

Conger, G. J., and Anderson, H. U. Nonstoichiometry in Ba-TiO_3 (10) 539.

Cooley, R. F., and Reed, J. S. Equilibrium cation distribution in $NiAl_2O_4$, $CuAl_2O_4$, and $ZnAl_2O_4$ spinels (8) 395.

Cooper, A. R. See Varshneya, A. K.

Cooper, A. R., Varshneya, A. K., Sarkar, S. K., Swift, J., Klein, L., and Yen, C. F. Some aspects of the thermal history of lunar glass (5) 260.

Coppola, J. A., and Bradt, R. C. Measurement of fracture surface energy of SiC (9) 455.

Coppola, J. A., Krohn, D. A., and Hasselman, D. P. H. Strength loss of brittle ceramics subjected to severe thermal shock (9) 481.

Cordone, L. G., and Martinsen, W. E. Glow-discharge apparatus for rapid sintering of Al_2O_3 (7) 380.

Cost, J. R. See Rossi, R. C.

Craig, D. F., and Hummel, F. A. Zirconium pyrovanadate transitions (10) 532.

Croft, W. J. See Galasso, F.

Crouch, A. G. High-temperature deformation of polycrystalline Fe_2O_3 (11) 558.

Curran, M. J. See Greskovich, C.

Cutler, I. B. See McAllister, P. V. ; Rao, W. R.

Cutter, I. A., and McPherson, R. Surface domain reorientation produced by abrasion and annealing of polycrystalline $BaTiO_3$ (7) 334.

Daniel, J. S. See Zikovsky, L.

Davis, R. F., Aksay, I. A., and Pask, J. A. Decomposition of mullite (2) 98.

Davis, R. F., and Pask, J. A. Diffusion and reaction studies in the system Al_2O_3-SiO_2 (10) 525.

Daw, J. D., Nicholson, P. S., and Embury, J. D. Inhomogeneous dehydroxylation of talc (3) 149.

Day, D. E. See Abdel-Latif, A. I. A. ; Fleming, J. W., Jr.

Dear, P. S. See Fields, J. M., Jr.

De Bruyne, R. See De Maayer, P.

Deganello, Sergio A high-temperature modification of γ-Na_3BeF_4 (11) 584.

De Luca, J. P., and Leitnaker, J. M. Phase behavior in the Pu-Cr-N system (5) 273.

De Maayer, P., De Bruyne, R., and Brabers, M. J. Decomposition temperature of $Th(WO_4)_2$ (2) 113.

Demirel, T. See Huang, R. J.

de Wet, J. D. See Vail, J. W.

Diamond, Sidney Interactions between cement minerals and hydroxycarboxylic-acid retarders: II, Tricalcium ion (4) 177; Interactions between cement minerals and hydroxycarboxylic-acid retarders: III, Infrared spectral identification of the aluminosalicylate complex (8) 405.

DiMarcello, F. V., Key, P. L., and Williams, J. C. Preferred orientation in Al_2O_3 substrates (10) 509.

DiSalvo, Raymond, Roy, D. M., and Mulay, L. N. EPR studies of radiation damage in hydrogen-impregnated glass (10) 536.

Donald, I. W., and McCurrie, R. A. Microstructure and indentation hardness of an MgO-Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramic (6) 289.

Douglass, D. L. See Kumar, A.

Dozier, A. W., Wilson, L. K., Friebele, E. J., and Kinser, D. L. Correlation of structure and electrical properties of 55FeO-45P_2O_5 glass (7) 373.

Durden, L. R. See Eusner, P. R.

Eagan, R. J., and Bergeron, C. G. Determination of water in lead borate glasses (1) 53.

Ely, Richard Strength of titania and aluminum silicate under combined stresses (7) 347.

Embury, J. D. See Daw, J. D.

Eryou, N. D. See Jeryan, R. A.

Eusner, P. R., Durden, L. R., and Slack, L. H. Unusual electrical effects in As-Te semiconducting glasses (1) 43.

Eustache, J., and Magnan, R. Method for determining resistance of mortars to sulfate attack (5) 237.

Evans, J. H. See Mahajan, S.

Eysel, W. See Pieper, G.

Farnum, E. H. See McVay, G. L.

Fennelly, T. J., and Reed, J. S. Mechanics of pressure slip casting (5) 264; Compression permeability of Al_2O_3 cakes formed by pressure slip casting (8) 381.

Fields, J. M., Jr., Dear, P. S., and Brown, J. J., Jr. Phase equilibria in the system BaO-SrO-SiO_2 (12) 585.

Fierens, Paul, and Verhaegen, J. P. Structure and reactivity of chromium-doped tricalcium silicate (6) 309.

Fine, M. E. See Kruse, E. W., III ; Marcus, H. L.

Fleming, J. W., Jr., and Day, D. E. Relation of alkali mobility

and mechanical relaxation in mixed-alkali silicate glasses (4) 186.
Fort, A., Sharp, D., Ash, B., Papworth, K., and Reed, D. Influence of liquid environments on the strength of ferrite memory cores (6) 329.
Freiman, S. W., and Hench, L. L. Effect of crystallization on the mechanical properties of Li_2O-SiO_2 glass-ceramics (2) 86.
Freiman, S. W., Onoda, G. Y., Jr., and Pincus, A. G. Controlled spherulitic crystallization in $3BaO$-$5SiO_2$ glass (7) 354.
Friebele, E. J. See Dozier, A. W.
Friebele, E. J., Wilson, L. K., and Kinser, D. L. Magnetic behavior and microstructure of vanadium phosphate glasses (3) 164.
Fujiki, Y., Mitsuhashi, T., and Suzuki, Y. Hydrothermal growth and etching of ZrO_2 crystals (4) 222.
Fulrath, R. M. See Holman, R. L.

Galasso, F., Kuntz, U., and Croft, W. J. Pyrolytic Si_3N_4 (8) 431.
Gallagher, P. K. See Johnson, D. W., Jr.
Garcia, D., and Speidel, D. Reexamination of the system TiO_2-SnO_2 (6) 322.
Garvie, R. C., and Nicholson, P. S. Structure and thermomechanical properties of partially stabilized zirconia in the CaO-ZrO_2 system (3) 152; Phase analysis in zirconia systems (6) 303.
Gazza, G. E. Hot-pressing of $LiAl_5O_8$ (3) 172.
Gebauer, J. See Hasselman, D. P. H.
Gebauer, J., Hasselman, D. P. H., and Thomas, D. A. Effect of temperature on the strength of a polymer-impregnated porous ceramic (3) 175.
Gebauer, J., Krohn, D. A., and Hasselman, D. P. H. Thermal-stress fracture of a thermomechanically strengthened aluminosilicate ceramic (3) 198.
Glicksman, L. R. See Jeryan, R. A.
Gokhale, K. V. G. K. See Maiti, H. S.
Goldstein, Bernard, and Carlson, D. E. Determination of the composition of glass surfaces by Auger spectroscopy (1) 51.
Gooch, D. J., and Groves, G. W. Prismatic slip in sapphire (2) 105.
Gordon, R. S. See Marchant, D. D.
Gordon, R. S., and Terwilliger, G. R. Transient creep in Fe-doped polycrystalline MgO (9) 450.
Greskovich, C., and Lay, K. W. Grain growth in very porous Al_2O_3 compacts (3) 142.
Greskovich, C., O'Clair, C. R., and Curran, M. J. Preparation of transparent Y_2O_3-doped ThO_2 (6) 324.
Griffiths, C. R., and Russell, R., Jr. Time effects in the hysteresis loop of $(Pb,Sr)TiO_3$ (2) 110.
Grossman, D. G. Machinable glass-ceramics based on tetrasilicic mica (9) 446.
Groves, G. W. See Gooch, D. J.
Gruver, R. M. See Buessem, W. R.
Guha, J. P., and Kolar, D. Identification of $BaO.4TiO_2.Al_2O_3$ in the system BaO-TiO_2-Al_2O_3 (1) 55.
Gulden, T. D. Carbon thermal diffusion in the UC_2-C system (1) 14.
Gupta, T. K. Strength degradation and crack propagation in thermally shocked Al_2O_3 (5) 249; Possible correlation between density and grain size during sintering (5) 276; Strength behavior of thermally shocked ZnO (8) 429.

Haas, L. A. See Khalafalla, S. E.
Haerdtl, K. H., and Hennings, D. Distribution of *A*-site and *B*-site vacancies in $(Pb,La)(Ti,Zr)O_3$ ceramics (5) 230.
Hahn, T. See Pieper, G.
Hajmrle, K., and Angers, R. Method of studying sintering by electron microscopy (3) 173.
Halbfinger, G. P., and Kolodney, Morris Activated sintering of ThO_2 and ThO_2-Y_2O_3 with NiO (10) 519.
Hallett, J. B. See Childs, B. G.
Hancock, J. D., and Sharp, J. H. Method of comparing solid-state kinetic data and its application to the decomposition of kaolinite, brucite, and $BaCO_3$ (2) 74.
Hang, K. W. See Carlson, D. E.
Hara, Hiroshi See Shimizu, Takashi
Harding, F. L. Dependence of melt oxygen activity and water retention on composition of amber glass (7) 368.
Haroun, N. A. Reply to "Discussion of 'Effect of additives on sintering of CaF_2'" (6) 328.
Harvey, P. J. See Childs, B. G.
Hasselman, D. P. H. See Coppola, J. A.; Gebauer, J.; Krohn, D. A.; Penty, R. A.; Steiner, C. J. P.
Hasselman, D. P. H., Gebauer, J., and Manson, J. A. Elastic behavior of polymer-impregnated porous ceramics (12) 588.
Hastings, I. J., MacEwan, J. R., and Bourque, L. R. Effect of swelling on thermal conductivity and postirradiation densification of U_3Si (5) 240.
Hayakawa, M., Cohen, J. B., and Reed, T. B. Measurement of the lattice parameter of wustite at high temperatures (3) 160.
Hayakawa, S. See Matsuoka, T.
Hench, L. L. See Freiman, S. W.
Hennings, D. See Haerdtl, K. H.
Herman, H., and MacCrone, R. K. Comments on "Separation of phases by spinodal decomposition in the systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3 (1) 50.
Herron, R. H. See Leonard, R. J.
Higgins, T. J., Macedo, P. B., and Volterra, V. Mechanical and ionic relaxation in $Na_2O.3SiO_2$ glass (10) 488.
Holcombe, C. E., Jr., and Horne, O. J., Jr. Preparation of boron suboxide, B_7O (2) 106.
Holman, R. L., and Fulrath, R. M. Intrinsic nonstoichiometry in single-phase $Pb(Zr_{0.5}Ti_{0.5})O_3$ (4) 192.
Horne, O. J., Jr. See Holcombe, C. E., Jr.
Huang, R. J., Demirel, T., and McGee, T. D. Adsorption of water vapor on E-glass (8) 399.
Hulscher, W. S., and Jonker, G. H. Comment on "Electron diffraction superlattice lines in magnesium ferrite" (12) 632.
Hummel, F. A. See Craig, D. F.; Richerson, D. W.
Hunter, O., Jr. See Manning, W. R.

Inagaki, Michio See Naka, Shigeharu
Ito, Suketoshi See Naka, Shigeharu

Janowski, K. R. See Rossi, R. C.
Jeryan, R. A., Eryou, N. D., and Glicksman, L. R. Optical method of measuring temperature in hot glass (2) 71.
Johnson, D. L. Discussion of "Effect of additives on sintering of CaF_2" (6) 327. See Venkatu, D. A.
Johnson, D. W., Jr., and Gallagher, P. K. Kinetics of the thermal decomposition of $BeSO_4$ (5) 232.
Johnstone, J. K. See Stacy, D. W.
Jones, J. T. See Bell, H.
Jonker, G. H. Nature of aging in ferroelectric ceramics (1) 57. See Hulscher, W. S.
Jungquist, G. E. See Ownby, P. D.
Kato, A., and Anju, Y. Expansion of Ag_2O lattice by annealing (1) 25.
Kato, A., Nishibashi, R., Nagano, M., and Mochida, I. Relative activity of oxygen ions in molten sodium phosphate as determined from the solubility of sulfur trioxide (4) 183.
Key, P. L. See DiMarcello, F. V.
Khalafalla, S. E., and Haas, L. A. Kinetics of carbothermal reduction of quartz under vacuum (8) 414.
King, G. A. See Ridge, M. J.
Kinser, D. L. See Dozier, A. W.; Friebele, E. J.
Klein, L. See Cooper, A. R.
Klemm, W. A., and Berger, R. L. Calcination and cementing properties of $CaCO_3$-SiO_2 mixtures (10) 485.
Kolar, D. See Guha, J. P.
Kolodney, Morris See Halbfinger, G. P.
Konishi, A. See Kunugi, M.
Krause, J. T., and O'Bryan, H. M., Jr. Acoustic detection of ferroelectric phase transitions in PLZT ceramics (10) 497.
Kreidler, E. R. Phase equilibria in the system CaO-BaO-WO_3 (10) 514.
Krishnamachari, V. See Bell, H.
Krohn, D. A. See Coppola, J. A.; Gebauer, J.
Krohn, D. A., and Hasselman, D. P. H. Static and cyclic fatigue behavior of a polycrystalline alumina (4) 208.
Kruse, E. W., III, and Fine, M. E. Precipitation strengthening of MgO by $MgFe_2O_4$ (1) 32.
Kumar, A., Rajdev, D., and Douglass, D. L. Effect of oxide defect structure on the electrical properties of ZrO_2 (9) 439.
Kuntz, U. See Galasso, F.
Kunugi, M., Soga, N., Sawa, H., and Konishi, A. Thermal conductivity of cristobalite (11) 580.
Kuwano, Y., and Shiroki, K. Preparation of neodymium hydroxide by vapor-phase reaction (7) 378.

Langdon, T. G. Grain-boundary sliding in ceramics (8) 430; Dependence of creep rate on porosity (12) 630.
Lay, K. W. See Greskovich, C.
Leitnaker, J. M. See De Luca, J. P.
Leonard, R. J., and Herron, R. H. Significance of oxidation-reduction reactions within BOF refractories (1) 1.
Leonesio, R. B. Fracture and healing effects in mica crystals (9) 437.
Lessoff, H. Comments on "Influence of liquid environments on the strength of ferrite memory cores" (6) 330.
Lindemer, T. B. Kinetics of the UO_2-C-N_2 reaction at 1700°C (12) 601.
Litvan, G. G. Phase transitions of adsorbates: IV, Mechanism of frost action in hardened cement paste (1) 38.
Lynch, R. W., and Morosin, B. Thermal expansion, compressibility, and polymorphism in hafnium and zirconium titanates (8) 409.
MacCrone, R. K. See Herman, H.
Macedo, P. B. See Aggarwal, I. D.; Higgins, T. J.; Provenzano, V.
MacEwan, J. R. See Hastings, I. J.
Mackenzie, J. D. See Sakka, S.
MacKenzie, K. J. D. Infrared frequency calculations for ideal mullite $(3Al_2O_3.2SiO_2)$ (2) 68.
Magnan, R. See Eustache, J.
Mahajan, S., Evans, J. H., and Wilyman, P. Stacking faults and twins in nonstoichiometric MoC (3) 174.
Maiti, H. S., Gokhale, K. V. G. K., and Subbarao, E. C. Kinetics and burst phenomenon in ZrO_2 transformation (6) 317.
Manghnani, M. H. Pressure and temperature dependence of the elastic moduli of Na_2O-TiO_2-SiO_2 glasses (7) 360.
Manning, W. R., Hunter, O., Jr., Calderwood, F. W., and Stacy, D. W. Thermal expansion of Nb_2O_5 (7) 342.
Manson, J. A. See Hasselman, D. P. H.
Marchant, D. D., and Gordon, R. S. Grain size distributions and grain growth in MgO and MgO-Fe_2O_3 solid solutions (1) 19.
Marchese, B., Mascolo, G., and Sersale, R. Relation of composition of hydrogarnet to resistance to sulfate attack (3) 146.
Marcialis, A. See Collepardi, M.
Marcus, H. L., and Fine, M. E. Grain-boundary segregation in MgO-doped Al_2O_3 (11) 568.
Marlowe, M. O. Simulation of gaseous fission products in UO_2 (7) 379.
Marshall, Ann See Schnaus, U. E.
Martinsen, W. E. See Cordone, L. G.
Mascolo, G. See Marchese, B.
Matsuoka, T., Matsuo, Y., Sasaki, H., and Hayakawa, S. Preparation and characterization of Cd_2TiWO_7 (2) 106; PTCR behavior of $BaTiO_3$ with Nb_2O_5 and MnO_2 additives (2) 108.
Matsuo, Y. See Matsuoka, T.
Mazdiyasni, K. S. See Brown, L. M.
Mazdiyasni, K. S., and Brown, L. M. Synthesis and mechanical properties of stoichiometric aluminum silicate (mullite) (11) 548; Synthesis of Nb_2O_5-doped $BaTiO_3$ with improved electrical properties (12) 633.
McAllister, P. V., and Cutler, I. B. Thermal grooving of MgO and Al_2O_3 (7) 351.
McCurrie, R. A. See Donald, I. W.
McDaniel, C. L. Phase relations in the CaO-Pt system in air (8) 426.
McGee, T. D. See Huang, R. J.
McNeilly, C. E. See Chikalla, T. D.
McPherson, R. See Cutter, I. A.
McVay, G. L., and Farnum, E. H. Atmosphere effects on Na diffusion in glass (5) 275.
Mecholsky, J. J. See Aggarwal, I. D.
Mehta, P. K. Stability of ettringite on heating (1) 55.
Meitzler, A. H., and O'Bryan, H. M., Jr. Lanthanum dependence of elastic and piezoelectric properties of PLZT ceramics with a Zr/Ti ratio of 65/35 (10) 504.
Miller, A. D. See Sarkar, S. K.
Minagawa, Shigekazu Kinetics of growth of Al_2O_3 whiskers (2) 77.
Mitchell, P. W. D. Chemical method for preparing $MgAl_2O_4$ spinel (9) 484.
Mitsuhashi, T. See Fujiki, Y.
Mochida, I. See Kato, A.
Morosin, B. See Lynch, R. W.
Moynihan, C. T. See Aggarwal, I. D.; Provenzano, V.; Schnaus, U. E.
Mueller, J. I. See Sarkar, S. K.
Mulay, L. N. See DiSalvo, Raymond

Nafziger, R. H., and Riazance, N. Alkaline-earth-fluoride-LaF_3 systems with implications for electroslag melting (3) 130.
Nagano, M. See Kato, A.
Naka, Shigeharu, Ito, Suketoshi, and Inagaki, Michio Effect of shear on the quartz-coesite transition (6) 323.
Nelson, J. A. See Wurst, J. C.
Nemeth, J., Youdelis, W. V., and Parr, J. G. High-temperature creep behavior of polycrystalline $SrZrO_3$ (3) 125.
Newman, R. L. Prediction of thermal-shock resistance during heating at very high rates (9) 464.
Nicholson, P. S. See Burte, A. S.; Daw, J. D.; Garvie, R. C.
Nishibashi, R. See Kato, A.

O'Bryan, H. M., Jr. See Krause, J. T.; Meitzler, A. H.
O'Clair, C. R. See Greskovich, C.
Onoda, G. Y., Jr. See Freiman, S. W.
O'Rourke, J. A. See Wagner, P.
Osmer, J. A., and Chase, A. B. Crystallization of BeO, Be_2SiO_4, and SiO_2 from Li_2MoO_4-MoO_3 (6) 292.
Ownby, P. D., and Jungquist, G. E. Final sintering of Cr_2O_3 (9) 433.

Papworth, K. See Fort, A.
Parr, J. G. See Nemeth, J.
Pask, J. A. See Davis, R. F.
Penty, R. A., Hasselman, D. P. H., and Spriggs, R. M. Young's modulus of high-density polycrystalline mullite (3) 169.
Piche, E. W., and Rubin, G. A. Effect of pressure on the dielectric strength of sapphire (11) 578.
Pieper, G., Eysel, W., and Hahn, T. Solid solubility and polymorphism in the system Sr_2SiO_4-Sr_2GeO_4-Ba_2GeO_4-Ba_2SiO_4 (12) 619.
Pincus, A. G. See Freiman, S. W.
Provenzano, V., Boesch, L. P., Volterra, V., Moynihan, C. T., and Macedo, P. B. Electrical relaxation in $Na_2O.3SiO_2$ glass (10) 492.

Queeney, R. A. See Stinchcomb, W. W.
Rajdev, D. See Kumar, A.
Rao, A. S., and Chaklader, A. C. D. Plastic flow during hot-pressing (12) 596.
Rao, W. R., and Cutler, I. B. Initial sintering and surface diffusion in Al_2O_3 (3) 170.
Rasmussen, J. J. Surface tension, density, and volume change on melting of Al_2O_3 systems, Cr_2O_3, and Sm_2O_3 (6) 326.
Reed, D. See Fort, A.
Reed, J. S. See Cooley, R. F., Fennelly, T. J.
Reed, T. B. See Hayakawa, M.
Rhee, S. K. Wetting of TaC by liquid Cu and liquid Ag (3) 157; Critical surface energies of Al_2O_3 and graphite (6) 300; Discussion of "Porosity effects in polycrystalline graphite" (11) 580.
Riazance, N. See Nafziger, R. H.
Rice, R. W. Deformation, recrystallization, strength, and fracture of press-forged ceramic crystals (2) 90.
Richards, C. W. See Sellevold, E. J.
Richerson, D. W., and Hummel, F. A. Synthesis and thermal expansion of polycrystalline cesium minerals (5) 269.
Ridge, M. J., and King, G. A. Comments on use of reduced time in plotting kinetic data (2) 112.
Roberts, F. P. See Chikalla, T. D.
Roberts, J. T. A., and Ueda, Y. Influence of porosity on deformation and fracture of UO_2 (3) 117.
Roehrig, F. K., and Wright, T. R. Carbide synthesis by freeze-

drying (1) 58.
Roskovec, V. See Sestak, J.
Rossi, R. C., Cost, J. R., and Janowski, K. R. Influence of the shape of dispersed particles on the elastic behavior of composite materials (5) 234.
Roy, D. M. See DiSalvo, Raymond
Roy, Rustum See Takamori, Takeshi
Rubin, G. A. See Piche, E. W.
Russell, R., Jr. See Griffiths, C. R.

Sakka, S., and Mackenzie, J. D. Phototropic glasses activated by TlCl (11) 553.
Sakka, Sumio See Yamamoto, Tokuji
Samanta, S. C., and Coble, R. L. Correlation of grain size and density during intermediate-stage sintering of Ag (11) 583.
Sarkar, S. K. See Cooper, A. R.
Sarkar, S. K., Miller, A. D., and Mueller, J. I. Solubility of oxygen in ZrC (12) 628.
Sasaki, H. See Matsuoka, T.
Sawa, H. See Kunugi, M.
Schipper, D. J., van Doorn, C. Z., and Bolwijn, P. T. Preparation of cathodochromic sodalites (5) 256.
Schnaus, U. E., Marshall, Ann, and Moynihan, C. T. Heat capacities of glasses and liquids in the pseudobinary system $Ge_xAs_{40-x}S_{60}$ (4) 180.
Schultz, A. H., and Stubican, V. S. Reply to "Comments on 'Separation of phases by spinodal decomposition in the systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3'" (1) 50.
Scott, B. A., and Burns, G. Determination of stoichiometry variations in $LiNbO_3$ and $LiTaO_3$ by Raman powder spectroscopy (5) 225; Crystal growth and observation of the ferroelectric phase of $PbZrO_3$ (7) 331.
Sellevold, E. J., and Richards, C. W. Short-time creep transition for hardened cement paste (6) 284.
Sersale, R. See Marchese, B.
Sestak, J., Zaveta, K., Roskovec, V., and Zounova, F. Preparation and magnetic properties of the glassy system MnO-Fe_2O_3-B_2O_3 (10) 537.
Setaka, Nobuo, and Ajiri, Koichi Influence of vapor-phase composition on morphology of SiC single crystals (10) 540.
Sharp, D. See Fort, A.
Sharp, J. H. See Hancock, J. D.
Shaw, R. R., and Breedis, J. F. Secondary phase separation in lead borate glasses (8) 422.
Shelby, J. E. Helium migration in natural and synthetic vitreous silica (2) 61; Helium migration in TiO_2-SiO_2 glasses (4) 195.
Shimizu, Takashi, and Hara, Hiroshi Oxidation of CO on La_2O_3-doped $BaTiO_3$ (10) 533.
Shiroki, K. See Kuwano, Y.
Slack, L. H. See Eusner, P. R.
Soga, N. See Kunugi, M.
Solomon, A. A. Influence of impurity particles on the fracture of UO_2 (12) 622.
Solovyev, G. I., and Spear, K. E. Phase behavior in the Sm-B system (9) 475.
Sorrell, C. A. PbO transformation induced by water (1) 47.
Spear, K. E. See Solovyev, G. I.
Speidel, D. See Garcia, D.
Spriggs, R. M. See Penty, R. A. ; Steiner, C. J. P.
Srinivasan, G. R. See Aggarwal, I. D.
Stacy, D. W. See Manning, W. R.
Stacy, D. W., Johnstone, J. K., and Wilder, D. R. Axial thermal expansion of HfO_2 (9) 482.
Steiner, C. J. P., Spriggs, R. M., and Hasselman, D. P. H. Synergetic pressure-sintering of Al_2O_3 (2) 115.
Stinchcomb, W. W., and Queeney, R. A. High-temperature fatigue fracture initiation in MgO single crystals (1) 11.
St-Jacques, R. G., and Angers, R. Creep of CaO-stabilized ZrO_2 (11) 571.
Stockdale, G. F. See Carlson, D. E.
Stormont, R. W. See Cocks, F. H.
Stubican, V. S. See Schultz, A. H.
Subbarao, E. C. See Maiti, H. S.
Suzuki, Y. See Fujiki, Y.
Swanson, G. D. Fracture energies of ceramics (1) 48.
Swift, J. See Cooper, A. R.

Takamori, Takeshi, and Roy, Rustum Preparation of thin glass films for transmission electron microscopy by splat cooling (10) 538.
Tallan, N. M. See Tripp, W. C.
Tashiro, Megumi See Yamamoto, Tokuji
Terwilliger, G. R. See Gordon, R. S.
Thomas, D. A. See Gebauer, J.
Tremblay, R. See Angers, R.
Tripp, W. C., and Tallan, N. M. Revised weight change in nonstoichiometric ZrO_2 (1) 60.
Turner, J. A. See Turner, W. H.
Turner, W. H., and Turner, J. A. Ligand-field spectra and structure of nickel in silicate glasses (4) 201.
Turriziani, R. See Collepardi, M.

Ueda, Y. See Roberts, J. T. A.

Vagnard, G. See Zikovsky, L.
Vail, J. W., and de Wet, J. D. Hydrogarnet phase in kaolinite-lime-water slurries (8) 432.
van Doorn, C. Z. See Schipper, D. J.
Varshneya, A. K. See Cooper, A. R.
Varshneya, A. K., and Cooper, A. R. Diffusion in the system K_2O-SrO-SiO_2: II, Cation self-diffusion coefficients (4) 220; Diffusion in the system K_2O-SrO-SiO_2: III, Interdiffusion coefficients (6) 312; Diffusion in the system K_2O-SrO-SiO_2: IV, Mobility model, electrostatic effects, and multicomponent diffusion (8) 418; Corrections: Diffusion in the system K_2O-SrO-SiO_2: III and IV (11) 584.
Venkatu, D. A. Discussion of "Compressive creep of rutile at high temperatures" (1) 60.
Venkatu, D. A., and Johnson, D. L. Analysis of sintering equations pertaining to constant rates of heating—correction (2) 116.
Verhaegen, J. P. See Fierens, Paul .
Vest, R. W. See Chatterji, D.
Vezzoli, G. C. Electrical resistance of liquid sulfur to 420°C and of liquid selenium to 700°C (2) 65.
Vlajic, M. See Abdel-Azim, M. S.
Volterra, V. See Higgins, T. J. ; Provenzano, V.

Wagner, J. B., Jr. See Chang, R. H.
Wagner, P., O'Rourke, J. A., and Armstrong, P. E. Porosity effects in polycrystalline graphite (4) 214.
Walters, D. S., and Wirtz, G. P. Electron diffraction superlattice lines in magnesium ferrite (1) 59.
Wheeler, J., and Chatterji, S. Settling of particles in fresh cement pastes (9) 461.
Wiederhorn, S. M. A chemical interpretation of static fatigue (2) 81.
Wilder, D. R. See Stacy, D. W.
Williams, J. C. See DiMarcello, F. V.
Wilson, L. K. See Dozier, A. W. ; Friebele, E. J.
Wilyman, P. See Mahajan, S.
Wirtz, G. P. Reply to "Comment on 'Electron diffraction superlattice lines in magnesium ferrite'" (12) 632. See Walters, D. S.
Woolfrey, J. L. Effect of green density on the initial-stage sintering kinetics of UO_2 (8) 383.
Woolfrey, J. L., and Bannister, M. J. Nonisothermal techniques for studying initial-stage sintering (8) 390.
Wright, R. E. Acoustic emission of aluminum titanate (1) 54.
Wright, T. R. See Roehrig, F. K.
Wurst, J. C., and Nelson, J. A. Lineal intercept technique for measuring grain size in two-phase polycrystalline ceramics (2) 109.

Yamamoto, Tokuji, Sakka, Sumio, and Tashiro, Megumi Formation of defects in glass under electron bombardment (9) 473.
Yamaoka, Shinobu Synthesis of $PbZrS_3$ at high pressures (2) 111.
Yen, C. F. See Cooper, A. R.
Yen, C. F., and Coble, R. L. Spheroidization of tubular voids in Al_2O_3 crystals at high temperatures (10) 507.
Youdelis, W. V. See Nemeth, J.
Young, J. E. See Blachere, J. R.

Zaveta, K. See Sestak, J.
Zikovsky, L., Vagnard, G., and Daniel, J. S. Kinetics of recrystallization and grain growth in Cu_2O (3) 134.
Zounova, F. See Sestak, J.

SUBJECT INDEX TO THE JOURNAL

Volume 55, 1972

Numbers in parentheses refer to *monthly* issue of *The Journal;* number following is *page* number. Cross references are listed on page 641.

Abrasion, of $BaTiO_3$, in surface domain reorientation (7) 334.
Acids, retarders, hydroxycarboxylic, interactions with cement minerals (8) 405.
salicylic. reaction with tricalcium aluminate (4) 177.
Additives, effect on sintering of CaF_2 (6) 327.
reply (6) 328.
iron. effect on transient creep of MgO (9) 450.
Adsorption, adsorbates, phase transitions of (1) 38.
of water vapor on E-glass (8) 399.
Aging, in ferroelectric ceramics (1) 57.
Alkaline earths, fluoride, - LaF_3 systems, in electroslag melting (3) 130.
Alkalis, concentration, effect on ESR spectra of borate glasses (3) 140.
mobility. relation to mechanical relaxation in mixed-alkali silicate glass (4) 186.
Aluminosilicates, ceramic, thermal-stress fracture in (4) 198.
Aluminum, oxide, compatibility with $BaTiO_3$ (1) 55.
critical surface energy (6) 300.
crystals, spheroidization of voids in (10) 507.
density vs grain size during sintering (5) 276.
effect of melting on surface tension, density, and vol (6) 326.
glow-discharge apparatus for sintering (7) 380.
MgO-doped, grain-boundary segregation in (11) 568.
Aluminum oxide *(continued)*
polycrystalline, static and cyclic fatigue in (4) 208.
porous compacts, grain growth in (3) 142.
quenched, computation of residual stress in (2) 101.
sintering, effect of TiO_2 (2) 114; sintering and diffusion in (3) 170.
slip, mechanics of pressure slip casting (5) 264; slip cast, compression permeability of (8) 381.
substrates, preferred orientation in (10) 509.
synergetic pressure-sintering of (2) 115.
thermal grooving of (7) 351.
thermally shocked, strength degradation and crack propagation in (5) 249.
whiskers, kinetics of growth (2) 77.
silicate. stoichiometric, synthesis and mechanical properties (11) 548.
strength under stress (7) 347.
titanate. acoustic emission of (1) 54.
Analysis, of sintering equations, pertaining to constant rates of heating, correction (2) 116.
Anisotropy, effect on solid-state reaction of CaO and β quartz (9) 469.
zero. in stoichiometric Ni-Zn ferrites containing 0.5% CoO_x relation to magnetic losses (1) 28.
Annealing, of $BaTiO_3$, in surface domain reorientation (7) 334.
expansion of Ag_2O lattice by (1) 25.
Atmosphere, effects, on Na diffusion in glass (5) 275.
Barium, carbonate, decomposition, analysis of (2) 74.
Mg titanate. rutile substructures in (9) 479.
titanate. compatibility with Al_2O_3 (1) 55.
dependence on time of physical properties (1) 57.
La_2O_3-doped, oxidation of CO on (10) 533.
Nb_2O_5 doped (12) 633.
Nb_2O_5 and MnO_2, PTCR behavior (2) 108.
nonstoichiometry in (10) 539.
polycrystalline, surface domain reorientation in (7) 334.
Beryllium, Be_2SiO_4 and BeO, equilibrium with SiF_4 in molten Li_2BeF_4 (11) 564.
oxide. and Be_2SiO_4, crystallization from Li_2MoO_4-MoO_3 (6) 292.
density vs grain size during sintering (5) 276.
sulfate. kinetics of thermal decomposition (5) 232.
Boron, suboxide, B_7O, preparation (2) 106.
Bromellite, single crystals, growth of (6) 292.
Brucite, dehydroxylation, analysis of (2) 74.
Burst phenomena, in ZrO_2 transformation (6) 317.
Cadmium, Cd_2TiWO_7, preparation and characterization (2) 106.
telluride. hot-pressing of (11) 583.
Calcination, of $CaCO_3$-SiO_2 mixtures (10) 485.

Calcium, $CaCO_3$-SiO_2 mixtures, calcination and cementing properties (10) 485.
fluoride. effect of additives on sintering (6) 327; effect of additives on sintering, reply (6) 328.
oxide. and β quartz, effect of anisotropy and water vapor on solid state reaction of (9) 469.
creep of ZrO_2 stabilized with (11) 571.
- stabilized ZrO_2 (3) 152.
tricalcium. aluminate hexahydrate, effect of Si on crystallography of (3) 146.
aluminate-salicylic acid reaction (4) 177.
silicate, Cr-doped, structure and reactivity (6) 309.
zirconate. formation by solid-state reaction (8) 425.
Carbides, synthesis, by freeze-drying (1) 58.
Carbon, monoxide, oxidation on La_2O_3-doped $BaTiO_3$ (10) 533.
reaction with UO_2 and N_2 at 1700°C (12) 601.
thermal diffusion. in UC-C system (1) 14.
Cathodochromism, induction in sodalites (5) 256.
Cations, distribution, in spinels (8) 395.
Cements, minerals, interaction with hydroxycarboxylic-acid retarders (8) 405.
interactions with retarders (4) 177.
paste. fresh, particle settling in (9) 461.
hardened, creep transition (6) 284.
hardened, mechanism of frost action in (1) 38.
penetration of chloride ions (10) 534.
properties. of $CaCO_3$-SiO_2 mixtures (10) 485.
Ceramics, brittle, effect of thermal shock on strength (9) 481.
grain boundary sliding in (8) 430.
polycrystalline. two-phase, grain size measurement in (2) 109.
porous. polymer-impregnated, effect of temp. on strength (3) 175; polymer-impregnated, elastic behavior (12) 588.
strength. effect of porosity (12) 610.
Cesium, minerals, polycrystalline, synthesis and thermal expansion (5) 269.
Chemistry, of crack growth in glass (2) 81.
method. for preparing $MgAl_2O_4$ spinel (9) 484.
Chlorides, ions, penetration into cement pastes and concretes (10) 534.
Chromium, Cr_2O_3, final sintering of (9) 433.
oxide. effect of melting on surface tension, density and vol (6) 326.
Cobalt, oxide, effect on magnetic losses in Ni-Zn ferrites (1) 28.
Coesite, quartz-, transition, effect of shear (6) 323.
Composites, effect of shape of dispersed particles on elasticity (5) 234.
Compressibility, in Hf and Zr titanates (8) 409.
Compression, permeability, of slip cast Al_2O_3 (8) 381.
Computation, of residual stresses in quenched Al_2O_3 (2) 101.
Concretes, effect of ettringite in hydrated cement paste (1) 55.
penetration of chloride ions (10) 534.
Conductivity, electrical, dc, in hematite at high temps. (4) 211.
thermal. of cristobalite (11) 580.
of U_3Si, effect of swelling (5) 240.
Convection, in slag-porous ceramic reactions (12) 592.
Cooling, splat, for preparing films for transmission electron microscopy (10) 538.
Copper, $CuAl_2O_4$ spinel, equilibrium cation distribution in (8) 395.
density vs grain size during sintering (5) 276.
liquid. wetting of TaC by (3) 157.
oxide. recrystallization and grain growth (3) 134.
Corrections, for "Diffusion in the System K_2O-SrO-SiO_2: III, IV" (11) 584.
Cracks, formation, in Al titanate, detection by acoustic emission (1) 54.
propagation and strength degradation in Al_2O_3 (5) 249.
in sapphire. spheroidization of (10) 507.
Creep, of CaO-stabilized ZrO_2 (11) 571.
compressive. of rutile at high temps. (1) 60.
of Fe_2O_3. polycrystalline (11) 558.
high-temp., of $SrZrO_3$ (3) 125.
in MgO. polycrystalline (12) 606.
- resistant substructure in rutile. recovery of (1) 6.
transient. in Fe-doped polycrystalline MgO (9) 450.
transition. for hardened cement paste (6) 284.
Cristobalite, thermal conductivity of (11) 580.
Crystallization, of BeO, Be_2SiO_4, and SiO_2 from Li_2MoO_4-MoO_3 (6) 292.
controlled spherulitic. in 3 BaO-5SiO_2 glass (7) 354.
effect on mechanical properties of Li_2O-SiO_2 glass-ceramic (2) 86.
re-. of Cu_2O, kinetics of (3) 134.
of press-forged ceramic crystals (2) 90.
Crystallography, of MoC (3) 174.
Crystals, ceramic, deformation, recrystallization, strength, and fracture (2) 90.
growth. and etching of ZrO_2 (4) 223.
of $PbZrO_3$ ferroelectric phase (7) 331.
lattice. parameter of wustite at high temps. (3) 160.
parameters for Nb_2O_5 (7) 343.
sapphire. prismatic slip in (2) 105.

Decomposition, of kaolinite, brucite, and $BaCO_3$, analysis of (2) 74.
of mullite (2) 98.
spinodal. phase separation by in systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3 (1) 50.
temp., of $Th(WO_4)_2$ (2) 113.
thermal. of $BeSO_4$, kinetics of (5) 232.
inhomogeneous, of talc (3) 149.
Deformation, high-temp., of polycrystalline Fe_2O_3 (11) 558.
of press-forged ceramic crystals (2) 90.
Deformation of UO_2, effect of porosity (3) 117.
Densification, postirradiation, of U_3Si, effect of swelling (5) 240.
Density, of Al_2O_3 systems, Cr_2O_3, and Sm_2O_3, change on melting (6) 326.
correlation with grain size in Ag sintering (11) 583.
during sintering. correlation with grain size (5) 276.
of glass spherules. lunar (5) 260.
green. effect on initial-stage sintering kinetics of UO_2 (8) 383.
Dielectric properties, strength, of sapphire, effect of pressure (11) 578.
Diffusion, coeffs., for O and Fe in Fe_2O_3 (11) 558.
of He in vitreous silica (2) 61.
kinetics. in system Al_2O_3-SiO_2 (10) 525.
Na. in glass, atm effects (5) 275.
self-. in mixed-alkali glasses (4) 186.
in slag-porous ceramic reactions (12) 592.
surface. and initial sintering in Al_2O_3 (3) 170.
in system Al_2O_3-SiO_2 (10) 525.
in system K_2O-SrO-SiO_2 (4) 220; (6) 312; (8) 418.
in system K_2O-SrO-SiO_2: III, IV. corrections (11) 584.
thermal. C, in UC-C system (1) 14.
vol. as mechanism of groove formation in MgO and Al_2O_3 (7) 351.
Diffusivity, of He in TiO_2-SiO_2 glasses (4) 195.
Dislocations, in MgO, creep-deformed polycrystalline (12) 606.

Elasticity, of composites, effect of shape of dispersed particles (5) 234.
modulus. of Na_2O-TiO_2-SiO_2 glasses (7) 360.
properties. of PLZT ceramics, effect of La (10) 504.
Young's modulus. of mullite (3) 169.
Elastic properties, of polymer-impregnated porous ceramics (12) 588.
Electrical properties, of $BaTiO_3$, Nb_2O_5 doped (12) 633.

Electrical properties, of FeO-P_2O_5 glass, relation to structure (7) 373.
of Si_3N_4. pyrolytic (8) 431.
Electricity, unusual effects in As-Te semiconducting glasses (1) 43.
Electrodes, polarization, in alkali-containing glasses (7) 337.
Electron diffraction, superlattice lines, in Mg ferrite (1) 59.
comment and reply (12) 632.
Electrons, bombardment, in formation of glass defects (9) 473.
microprobe study of lunar glass (5) 260.
Electrostatic processes, effect on diffusion in system K_2O-SrO-SiO_2 (8) 418.
Emission, acoustic, of Al titanate (1) 54.
Energy, critical surface, of Al_2O_3 and graphite (6) 300.
fracture. of ceramics (1) 48.
fracture surface. of SiC, measurement (9) 455.
Enstatite, crystallites, formation in talc (3) 149.
Equations, Orowan, Petch, and Knudsen, relation to strength-vs-grain-size data (5) 243.
Equilibrium studies, in BaO-SrO-SiO_2 system (12) 585.
in CaO-BaO-WO_3 system (10) 514.
of SiF_4 with SiO_2, Be_2SiO_4, and BeO in molten Li_2BeF_4 (11) 564.
in Sm-B system (9) 475.
in SrO-CdO-V_2O_5 system (10) 500.
Ettringite, stability on heating (1) 55.
Expansion, of Ag_2O lattice by annealing (1) 25.
thermal. axial, of HfO_2 (9) 482.
of Cs minerals, polycrystalline (5) 269.
in Hf and Zr titanates (8) 409.
of Nb_2O_5 (7) 342.

Fatigue, fracture initiation in MgO single crystals at high-temp. (1) 11.
static. chemical interpretation (2) 81.
and cyclic, in polycrystalline alumina (4) 208.
Ferrites, memory cores, effect of liquid environments on strength (6) 329; effect of liquid environments on strength, comments (6) 330.
Ni-Zn. effect of CoO on magnetic losses in (1) 28.
Ferroelectric materials, ceramic, nature of aging in (1) 57.
Ferroelectric phases, of $PbZrO_3$, crystal growth and observation (7) 331.
Ferroelectric properties, phase transitions in PLZT ceramics, acoustic detection (10) 497.
Films, thin glass, for transmission electron microscopy, preparation by splat cooling (10) 538.
Fission products, gaseous, in UO_2, simulation (7) 379.
Flaws, defect structure, effect on electrical properties of ZrO_2 (9) 439.
in glass. formation under electron bombardment (9) 473.
Flow, plastic, during hot-pressing (12) 596.
Fracture, energies, of ceramics (1) 48.
initiation. by fatigue in MgO single crystals at high temp. (1) 11.
in mica crystals (9) 437.
of press-forged ceramic crystals (2) 90.
surface energy of SiC. measurement (9) 455.
thermal-stress. of aluminosilicate ceramic (4) 198.
of UO_2. effect of impurities (12) 622.
effect of porosity (3) 117.
Freeze-drying, carbide synthesis by (1) 58.
Freezing point, of water in porous glass (6) 306.
Frequency, ir, calculations for ideal mullite (2) 68.
Friction, internal, of $Li_2O.Al_2O_3.2SiO_2$ glass, ion-exchanged (6) 279.
of $Li_2O.Al_2O_3.2SiO_2$ glass, (5) 254.
Frost resistance, mechanism of frost action in hardened cement paste (1) 38.
Frost resistance *(continued)*

Garnets, hydro-, phase in kaolinite-lime-water slurries (8) 432.
relation of composition to sulfate resistance (3) 146.
Gases, fission products, in UO_2, simulation (7) 379.
Glasses, alkali-containing, electrode polarization in (7) 337.
alkali Sr silicate. determination of surface composition by Auger spectroscopy (1) 51.
amber. dependence of melt O activity and water retention on composition (7) 368.
As-Te. semiconducting, unusual electrical effects in (1) 43.
BaO-SiO_2. controlled spherulitic crystallization in (7) 354.
borate. Ti centers induced in by irradiation (3) 137.
- ceramics. Li_2O-SiO_2, effect of crystallization on mechanical properties (2) 86.
machinable, based on tetrasilicic mica (9) 446.
MgO-Li_2O-Al_2O_3-SiO_2-TiO_2, microstructure and indentation hardness (6) 289.
crack growth in. effect of water (2) 81.
defects. formation under electron bombardment (9) 473.
E. adsorption of water vapor on (8) 399.
FeO-P_2O_5. relation of structure and electrical properties (7) 373.
formation. in system Cs_2O-Al_2O_3-SiO_2 (9) 483.
in systems M_mSe_n-$Ge_{1.5}As_{0.5}Se_3$ (7) 366.
H-impregnated. EPR study of radiation damage in (10) 536.
irradiated. activity of (4) 220.
lead borate. determination of H_2O in (1) 53.
secondary phase separation in (8) 422.
$Li_2O.Al_2O_3.2SiO_2$. ion-exchanged, internal friction of (6) 279, proton-exchanged, internal friction of (5) 254.
lunar. thermal history of (5) 260.
mixed-alkali silicate. alkali mobility and mechanical relaxation in (4) 186.
molten. temp. measurement by optical method (2) 71.
Na diffusion in. atm effects (5) 275.
$Na_2O.3SiO_2$. electrical relaxation (10) 492.
mechanical and ionic relaxation (10) 488.
Na_2O-TiO_2-SiO_2. elastic modulus of (7) 360.
phototropic. activated by TlCl (11) 553.
porous. freezing point of water in (6) 306.
reactive. effect on Ag-Pd sintering (6) 296.
silicate. ligand-field spectra and structure of Ni in (4) 201.
surfaces. determination of composition by Auger spectroscopy (1) 51.
in system $Ge_xAs_{40-x}S_{60}$ (4) 180.
thin films. for electron microscopy, preparation by splat cooling (10) 538.
TiO_2-SiO_2. He migration in (4) 195.
V phosphate. magnetic behavior and microstructure (3) 164.
Glow discharge, apparatus for rapid sintering of Al_2O_3 (7) 380.
Grain boundaries, segregation in MgO-doped Al_2O_3 (11) 568.
sliding. in ceramics (8) 430.
Grain growth, in Cu_2O, kinetics of (3) 134.
and grain size distributions. in MgO and MgO-Fe_2O_3 solid solutions (1) 19.
in porous Al_2O_3 compacts (3) 142.
Grain size, measurement in 2-phase polycrystalline ceramics (2) 109.
Graphite, critical surface energy (6) 300.
polycrystalline. porosity effects (4) 214; porosity effects (11) 580.
Grooving, thermal, of MgO and Al_2O_3 (7) 351.

Hafnium, dioxide, axial thermal expansion of (9) 482.
titanate. thermal expansion, compressibility, and polymorphism in (8) 409.
Hardness, indentation, of MgO-Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramic (6) 289.
Healing, of cracks in mica crystals (9) 437.
Heat, capacity, of glasses and liquids in system $Ge_xAs_{40-x}S_{60}$ (4) 180.
Heating, constant rate, in sintering study (8) 390.
at high rates. prediction of thermal shock resistance (9) 464.
Helium, migration, in TiO_2-SiO_2 glasses (4) 195.
in vitreous silica (2) 61.
Hematite, at high temp., dc conductivity and Fe tracer diffusion (4) 211.
Hydrogen ion concentration, of ground glass, effect of temp. (2) 82.
Hysteresis, loops, of (Pb,Sr)TiO_3, time effects in (2) 110.

Impurities, effect on UO_2 fracture (12) 622.
Ions, effect on $Li_2O.Al_2O_3.2SiO_2$ glass fiber (6) 279.
Iron, oxide, effect on sintering and density of $SrZrO_3$ (3) 125.
polycrystalline, high-temp. deformation (11) 558.
tracer diffusion in hematite at high temps. (4) 211.
Irradiation, Ti centers induced in borate glasses by (3) 137.

Kaolinite, dehydroxylation, analysis of (2) 74.
Kinetics, of $BeSO_4$ thermal decomposition (5) 232.
of carbothermal reduction of quartz under vacuum (8) 414.
data. reduced time in plotting (2) 112.
of growth of Al_2O_3 whiskers (2) 77.
of recrystallization and grain growth in Cu_2O (3) 134.
sintering. of UO_2, effect of green density (8) 383.
solid-state. method of comparing data (2) 74.
of UO_2-C-N_2 reaction at 1700°C (12) 601.
in ZrO_2 transformation (6) 317.

Lanthanum, effect on ferroelectric phase transitions in PZT ceramics (10) 497.
oxide. $BaTiO_3$ doped with (10) 533.

Lanthanum in Pb titanate-zirconate (5) 230.
in PLZT ceramics. effect on properties (10) 504.
Lasers, He-Ne, in measuring hot glass temp. (2) 71.
Lead, borate, secondary phase separation in (8) 422.
La zirconate-titanate. cold-pressing and low-temp. sintering (11) 541.
oxide. transformation induced by water (1) 47.
(Pb,Sr)TiO_3. hysteresis loop, time effects in (2) 110.
$PbZrS_3$. synthesis at high pressures (2) 111.
$Pb(Zr_{0.5}Ti_{0.5})O_3$. single-phase, nonstoichiometry in (4) 192.
zirconate. ferroelectric phase, crystal growth of (7) 331.
zirconate-titanate. ceramics, effect of La on (10) 504.
dependence on time of physical properties (1) 57.
La-doped, ferroelectric phase transitions in (10) 497.
vacancy distribution in (5) 230.
Liquids, environment, effect on strength of ferrite memory cores (6) 329; effect on strength of ferrite memory cores, comments (6) 330.
in system $Ge_xAs_{40-x}S_{60}$ (4) 180.
Lithium, aluminate, hot-pressing of (3) 172.
Li_2BeF_4. molten, equilibria of SiF_4 with SiO_2, Be_2SiO_4, and BeO in (11) 564.
Li_2MoO_4-MoO_3 flux. growth of BeO, Be_2SiO_4, and SiO_2 from (6) 292.
niobate and tantalate. stoichiometry variations (5) 225.

Magnesium, ferrite, electron diffraction superlattice lines in (1) 59.
comment and reply (12) 632.
oxide. creep-deformed, dislocation structures in (12) 606.
dense layer formation in BOF refractories (1) 3.
effect on grain-boundary segregation in Al_2O_3 (11) 568.
effect on microstructure of Al_2O_3 (3) 142.
elasticity, effect of particle shape (5) 234.
Fe-doped, transient creep in (9) 450.
and MgO-Fe_2O_3 solid solutions, grain growth and grain size distributions in (1) 19.
precipitation strengthening of $MgFe_2O_4$ by (1) 32.
single crystals, high-temp. fatigue fracture initiation in (1) 11.
thermal grooving of (7) 351.
Magnetic properties, of glassy system MnO-Fe_2O_3-B_2O_3 (10) 537.
magnetic loss. in Ni-Zn ferrite containing CoO (1) 28.
of vanadium phosphate glasses (3) 164.
Manganese, MnO_2, in $BaTiO_3$. PTCR behavior (2) 108.
Measurement, of grain size in 2-phase polycrystalline ceramics (2) 109.
Mechanical properties, of Li_2O-SiO_2 glass-ceramics, effect of crystallization (2) 86.
of MgO single crystals. effect of magnesioferrite precipitates (1) 32.
of stoichiometric Al silicate (11) 548.
Mechanics, of pressure slip casting (5) 264.
Melting, effect on surface tension, density, and vol of Al_2O_3 systems, Cr_2O_3, and Sm_2O_3 (6) 326.
electroslag. alkaline earth fluoride-LaF_3 systems in (3) 130.
Melts, O activity, dependence on amber glass composition (7) 368.
Memory cores, ferrite, effect of liquid environments on strength (6) 329; effect of liquid environments on strength, comments (6) 330.
Mica, crystals, fracture and healing in (9) 437.
tetrasilicic. in machinable glass-ceramics (9) 446.
Microscopy, electron, in study of sintering (3) 173.
transmission electron. dispersion of powders for (10) 535.
film preparation by splat cooling (10) 538.
Minerals, cement, interactions with hydroxycarboxylic-acid retarders (8) 405.
Mobility, alkali, relation to mechanical relaxation in mixed-alkali silicate glasses (4) 186.
Models, mobility, for diffusion in system K_2O-SrO-SiO_2 (8) 418.
working. for effect of porosity on ceramic strength (12) 610.
Modifications, polymorphic, of Pm_2O_3 (8) 428.
Molybdenum, carbide, nonstoichiometric, crystallography of (3) 174.
Mortars, resistance to sulfates (5) 237.
Mullite, decomposition (2) 98.
ideal. ir frequency calculations for (2) 68.
polycrystalline. Young's modulus of (3) 169.
synthesis and mechanical properties (11) 548.

Neodymium, hydroxide, preparation by vapor-phase reaction (7) 378.
Nickel, $NiAl_2O_4$ spinel, equilibrium cation distribution in (8) 395.
oxide. effect on sintering of ThO_2 and ThO_2-Y_2O_3 (10) 519.
in silicate glasses. ligand-field spectra and structure of (4) 201.
Niobium, diffused with carbon (5) 277.
Nb_2O_5. in $BaTiO_3$. PTCR behavior (2) 108.
thermal expansion (7) 342.
Oxide. in $BaTiO_3$, effect on electrical properties (12) 633.
Nonisothermal techniques, for studying initial-stage sintering (8) 390.

Optical methods, of temp. measurement in hot glass (2) 71.
Orientation, preferred, in Al_2O_3 substrates (10) 509.
re-. surface domain, from abrasion and annealing of $BaTiO_3$ (7) 334.
Oxidation, of CO on La_2O_3-doped $BaTiO_3$ (10) 533.
- reduction reactions. within BOF refractories (1) 1.
Oxygen, activity, of amber glass melt, dependence on composition (7) 368.
Oxygen ions. in molten Na phosphate, activity of (4) 183.
solubility in ZrC (12) 628.

Palladium, Ag-, sintering in presence of reactive glass (6) 296.
Particles, dispersed, in composite materials, effect of shape (5) 234.
settling. in fresh cement pastes (9) 461.
size. correlation with density in Ag sintering (11) 583.
determination (10) 535.
during sintering, correlation with density (5) 276.
vs strength, for ceramics (5) 243.
Penetration, of chloride ions into cement pastes and concretes (10) 534.
Permeability, compression, of slip cast Al_2O_3 (8) 381.
of He in TiO_2-SiO_2 glasses (4) 195.
of He in vitreous silica (2) 61.
Phase diagrams, Al_2O_3-SiO_2, single eutectic metastable binary (10) 527.
BaO-SrO-SiO_2. compatibility relations (12) 586.
BaO-WO_3 (10) 516.
$BaSi_2O_5$-$SrSiO_3$. Ba^2SiO_4-Sr_2SiO_4, and $BaSiO_3$-$SrSiO_3$ (12) 587.
$CaWO_4$-$BaWO_4$ and CaO-BaO-WO_3 (10) 517.
CdO-V_2O_5 and $Cd(VO_3)_2$-$Sr(VO_3)_2$ (10) 502.
Nb-C. modification (5) 277.
of PLZT ceramics (10) 499.
SrO-SiO_2. revised (12) 586.
SrO-V_2O_5 (10) 501.
Phases, analysis, of ZrO_2 systems (6) 303.
behavior. in Pu-Cr-N system (5) 273.
relations. in CaO-Pt system in air (8) 426.
separation. by spinodal decomposition in systems Al_2O_3-Cr_2O_3-Fe_2O_3 and Al_2O_3-Cr_2O_3 (1) 50.
transition. of adsorbates (1) 38.
Phenacite, crystals, single, growth of (6) 292.
Physical properties, of porous polycrystalline graphite (4) 214.
of tetrasilicic-mica glass-ceramics (9) 449.
Piezoelectricity, properties, of PLZT ceramics, effect of La (10) 504.
Polarization, electrode, in alkali-containing glasses (7) 337.
Pollucite, Synthesis Data, lattice parameters, and refractive indices (5) 270.
Polymorphism, in Hf and Zr titanates (8) 409.
in system Sr_2SiO_4-Sr_2GeO_4-Ba_2GeO_4-Ba_2SiO_4 (12) 619.
Porosity, effect on ceramic strength, working model (12) 610.
effect on deformation and fracture of UO_2 (3) 117.
effect on Young's modulus of mullite (3) 169.
in polycrystalline graphite (4) 214; (11) 580.
Potassium, self-diffusion coeffs. (4) 220.
Powders, dispersion for electron microscopy (10) 535.
Precipitation, strengthening, of MgO by $MgFe_2O_4$ (1) 32.
Pressing, cold, of alkoxy-derived PLZT (11) 541.
hot. of $LiAl_5O_8$ (3) 172.
plastic flow during (12) 596.
of ZnS and CdTe (11) 583.
Pressure, CO, effect on carbothermal reduction of quartz (8) 414.
dependence. of elastic moduli of Na_2O-TiO_2-SiO_2 glasses (7) 360.
effect on sapphire dielectric strength (11) 578.
Promethium, oxide, polymorphic modifications (8) 428.
Protons, effect on $Li_2O.Al_2O_3.2SiO_2$ glass fiber (5) 254.
Pyrophyllite, polymer-impregnated, effect of temp. on strength (3) 175.

Quartz, Beta, and CaO, effect of anisotropy and water vapor on solid-state reaction of (9) 469.
carbothermal reduction under vacuum. kinetics of (8) 414.
- coesite transition. effect of shear (6) 327.

Radiation, damage, in H-impregnated glass, EPR study (10) 536.
Reactions, in system Al_2O_3-SiO_2 (10) 525.
Reactivity, of Cr-doped tricalcium silicate (6) 309.
Recovery, of high-temp. creep-resistant substructure in rutile (1) 6.
Reduction, carbothermal, of quartz under vacuum, kinetics of (8) 414.
oxidation-. reactions within BOF refractories (1) 1.
Refractive index, of glass, lunar (5) 260.
Refractories, crucibles, $Pb(Zr,Ti)O_3$, synthesis of (4) 194.
oxidation-reduction reactions in (1) 1.
Relaxation, electrical, in $Na_2O.3SiO_2$ glass (10) 492.
mechanical. in mixed-alkali silicate glasses (4) 186.
mechanical and ionic. in $Na_2O.3SiO_2$ glass (10) 488.
Resistance, electrical, of liquid S and Liquid Se (2) 65.
positive temp. coeff., of $BaTiO_3Nb_2O_5$ and MnO_2 (2) 108.
Resonance, electron paramagnetic, of alkali borate glasses, effect of irradiation (3) 137.
of radiation damage in H-impregnated glass (10) 536.
Retardants, hydroxycarboxylic-acid, interaction with cement minerals (4) 177; interaction with cement minerals (8) 405.
Rutile, compressive creep at high temps. (1) 60.
recovery of high-temp. creep-resistant substructure in (1) 6.
substructures. in Ba Mg titanate (9) 479.

Samarium, oxide, effect of melting on surface tension, density, and vol (6) 326.
Sapphire, dielectric strength, effect of pressure (11) 578.
prismatic slip in (2) 105.
Sedimentation, of particles in fresh cement pastes (9) 461.
Segregation, grain-boundary, in MgO-doped Al_2O_3 (11) 568.
Selenium, liquid, electrical resistance to 700°C (2) 65.
pseudobinary metallic systems. glass formation in (7) 366.
Semiconductors, glass, As-Te, unusual electrical effects in (1) 43.
Separation, phase, secondary, in Pb borate glasses (8) 422.
Shear, effect on quartz-coesite transition (6) 323.
Shock, thermal, of Al_2O_3, relation to strength loss (5) 249.
effect on strength of brittle ceramics (9) 481.
Shock resistance, thermal, reduction at high heating rates (9) 464.
Silicon, carbide, measurement of fracture surface energy in (9) 455.
single crystals, effect of vapor-phase composition on morphology (10) 540.
dioxide. $CaCO_3$-, calcination and cementing properties (10) 485.
crystallization from Li_2MoO_4-MoO_3 (6) 292.
phase transformation, effect on carbothermal reduction of quartz (8) 414.
vitreous He migration in (2) 61.
nitride. pyrolytic (8) 431.
SiF_4. equilibria with SiO_2, Be_2SiO_4, and BeO in molten Li_2BeF_4 (11) 564.
Silver, liquid, Wetting of TaC by (3) 157.
oxide. lattice, expansion by annealing (1) 25.
- Pd. sintering in presence of reactive glass (6) 296.
sintering. grain size and density in (11) 583.
wire. as substrate in electron microscopy of Ag particles (3) 173.
Sintering, activated, of ThO_2 and ThO_2-Y_2O_3 with NiO (10) 519.
of Al_2O_3. glow-discharge apparatus for (7) 380.
of CaF_2. effect of additives (6) 327; effect of additives, reply (6) 328.
equations pertaining to constant rates of heating correction (2) 116.
final. of Cr_2O_3 (9) 433.
initial. of alumina, effect of TiO_2 (2) 114.
and surface diffusion in Al_2O_3 (3) 170.
initial-stage. nonisothermal techniques for studying (8) 390.
kinetics. initial-stage, of UO_2, effect of green density (8) 383.
low-temp.. of alkoxy-derived PLZT (11) 541.
pressure. synergetic, of Al_2O_3 (2) 115.
of silver. grain size and density in (11) 583.
of silver-Pd in presence of reactive glass (6) 296.
of $SrZrO_3$. effect of Fe_2O_3 (3) 125.
study by electron microscopy (3) 173.
Slags, electro-, alkaline earth fluoride-LaF_3 systems in melting of (3) 130.
reactions with porous ceramics. diffusion and convection in (12) 592.
Slip casting, pressure, of Al_2O_3, effect on compression permeability (8) 381.
mechanics of (5) 264.
Slurries, kaolinite-lime-water, hydrogarnet phase in (8) 432.
Sodalites, cathodochromic, preparation (5) 256.
Sodium, diffusion, in glass, atm effects (5) 275.
Na_2BeF_4. γ-,high-temp. modification (11) 584.
phosphate. molten, activity of O ions in (4) 183.
Solid state, reaction, of CaO and β quartz (9) 469.
formation of $CaZrO_3$ (8) 425.
Solubility, of He in TiO_2-SiO_2 glasses (4) 195.
of He in vitreous silica (2) 61.
of O in ZrC (12) 628.
solid. in system Sr_2SiO_4-Sr_2GeO_4-Ba_2GeO_4-Ba_2SiO_4 (12) 619.
of SO_3. in determining activity of O ions in Na phosphate (4) 183.
Solution, Ex-, in system SnO_2-TiO_2 (6) 322.
Solutions, solid, MgO-Fe_2O_3, grain size distributions and grain growth in (1) 19.
PLZT. vacancy sites in (5) 230.
Spalling, failure, method of treating (9) 464.
Spectra, ir, in identification of aluminosalicylate complex (8) 405.
ligand-field. of Ni in silicate glasses (4) 201.
Spectroscopy, Auger, for determining composition of glass surfaces (1) 51.
optical absorption. of ThO_2 (11) 544.
Raman powder. for determining stoichiometry variations (5) 225.
Spheroidization, of voids in Al_2O_3 crystals at high temps. (10) 507.
Spinels, $MgAl_2O_4$, preparation by chemical method (9) 484.
$NiAl_2O_4$. $CuAl_2O_4$, and $ZnAl_2O_4$, equilibrium cation distribution in (8) 395.
Stability, of ettringite on heating (1) 55.
Stoichiometry, non-, in $BaTiO_3$ (10) 539.
in single-phase $Pb(Zr_{0.5}Ti_{0.5})O_3$ (4) 192.
variations. in $LiNbO_3$ and $LiTaO_3$ (5) 225.
Strength, degradation and crack propagation in Al_2O_3 (5) 249.
dielectric. of sapphire, effect of pressure (11) 578.
of ferrite memory cores. effect of liquid environments (6) 329; effect of liquid environments, comments (6) 330.
loss. of brittle ceramics with thermal shock (9) 481.
of porous ceramic. polymer-impregnated, effect of temp. (3) 175.
of press-forged ceramic crystals (2) 90.
of titania. under stress (7) 347.
uniaxial. of ceramics, model for porosity effect (12) 610.
vs grain size. for ceramics (5) 243.
of ZnO. thermally shocked (8) 429.
Strengthening, precipitation, of MgO by $MgFe_2O_4$ (1) 32.

Strengthening thermomechanical. effect on stress fracture of aluminosilicate ceramic (4) 198.
Stresses, effect on strength of TiO_2 and Al silicate (9) 347.
residual. computation in quenched Al_2O_3 (2) 101.
Strontium, (Pb,Sr)TiO_3, hysteresis loop, time effects in (2) 110.
self-diffusion coeffs. (4) 220.
zirconate. polycrystalline, high-temp. creep (3) 125.
Structure, of Cr-doped tricalcium silicate (6) 309.
crystal. in calculation of ir frequencies of mullite (2) 68.
defect. effect on electrical properties of ZrO_2 (9) 439.
of $FeO-P_2O_5$ glass. relation to electrical properties (7) 373.
micro-. of $MgO-Li_2O-Al_2O_3-SiO_2-TiO_2$ glass- ceramic (6) 289.
of mullite (2) 98.
of vanadium phosphate glasses (3) 164.
of Ni in silicate glasses (4) 201.
sub-. creep-resistant, in rutile, recovery of (1) 6.
rutile, in Ba Mg titanate (9) 479.
of ZrO_2 in $CaO-ZrO_2$ system (3) 152.
Substrates, Al_2O_3, preferred orientation in (10) 509.
Sulfates, mortar resistance to, test for (5) 237.
resistance of hydrogarnet to (3) 146.
Sulfur, liquid, electrical resistance to 420°C (2) 65.
trioxide. solubility, in determining activity of O ions in Na phosphate (4) 183.
Swelling, of U_3Si, effect on conductivity and postirradiation (5) 240.
Synthesis, of carbide, by freeze-drying (1) 58.
of cathodochromic sodalites (5) 259.
of Cs minerals. polycrystalline (5) 269.
of $PbZrS_3$ at high pressures (2) 111.
of stoichiometric Al silicate (11) 548.
Systems, alkaline earth fluoride-LaF_3, in electroslag melting (3) 130.
$Al_2O_3-Cr_2O_3$ and $Al_2O_3-Cr_2O_3-Fe_2O_3$ phase separation by spinodal decomposition in (1) 50.
$BaO-SrO-SiO_2$. phase equilibria in (12) 585.
$BaO-TiO_2-Al_2O_3$. identification of $BaO.4TiO_2.Al_2O_3$ in (1) 55.
$CaO-BaO-WO_3$. phase equilibria in (10) 514.
CaO-Pt. phase relations in air (8) 426.
$CaO-SiO_2-Al_2O_3$. porous ceramic bodies in, reactions with slag (12) 592.
$CaO-ZrO_2$. structure and properties of partially stabilized ZrO_2 in (2) 152.
clay-lime-water. hydrogarnet phase in (8) 432.
$Cs_2O-Al_2O_3-SiO_2$. glass formation in (9) 483.
$Ge_xAs_{40-x}S_{60}$ (4) 180.
In-O. thermodynamic properties (11) 575.
$K_2O-MgF_2-MgO_5iO_2$. mica from glasses in (9) 446.
$K_2O-SrO-SiO_2$. diffusion in (4) 220; diffusion in (8) 418; diffusion in, III, IV, corrections (11) 584.
interdiffusion coeffs. (6) 312.
$M_mSe_n-Ge_{1.5}As_{0.5}Se_3$ glass formation in (7) 366.
$MnO-Fe_2O_3-B_2O_3$. preparation and magnetic properties (10) 537.
$PbO-B_2O_3$. secondary phase separation in (8) 422.
Pu-Cr-N. phase behavior in (5) 273.
Sm-B. phase behavior in (9) 475.
$SrO-CdO-V_2O_5$. phase equilibria in (10) 500.
$Sr_2SiO_4-Sr_2GeO_4-Ba_2GeO_4-Ba_2SiO_4$. solid solubility and polymorphism in (12) 619.
TiO_2-SnO_2. reexamination (6) 322.
UC_2-C. carbon thermal diffusion in (1) 14.
$V_2O_5-P_2O_5$. magnetic behavior and microstructure of glasses in (3) 164.

Talc, inhomogeneous dehydroxylation of (3) 149.
Tantalum, carbide, wetting by liquid Cu and Ag (3) 157.
Tellurium, chloride, as activator for phototropic glasses (11) 553.
Temperature, decomposition, of $Th(WO_4)_2$ (2) 113.
dependence. of elastic moduli of $Na_2O-TiO_2-SiO_2$ glasses (7) 360.
effect on strength of polymer-impregnated ceramic (3) 175.
measurement. in hot glass by optical method (2) 71.
Tension, surface, of Al_2O_3 systems, Cr_2O_3, and Sm_2O_3, change on melting (6) 326.
Tests, for mortar resistance to sulfate attack (5) 237.
Thermal history, of lunar glass (5) 260.
Thermal properties, of porous polycrystalline graphites (4) 214.
Thermodynamic properties, of In-O system (11) 575.
Thermomechanical properties, of ZrO_2 in $CaO-ZrO_2$ system (3) 52.
Thorium, dioxide, optical absorption spectroscopy (11) 544.
and $ThO_2-Y_2O_3$ with NiO, activated sintering (10) 519.
Y_2O_3-doped transparent (6) 324.
$Th(WO_4)_2$. decomposition temp. (2) 113.
Time, effect on hysteresis loop of (Pb,Sr)TiO_3 (2) 110.
reduced. use in plotting kinetic data (2) 112.
Titanates, Ba Mg, rutile substructures in (9) 479.
Hf and Zr. properties of (8) 409.
Titanium, centers, induced in borate glasses by irradiation (3) 137.
dioxide. effect on sintering of alumina (2) 114.
as nucleating agent in glass-ceramic (6) 289.
Transitions, ZrV_2O_7 (10) 532.
Transparency, of Li aluminate (3) 172.
Tridymite, single crystals, growth of (6) 292.
Tungsten, carbide, synthesis by freeze-drying (1) 58.
Uranium, dioxide, - C-N_2, kinetics of reaction at 1700 °C (12) 601.
deformation and fracture, effect of porosity (3) 117.
effect of green density on sintering kinetics (8) 383; effect of impurities on fracture of (12) 622.
simulation of gaseous fission products in (7) 379.
U_3Si. effect of swelling on thermal conductivity and postirradiation densification (5) 240.

Vacancies, *A*-and *B*-site, in (PB,La)(Ti,Zr)O_3 ceramics (5) 230.
Vanadium, pentoxide, effect on magnetic ordering of V phosphate glasses (3) 164.
Vapors, composition, effect on morphology of SiC single crystals (10) 540.
phase reactions in preparation of $Nd(OH)_3$ (7) 378.
Volume, change on melting of Al_2O_3 systems, Cr_2O_3, and Sm_2O_3 (6) 326

Water, effect on growth of cracks in glass (2) 81.
in Pb borate glasses. determination of (1) 53.
in porous glass. freezing point (6) 306.
retention. dependence on amber glass composition (7) 368.
transformation in PbO induced by (1) 47.
vapor. adsorption on E-glass (8) 399.
effect on solid-state reaction of CaO and β quartz (9) 469.
Weight, change, revised, in nonstoichiometric ZrO_2 (1) 60.
Wetting, of alumina and graphite (6) 300.
of TaC by liquid Cu and Ag (3) 157.
Wustite, lattice parameter, measurement at high temps. (3) 160.

X rays, data, for $BaO.4TiO_2.Al_2O_3$ (1) 55.
for Cd_2TiWO_7 (2) 107.
lattice parameters. for phases in system MgF_2- LaF_3 (3) 132.
powder diffraction data. for $PbZrS_3$ (2) 111.

Yttrium, oxide, in transparent ThO_2 (6) 324.

Zinc, oxide, density vs grain size during sintering (5) 276.
thermally shocked, strength of (8) 429.
sulfide. hot-pressing of (11) 583.
$ZnAl_2O_4$ spinel. equilibrium cation distribution in (8) 395.
Zirconium, carbide, O solubility in (12) 628.
dioxide. CaO-stabilized, creep of (11) 571.
crystals, hydrothermal growth and etching (4) 223.
electrical properties, effect of defect structure (9) 439.
partially stabilized, structure in $CaOZrO_2$ system (3) 152.
transformation, kinetics and burst phenomenon in (6) 317.
oxide. nonstoichiometric, revised weight change in (1) 60.
solid state reaction with CaO (8) 425.
systems, phase analysis (6) 303.
pyrovanadate. transitions (10) 532.
titanate. thermal expansion, compressibility, and polymorphism in (8) 409.

INDEX GUIDE

"See" and "See also" references indicate categories under which related or similar information may be indexed. The list is general and categories will not necessarily appear in the index every year.

Adsorption. See also *Diffusion; Sorption.*
Alumina. See *Aluminum, oxide.*
Aluminum, oxide. See also *Refractories.*
Analysis. See specific types.
Anions. See *Ions.*
Anisotropy. See also *Crystals.*

Bending. See *Deformation.*
Beryllia. See *Beryllium, oxide.*

Calcia. See *Calcium, oxide.*
Calcination. See also *Firing.*
Carbides. See also specific types.
Carbon. See also *Graphite.*
Cements. See also *Concretes; Mortars; Refractories.*
Cermets. See *Composite materials.*
Chromia. See *Chromium, oxide.*
Clays. See also specific types.
Clinker, cement. See *Cements.*
Coatings. See also *Enamels.*
Columbium. See *Niobium.*
Concretes. See also *Cements; Mortars; Refractories.*
Cores, memory. See *Magnetic cores.*
Corundum. See *Aluminum, oxide; Sapphire.*
Cracks. See also *Defects; Fracture.*
Creep. See also *Fatigue; Plasticity.*
Crystallites. See also *Crystals, structure.*
Crystallization. See also *Crystals, growth.*

Defects. See also *Cracks; Fracture; Structure.*
Dicalcium silicate. See *Calcium.*
Dielectrics. See also *Ferrites; Ferroelectric materials; Glasses.*
Differential thermal analysis. See *Thermal analysis.*
Diffraction. See also *Electron diffraction; Neutrons; Optical properties; X rays.*
Diffusivity. See also *Diffusion.*
Dislocations. See also *Creep; Defects.*
Dissolution. See *Solution.*
Doping. See *Additives.*

Electrical conductance. See *Resistance, electrical.*
Electrical conductivity. See *Conductivity, electrical.*
Electrical resistance. See *Resistance, electrical.*
Enamels. See also *Coatings.*
Energy. See also *Enthalpy; Entropy; Kinetics.*
Entropy. See also *Thermodynamics.*
Equilibrium studies. See also *Phase diagrams; Systems.*

Ferric, Ferrous compounds. See *Iron.*
Ferroelectric materials. See also *Dielectrics;* specific types.
Fibers. See also *Composites;* specific types.
Filaments. See also *Fibers.*
Films. See also *Coatings;* specific types.
Flaws. See *Defects.*
Fluxes. See also *Crystals, growth;* specific types.
Fracture. See also *Cracks.*

Gels. See *Colloids.*
Glasses, fibers. See *Fibers, glass.*
Glasses, semicrystalline. See *Glass-ceramics.*
Grains. See also *Particles.*
Graphite. See also *Carbon; Composites; Refractories.*

Heat, capacity. See *Specific heat.*
Heat conductivity. See *Conductivity, thermal.*
Heat content. See *Enthalpy.*

Impurities. See also *Addition.*
Infrared, absorption. See *Absorption.*
Infrared, spectra. See *Spectra.*
Ions. See also specific types.
Irradiation. See also *Radiation;* specific types.

Kaolinite. See also *Kaolin.*

Lanthana. See *Lanthanum, oxide.*
Lattice parameters. See *Crystals, lattice.*

Magnesia. See *Magnesium, oxide.*
Microhardness. See *Hardness, micro-.*
Microscopy. See also *Structure, micro-.*
Modulus of elasticity. See *Elasticity.*
Moisture. See *Humidity; Hydration; Steam; Water.*
Mortars. See also *Cements; Concretes.*

Opacifiers. See *Additives.*
Optical properties. See also specific types.
Organic compounds. See also specific types.
Oxalates. See also specific types.
Oxides. See also *Rare earths;* specific types.

Permeability. See also *Porosity.*
Permittivity. See *Dielectric properties.*
Phase diagrams. See also *Equilibrium studies; Phase transformations; Systems.*
Phase equilibria. See *Equilibrium studies.*
Phase transformations. See also *Equilibrium studies; Phase diagrams; Systems.*
Physical properties. See also specific types.
Pores. See *Porosity.*
Porosity. See also *Permeability.*

Quartz. See also *Glasses; Refractories; Silicon, dioxide.*

Radioisotopes. See *Isotopes, radio-.*
Reflectance. See *Reflection.*
Refractories. See also specific types.
Retardants. See also *Additives.*
Rutile. See *Titanium, dioxide.*

Sapphire. See also *Aluminum, oxide.*
Silica. See *Silicon, dioxide.*
Single crystals. See *Crystals, single;* specific types.
Sodium. See also *Alkalis.*
Solid solutions. See *Solutions, solid.*
Solutions, solid. See also *Equilibrium studies.*
Spalling. See also *Fracture;* specific materials.
Specific gravity. See *Density.*
Specific heat. See *Heat, capacity.*
Spectra. See also *Optical properties.*
Spinels. See also specific types.
Stannic, Stannous. See *Tin.*
Structure, micro-. See also *Grains, size; Porosity.*
Systems. See also *Equilibrium studies; Phase diagrams.*

Tests. See also specific properties.
Thermal conductivity. See *Conductivity, thermal.*
Thermal expansion. See *Expansion, thermal.*
Thermal shock resistance. See *Shock resistance, thermal.*
Thermoelectric properties. See *Electrical properties.*
Thermogravimetry. See *Thermal analysis, gravimetric.*
Thoria. See *Thorium, dioxide.*
Titania. See *Titanium, dioxide.*
Transport processes. See also *Diffusion; Ions; Kinetics; Resistivity, electrical; Viscosity.*

Urania. See *Uranium, dioxide.*
Uvarovite. See *Garnets.*

Vapors. See also *Gases; Water.*
Viscosity. See also *Density; Friction, internal; Solutions.*

Water. See also *Humidity; Hydration; Moisture; Steam; Vapors.*

Young's modulus. See *Elasticity, modulus.*
Ytterbia. See *Ytterbium, oxide.*
Yttria. See *Yttrium, oxide.*

Zirconia. See *Zirconium, dioxide.*

Calcium, $CaCO_3$-SiO_2 mixtures, calcination and cementing properties (10) 485.
fluoride. effect of additives on sintering (6) 327; effect of additives on sintering, reply (6) 328.
oxide. and β quartz, effect of anisotropy and water vapor on solid state reaction of (9) 469.
creep of ZrO_2 stabilized with (11) 571.
- stabilized ZrO_2 (2) 152.
tricalcium. aluminate hexahydrate, effect of Si on crystallography of (3) 146.
aluminate-salicylic acid reaction (4) 177.
silicate, Cr-doped, structure and reactivity (6) 309.
zirconate. formation by solid-state reaction (8) 425.
Carbides, synthesis, by freeze-drying (1) 58.
Carbon, monoxide, oxidation on La_2O_3-doped $BaTiO_3$ (10) 533.
reaction with UO_2 and N_2 at 1700°C (12) 601.
thermal diffusion. in UC_2-C system (1) 14.
Cathodochromism, induction in sodalites (5) 256.
Cations, distribution, in spinels (8) 395.
Cements, minerals, interaction with hydroxycarboxylic-acid retarders (8) 405.
interactions with retarders (4) 177.
paste. fresh, particle settling in (9) 461.
hardened, creep transition (6) 284.
hardened, mechanism of frost action in (1) 38.
penetration of chloride ions (10) 534.
properties. of $CaCO_3$-SiO_2 mixtures (10) 485.
Ceramics, brittle, effect of thermal shock on strength (9) 481.
grain boundary sliding in (8) 430.
polycrystalline. two-phase, grain size measurement in (2) 109.
porous. polymer-impregnated, effect of temp. on strength (3) 175; polymer-impregnated, elastic behavior (12) 588.
strength. effect of porosity (12) 610.
Cesium, minerals, polycrystalline, synthesis and thermal expansion (5) 269.
Chemistry, of crack growth in glass (2) 81.
method. for preparing $MgAl_2O_4$ spinel (9) 484.
Chlorides, ions, penetration into cement pastes and concretes (10) 534.
Chromium, Cr_2O_3, final sintering of (9) 433.
oxide. effect of melting on surface tension, density and vol (6) 326.
Cobalt, oxide, effect on magnetic losses in Ni-Zn ferrites (1) 28.
Coesite, quartz-, transition, effect of shear (6) 323.
Composites, effect of shape of dispersed particles on elasticity (5) 234.
Compressibility, in Hf and Zr titanates (8) 409.
Compression, permeability, of slip cast Al_2O_3 (8) 381.
Computation, of residual stresses in quenched Al_2O_3 (2) 101.
Concretes, effect of ettringite in hydrated cement paste (1) 55.
penetration of chloride ions (10) 534.
Conductivity, electrical, dc, in hematite at high temps. (4) 211.
thermal. of cristobalite (11) 580.
of U_3Si, effect of swelling (5) 240.
Convection, in slag-porous ceramic reactions (12) 592.
Cooling, splat, for preparing films for transmission electron microscopy (10) 538.
Copper, $CuAl_2O_4$ spinel, equilibrium cation distribution in (8) 395.
density vs grain size during sintering (5) 276.
liquid. wetting of TaC by (3) 157.
oxide. recrystallization and grain growth (3) 134.
Corrections, for "Diffusion in the System K_2O-SrO-SiO_2: III, IV" (11) 584.
Cracks, formation, in Al titanate, detection by acoustic emission (1) 54.
propagation and strength degradation in Al_2O_3 (5) 249.
in sapphire. spheroidization of (10) 507.
Creep, of CaO-stabilized ZrO_2 (11) 571.
compressive. of rutile at high temps. (1) 60.
of Fe_2O_3, polycrystalline (11) 558.
high-temp., of $SrZrO_3$ (3) 125.
in MgO. polycrystalline (12) 606.
- resistant substructure in rutile. recovery of (1) 6.
transient. in Fe-doped polycrystalline MgO (9) 450.
transition. for hardened cement paste (6) 284.
Cristobalite, thermal conductivity of (11) 580.
Crystallization, of BeO, Be_2SiO_4, and SiO_2 from Li_2MoO_4-MoO_3 (6) 292.
controlled spherulitic. in 3 BaO-5SiO_2 glass (7) 354.
effect on mechanical properties of Li_2O-SiO_2 glass-ceramic (2) 86.
re-. of Cu_2O, kinetics of (3) 134.
of press-forged ceramic crystals (2) 90.
Crystallography, of MoC (3) 174.
Crystals, ceramic, deformation, recrystallization, strength, and fracture (2) 90.
growth. and etching of ZrO_2 (4) 223.
of $PbZrO_3$ ferroelectric phase (7) 331.
lattice. parameter of wustite at high temps. (3) 160.
parameters for Nb_2O_5 (7) 343.
sapphire. prismatic slip in (2) 105.

Decomposition, of kaolinite, brucite, and $BaCO_3$, analysis of (2) 74.
of mullite (2) 98.
spinodal. phase separation by in systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3 (1) 50.
temp., of $Th(WO_4)_2$ (2) 113.
thermal. of $BeSO_4$, kinetics of (5) 232.
inhomogeneous, of talc (3) 149.
Deformation, high-temp., of polycrystalline Fe_2O_3 (11) 558.
of press-forged ceramic crystals (2) 90.
Deformation of UO_2. effect of porosity (3) 117.
Densification, postirradiation, of U_3Si, effect of swelling (5) 240.
Density, of Al_2O_3 systems, Cr_2O_3, and Sm_2O_3, change on melting (6) 326.
correlation with grain size in Ag sintering (11) 583.
during sintering. correlation with grain size (5) 276.
of glass spherules. lunar (5) 260.
green. effect on initial-stage sintering kinetics of UO_2 (8) 383.
Dielectric properties, strength, of sapphire, effect of pressure (11) 578.
Diffusion, coeffs., for O and Fe in Fe_2O_3 (11) 558.
of He in vitreous silica (2) 61.
kinetics. in system Al_2O_3-SiO_2 (10) 525.
Na. in glass, atm effects (5) 275.
self-. in mixed-alkali glasses (4) 186.
in slag-porous ceramic reactions (12) 592.
surface. and initial sintering in Al_2O_3 (3) 170.
in system Al_2O_3-SiO_2 (10) 525.
in system K_2O-SrO-SiO_2 (4) 220; (6) 312; (8) 418.
in system K_2O-SrO-SiO_2: III, IV. corrections (11) 584.
thermal. C, in UC_2-C system (1) 14.
vol. as mechanism of groove formation in MgO and Al_2O_3 (7) 351.
Diffusivity, of He in TiO_2-SiO_2 glasses (4) 195.
Dislocations, in MgO, creep-deformed polycrystalline (12) 606.

Elasticity, of composites, effect of shape of dispersed particles (5) 234.
modulus. of Na_2O-TiO_2-SiO_2 glasses (7) 360.
properties. of PLZT ceramics, effect of La (10) 504.
Young's modulus. of mullite (3) 169.
Elastic properties, of polymer-impregnated porous ceramics (12) 588.
Electrical properties, of $BaTiO_3$, Nb_2O_5 doped (12) 633.

Electrical properties, of FeO-P_2O_5 glass, relation to structure (7) 373.
of Si_3N_4. pyrolytic (8) 431.
Electricity, unusual effects in As-Te semiconducting glasses (1) 43.
Electrodes, polarization, in alkali-containing glasses (7) 337.
Electron diffraction, superlattice lines, in Mg ferrite (1) 59.
comment anu reply (12) 632.
Electrons, bombardment, in formation of glass defects (9) 473.
microprobe study of lunar glass (5) 260.
Electrostatic processes, effect on diffusion in system K_2O-SrO-SiO_2 (8) 418.
Emission, acoustic, of Al titanate (1) 54.
Energy, critical surface, of Al_2O_3 and graphite (6) 300.
fracture. of ceramics (1) 48.
fracture surface. of SiC, measurement (9) 455.
Enstatite, crystallites, formation in talc (3) 149.
Equations, Orowan, Petch, and Knudsen, relation to strength-vs-grain-size data (5) 243.
Equilibrium studies, in BaO-SrO-SiO_2 system (12) 585.
in CaO-BaO-WO_3 system (10) 514.
of SiF_4 with SiO_2, Be_2SiO_4, and BeO in molten Li_2BeF_4 (11) 564.
in Sm-B system (9) 475.
in SrO-CdO-V_2O_5 system (10) 500.
Ettringite, stability on heating (1) 55.
Expansion, of Ag_2O lattice by annealing (1) 25.
thermal. axial, of HfO_2 (9) 482.
of Cs minerals, polycrystalline (5) 269.
in Hf and Zr titanates (8) 409.
of Nb_2O_5 (7) 342.

Fatigue, fracture initiation in MgO single crystals at high-temp. (1) 11.
static. chemical interpretation (2) 81.
and cyclic, in polycrystalline alumina (4) 208.
Ferrites, memory cores, effect of liquid environments on strength (6) 329; effect of liquid environments on strength, comments (6) 330.
Ni-Zn. effect of CoO on magnetic losses in (1) 28.
Ferroelectric materials, ceramic, nature of aging in (1) 57.
Ferroelectric phases, of $PbZrO_3$, crystal growth and observation (7) 331.
Ferroelectric properties, phase transitions in PLZT ceramics, acoustic detection (10) 497.
Films, thin glass, for transmission electron microscopy, preparation by splat cooling (10) 538.
Fission products, gaseous, in UO_2, simulation (7) 379.
Flaws, defect structure, effect on electrical properties of ZrO_2 (9) 439.
in glass. formation under electron bombardment (9) 473.
Flow, plastic, during hot-pressing (12) 596.
Fracture, energies, of ceramics (1) 48.
initiation. by fatigue in MgO single crystals at high temp. (1) 11.
in mica crystals (9) 437.
of press-forged ceramic crystals (2) 90.
surface energy of SiC. measurement (9) 455.
thermal-stress. of aluminosilicate ceramic (4) 198.
of UO_2. effect of impurities (12) 622.
effect of porosity (3) 117.
Freeze-drying, carbide synthesis by (1) 58.
Freezing point, of water in porous glass (6) 306.
Frequency, ir, calculations for ideal mullite (2) 68.
Friction, internal, of $Li_2O.Al_2O_3.2SiO_2$ glass, ion-exchanged (6) 279.
of $Li_2O.Al_2O_3.2SiO_2$ glass, (5) 254.
Frost resistance, mechanism of frost action in hardened cement
Frost resistance *(continued)*
paste (1) 38.
Garnets, hydro-, phase in kaolinite-lime-water slurries (8) 432.
relation of composition to sulfate resistance (3) 146.
Gases, fission products, in UO_2, simulation (7) 379.
Glasses, alkali-containing, electrode polarization in (7) 337.
alkali Sr silicate. determination of surface composition by Auger spectroscopy (1) 51.
amber. dependence of melt O activity and water retention on composition (7) 368.
As-Te. semiconducting, unusual electrical effects in (1) 43.
BaO-SiO_2. controlled spherulitic crystallization in (7) 354.
borate. Ti centers induced in by irradiation (3) 137.
- ceramics. Li_2O-SiO_2, effect of crystallization on mechanical properties (2) 86.
machinable, based on tetrasilicic mica (9) 446.
MgO-Li_2O-Al_2O_3-SiO_2-TiO_2, microstructure and indentation hardness (6) 289.
crack growth in. effect of water (2) 81.
defects. formation under electron bombardment (9) 473.
E. adsorption of water vapor on (8) 399.
FeO-P_2O_5. relation of structure and electrical properties (7) 373.
formation. in system Cs_2O-Al_2O_3-SiO_2 (9) 483.
in systems M_mSe_n-$Ge_{1.3}As_{0.3}Se_3$ (7) 366.
H-impregnated. EPR study of radiation damage in (10) 536.
irradiated. activity of (4) 220.
lead borate. determination of H_2O in (1) 53.
secondary phase separation in (8) 422.
$Li_2O.Al_2O_3.2SiO_2$. ion-exchanged, internal friction of (6) 279.
proton-exchanged, internal friction of (5) 254.
lunar. thermal history of (5) 260.
mixed-alkali silicate. alkali mobility and mechanical relaxation in (4) 186.
molten. temp. measurement by optical method (2) 71.
Na diffusion in. atm effects (5) 275.
$Na_2O.3SiO_2$. electrical relaxation (10) 492.
mechanical and ionic relaxation (10) 488.
Na_2O-TiO_2-SiO_2. elastic modulus of (7) 360.
phototropic. activated by TlCl (11) 553.
porous. freezing point of water in (6) 306.
reactive. effect on Ag-Pd sintering (6) 296.
silicate. ligand-field spectra and structure of Ni in (4) 201.
surfaces. determination of composition by Auger spectroscopy (1) 51.
in system $Ge_xAs_{40-x}S_{60}$ (4) 180.
thin films. for electron microscopy, preparation by splat cooling (10) 538.
TiO_2-SiO_2. He migration in (4) 195.
V phosphate. magnetic behavior and microstructure (3) 164.
Glow discharge, apparatus for rapid sintering of Al_2O_3 (7) 380.
Grain boundaries, segregation in MgO-doped Al_2O_3 (11) 568.
sliding. in ceramics (8) 430.
Grain growth, in Cu_2O, kinetics of (3) 134.
and grain size distributions. in MgO and MgO-Fe_2O_3 solid solutions (1) 19.
in porous Al_2O_3 compacts (3) 142.
Grain size, measurement in 2-phase polycrystalline ceramics (2) 109.
Graphite, critical surface energy (6) 300.
polycrystalline. porosity effects (4) 214; porosity effects (11) 580.
Grooving, thermal, of MgO and Al_2O_3 (7) 351.

Hafnium, dioxide, axial thermal expansion of (9) 482.
titanate. thermal expansion, compressibility, and polymorphism in (8) 409.
Hardness, indentation, of MgO-Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramic (6) 289.
Healing, of cracks in mica crystals (9) 437.
Heat, capacity, of glasses and liquids in system $Ge_xAs_{40-x}S_{60}$ (4) 180.
Heating, constant rate, in sintering study (8) 390.
at high rates. prediction of thermal shock resistance (9) 464.
Helium, migration, in TiO_2-SiO_2 glasses (4) 195.
in vitreous silica (2) 61.
Hematite, at high temp., dc conductivity and Fe tracer diffusion (4) 211.
Hydrogen ion concentration, of ground glass, effect of temp. (2) 82.
Hysteresis, loops, of (Pb,Sr)TiO_3, time effects in (2) 110.

Impurities, effect on UO_2 fracture (12) 622.
Ions, effect on $Li_2O.Al_2O_3.2SiO_2$ glass fiber (6) 279.
Iron, oxide, effect on sintering and density of $SrZrO_3$ (3) 125.
polycrystalline, high-temp. deformation (11) 558.
tracer diffusion in hematite at high temps. (4) 211.
Irradiation, Ti centers induced in borate glasses by (3) 137

Kaolinite, dehydroxylation, analysis of (2) 74.
Kinetics, of $BeSO_4$ thermal decomposition (5) 232.
of carbothermal reduction of quartz under vacuum (8) 414.
data. reduced time in plotting (2) 112.
of growth of Al_2O_3 whiskers (2) 77.
of recrystallization and grain growth in Cu_2O (3) 134.
sintering. of UO_2, effect of green density (8) 383.
solid-state. method of comparing data (2) 74.
of UO_2-C-N_2 reaction at 1700°C (12) 601.
in ZrO_2 transformation (6) 317.

Lanthanum, effect on ferroelectric phase transitions in PZT ceramics (10) 497.
oxide. $BaTiO_3$ doped with (10) 533.

JOURNAL

of the

American Ceramic Society

A MONTHLY PUBLICATION DEVOTED TO THE ARTS AND SCIENCES RELATED TO CERAMICS

VOLUME 55, 1972

F. P. Reid, *Publisher and Executive Director*
William J. Smothers, *Editor*
Margie K. Reser, *Technical Editor*
M. Geraldine Smith, *Associate Editor*
Nancy L. Reed, *Assistant Editor*
Olive Scott, *Senior Editorial Assistant*
Martha Bell, *Editorial Assistant*

Committee on Publications: Seymour L. Blum, *Chairman;*
Arthur L. Friedberg, John R. Hutchins III, J. B. Wachtman, Jr.;
ex officio members: F. P. Reid, William J. Smothers, Floyd A. Hummel

Executive, Editorial, and Advertising Offices:
65 Ceramic Drive, Columbus, Ohio 43214

Officers of the American Ceramic Society, 1972–1973

SOCIETY OFFICERS

President: THEODORE J. PLANJE, University of Missouri—Rolla, School of Mines and Metallurgy, Rolla, Mo. 65401
President-Elect: JAMES R. JOHNSON, 2393 South Shore Blvd., White Bear Lake, Minn. 55110 (3M Co.)
Vice Presidents:
JOSEPH E. BURKE, General Electric Co. Research & Development Center, Box 8, Schenectady, N. Y. 12301
ROBERT S. DU FRESNE, Tektronix, Inc., Box 500, Beaverton, Ore. 97005
WILLIAM R. PRINDLE, American Optical Corp., Framingham, Mass. 01701
Treasurer: STEPHEN D. STODDARD, 203 Chamisa Ave., Los Alamos, N. M. 87544 (Los Alamos Scientific Lab)

DIVISION AND CLASS OFFICERS

Basic Science Division

Trustee: RALPH CARTER (1975), General Electric Co., Research & Development Center, Box 8, Schenectady, N. Y. 12301
Chairman: RICHARD M. SPRIGGS, Lehigh University, Office of the President, Alumni Memorial Bldg., Bethlehem, Pa. 18015
Chairman-Elect: THOMAS VASILOS, 92 Bartlett Rd., Winthrop, Mass. 02152 (Avco Systems Div.)
Vice Chairman: SHELDON M. WIEDERHORN, National Bureau of Standards, Washington, D. C. 20234
Secretary: PAUL J. JORGENSEN, Stanford Research Institute, Menlo Park, Calif. 94025

Cement Division

Trustee: PETER J. SEREDA (1975), Div. of Building Research, National Research Council, Montreal Rd., Ottawa, Ont., K1A OR6, Canada
Chairman: SIDNEY DIAMOND, Purdue University, School of Civil Engineering, Lafayette, Ind. 47907
Chairman-Elect: A. A. TABIKH, TMS International, 5051 Berean, Irvine, Calif. 92664
Secretary: FORREST R. HURLEY, Martin Marietta Corp., 1450 S. Rolling Rd., Baltimore, Md. 21227

Ceramic-Metal Systems Division

Trustee: ARTHUR L. FRIEDBERG (1973), University of Illinois, 204 Ceramics Building, Urbana, Ill. 61801
Chairman: RICHARD A. EPPLER, Pemco Ceramics Group, Glidden-Durkee, Div. of SCM Corp., 5601 Eastern Ave., Baltimore, Md. 21224
Vice Chairman: JULES J. DUGA, 2605 Bryden Rd., Columbus, Ohio 43209 (Consultant)
Secretary: JOHN D. BUCKLEY, 23 E. Governor Dr., Newport News, Va. 23602 (NASA)
Counselor: H. S. INGHAM, JR., Metco Inc., 1101 Prospect Ave., Westbury, L. I., N. Y. 11590
Counselor: ROBERT J. MCWILLIAMS, 1480 Rush-Henrietta Rd., Rush, N. Y. 14543 (R. J. McWilliams Engineering Co.)

Electronics Division

Trustee: MERLE D. RIGTERINK (1975), Bell Labs, 600 Mountain Ave., Murray Hill, N. J. 07974
Chairman: JAMES R. FLOYD, U. S. Graphite-Engineered Materials, Div. of Wickes Corp., 1621 E. Holland Ave., Saginaw, Mich. 48601
Chairman-Elect: LEWIS C. HOFFMAN, 34 S. Cliffe Dr., Wycliffe, Wilmington, Del. 19809 (E. I. du Pont de Nemours & Co., Inc.)
Vice Chairman: JOHN C. WILLIAMS, 7 Mt. Vernon Way, Whippany, N. J. 07981 (Bell Labs)
Secretary: DAVID L. WILCOX, 2184 Glenkirk Dr., San Jose, Calif. 95124 (IBM Corp.)

Glass Division

Trustee: GUY E. RINDONE (1974), Pennsylvania State University, Dept. of Materials Science, 201 Mineral Industries Bldg., University Park, Pa. 16802
Chairman: ROBERT GARDON, Ford Motor Co., Box 2053, Dearborn, Mich. 48121
First Vice Chairman: DANIEL R. STEWART, 1399 Fort St., Maumee, Ohio 43537 (Owens-Illinois, Inc.)
Second Vice Chairman: LARRY L. HENCH, University of Florida, Dept. of Metallurgical and Materials Engineering, Gainesville, Fla. 3260[illegible]
Secretary: JOSEPH J. HAMMEL, PPG Industries, Inc. Glass Research Center, Box 11472, Pittsburgh, Pa. 15238

Materials & Equipment Division

Trustee: FRANK J. ZVANUT (1975), 710 Dorchester Dr., Tyler, Texas 75701 (Frank Zvanut Co.)
Chairman: RICHARD C. HANNON, R. R. 3, Carrollton, Ohio 44615 (Fusion Ceramics Inc.)
Chairman-Elect: CARL E. HAGBERG, 19 Lawnside Dr., Trenton, N. J. 08638 (Kentucky-Tennessee Clay Co.)
Vice Chairman: WILLIAM C. SPANGENBERG, Hammond Lead Products, Inc., Box 486, Carnegie, Pa. 15106
Secretary: J. RICHARD SCHORR, Columbia Gas System Service Corp., 1600 Dublin Rd., Columbus, Ohio 43215

Nuclear Division

Trustee: JOSEPH H. HANDWERK (1973), 73 Woodland Forest, Tuscaloosa, Ala. 35401 (U.S. Bureau of Mines)
Chairman: EUGENE D. LYNCH, 3631 Willow Lawn Dr., Lynchburg, Va. 24503 (Babcock & Wilcox Co.)
Vice Chairman: WILLIAM R. JACOBY, Westinghouse Electric Corp., Box 217, Cheswick, Pa. 15024
Secretary: ALEXIS I. KAZNOFF, General Electric Co., Vallecitos Nuclear Center, Vallecitos Rd., Pleasanton, Calif. 94566

Refractories Division

Trustee: EDWIN RUH (1973), 892 Old Hickory Rd., Pittsburgh, Pa. 15243 (Harbison-Walker Refractories Co., Div. of Dresser Industries, Inc.)
Chairman: KARL H. SANDMEYER, 338 Walnut Lane, Youngstown, N. Y. 14174 (Carborundum Co.)
Vice Chairman: LEROY D. HART, 8909 Redoak Dr., Crestwood, Mo. 63126 (Aluminum Co. of America)
Secretary: ARTHUR J. METZGER, Dept. of Ceramic Engineering, Ohio State University, 2041 N. College Rd., Columbus, Ohio 43210

Structural Clay Products Division

Trustee: GILBERT C. ROBINSON (1975), Box 91, Clemson, S. C. 29631 (Clemson University)
Chairman: JOHN H. VAN RAVESTEIN, J. C. Steele & Sons, Inc., Box 951, Statesville, N. C. 28677
Chairman-Elect: JOSEPH H. BELGER, Lingl Corp., Dresden Hwy., Box 1059, Paris, Tenn. 38242
Vice Chairman: JAMES L. CLARK, 2761 South Jay, Denver, Colo. 80227 (Robinson Brick & Tile Co.)
Secretary: WILLIAM L. PANGBORN, United States Concrete Pipe Co., Box 152, Uhrichsville, Ohio 44683

White Wares Division

Trustee: DAVID J. BARBOUR (1974), 251 E. Highland Dr., Zanesville, Ohio 43701 (Consultant)
Chairman: ROBERT B. OBERST, 1943 Rosebery Dr., Columbus, Ohio 43221 (Industrial Ceramic Products, Inc.)
Chairman-Elect: STANLEY I. WARSHAW, American Standard Inc., Box 2003, New Brunswick, N. J. 08903
Vice Chairman: WILLIAM J. KELLY, 7 Van Saun Dr., Trenton, N. J. 08628 (United Sierra Div., Cyprus Mines Corp.)
Secretary: GEORGE J. HUND, SR., 221 Poplar Ave., N.W., Canton, Ohio 44708 (Sparta Ceramic Co.)

Ceramic Educational Council

Trustee: WILLIS G. LAWRENCE (1974), SUNY, College of Ceramics at Alfred University, Alfred, N. Y. 14802
President: WILLIAM C. HACKLER, Virginia Polytechnic Institute & State University, Ceramic Engineering, Blacksburg, Va. 24061
President-Elect: WILLIAM B. CAMPBELL, 1892 Inchcliff Rd., Columbus, Ohio 43221 (Ohio State University)
Vice President: ORVILLE HUNTER, JR., Iowa State University, 110 Engineering Annex, Ames, Iowa 50010
Secretary: MARTIN H. LEIPOLD, JR., University of Kentucky, Dept. of Materials Science, Lexington, Ky. 40506
Corresponding Secretary: JOHN F. MCMAHON, 13 Sayles St., Alfred, N. Y. 14802 (Consultant)

National Institute of Ceramic Engineers

Trustee: WINSTON DUCKWORTH (1974), Battelle, Columbus Labs, 505 King Ave., Columbus, Ohio 43201
President: EDWARD P. MCNAMARA, 2644 Twohig Ave., San Angelo, Texas 79601 (Monarch-Marshall Tiles, Inc.)
President-Elect: FORREST W. NELSON, A. O. Smith Corp., Box 584, Milwaukee, Wis. 53201
Vice President: ROBERT S. DU FRESNE, Tektronix, Inc., Box 500, Beaverton, Ore. 97005
Secretary: ROBERT E. MOORE, University of Missouri—Rolla, School of Mines & Metallurgy, Rolla, Mo. 65401

TABLE OF CONTENTS

VOLUME 55, 1972

January [No. 1], pp 1–60

1. R. J. Leonard and R. H. Herron: Significance of Oxidation-Reduction Reactions Within BOF Refractories 1
2. H. Bell, V. Krishnamachari, and J. T. Jones: Recovery of High-Temperature Creep-Resistant Substructure in Rutile 6
3. W. W. Stinchcomb and R. A. Queeney: High-Temperature Fatigue Fracture Initiation in MgO Single Crystals 11
4. T. D. Gulden: Carbon Thermal Diffusion in the UC_2-C System 14
5. D. D. Marchant and R. S. Gordon: Grain Size Distributions and Grain Growth in MgO and MgO-Fe_2O_3 Solid Solutions 19
6. Akio Kato and Yasuhide Anju: Expansion of Ag_2O Lattice by Annealing 25
7. F. G. Brockman: Nickel-Zinc Ferrites: IV, Zero Anisotropy in Stoichiometric 50NiO/50ZnO Ferrite Containing 0.5 Mol% CoO—Relation Between 60-Hz and 2.5-MHz Magnetic Losses 28
8. E. W. Kruse III and M. E. Fine: Precipitation Strengthening of MgO by $MgFe_2O_4$ 32
9. G. G. Litvan: Phase Transitions of Adsorbates: IV, Mechanism of Frost Action in Hardened Cement Paste 38
10. P. R. Eusner, L. R. Durden, and L. H. Slack: Unusual Electrical Effects in As-Te Semiconducting Glasses 43

Discussions and Notes

Charles A. Sorrell: PbO Transformation Induced by Water 47
Gerald D. Swanson: Fracture Energies of Ceramics 48
H. Herman and R. K. MacCrone: Comments on "Separation of Phases by Spinodal Decomposition in the Systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3" 50
A. H. Schultz and V. S. Stubican: Reply 50
Bernard Goldstein and David E. Carlson: Determination of the Composition of Glass Surfaces by Auger Spectroscopy 51
R. J. Eagan and C. G. Bergeron: Determination of Water in Lead Borate Glasses 53
R. E. Wright: Acoustic Emission of Aluminum Titanate 54
J. P. Guha and D. Kolar: Identification of $BaO{\cdot}4TiO_2{\cdot}Al_2O_3$ in the System BaO-TiO_2-Al_2O_3 55
P. K. Mehta: Stability of Ettringite on Heating 55
G. H. Jonker: Nature of Aging in Ferroelectric Ceramics 57
F. K. Roehrig and T. R. Wright: Carbide Synthesis by Freeze-Drying 58
D. S. Walters and G. P. Wirtz: Electron Diffraction Superlattice Lines in Magnesium Ferrite 59
Walter C. Tripp and Norman M. Tallan: Revised Weight Change in Nonstoichiometric ZrO_2 60
D. A. Venkatu: Discussion of "Compressive Creep of Rutile at High Temperatures" 60

February [No. 2], pp. 61–116

11. J. E. Shelby: Helium Migration in Natural and Synthetic Vitreous Silica 61
12. Gary C. Vezzoli: Electrical Resistance of Liquid Sulfur to 420°C and of Liquid Selenium to 700°C 65
13. K. J. D. MacKenzie: Infrared Frequency Calculations for Ideal Mullite ($3Al_2O_3{\cdot}2SiO_2$) 68
14. R. A. Jeryan, N. D. Eryou, and L. R. Glicksman: Optical Method of Measuring Temperature in Hot Glass 71
15. J. D. Hancock and J. H. Sharp: Method of Comparing Solid-State Kinetic Data and Its Application to the Decomposition of Kaolinite, Brucite, and $BaCO_3$ 74
16. Shigekazu Minagawa: Kinetics of Growth of Al_2O_3 Whiskers 77
17. S. M. Wiederhorn: A Chemical Interpretation of Static Fatigue 81
18. S. W. Freiman and L. L. Hench: Effect of Crystallization on the Mechanical Properties of Li_2O-SiO_2 Glass-Ceramics 86
19. Roy W. Rice: Deformation, Recrystallization, Strength, and Fracture of Press-Forged Ceramic Crystals 90
20. Robert F. Davis, İlhan A. Aksay, and Joseph A. Pask: Decomposition of Mullite 98
21. W. R. Buessem and R. M. Gruver: Computation of Residual Stresses in Quenched Al_2O_3 101

Discussions and Notes

D. J. Gooch and G. W. Groves: Prismatic Slip in Sapphire 105
C. E. Holcombe, Jr., and O. J. Horne, Jr.: Preparation of Boron Suboxide, B_6O 106
T. Matsuoka, Y. Matsuo, H. Sasaki, and S. Hayakawa: Preparation and Characterization of Cd_2TiWO_7 106
T. Matsuoka, Y. Matsuo, H. Sasaki, and S. Hayakawa: PTCR Behavior of $BaTiO_3$ with Nb_2O_5 and MnO_2 Additives 108
J. C. Wurst and J. A. Nelson: Lineal Intercept Technique for Measuring Grain Size in Two-Phase Polycrystalline Ceramics 109
C. R. Griffiths and R. Russell, Jr.: Time Effects in the Hysteresis Loop of $(Pb,Sr)TiO_3$ 110
Shinobu Yamaoka: Synthesis of $PbZrS_3$ at High Pressures 111
M. J. Ridge and G. A. King: Comments on Use of Reduced Time in Plotting Kinetic Data 112
P. De Maayer, R. De Bruyne, and M. J. Brabers: Decomposition Temperature of $Th(WO_4)_2$ 113
R. J. Brook: Effect of TiO_2 on the Initial Sintering of Al_2O_3 114
C. J. P. Steiner, R. M. Spriggs, and D. P. H. Hasselman: Synergetic Pressure-Sintering of Al_2O_3 115
D. A. Venkatu and D. Lynn Johnson: Analysis of Sintering Equations Pertaining to Constant Rates of Heating—Correction 116

March [No. 3], pp. 117–76

22. J. T. A. Roberts and Y. Ueda: Influence of Porosity on Deformation and Fracture of UO_2 117
23. J. Nemeth, W. V. Youdelis, and J. Gordon Parr: High-Temperature Creep Behavior of Polycrystalline $SrZrO_3$ ... 125
24. R. H. Nafziger and N. Riazance: Alkaline-Earth-Fluoride–LaF_3 Systems with Implications for Electroslag Melting .. 130
25. L. Zikovsky, G. Vagnard, and J. S. Daniel: Kinetics of Recrystallization and Grain Growth in Cu_2O 134
26. Salah Arafa: Titanium Centers Induced in Borate Glasses by Irradiation 137
27. C. Greskovich and K. W. Lay: Grain Growth in Very Porous Al_2O_3 Compacts 142
28. B. Marchese, G. Mascolo, and R. Sersale: Relation of Composition of Hydrogarnet to Resistance to Sulfate Attack 146
29. Jeffrey D. Daw, Patrick S. Nicholson, and J. David Embury: Inhomogeneous Dehydroxylation of Talc 149
30. Ronald C. Garvie and Patrick S. Nicholson: Structure and Thermomechanical Properties of Partially Stabilized Zirconia in the CaO-ZrO_2 System 152
31. S. K. Rhee: Wetting of TaC by Liquid Cu and Liquid Ag 157
32. M. Hayakawa, J. B. Cohen, and T. B. Reed: Measurement of the Lattice Parameter of Wustite at High Temperatures 160

33. E. J. Friebele, L. K. Wilson, and D. L. Kinser: Magnetic Behavior and Microstructure of Vanadium Phosphate Glasses 164
Discussions and Notes
R. A. Penty, D. P. H. Hasselman, and R. M. Spriggs: Young's Modulus of High-Density Polycrystalline Mullite 169
W. Raja Rao and Ivan B. Cutler: Initial Sintering and Surface Diffusion in Al_2O_3 170
G. E. Gazza: Hot-Pressing of $LiAl_5O_8$ 172
K. Hajmrle and R. Angers: Method of Studying Sintering by Electron Microscopy 173
S. Mahajan, J. H. Evans, and P. Wilyman: Stacking Faults and Twins in Nonstoichiometric MoC 174
J. Gebauer, D. P. H. Hasselman, and D. A. Thomas: Effect of Temperature on the Strength of a Polymer-Impregnated Porous Ceramic 175

April [No. 4], pp. 177–224

34. Sidney Diamond: Interactions Between Cement Minerals and Hydroxycarboxylic-Acid Retarders: II, Tricalcium Aluminate-Salicylic Acid Reaction 177
35. Urban E. Schnaus, Ann Marshall, and Cornelius T. Moynihan: Heat Capacities of Glasses and Liquids in the Pseudobinary System $Ge_2As_{\infty-2}S_\infty$ 180
36. Akio Kato, Reiko Nishibashi, Masamitsu Nagano, and Isao Mochida: Relative Activity of Oxygen Ions in Molten Sodium Phosphate as Determined from the Solubility of Sulfur Trioxide 183
37. James W. Fleming, Jr., and Delbert E. Day: Relation of Alkali Mobility and Mechanical Relaxation in Mixed-Alkali Silicate Glasses 186
38. R. L. Holman and R. M. Fulrath: Intrinsic Nonstoichiometry in Single-Phase $Pb(Zr_{0.8}Ti_{0.2})O_3$ 192
39. J. E. Shelby: Helium Migration in TiO_2-SiO_2 Glasses 195
40. J. Gebauer, D. A. Krohn, and D. P. H. Hasselman: Thermal-Stress Fracture of a Thermomechanically Strengthened Aluminosilicate Ceramic 198
41. Warren H. Turner and Judy A. Turner: Ligand-Field Spectra and Structure of Nickel in Silicate Glasses 201
42. D. A. Krohn and D. P. H. Hasselman: Static and Cyclic Fatigue Behavior of a Polycrystalline Alumina 208
43. R. H. Chang and J. B. Wagner, Jr.: Direct-Current Conductivity and Iron Tracer Diffusion in Hematite at High Temperatures 211
44. P. Wagner, J. A. O'Rourke, and P. E. Armstrong: Porosity Effects in Polycrystalline Graphite 214
45. A. K. Varshneya and A. R. Cooper: Diffusion in the System K_2O-SrO-SiO_2: II, Cation Self-Diffusion Coefficients 220
Discussions and Notes
Y. Fujiki, T. Mitsuhashi, and Y. Suzuki: Hydrothermal Growth and Etching of ZrO_2 Crystals 223

May [No. 5], pp. 225–78

46. B. A. Scott and G. Burns: Determination of Stoichiometry Variations in $LiNbO_3$ and $LiTaO_3$ by Raman Powder Spectroscopy 225
47. K. H. Härdtl and D. Hennings: Distribution of *A*-Site and *B*-Site Vacancies in (Pb,La)(Ti,Zr)O_3 Ceramics 230
48. D. W. Johnson, Jr., and P. K. Gallagher: Kinetics of the Thermal Decomposition of $BeSO_4$ 232
49. R. C. Rossi, J. R. Cost, and K. R. Janowski: Influence of the Shape of Dispersed Particles on the Elastic Behavior of Composite Materials 234
50. J. Eustache and R. Magnan: Method for Determining Resistance of Mortars to Sulfate Attack 237
51. I. J. Hastings, J. R. MacEwan, and L. R. Bourque: Effect of Swelling on Thermal Conductivity and Postirradiation Densification of U_3Si 240
52. S. C. Carniglia: Reexamination of Experimental Strength-vs-Grain-Size Data for Ceramics 243
53. T. K. Gupta: Strength Degradation and Crack Propagation in Thermally Shocked Al_2O_3 249
54. A. Ismail A. Abdel-Latif and Delbert E. Day: Internal Friction of Proton-Exchanged Li_2O·Al_2O_3·2SiO_2 Glass 254
55. D. J. Schipper, C. Z. van Doorn, and P. T. Bolwijn: Preparation of Cathodochromic Sodalites 256
56. A. R. Cooper, A. K. Varshneya, S. K. Sarkar, J. Swift, L. Klein, and F. Yen: Some Aspects of the Thermal History of Lunar Glass 260
57. Terrence J. Fennelly and James S. Reed: Mechanics of Pressure Slip Casting 264
58. David W. Richerson and F. A. Hummel: Synthesis and Thermal Expansion of Polycrystalline Cesium Minerals 269
Discussions and Notes
J. P. De Luca and J. M. Leitnaker: Phase Behavior in the Pu-Cr-N System 273
G. L. McVay and E. H. Farnum: Atmosphere Effects on Na Diffusion in Glass 275
T. K. Gupta: Possible Correlation Between Density and Grain Size During Sintering 276
W. F. Brizes and H. D. Brody: Modification of the Nb-C Phase Diagram 277
Ronald C. Garvie and Patrick S. Nicholson: Structure and Thermomechanical Properties of Partially Stabilized Zirconia in the CaO-ZrO_2 System—Correction 278

June [No. 6], pp. 279–330

59. A. Ismail A. Abdel-Latif and Delbert E. Day: Internal Friction of Ion-Exchanged Li_2O·Al_2O_3·2SiO_2 Glass 279
60. Erik J. Sellevold and Cedric W. Richards: Short-Time Creep Transition for Hardened Cement Paste 284
61. I. W. Donald and R. A. McCurrie: Microstructure and Indentation Hardness of an MgO-Li_2O-Al_2O_3-SiO_2-TiO_2 Glass-Ceramic 289
62. Judith A. Osmer and A. B. Chase: Crystallization of BeO, Be_2SiO_4, and SiO_2 from Li_2MoO_4-MoO_3 292
63. Sandford S. Cole, Jr.: Sintering of Ag-Pd in the Presence of a Reactive Glass 296
64. S. K. Rhee: Critical Surface Energies of Al_2O_3 and Graphite 300
65. Ronald C. Garvie and Patrick S. Nicholson: Phase Analysis in Zirconia Systems 303
66. J. R. Blachere and J. E. Young: The Freezing Point of Water in Porous Glass 306
67. Paul Fierens and Jean-Pierre Verhaegen: Structure and Reactivity of Chromium-Doped Tricalcium Silicate 309
68. A. K. Varshneya and A. R. Cooper: Diffusion in the System K_2O-SrO-SiO_2: III, Interdiffusion Coefficients 312
69. H. S. Maiti, K. V. G. K. Gokhale, and E. C. Subbarao: Kinetics and Burst Phenomenon in ZrO_2 Transformation 317
Discussions and Notes
D. Garcia and D. Spiedel: Reexamination of the System TiO_2-SnO_2 322
Shigeharu Naka, Suketoshi Ito, and Michio Inagaki: Effect of Shear on the Quartz-Coesite Transition 323
C. Greskovich, C. R. O'Clair, and M. J. Curran: Preparation of Transparent Y_2O_3-Doped ThO_2 324
J. J. Rasmussen: Surface Tension, Density, and Volume Change on Melting of Al_2O_3 Systems, Cr_2O_3, and Sm_2O_3 326
D. Lynn Johnson: Discussion of "Effect of Additives on Sintering of CaF_2" 327
N. A. Haroun: Reply 328
A. Fort, D. Sharp, B. Ash, K. Papworth, and D. Reed: Influence of Liquid Environments on the Strength of Ferrite Memory Cores 329
H. Lessoff: Comments on "Influence of Liquid Environments on the Strength of Ferrite Memory Cores" 330

July [No. 7], pp. 331–80

70. B. A. Scott and Gerald Burns: Crystal Growth and Observation of the Ferrolectric Phase of $PbZrO_3$ 331
71. I. A. Cutter and R. McPherson: Surface Domain Reorientation Produced by Abrasion and Annealing of Polycrystalline $BaTiO_3$ 334
72. D. E. Carlson, K. W. Hang, and G. F. Stockdale: Electrode "Polarization" in Alkali-Containing Glasses 337
73. W. R. Manning, O. Hunter, Jr., F. W. Calderwood, and D. W. Stacy: Thermal Expansion of Nb_2O_5 342
74. Richard E. Ely: Strength of Titania and Aluminum Silicate Under Combined Stresses 347
75. Patrick V. McAllister and Ivan B. Cutler: Thermal Grooving of MgO and Al_2O_3 351
76. S. W. Freiman, G. Y. Onoda, Jr., and A. G. Pincus: Controlled Spherulitic Crystallization in $3BaO\text{-}5SiO_2$ Glass 354
77. Murli H. Manghnani: Pressure and Temperature Dependence of the Elastic Moduli of $Na_2O\text{-}TiO_2\text{-}SiO_2$ Glasses 360
78. I. D. Aggarwal, C. T. Moynihan, P. B. Macedo, J. J. Mecholsky, and G. R. Srinivasan: Glass Formation in the Pseudobinary Metallic Selenide Systems $M_mSe_n\text{-}Ge_{1.5}As_{0.5}Se_3$ 366
79. Foster L. Harding: Dependence of Melt Oxygen Activity and Water Retention on Composition of Amber Glass 368
80. A. W. Dozier, L. K. Wilson, E. J. Friebele, and D. L. Kinser: Correlation of Structure and Electrical Properties of $55FeO\text{-}45P_2O_5$ Glass 373

Discussions and Notes

Yasuhiko Kuwano and Ken-ichi Shiroki: Preparation of Neodymium Hydroxide by Vapor-Phase Reaction 378
M. O. Marlowe: Simulation of Gaseous Fission Products in UO_2 379
L. G. Cordone and W. E. Martinsen: Glow-Discharge Apparatus for Rapid Sintering of Al_2O_3 380

August [No. 8], pp. 381–432

81. Terrence J. Fennelly and James S. Reed: Compression Permeability of Al_2O_3 Cakes Formed by Pressure Slip Casting 381
82. J. L. Woolfrey: Effect of Green Density on the Initial-Stage Sintering Kinetics of UO_2 383
83. J. L. Woolfrey and M. J. Bannister: Nonisothermal Techniques for Studying Initial-Stage Sintering 390
84. Richard F. Cooley and James S. Reed: Equilibrium Cation Distribution in $NiAl_2O_4$, $CuAl_2O_4$ and $ZnAl_2O_4$ Spinels 395
85. R. J. Huang, T. Demirel, and T. D. McGee: Adsorption of Water Vapor on E-Glass 399
86. Sidney Diamond: Interactions Between Cement Minerals and Hydroxycarboxylic-Acid Retarders: III, Infrared Spectral Identification of the Aluminosalicylate Complex 405
87. R. W. Lynch and B. Morosin: Thermal Expansion, Compressibility, and Polymorphism in Hafnium and Zirconium Titanates 409
88. S. E. Khalafalla and L. A. Haas: Kinetics of Carbothermal Reduction of Quartz Under Vacuum 414
89. A. K. Varshneya and A. R. Cooper: Diffusion in the System $K_2O\text{-}SrO\text{-}SiO_2$: IV, Mobility Model, Electrostatic Effects, and Multicomponent Diffusion 418
90. R. R. Shaw and J. F. Breedis: Secondary Phase Separation in Lead Borate Glasses 422

Discussions and Notes

R. Angers, R. Tremblay, and A. C. D. Chaklader: Formation of $CaZrO_3$ by Solid-State Reaction Between CaO and ZrO_2 425
C. L. McDaniel: Phase Relations in the CaO-Pt System in Air 426
T. D. Chikalla, C. E. McNeilly, and F. P. Roberts: Polymorphic Modifications of Pm_2O_3 428
T. K. Gupta: Strength Behavior of Thermally Shocked ZnO 429
Terence G. Langdon: Grain-Boundary Sliding in Ceramics 430
F. Galasso, U. Kuntz, and William J. Croft: Pyrolytic Si_3N_4 431
J. W. Vail and J. D. de Wet: Hydrogarnet Phase in Kaolinite-Lime-Water Slurries 432

September [No. 9], pp. 433–84

91. P. D. Ownby and G. E. Jungquist: Final Sintering of Cr_2O_3 433
92. Robert B. Leonesio: Fracture and Healing Effects in Mica Crystals 437
93. Arun Kumar, Dilip Rajdev, and D. L. Douglass: Effect of Oxide Defect Structure on the Electrical Properties of ZrO_2 439
94. David G. Grossman: Machinable Glass-Ceramics Based on Tetrasilicic Mica 446
95. R. S. Gordon and G. R. Terwilliger: Transient Creep in Fe-Doped Polycrystalline MgO 450
96. J. A. Coppola and R. C. Bradt: Measurement of Fracture Surface Energy of SiC 455
97. J. Wheeler and S. Chatterji: Settling of Particles in Fresh Cement Pastes 461
98. Richard L. Newman: Prediction of Thermal-Shock Resistance During Heating at Very High Rates 464
99. Arvind S. Burte and Patrick S. Nicholson: Influence of Anisotropy and Water Vapor on the Solid-State Reaction of CaO and Beta Quartz 469
100. Tokuji Yamamoto, Sumio Sakka, and Megumi Tashiro: Formation of Defects in Glass Under Electron Bombardment 473
101. G. I. Solovyev and K. E. Spear: Phase Behavior in the Sm-B System 475

Discussions and Notes

F. H. Cocks and R. W. Stormont: Rutile Substructures in Barium Magnesium Titanate 479
J. A. Coppola, D. A. Krohn, and D. P. H. Hasselman: Strength Loss of Brittle Ceramics Subjected to Severe Thermal Shock 481
Denzil W. Stacy, J. Keith Johnstone, and D. R. Wilder: Axial Thermal Expansion of HfO_2 482
P. L. Bollin: Glass Formation in the System $Cs_2O\text{-}Al_2O_3\text{-}SiO_2$ 483
P. W. D. Mitchell: Chemical Method for Preparing $MgAl_2O_4$ Spinel 484

October [No. 10], pp. 485–540

102. W. A. Klemm and R. L. Berger: Calcination and Cementing Properties of $CaCO_3\text{-}SiO_2$ Mixtures 485
103. T. J. Higgins, P. B. Macedo, and V. Volterra: Mechanical and Ionic Relaxation in $Na_2O\cdot 3SiO_2$ Glass 488
104. V. Provenzano, L. P. Boesch, V. Volterra, C. T. Moynihan, and P. B. Macedo: Electrical Relaxation in $Na_2O\cdot 3SiO_2$ Glass 492
105. J. T. Krause and H. M. O'Bryan, Jr.: Acoustic Detection of Ferroelectric Phase Transitions in PLZT Ceramics 497
106. Jesse J. Brown, Jr.: Phase Equilibria in the System $SrO\text{-}CdO\text{-}V_2O_5$ 500
107. A. H. Meitzler and H. M. O'Bryan, Jr.: Lanthanum Dependence of Elastic and Piezoelectric Properties of PLZT Ceramics with a Zr/Ti Ratio of 65/35 504
108. C. F. Yen and R. L. Coble: Spheroidization of Tubular Voids in Al_2O_3 Crystals at High Temperatures 507
109. F. V. DiMarcello, P. L. Key, and J. C. Williams: Preferred Orientation in Al_2O_3 Substrates 509
110. Eric R. Kreidler: Phase Equilibria in the System $CaO\text{-}BaO\text{-}WO_3$ 514
111. George P. Halbfinger and Morris Kolodney: Activated Sintering of ThO_2 and $ThO_2\text{-}Y_2O_3$ with NiO 519
112. Robert F. Davis and Joseph A. Pask: Diffusion and Reaction Studies in the System $Al_2O_3\text{-}SiO_2$ 525

Discussions and Notes
Douglas F. Craig and F. A. Hummel: Zirconium Pyrovanadate Transitions 532
Takashi Shimizu and Hiroshi Hara: Oxidation of CO on La_2O_3-Doped $BaTiO_3$ 533
Mario Collepardi, Aldo Marcialis, and Renato Turriziani: Penetration of Chloride Ions into Cement Pastes and Concretes 534
M. S. Abdel-Azim and M. Vlajic: Method for Determining Particle Size 535
Raymond DiSalvo, Della M. Roy, and L. N. Mulay: EPR Studies of Radiation Damage in Hydrogen-Impregnated Glass 536
J. Sestak, K. Zaveta, V. Roskovec, and F. Zounova: Preparation and Magnetic Properties of the Glassy System MnO-Fe_2O_3-B_2O_3 537
Takeshi Takamori and Rustum Roy: Preparation of Thin Glass Films for Transmission Electron Microscopy by Splat Cooling 538
G. J. Conger and H. U. Anderson: Nonstoichiometry in $BaTiO_3$ 539
Nobuo Setaka and Koichi Ajiri: Influence of Vapor-Phase Composition on Morphology of SiC Single Crystals 540

November [No. 11], pp. 541–84

113. L. M. Brown and K. S. Mazdiyasni: Cold-Pressing and Low-Temperature Sintering of Alkoxy-Derived PLZT 541
114. B. G. Childs, P. J. Harvey, and J. B. Hallett: Optical Absorption Spectroscopy of ThO_2 544
115. K. S. Mazdiyasni and L. M. Brown: Synthesis and Mechanical Properties of Stoichiometric Aluminum Silicate (Mullite) 548
116. Sumio Sakka and J. D. Mackenzie: Phototropic Glasses Activated by TlCl 553
117. A. G. Crouch: High-Temperature Deformation of Polycrystalline Fe_2O_3 558
118. C. E. Bamberger and C. F. Baes, Jr.: Equilibria of SiF_4 with SiO_2, Be_2SiO_4, and BeO in Molten Li_2BeF_4 564
119. H. L. Marcus and M. E. Fine: Grain-Boundary Segregation in MgO-Doped Al_2O_3 568
120. R. G. St-Jacques and R. Angers: Creep of CaO-Stabilized ZrO_2 571
121. D. Chatterji and R. W. Vest: Thermodynamic Properties of the System Indium-Oxygen 575
Discussions and Notes
E. W. Piche and G. A. Rubin: Effect of Pressure on the Dielectric Strength of Sapphire 578
M. Kunugi, N. Soga, H. Sawa, and A. Konishi: Thermal Conductivity of Cristobalite 580
S. K. Rhee: Discussion of "Porosity Effects in Polycrystalline Graphite" 580
E. Carnall, Jr.: Hot-Pressing of ZnS and CdTe 582
Sudarsan C. Samanta and Robert L. Coble: Correlation of Grain Size and Density During Intermediate-Stage Sintering of Ag 583
Sergio Deganello: A High-Temperature Modification of Gamma Na_2BeF_4 584
A. K. Varshneya and A. R. Cooper: Diffusion in the System K_2O-SrO-SiO_2: III, Interdiffusion Coefficients and IV, Mobility Model, Electrostatic Effects, and Multicomponent Diffusion—Corrections 584

December [No. 12], pp. 585–648

122. James M. Fields, Jr., Paul S. Dear, and Jesse J. Brown, Jr.: Phase Equilibria in the System BaO-SrO-SiO_2 585
123. D. P. H. Hasselman, J. Gebauer, and J. A. Manson: Elastic Behavior of Polymer-Impregnated Porous Ceramics 588
124. N. H. Christensen and O. Bang: Diffusion and Convection in Reactions of Slag with Porous Ceramic Bodies 592
125. A. S. Rao and A. C. D. Chaklader: Plastic Flow During Hot-Pressing 596
126. T. B. Lindemer: Kinetics of the UO_2-C-N_2 Reaction at 1700°C 601
127. J. B. Bilde-Sörensen: Dislocation Structures in Creep-Deformed Polycrystalline MgO 606
128. S. C. Carniglia: Working Model for Porosity Effects on the Uniaxial Strength of Ceramics 610
129. G. Pieper, W. Eysel, and Th. Hahn: Solid Solubility and Polymorphism in the System Sr_2SiO_4-Sr_2GeO_4-Ba_2GeO_4-Ba_2SiO_4 619
130. A. A. Solomon: Influence of Impurity Particles on the Fracture of UO_2 622
131. S. K. Sarkar, A. D. Miller, and J. I. Mueller: Solubility of Oxygen in ZrC 628
Discussions and Notes
Terence G. Langdon: Dependence of Creep Rate on Porosity 630
W. S. Hulscher and G. H. Jonker: Comment on "Electron Diffraction Superlattice Lines in Magnesium Ferrite" 632
G. P. Wirtz: Reply 632
K. S. Mazdiyasni and L. M. Brown: Synthesis of Nb_2O_5-Doped $BaTiO_3$ with Improved Electrical Properties 633
Author Index to *The Journal* 635
Subject Index to *The Journal* 637

CERAMIC ABSTRACTS

December 1972 *SECTION*

Compiled by the American Ceramic Society

AUTHOR INDEX FOR 1972

The number in parentheses refers to the issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the issue number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates position of the abstract on the page.

Abakumov, V. B. See Kestner, O. E.
Abate-Daga, G., and Amato, I. Preparation and characterization of a "molecular" cermet of U-Mo oxide, (1) 15*i*.
Abbakumov, V. G. See Shumilin, A. A.
Abbey, W. See Gooding, R. W.
Abbott, C. E., Barnes, G. A., and McEntee, J. F. A. Thermoelectric device, P (4) 91*c*.
Abbott, F. R. Low-frequency electroceramic sonar transducer, P (8) 201*b*.
Abboud, H. I., and Furnish, O. C. [Rotary] kiln preheat and drying section, P (1) 19*e*.
Abbruscato, V. J. See Palilla, F. C.
Abdel-Azim, M. S. See Haroun, N. A.
Abdel-Azim, M. S., and Vlajic, M. Method for determining particle size, (11) 278*a*.
Abd-El-Enein, S. A. See Mikhail, R. S.
Abd-El-Khalik, M. See Mikhail, R. S.
Abdel-Latif, A. I. A., and Day, D. E. Internal friction of ion-exchanged $Li_2O{\cdot}Al_2O_3{\cdot}2SiO_2$ glass, (7) 159*d*. Internal friction of proton-exchanged $Li_2O{\cdot}Al_2O_3{\cdot}2SiO_2$ glass, (6) 132*b*.
Abdurakhmanov, R. A. See Berg, L. G.
Abe, Hiroshi. See Nishikawa, Tomozo.
Abe, Masanori, Kawachi, M., and Nomura, S. Compensation temp. of spontaneous magnetization in spinel Fe_2MoO_4, (3) 72*f*.
Abe, Shinjun. See Tomita, Kinzo.
Abe, Yoshihiro. See Naruse, Akira.
Abeck, W., Kober, H., and Seidel, B. Magnetic material and method of making, P (7) 169*b*.
Abeshouse, D. J., Zimmerman, G. O., Kelland, D. R., and Maxwell, E. Low-temp. phase transition in Ce Mg nitrate, (6) 150*b*.
Aboaf, J. A. Some properties of vapor-deposited Si_3N_4 films obtained by the reaction of $SiBr_4$ and NH_3, (2) 39*c*. Stresses in SiO_2 films obtained from the thermal decomposition of tetraethyl orthosilicate—effect of heat treatment and humidity, (2) 39*d*.
Abou-El-Azm, A., and El-Batal, H. A. Absorption of Cr(III) ions in ternary alkali and alkaline earth oxide-SiO_2 glasses, (11) 267*g*.
Aboutboul, H. A. See Krekeler, J. H.
Aboutboul, H. A., Kirch, W., and Krekeler, J. H. Preparation of SiO_2 gels, P (7) 175*e*.
Aboutboul, H. A., Krekeler, J. H., and Kirch, W. Preparation of SiO_2 gels, P (7) 175*e*.
Abouzeid, A. Z. M., and Fuerstenau, D. W. Effect of humidity on mixing of particulate solids, (7) 172*b*.
Abraham, K. P. See Rao, V. V. V. N. S. R.
Abraham, M. M., Finch, C. B., Reynolds, R. W., and Zeldes, H. ESR spectrum of divalent Eu in ThO_2, (6) 147*b*.
Abrahams, J. H., Jr. See Shutt, T. C.
Abrahams, S. C. Ferroelasticity, (2) 38*g*.
Abrahams, S. C., and Bernstein, J. L. Ferroelastic effect in $RbFeF_4$ and $CsFeF_4$, (11) 281*i*.
Abramovici, R., and Enache, M. Calculation of the optimum size ratio between particles of 2 substances reacting in the solid state, (5) 118*d*.
Abratis, H., Kaboth, D., and Klose, G. R. Chemical behavior of refractories in contact with molten steels under vacuum conditions, (5) 109*a*.
Abrikosov, N. Kh., Skudnova, E. V., Poretskaya, L. V., and Osinova, T. A. System Bi-Pb-Te, (9) 239*d*.
Accettura, F. See MacKenzie, D. J.
Acello, S. J. Ceramic capacitor terminals, P (9) 224*i*.
Acker, E. G. See Winyall, M. E.
Ackermann, R. J., and Sorrell, C. A. Thermal expansion and orthorhombic-tetragonal transition of the WO_3 phase, (8) 211*j*.
Acoveno, F. Production of CuO, NiO, and ZnO, P (6) 144*d*.
Adams, A. L. See King, L. C.
Adams, A. L., and Dachs, L. L. Emerging composites, (2) 31*h*.
Adams, A. L., Yearsley, G. A., Simmons, M. I., and Yager, B. P. Method of ball bonding with an automatic semiconductor bonding machine, P (5) 113*e*.
Adams, J. See Manley, B. W.
Adams, J. R. Spraying equipment as related to air pollution, (10) 254*e*.
Adams, R. B. See Stuart, W. I.
Adamski, J. A., Jackson, W. B., and Maher, R. D. Verneuil crystallizer with powder bypass means, P (1) 15*a*.
Adamski, J. A., and Weiner, J. R. Postmix gas ring burner, P (2) 45*h*.
Adamson, M. G. Thermal diffusion of O in hyperstoichiometric urania with very low C content, (7) 171*c*.
Addamiano, A., and Perusek, R. J. Single-crystal SiC display device, P (4) 90*h*.
Addison, J. R. See Lichtenberger, G. J.
Addiss, R. R., Jr. See Ghosh, A. K.; Lauer, R. B.
Adelmeier, E. "Bearded-man" and "schnelle" stoneware in Germany—an exhibition in Cologne, (5) 101*j*.
Adel'son, L. M. See Tkachev, V. V.
Adhav, R. S. Linear electrooptic effects in tetragonal phosphates and arsenates, (1) 11*c*.
Adkinson, A. R., Carter, R. G., and Harland, G. E., Jr. Mesa-type semiconductor device, P (3) 65*b*.
Adler, D. Amorphous Semiconductors, B (10) 262*c*.
Adler, I. See Yin, Lo I.
Adler, J. G. See Geiger, A. L.
Adler, L. See Whaley, H. L.
Adler, L., and Whaley, H. L. Ultrasonic flaw determination by spectral analysis, P (8) 206*a*.
Adshead, D. G. Package tunnel kilns and the Permak system, (2) 45*i*.
Aerts, L. J., Bairiot, H. F. J. G., and van Asbroeck, P. L. Fuel element, P (4) 91*f*.
Afinogenov, F. I. See Nekrasov, N. N.
Afinogenov, Yu. P., and Belozerova, L. P. System $3SnCl_2+2Al=2AlCl_3+3Sn$, (5) 124*g*.
Afinogenov, Yu. P., and Khaustova, Z. N. System $TeCl_4$-TlCl, (8) 211*h*.
Afonskii, N. S. See Lykova, L. N.
Agarwal, B. D., Panizza, G. A., and Broutman, L. J. Micromechanics analysis of porous and filled ceramic composites, (1) 17*j*.
Agarwal, B. P. See Patel, A. R.
Aggarwal, I. D., Moynihan, C. T., Macedo, P. B., Mecholsky, J. J., and Srinivasan, G. R. Glass formation in the pseudobinary metallic selenide systems M_nSe_n-$Ge_{1.5}As_{0.5}Se_3$, (8) 190*a*.
Aggarwal, P. S., Gard, J. A., Glasser, F. P., and Biggar, G. M. Synthesis and properties of $2CaO{\cdot}Al_2O_3$, (8) 188*c*.
Aginsky, D. M. Upgrading dimensional quality of pressed products, (9) 221*d*.
Aglietti, G. See Barilli, F.
Agrawal, M. P., and Bhandari, R. C. Thermal formation factor of consolidated porous medium—sandstones, (3) 71*g*.
Agrios, J. P., and Lipetz, N. Slot line nonreciprocal phase shifter, P (1) 14*f*.
Agusta, B. Inversion prevention system for semiconductor devices, P (2) 40*e*.
Agusta, B., and Sahni, R. J. Process of producing an array of integrated circuits on semiconductor substrate, P (2) 42*d*.
Aharoni, S. M. See Litt, M. H.
Ahmad, N. See Davis, C. E.
Ahmed, S., and Weintroub, S. Chemical and thermal etching of Te single crystals, (7) 176*d*.
Ahn, B. H., Shurtz, R. R., and Trussell, C. W. Dependence of growth properties of Si-doped GaAs epitaxial layers on orientation, (5) 111*j*.
Ahn, Kie Y. Transition metal-doped EuO films, P (5) 114*d*.
Ahn, Kie Y., and Methfessel, S. Magneto-optical elements, P (5) 113*c*.
Ahn, Kie Y., and Park, K. C. Bistable resistor of EuO, EuS, or EuSe doped with 3*d* transition or VA element, P (7) 168*i*.
Aikawa, Katsuaki. See Furuuchi, Shigemasa.
Aiki, Kunio, Narita, K., Tanabe, M., and Takaoka, S. ESR studies of Gd^{3+} ion in La_2O_2S single crystal, (4) 96*e*.
Ainger, F. W., Bickley, W. P., and Smith, G. V. Search for new ferroelectrics with the W bronze structure, (7) 167*g*.
Ainsworth, J. H., and Moore, R. E. Frequency-phase technique for damping measurements applied to several materials at elevated temps., (5) 116*f*.
Aisenberg, S., and Chabot, R. Ion-beam deposition of thin films of diamondlike C, (6) 149*b*.
Aitken, M. J. Authenticity of vessels and figurines in the Hacilar style (II) thermoluminescence tests, (5) 101*h*.
Aizenberg, A. N. Phase chemical analysis of high-Al_2O_3 refractory after service in Cu smelting furnace, (8) 195*b*.
Aizu, Keitsiro. Inferred temp. dependences of electrical, mechanical, and optical properties of ferroelectric-ferroelastic $Gd_2(MoO_4)_3$, (3) 73*h*.
Ajersch, F. See Bale, C. W.
Ajichi, Yoshio. See Kitamura, Toshinori.
Ajiri, Koichi. See Setaka, Nobuo.
Akagi, S. See Toyuki, H.
Akahane, Ryozo. See Katsuta, Yukio.
Akai, Shinichi, and Shimoda, T. Ga compounds with reduced Si contamination and method of mfg., P (3) 65*b*.
Akaishi, Takao. See Ohmae, Kenji.
Akasaki, Isamu. Process of fabricating electroluminescent element, P (6) 139*e*.
Akashi, Naotomo. See Ito, Kuniniko.
Akashi, Tsuneo. See Ohno, Tomeji; Sugano, Izuru.
Akashi, Tsuneo, Sugano, I., Okuda, T., Onodo, Y., and Tsuji, T. Heat-treating sintered Mn-Zn ferrites to improve properties, P (7) 168*j*.
Akatsu, Ken, and Higuchi, K. Strength and color of portland cement clinker burned in a reducing atm, (9) 215*a*. Studies on cement clinker (VII) effects of burning condition on the grindability and bulk wt of portland cement clinker, (4) 79*d*.
Akatsu, Ken, and Ikeda, I. Studies on cement clinker (VIII) effects of "solid" and "liquid" phases on the grindability and bulk wt of portland cement clinker, (4) 79*d*.
Akatsu, Ken, Maeda, K., and Ikeda, I. Effect of Cr_2O_3 and P_2O_5 on the strength and color of portland cement clinker, (9) 214*f*.
Akazawa, Hakuichi, Washio, S., Kaji, K., and Fujita, S. Production of gypsum, P (6) 130*g*.
Akeyoshi, Kazuyuki, and Hayashi, N. Electrically heatable glass product and method for production, P (3) 58*a*.
Akhunov, A. M., Maxutov, R., Gubarev, Y. F., Zalyaliev, M. A., Sabirov, I. M., and Imamutdinova, K. Kh. Apparatus for welding

glass rods, particularly tubular glass rods, P (3) 57*g*.
Akiba, Tokuji. See Mori, Hitoaki.
Akimoto, Syuniti, and Syono, Y. High-pressure transformations in $MnSiO_3$, (9) 235*j*.
Akimoto, Yasumasa, Sato, M., Hoshino, Y., and Satou, M. Preparation and magnetic characteristics of chemically deposited fine Co particles, (11) 274*e*.
Akinina, Z. S. See Semenov-Kobzar, A. A.
Akino, Toshiro, and Motizuki, K. Spin configuration of magnetic ions on B-sites in normal cubic spinels, (3) 75*j*.
Akita, Minoru. See Watanabe, Shigeo.
Aksay, I. A. See Davis, R. F.
Akstinat, M. H. Drawing compounds for metals which are to be enameled, (5) 105*a*.
Akulich, S., and Demidovich, B. Manufacture of cellular glass and the possibilities of its technological development in the USSR, (2) 32*i*.
Akulova, G. I. See Shindel'man, Yu. I.
Aladjem, A. Metal oxide film structure, P (10) 251*g*.
Albers, W., and Verberkt, J. Semiconductor heterojunction device, P (5) 114*f*.
Albers, W. A., Jr. (editor). Physics of Opto-Electronic Materials, B (2) 51*j*. Process for making tetragonal GeO_2, P (9) 227*j*.
Albers, W. A., Jr., and Swets, D. E. Process of abrading with GeO_2, P (4) 77*h*.
Albers, E. W. See Maher, P. K.; Scherzer, J.
Albert, J. Basic principles in the examination of composition and ceramic and technological properties of brick clays, (5) 108*b*.
Albert, R. E. Process for the preparation of mullite-bonded refractory materials, P (2) 37*d*.
Albert, R. J., and Hoge, J. H. Aggregate containing a treatment agent for improving concrete properties, P (7) 157*b*.
Albertini, E. Method of making firing setters for tiles and other ceramic articles, P (8) 196*g*.
Albrecht, C., and Proper, J. Method of determining noise in X-ray films, (9) 231*h*.
Albrecht, P. Miniature light bulb, P (3) 59*i*.
Albrecht, W. L. Method of preparing SiO_2 sols containing large-particle-size SiO_2, P (10) 257*i*.
Albus, P. Method of producing an hf Si transistor, P (4) 89*i*. Planar technique for producing semiconductor microcomponents, P (10) 252*j*.
Alcock, C. B. See Lee, H. M.
Alderoft, D., Bye, G. C., and Chigbo, G. O. Crystallization processes in Al hydroxide gels (V) study by N adsorption of some factors influencing the porous texture of pseudoboehmite xerogels, (2) 47*h*.
Alderdice, D. S., Collins, G., and Foon, R. Induced electron emission processes and the Einstein photoelectric law, (4) 97*g*.
Aldridge, F. T. Process of making acicular, stable magnetic Fe particles, P (3) 67*a*.
Aleixandre Ferrandis, V. Porosity and its effects on the technical properties of ceramic products, (4) 98*g*.
Alekseenko, L. A. See Yakunina, G. M.
Alekseev, F. P. See Mokhosoev, M. V.
Alekseeva, A. N., and Val'kovskaya, L. I. Effect of some properties of aluminosilicate refractories on their glass resistance, (8) 195*d*.
Alekseeva, L. S. See Sterlyadkina, Z. K.
Alekseeva, Z. D. Polymorphism of the silicates of Rb and Cs, (8) 210*e*.
Alekseyuk, L. A. Preparation of Sc-containing Ni ferrites by the hydroxide-coprecipitation technique, (10) 249*g*.
Aleonard, S. See Pontonnier, L.
Aleshin, B. N., Kireev, P. S., Ryabov, V. A., and Fedoseev, D. V. Strength of glass fibers, (8) 191*h*.
Alexander, D. E. Supporting insulator for electrical heating elements, P (9) 223*e*.
Alexander, D. G., and Carlson, O. N. V-VO phase system, (6) 153*a*.
Alexander, G. E. See Sutarno.
Alexander, J. A. Arcuate shaped composites of refractory tapes embedded in a metal matrix, P (6) 135*e*.
Alexander, J. H. See Sterling, H. F.
Alexeev, A. I. See Ryss, Yu. S.
Alford, W. J. See Fay, H.
Alfs, H. See List, F.
Ali, A. See Samdani, S. G.
Ali, M. A., Majumdar, A. J., and Rayment, D. L. C fiber reinforcement of cement, (7) 156*d*.
Ali, M. A., and Pincus, A. G. Uv-transmitting borosilicate glass composition and article, P (9) 220*b*.
Ali, M. A., Schwartz, M. A., and Li, Pei-Ching. Zn-La borate glass composition, P (10) 245*j*.
Alig, R. C., Kiss, Z. J., Brown, J. P., and McClure, D. S. Energy levels of Ce^{3+} in CaF_2, (6) 147*f*.
Alkemade, C. Th. J. See Kalff, P. J.
Allais, G. See Maisseu, A.
Allan, W. B. See Smith, Howard C.
Allen, C. A., and Lund, D. F. Dynamic MOS memory array chip, P (11) 274*f*.
Allen, C. H., and Leach, C. E. Tm oxide heat source and method for forming, P (1) 16*e*.
Allen, D. R. See Sawabini, C. T.
Allen, E. M. Process for preparing pigmentary metal oxide [TiO_2], P (7) 175*h*.
Allen, H. A., and Mehal, E. W. Deposition of epitaxial $InAs_xP_{(1-x)}$ on GaAs and GaP substrates, (9) 234*i*.
Allen, J. E. Shaft or stack furnace and method and apparatus for lining, P (10) 248*d*.
Allen, J. W., Macfarlane, R. M., and White, Robert L. Magnetic Davydov splittings in the optical absorption spectrum of Cr_2O_3, (5) 121*d*.
Allen, L. R. B_4C film product, P (9) 222*b*. Composite materials with flake reinforcement, P (8) 196*g*.
Allen, M. A. See Villers, P.
Allen, T. Method and apparatus for determination of particle-size distribution, P (9) 231*i*.
Alliegro, R. A., and Learned, A. W., III. Composite ceramic armor with metallic support strip, P (11) 273*b*.
Allington, T. R. Method of electrically mounting components in hybrid circuits, P (10) 251*b*. Method of making a thick-film hybrid circuit, P (9) 226*b*.
Allington, T. R., and McClellan, J. R. Method of adjusting the resistivity of thick-film screen-printed resistors, P (8) 201*i*.
Allison, D. F. Semiconductor structure with dielectric and air isolation and method, P (8) 202*b*. See Camenzind, H. R.
Allison, J. B. See Erhard, A. E.
Allnatt, A. R., and Sime, S. J. Premelting electrical conductivity of crystalline NaCl, (5) 122*f*.
Allnutt, A. J. See West, R. N.
Allpress, J. G. Crystallographic shear in WO_3·xNb_2O_5 (x=0.03–0.09), (10) 258*j*.
Allred, W. P. See Willardson, R. K.
Almasi, J. C., and Martin, W. S. Face-pumped laser device with laterally positioned pumping means, P (10) 250*c*.
Alms, E. E., and Mitchell, J. E. Pilot for gas burner, P (6) 143*c*.
Aloi, A. S. See Kirgintsev, A. N.
Alper, A. M. (editor). High Temp. Oxides (Part IV) Refractory Glasses, Glass-Ceramics, and Ceramics, B (4) 100*g*.
Alper, A. M., Doman, R. C., Johnson, N. E., and McNally, R. N. Fusion-cast carbide ceramic comprising free Si, P (9) 222*f*.
Alper, A. M., Lewis, R. M., and McNally, R. N. ZrO_2-Al_2O_3-SiO_2 fusion-cast refractory, P (4) 85*b*.
Alpert, M. B., and Preston, J. P. Photoconductive TiO_2 composition and method of preparation, P (4) 94*e*.
Alpert, N. L. Keiser, W. E., and Szymanski, H. A. (editors). IR Theory and Practice of Infrared Spectroscopy, B (4) 100*c*.
Alt, G. Hammer crusher, P (3) 71*j*.
Altekar, V. A. See Athavole, A. S.
Altenburger, E. G. See King, L. C.
Alterovitz, S., and Gerlich, D. Third-order elastic moduli of CaF_2, (5) 125*d*.
Alvarez, A. G. See Thomas, H. J.
Alvarez-Estrada, D., and Duran Botia, P. V_2O_5 attack on basic refractories in glass furnace regenerators, (4) 84*e*, (10) 247*a*.
Alvero, J. S. Cellular concrete and method for producing, P (3) 54*e*.
Alves, R. V. See Sobon, L. E.
Alves, R. V., Buchanan, R. A., Wickersheim, K. A., and Yates, E. A. C. Nd-activated La oxysulfide—a new high-gain laser material, (5) 112*a*.
Amato, I. See Abate-Daga, G.
Amato, I., and Negro, A. Sintered glass-ceramics derived from the system Al_2O_3-MgO-SiO_2 with ZrO_2 as a nucleating agent, (4) 81*a*.
Ambs, H. Structural isotypes of hematite, corundum, calcite, and quartz, (1) 25*j*.
Amelinckx, S. See De Ridder, R.; van Landuyt, J.
Amemiya, Toshioki. See Masuyama, Takeshi.
Amemiya, Yoshihide. See Somiya, Shigeyuki.
Amero, J. J. Crystalline abrasive Al_2O_3, P (2) 29*f*. See Jones, Cecil M., II.
Amick, J. A. See Shaw, J. M.
Amin, R. B., and Hoffman, L. C. Air firable compositions containing V oxide and B and devices therefrom, P (3) 64*c*.
Ammermann, F. E. See Teague, D. M.
Amodei, J. J. Nonlinear coloration effects in transition-metal-doped $SrTiO_3$ crystals, (6) 150*c*.
Amos, R. W. J. See Drake, C. F.
Amster, R. L. Photosensitization of Tb fluorescence by Eu in CaF_2, (9) 237*f*. Sr thiogallate phosphors coactivated by Ce and Nd, P (3) 67*i*.
Amzallag, E., Chang, Tung Symon, Johnson, B. C., Pantell, R. H., and Puthoff, H. E. Stimulated Raman and polariton scattering in $LiIO_3$, (5) 124*f*.
Amzallag, E., Chang, Tung Symon, Pantell, R. H., and Feigelson, R. S. Raman scattering by $Sr_xBa_{1-x}Nb_2O_6$, (5) 123*d*.
Anand, Y. See Howell, C. M.
Anantaraman, S. Glass-lined reactors for corrosive service, (11) 267*d*.
Anantha, N. G. Surface barrier transistor, P (2) 42*h*.
Anastasia, L. J. See Jonke, A. A.
Anastassakis, E. Stark effect on impurity levels in diamond, (6) 151*j*.
Anbo, Eiji. See Watanabe, Koichi.
Andeen, C., Fontanella, J., and Schuele, D. Low-frequency dielectric constants of the alkaline earth fluorides by the method of substitution, (4) 97*a*.
Anderegg, C. M. See Moorer, H. H.
Andermann, G., and Duesler, E. Improved ir optical-index values for MgO, (8) 209*a*.
Andersen, A. A. Apparatus for drying granular or particulate material, P (8) 206*g*.
Andersen, A. M. Method for molding forms on various substrates, P (10) 251*i*.
Anderson, C. A. See Segnit, E. R.
Anderson, D. E. Process for coating amorphous Se, P (7) 170*e*.
Anderson, G. W., and Compton, W. D. Optical absorption properties of vanadate glasses, (5) 106*f*.
Anderson, H. U. See Conger, G. J.
Anderson, J. W. Lamp having improved press seal, P (9) 219*g*. See Harbur, D. R.
Anderson, J. W., and Loughridge, F. A. Photoflash lamp having laminated glass envelope, P (10) 245*i*.
Anderson, L. W., and Stephenson, M. J. Separation of Ti fluoride and Nb fluoride from gaseous UF_6 containing same, P (3) 68*i*.
Anderson, N. C. See Rupert, R. E.
Anderson, R. C. Transparent ZrO_2-, HfO_2-, and ThO_2-rare earth ceramics, P (5) 111*f*.
Anderson, R. C., and Strittmatter, D. J. Method of bonding a glass prism to a metal, P (2) 34*c*.
Anderson, R. L. See Marconato, R.
Anderson, R. V. See Economy, J.
Anderson, W. G. Ceramic sanitary ware resembling natural stone or marble, P (4) 85*i*.
Anderson, W. G., and Ogren, C. W. Hole-forming attachment for powder press, P (3) 62*b*.
Anderson, W. W., and Swanson, R. M. Shallow hole levels in ion-implanted CdS, (7) 180*b*.
Anderson, Y. R., and Escott, G. K. Means for prefabricating brick panels, P (5) 108*g*.
Andersson, S. See Astroem, A.
Ando, M. Successively joinable C electrode for gouging metallic articles, P (4) 85*a*.
Andre, E., and Le Duc, J. M. Method of crystallizing a binary semiconductor compound, P (4) 88*f*.
Andreeva, E. P., Keshelava, B. F., and Rebinder, P. A. Physicochemical nature of transformations related to change of composition of Ca hydrosilicates during hydration hardening, (7) 157*f*.
Andreeva, N. A., Gropyanov, V. M., and Kozlovskii, L. V. Change in structure of ZrO_2 at high temps. in a vacuum, (8) 208*a*.
Andreevska, G. D., and Gorbatkina, Yu. A. Adhesion of polymeric binders to glass fiber, (7) 158*b*.
Andresen, A. F. See Holseth, H.; Selte, K.
Andreu, J. Heat treatment furnace, P (2) 45*g*.
Andrew, K. F., Tallman, R. L., and Gulbransen, E. A. Photoflash lamp with Y combustible filling, P (10) 245*j*.
Andrews, J. M. See Nicollian, E. H.
Andrews, R. H., and Thomas, A. G. Investigation of the surface topography of Al_2O_3 substrates, (9) 224*g*. Sintering of thermoelectric devices based on Fe disilicide, (7) 168*a*.
Andrews, R. L. Hermetically sealed coaxial connecting means, P (2) 40*a*.
Andrianov, N. T., Lukin, E. S., and Poluboyarinov, D. N. Aging of aluminomagnesia spinel ceramics, (8) 194*g*.
Andrusieczko, A. Melting of opal glass in an electrically heated furnace, (9) 217*j*.
Andrysiak, C. D., and Wilson, R. W. Method for forming multibore tubing, P (1) 4*i*.
Andryushchenko, A. I. See Likhoradov, A. P.
Angello, S. J. See Handy, R. M.
Angers, R. See Hajmrle, K.
Angers, R., Tremblay, R., and Chaklader, A. C. D. Formation of $CaZrO_3$ by solid-state reaction between CaO and ZrO_2, (9) 235*c*.
Angstadt, R. L. Method for processing rare earth fluorocarbonate ores, P (3) 71*d*.
Angstadt, R. L., and Bell, R. N. Production of Al_2O_3 and portland cement from clay and limestone, P (5) 118*b*.
Angus, H. C., and Gainsbury, P. E. Oxide resistor materials, P (10) 252*g*.
Angus, J. C. Manufacture of synthetic diamonds, P (1) 1*h*; P (4) 77*g*.
Angus, J. C., and Gardner, N. C. Process for the catalytic growth of metastable crystals [diamonds] from the vapor phase, P (8) 207*c*.
Anju, Yasuhide. See Kato, Akio.
Annabi, F. See Odent, G.
Anoshina, N. P., Komissarova, L. N., Teterin, E. G., Shatskii, V. M., and Isupova, L. A. Preparation and some properties of the molybdate and tungstate of Sc, (8) 210*h*.
Ansari, A. A. See Jonscher, A. K.
Ansell, G. S. See Nayar, H. S.
Anselme, A. P. See Clement, C.
Ansimova, T. A. See Pitak, N. V.
Anthon, F. B. Abrasive finishing article, P (1) 1*g*.
Anthony, A. J. See Finch, L. M.
Anthony, A. M. See Odier, P.
Antonevich, J. N. Methods and apparatus for testing glassware, P (3) 59*i*.
Antonin, V. See Koller, A.
Antonov, V. K. See Shchepetkin, A. A.
Antonova, N. P. See Budnikov, P. P.
Antoshchenko, S. Ya. See Potryasov, V. N.
Antsiferov, V. N., and Polyakov, V. A. Strengthening of the 80% Ni-20% Cr alloy with dispersed oxide inclusions, (10) 247*j*.
Antypas, G. A. Ga-GaP-GaAs ternary phase diagram, (9) 235*f*. See James, L. W.
Anzai, Kazuo. See Somiya, Shigeyuki.
Aoki, Koichi, Hirai, T., and Yajima, S. Prep-

aration and thermal expansion of pyrolytic graphite-Br residual compounds, (2) 49*c*.
Aoki, Kozi. See Katsuki, Kazuo.
Aoyagi, Kiyoshi. See Sugano, Satoru; Uesaka, Yasutaro.
Aplan, F. F. See Simkovitch, G.
Aponick, A. A., Jr., and Gottling, J. G. [3-terminal] solid-state device, P (10) 253*c*.
Aposporos, N. J. Ceramic package for an integrated circuit, P (9) 224*i*.
Appel, J. Soft-mode superconductivity in $SrTiO_{3-x}$, (5) 123*j*.
Appels, J. A. See Tulp, T. J.
Appleby, H., and Cowlard, F. C. Mfg. vitreous C bodies, P (3) 61*f*.
Appleton, L. H. American Indian Design and Decoration, B (3) 76*b*.
Apollonov, V. N. See Timofeeva, N. V.
Aquili, G. See Perri, G.
Arabei, B. G. See Levinskii, Yu. V.
Arafa, A. A., Kenawy, M. E., and El-Daoushy, M. F. Electrical conductivity of pure and impure polycrystalline Cu_2O, (4) 96*h*.
Arafa, S. Ti centers induced in borate glasses by irradiation, (4) 81*g*.
Arai, Kazuo, and Saito, S. Glass transition in chalcogenide glasses, (4) 80*d*.
Arakawa, Masafumi. Powder packing process, (6) 141*f*.
Arakawa, Masafumi, Banerjee, S., and Williamson, W. O. Extrusion behavior of hard shale, (1) 6*b*.
Arakawa, Yoshiteru. See Yamada, Eiichi.
Araki, Kenichi, Kohno, K., and Hayashi, M. Basic study on the mix proportions and compacting conditions of zero slump concrete, (6) 127*j*.
Araki, Kenichi, Kohno, K., and Mizuguchi, H. Mix proportion, consistency, and strength of dry mix concretes using crushed stones, (6) 129*e*.
Araki, Kenichi, and Togawa, K. Fundamental studies on the shear strength of reinforced concrete beams with artificial lightweight aggregates, (10) 241*h*.
Araki, Tadashi, Takita, H., and Asano, K. Process for production of C fibers, P (9) 222*e*.
Aratani, Fukuo, Omori, Y., and Sanbongi, K. Equilibrium study on the reaction $4CaO(s)+2P+5H_2O(g)=4CaO\cdot P_2O_5(s)+5H_2(g)$, (3) 73*f*.
Araujo, R. J. Colorless heat-absorbing glass, P (6) 132*d*. Photochromic glass containing Ta oxide for optical fiber fabrication, P (4) 82*g*.
Araujo, R. J., Cramer, W. H., and Stookey, S. D. Method of forming photochromic polarizing glasses, P (7) 162*c*.
Arav, R. I., Zhelobaeva, N. P., and Milovidova, L. V. Effect of temp. on carbonation of $Mg(OH)_2$, (7) 177*j*.
Arber, S. G., and Young, O. W. J. Preparation of BN, P (1) 9*f*.
Archer, E. D. See Shively, J. H.
Archer, F. C., DeDiemar, R. B., and Schuman, L. J. Gyratory crusher, P (2) 46*g*.
Arey, W. F., Jr., Hamner, G. P., Mason, R. B., and Rigney, J. A. Dewaxing process wherein relatively small pore size crystalline aluminosilicate zeolites are used to chemically convert *n*-paraffins in hydrocarbon oils, P (11) 279*g*.
Arey, W. F., Jr., and Mattox, W. J. Metal nitrides as cracking catalysts, P (4) 94*h*.
Argentina, G. M. See Baba, P. D.
Argentina, G. M., and Baba, P. D. Li Ti Bi ferrites, P (4) 88*a*.
Argiro, T. J. Composition for reducing friction on coated abrasive cloth, P (5) 101*f*.
Argon, A. S., Nigam, A. K., and Padawer, G. E. Plastic deformation and strain hardening in pure NaCl at low temps., (10) 260*j*.
Argon, A. S., and Padawer, G. E. Dislocation motion in pure NaCl at low temps., (10) 258*h*.
Arguello, C. A., Rousseau, D. L., and Porto, S. P. S. First-order Raman effect in wurtzite-type crystals, (5) 120*i*.
Argyle, B. E. See Giess, E. A.
Arifov, U. A. (editor). Secondary Emission and Structural Properties of Solids, B (6) 154*f*.
Ariga, Shozo. See Yamamoto, Zensaku.
Arita, Shigeru, Kamei, I., and Okumura, T. Mfg. method [etching] for semiconductor device, P (8) 201*c*.
Arizumi, Tetsuya. See Ogawa, Hiroshi.
Arkhipov, S. M. See Kirgintsev, A. N.
Arkless, K., Cleaver, D., and Hare, A. L. Improved oxidation process for the [electric arc] production of pigmentary white metal oxides, P (3) 71*b*.
Armington, A. F., and O'Connor, J. J. Method of [solution] growing crystals by shifting the equilibrium of chemical complexes, P (9) 230*a*.
Armstrong, P. E. See Wagner, P.
Arndt, H. H., Schaedel, J., and Mueller, D. 3-layer metallic contact strip as a semiconductor structural component, P (4) 91*d*.
Arnett, C. J., and Hoover, J. M. Thermocouple input temp. sensing circuitry, P (7) 174*b*.
Arnl, H. T. See Blaine, R. L.
Arnold, A. Bulletproof compound transparent panels, P (8) 198*e*.
Arnold, G. P. See Krikorian, N. H.
Arrance, F. C., and Berger, C. Process of forming a sintered Zn electrode, P (3) 67*a*.
Arrowsmith, J., and Savage, H. K. Kiln furniture and refractories (1), (1) 10*d*.
Arsenovici, L. C., and Townsend, P. D. Spatial distribution of defects produced in alkali halides by electron irradiation, (10) 261*c*.
Arstikaitis, A. A. Cleaning control for electrostatic precipitator, P (1) 16*g*.
Artamonov, A. Ya., and Shishkin, L. S. Influence of grinding conditions on hardness and wear resistance of a quenched cermet material, (10) 246*i*.
Arthur, J. R., Jr. Technique for growth of epitaxial compound semiconductor films, P (2) 42*j*.
Arthur, J. R., Jr., and Morris, F. J. Method of growing compound semiconductor films on an amorphous substrate, P (9) 226*i*.
Arthur, J. R., Jr., and Wagner, R. S. Growth of needlelike VLS [vapor-liquid-solid] crystals, P (4) 88*c*.
Arthur, M. E., and Fussell, L. E. Effect of sintering conditions on Al_2O_3-MoMn bond strengths, (1) 2*h*.
Artman, J. O. See Chen, Mao-Chieh.
Artmann, P. Lightweight concrete material and process for producing, P (8) 188*e*.
Asahara, Genshiro. See Wada, Toru.
Asahara, Norlyoshi. See Sudoh, Giichi.
Asahara, Yoshiyuki, and Izumitani, T. Glass for ultrasonic delay line, P (10) 244*a*.
Asaida, Yuhko. See Chikawa, Jun-ichi.
Asanabe, Shizuo. See Shinoda, Daizaburo.
Asano, Kiro. See Araki, Tadashi.
Asano, Shunkichi. See Inoue, Yoshiki.
Asano, Shunkichi, Ishihara, S., and Inoue, Y. Carbonation of Ca aluminates, (6) 145*d*.
Asano, Shunkichi, Kamatani, Y., and Inoue, Y. Carbonation of Ca silicates, (6) 145*e*.
Asano, Shunkichi, Sugita, T., Yamagiwa, Y., and Inoue, Y. Carbonation of Ca hydroxide, (6) 145*d*.
Asao, Sadao. See Tsuboi, Tatsuaki.
Asaro, F., Perlman, I., and Dothan, M. Introductory study of Mycenaean IIICI ware from Tel Ashdod, (5) 102*c*.
Asbury, J. J. Method for producing porous U, P (3) 68*f*.
Asbury, J. J., and Googin, J. M. Method for mfg. of inorganic thermal insulation, P (4) 84*f*.
Ash, B. See Fort, A.
Ash, E. A. See Mason, I. M.
Ashar, K. G. Method of making pedestal transistor having minimal side injection, P (10) 251*g*.
Ashby, G. E. See Flack, H. P.
Ashby, M. F. See Frost, H. J.
Ashford, J. W. See Holm, R. L.
Ashley, K. L., and Doerbeck, F. H. Investigation of GaAs emission diode characteristics with transistor structures, (6) 149*a*.
Ashton, C. L., Hays, R. G., and Pennell, R. C. Method of diffusing impurities into selected areas of a semiconductor, P (10) 251*b*.
Ashton, W. H., and Russell, R. S. Talc beneficiation, P (11) 280*b*.
Ashworth, E. A. See Lythe, T. W.
Aslanova, M. S., and Yakovleva, M. A. Method of mfg. [fiber glass] tape possessing semiconducting properties, P (5) 107*d*.
Aspden, R. Adjustable lap, P (8) 185*e*.
Assaud, L. M. See Sadran, G. H.
Assour, J. M. Radiation-sensing device comprising an array of photodiodes and switching devices in a body of semiconductor material, P (1) 14*f*.
Assour, J. M., and Rosen, A. Assembly of series connected semiconductor elements having good heat dissipation, P (3) 64*g*.
Astbury, N. F. New method of studying pore size distribution, (11) 278*d*.
Astbury, N. F., and Vyse, J. New method for the study of pore size distribution, (1) 18*a*.
Astrin, V. A. See Rabodzei, N. V.
Astroem, A., and Andersson, S. Preparation and crystal structures of various forms of SbOF, (3) 74*h*.
Ateya, B. G. See Austin, L. G.
Athanas, T. G. Formation of openings in insulating layers in MOS semiconductor devices, P (10) 250*e*. Input transient protection for complementary IGFET integrated-circuit device, P (10) 250*i*.
Athavale, A. S., and Altekar, V. A. Kinetics of selective chlorination of ilmenite using HCl in a fluidized bed, (2) 46*e*.
Atobe, Kozo. See Okada, Moritami.
Atsumi, Mitsuo. See Tanaka, Sadao.
Attaway, D. H. See Calder, J. A.
Audesse, E. G., Griffin, R. M., Tartakoff, A., and Gutta, J. J. W halogen lamp, P (5) 107*i*.
Augi, J. M. Test cell for dielectric constants, (3) 70*f*.
August, R. R., and Palmquist, R. L. Monolithic heteroepitaxial microwave tunnel diode, P (9) 227*a*.
Augustin, E. H., and Kudrzycki, R. M. Glass edge grinding machine, P (3) 58*g*.
Austerman, S. B. See Slack, G. A.
Austin, G. W. Process of submerged nozzle continuous casting using a basalt flux, P (10) 248*a*.
Austin, I. G. Polaron conduction in disordered 3*d* oxides, (6) 151*d*.
Austin, I. G., and Garbett, E. S. Far-ir vibrational spectra of crystalline and amorphous As_2Se_3, (6) 148*e*.
Austin, L. G., Luckie, P. T., and Ateya, B. G. Residence time distributions in mills, (5) 104*j*.
Austin, M. J., Fletcher, W. W., Hickson, K., Leech, R. J. Mathematical correction of matrix effects in the X-ray fluorescence analysis of soda-lime-SiO_2 glasses, (2) 32*j*.
Austin, M. J., Fletcher, W. W., Leech, R. J., and Hickson, K. Mathematical correction of matrix effects in the analysis of Na_2O-CaO-SiO_2 glasses by X.R.F., (8) 205*e*.
Avaliani, A. Sh. See Morozov, I. S.
Averjanov, V. I. See Porai-Koshits, E. A.
Averkiou, G. See Drozdowicz, K. P.
Avetikyan, G. B., Baidakov, L. A., and Strakhov, L. P. Magnetic susceptibility of glasses of system Ge-Se, (9) 217*f*.
Avgustinik, A. I., Zhuravlev, G. I., and Matusov, I. A. Reaction of Al_2O_3 melt with Ta, Mo, and Nb, (7) 163*j*. Reaction of SiO_2 melt with some refractory metals, (7) 163*g*.
Avril, A. C. Bag stacking machine, P (10) 254*j*.
Awazu, Kenzo, Matsunaga, K., Muto, K., Kai, J., and Oi, K. Y orthophosphate phosphor, P (10) 253*f*.
Axe, J. D., Shirane, G., and Mueller, K. A. Zone-boundary phonon instability in cubic $LaAlO_3$, (5) 125*j*.
Axelrod, N. N. Group III-V Schottky barrier diodes, P (10) 250*f*.
Ayers, D. R. Pressure control system for glassware press molding, P (1) 5*b*. Temp. control system for glass-shaping molds, P (4) 83*a*.
Ayers, P. J. H. Magnetic transducer, P (10) 251*e*.
Ayme-Jouve, M. L. See Esnoult, M. R. G.
Ayres, R. J. Electric incandescent lamp with tapered sealing collar, P (6) 132*f*.
Ayuta, Koichi. See Yokomichi, Hideo.
Azumi, Tsukuru. See Mizunuma, Tsutomu.

Baak, T. SiO_2-CdO glass batches for producing low to medium expansion glasses, P (7) 162*j*. Thermal coeff. of refractive index of optical glasses, (1) 3*j*. See Dietz, E. D.; Tobin, M. C.
Baas, W., Tegel, M. J., and Kerkmeester, H. B. Semiconductor device including a circuit arrangement of diodes, P (1) 14*i*.
Baba, P. D. See Argentina, G. M.
Baba, P. D., and Argentina, G. M. Li-Ti-Zn ferrites, P (6) 138*d*.
Babaev, P. I. See Dubinin, M. M.
Babcock, C. L. See Busdiecker, R. A.
Babcock, G. L. See LaCombe, D. J.
Babich, M. M., Lisovskii, A. F., and Lisovskaya, N. B. Low-temp. oxidation of hard-alloy mixtures, (10) 260*a*.
Babievskaya, I. Z. See Perel'man, F. M.
Babitsyn, P. K., and Ushatinskii, I. N. Separation of clay minerals in the apparatus SIM-1 in combination with ultrasound, (8) 207*a*.
Babkina, V. A. See Shchavelev, O. S.
Baburek, J. Beneficiation of kaolins with high-intensity magnetic separators, (9) 232*e*. Determining the zones in the Karlsbad kaolin deposits, (5) 117*d*. Migration of trace elements in the vertical section of the kaolin deposit at Karlovy Vary, West Bohemia, (1) 20*b*.
Bach, H. Possibilities and limitations in preparing glasses and nonconductors and their surface coatings for electron microscope analysis, (7) 173*b*.
Bach, H., and Gliemeroth, G. Immiscibility and phototropy in glasses containing Ag halides, (8) 190*c*.
Bachelard, R. Process for producing cryolite, P (3) 71*i*. Production of gaseous HF, P (6) 144*d*.
Bacher, R. J., and Nakayama, T. Hermetic printed capacitor, P (11) 274*i*.
Bachinski, S. W., and Mueller, G. Experimental determinations of the microcline-low albite solvus, (1) 22*e*.
Bachmann, K., and Williams, W. S. Low-temp. electrical resistivity and Hall effect of single-crystal α-WC, (6) 149*j*.
Bachmeier, A. Method of making contact to semiconductor devices, P (4) 89*a*.
Bachus, K. P. See Rausch, W.
Badami, A. V., Ebert, E., Keinlage, B. M., Kroell, K. E., and Pogge, H. B. Method for minimizing autodoping in epitaxial deposition, P (9) 226*f*.
Bade, E., and Thelen, J. Cooling arrangement for the product of rotary furnaces, P (4) 93*j*.
Badger, A. E. See Oelke, W. W.
Badyan, A. Kh., Kislyi, P. S., and Shvab, S. A. Effect of powder-grinding conditions on the properties of $MoSi_2$ heating elements, (10) 246*j*.
Baelde, A. See van de Water, J. T.
Baer, M., and Campbell, J. O. Glass concentrate capsules, P (9) 219*b*. Glass-fiber-reinforced composite and method of making, P (9) 219*c*. Process for the preparation of glass concentrate capsules in a polyvinyl chloride matrix, P (4) 82*i*. Process for the preparation of glass concentrate capsules in a thermoplastic matrix, P (4) 82*i*.
Baer, R. H. Multilayer core memory process, P (4) 89*f*.
Bagdasarov, Kh. S. See Krylov, V. S.
Bagieu-Beucher, M., and Durif, A. Crystallographic data for $Be(PO_3)_2$, (8) 208*c*.
Bagieu-Beucher, M., Tordjman, I., and Durif, A. Crystal structure of Ce(III) trimetaphosphate, trihydrate, (6) 145*i*.
Bagley, B. G., and Bair, H. E. Thermally induced transformations in glassy chalcogenides, (6) 152*d*.

Bagley, B. G., and Northover, W. R. Electron microscopic observations of thermally induced transformations in amorphous chalcogenide thin films, (6) 136*h*.
Baglio, J. A., and Dann, J. N. Crystal structure of β-$Sr_3V_2O_7$, (8) 208*j*.
Bagyal, P., and Fritz, G. Reduction of reject percentage by technological changes in the Malyi Brick Factory, (5) 108*c*.
Bahl, M. K. See Bhide, V. G.
Bahl, S. K., and Chopra, K. L. Electrical conduction in amorphous GeTe films, (6) 136*g*.
Baidakov, L. A. See Avetikyan, G. B.
Baidakov, L. A., and Shcherbakov, V. A. Chemical shifts in MNR of ^{31}P in vitreous P selenides, (9) 233*h*.
Baigas, J. F., Jr. Air filter assembly providing increased filtering surface area for a given volumetric size, P (1) 16*i*.
Bailey, A. C., and Camp, H. E. Method of making glass razor blades, P (1) 4*j*.
Bailey, B. L. Method and apparatus for controlling orientation of needlelike C particles in extruded carbonaceous stock, P (9) 222*j*.
Bailey, F. P. See Fehrenbacher, L. L.
Bailey, J. E., Lewis, D., Librant, Z. M., and Porter, L. J. Phase transformations in milled ZrO_2, (11) 282*d*.
Bailey, J. T. High-Al_2O_3 bodies comprising anorthite, gehlenite, and spinel, P (4) 86*a*. Ultrapure Al_2O_3 ceramics formed by coprecipitation, P (5) 111*g*.
Bailey, J. T., and Russell, R., Jr. Preparation and properties of dense spinel ceramics in the $MgAl_2O_4$-Al_2O_3 system, (1) 10*g*.
Bailey, R. F. High-temp. semiconductor and method of fabrication, P (2) 40*c*. Semiconductor devices with diffused Pt, P (5) 114*e*.
Bain, J. A. Plasticity chart as an aid to the identification and assessment of industrial clays, (6) 143*h*.
Bair, H. E. See Bagley, B. G.
Baird, T., Cairns-Smith, A. G., Mackenzie, D. W., and Snell, D. S. Electron microscope studies of synthetic hectorite, (9) 235*d*.
Bairiot, H. F. J. G. See Aerts, L. J.
Bajza, A. Factors influencing the strength of cement compacts, (5) 103*e*.
Baker, E. H. See Iqbal, M.
Baker, E. M. See Mellen, E. J., Jr.
Baker, L. K., and Shardlow, L. R. Multiple pellet semiconductor device, P (3) 66*d*.
Baker, M. A. 1939 exposure test of porcelain enamels on steel, 30-year inspection, (1) 2*i*. Three-year inspection of nature-tone porcelain enamels on steel, (7) 157*h*.
Baker, N. H., Jr. See Sweet, L. H.
Baker, R. W. See McDaniel, C. V.
Bakhtalovskii, I. V. Introducing new equipment in the (Soviet) ceramic industry, (8) 197*e*.
Bakhtin, Yu. G. See Ryss, Yu. S.
Bakker, W. T. Al_2O_3 refractories, P (7) 164*a*. High-Al_2O_3 refractories, P (5) 109*h*. Mfg. mullite refractory grain and product, P (5) 109*i*. See Snyder, G. E. D.
Bakshutov, V. S. See Butt, Yu. M.
Bakum, S. I. See Dymova, T. N.
Bala, M. J. See Blecherman, S. S.
Bala, M. J., and Blecherman, S. S. Mechanism for controlling the thickness of a coating in a vapor deposition apparatus, P (9) 226*a*.
Balaban, G. I. See Likhoradov, A. P.
Balakaeva, T. A. See Kharitonov, Yu. Ya.
Balashov, Yu. A., Frenkel, M. Ya., and Yaroshevskii, A. A. Effect of crystallochemical factors on the separation of rare earth elements during crystallization differentiation of silicates, (1) 21*i*.
Balasingh, C. See Singh, A. K.
Balazs, G. See Boros, M.
Balchan, A. S., and Cowan, G. R. Method of treating solids with high dynamic pressure, P (9) 213*e*.
Baldini, G., and Bosacchi, B. Jahn-Teller effect in the Γ exciton of LiBr, (6) 149*c*.
Baldwin, N. H. Changing the base on a wheel-thrown pot, (2) 30*b*.
Bale, C. W., Ajersch, F., and Toguri, J. M. Chemical control technique to determine the thermochemical properties of liquid metal-nonmetal systems, (6) 141*j*.
Balek, V. See Zaborenko, K. B.
Balents, L. M. See Franklin, D. L.
Balint, P., and Skvorecz, T. Testing the ceramic properties of clays by their sorptive moisture content, (6) 142*i*.
Balitskii, V. K. See Sychev, M. M.
Balkevich, V. L. See Poluboyarinov, D. N.
Ball, C. G., Grimm, A. C., and Melville, T. Portland cement compositions reinforced with nonround filaments, P (7) 157*e*.
Ball, F. J., Torrence, S. L., and Repik, A. J. Dry fluidized activated C processes for stack SO_2 recovery as S, (4) 92*b*.
Ball, M. C. Phase equilibrium studies in the system Na_2O-NbO_2, (1) 23*i*.
Ball, N., Price, J. W., and Rigge, R. J. Pseudoboehmitic Al_2O_3 and process for making, P (4) 95*a*.
Ballantine, J. M. Mfg. fiber optic stacks, P (1) 4*b*.
Ballard, R. K. Preparation of chemically reactive UO_2, P (1) 16*d*.
Ballard, S. S. See Browder, J. S.
Ballman, A. A., and Carruthers, J. R. Growth of crack-free Ba Na niobate and related materials, P (6) 137*h*.
Balta, P., and Stoicanescu, C. Aspects of the effect of chemical and structural changes in the melt on the properties of glass, (11) 267*h*.
Balteaux, R. H. See Boulet, F. H.
Balthis, J. H., Jr., and Gilbert, W. W. Process for the preparation of ferromagnetic Cr oxide by removing H_2O before cooling synthesis mixture, P (4) 94*h*.
Balyaev, I. N., and Kesarev, V. V. Vapor pressure over molten salts in the systems $CdCl_2$-MCl, (8) 211*f*.
Balzau, G., and Fosshag, W. Container for holding fine material, P (5) 115*f*.
Bando, Yoshichika. See Iwauchi, Kozo.
Bandyopadhyay, G. K., and Ray, H. S. Kinetics of O dissolution in molten Pb, (6) 149*g*.
Banerjee, J. C., De, S. K., and Nandi, D. N. Bloating type refractories—a preliminary study, (11) 271*e*.
Banerjee, J. C., and Ramesam, K. High temp. creep of basic refractories, (11) 271*i*.
Banerjee, M., and Budworth, D. W. Preparation of transparent MgO bodies (II) by sintering, (11) 282*h*.
Banerjee, S. See Arakawa, Masafumi.
Banerjee, S. K. Problems of firing in pottery industry in India, (11) 272*j*.
Banes, N. M., Jr., and Bottcher, J. H. Light source, P (4) 88*j*.
Banfield, J. H. See Vossen, J. L., Jr.
Banks, E. See Tauber, A.
Bannister, M. J. See Van Peer, W. J.; Woolfrey J. L.
Bannister, M. J., and Buykx, W. J. Oxidation of UO_2 fuel pellets during H sintering, (11) 276*c*.
Banno, Hisao, Tsunooka, T., and Sakai, M. Polarizable ferroelectric ceramic compositions having improved electromechanical coupling coeff. and dielectric constant, P (4) 90*a*.
Banyas, J. D., and Wallington, F. L. Container handling apparatus, P (5) 107*d*.
Barag, D. Glass pilgrim vessels from Jerusalem (II,III), (11) 265*j*.
Baranov, A. T. See Budnikov, P. P.
Barber, A. C. See Morton, P. H.
Barber, D. J. Mounting methods for mineral grains to be examined by high resolution electron microscopy, (4) 93*f*.
Barber, M. See Thomas, J. M.
Barber, S. W., and Nelson, W. F. Luminescent device having rare earth-doped SiO_2 glass luminescent material, P (4) 88*c*.
Barber, W. G. See Loxley, T. A.
Barbier, M. J. See Poignet, J. C.
Barbuto, A. See Zeppieri, D. J.
Barclay, J. A. See Tyrrell, M. E.
Barelss, D. A. Package for large glass panels, P (1) 5*f*.
Barelli, A. E., and Shaunfield, W. N., Jr. Avalanche photodiode utilizing Schottky-barrier configurations, P (3) 64*h*.
Barham, D. See Waffle, A. L.
Barilli, F., Cozza, G., Aglietti, G., and Ligorati, F. Process for recovering Na fluosilicate in the production of phosphoric acid, P (1) 20*i*.
Barker, W. W., and Knop, O. Statistics with constraint for simple and fcc arrays—application to ionic conductivity and nonstoichiometry in fluorite oxides, (9) 238*e*.
Barlow, G. See Shutt, T. C.
Barlow, H. See Loasby, R. G.
Barnard, P. G., Ritchey, R. A., and Kenworthy, H. Recovery of chromite and SiO_2 from steel industry waste molding sands, (1) 8*f*.
Barnebl, A. C., and Bliem, F. Rotary vacuum drum filters, P (4) 92*h*.
Barnes, G. A. See Abbott, C. E.
Barnes, R. D. See Fredrickson, D. R.
Barnett, A. M., Jensen, H. A., and Meikleham, V. F. Selective uniform liquid phase epitaxial growth, P (6) 139*j*.
Barnett, C. W. H. Composite shell with ceramic base, P (5) 111*c*.
Barnett, E. F. See Siegbahn, K.
Barnett, J. D. See Forman, R. A.
Barnett, M. J. See Hill, G. J.
Baron, A., Bernard, A., Deloye, F. X., Louvrier, J., Millet, J., Sierra, R., Struillou, R., and Voinovitch, I. A. Mineralogical Analysis of Argillaceous Soils, B (1) 28*j*.
Baron, V. V. See Savitskii, E. M.
Baronian, W. Optical properties of thin BN films, (5) 122*f*.
Barr, L. W., and Dawson, D. K. Correlations between melting temps. and formation and cation motion energies of Schottky defects in ionic crystals, (9) 234*c*.
Barrer, R. M., and Cole, J. F. Aluminosilicates containing sodalite and/or cancrinite cages encapsulating salts, P (10) 257*b*.
Barrer, R. M., Cole, J. F., and Sticher, H. Crystalline zeolite and method of preparation, P (8) 207*d*.
Barrer, R. M., and Vaughan, D. E. W. Trapping and diffusion of rare gases in phillipsite, zeolite K-M, and other silicates, (2) 50*e*.
Barrett, C. S. See Heinrich, K. F. J.
Barrett, C. S., Newkirk, J. B., and Ruud, C. O. (editors). Advances in X-Ray Analysis (Vol. 14) Proceedings of the 19th Annual Conference on Applications of X-Ray Analysis, Aug. 1970, Denver, Colorado, B (1) 26*e*.
Barrett, H. H. Ultrasonic attenuation by interaction with the soft optic mode in $KTaO_3$, (5) 125*a*.
Barriere, J. [Plastic] coated bottles, P (8) 193*h*.
Barrington, C. A. Dicing of semiconductors, P (4) 87*b*.
Barros, F. de S., Hafemeister, D., and Viccaro, P. J. Moessbauer study of the ^{57}Co implanted in diamond, (5) 122*c*.
Barrow, R. F., Burton, W. G., and Jones, Peter A. Electronic spectrum of gaseous BaS, (5) 120*b*.
Barry, T. L. Divalent Eu-activated Ba Mg pyrosilicate, P (7) 168*e*. Luminescent properties of Eu^{2+} and Eu^{2+}+Mn^{2+} activated $BaMg_2Si_2O_7$, (9) 224*i*.
Barsegov, D. G. See Il'yasov, I. I.
Barson, F., and Lehman, H. S. Fabrication of semiconductor devices with cup-shaped regions, P (9) 225*i*.
Barsotti, L. R. See Kelly, A. C.
Bart, R. K. See Kiovsky, J. R.; Wallace, R. W.
Barta, J., Shook, W. B., and Graves, G. A. Impact strength of Al_2O_3 composites, (6) 131*b*.
Bartch, D. W. See Long, G. E., III.
Barten, P. G. J. Cathode-ray tube provided with at least 1 electron gun for producing a number of individually prefocused electron beams, P (2) 39*f*. Color cathode-ray tube with plural cathodes and 3 common grids each having same plurality of beam-defining apertures, P (5) 107*c*.
Bartenev, G. M. Structure and Mechanical Properties of Inorganic Glasses, B (2) 52*e*. Structure and strength of glass fibers, (3) 57*i*.
Barth, M. Saucer with cup-retaining recess, P (4) 78*a*.
Bartholomew, C. Y. See Maguire, C. F.
Bartholomew, R. F. Glassy acetate material, P (6) 133*a*. Method for treating a molten salt with H_2O vapor, P (8) 193*b*.
Bartholomew, R. F., and Frankl, D. R. Electrical properties of some Ti oxides, (6) 147*h*.
Bartlett, H. J. Product for fabrication of dense ceramic armorplate and the like, P (6) 136*d*.
Bartlett, P. G. Crystal-controlled cross-coupled NAND gate square wave generator, P (2) 39*i*.
Bartlett, R. W. Conversion and extraction efficiencies for ground particles in heterogeneous process reactors, (6) 141*d*.
Barton, J. L., and Leblond, M. Electric conduction in glasses at high fields, (11) 268*c*.
Barton, P. B., Jr. See Bethke, P. M.
Bartram, R. H. See Landry, R. J.
Barz, H. E. See Matthias, B. T.
Basart, J. C. M. See Knippenberg, W. F.
Basavaiah, S. See Park, K. C.
Basavara, T. N. See Tagore, A. K.
Basche, M., Fanti, R., Galasso, F. S., Kuntz, U. E., and Schile, R. D. Method for producing B-C fibers, P (10) 248*c*.
Basche, M., and Kuntz, U. E. Process for forming stoichiometric SiC coatings and filaments, P (3) 61*c*.
Bash, S. M., and Terekhovich, S. V. Effect of vitrophyres and tephrite basalts on structural and technical properties of portland cement, (8) 186*a*.
Bashev, F. P. Decorative slag binder, (8) 186*d*.
Basin, E. V. See Levin, D. I.
Baskin, Y. See Kuznietz, M.
Bass, C. D. See Beder, E. C.
Bass, M. See Monchamp, R. R.
Basseville, P. See Besamat, R.
Basu, A., and Harasimham, K. S. Convective heat transfer between air and a cloud of falling particles, (7) 174*d*.
Basu, J. See Maiti, J. N.
Basu, R. K., and Lahiri, D. Rheological properties of china clay suspensions, (11) 273*c*.
Basumajumder, A. See Mitra, N. K.
Batalin, G. I. See Karpinos, D. M.
Bates, C. H., Drew, C. J., and Kell, R. C. Simplified process for preparing translucent Al_2O_3 tubes from boehmite powder, (2) 36*h*.
Bateson, S. See El-Assal, K.
Bateson, S., and Sadler, A. G. (editors). Frontiers in Glass Science and Technology, B (3) 76*i*.
Batho, C. J. See Saull, R. C.
Batra, R. L. Slow plastic flow of a Bingham material between rotating concentric infinite cylinders with axial roughness, (4) 98*d*.
Batsanov, S. S. See Filatkina, V. S.
Battigelli, J. Method and apparatus for the production of glass or other fibers from thermoplastic materials, P (6) 133*j*.
Battles, J. E., Shinn, W. A., Blackburn, P. E., and Edwards, R. K. Mass spectrometric study of the volatilization behavior in the Pu-C system, (8) 203*b*.
Batz, M. Semiconductor device and method of making, P (2) 42*j*.
Bauder, U. See Kleinteich, R.
Baudran, A. Considerations on rapid firing and progress in this field in France, (2) 43*h*.
Baudran, A., Enguerrand, M., and Risse, M. Acceleration of the setting of cast sanitary ware, (2) 37*h*.
Bauer, C. L. Coordinate paths for depinning and repinning of dislocations, (6) 145*d*.
Bauer, D., and Fratzscher, H. Process for obtaining an asbestos-fiber material of a high degree of separation, P (9) 222*d*.
Bauer, F. See Toppler, B.
Bauer, J. M., and Brossard, A. Refractory structure, P (8) 197*b*.
Bauer, R., Jacob, H., and Braun, W. Packaging epitaxially coated semiconductor disks, P (10) 252*g*.
Bauer, W. C. See Conroy, A. R., Jr.
Baugher, J. F., and Bray, P. J. ^{11}B NMR in Ge borate glasses, (11) 267*j*.

Baughman, R. J., Lefever, R. A., and Wilcox, W. R. Evaporation of NaCl melts, (7) 177*e*.
Bauleke, M. P. DTA study of Kansas montmorillonitic clays from Phillips and Wallace counties, (3) 71*c*. Incipient expansion in Kansas volcanic ash, (3) 71*c*.
Baum, C. S. See Wendler, C. F.
Baum, G. Liquids thickened with submicroscopic β-SiC fiber sheathed with SiO_2, P (7) 164*f*.
Baum, J. J., and Helenberg, H. W. Large vol planar pair Ge (Li) detector, P (2) 40*f*.
Baum, W. Borosilicate glass for producing articles by centrifugal casting, P (7) 161*j*. Sintered borosilicate glass, P (6) 133*g*.
Bauman, W. C. Process for producing solutions of Mg values, P (2) 37*d*.
Baur, W. H. Prediction of bond length variations in Si–O bonds, (4) 98*h*. See Khan, A. A.
Bauschmann, W. Softening under load of a brick material during firing in specific atms, (1) 18*i*.
Bawa, M. S., and Petty, A. J. High-temp. paint material, P (2) 31*i*.
Baxendale, J. H., Ward, M. D., and Wardman, P. Heats of ionization of HO_2 and OH in aqueous solution, (3) 73*f*.
Baxter, W. J. Work function of TaC and the effects of adsorption and sputtering of Cs, (5) 125*f*.
Bayard, M. See Wengert, P. R.
Baybarz, R. D., and Peterson, J. R. ^{253}Cf neutron source and method of making, P (5) 115*b*.
Bayer, E., and Vogelbruch, W. Device for uniting the edges of a double or multiple glass pane, P (7) 161*c*.
Bayer, O. Method of producing transparent or opaque fused SiO_2 or glass with a high Si content, P (9) 219*d*.
Bayer, P. D. See Calow, C. A.
Bayliss, P., and Levinson, A. A. Low-temp. hydrothermal synthesis from dolomite or calcite, quartz, and kaolinite, (5) 121*a*.
Bazant, Z. P. Thermodynamics of hindered adsorption and its implications for hardened cement paste and concrete, (6) 130*a*.
Bazell, S. See Bortz, S. A.
Bazinet, W. P., Jr., and Salce, J. E. High-temp. termination for fiber optic bundle, P (10) 244*e*.
Bazuev, G. V., and Krylov, E. I. Metaniobate and metatantalate of Cu, (8) 209*f*.
Beach, A. D. Infrared optical scanning system comprising a rotatable faceted mirror having inclined facets, P (1) 18*g*.
Beach, H. J., EnDean, H. J., Frawley, F. E., and Yates, D. Cement composition for lining pipe, P (9) 215*e*.
Beadle, W. E., Benson, K. E., Mathews, J. R., and Von Ohlsen, L. H., Jr. Fabrication process for light-sensitive Si diode array target, P (9) 225*h*.
Beale, J. R. A. See Robinson, D. P.
Beall, G. H. Transparent glass-ceramic articles comprising Zn spinel, P (10) 245*i*.
Beall, G. H., and Martin, F. W. Low-expansion Zn petalite-β quartz glass-ceramic articles, P (10) 244*g*.
Beall, G. H., Montierth, M. R., and Smith, Gail P. Machinable glass-ceramic, (7) 159*e*.
Beamond, T. W. See Spencer, D. R. F.
Bean, K. E. See Gleim, P. S.
Bean, K. E., and Gleim, P. S. Monolithic integrated-circuit structure [Si] and method of fabrication, P (3) 66*b*.
Bean, L. W. Sintering of Mo metalizing, (1) 11*j*.
Beaney, P. A. Process for bonding particulate materials, P (5) 110*a*.
Beard, R. Measurement of compressive strains in bricks and brickwork of a 4 ½-in. test wall under axial loading, (9) 220*e*. See Dinnie, A.
Beare, G. K., Konelman, B., and Seeger, D. E. Indicating flash lamp, P (10) 244*f*.
Beasley, J. D. Electrooptical modulator, P (3) 64*i*.
Beattie, A. G., and Samara, G. A. Pressure dependence of the elastic constants of $SrTiO_3$, (4) 98*b*.
Beattie, W. H., and Tisinger, R. M. Light scattering functions and particle-scattering factors for ellipsoids of revolution, (1) 17*g*.
Beatty, R. L. See Beutler, H.
Beatty, R. L., and Kiplinger, D. V. Pulsed method for impregnation of graphite, P (9) 229*a*.
Beau, R., and Fourniquet, J. Agglomerated SiO_2 bodies and method, P (7) 175*i*.
Beaudoin, J. J., and MacInnis, C. Dimensional changes of hydrated portland cement paste during slow cooling and warming, (7) 156*e*. Effect of admixtures on the strength-porosity relationship of portland cement paste, (4) 78*d*.
Beaudry, H. J. Continuous sputtering system, P (2) 39*i*.
Beaumont, P. W. R. See Harris, B.
Becher, P. F. Mechanical behavior of polycrystalline TaC, (2) 48*a*.
Becher, W. See Massonne, J.
Becherescu, D., Cipau, R., and Marx, F. Reaction between Bi_2O_3 and ZrO_2 at high temps., (5) 123*e*.
Becherescu, D., Menessy, I., and Cristea, V. Relation between the behavior of phosphate glasses under irradiation and their structure, (5) 106*h*.
Beck, F., and Csizi, G. Production of [activated] electrodes, P (10) 252*c*.
Beck, J. H. Furnace conveyor system, P (2) 44*j*. Movable hearth furnace, P (4) 94*a*.
Beck, M. S. Measurement of the flow of particulate material, P (5) 116*f*.
Beck, R. W. Coatings for Ge semiconductor devices, P (3) 64*c*.
Becke, H. W., Cave, E. F., and Stalnitz, D. High-power hf device, P (8) 200*h*.
Beckenbach, K. Inclined kiln for the firing and sintering of material and a method for operating the kiln, P (8) 206*d*.
Becker, E. See Mahler, E.
Becker, J. J. Permanent magnet material powders having superior magnetic characteristics, P (7) 169*j*, P (9) 227*d*.
Becker, J. J., and Cech, R. E. Method of stabilizing permanent magnetic material powders, P (2) 41*b*.
Becker, K. Machine for the production of containers or the like of vitreous material, P (3) 58*g*. Machine for the production of glass bottles or the like, P (6) 133*e*.
Beckett, J. See Wallis, G.
Beckmann, B., Strunk-Lichtenberg, G., and Heide, H. Early Siegburg ceramic ware and its development to stoneware. Scientific analyses of the history of the ceramics of the Middle Ages, (7) 155*g*.
Beckmann, R., and Schneider, J. Laminated safety glass and laminated bulletproof glass, P (8) 193*f*.
Beder, E. C., Bass, C. D., and Shackleford, W. L. Transmissivity and absorption of fused quartz between 0.22 and 3.5 μm from room temp. to 1500°C, (10) 243*b*.
Bedetti, G. Apparatus for the combustion of $TiCl_4$ with O for the production of TiO_2 pigment, P (10) 257*c*.
Beebe, R. R. See Thomas, T. B.
Beebe, R. R., and Murphy, E. J. Method and apparatus for shipping mineral solids and other particulate matter, P (1) 20*d*.
Beech, D. G. New method for the study of pore size distribution—some notes on theory, (1) 18*c*. See Bennett, H.; West, H. W. H.
Beech, D. G., and West, H. W. H. (editors). Gas Firing, B (10) 263*d*.
Beecken, H. Process for the production of active PbO_2, P (6) 144*d*.
Beekmans, N. M. See Heyne, L.
Beer, L. N. See Nelson, F. W.
Beese, N. C. Sealed-beam high-intensity Xe lamp with cooling structure, P (11) 270*i*.
Beeson, E. J. G. See Stanyon, H. E.
Beeson, E. J. G., and Stanyon, H. E. Lamp having 2 separate phosphor coatings, P (4) 82*e*.
Begemann, J. See Rehmet, M.
Begum, R. J. See Murthy, N. S. S.
Behrens, R. Ash glazes for cone 6, (2) 30*a*. Cone 6 stoneware, (2) 30*d*. Crackle glazes, (2) 30*d*. Cr, the swinging glaze colorant, (2) 30*c*. Glaze Projects—a Formulary of Leadless Glazes, B (2) 50*j*. Oven and range-top clay bodies and glazes, (2) 30*b*. Raku glazes, (2) 30*c*. Testing clay bodies, (2) 30*e*.
Behrndt, K. H. Formation of amorphous films, (6) 136*i*.
Beigel, B. Seals for rotary kilns, (8) 187*d*.
Beiler, L. B. See Jacobs, C. A. J.
Beike, H. Method and apparatus for pulverizing materials, P (2) 44*d*.
Beinard, G. S. See Lyashkevich, I. M.
Beisswenger, H. Mixing apparatus for powdered nuclear fuel, P (10) 254*a*.
Beke, B. Grinding equipment with more than one classifier, (9) 214*i*.
Beken, J. M. Continuous intensive mixing, (9) 229*d*.
Belen'kaya, I. M., Dubinin, M. M., and Krishtofori, I. I. Formation and properties of H form mordenite (II) preparation of H form of natural mordenite and associated process; (III) adsorption of H_2O vapors on modified samples of synthetic mordenite; (IV) structure and porosity of modified H forms of synthetic mordenite, (3) 73*j*.
Belhomme, C. See Yperman, J. M. B. G.
Belitskii, M. E. Oxidation resistance and some strength properties of sintered Ni-base materials with small natural-mica additions, (10) 260*e*.
Bell, B. B., and Pederson, W. E. Slurry process for coating particulate material on a surface, P (7) 170*d*.
Bell, H., Krishnamachari, V., and Jones, J. T. Recovery of high-temp. creep-resistant substructure in rutile, (2) 49*g*.
Bell, H. B. See Rouf, M. A.
Bell, H. W., III. Improved device for supporting semiconductor wafers, P (10) 250*i*.
Bell, N., and Lam, Hung-Kei H. Purification of $MgCl_2$ solutions, P (10) 257*h*.
Bell, P. M. See Mao, H. K.
Bell, P. S. See Billingham, J.
Bell, R. K. See Shultz, J. I.
Bell, R. L. Photoemitter having a *p*-type semiconductive substrate overlaid with Cs and *n*-type Cs oxide layers, P (6) 139*a*. See James, L. W.
Bell, R. N. See Angstadt, R. L.
Belle, J. See Burke, T. J.
Bellis, H. E. Ni or Co wear-resistant compositions and coatings, P (10) 248*d*.
Bellon, S. See Linstedt, H.
Belmas, J. See Pestie, J. P.
Beloborodova, E. A. See Karpinos, D. M.
Belohlav, L. R. See Steuetz, D. E.
Beloivan, A. F., Vishnevskii, V. B., and Chernyavskaya, N. I. Properties of mica ceramics based on chemically dispersed mica, (10) 260*d*.
Belostotskaya, N. S. See Sheinin, E. I.
Belotskii, D. P., Panchuk, O. E., Panchuk, I. E., and Rybailo, O. I. System CdSb-CdTe, (9) 239*f*.
Belov, N. V. See Ganiev, R. M.
Belozerova, L. P. See Afinogenov, Yu. P.
Belruss, V., Kalnajs, J., Linz, A., and Folweiler, R. C. Top-seeded solution growth of oxide crystals from nonstoichiometric melts, (2) 39*h*.
Belt, R. F., and Florio, G. C. Permeability and temp. coeff. changes in hot-pressed flame-sprayed Ni-Zn ferrites, (7) 167*b*.
Belton, G. R., and Worrell, W. L. (editors). Heterogeneous Kinetics at Elevated Temps., B (6) 154*g*.
Belue, J. C., and Jones, Weston C. [Fiber] drying chamber apparatus and method, P (10) 244*f*.
Belyaev, I. N. Physicochemical analysis of systems important for the preparation of ferroelectric and piezoelectric materials, (5) 122*d*.
Belyaev, I. N., and Kazanbekov, R. G. Binary systems of the tungstates and sulfates of Ag, K, and Cs, (1) 21*a*. Reaction of the sulfates and tungstates of K and Ag during crystallization from melts and in the solid state, (5) 123*h*.
Belyaev, I. N., and Shilov, S. A. System KF-CoF_2 as a possible model of the system BaO-TiO_2, (1) 25*j*. Systems $KNbO_3$-KMF_3 (M= Mg,Mn), (2) 50*c*.
Belykh, P. D. See Zakhvalinskii, M. N.
Belz, H. M. See Stieber, H. C.
Benali-Baitich, O. See Wendling, E.
Ben-Amoz, M. Propagation of finite-amplitude waves in unidirectionally reinforced composites, (7) 179*h*.
Bendixen, K. E. Fuel burner unit for mounting in a common air box, P (10) 256*f*.
Ben-Dor, L., Glasner, A., and Zudkevitz, A. Reactions caused by additive coloration of Tl^+- and Pb^{2+}-doped KCl, (9) 238*e*.
Benedetti, F. See Prijn, C.
Benedict, R. P. Apparatus for measuring the avg temp. of a gas stream, P (3) 70*g*.
Benedict, R. P., and Russo, R. J. Grounded thermocouple circuits, (11) 279*c*.
Beneking, H. Blocking FET, P (8) 200*e*. Semiconductor device, P (8) 202*h*.
Benezech, G. See Millet, J.
Bengtson, R. H. See Hyland, J. W., Jr.
Benham, T. H. Metalizing chamber viewing system, P (3) 69*b*.
Beninga, D. H. Ceramic-rubber composites, P (1) 10*c*. Ceramic seal, P (3) 62*a*. Composite capstan assembly, P (3) 62*a*. Composite ceramic-organic material and method for making, P (9) 223*b*.
Beninga, D. H., and Gibbons, H. P. Organic resin-ceramic composite and method for making, P (1) 10*f*.
Benjamin, J. S. Sintered refractory articles of manufacture, P (3) 61*e*.
Bennett, C. A. Glass laser coupling reflector, P (3) 65*c*.
Bennett, G. S. Mosaic acoustic transducer for cathode-ray tubes, P (3) 66*c*.
Bennett, H. "Wet" chemical methods of analysis for major and minor constituents, (9) 231*c*.
Bennett, H., Eardley, R. P., and Beech, D. G. Sampling of hard heterogeneous materials (I) derivation of a new and simple technique, (1) 18*f*.
Bennett, H., and Reed, R. A. Chemical Methods of Silicate Analysis—A Handbook, B (7) 182*h*.
Bennett, H. L. Device for measuring the friability of particulate solid materials, P (5) 116*e*.
Bennett, H. M. See Jensen, T. H.
Bennett, H. S. Heat diffusion near absorbing centers in laser materials, (1) 11*h*. Inclusions in laser materials, (1) 11*i*. See Franklin, A. D.
Bennett, L. H., and Carter, G. C. Enhanced lever rule for high-precision phase diagram determination, (6) 147*g*.
Bennett, M. C., and Gardiner, S. D. Manufacture of aragonite, P (9) 232*h*.
Bennett, P. E. See Johnson, A. B.
Bennett, R. B. See Niesz, D. E.
Benning, B. L. R. Production of Ba hydroxide monohydrate, P (8) 207*d*.
Benoit a la Guillaume, C., Debever, J. M., and Salvan, F. Radiative recombination in highly excited CdS, (5) 123*c*.
Benson, K. E. See Beadle, W. E.
Benson, L. V., and Matthews, R. K. Electron microprobe studies of Mg distribution in carbonate cements and recrystallized skeletal grainstones from the Pleistocene of Barbados, West Indies, (8) 186*b*.
Benthien, E. Comparison of national and international specifications for film resistors of high accuracy, (1) 11*a*.
Bentley, G. I., and Roe, J. L. Liquid filter for removing fine clay particles and the like, P (11) 277*b*.
Bentsen, L. J. See Smead, R. G.
Bentvelsen, P. A. C. Electric cable insulating housing filled with high-resistance material [SiC], P (4) 85*j*.

Bentzien, L. T. Plate shifter and scraper assembly for filter presses, P (5) 115*i*.
Benyei, K. Effect of alkalis and chlorides on the formation of alite and belite, (7) 177*f*.
Benz, M. G. See Martin, D. L.
Benz, M. G., and Martin, D. L. Heat-aged sintered Co-rare earth intermetallic product and process, P (11) 274*h*.
Benz, R., Hoffman, C. G., and Rupert, G. N. UC-UC_2 phase boundaries, (4) 91*h*.
Beran, P., and Berka, A. Determination of H_2O in magnesite, (10) 255*c*.
Berard, M. F. See Jones, J. T.
Berden, W. J. H. Plaster molds in ceramic slip casting process, (4) 85*j*. Pores in plaster molds, (9) 223*d*.
Berdichevskii, N. I. See Morachevskii, A. G.
Berecki, W. A. See Bovenkerk, H. P.
Berejka, A. J. See Higgins, J. J.
Beremand, G. B. See Petrasek, D. W.
Beresford, M. P., and Scott, B. F. Method and apparatus for working material using laser beams, P (3) 69*c*.
Beretka, J., Ridge, M. J., and Brown, T. Reaction between finely divided Fe(III) oxide and $BaCO_3$ in vacuo, (1) 24*a*.
Berezhnaya, V. T. See Bukhalova, G. A.
Berezhnoi, A. I., and Il'chenko, L. N. Effect of precrystallization heat treatment on the nature of the low-temp. crystallization of photosensitive glass, (9) 217*c*.
Berezhnoi, A. S. Advances in the study of the physicochemical systems as the basis of refractories technology, (8) 194*g*.
Berg, L. G., and Egunov, V. P. Magnitudes of the areas in thermographic measurements of thermal effects, (5) 116*g*.
Berg, L. G., Pribylov, K. P., Egunov, V. P., and Abdurakhmanov, R. A. Thermal dehydration of Fe(III) hydroxide, (8) 211*j*.
Berg, M. See Schwyn, R. E.
Berg, R. H. Method of mounting disks in glass walls heat working only once, P (10) 245*d*.
Berger, C. See Arrance, F. C.
Berger, G. See Keller, W.
Berger, R. L. $Ca(OH)_2$—its role in the fracture of Ca_3SiO_5 paste, (7) 156*b*. See Klemm, W. A.
Berger, R. L., and McGregor, J. D. Influence of admixtures on the morphology of $Ca(OH)_2$ formed during Ca_3SiO_5 hydration, (5) 103*a*.
Bergeron, C. G. See Eagan, R. J.
Berggren, M. J., Imbusch, G. F., and Scott, P. L. Optical and ESR studies of 4th-nearest-neighbor Cr ion pairs in ruby, (6) 150*e*.
Bergh, A. A., and Paola, C. R. Horizontal liquid phase crystal growth apparatus, P (9) 225*d*.
Berglund, C. N. See Nicollian, E. H.; Powell, R. J.
Berglund, C. N., and Boll, H. J. Monolithic semiconductor apparatus adapted for sequential charge transfer, P (8) 201*i*.
Berglund, C. N., and Guggenheim, H. J. Electronic properties of VO_2 near the semiconductor-metal transition, (6) 147*d*.
Berglund, C. N., and Jayaraman, A. Hydrostatic-pressure dependence of the electronic properties of VO_2 near the semiconductor-metal transition temp., (6) 148*e*.
Berglund, C. N., and Klein, N. Thermal effects on switching of solids from an insulating to a conductive state, (4) 99*h*.
Berglund, C. N., and Lepselter, M. P. Temp.-stabilized electronic devices, P (2) 42*j*.
Bergman, A. G. See Drobasheva, T. I.; Kozachenko, E. L.; Matrosova, V. A.; Sanzharov, A. S.
Bergman, A. G., Gasanaliev, A. M., and Trunin, A. S. System $Na_2B_4O_7$,PO_3,P_2O_7, (5) 124*f*. Ternary system Na_2Cl,SO_4,PO_3, (8) 189*d*. System Na_2SO_4-$Na_2B_4O_7$-$Na_4P_2O_7$, (1) 25*j*.
Bergman, A. G., and Gontar, K. V. System Li,K,Ba‖F,Cl, (8) 211*g*.
Bergman, A. G., and Sanzharov, A. S. Ternary reciprocal system of the carbonates and tungstates of K and Na, (5) 124*i*.
Bergmanis, K. A., Klotins, E. E., and Matis, I. G. Device for measuring permittivity of materials, (9) 231*f*.
Bergmans, H. J. Integrated Hall-effect device, P (9) 225*e*.
Bergna, H. E. Hot-pressed TiN-TiC compositions, P (10) 247*i*. Ni-Mo-bonded TiN-TiC, P (9) 222*b*.
Berikashvili, I. G. See Il'yasov, I. I.
Bering, B. P., Kabanova, O. N., Serpinskii, V. V., Surinova, S. I., and Yakubov, T. S. New method for calculation of the adsorption of binary vapor mixtures on microporous adsorbents, (3) 69*j*.
Berka, A. See Beran, P.
Berka, L. H. See Christian, P. A.
Berkovich, T. M., and Dolinskaya, E. S. Optimal fractional composition of chrysotile asbestos and asbestos cement, (9) 214*j*.
Berl, K. Combining enamels and plastics (I–III), (2) 30*c*. Enameled masks, (2) 30*f*.
Berlincourt, D. A., and Pim, K. A. Multielement piezoelectric circuit component, P (10) 252*f*.
Berlinger, W. See Mueller, K. A.
Berman, H. S. SiC semiconductor device with heavily doped SiC ohmic contacts, P (1) 14*d*.
Berman, R. Diamonds as heat sinks—a review, (4) 86*e*.
Bernard, A. See Baron, A.
Bernard, C. E. Furnace for glass processes, P (5) 107*e*.
Bernath, L., and Facha, J. V. Articulated fuel element housing, P (9) 228*j*.
Bernier, J. C. See Bernigaud, G.; Massard, P.
Bernigaud, G., Bernier, J. C., and Michel, A. Evolution of crystallographic order in the systems Ta_2VO_8-VO_2 and WV_2O_8-VO_2, (7) 177*f*.
Bernshtein, R. S. See Karklit, A. K.
Bernstein, B. Semiconductor assembly with heat sink and connector bodies, P (5) 114*c*.
Bernstein, J. L. See Abrahams, S. C.
Bernstein, M. Method of bonding quartz to metal, P (8) 193*b*.
Berre, B., Fossheim, K., and Muller, K. A. Critical attenuation of sound by soft modes in $SrTiO_3$, (6) 145*f*.
Berry, B. S. See Nowick, A. S.
Berry, D. S. High-temp. proportional counter and insulator construction therefor, P (2) 40*b*.
Berry, J. W., and Deutschman, A. J., Jr. Hydrothermal method of growing ZnO crystals, P (2) 40*c*.
Berry, N. H. Ignition circuit radiation suppression resistor, P (10) 250*h*.
Berry, P. F., Hall, J. D., and Furuta, T. Radioisotope analytical instrument for cement analysis of concrete, P (3) 54*d*.
Berry, T. E. Zn-containing zeolite catalyst, P (7) 176*b*.
Berry, W. What it takes to grind to millionths, (2) 29*i*.
Bertin, E. P. Principles and Practice of X-Ray Spectrometric Analysis, B (1) 28*e*.
Bertolacini, R. J., and Gutberlet, L. C. U-containing and aluminosilicate-containing hydrocarbon conversion catalyst and process, P (7) 176*b*.
Bertoldi, G. See Remmers, K.
Berton, J. F., and Roelandt, B. Influence of sintering parameters on electrical properties of a high dielectric constant ceramic, (9) 224*f*.
Bertrand, W. F. See Teague, D. M.
Bertsch, H. C., and Russo, M. E. Increasing the particle size of precipitated halophosphate phosphors with the aid of seed material, P (8) 200*i*.
Berul, S. I., Rozanov, I. A., and Sizova, N. V. Chromatographic investigation of compounds formed in the systems $NaPO_3$-Fe_2O_3 and $NaPO_3$-Al_2O_3, (1) 21*c*.
Besamat, R., and Basseville, P. Method of mfg. thin-film circuits, P (1) 13*b*.
Beschke, H., Pfleger, H., Ferch, H., and Eisenmenger, E. Production of finely divided organically modified silicas, P (8) 207*e*.
Besedin, A. F. See Nekrasov, N. N.
Besse, J. P. See Vedrine, A.
Besser, P. J. See Mee, J. E.
Besser, P. J., Mee, J. E., Elkins, P. E., and Heinz, D. M. Stress model for heteroepitaxial magnetic oxide films grown by chemical vapor deposition, (2) 49*i*.
Besson, J. See Caillet, M.
Bessonov, A. F. Phase transformations during heating of a specimen from a mixture of MgO, SiO_2, CaO, and Fe_2O_3, (8) 210*b*.
Bethke, P. M., and Barton, P. B., Jr. Subsolidus relations in the system PbS-CdS, (4) 99*e*.
Bettinali, C., and Ferraresso, G. Luminescence centers in Pb silicate glasses, (3) 56*d*.
Betts, F. See Bienenstock, A.
Betz, G., Dobrozemsky, R., Viehboeck, F. P., and Wotke, H. Determination of the distribution of fission products in fuel particle coatings by the sputtering technique, (5) 114*h*.
Betzer, C. L. Burner grate [coating], P (10) 242*h*.
Beumer, P. See Zirngibl, H.
Beutler, H., and Beatty, R. L. Low density pyrolytic C coating process, P (11) 276*d*.
Bevan, C. G. Treatment [fluidization] of particulate material, P (11) 277*g*.
Beveridge, D. L., and Bulkin, B. J. Descriptive crystal orbital theory of conduction in diamond and graphite, (1) 21*g*.
Bezjak, A., and Jelenic, I. Quantitative determination of major and minor phases in portland cement from X-ray diffraction patterns represented by Fourier series, (5) 104*g*.
Bezruk, E. T. See Markovskii, L. Ya.
Bezsmertnaya, Z. G. See Bogdanova, G. S.
Bezykornov, A. I., Bogomolov, N. I., and Koval'chenko, M. S. Grain geometry and strength of some refractory-compound powders, (10) 259*j*.
Bhalla, V. K. See Harding, B. C.
Bhandari, R. C. See Agrawal, M. P.
Bharadwaj, S. C., Bishui, B. M., Ghosh, D. K., and Verma, S. S. Thermal conductivity of vitreous enamel-metal composites and allied ceramic materials by divided bar method, (11) 267*d*.
Bhargava, A. K. See Morris, D. E.
Bhargava, J. K. Choice of voltage and film in radiography of thin rock slabs, (8) 204*i*.
Bhatt, H. J. Semiconductor device, electrical conductor, and fabrication methods therefor, P (4) 90*c*.
Bhatt, H. J., and Tuttle, J. W. Semiconductor device, electrical conductor, and fabrication methods therefor, P (4) 90*c*.
Bhide, V. G., and Bahl, M. K. X-ray *K*-absorption edge of Nb in Nb metal and its oxides, (6) 153*b*.
Biagini, S. Apparatus for skimming the surface of molten metal baths in mfg. glass, P (7) 161*h*.
Biancifiori, M. A. See Bordonali, C.
Bickerdike, R. L., and Hughes, G. C materials and articles, P (10) 247*e*.
Bickerstaff, K. See Branch, G. H.
Bickley, W. P. See Ainger, F. W.
Biczo, G. See Ladik, J.
Biederman, E. W., Jr. Lightweight cements for oil wells, P (9) 215*f*.
Bienenstock, A., Betts, F., and Ovshinsky, S. R. Structural studies of amorphous semiconductors, (6) 152*c*.
Bierbrauer, G. Experiences with kiln furniture, (10) 246*f*.
Biggar, G. M. See Aggarwal, P. S.; O'Hara, M. J.
Biggers, J. V., and Schulze, W. A. Dc bias effects in $BaTiO_3$ ceramics, (9) 223*h*.
Bikerman, J. J. Comments on "Development of the bubble technique for the measurement of the surface energy of solids," (5) 119*i*.
Bilaine, J. See Penicaud, L.
Billeter, T. R. Using microwave techniques for high temp. measurements, (9) 231*b*.
Billhardt, H. W. New data on basic Pb sulfates, (9) 237*e*.
Billingham, J., Bell, P. S., and Lewis, M. H. Superlattice with monoclinic symmetry based on the compound V_6C_5, (10) 261*b*.
Billings, D. D. See Conroy, A. R., Jr.
Billy, M. See Goursat, P.
Bilous, O., Meulemans, D. R., Pecorado, R. P., and Selby, M. C. Process for fabricating semiconductor devices having compensated barrier zones between *np* junctions, P (3) 66*j*.
Bimberg, R. See Riedel, W.
Binder, W. See Stich, H.
Binns, D. B. Ceramics for electrical insulation at high frequencies, (7) 166*h*. Conducting glazes (I) properties of glazes based on Fe oxide, (11) 272*g*.
Binns, D. B., Cooper, M. T., and Littler, E. S. Breakdown strength of electrical refractories at high temp., (7) 164*j*.
Binogradova, L. V. See Poluboyarinov, D. N.
Birchall, J. D. Precipitated $CaCO_3$, P (4) 94*e*.
Bird, U. S. See Gammill, A. M.
Birgeneau, R. J. See Cox, D. E.
Birin, E. A. See Galkin, N. P.
Birks, L. S. Electron Probe Microanalysis, B (11) 283*f*.
Birie, J. D. Refining of cubic BN, P (8) 197*a*.
Birner, R. A., and Einfalt, A. C. Glass-forming machine with position sensing means, P (1) 4*g*.
Biro, S. Development of drawn sheet glass mfg., (5) 105*i*.
Biryuk, L. I., Goroshchenko, Ya. G., Khandros, E. L., and Kalinichenko, A. M. Changes in composition and structure of Ti hydroxide during heating, (6) 145*i*.
Biryukova, R. S., and Popova, O. I. Chemical properties of Nb germanides, (6) 145*a*.
Bischoff, K., Harrison, J. D. L., and Potter, P. E. Preparation and characterization of sintered U-Pu oxides, (1) 16*a*.
Bishop, S. G., Moore, W. J., and Swiggard, E. M. Cd phosphide laser, P (5) 112*f*.
Bishui, B. M. See Bharadwaj, S. C.
Bisinella, A. J. Sand mulling or conditioning apparatus and plow construction therefor, P (9) 230*d*.
Bisque, R. E. See Stevens, D. N.
Biswas, S. R. See Mukerji, J.
Bit, E. F. See Borisov, V. G.
Bither, T. A. Compound $Pd_3P_2S_8$, P (7) 168*b*. Pd phosphide chalcogenides, P (7) 169*i*. See Marcus, S. M.
Bitterli, C. See Mahan, A. I.
Bittmann, C. A., and Parker, G. W. Two-layer metalized hf transistor employing extended contacts to shield input terminal from output terminal and mounted in a coaxial cable, P (2) 43*a*.
Bizot, D. Studies in the system NbF_5-PbF_2, (10) 261*g*.
Bizzarri, V. Shaped bodies resistant to oxidation, particularly electric resistance elements, P (5) 110*c*.
Bjerkelund, E., and Kjekshus, A. Compounds with the marcasite-type crystal structure (VII) phases $Cr_{1-x}Fe_xSb_2$, $Fe_{1-x}Co_xSb_2$, $Co_{1-x}Ni_xSb_2$, and $Ni_{1-x}Fe_xSb_2$, (5) 118*h*.
Blachere, J. R., and Young, J. E. Freezing point of H_2O in porous glass, (7) 159*c*.
Black, J. C., and Buckley, F. All-transistor logic employing transistors of a single conductivity type, P (6) 137*f*.
Black, J. R., and Gurev, H. S. Vertical resistor, P (10) 253*f*.
Blackburn, P. E. See Battles, J. E.
Blaine, R. L., and Arni, H. T. Interrelations between cement and concrete properties (V) freezing-and-thawing durability, saturation, H_2O loss and absorption, dynamic modulus, (7) 156*f*.
Blake, D. L. See Shulver, W.
Blakeslee, K. C. See Levitt, S. R.
Blakeslee, K. C., and Condrate, R. A., Sr. Vibrational spectra of hydrothermally prepared hydroxyapatites, (1) 26*a*.
Blanchard, J. L. Magnetic memory member, P (11) 275*a*.
Blandy, C. Prefabrication in refractory construction, (9) 232*b*.
Blankenburg, H. Comparison of the preparation of a porcelain body by the conventional

method and by use of a spray-dried prepared body, (9) 223*b*.

Blasse, G. Uv absorption bands of Bi^{3+} and Eu^{2+} in oxides, (8) 211*e*. See Bril, A.

Blasse, G., and de Vries, J. Bi-activated Y oxysulfate, P (4) 87*f*.

Blaszyk, P. E. See Riebling, E. F.

Blatchford, J. K., Peterson, E. C., and Burda, J. C. Method of making a [ceramic-coated] heating element, P (10) 242*g*.

Blau, H. H. See Dietz, E. D.

Blazek, W. S. Method of making accurate cores, P (10) 248*a*.

Blech, J. J. Gas turbine ceramic regenerator, P (10) 247*h*.

Blechermar, S. S. See Bala, M. J.

Blecherman, S. S., Bala, M. J., Evans, D. J., and Ulion, N. E. Vapor collimation in vacuum deposition of coatings, P (3) 68*a*.

Bleckmann, H. See Schwiete, H. E.

Bleckmann, H., and Zografou, C. Effect of mineralizers on the structure and strength of hard porcelain and oxide bodies, (10) 248*f*.

Bleh, O. See Keddeinis, H.

Bleha, W. P., Jr., and Scholl, R. F. Storage tube comprising electroluminescent phosphor and CdS field sustained conducting target, P (10) 253*d*.

Bleil, C. E. Crystal pulling from molten melts including solute introduction means below the seed-melt interface, P (1) 12*f*. Horizontal growth of crystal ribbons, P (10) 250*h*. Semiconductive chip attachment method, P (5) 114*b*.

Bless, P. W., von Dreele, R. B., Kostiner, E., and Hughes, R. E. Anion and cation defect structure in Mg fluorogermanate, (10) 258*b*.

Blickle, T., and Nemeth, J. New correlation for calculating pressure decrease in gases flowing through fixed beds, (2) 44*f*.

Bliem, F. See Barnebl, A. C.

Blinc, R., and Mali, M. ^{87}Rb quadrupole coupling and the ferroelectric transition in RbH_2AsO_4, (5) 123*d*.

Blinchikov, A. L. See Nekrasov, N. N.

Block, A. Abrasive pack with anchor assembly, P (10) 241*e*.

Block, J. See McKennev, R. L., Jr.

Block, S. See Forman. R. A.

Blodgett, W. E. See Wallick, C. R., Jr.

Bloemen, J. L. H. H. Spray dryer in the ceramic industry, (4) 92*g*.

Blohm, R. Means for cleaning and cooling grinding wheels, P (9) 213*e*.

Bloice, J. A. Flame quality and presence monitor for multiburner furnaces, P (2) 45*g*.

Blonskaya, V. M., Lopatnikova, L. Ya., and Pankratov, V. L. Effect of mineralizers on the formation of clinker in a rotary kiln, (8) 186*j*.

Bloom, D. N. See Stevens, D. N.

Bloom, H., and Weeks, I. A. Densities of alkali metal chloride+$ZnCl_2$ melts, (6) 146*g*. Electrical conductances of some alkali chloride+$ZnCl_2$ melts, (6) 147*d*. Viscosities of NaCl+$ZnCl_2$ melts, (6) 153*c*.

Bloss, F. D. Crystallography and Crystal Chemistry—an Introduction, B (1) 26*j*.

Blosser, E. R., Iden, R. B., and Hall, E. H. Method for determining presence of OH in MgO, P (1) 18*h*.

Bludov, B. F. See Ved, E. I.

Blum, J. M., and Hoekstra, J. P. Method for alloying metals in the presence of reactive materials, P (9) 226*c*.

Blum, N. A. See Chappert, J.

Blum, P. Rock sampling, P (1) 17*b*; P (2) 44*c*.

Blum, S. E., and Chicotka, R. J. Method for growth of a mixed crystal with controlled composition, P (4) 88*i*. Method for the synthesis and growth of high-purity III–V semiconductor compositions in bulk, P (2) 41*c*.

Blum, S. E., Foster, L. M., and Plaskett, T. S. Group III–V semiconductor twinned crystals and their preparation by solution growth, P (5) 112*f*.

Blume, A. J. Extrusion die design, (3) 69*a*.

Blumenberg, H. H. Miniaturized cathode-ray tube with precisely oriented electrostatic deflection electrodes, P (1) 13*j*.

Blumenfeld, M. A., and Sonneborn, K. J. Method of making a P glass passivated transistor, P (2) 41*g*.

Blumenthal, E. See Kay, J.

Blumenthal, J. L. See Carroll, D. F.

Blumenthal, R. N. See Long, S. A.; Panlener, R. J.

Blunt, R. F. See Cohen, M. I.

Blunt, R. F., Candela, G. A., Forman, R. A., Kahn, A. H., and Mangum, B. W. Magnetic susceptibility and optical studies of Cr^{3+} in Al_2O_3 (ruby)—magnetic method for determining concentration, (5) 121*d*.

Blythe, G. E. K. Method for the commimution of particulate solid materials, P (2) 44*d*.

Boatman, J. C. Apparatus for forming monocrystalline ribbons of Si, P (3) 64*e*.

Boaz, P. Method [baffle] for controlling the rate of flow of molten glass from a channel, P (3) 59*b*.

Bobb, J. S. S. Method of preparing an SiO_2 sol and product, P (7) 175*d*.

Bobeck, A. H., Schmidt, P. H., Spencer, E. G., Van Uitert, L. G., and Walters, E. M. Magnetic devices utilizing garnet compositions, P (2) 40*h*.

Bobeck, A. H., Sherwood, R. C., and Van Uitert, L. G. Magnetic devices utilizing garnet compositions, P (9) 225*i*.

Bobeck, A. H., Smith, David H., Spencer, E. G., and Van Uitert, L. G. Magnetic devices utilizing garnet compositions, P (6) 138*h*.

Bobos, G. E. See Irving, S. M.

Bobrowsky, A. See Roy, D. M.

Bobryshev, A. I. See Tertykh, V. A.

Bochkareva, N. N. See Kochergin, V. P.

Bockstie, L. G., Jr. Impregnating and coating composition for porous ceramic insulation, P (9) 219*f*.

Bockstiegel, G. Study of the work of compaction in powder pressing, (10) 254*e*.

Bockstiegel, G. E., and Hack, P. Process for mfg. ZrO_2 and Al_2O_3 abrasive of high grit toughness, P (1) 1*g*.

Bocs, A. See Opoczky, L.

Bocsi, I., Gemesi, J., and Kabdebon, I. Measurements and changes carried out with the pilot furnace of the Sajoszentpeter Glass Works [Hungary], (6) 143*b*.

Bodart, M. See Javaux, G.

Bode, W. W., Dunlap, G. H., Kobylak, A. M., Richards, R. S., and Pfaender, L. V. Fabrication of planar capillary tube structure for gas discharge panel, P (11) 270*f*. Method of making [glass] gas discharge device, P (7) 162*d*.

Bodine, A. G. Sonic method and apparatus for processing slurries for transportation, P (11) 277*g*.

Bodman, S. W., Shah, Y. T., and Skriba, M. C. Settling of flocculated suspensions of TiO_2 and alum mud in H_2O, (5) 111*b*.

Bodnar, R. E., and James, D. L. Preparation and magnetic susceptibility of alkali Nd titanate perovskites, (9) 237*g*.

Bodway, G. E. Method of producing thin-film circuit elements, P (2) 41*a*.

Boeckeler, B. C. See Nemeth, B. J.

Boeke, K. See Nienhuis, W. F.

Boer, K. W. Electrical conduction mechanism in highly disordered semiconductors, (6) 147*e*.

Boer, K. W., Dussel, G. A., and Voss, P. Evidence for a reduction of the work function of blocking Au contacts with increasing photocurrents in CdS, (5) 120*c*.

Boerner, M., and Goldbach, G. Semiconductor laser diode arrangement for exciting lightwave conductors, P (2) 42*d*.

Boesch, L. P. See Provenzano, V.

Boettcher, A. Coated-particle fuel and fertile element for nuclear reactors and method of operating same, P (9) 228*j*.

Boettcher, G. E. Cold cathode vacuum discharge tube with cathode discharge face parallel with anode, P (8) 192*d*.

Boffe, M. See Toussaint, F.

Boffe, M., and Toussaint, F. Diffusion methods for improving the properties of glass, vitrocrystalline, and stone materials, P (4) 81*e*.

Bogart, B. S., and Dilliard, P. D. Chemical strengthening of glass articles produced with flame treatment, P (2) 33*g*.

Bogatikova, V. K. See Khoroshavin, L. B.

Bogdan, J. R. See Farmer, A.

Bogdanova, G. S., Orlova, E. M., and Bezsmertnaya, Z. G. Phase composition and properties of sitalls of the system Li_2O-Al_2O_3-GeO_2-TiO_2, (8) 191*j*.

Bogenschuetz, A. F., and Krahl, P. Investigations on dielectric pastes. (Protection against arcing), (8) 199*j*.

Boggum, P. Technical design and selection of refractory materials for the equipment of an Na silicate melting furnace, (7) 163*j*.

Bognar, L. L. Forming vessels from green glass-ceramic sheets, P (10) 244*g*. Method and apparatus for forming hollow articles from sheet glass, P (1) 4*f*.

Bogomolov, N. I. See Bezykornov, A. I.

Boguslavskii, I. A. See Pukhlik, O. I.

Boguslavskii, N. M. Apparatus for thermal treatment of free-flowing materials and slurry, P (11) 277*f*.

Bohannon, R. O., Jr. Process for fabricating integrated circuit having matched complementary transistors, P (11) 275*a*.

Bohm, J. Electronic switch, P (1) 12*a*.

Boiko, P. A., and Moroz, A. L. Investigation of the influence of simple and binary carbides of Group-IV and Group-V metals on certain properties of cermet Ni, (10) 259*d*.

Boisvert, A. R., and Boule, W. L. Semiconductor device having a connecting pad of low-resistivity semiconductor material interconnecting Au electrodes and Al contacts of an enclosure, P (3) 67*b*.

Boiteau, C. See Jumentier, C.

Boix, A., and Debras-Guedon, J. Analysis of chrome and MgO refractories and their raw materials, (9) 221*e*.

Bokov, O. V. See Nezhevenko, L. B.

Bokros, J. C. [C] coated article and method for making, P (10) 247*d*.

Boksjo, C. I., and Sehman, B. A. Thyristor with a control device and having several control electrodes, P (9) 228*a*.

Bol, J., Buettner, H., and Kuhn, P. Temp.-indicating dispersion filter, P (10) 245*h*.

Bole, H. B. Lens blocking apparatus, P (9) 219*g*.

Bolef, D. I. See Melcher, R. L.

Boleky, E. J., and Burns, J. R. Fabrication of semiconductor devices, P (6) 137*e*.

Bolgar, A. S. See Ryklis, E. A.

Boll, H. J. See Berglund, C. N.

Bollin, P. L. Glass formation in the system Cs_2O-Al_2O_3-SiO_2, (10) 243*e*.

Bollmeier, A. F. See Mason, G. W.

Bologna, J. P. See Bowser, G. H.

Bolton, A. P. Process for improving the activity of zeolitic catalyst compositions, P (6) 144*a*.

Boltyanskii, A. V. See Pyatikop, P. D.

Bolwijn, P. T. See Schipper, D. J.

Bomar, R. L. See Tweed, D. G.

Bonazoli, R. P. See Kimball, S. F.

Bondam, J. Infrared absorption spectra of a number of Na fluoroaluminates in the wave number region 500–800 cm^{-1}, (11) 281*a*.

Bondar, I. A., Koroleva, L. N., and Toropov, N. A. Phase equilibria in the system Y_2O_3-Nb_2O_5, (9) 237*b*.

Bondar, I. A., and Petrova, M. A. Synthesis of single crystals of the diorthogermanates of Gd and Er from solution in molten Bi_2O_3, (8) 211*c*.

Bondar, I. Ya. See Flem, Z. L.

Bondarenko, L. M. See Borisov, V. G.

Bondarenko, V. P. See Kudintseva, G. A.

Bondarev, K. T., Kozmin, M. I., Minakov, A. G., Minin, V. I., Mitkevich, G. I., and Strekalov, A. V. Float glass apparatus for producing sheet glass crystalline material from a glass band, P (11) 270*f*.

Bonet, C., Vallbona, G., and Foex, M. Production of glassy spheres from quartz particles by processing through an N plasma stream, (9) 218*c*.

Bonetti, G. See Gottardi, V.

Bongers, P. F. See Wittekoek, S.

Bonham, R. D. Parliament of owls, (2) 30*b*. Thomas Shafer, (4) 78*a*. Tom Shafer demonstrates building a jar, (2) 30*f*.

Bonnan, D. See Heyndryckx, P.

Bonnel, B., and Hovasse, C. Portland cement composition having an accelerated set, P (8) 188*f*.

Bonner, W. A. Technique for the growth of single-crystal $PbMoO_4$, P (7) 170*e*.

Bonner, W. A., Singh, S., and Van Uitert, L. G. Li formate nonlinear devices, P (10) 251*b*.

Bonnet, A. See Jumentier, C.

Bonniaud, R., and Sombret, C. Glass as a coating material for radioactive waste, (11) 268*f*.

Booe, J. M. Cr-C and Cr-Ni-C resistive films, P (2) 39*f*.

Boon, A. Method of securing a metal supporting member to a glass wall by means of glaze, P (3) 59*g*.

Boone, S. See Roos, J.

Boore, E. J., and Sutter, D. M. Testing bond strength of semiconductor device assemblies, P (5) 114*b*.

Booth, A. E. Method of mfg. low-density insulating refractories, P (6) 135*a*.

Booth, F., Bourne, D. E., and Harrison, M. C. Calculations of the temp. distribution in glass in the sheet drawing process, (9) 216*c*.

Booth, R. E. See Phillips, S. V.

Bootsma, G. A., Knippenberg, W. F., and Verspui, G. Phase transformations, habit changes, and crystal growth in SiC, (7) 179*a*.

Borchardt, G., and Schmalzried, H. Diffusion in orthosilicates, (9) 234*b*.

Borchardt, H. J. Preparation of fibrous TiO_2, P (7) 175*e*.

Borchert, E., Frese, W., Pikorz, W., and Sonntag, A. Thyristor having at least 4 semiconductive regions and method of making, P (4) 91*e*.

Bordonali, C., and Biancifiori, M. A. Apparatus to be used for the analysis of traces of chemical elements through atomic absorption, P (11) 278*g*.

Borgne, R., Joly, J., and Rosiaux, E. Cathode sputtering apparatus for the deposition of composite thin films, P (8) 200*f*.

Borgstedt, H. U., Ruehle, M., and Winclerz, P. Composite material of V alloys and Fe or Ni alloys, P (10) 253*j*.

Borisov, A. F. See Zadumin, V. I.

Borisov, M. B. Making and using plastic pottery molds, (8) 197*h*.

Borisov, V. G. See Likhoradov, A. P.

Borisov, V. G., Rodgol'ts, Yu. S., Kononchuk, O. P., Kolesnik, L. N., Bondarenko, L. M., Glushchenko, V. I., Voronov, Yu. F., Filonov, O. V., Bit, E. F., Nesterova, A. L., and Kukuruznyak, I. S. Converter refractories with "hard" tars having an enhanced coke residue, (8) 194*j*.

Borisova, I. I., Kiryukhina, N. A., and Moiseeva, V. P. Industrial method of Cu plating mirrors, (8) 190*e*.

Borisova, Z. U. See Ipat'eva, V. V.; Pazin, A. V.

Borisova, Z. U., Valpolin, A. A., Goryunova, N. A., Kouzova, N. I., and Osmanov, E. O. Kinetics of dissolution of vitreous and crystalline specimens of the system CdGe-$(As_2P_{1-x})_2$, (7) 178*b*.

Bork, W. W. Strong markets will continue through the 70's, (11) 271*a*.

Borland, L. D., and Ward, G. V. Method for inoculating investment casting mold, P (1) 9*b*.

Borley, G. Analytical requirements of the fundamental geochemist, (9) 230*f*.

Borodai, F. Ya., and Evdokimova, T. M. Refractory compositions based on aluminophosphate binder, (8) 195*e*.

Borok, B. A. (editor). Researches in Powder Metallurgy (Vol. 2), B (10) 264*i*.

Boros, M., and Balazs, G. Hydration of C_3A-$CaSO_4$-H_2O systems, (5) 103*i*.

Borowski, B. J. Fe-containing TiO_2-opacified porcelain enamels, P (9) 216*a*.

Borrelli, N. F. Electric field induced birefringence in glasses, (2) 32*f*.

Borrelli, N. F., and Layton, M. M. Bistable optical elements using transparent ferroelectric glass-ceramics, P (5) 107*a*.

Borshchevskii, A. S., and Roenkov, N. D. Phase diagram of the system Cd-Ge-As, (5) 122*c*.

Bortz, S. A., Rechter, H. L., Reynolds, W. E., and Bazell, S. Reinforced porous ceramic bone prosthesis, P (8) 198*i*.

Borzunov, E. E., Shukhnin, L. N., and Kruglitskii, N. N. Investigation of compactibility of disperse structures, (2) 48*i*.

Bosacchi, B. See Baldini, G.

Boschini, M. A. See Poole, J. P.

Boshoff, D. A tale of bricks, (3) 60*b*.

Boskovic, S., Kostic, E., and Ristic, M. M. Sintering of NiO, (9) 238*j*.

Bossers, C. F. Method and apparatus for fabricating a cathode-ray tube envelope having an annular shaped rear window, P (9) 219*i*.

Bosworth, F. C. See Loop, F. M.

Boszilkov, V. See Grofcsik, J.

Bothge, D. Automatic stoneware pipe works for an output of 20,000 tons of fired ware per year, (7) 163*c*.

Botia, P. Duran. See Duran Botia, P.

Bottcher, J. H. See Banes, N. M., Jr.

Bouchard, R. J. Compositions for making electrical elements containing pyrochlore-related oxides, P (10) 250*c*.

Bouchard, R. J., and Weiher, J. F. $La_xSr_{1-x}RuO_3$—a new perovskite series, (8) 209*d*.

Boucher, A., and Hollan, L. Thermodynamic and experimental aspects of GaAs vapor growth, (9) 239*c*.

Boucher, R. C. E., Otto, J. L. M., and Taxil, A. M. V. Discharge lamp having vapor pressure control means, P (4) 81*e*.

Bouillaud, Y. Nonstoichiometric $NaNbO_3$, (8) 209*h*.

Bouis, H. See Chatelain, R.

Boule, W. L. See Boisvert, A. R.

Boulet, F. H., and Balteaux, R. H. Encasing process for press electrode semiconductor components, P (2) 40*f*.

Boulogne, A. R., and Faraci, J. P. Method of preparing a ^{252}Cf neutron, P (4) 91*i*.

Bourg, H. J., Jr. See Fisher, P. D.

Bourggraff, R., and Classen, F. Float glass apparatus with heat exchange control, P (1) 4*c*. Glass tank with a float supported by cooling elements, P (2) 34*g*.

Bourne, D. E. See Booth, F.

Bourne, D. J., and Lamb, F. E. Method of producing soda ash, P (8) 207*h*.

Bourne, R. F. Dust collectors, P (6) 141*e*.

Bourque, L. R. See Hastings, I. J.

Boussekey, B. See Durinck, R.

Bouwman, G. Progress in the construction of batch-type and continuous ceramic kilns, (10) 256*i*.

Boux, J. F. See Pennachetti, J. T.

Bovenkerk, H. P., and Berecki, W. A. Resinoid grinding wheels containing Ni-coated cubic BN particles, P (6) 127*h*.

Bowden, C. M., Meyer, H. C., and McDonald, P. F. Ultrasonic electron-nuclear double resonance of $CaF_2:U^{4+}$, (6) 152*h*.

Bowen, D. H., Mattingley, N. J., and Sambell, R. A. J. Apparatus for coating fibers, P (6) 131*f*.

Bowen, D. H., Sambell, R. A. J., Lambe, K. A. D., and Mattingley, N. J. C fibers embedded in glass matrix, P (10) 247*d*.

Bower, R. W. IGFET device having source and drain regions formed in part by ion implantation and method of making, P (2) 40*c*.

Bower, R. W., and Shifrin, G. A. Method of making ohmic contacts to semiconductor bodies by indirect ion implantation, P (1) 13*g*.

Bowes, W. M. See Burk, M.

Bowles, A. G. High production isostatic molding device, P (10) 254*d*.

Bowman, A. L. See Krikorian, N. H.

Bowman, E. W. Glass annealing lehrs, P (1) 4*e*.

Bowman, J. L. See Bresee, H. J.

Bowman, W. S. See Sutarno.

Bowser, G. H., Shoop, V. A., Pyzewski, S. J., Mazzoni, R. J., and Bologna, J. P. Method for fabricating a multiple glazed unit, P (9) 219*a*.

Boxall, L. G., and Johnson, K. E. Activity coeffs. of $AgNO_3$ in nitrate salts, (6) 144*i*.

Boyarintsev, P. K. See Kharakhorin, F. F.

Boyarshinov, E. G. See Dvorkin, L. I.

Boyce, W. A. Subminiature electric lamp having a composite envelope, P (4) 83*a*.

Boyd, F. R., and Smith, Douglas. Compositional zoning in pyroxenes from lunar rock 12021, *Oceanus Procellarum*, (8) 208*e*.

Boyd, G. D., Buehler, E., and Gandrud, W. B. Coherent optical devices employing Zn Ge phosphide, P (10) 244*a*.

Boyd, G. E. See Brooker, M. H.

Boyd, W. W. See Wakefield, G.

Boyer, M., and Souchay, P. Measurement of the molecular weights of the isopolytungstate ions, (6) 150*f*.

Boylan, D. R. See Wheelock, T. D.

Boyles, B. J. Apparatus for press bending glass sheets, P (2) 33*c*.

Boynton, T. E. Means for [spray] marking glass and the like, P (3) 58*h*.

Bozanic, D. A., Mergerian, D., and Minarik, R. W. Spin-echo studies of exchange effects in heavily doped $TiO_2:Fe^{3+}$, (6) 151*i*.

Bozarth, J. L. See Dumesnil, M. E.

Bozhko, S. A. See Samsonov, G. V.

Bozler, C. O. Apparatus for growing films [vapor deposition], P (5) 112*f*.

Brabers, M. J. See De Maayer, P.

Brabers, V. A. M. Magnetostriction of Mn ferrites at 293°K, (6) 150*d*. See van Landuyt, J.

Brack, K., Gorey, E. F., and Schwuttke, G. H. Monocrystalline semiconductor body having dielectrically isolated regions and method of forming, P (9) 226*j*. Semiconductor isolation structure and method of producing, P (3) 67*f*.

Brackelmanns, N. W. Method for making transistors including gain-determining step, P (9) 226*b*.

Braddock, W. B. See Pitzer, D. C.

Bradley, J. S., Duschatko, R. W., and Hinch, H. H. Pocket permeameter—hand-held device for rapid measurement of permeability, (8) 205*i*.

Bradley, R. O. See Steitz, W. R.

Bradley, W. L. See Coutinho, C. B.

Bradshaw, A. Mfg. pottery ware, P (1) 10*d*.

Bradshaw, A., and Meadows, F. W. Clayware shaping machine with adjustable tool supporting means, P (7) 166*a*.

Bradshaw, E. See Rabatin, J. G.

Bradshaw, R. I. See Rao, R.

Bradstreet, S. W. See Davis, L. W.

Bradt, R. C. See Coppola, J. A.; Hasselman, D. P. H.

Brady, G. D. Graphite anodes for impressed current cathodic protection—practical approach, (5) 109*g*.

Brady, J. G. See Wallace, R. W.

Brady, L. J. Electrical resistance elements, their composition and method of mfg., P (7) 168*f*.

Brady, W. C., Tiede, R. L., Veazie, F. M., and Wolf, W. W. Light-transmitting glass fibers—core and cladding glass compositions, P (1) 4*a*.

Braetsch, P. See Hock, H.

Bragard, A. A. Coating metallic materials, P (7) 158*a*.

Braginski, A. I., Isenberg, A. O., Miller, M. T., and Oeffinger, T. R. Chlorination of Y_2O_3 in presence of C, (9) 232*g*.

Braginski, A. I., Oeffinger, T. R., and Takei, W. J. Compositional variation in YIG films, (10) 248*j*.

Brahmecha, B. G., and Sinha, K. P. Resistivity anomaly in semiconducting $BaTiO_3$, (3) 75*a*.

Bramman, J. I., Sharpe, R. M., and Dixon, R. Fission-product inclusions in irradiated U-Pu carbide, (7) 171*h*.

Branch, G. H., Hall, J. E., Bickerstaff, K., and Russell-Rayner, A. P. Conveying of glass sheets, P (10) 244*b*.

Brand, J. S., and Honeiser, V. P. Mfg. printed circuits, P (7) 169*c*.

Brand, M. Sundials, (2) 30*e*. See Varga, J.

Brand, W. L. Method of vapor depositing a W-W oxide coating, P (9) 226*i*. Vapor-plated cermet resistor, P (9) 228*c*.

Brandes, R. G., and Pleass, C. M. Resistance heater and method for preparation, P (4) 90*i*.

Brandi, H. W. Hermetically sealed resistor, P (5) 112*g*.

Brandle, K. See Zirngibl, H.

Brandsma, A. See Helgeland, W.

Brandt, I. L., and Penrod, O. R. Electric resistance composition, P (5) 112*i*.

Brandt, W. W., Ikeda, T., and Schelly, Z. A. Diffusion of several gases in vitreous B_2O_3, (3) 55*b*.

Braniski, A. A new refractory high-Al_2O_3 cement, (8) 194*i*.

Branscomb, T. M., and Hunter, O., Jr. Improved thermal diffusivity method applied to TiB_2, ZrB_2, and HfB_2 from 200°–1300°C, (4) 97*e*.

Brants, J. P., and van der Meulen, J. Masonry materials that resist efflorescence and are colored with increased intensity and permanence, and methods of producing such materials, P (10) 246*c*.

Brantte, A., Frostling, B. H. I., and Lindgren, P. H. Apparatus for a quantitative analysis of a gas or gas mixture in respect of its content of organic substances, P (9) 231*d*.

Branwood, A. See Rothwell, R.

Bratschun, W. R., Mountvala, A. J., and Pincus, A. G. Uses of ceramics in microelectronics—survey, (2) 39*j*.

Brattas, L., and Kjekshus, A. Nonmetal-rich region of the Hf-Te system, (11) 281*g*.

Bratton, R. J. See Moratis, C. J.; Spengler, C. J.

Braun, F., Sr. Toilet bowl structure, P (7) 166*b*.

Braun, W. See Bauer, R.

Braunstein, J., Mamantov, G., and Smith, G. Pedro. (editors). Advances in Molten Salt Chemistry (Vol. 1), B (4) 100*b*.

Bray, P. J. See Baugher, J. F.; Griscom, D. L.; Hendrickson, J. R.; Kim, Y. M.; Park, M. J.; Rhee, C.; Taylor, P. C.

Bre, M. Diffusivity of glasses at high temps., (7) 158*j*.

Breckheimer, W. See Kunz, W.

Brede, D. W., Cook, M. H., Freeman, M. E., and Turk, H. L. Glass-bonded ceramic body for a magnetic head, P (2) 40*i*.

Bredt, J. H. See Kendall, L. F., Jr.

Bredzs, N., and Miller, F. M. Cermet-type alloy and method of making, P (9) 222*c*. Cermet-type alloy coating on metal base, P (10) 242*h*.

Breece, J. M. See Goodman, A. M.

Breedis, J. F. See Shaw, R. R.

Brekhunets, A. G., Kokot, I. F., Mank, V. V., and Mokhosoev, M. V. Nature of the H_2O in hydrated La oxide, (1) 23*d*.

Brennan, L. C. Preparation of III–V alloys for ir detectors, P (4) 90*b*.

Brennen, R. F. Spark plug, P (10) 242*h*.

Brennet, P. See Wollast, R.

Brent, J. T., Jr., and Page, J. S. Process for purifying gypsum using fluosilicic acid, P (5) 104*i*.

Bresciani, A. See Bresciani, L.

Bresciani, L., Comense, M., and Bresciani, A. Apparatus for etching a face of a large-size glass plate preferably according to predetermined patterns, P (2) 33*b*.

Bresee, H. J., and Bowman, J. L. Low-noise FET with channel having subsurface portion of high conductivity, P (7) 169*b*.

Breslmair, G. See Trojer, F.

Breslow, R. A., Owens, F., and Gilliam, O. R. EPR in γ-ray-irradiated Nb-doped $CaMoO_4$, (7) 177*a*.

Bretsch, M. A. See Podiak, R. S.

Brett, N. H. See Guilliatt, I. F.; Hossain, D.; Prendergast, I. D.; Sircar, A.

Breu, R. See Gaeth, R.

Brewer, G. E. F. Electrodeposition of ceramic coatings, (4) 79*j*.

Brewer, G. E. F., and Swider, R. A. Anodic deposition of ceramic frit with cationic envelope, P (4) 80*b*. Anodic deposition of frit in dual envelope, P (3) 64*d*.

Brewer, G. R. Electron and ion beams in microelectronic fabrication processes (I,II), (11) 273*e*.

Brice, W. R. See Chang, Luke L. Y.

Brichard, E. Apparatus for the treatment or production of flat glass floating on a liquid, P (7) 161*h*. Method of constructing a composite refractory hearth in a float glass furnace, P (8) 196*f*. Process for the treatment or production of floating flat glass, P (6) 133*f*. Refractory furnace wall of a glass sheet floating tank, P (7) 164*e*.

Brichard, E., and Declaye, J. Refractory elements for a glass float furnace wall, P (9) 222*f*.

Brichard, E., Jaupain, M., Plumat, E., and Deschepper, P. Method of forming refractory masses, P (11) 272*g*.

Bricker, J. A., and Shaw, H. E., Jr., Glass defect detection system, P (8) 192*j*.

Bridenbaugh, P. M. See Miller, R. C.

Bridenbaugh, P. M., Carruthers, J. R., and Nash, F. R. Modified Li niobate composition and devices utilizing same, P (9) 226*j*.

Bridges, R. J. Automatic SCR precipitator control, P (6) 141*d*.

Brigham, K., and Vickery, R. C. Castable-refractory die composition essentially free of Ca aluminate and method of using, P (6) 136*d*. Dental prosthesis model base composition containing CaF_2, P (6) 136*a*.

Bright, C. R. Glass lens edging apparatus, P (10) 244*b*.

Bril, A., Blasse, G., and de Poorter, J. A. Fast decay phosphors, (9) 224*c*.

Brill, K., and Grothe, W. Metallic vapor deposition arrangement, P (7) 169*d*.

Brindley, G. W. See Wardle, R.

Brinkmann, F. J., and Gerding, H. Spectroscopic study of the compound $PCl_5 \cdot FeCl_3$, (6) 151*i*. Structure of the compounds $TeCl_4 \cdot 2TlCl$, $SeCl_4 \cdot 2TlCl$, and $FeCl_3 \cdot 2AlCl_3$, (6) 152*c*.

Briody, T. F. Vapor deposition apparatus, P (8) 203*a*.

Brisi, C., Montorsi, M., and Burlando, G. A. Research on Sr uranates, (1) 16*e*.

Brisse, F. See Touzain, P.

Brissot, J. J. L. E. Method of producing $CaCO_3$ single crystals, P (8) 207*h*.

Brixner, L. H. Eu Sr chloride phosphate fluorescent composition, P (4) 87*g*. Fe-substituted $BaTiO_3$ ferroelectric compositions and capacitors comprising same, P (2) 40*f*.

Brizes, W. F., and Brody, H. D. Modification of the Nb-C phase diagram, (6) 150*i*.

Bro, P. See Dey, A. N.

Broce, M. E., Colman, D., and Mize, J. P. Transducer apparatus and system utilizing insulated-gate semiconductor field-effect devices, P (2) 43*c*.

Brociner, R. E. Grinding of minerals, P (3) 69*g*.

Brockman, F. G. Ni-Zn ferrites (IV) zero anisotropy in stoichiometric 50NiO/50ZnO ferrite containing 0.5 mol% CoO—relation between 60-Hz and 2.5-MHz magnetic losses, (2) 38*j*.

Brockmann, H. Furnace having structure for feeding work through a heat tunnel, P (9) 232*c*.

Broderick, J. P., Wishnie, F. T., and Keys, D. L. Flame spray torch, P (3) 69*f*.

Brodsky, M. H., and Title, R. S. ESR in amorphous Si, Ge, and SiC, (6) 147*b*.

Brody, H. D. See Brizes, W. F.

Brody, S. B., Chambers, F. A., and Seitelman, M. Conductivity of PbO, (5) 119*a*.

Brody, T. P. See Page, D. J.

Brody, T. P., Page, D. J., and Raygor, P. O.

Thin-film electronic components on flexible metal substrates, P (8) 202*h*.

Broemer, H. See Leitz, E.

Broemer, H., and Meinert, N. Optical fluorophosphate glass having an anomalous partial dispersion ratio, P (9) 219*f*.

Broemer, H., Meinert, N., and Preuss, H. J. Nuclear radiation absorbing glass, P (3) 59*a*.

Broersma, F. R. See Elo, A., Jr.

Broida, H. P. See Sakurai, Katsumi.

Brojdo, S. Semiconductor apparatus for image sensing and dynamic storage, P (10) 252*g*.

Bromley, J. See Sach, R. S.

Brook, R. A. See West, R. N.

Brook, R. J. Effect of TiO_2 on the initial sintering of Al_2O_3, (3) 72*i*.

Brooker, M. H., Irish, D. E., and Boyd, G. E. Ionic interactions in crystals—ir and Raman spectra of powdered $Ca(NO_3)_2$, $Sr(NO_3)_2$, $Ba(NO_3)_2$, and $Pb(NO_3)_2$, (7) 178*a*.

Brookes, C. A. Indentation hardness of diamond, (4) 77*g*.

Brooks, D. R. See Lamont, W. E.

Brooks, W. T. Nonvoltage sensitive indicator light, P (9) 227*b*.

Brossard, A. See Bauer, J. M.

Brossard, D. Method and apparatus for the production of fibers from thermoplastic materials, particularly glass fibers, P (7) 162*i*.

Brosselard, E. See Luff, P. P.

Brostigen, G., and Kjekshus, A. Compounds with the marcasite-type crystal structure (V) crystal structure of FeS_2, $FeTe_2$, and $CoTe_2$, (5) 118*h*.

Brough, R., Harrison, R., and Dinsdale, A. Function of H_2O in damage to glazed tiles by frost, (1) 6*b*.

Broutman, L. J. See Agarwal, B. D.

Brouwer, H. J., de Veer, S. M., and Zeedijk, H. SO_2 monitoring network in the Rhine estuary region, (9) 231*j*.

Brouwers, J. S. H. Modern mechanical methods for roof tile pressing, (4) 83*i*.

Browder, J. S., and Ballard, S. S. Thermal expansion measurements on 4 optical materials from room temp. to 10°K, (10) 243*a*.

Brower, W. S., Jr., and Parker, H. S. Growth of single-crystal Cu_2O, (7) 177*i*.

Brown, A. E. See Collins, T.

Brown, Charles E., and Stech, H. G. Hybrid microelectronic packages—a compilation of various manufacturers' types, (3) 63*b*.

Brown, C. Justus, Jr. Mixing glass batch materials, P (1) 5*d*.

Brown, D., Chaudhri, G., and Feltham, P. Energy barriers in high-temp. creep of Ge and LiF single crystals, (6) 147*e*.

Brown, Dale M. Self-registered MOSFET—a brief review, (11) 274*j*.

Brown, Dale M., and Engeler, W. E. FETs with superior passivating films and method of making, P (5) 112*d*.

Brown, Dale M., and Garfinkel, M. Diffusion masking in semiconductor preparation, P (5) 112*i*.

Brown, D. B., and Gilfrich, J. V. Measurement and calculation of absolute X-ray intensities, (5) 116*g*.

Brown, Don W. See Condas, G. A.

Brown, G. A. See Carlson, H. G.

Brown, Howard W. See Clark, T. J.

Brown, John J., Jr. Method and apparatus for dehacking brick, P (9) 221*b*.

Brown, Jesse J., Jr. Phase equilibria in the system SrO-CdO-V_2O_5, (11) 281*j*. See Palumbo, D. T.

Brown, J. P. See Alig, R. C.

Brown, K. R. See Lane, R.

Brown, Lionel A. Arikara Indian ceramics, (2) 30*a*.

Brown, Lloyd H., and Watson, D. D. Fiber glass laminates containing furfuryl resin binder, P (10) 244*f*.

Brown, L. M. See Mazdiyasni, K. S.

Brown, Norman L. See McPhee, A. D.

Brown, Pervis. Process for flotation treatment of glass beads, P (3) 59*d*.

Brown, Raymond E. See St. Clair, H. W.

Brown, R. L. See Parr, N. L.

Brown, Robert F., and Walker, A. B. Feasibility demonstration of electrostatic precipitation at 1700°F, (4) 92*c*.

Brown, Sherman D., Schroeder, T. F., and Conabee, E. E. Process and article comprising a layer of a ternary composition of HfO_2, ZrO_2, and TiO_2 bonded to an SiO_2 substrate, P (8) 202*d*.

Brown, S. V., McDonough, T. B., and Shaffer, J. W. Fulminating material application technique, P (9) 219*a*.

Brown, T. See Beretka, J.

Brown, T. W., Delin, M. A., and Scoville, R. D. Fuel burner safety control circuit, P (3) 70*i*.

Brown, Verne R. Thin-film semiconductor strain gages and method for making, P (3) 68*a*.

Brownridge, I. C. Li-Drifted Ge Detectors—Their Fabrication and Use, B (7) 183*c*.

Broyles, A. R. See Cimbalo, R. N.

Brubaker, B. D., and Waldman, N. Foamed clay process, P (10) 246*c*.

Bruce, H. W., and Sandvoss, W. E. Vacuum coating apparatus having means for positioning one of a plurality of members at a selected location between the substrate and the coating material source, P (8) 202*j*.

Bruce, J. A. G., Levy, H. M., and Oborn, P. Phosphate and phosphors prepared therefrom, P (4) 89*i*.

Brueckner, R. See Hums, D.; Nowak, A. E.

Brueckner, R., and Navarro, J. F. Stresses and ionic transport in float glass, (8) 191*i*.

Bruen, C. P. See Kelly, D. H.

Bruening, R. Model investigations on end-fired furnace (IV) influence of a doghouse and geometric variations of the superstructure, (7) 160*a*.

Brugger, K. Effect of thermal stress on refractive index in clad fibers, (8) 190*d*.

Bruhns, T. V. See Walters, J. P.

Brumberg, R. M., Trostanetskii, L. M., and Khlebnikov, A. L. Method of conveying free-flowing and lump materials upward and a vibratory elevator embodying said method, P (3) 69*c*.

Brunauer, S. See Odler, I.; Yudenfreund, M.

Brunauer, S., and Odler, I. Significance of surface area and porosity, (6) 130*d*.

Brunel, M. See Gondrand, M.

Brungraber, L. E., and Rudin, W. Protective refractory member, P (6) 135*e*.

Brusbek, D. K., and Starr, F. C., Jr. Abrasive compositions, P (7) 155*f*.

Bryant, F. J., and Hamid, S. A. Electron-induced traps in ZnS single crystals, (6) 147*i*.

Bryant, L. S., and Hickenbotham, H. D. Process of reclaiming offgrade TiO_2, P (2) 46*f*.

Bryce, C. Ferrite materials, P (8) 200*d*.

Bryson, R. O. Forehearth color concentrate, P (8) 192*i*.

Bryzgalov, A. N., Chernyi, L. N., Kuznetsov, A. F., and Kleshchev, G. V. Possible mechanism for formation of a growth pyramid on the pinacoid of synthetic quartz crystals, (8) 210*d*.

Bube, R. H. See Huggins, R. A.

Buccilli, P. R. See Spacil, H. S.

Buchanan, D. N. E. See Robbins, M.

Buchanan, R. A. See Alves, R. V.; Sobon, L. E.

Bucher, E. W. Glass laminating procedure apparatus, P (7) 161*j*.

Buchmayer, P. Use of palletizers for packing containers. Requirements and technical development, (8) 192*d*.

Buck, D. C. Ferrite wave guide phase shifter exhibiting negative phase shift, P (10) 250*c*.

Buck, D. C., and Schellenberg, J. M. Temp.-independent YIG filter, P (6) 140*a*.

Buck, R. H. Glazing of vacuum-evaporated Au-Cr films with a Pb-containing glass at 775°C, (9) 217*i*.

Buck, R. H., Jr., and Zbikowski, T. Mold pattern, P (10) 248*c*.

Buck, R. W. Composition for metalizing ceramic, P (8) 189*b*.

Bucke, D. P., Jr., and Mankin, C. J. Clay-mineral diagenesis within interlaminated shales and sandstones, (8) 208*d*.

Buckley, F. See Black, J. C.

Buckley, J. D. Advanced Materials—Composites and Carbon, B (7) 182*g*.

Buckner, D. A., and Wilcox, P. D. Effects of calcining on sintering of Pb zirconate-titanate ceramics, (4) 86*g*.

Budan, G. See Hartmann, H.

Budd, S. M. Mfg. glass containers, P (8) 193*g*.

Budin, J. P., and Raffy, J. Heating furnace, P (3) 70*a*.

Budnikov, P. P., Baranov, A. T., Volkov, O. S., Vorob'ev, A. A., and Garashin, V. R. Interaction of Al-containing clinker minerals with siliceous and carbonate microaggregates during autoclaving, (8) 187*c*.

Budnikov, P. P., Insartseva, S. A., Lepeshova, V. I., Sokhatskaya, G. A., and Shubin, V. I. Microstructure of porous periclase-spinelide refractories, (7) 163*g*.

Budnikov, P. P., Kharitonov, F. Ya., Medvedovskaya, E. I., Kerbe, F. G., and Shalchin, V. S. Sintering and recrystallization during hot-pressing of high-purity MgO-Al_2O_3 spinel, (8) 210*c*.

Budnikov, P. P., Khigerovich, M. I., Merkin, A. P., Sakharov, G. P., and Matrosovich, A. N. Influence of high temps. on the kinetics of hydration and crystallization of hemihydrate gypsum, (7) 156*c*.

Budnikov, P. P., Khoroshavin, L. B., Perepelitsyn, V. A., Ust'yantsev, V. M., and Kosolapova, E. P. Structural-mineralogical changes in dunite during heating, (7) 181*e*.

Budnikov, P. P., Kostyukov, N. S., Antonova, N. P., Kolotil, I. I., Medvedovskaya, E. I., Naidenova, G. A., and Moroz, I. Kh. Effect of radioactive emissions on electrical porcelain, (9) 224*a*.

Budnikov, P. P., and Shishkov, N. V. Behavior of Ca chromite during heating, (9) 233*h*.

Budworth, D. W. Theoretical approach to the crawling of glazes, (1) 10*a*. Theory of pore closure during sintering, (1) 26*b*. See Banerjee, M.; Haroun, N. A.; Prendergast, I. D.; Smethurst, E.

Buehl, W. M. Method of fining glass, P (3) 59*d*.

Buehler, E. See Boyd, G. D.

Buehler, E., and Wernick, J. H. Growth of single crystals of the II-IV-V diamondlike compounds $ZnSiP_2$, $CdSiP_2$, $ZnGeP_2$, and $CdSnP_2$ and standard enthalpies of formation for $ZnSiP_2$ and $CdSiP_2$, (7) 177*j*.

Buell, H. W. Oversized abrasive-coated products, P (10) 241*f*.

Buessem, W. R., and Gruver, R. M. Computation of residual stresses in quenched Al_2O_3, (3) 72*g*.

Buettner, H. See Bol, J.

Buettner, R. Production lines for plate mfg., (11) 272*j*.

Buhrer, C. F. Ferrimagnetic Fe garnet having large Faraday effect, P (7) 168*h*.

Buhrer, E. Method and apparatus for dosing 2 types of molding sand into a molding box of a foundry mold, P (8) 196*d*.

Bulst, D. S. Investigations with the Leitz heating microscope type IIA-P in the field of ceramics, (1) 17*e*.

Bukhalova, G. A., Berezhnaya, V. T., and Okol'chishena, N. E. Properties of compounds of the type $M^{I}M^{II}F_3$, (1) 24*e*.

Bukhalova, G. A., and Sementsova, D. V. Reciprocal system of the fluorides and chlorides of K, Ca, and Ba, (5) 123*a*.

Bukhovets, V. G., Sazhin, V. S., Shor, O. I., and Kalita, Z. A. Solid phases forming in the system Na_2O-K_2O-Al_2O_3-SiO_2-H_2O, (10) 261*b*.

Bulavin, I. A., and Medvedovskaya, Z. I. Synthesis of Li aluminosilicates, (8) 211*b*.

Buldakov, A. A., Rozlovskii, A. A., Ignatova, T. S., and Nazarova, T. I. Corrosion resistance of refractories in Sb salt melts, (8) 195*a*.

Bulkin, B. J. See Beveridge, D. L.

Bull, M. R. Brick shortage in South Africa, (2) 35*e*.

Bullinger, H. B. Photoetching of metal oxide layers, P (2) 41*j*.

Bullis, W. M. (editor). Methods of measurement for semiconductor materials, process control, and devices, (1) 11*c*; (7) 167*i*; (9) 224*j*; (10) 249*f*.

Bullough, R. See Simmons, J. A.

Bulthuis, K., and Shannon, J. M. Temp.-compensated semiconductor resistor containing neutral inactive impurities, P (11) 275*j*.

Bump, T. R. See Huebotter, P. R.

Buntz, B. J. See Mills, L.

Burbank, R. D. See Cohen, E.

Burchard, W. G., and Buresch, F. E. Stability of cubic ZrO_2, (7) 180*h*.

Burda, J. C. See Blatchford, J. K.

Buresch, F. E. See Burchard, W. G.

Burfoot, J. C., and Slack, J. R. Growth and electrical properties of $BaTiO_3$ flash-evaporated thin films, (9) 224*d*.

Burgess, J. F., Neugebauer, C. A., and Joynson, R. E. Method of forming high-stability self-registered FETs, P (2) 41*e*.

Burgess, K. H. See Nicklin, T.

Burgess, L. E. Electrical resistance material and method of making, P (4) 87*d*.

Burggraaf, A. J. See Zijlstra, A. L.

Buri, A. See Marotta, A.

Buri, A., Marotta, A., and Orsini, P. G. Devitrification of melilitic glass studied by electron microscope, (10) 243*b*. Role of TiO_2 in the crystallization of glasses in the SiO_2-Al_2O_3-CaO-MgO system, (4) 80*j*.

Burikina, A. L. See Krasnov, A. N.

Burk, M. Recovery of Al_2O_3 from aluminosilicates, P (9) 233*b*.

Burk, M., Bowes, W. M., and Krieg, H. C., Jr. Al_2O_3 extraction from aluminosilicate ores and K_2SO_4 ores, P (7) 175*j*.

Burke, C. E. Q-switched frequency doubling laser, P (2) 42*e*.

Burke, O. W. Modified SiO_2 pigments and processes for producing, P (11) 279*h*.

Burke, T. J., Belle, J., and Clayton, J. C. Nuclear fuel comprising UO_2 in a porous ceramic oxide matrix, P (8) 203*e*.

Burke, W. J., and Pressley, R. J. Zeeman effect of Cr^{3+} fluorescence in $SrTiO_3$, (5) 125*j*.

Burkhardt, W. Continuous process for the production of high-density ThO_2, (9) 228*f*.

Burlando, G. A. See Brisi, C.

Burmeister, R. A., Jr. Method and means for producing semiconductor material, P (3) 66*a*.

Burn, I. Energy storage capacitor, P (5) 112*a*.

Burn, R. A. See Wieder, H.

Burnett, A. D. See Tchalenko, J. S.

Burnett, D. G., and Douglas, R. W. Nucleation and crystallization in the Na_2O-BaO-SiO_2 system, (3) 56*h*.

Burnett, P., and Heuer, A. H. Method of growing MgO whiskers, P (4) 84*d*.

Burnett, R. C. See Horsley, G. W.

Burns, G. Powder Raman spectra—application to displacive ferroelectrics, (2) 38*d*. See Scott, B. A.

Burns, G., Giess, E. A., and O'Kane, D. F. New ferroelectric materials and process of preparation, P (5) 113*d*.

Burns, J. Cathode-ray character-display tube, P (10) 249*h*. Diode array radiation-responsive device, P (8) 200*j*.

Burns, J. R. See Boleky, E. J.

Burns, J. R., and Scott, J. H. Epitaxial semiconductor device having adherent bonding pads, P (4) 87*g*.

Burns, S. J. Fracture surface energies from dynamical cleavage analysis, (10) 259*h*.

Burock, R., Swirsky, D. M., and Whitner, R. A. Methods of using inorganic resists, P (6) 139*g*.

Burovskii, N. I. See Khan, B. Kh.

Burroughs, J. E. See Campbell, W. B.

Burroughs, J. E., and Kator, W. G. Cement retarder determination, P (2) 31*e*.

Burrows, B. Principles of electrochemical energy conversion, (4) 86*f*.

Bursill, L. A. Electron microscope study of a

homologous series of shear structures based on MoO_3, (10) 259*e*.
Bursill, L. A., and Hyde, B. G. Aggregation of Wadsley defects in slightly reduced rutile, (6) 145*a*.
Burt, J. G. Accurate temp. control for laboratory furnaces using thermocouple modulation, (2) 44*e*.
Burte, A. S., and Nicholson, P. S. Influence of anisotropy and H_2O vapor on the solid-state reaction of CaO and β-quartz, (10) 259*c*.
Burtis, S. F. See Ryan, R. J.
Burton, W. G. See Barrow, R. F.
Burykina, A. L. See Evtushok, T. M.; Oshchipko, I. S.
Burykina, A. L., Evtushenko, O. V., and Evtushok, T. M. Diffusion welding and soldering of metal wire to graphite and graphitized viscose, (10) 249*a*.
Burykina, A. L., and Evtushok, T. M. Reaction of graphite and pyrolytic graphite with Ti and Zr nitrides, (3) 60*h*.
Busanovich, C. J. See Moore, R. M.
Bushy, T. S. Glass furnaces [with chamfered walls], P (11) 270*a*.
Busby, T. S., and Carter, M. Conversion of MgO to $MgSO_4$ in glass furnace regenerators, (3) 55*h*. Effect of firing temps. and composition on the creep properties of magnesite bricks, (1) 7*f*.
Busby, T. S., Cox, G. C., and Gillespie, B. E. Upward drilling—physicochemical aspects and the implications for furnace design, (2) (2) 33*f*.
Busch, R. E., Freeman, R. W., and Luedeman, R. T. High-temp. bimetal thermometer, P 70*b*.
Buschor, K. Apparatus for the electrostatic coating of objects with atomized solids particles, P (2) 43*i*.
Busdiecker, R. A., and Rapp, J. E. SiO_2-Al_2O_3-Li_2O glasses, glass-ceramics, and method, P (2) 35*c*.
Busdiecker, R. A., Rapp, J. E., and Babcock, C. L. Mirror blank core and method of making, P (8) 193*g*.
Bush, A. N. See Obidina, S. P.
Busse, O., and Klesper, H. Filter press, P (2) 44*b*. Filter press with cleaning apparatus, P (3) 69*f*.
Busse, R. See Kind, G.
Butcher, H. J., and Simpson, E. A. Platelet SiO_2, its production and uses, P (10) 257*a*.
Butkovic, P. See Mihalik, V.
Butler, C. T. See Sturm, B. J.
Butler, C. T., and Sturm, B. J. Method for the production of single crystals, P (4) 92*f*.
Butler, E. Dislocations in β-Si_3N_4, (6) 146*d*.
Butler, K. H. See Thomas, Martha J. B.
Butschko, G., Jr. See Weber, P. O.
Butt, Yu. M., Imashev, M. K., Ramankulov, M. R., Kynatov, P. B., and Surina, A. V. Hardening of cement with slag electrophosphorus production in early stage of hydration, (8) 186*f*.
Butt, Yu. M., Timashev, V. V., Bakshutov, V. S., Lukatskaya, L. A., and Ilyukhin, V. V. Structure of concrete hardened for many years, (8) 187*h*.
Button, D. D. Oxide resistor heating element, P (2) 41*i*.
Buykx, W. J. See Bannister, M. J.
Buzard, J. B., Coleman, K. W., and Zelenz, M. L. Method of making resistor, P (6) 138*j*.
Buzbee, B. L., and Dorr, F. W. Computing thermal conductivity from experimental data, (3) 69*h*.
Buzzanca, G. See Pizzini, S.
Buzzelli, E. S. Electrical energy storage device containing a B_4C electrode, P (1) 12*i*. Electrical energy storage device containing an SiC electrode, P (1) 12*i*.
Buzzi, U., Dufresne, J. P., and Farfaletti-Casali, F. Apparatus for charging and discharging fuel elements in a vertical-channel nuclear reactor, P (10) 253*i*.
Bye, G. C. See Aldcroft, D.
Bye, G. C., and Howard, C. R. Examination by N adsorption of the thermal decomposition of pure and SiO_2-doped goethite, (5) 120*d*. Synthesis of Ba hexaferrite from Fe oxide and $BaCO_3$ (I) general features of the reaction, (5) 124*a*.
Bykov, I. I. See Khan, B. Kh.
Bynum, S. A. Se-S photoconductive target, P (2) 42*h*.
Byrd, C. O., Jr. Interlocking tile structure, P (4) 84*c*.
Byrnes, P. A., Jr., and Lepselter, M. P. Method for etching thin-film materials by direct cathodic back sputtering, P (8) 201*f*.
Bystrova, V. I., Polyakova, N. L., and Mikhailova, G. A. Glaze for ceramic parts and articles, P (2) 38*c*.

Cable, Harold E., and Cable, Herbert E. Electrodes for welding and the like, P (6) 131*b*.
Cable, Herbert E. See Cable, Harold E.
Cable, M., and Martlew, D. Corrosion of SiO_2 by Na_2CO_3 and carbonate-rich melts, (7) 158*j*; correction, (11) 268*g*.
Cacheux, J. A., and Meuleman, J. Polygonal-shaped radiation detector employing plural prism-shaped semiconductor crystals, P (3) 66*i*.
Caddock, R. E. Resistor with heat-dissipating means, P (4) 86*b*.
Cafferata, G. W. Anhydrous Ca sulfate, P (7) 157*b*.
Caffrey, R. E. See Tung, S. K.
Cahen, O., Picquendar, J. E., and Pircher, G. System and method for positioning a wafer coated with photoresist and for controlling the displacements of the wafer in a scanning electron apparatus, P (6) 142*i*.
Caillet, M. See Pontonnier, L.; Touzain, P.
Caillet, M., Lagarde, Y., and Besson, J. Carburizing and nitriding of Mo, (6) 145*e*.
Caimann, V., and Winter, E. Practical application of a correction method for removal of interelement effects in X-ray fluorescence analysis of glasses, (8) 191*c*.
Cairns-Smith, A. G. See Baird, T.
Cais, M. See Gamble, F. R.
Calder, J. A., and Attaway, D. H. Preliminary studies of stable C isotopes in selected Kansas shales, (3) 71*f*.
Calderwood, F. W. See Manning, W. R.
Caldwell, D. L. See Mod, W. A.
Caldwell, J. F. See Herzog, A. H.
Calella, P. See Walsh, P. J.
Caley, R. H. Electrical conductivities and optical absorption spectra of W-V-phosphate glasses, (8) 190*d*. See Murthy, G. K.
Calfee, J. D. See Gothard, E. S.
Calhoun, B. A. See Giess, E. A.
Calkin, B. See Storms, E.
Callaerts, R. See Nagels, P.
Callahan, J. P., and Stark, R. A. Ceramic chip electrical components, P (3) 64*j*.
Callarotti, R. See Nava, R.
Calow, C. A., Bayer, P. D., and Porter, I. T. Solid state bonding of Ni, Cr, and Nichrome sheets to α-Al_2O_3, (2) 38*j*.
Calow, C. A., and Porter, I. T. Solid state bonding of Ni to Al_2O_3, (2) 38*i*.
Calvert, J. M. See Derry, D. J.
Calvet, R., and Prost, R. Cation migration into empty octahedral sites and surface properties of clays (montmorillonites), (5) 118*d*.
Calvo, M. L. See Robredo, J.
Calvo, R., Isaacson, R. A., and Sroubek, Z. Spin-lattice coeffs. for Gd^{3+} and Eu^{2+} in CaF_2 and for Gd^{3+} in CaO, (5) 124*d*.
Calza Bini, A., Ferrante, E., Nobili, A., Rotoloni, P. L., and Testa, G. Fuel microstructure variations as a consequence of the 1st irradiation period and of the ways of approach-to-power, (3) 68*d*.
Camahort, J. L., and Gomez, M. P. BN-coated B filaments, P (4) 84*g*.
Camenzind, H. R. See Nelson, C. E.
Camenzind, H. R., and Allison, D. F. Bulk resistor and integrated circuit using the same, P (3) 64*i*.
Cameron, J. See Mitchell, A.
Camp, H. E. See Bailey, A. C.
Campbell, A. E., Jr., and Jensen, A. O. Metalized and brazed ceramics, P (9) 226*b*.
Campbell, D., and Chamberland, R. O. Reed material for sealed contact application, P (9) 227*b*.
Campbell, H. See Shutt, T. C.
Campbell, J. E. Simulated leaded stained glass, P (7) 163*a*.
Campbell, J. H. Fluorescent light source with a plurality of sequentially energized electrodes, P (2) 54*b*.
Campbell, J. K. Emulsion and process for binding pigments to glass fabrics, P (4) 81*g*.
Campbell, J. O. See Baer, M.
Campbell, W. B. Apparatus for fluidizing materials, P (6) 141*h*.
Campbell, W. B., Burroughs, J. E., and Cochran, J. K. Surgically implantable prosthetic joint, P (5) 111*f*.
Campbell, W. B., and Cochran, J. K. Apparatus for contact angle measurements, (1) 17*f*.
Canale, P. See Millet, J.
Candela, G. A. See Blunt, R. F.
Canegallo, G., and Costa, U. Metallic film resistors, P (1) 12*j*.
Canfield, S. A. Apparatus for measuring tension in glass fiber mfg., P (7) 161*f*.
Canner, J. P., Yagnik, C. M., Gerson, R., and James, W. J. Moessbauer-effect studies of the phase transitions in antiferroelectric $PbZrO_3$ and ferroelectric $PbTi_{0.2}Zr_{0.8}O_3$, (7) 178*i*.
Canning, M. L., Dunn, R. S., and Jeansonne, G. E. Method of fabricating integrated circuit arrays, P (5) 113*e*.
Cannon, S. M. See Mahan, A. I.
Cannon, W. A. Method for producing a fluorocarbon coating on metals and ceramics and the product thereof, P (3) 54*f*.
Canonico, D. A., Cole, N. C., and Houck, C. W. Method for brazing graphite and other refractory materials, P (10) 248*a*.
Cantagrel, M., and Marchal, M. Strengthening of metals by refractory fibers, (11) 271*h*.
Capek, R. G., and Takahashi, F. T. Method of fabricating multilayer ceramic capacitors, P (11) 275*c*.
Capestan, M. See Vedrine, A.
Capio, C. See Levinstein, H. J.
Capita, E. R. Method and means of producing a large-diam. single-crystal rod from a polycrystal bar, P (1) 13*d*.
Caporaso, A. J. See Kolb, E. D.
Cappel, F. Method of producing dicalcium ferrite sinter, P (9) 222*a*.
Capps, W. See Kao, R.
Carbajal, B. G., III, Gosney, W. M., and Hall, L. H. Complementary IGFE devices, P (10) 250*b*.
Carcey, J. Die furnace, especially for the fabrication of sintered products, P (10) 256*e*.
Card, A. C., and Kao, K. C. Effects of proton radiation on capacitance/voltage characteristics of MOS capacitors, (4) 86*g*.
Carini, G. F. Using metal powders in continuous cleaning coatings, (6) 131*b*. See Davies, B.
Carithers, V. G. See Davis, J. E.
Carl, K. F. L., and Haerdtl, K. H. Ceramic bodies for electromechanical transducers, P (11) 274*d*.
Carls, E. L. See Jonke, A. A.
Carlson, D. E. See Goldstein, B.
Carlson, D. E., Hang, K. W., and Stockdale, G. F. Electrode "polarization" in alkali-containing glasses, (8) 190*h*.
Carlson, H. G. See Harrap, V.
Carlson, H. G., Fuller, C. R., and Brown, G. A. Method for increasing the stability of semiconductor devices, P (44) 88*j*.
Carlson, K. D., Kaiser, K., Moser, C., and Wahl, A. C. Electronic structure and low-lying triplet states of CaO, (6) 147*d*.
Carlson, O. N. See Alexander, D. G.
Carlson, T. E. Negatively charging piezoelectric power supply, P (3) 66*e*.
Carlson, W. H., and Ehrenreich, L. C. Reinforced C and graphite bodies, P (8) 197*b*.
Carlsson, B., and Rundqvist, S. Crystal structure of Nb_3As_8, (4) 95*h*.
Carman, J. N., and McKnight, H. G. Production of single-crystal sapphire by carefully controlled cooling from a melt of Al_2O_3, P (1) 10*f*.
Carnahan, R. B. See Youtsey, K. J.
Carnall, E., and Pearlman, D. Transparent Gd_2O_3 ceramics and phosphors, (10) 249*a*.
Carnes, J. E., and Duffy, M. T. Self-healing breakdown measurements of pyrolytic Al_2O_3 films on Si, (5) 112*c*.
Carnevale, A. See Peterson, G. E.
Carniglia, S. C. Discussion of "Hot-pressing and mechanical properties of Al_2O_3 with an Modispersed phase," (1) 21*h*. Reexamination of experimental strength-vs-grain-size data for ceramics, (6) 151*j*.
Carpenter, D. R., Manley, G. W., McDermott, P. S., and Riley, R. J. Method for epitaxially growing thin films, P (3) 65*f*.
Carpenter, J. A., Tenney, D. R., and Houska, C. R. Method for determining composition profiles and diffusion-generated substructure in small diffusion zones, (5) 116*h*.
Carpenter, J. H., Jr. Abrasive treating apparatus, P (4) 77*i*.
Carpenter, R. E. Preparation of glass-reinforced polyester sheets, P (1) 5*a*.
Carpenter, S. H. See James, D. R.
Carpy, A., and Galy, J. High-pressure synthesis and preliminary X-ray investigation of a new V fluoride bronze, $K_xVO_{3x}F_{3-3x}$ (x=0.25), (4) 96*j*.
Carr, D. D. Specialty sand resources of Ind., (3) 71*f*.
Carr, K. L. Stub-tuned circulator, P (10) 253*e*.
Carr, P. H. Mixing of noncollinear elastic surface waves on $LiNbO_3$, (7) 178*h*.
Carr, R. M., and Chih, Hwa. Complexes of halloysite with organic compounds, (9) 233*i*.
Carr-Brion, K. G., and Jenkinson, D. A. Method and apparatus for determining the mean size of given particles in a fluid, P (10) 256*a*.
Carrell, M. A., Goundry, P. C., Post, R. C., and McNeill, K. E. Apparatus for the formation of SiO_2 articles, P (2) 43*i*.
Carroll, D., and Starkey, H. C. Reactivity of clay minerals with acids and alkalis, (5) 123*j*.
Carroll, D. F. Scanning electron micrographs of plasma-arc-sprayed Al_2O_3, (1) 18*g*.
Carroll, D. F., Blumenthal, J. L., and Ogren, J. R. Controlled emittance coatings for Pt-group metals, P (2) 31*j*.
Carruth, W. L., and Negus, R. W. Method of forming a K ion sensitive glass electrode, P (2) 34*d*.
Carruthers, J. R. See Ballman, A. A.; Bridenbaugh, P. M.; Peterson, G. E.; Schempp, E.
Carruthers, T. G. See Wheat, T. A.
Carsky, J. Calculation of the properties of ternary systems on the basis of binary data, (7) 176*j*.
Carson, F. J. See Oelke, W. W.
Carson, J. B. See Evey, G. H.
Carter, G. See Nobes, M. J.
Carter, G., Colligon, J. S., and Nobes, M. J. Equilibrium topography of sputtered amorphous solids (II), (2) 47*e*.
Carter, G. C. See Bennett, L. H.
Carter, M. See Busby, T. S.
Carter, R. E. See Nadeau, J. S.
Carter, R. E., Rosolowski, J. H., and Nadeau, J. S. Temp. gradient-induced migration of gas-filled bubbles in KCl, (4) 99*f*.
Carter, R. G. See Adkinson, A. R.
Carter, V. J. Semiconductor assembly including aperture-mounted diaphragm-supported wafer, P (6) 140*a*.
Cartz, L. See Riedner, R. J.
Carver, B. G., and Crooks, R. Die-casting apparatus with ceramic shot duct liner, P (9) 222*d*.
Casale, M. E. A., Collier, O. N., and Iles, G. S. Resistor composition, P (5) 114*b*.
Case, W. E. See West, E. D.
Case, W. S., Jr. Production of divanadium carbide by solid-state reduction of V oxides, P (1) 9*b*.
Casella, R. C. See Cohen, M. I.
Caserta, R. T., and Rine, J. C. Method of mfg. a fiber-reinforced grinding wheel, P (2) 29*g*.

Casey, M., and Wilks, J. Experiments on the wear of diamond turning tools, (6) 127*e*. Friction of diamond sliding on diamond, (6) 127*f*.
Cash, J. H., Jr., and Cunningham, J. A. Rf sputtering method, P (10) 252*e*.
Caslavsky, J. L., Gazzara, C. P., and Middleton, R. M. Study of basal dislocations in sapphire, (10) 261*h*.
Cass, R. A. See Ray, J. D.; Steingiser, S.
Cass, R. A., and Steingiser, S. Heat treatment of graphite fibers, P (4) 84*a*.
Casselton, R. E. W., Penny, J., and Reynolds, M. J. Structural consequences of blackening in Y_2O_3-stabilized ZrO_2, (2) 49*j*.
Casselton, R. E. W., Thorp, J. S., and Wright, D. A. Electrical conduction and blackening in Y_2O_3-stabilized ZrO_2, (9) 235*a*.
Cassidy, D. J. Ceramic regenerator seals, P (6) 136*e*.
Castellucci, N. T. Method of making a [cellular glass] tower packing element, P (8) 193*d*.
Castellucci, N. T., and Krouskop, N. C. Process for burning a combustible liquid using cellular ceramic nodules, P (8) 198*h*.
Castles, G. R. See Ettre, K.
Castonguay, R. A., Hanley, B. C., Mallahan, F. J., and Wenckus, J. F. Pressure- and temp.-controlled crystal growing apparatus, P (5) 117*a*.
Castrucci, P. P., Grochowski, E. G., North, W. D., and Palfi, T. L. Common emitter transistor integrated circuit structure, P (6) 137*i*.
Cataldo, R. S. Low-voltage spark plugs, P (8) 201*b*.
Cathers, W. P. Glass turnover and packing device, P (10) 244*d*.
Catherwood, B. R. See Conley, R. F.
Cathey, L. Thermoelectric [PbTe] generator, P (10) 253*b*.
Cauge, T. P. See Kocsis, J.
Causey, D. R., and Lenzing, J. R. Method of producing single semiconductor crystals, P (2) 41*a*.
Cave, E. F. See Becke, H. W.
Caveney, R. J., Jenkins, S. E., and Zuidema, G. Thermal conduction across metal-diamond interfaces, (4) 77*g*.
Cavitt, R. L. See Miller, R. G.
Cebell, W. A., and Chilingarian, G. V. Some data on compressibility and density anomalies in halloysite, hectorite, and illite clays, (8) 210*f*.
Cech, R. E. Reduction-fusion process for the production of rare earth intermetallic compounds, P (3) 67*f*. See Becker, J. J.
Cecil, C. B., and Heald, M. T. Experimental investigation of the effects of grain coatings on quartz growth, (1) 22*f*.
Cecil, O. B. See Sivertsen, D. R.
Cecil, T. A., and Jacobs, D. A. Method for bleaching gray kaolin clay, P (3) 71*c*.
Celentano, V. D. Surface preparation on B filaments for adhesive applications, P (3) 61*f*.
Cement Association of Japan (Tokyo). Review of the 25th General Meeting of the Cement Association of Japan, B (11) 284*e*.
Cense, A. See Wensink, B. L.
Cerulli, N. F. See Pakutka, W. M.
Cesca, T., Pescarolo, B., and Monaldi, R. Process for the production of MgO, P (2) 46*d*.
Ceva, H. See Nava, R.
Cevales, G. Thermal evolution of the electrofused refractories of the Al_2O_3-ZrO_2-SiO_2 type, (4) 84*c*.
Chabot, R. See Aisenberg, S.
Chadderton, L. T. See Jain, S. C.
Chadwick, G. A. See Kirchner, H. O. K.
Chaklader, A. C. D. Preparing high-density MgO refractories, P (9) 222*c*. See Angers, R.; St-Jacques, R. G.
Chakrabarti, R. K. See Das, D.
Chakravarty, N. K., Thakur, R. L., and Thiagarajan, S. Glass-ceramics from MgO-Al_2O_3-SiO_2-TiO_2, (11) 268*g*.
Chakraverty, B. K. Heterogeneous nucleation on a substrate, (8) 199*j*.
Chakraverty, B. K., and Plenier, A. MIS structures with thermally reversible memory, P (10) 251*g*.
Chakravorty, D. See Subbarao, E. C.
Chakravorty, S. K. See Roy, S. B.
Chalmers, B. See Weins, M. J.
Chamberland, R. O. See Campbell, D.
Chambers, F. A. See Brody, S. B.
Chamness, E. Folding method for large slab constructions, (2) 30*f*.
Champetier, R. J., and Kan, Hung-Kuen A. Method of preparing high-purity ZrO_2, P (4) 94*j*.
Champion, C. E. See Marinenko, G.
Champion, J. A. Fiber reinforcement of materials, (4) 83*j*.
Chan, R. K., Murthi, K. S., and Harrison, D. Thermogravimetric analysis of Ontario limestones and dolomites (I) calcination, surface area, and porosity; (II) reactivity of SO_2 with calcined samples, (7) 181*e*.
Chan, T. C. Complementary semiconductor devices in monolithic integrated circuits, P (5) 112*h*.
Chandler, T. R. D. See Quinn, T. J.
Chandrasekhar, B. S. See Geiger, A. L.
Chang, Hung Chi, and Chu, Ting Li. Process for the thermal treatment of a semiconductor material having a volatile component, P (2) 42*d*.
Chang, Hung Chi, and Ostroski, J. W. Passivated surfaces and protective coatings for semiconductor devices and processes for producing, P (11) 275*h*.
Chang, J. J., Ho, I. T., Vogl, N. G., Jr., and Wu, B. P. F. Minimemory cell with epitaxial layer resistors and diode isolation, P (3) 66*j*.
Chang, J. J., and Vora, M. B. Method of forming shallow junction semiconductor devices, P (1) 13*e*. Process for forming semiconductor devices with polycrystalline diffusion pathways and devices formed thereby, P (3) 66*j*.
Chang, Kern K. N., and Prager, H. J. High-power semiconductor device assembly, P (6) 137*j*.
Chang, Luke L. Y. Subsolidus phase relations in aragonite-type carbonates (I) the system $CaCO_3$-$SrCO_3$-$BaCO_3$, (9) 238*j*.
Chang, Luke L. Y., and Brice, W. R. Subsolidus phase relations in aragonite-type carbonates (II) the systems $CaCO_3$-$SrCO_3$-$PbCO_3$ and $CaCO_3$-$BaCO_3$-$PbCO_3$, (9) 238*j*.
Chang, Nai-Chien. See Kisliuk, P.
Chang, R. H., and Wagner, J. B., Jr. Direct-current conductivity and Fe tracer diffusion in hematite at high temps., (5) 119*e*.
Chang, Te-Tse. See Ensign, T. C.
Chang, Tung Symon. See Amzallag, E.
Chang, Tung Symon, and Imbusch, G. F. Effect of domain structure on the fluorescence of Cr^{3+}-doped $SrTiO_3$, (7) 177*g*.
Chapman, A. T. See Gerdes, R. J.
Chapman, D. W. Ferroelectric/photoconductor memory element, P (10) 250*d*.
Chapman, D. W., and Mehta, R. R. Ferroelectric/photoconductor storage device with an interface layer, P (10) 250*d*.
Chapman, D. W., Michaelsen, J. D., and Stryker, F. J. Composition of ferroelectric matter, P (9) 225*a*.
Chapman, G. C., and Le Sueur, J. T. Apparatus and methods for melting glass compositions for glass laser rods, P (8) 192*h*.
Chapman, J. H. Clay processing, P (7) 175*a*.
Chapman, R. P., and Irving, B. F. Support means for ceramic shell molds, P (1) 9*f*.
Chapman, V. F. Conveyors, P (4) 83*h*.
Chaporova, I. N., Pivovarov, L. E., Ivensen, V. A., Eiduk, O. N., Sultanyan, T. A., Varaksina, A. V., Korotkova, R. F., and Chistyakova, V. A. Effects of plastic deformation on the structure of WC-Co alloys, (3) 60*h*.
Chappert, J., Frankel, R. B., Misetich, A. A., and Blum, N. A. Multiple charge states, hyperfine interactions, and relaxation processes of Fe in ^{57}Co-doped MgO, (5) 122*g*.
Chapron, C. Epitaxial transistor with limited area buried layer and lifetime killers, P (1) 12*b*. Semiconductor device having an integrated pulse gate circuit and method of mfg. the device, P (7) 170*a*.
Charles, R. J., Dondalski, W. J., and Mitoff, S. P. Sintered β-Al_2O_3 bodies and method, P (1) 10*g*.
Charles, R. J., Mitoff, S. P., and Morris, W. G. Method of making sintered β-Al_2O_3 bodies, P (1) 10*e*. Method of producing β-Al_2O_3 electrolytes, P (3) 66*d*.
Charlesworth, D. Group of vessels from the commandant's house, Housesteads, (11) 266*a*.
Charlu, T. V., Chaudhuri, A. K., and Margrave, J. L. Thermodynamic properties of inorganic substances (VIII) high temp. enthalpy increments for some rare-earth trifluorides, (8) 211*c*.
Charnell, J. F. Gel growth of large crystals of NaA and NaX zeolites, (7) 177*g*.
Charpentier, A. J., and Deverell, H. E. Ceramic die assembly, P (2) 38*b*.
Charpentier, M. Method and apparatus for the production of glass or other fibers from thermoplastic materials, P (6) 133*j*.
Chary, M. N. See Samdani, S. G.
Chasanov, M. G. See Fredrickson, D. R.
Chase, A. B. See Osmer, J. A.
Chase, E. W., and Robinson, H. J. SnO_2 etching method, P (9) 228*b*.
Chase, R. B. Method of repairing a ceramic-lined nozzle, P (7) 158*a*. Method of repairing a damaged vitreous coated nozzle, P (2) 31*j*.
Chatelain, A., and Weeks, R. A. EPR study of ordered Mn^{2+} in Mg_2SiO_4, (6) 147*a*.
Chatelain, R., and Bouis, H. Apparatus for cutting glass. P (2) 33*a*.
Chatova, V. L. See Morozov, I. S.
Chatterjee, M. K. See Chaudhuri, S. P.
Chatterji, S. Formation of the microstructure of cement pastes and its relation with various physical properties, (2) 31*b*. See Wheeler, J.
Chau, Cheuk-Kin. See Rosenbaum, R. L.
Chaudhri, G. See Brown, D.
Chaudhuri, A. K. See Charlu, T. V.
Chaudhuri, S. See Kuenkele, R.
Chaudhuri, S. P., and Chatterjee, M. K. Kinetic study of spalling of aluminosilicate refractories, (11) 271*j*.
Chaus, I. S., Kompanichenko, N. M., and Sheka, I. A. Study of interaction in the system In_2S_3-NiS by the coprecipitation method, (2) 50*d*.
Chaussonnet, P. E. See Van Impe, J.
Chay, Dong M., and Iler, R. K. Metal/carbide-oxide composite, P (10) 247*j*.
Cheary, W. G. Printed circuits and method of making, P (10) 252*j*.
Cheavens, T. H. See Warthen, J. L.
Chebukov, M. F., and Grakhova, S. K. Effect of CaF_2 on the phase composition of siliceous clinkers, (8) 186*i*.
Chebukov, M. F., P'yachev, V. A., and Cherepanova, V. N. Influence of SiO_2 on the firing and properties of cement, (8) 187*b*.
Chedaille, J., and Koopmans, G. Multifuel burner, P (9) 232*d*.
Chekhovskoi, V. Ya. See Petrov, V. A.
Chelidze, M. G. Dynamic model of the vertical drawing process for sheet glass, (8) 190*a*.
Chemodanov, D. I., Chikovani, N. S., Yanina, R. I., and Miller, I. N. Binding properties of systems $Ca(OH)_2$-(Ge,Sn,Pb,Ti,Zr,Mn)O_2-H_2O under autoclave treatment conditions, (9) 233*i*.
Chemtob, E. M. Process for the production of K sulfate and borax, P (8) 207*f*.
Chemtob, E. M., and White, W. R. Reagent flotation of borax from salt mixtures at low temps., P (4) 95*b*.
Chen, A. C. M., and Lommel, J. M. Thin-film Ni temp. sensor and method of forming, P (8) 202*h*.
Chen, C. P., and Weisz, R. S. Strength of ferrite memory cores, (7) 168*d*.
Chen, J. H., and McDonough, M. S. Dielectric relaxation in alkaline-earth fluoride crystals, (5) 119*j*.
Chen, Mao-Chieh, and Artman, J. O. EPR of Co-doped $PbWO_4$, (6) 147*j*.
Chen, Nai Yuen. Reactivation of deactivated zeolite catalysts, P (11) 280*b*.
Chen, Wei-Kong, Peterson, N. L., and Reeves, W. T. Isotope effect for cation self-diffusion in CoO crystals, (6) 149*c*.
Chen, Yok, Kolopus, J. L., and Sibley, W. A. Luminescence of the F^+ center in MgO, (6) 150*b*.
Chen, Yok, Williams, R. T., and Sibley, W. A. Defect cluster centers in MgO, (5) 119*d*.
Cheney, G. T., and King, E. F. Shift register stage using IGFETs, P (9) 227*i*.
Cheng, Jack C. See Kemp, J. C.
Chenot, C. F. Luminescent Mn-activated Sr Ba chloroaluminate phosphor composition—process and lamp, P (6) 138*e*. Eu–Sm-coactivated Sr fluoroborate phosphor, P (8) 200*c*. See Taubner, F. R.
Chepiga, M. V. See Kuz'ma, Yu. B.
Cherel, G. H. Apparatus and method for processing spent nuclear fuel elements, P (10) 253*h*.
Cherenkova, G. I. See Zaitsev, B. E.
Cherep, I. L. See Kulygin, I. P.
Cherepanova, V. N. See Chebukov, M. F.
Cherin, P., Lind, E. L., and Davis, E. A. Preparation and crystallography of CdZn sulfide solid solutions, (2) 49*a*.
Cherneva, E. F., and Florinskaya, V. A. Standard ir spectra of the simplest silicates, (9) 218*f*.
Chernov, A. A. Growth of solid solutions—the statistics of trial and error, (8) 209*e*.
Chernov, R. V., Delimarskii, Yu. K., and Savchenko, L. T. Kinetic and thermodynamic analyses of interactions of TiO_2 with hydrosulfates of alkali metals, (2) 48*j*.
Chernyavskaya, N. I. See Beloivan, A. F.
Chernyavskii, K. S., and Golovashkina, N. V. Emission electron microscopy in high temp. investigations of metals and alloys, (10) 255*d*.
Chernyavskii, V. L. See Mchedlov-Petrosyan, O. P.
Chernyi, L. N. See Bryzgalov, A. N.
Chernyshev, A. N. See Shemyakin, V. K.
Cherpak, A. G. See Voronovich, L. P.
Cheshire, A. G. Liquid [fuel] atomizing devices, P (7) 174*e*.
Cheshire, A. G., and Place, H. Liquid [fuel] atomizing devices, P (11) 279*b*.
Chesnut, W. C. Hand tool for sharpening cutting edges, P (3) 53*f*.
Chew, H. L. See Zimmer, W. F., Jr.
Chi, Dongsuk. See Lee, Hanju.
Chiao, T. T., and Moore, R. L. Strength of S-glass fiber, (11) 269*j*.
Chiba, Minoru. Semiconductive ceramic capacitor, P (9) 227*c*.
Chiba, Toshinobu. See Noguchi, Masayasu.
Chiba, Toshinobu, Noguchi, M., Mitsuhashi, T., Tanaka, T., and Tsuda, N. Correlation of lifetimes of positrons in oxides, (4) 95*d*.
Chicotka, R. J. Method of polishing GaP, P (10) 251*j*. See Blum, S. E.
Chigbo, G. O. See Aldcroft, D.
Chigrai, I. D. See Likhoradov, A. P.
Chih, Hwa. See Carr, R. M.
Chikalla, T. D., McNeilly, C. E., and Roberts, F. P. Polymorphic modifications of Pm_2O_3, (9) 228*i*.
Chikanov, N. D. Reactions of the pentachlorides of Ta and Nb with the chlorides of bivalent metals, (5) 123*i*.
Chikawa, Jun-ichi, Fujimoto, I., and Asaeda, Y. X-ray topography with chromatic-aberration correction, (7) 173*j*.
Chikovani, N. S. See Chemodanov, D. I.
Chiku, Takewo. Heating a sintered Al_2O_3 article in an atm containing Na or K ions, P (7) 166*b*.
Child, F. S. Impact of flat glass imports—turmoil in the flat glass industry, (3) 56*b*. Safety glazing and the state legislatures, (5) 106*j*.
Childs, E. E., Jr. Microwave method for tem-

pering tar-bonded refractory bricks, P (10) 248*c*.
Childs, P. E., Laub, L. W., and Wagner, J. B., Jr. Chemical diffusion in nonstoichiometric compounds, (9) 233*e*.
Chilingar, G. V. See Sawabini, C. T.
Chilingarian, G. V. See Cebell, W. A.
Chilton, G. E. Temp.-measuring apparatus, P (1) 18*i*. See Simonyan, K.
Chilton, G. E., and Simonyan, K. Multijunction photodiode detector, P (3) 66*d*.
Chilton, H. T. J. Production of SiO_2 sols by electrolysis, P (7) 176*b*.
Chilton, H. T. J., Everest, D. A., and Sayce, I. G. Process for the production of finely divided SiO_2, P (5) 118*a*.
Chin, J., Luby, C. S., and Mills, R. G. Nuclear reactor fuel coated particles, P (6) 141*a*.
Chino, Shigeo. See Siire, Toyokazu.
Chiola, V., Kamin, G. J., and Vanderpool, C. D. Process for preparing rare-earth normal tungstates, P (7) 170*f*.
Chiola, V., and Vanderpool, C. D. Process for mfg. anhydrous refractory metal iodides, P (3) 67*b*.
Chiron, B., and Duffau, L. Tunable microminiaturized microwave filters, P (10) 253*c*.
Chisholm, D. S. Conveying and forming method and apparatus for fibers having bulbous ends, P (11) 270*e*.
Chisholm, R. S. Electrolysis of brine using coated C anodes, P (6) 135*f*.
Chistov, Yu. D. See Volzhenskii, A. V.
Chistyakova, A. A., Sivkina, V. A., Khashkovskaya, A. P., and Sadkov, V. I. Solidification products based on an aluminophosphate binder and corundum, (9) 238*c*.
Chistyakova, A. A., Sivkina, V. A., Sadkov, V. I., and Khashkovskaya, A. P. Effect of corundum on phase composition of products of heating in the system Al_2O_3-P_2O_5-H_2O, (9) 234*g*.
Chistyakova, A. A., Sivkina, V. A., Sadkov, V. I., Khashkovskaya, A. P., and Povysheva, L. G. Aluminophosphate binder, (8) 194*h*.
Chistyakova, V. A. See Chaporova, I. N.
Chiu, Te-Long. Planar junction-gate FETs, P (3) 66*i*.
Chivers, M. A. See Groom, B.
Chizhik, S. P. See Lidorenko, N. S.
Chizhikov, D. M., Nikiforov, L. V., and Lainer, Yu. A. Synthesis of sulfides of Fe and Ge, (8) 211*d*.
Chizinsky, G. Method of making an FET, P (10) 251*f*.
Cho, A. Y., and Hayashi, I. *Pn* junction formation during molecular-beam epitaxy of Ge-doped GaAs, (6) 151*a*.
Choi, Sangheul. See Kondo, Renichi.
Choi, Sangheul, and Kondo, R. Dissolution of clinker minerals in the clinker melt, (3) 53*j*.
Choisnet, J., Deschanvres, A., and Raveau, B. New "benitoite" type germanates and silicates, (10) 260*c*.
Chopra, K. L. See Bahl, S. K.
Choshi, Isamu, and Kato, E. Zn crystalline glaze, (3) 61*i*.
Chou, Tsu-Wei. Elastic behavior of disclinations in nonhomogeneous media, (7) 177*a*.
Chou, Y. T., and Sha, G. T. <110> dislocation in cubic crystals, (5) 119*h*.
Chow, Lin. See Lin, Chinyueh.
Choyke, W. J. See Patrick, L.
Choyke, W. J., and Patrick, L. High absorption edges in cubic SiC, (6) 148*c*.
Chrenko, R. M. See Slack, G. A.
Chretien, A. See de Kozak, A.
Christensen, A. O. MOSFET decoder topology, P (7) 163*g*.
Christensen, J. J., Hill, J. O., and Izatt, R. M. Ion binding by synthetic macrocyclic compounds, (4) 97*j*.
Christensen, L. L., Larsen, H. L., and Jones, J. H. Testing and selection of coating systems for production operations, (1) 18*b*.
Christensen, O. Method for depositing thin films on thin elongated electrically insulating substrates, P (10) 251*a*.
Christensen, R. W., Smith, Everett C., and Tibol, G. Method of making junction-type semiconductor devices, P (4) 89*b*.
Christenson, R. M., and Le Bras, L. R. Control of H_2O-soluble acids in an electrodeposition bath, P (8) 192*f*. Controlling solids in electrodepositable compositions, P (8) 192*f*. Ultrafiltration of electrodepositable compositions, P (8) 194*d*.
Christenson, R. M., and Zwack, R. R. Double ion exchange of an ultrafiltrate derived from an electrodeposition bath, P (8) 193*e*. Ion exchange of an ultrafiltrate derived from an electrodeposition bath, P (8) 193*e*. Pretreating electrodepositable compositions, P (8) 193*i*.
Christian, P. A., and Berka, L. H. Polywater —a lesson and opportunity in science, (4) 98*g*.
Christian, W. E. Coated abrasive cones, P (9) 213*g*.
Christie, J. H., and Humphrey, J. R. Solid-state cell with a Te tetraiodide cathode, P (6) 140*f*.
Christopher, H. A. Method of forming sealed container for elemental Na, P (8) 193*d*.
Christopher, J. E. See Morris, R. C.
Chromecek, R., Meinhold, L., Otoupalova, J., and Kruntorad, V. Method of printing on glassware and earthenware articles, P (4) 82*e*.
Chu, Richard C. See Seely, J. H.
Chu, Ting Li. Pyrolytic coatings of Mo sulfide by plasma jet technique, P (8) 197*a*. See Chang, H. C.
Chu, Ting Li, and Ray, R. L. Resistivity measurements on Ge crystals by the spreading resistance technique, (3) 63*f*.
Chu, Ting Li, Gruber, Gilbert A., and Szedon, J. R. Method of vapor depositing a layer of Si_3N_4 on an Si base, P (7) 169*e*.
Chu, Yuan Hou, and Mieher, R. L. ENDOR study of a <111> interstitial defect in LiF, (6) 147*e*.
Chua, H. T. See Vadacz, L. L.
Chubb, W. See Hilbert, R. F.
Chubb, W., Keller, D. L., Wullaert, R. A., and Storhok, V. W. Fuel subassembly for a nuclear reactor, P (3) 68*i*. Nonswelling U_3N_4 fuel, P (8) 203*e*.
Chufarov, G. I. See Shchepetkin, A. A.
Chuiko, A. A. See Tertykh, V. A.
Chukhlantsev, V. G. See Galkin, Yu. M.; Polezhaev, Yu. M.
Chung, Il-Yong. See Muguruma, Hiroshi.
Church, J. M. See Green, P. S.
Ciach, T. D., Gillott, J. E., Swenson, E. G., and Sereda, P. J. Microstructure of Ca silicate hydrates, (4) 79*b*.
Ciach, T. D., and Swenson, E. G. Morphology and microstructure of hydrating portland cement and its constituents (I) changes in hydration of $3CaO$-Al_2O_3 alone and in the presence of triethanolamine or Ca lignosulfonate; (II) changes in hydration of Ca silicates alone and in the presence of triethanolamine and Ca lignosulfonate, both with and without gypsum; (III) changes in the hydration of a mixture of C_3S, C_3A, and gypsum with and without triethanolamine and Ca lignosulfonate present; (IV) changes in hydration of a C_3S, C_2S, C_3A, C_4AF, and gypsum paste with and without the admixtures triethanolamine and Ca lignosulfonate; (V) changes in hydration of portland cement with and without the presence of triethanolamine and Ca lignosulfonate, (5) 103*g*.
Cimbalo, R. N., and Broyles, A. R. Regeneration of Pt group metal-α-Al_2O_3 catalyst, P (11) 280*b*.
Cimino, A., Cordischi, D., Guarino, G., and Micheli, A. ESR study of occurrence of Ni^{3+} ions in MgO-NiO-Li_2O solid solutions, (1) 22*c*.
Cioni, M. Feed devices for glass vials, bottles, and like containers, P (7) 161*d*.
Cipau, R. See Becherescu, D.
Ciszek, T. F. Method of growing semiconductor rods from a pedestal, P (4) 88*i*.
Clack, J. See Nicklin, T.
Claesaens, F. D., and Hein, T. F. Mold-transferring system for ceramic articles, P (6) 141*g*.
Claffy, E. W. See Ginther, R. J.
Claiborne, L. T. Apparatus for converting bulk waves to Rayleigh waves at microwave frequencies, P (7) 168*h*.
Clark, C. D., and Walker, J. Optical measurements on the GR1 center in diamond, (4) 98*a*.
Clark, C. T. See Gartner, W. J.
Clark, E., and Summerling, R. A. Friction materials [asbestos], P (8) 196*j*.
Clark, G. D. See Strack, H. A.
Clark, G. W. See Finch, C. B.; Gerdes, R. J.
Clark, K. G. Properties and processes for photoresists in semiconductor manufacture (I-II), (3) 63*d*.
Clark, L., and Elgan, D. L. Process for fabricating small geometry high frequency semiconductor device, P (10) 252*a*.
Clark, Roger. Ceramic fiber blanket as a furnace hot-face lining, (8) 194*j*.
Clark, Robert J. See Isaksen, R. A.
Clark, T. J., and Brown, Howard W. Method of preparing curved pyrolytic graphite bodies having increased thickness to radius ratios, P (6) 135*b*. Pyrolytic graphite, P (10) 248*a*.
Clarke, C. M. See Ram, M. J.
Clarke, O. M., Jr. Clays of southwestern Ala., (3) 71*c*.
Clark-Monks, C. See Ellis, B.
Classen, F. Method for the production of a float glass strip having a roughened upper surface, P (10) 245*e*. See Bourggraff, R.
Classen, F., Kaes, K., Labrot, G., and Pape, H. Float glass apparatus with adjustable cooling means, P (6) 132*f*.
Claverie, J., Dexpert, H., Portier, J., Pauthenet, R., and Hagenmuller, P. Preparation and physical properties of the spinel-type $Zn_xFe_{3-x}O_{4-z}F_z$, (2) 49*b*.
Clawson, C. D., and Riley, J. F. Monolithic piezoelectric resonator for use as filter or transformer, P (2) 41*f*.
Clayton, C. G., and Wladyslaw, B. Method of X-ray fluorescence analysis of materials containing an interfering element, P (3) 70*e*.
Clayton, J. C. See Burke, T. J.
Clayton, R. N. See O'Neil, J. R.
Clayton, T. G. Mfg. of bricks, P (5) 104*h*.
Cleaver, B., and Smedley, S. I. Pressure dependence of electrical conductivity for fused mercuric halides, (5) 122*g*.
Cleaver, D. See Arkless, K.
Cleek, G. W. See Waxler, R. M.
Clemens, K. H. Determination of fracture radius of sheet steel enamels using a logarithmic spiral, (11) 267*f*.
Clement, C., Neel, E. E., and Anselme, A. P. Mordenite-containing hydrocracking catalyst, P (3) 71*e*.
Clerc, D., and Zahn, D. Semiconductor avalanche diode, P (8) 202*g*.
Clevenger, L. H. See Sloan, B. J., Jr.
Clifton, J. R. Thermal analysis of CaS dihydrate and supposed α and β forms of CaS hemihydrate from 25° to 500°C, (7) 181*c*.
Clifton, J. R., and Mathey, R. G. Interrelations between cement and concrete properties (VI), (1) 2*g*.
Clingman, W. H., Jr. See Stroup, R. F.
Clinton, S. D. See Haas, P. A.
Clouet, A. See Combe, C.
Coaton, J. R., and Rees, J. M. H-halogen filament lamp with an H getter flag, P (6) 133*b*.
Coble, R. L. See Yen, C. F.
Coburn, J. W., and Lee, K. Sputter deposition of EuO thin films, (7) 168*b*.
Cocca, F. J. Method and apparatus for detecting surface ions on Si diodes and transistors, P (9) 226*d*.
Cochran, F. L. Trapping of ^{131}I during remote metallographic operations, (1) 16*b*.
Cochran, J. K. See Campbell, W. B.
Cochran, W. W. See Cowley, R. A.
Cockayne, B., and Gasson, D. B. Machining of oxides using gas lasers, (2) 44*j*.
Cockayne, B., and Jones, D. W. (editors). Modern Oxide Materials—Preparation, Properties, and Device Applications, B (9) 240*h*.
Cocker, A. J. Removing dissolved O from molten Sn in a glass ribbon float bath, P (3) 59*f*.
Cocks, F. H., and Stormont, R. W. Rutile substructures in Ba Mg titanate, (10) 260*g*.
Cocks, T. G. Metal casting process, P (9) 222*j*.
Coes, L., Jr. Abrasives (Vol. 1 of Applied Mineralogy series), B (6) 153*c*.
Coffin, L. B. See Lawrence, W. G.
Coghlan, W. A., Menezes, R. A., and Nix, W. D. High-temp. creep in LiF single crystals, (6) 148*c*.
Cohen, C. I. Leaching glass films for filter making, P (2) 34*a*. See McKinnis, C. L.
Cohen, E., Risberg, L. A., Nordland, W. A., Burbank, R. D., Sherwood, R. C., and Van Uitert, L. G. Structural phase transitions in $PrAlO_3$, (6) 152*b*.
Cohen, H. M. See Sioui, R. H.
Cohen, J. B. See Hayakawa, M.
Cohen, M. H. Electronic structure and transport in covalent amorphous semiconducting alloys, (6) 147*d*. See Turnbull, D.
Cohen, M. I., Casella, R. C., Blunt, R. F., and Forman, R. A. Lattice absorption in Sr titanate, (6) 149*b*.
Cohen, M. J. High-temp. method and apparatus for analyzing gaseous samples, P (3) 70*b*.
Cohen, R. L. See Eibschuetz, M.
Cohen-Alloro, R., and Grassaud, J. Device for gravimetric separation of granular or pulverulent materials, P (8) 207*e*.
Coker, J. E., and Galli, G. Composites of IIB-VIA binary film compounds on IIA-VIIA binary compound substrate crystals and process therefor, P (8) 200*g*. See Galli, G.
Colclough, W. J. See Wells, H.
Coldrey, J. M. See Purton, M. J.
Cole, E. See Parke, S.
Cole, G. R. Brazable compositions, P (2) 33*f*.
Cole, J. F. Health aspects of ILZRO's Pb in glazes research, (1) 10*c*. See Barrer, R. M.
Cole, J. M., and Sinclair, W. Method of fabricating a magnetic memory matrix, P (10) 251*c*.
Cole, N. C. See Canonico, D. A.
Cole, S. S., Jr. Metalizing material, P (2) 40*j*. Sintering of Ag-Pd in the presence of a reactive glass, (7) 160*e*.
Cole, W. F., Lancucki, C. J., and Powell, D. A. Characterization of ceramic clays, (6) 141*h*.
Coleman, D. J., Jr., and Sze, S. M. Schottky barrier transit time negative resistance diode circuits, P (10) 252*f*.
Coleman, D. S. See Spencer, D. R. F.
Coleman, J. C. Rotary molding method of press shaping glass, P (2) 35*b*.
Coleman, K. W. See Buzard, J. B.
Coleman, M. Ladle lining, P (1) 9*a*.
Coleman, M. G., and Huffman, T. R. Directed emission light emitting diode, P (10) 250*h*.
Coleman, R. G. See Loney, R. A.
Coleman, R. G., and Keith, T. E. Chemical study of serpentinization—Burro Mountain, California, (1) 19*j*.
Coleman, R. V. See Morris, R. C.
Coless, T. L. See Oberly, J. E.
Collard, E. Heyday of the Scottish potters, (4) 77*j*.
Collard, J. R. Support for electrical components and method of making, P (10) 253*f*.
Collard, J. R., Narayan, S. Y., and Paczkowski, J. P. Semiconductor diode, P (9) 227*f*.
Collard, R., and Thyoux, G. Glass-forming apparatus with article support, P (2) 34*e*.
Collepardi, M., and Marchese, B. Morphology and surface properties of hydrated tricalcium silicate pastes, (5) 103*j*.
Collepardi, M., Marcialis, A., and Turriziani, R. Effects of temp. and humidity on Ca monosulfoaluminate hydrates, (1) 2*f*. Paste hydration of $4CaO$-$3Al_2O_3$-SO_3 in presence of $CaSO_4$, Ca_2SiO_5, and Ca_2SiO_4, (7) 157*d*. Penetration of chloride ions into cement pastes and concretes, (11) 266*i*.
Collet, M. G. Method of applying a layer of Si_3N_4, P (3) 65*d*.

Colley, C. R. Adsorbent selection for gas drying, (9) 232*b*.
Collier, C. W. Process for mfg. Al_2O_3 hydrate, P (9) 233*a*.
Collier, O. N. See Casale, M. E. A.
Colligon, J. S. See Carter, G.; Nobes, M. J.
Collin, P. See Guth, J. L.
Collins, A. T. See Williams, A. W. S.
Collins, A. T., Lightowlers, E. C., and Dean, P. J. Role of phonons in the oscillatory photoconductivity spectrum of semiconducting diamond, (5) 123*f*.
Collins, A. T., Lightowlers, E. C., and Williams, A. W. S. Formation of electrical contacts on insulating and semiconducting diamonds, (4) 86*h*.
Collins, A. T., and Williams, A. W. S. Nature of the acceptor center in semiconducting diamond, (4) 86*e*.
Collins, F. M. Switching by thermal avalanche in semiconducting glass films, (6) 132*j*.
Collins, G. See Alderdice, D. S.
Collins, N. E., and Halt, I. E. Ohmic contact for group III-V *p*-type semiconductors, P (11) 275*g*.
Collins, N. E., Kerber, E. W., and Neville, R. R. Solid state lamp assembly, P (10) 253*c*.
Collins, R. H., and Deverse, F. T. Plasticizer additive to photoresist for the reduction of pinholes, P (2) 42*b*.
Collins, R. H., Grochowski, E. G., and North, W. D. Si process technology for monolithic memory, (9) 224*e*.
Collins, R. H., and Logan, J. S. Prevention of inversion of *p*-type semiconductor material during rf sputtering of quartz, P (2) 42*c*.
Collins, S. A., Jr. See Toth, L. S.
Collins, T., and Brown, A. E. Low-loss Li ferrites for microwave latching applications, (5) 111*h*.
Collins, T. C. See Reynolds, D. C.
Collins, T. W. Ruth Duckworth, (2) 30*c*.
Colliva, D. Apparatus for mfg. sheets of asbestos cement or the like at a high hourly production rate, P (2) 37*c*.
Collongues, R. Nonstoichiometry, B (1) 28*b*. See Le Cars, Y.
Colman, D. See Broce, M. E.
Colombo, U., Hafford, B. C., and Uglietti, G. Process for producing pigment-grade TiO_2, P (8) 207*c*.
Colombo, U., Scacciati, G., Sironi, G., and Vaschetti, A. Continuous process for obtaining high-grade ZnO from Zn-containing minerals, P (6) 143*j*.
Colson, F. A. Barbara's birds, (2) 30*a*.
Colson, W. B., Niedermiller, H. C., and Deradoorian, B. Method for forming a honeycomb structure, P (10) 245*a*.
Coltrinari, E. L., and Kindig, J. K. Two-stage countercurrent leaching process for the recovery of phosphate, Y, and rare-earth values, P (6) 144*g*.
Colvert, J. H. See O'Keefe, W. H.
Colville, A. A., and Geller, S. Crystal structure of brownmillerite, Ca_2FeAlO_5, (7) 176*g*.
Combe, C., Clouet, A., Marchal, M., Villard, M., and Grenier, P. Apparatus for forming SiC filaments, P (8) 196*f*.
Combe, E. C., and Smith, D. C. Autoclave dehydration of gypsum, (5) 102*f*.
Comella-Riera, M. Grinding disk, P (2) 29*f*.
Comense, M. See Bresciani, L.
Comizzoli, R. B., and Warter, P. J., Jr. Hole-trap depletion-layer formation in CdS, (5) 121*b*.
Commons, C. H., Jr. Process of making thermal insulation, P (4) 84*i*.
Compton, W. D. See Anderson, G. W.
Comstock, R. L., and Moore, E. B. Process for making continuous magnetite films, P (3) 67*b*.
Comstock, R. L., and Nepela, D. A. Single-crystal ferrimagnetic films, P (1) 14*e*.
Conabee, E. E. See Brown, Sherman D.
Condas, G. A., and Brown, Don W. Variable sensitivity visual displayer for ir laser beams, P (10) 253*e*.
Conde, R. M., and Drost, W. Zeolitic desiccant bodies and process for preparing, P (3) 72*b*.
Condrate, R. A., Sr. See Blakeslee, K. C.; Jang, Sung Do; Levitt, S. R.
Conger, G. J., and Anderson, H. U. Nonstoichiometry in $BaTiO_3$, (11) 274*a*.
Conley, C. D. See Minoura, Nachio.
Conley, K. H. Classifying apparatus with adjustable fines outlet, P (9) 229*h*.
Conley, R. F., Lloyd, M. K., and Catherwood, B. R. Satin white-clay compositions and methods of mfg., P (3) 72*a*.
Connelly, J. H. Fiber optic core glass, P (7) 161*d*.
Conners, A. See Williams, Frank R.
Connolly, T. F. (editor). Electrical Properties of Solids—Surface Preparation and Methods of Measurement, B (10) 263*e*. Semiconductors—Preparation, Crystal Growth, and Selected Properties, B (10) 264*b*.
Connolly, T. J. Fast neutronic reactor utilizing ^{240}Pu fuel, P (9) 228*h*.
Conroy, A. R., Jr., Bauer, W. C., and Billings, D. D. Glass mfg. employing Na sulfite, P (2) 34*f*.
Conwicke, J. A. Method of fabricating radially oriented magnets, P (1) 13*c*.
Conze, P. See Rein, H. M.
Cook, A. K., and Fulton, E. Miniature lamp assembly, P (1) 5*d*.
Cook, A. M. Method and apparatus for cutting complex shapes, P (1) 16*j*. Molding apparatus for orienting elongated particles, P (2) 29*h*.
Cook, C. F., Jr. See Shappirio, J. R.
Cook, C. R., Jr. Method of fabricating a semiconductor [leads] device, P (10) 251*d*.
Cook, J. E. See Willardson, R. K.
Cook, J. L. See Lambdin, F.
Cook, L. S. See Yavorsky, P. J.
Cook, M. H. See Brede, D. W.
Cook, R. F. Combined electron microscopy and energy loss analysis of glass, (6) 131*h*.
Cook, R. L. See Nedeljkovic, A. I.
Cook, T. E. Moldable hydrated MgO and the formation of molded articles therefrom, P (7) 164*h*.
Cook, W. R., Jr. See Jaffe, B.
Cooke, V. F. G., and Lee, Sung Ki. Metalization of ceramics, P (1) 12*j*.
Cooley, R. F., and Reed, J. S. Equilibrium cation distribution in $NiAl_2O_4$, $CuAl_2O_4$, and $ZnAl_2O_4$ spinels, (9) 235*b*.
Cooney, W. J. Soil release chemicals and method of application to glass fabric or fiber, P (3) 59*g*.
Cooper, A. H. See Rouf, M. A.
Cooper, A. R. See Varshneya, A. K.
Cooper, A. R., Varshneya, A. K., Sarkar, S. K., Swift, J., Klein, L., and Yen, C. F. Some aspects of the thermal history of lunar glass, (6) 132*h*.
Cooper, A. R., and Young, C. G. Laser structures, P (6) 133*d*.
Cooper, A. S. See Matthias, B. T.
Cooper, G. A., and Figg, J. Fracture studies of set cement paste, (11) 266*h*.
Cooper, G. A., and Mayer, R. M. Strength of C fibers, (2) 49*f*.
Cooper, G. L. See Golis, M. J.
Cooper, M. T. See Binns, D. B.
Cooper, W. F. See Coppens, P.
Copeland, G. G. Two-state lime mud calciner, P (9) 215*i*.
Copeland, J. A., III. Method and apparatus for determining deep impurity concentration in semiconductors, P (1) 13*a*. Wide-band dc-pumped semiconductor maser, P (3) 68*a*.
Copeland, L. E. See Greening, N. R.
Copley, G. J., Rivers, A. D., and Smith, R. Reappraisal of contact angle measurements of Na and K silicate glasses on Pt in air, (11) 269*h*.
Coppens, P., Cooper, W. F., and Larsen, F. K. Charge distribution in the light-atom mineral kernite, (8) 208*b*.
Coppola, J. A. See Hasselman, D. P. H.
Coppola, J. A., and Bradt, R. C. Measurement of fracture surface energy of SiC, (10) 260*a*.
Coppola, J. A., Krohn, D. A., and Hasselman, D. P. H. Strength loss of brittle ceramics subjected to severe thermal shock, (10) 261*e*.
Coquin, G. A., Pinnow, D. A., and Warner, A. W. Physical properties of Pb-molybdate relevant to acousto-optic device applications, (4) 98*f*.
Cordelier, J. F. Investigation by electron microscopy of demixing of borosilicate glasses, (7) 159*e*.
Corderoy, H. M. Packaging of bottles, jars, and other articles, P (7) 162*f*.
Cordischi, D. See Cimino, A.
Cordone, L. G., and Martinsen, W. E. Glow-discharge apparatus for rapid sintering of Al_2O_3, (8) 205*a*.
Corenzwit, E. See Matthias, B. T.
Corish, J., Duffy, M. T., and O'Brian, C. D. Electrochemical study of incorporation of Ag vapor into α-Ag_2S, (6) 147*i*.
Corliss, D. S., Keast, R. R., and Saxman, R. L. Process of forming free-flowing particulate mixtures of phosphates and silicates, P (3) 71*g*.
Cornelisse, C. W. See Stein, H. N.
Cornelisse, C. W., Visser, T. J. M., Stein, H. N., and Stevels, J. M. Deviations from Newtonian rheological behavior in alkali borate glasses, (3) 55*a*.
Cornelissen, J., and De Rijk, A. M. M. Method of increasing the mechanical strength of glass articles, P (2) 34*d*.
Cornelissen, J., and Piesslinger, G. Properties and application of glass-ceramic materials, (4) 80*h*.
Cornelius, E. B., and Koester, D. W. Particles featuring γ-Al_2O_3, P (9) 233*d*.
Cornelius, W. L., and Martner, J. G. Apparatus for depositing thin lines, P (8) 200*c*. Multistation vacuum apparatus, P (9) 227*b*.
Cornell, R. C., Gittins, R., and Jenkins, A. Method and apparatus for determining the concentration of an electronegative gas in a mixture of electronegative and nonelectronegative gases, P (11) 278*i*.
Cornell, R. M. See Turnbull, J. A.
Cornetet, W. H., Jr. Moisture-measuring system using microwave and nucleonic measurements, P (6) 141*f*.
Corper, M. Refractories requirements of gas-metallurgy and the various applications of the Gazal process, (2) 36*f*.
Correll, E. M. Electrolytic capacitor employing glass-to-metal hermetic seal, P (3) 64*h*.
Corsini-Mena, A., Elli, M., Paorici, C., and Pelosini, L. Simple versatile method to grow Cd chalcogenide single crystals, (7) 180*e*.
Corson, B. L., and Royer, B. R. Method and apparatus for calcining particulate mineral materials, P (6) 143*b*.
Corth, R., and Michael, J. F. Method of making an undistorted coiled-coil TaC filament, P (7) 164*g*.
Cortorillo, S. Method of making a vapor discharge lamp, P (4) 82*d*.
Cost, J. R. See Rossi, R. C.
Costa, U. See Canegallo, G.
Costello, R. C., Jean, A. J., and Kucera, W. J. Method for producing castings in a permanent mold, P (4) 84*g*.
Cotter, J. F. Assorting device [bottles], P (4) 81*j*.
Cotter, J. J. Wave-guide ferrite circulator having conductive side of dielectric disk in contact with ferrite, P (8) 203*b*.
Cottin, B. Electron microscope studies of Al_2O_3 cement pastes, hydrated to C_2AH_8 and CAH_{10}, (5) 103*b*. Electron microscope studies of the kinetics of hydration of Al_2O_3 cement to CAH_{10} and C_2AH_8, (6) 128*f*.
Cottrill, J. R. See Hall, T. H., Jr.
Cotty, W. F., and Wilks, E. M. Differences between diamonds from different sources, (4) 77*f*.
Couch, E. L. Calculation of paleosalinities from B and clay mineral data, (3) 71*b*.
Coughlin, R. W. See Gebauer, J.
Court, D. B. See McCreary, W. J.
Coutinho, C. B., and Bradley, W. L. Interactions between $MoSi_2$ and some metals, (10) 242*g*.
Coutts, M. D. See Dismukes, J. P.
Couture, R. A., and Lajza, J. J., Jr. Etching completion indication, P (5) 112*a*.
Coutures, J. P. See Fava, J.; Rouanet, A.
Cowan, G. R. See Balchan, A. S.
Cowan, J. H. Jr., and Rostoker, D. Batch for producing cellulated glassy bodies from rock, P (9) 218*e*.
Cowlard, F. C. See Appleby, H.
Cowlard, F. C., and Ord, G. Heat-transfer apparatus, P (4) 88*d*. Mfg. of composite ferrites, P (6) 138*h*, P (8) 201*c*.
Cowley, R. A., Dolling, G., Cochran, W. W., Pawley, G. S., and Lefkowitz, I. Semiconducting ferroelectric transducers, P (2) 42*h*.
Cowper, G. [Counterflow] vibratory conveyor, P (1) 16*g*.
Cox, D. E., Shirane, G., Birgeneau, R. J., and MacChesney, J. B. Neutron-diffraction study of magnetic ordering in Ca_2MnO_4, (6) 150*a*.
Cox, G. C. See Busby, T. S.
Cox, P. D. Gas burner [premix], P (4) 93*j*.
Cox, R. H., and Strack, H. A. Ohmic contacts for GaAs semiconductors, P (9) 227*c*.
Cox, R. W. See Holmes, W. H.
Cox, R. W., Holmes, W. H., and Davies, E. Design, construction, and operation of an experimental tunnel kiln for rapid-firing studies, (1) 19*c*.
Coxe, E. F. Method for producing evacuated glass microspheres, P (1) 5*b*.
Cozza, G. See Barilli, F.
Crabb, J. C., Maines, J. D., and Ogg, N. R. Surface-wave diffraction in $LiNbO_3$, (4) 99*g*.
Crabtree, J. O. See Johnson, A. B.
Cracknell, A. P. See Daniel, M. R.
Craig, D. F., and Hummel, F. A. Zr pyrovanadate transitions, (11) 283*d*.
Craig, R. C. See Richardson, H. L.
Craik, D. J., Kitto, A. D., and Ross, D. P. Magnetization precession in ferrites as influenced by the microstructure, (7) 167*g*.
Cramer, W. H. See Araujo, R. J.
Crane, D. E. See Kolb, W. P., Jr.
Cranston, B. H. Methods for bonding leads and testing bond strength, P (4) 89*d*.
Craver, C. D. (editor). Polymer Characterization—Interdisciplinary Approaches, B (2) 52*d*.
Crawford, R. H. Bipolar-to-MOS interface stage, P (3) 64*i*.
Creer, M. H., Hardy, J. B. C., Rooksby, H. P., and Still, J. E. Some applications of thermohygrometric analysis to the study of clay and associated minerals, (6) 142*g*.
Cregeen, D. Channel intensifier glass compositions, P (5) 107*b*.
Crennan, J. M., Dyczek, J. R. L., and Taylor, H. F. W. Quantitative phase compositions of autoclaved cement-quartz cubes, (8) 187*a*.
Crespi, G. Dense magnesite furnace hearth having a superficial dolomite-containing layer and method, P (4) 84*i*.
Creyke, W. E. C. Fracture of glazed porcelain (I) under static loading, (1) 10*a*.
Cricchi, J. R. MIS array utilizing field-induced junctions, P (8) 201*h*.
Cripe, D. M. See Robinson, M.
Crishal, J. M., and Rice, E. J. Beam leads and method of fabrication, P (3) 64*i*.
Crisler, L. R. Production of Pu formate and PuO_2, P (8) 203*f*.
Criss, G. H. Phosphate-bonded monolithic refractory batch, P (2) 37*b*.
Cristea, V. See Becherescu, D.
Critchley, D., Dawber, F., and Grainger, K. F. Sampling of gaseous atms, P (10) 256*a*.
Crittenden, E. C., Jr. See Crooker, P. P.
Croft, W. J. See Galasso, F.
Croll, R. D., and Sinclair, G. I. Cushion means between abrasive and expanders, P (6) 127*h*.
Cronemeyer, D. C. See Giess, E. A.
Cronin, L. J. Thermionic cathode comprising mixture of BaO, CaO, and Li oxide, P (7) 170*f*.
Crook, D. N. See Tauber, E.
Crooker, P. P., Weeks, G. A., and Crittenden, E. C., Jr. Phonon and photon paramagnetic-response line shapes in ruby, (6) 150*g*.
Crooks, R. See Carver, B. G.

Crosby, D. P. See Wishon, B. E.

Crosby, G. E., and Shanefield, D. J. Method for bonding a metal pattern to a substrate, P (10) 251*a*.

Croskery, W. F. Electrical circuit assemblies, P (4) 87*c*.

Cross, L. E., and Lunghofer, E. P. Electromagnetic radiation-detection device comprising ferroelectric sensing, reference, and temp.-stabilizing components, P (1) 18*f*.

Cross, L. E., and Pohanka, R. C. Ferroelectricity in Bi oxide-type layer structure compounds, (2) 38*h*.

Cross, O. Environmental challenges for the heavy clay products industry, (9) 220*g*.

Crouch, A. G. Corrosion of bauxite-based refractories by products of residual fuel oil combustion, (1) 6*j*.

Crouch, A. G., Jolliffe, K. H., Graham, R. P., and Stoddart, D. E. Effect of the combustion products of residual fuel oil on the mechanical strength of high-Al_2O_3 and magnesite refractories, (1) 7*e*.

Crowley, M. S. Solving refractory problems in refineries, (10) 247*j*.

Crowley, M. S., and Johnson, R. C. Guidelines for installing and drying refractory concrete linings in petroleum and petrochemical units, (4) 84*b*. Guidelines for installing refractory concrete linings in cold weather, (3) 60*j*.

Crozier, D. S. See McMillan, P. W.

Csaki, I. Effect of deflocculating agents on clay minerals, (5) 110*i*. Plasticity of brick clays, (6) 143*h*.

Csetenyi, J., Erdelyi, T., and Takacs, S. Suitability of bauxite-accompanying clays of the Halimba area for ceramic purposes, (2) 46*e*.

Csicsery, S. M. Hydrocracking catalyst comprising a layered clay-type crystalline aluminosilicate component, a group VIII component, and Au and process using said catalyst; Cr or W [as the 3rd component]; Th or U [as the 3rd component], P (3) 71*a*. Hydrotreating catalyst comprising a clay-type aluminosilicate component and a crystalline zeolitic molecular sieve component and process using said catalyst, P (3) 71*a*.

Csicsery, S. M., Hickson, D. A., and Jaffe, J. Catalyst comprising layered crystalline clay-type aluminosilicate component and method of activating the catalyst, P (5) 117*e*.

Csillag, A., and Jaeger, H. Energy-controlled switching process in the amorphous system Te-As-Ge-Si, (6) 147*f*.

Csizi, G. See Beck, F.

Csurgay, I. See Nagy, K.

Cubicciotti, D. Gaseous trimer and tetramer of thallous fluoride, (8) 209*d*. Vaporization of thallous nitrate, (8) 211*g*. See Johnson, J. W.

Cuff, D. W. Stacked composite plate laser, P (4) 91*a*. Unitary glass laser system with asymmetrical pumping, P (3) 59*j*.

Cuff, D. W., and DeBaryshe, P. G. Athermalization of laser rods, P (8) 200*d*.

Culbreth, W. K., Jr., and Rickey, C. J. Quality control of ceramic stains, (3) 61*j*.

Cullers, R. J., Medaris, L. G., Jr., and Haskin, L. A. Gd—distribution between aqueous and silicate phases, (1) 22*a*.

Cummings, W. Production of SiO_2 sols, P (1) 20*j*.

Cummins, S. E. Ferroelectric Gd molybdate bistable light gate-memory cell, P (1) 12*c*. Ferroelectric Gd molybdate compensation type bistable light gate and logic cell having memory, P (2) 40*g*.

Cunningham, J. A. See Cash, J. H., Jr.

Cunningham, J. A., Fuller, C. R., Hooper, R. C., and Wakefield, R. H. Metalization system for semiconductors, P (7) 169*c*.

Cunningham, J. A., Fuller, C. R., and Wood, S. J., Jr. Method of forming a composite insulating layer, P (6) 138*e*.

Cunningham, J. A., and Orr, C. D. Ohmic contacts for semiconductor devices, P (9) 227*c*.

Cunningham, J. A., and Williams, Robert P. Multilevel ohmic contacts for semiconductor devices, P (7) 169*g*.

Cunningham, R. E. See Dunn, S. A.

Cunningham, W. P., and Whang, T. J. Apparatus for producing filaments of glass, P (2) 33*c*.

Curran, M. J. See Greskovich, C.

Currie, K. L. See Ferguson, J.

Curry, N. A. See Mallov, J. F.

Cutler, I. B. See McAllister, P. V.; Rao, W. R.; Rasmussen, S. T.

Cutter, I. A., and McPherson, R. Surface domain reorientation produced by abrasion and annealing of polycrystalline $BaTiO_3$, (8) 211*a*.

Cyr, D. Coiling a pot in a pot, (2) 30*c*. David Crespi's weed pots, (2) 30*e*. Pravoslav Rada, (4) 78*a*.

Cyrus, W. L. See Moss, M.

Cyvin, B. N., Cyvin, S. J., and Rao, D. B. Thermodynamic functions from spectroscopic data for some alkali fluorides, (6) 152*d*.

Cyvin, S. J. See Cyvin, B. N.; Oeye, H. A.

Czamanske, G. K. See Desborough, G. A.

Czapla, H. U. See Mahler, E.

Czaya, R. Thermal decomposition of Ca_2SiO_4·$CaCl_2$, (5) 104*d*.

Czeck, J. J., Lyon, G., and Reusser, R. E. Crystal grower with expandable chamber, P (10) 250*f*.

Czumber, F. E. See Wiltshire, A. J.

Dachs, L. L. See Adams, A. L.

Dagnall, R. M. Apparatus for spectroscopic analysis with modulated electrodeless discharge tube, P (6) 142*c*.

Dahlberg, R. Method of producing a Ge transistor, P (2) 41*j*.

Dahlberg, R. C., and Goeddel, W. V. Method of making nuclear fuel elements, P (7) 171*g*.

Dahlinger, R. J. Laser flashtube triggering arrangement, P (10) 251*a*.

Dahlman, F. A., and Mras, R. J. Glass-forming fluid flow control means, P (4) 82*a*.

Dahlstrom, D. A. See Emmett, R. C., Jr.

Dahms, F. A., and Foster, T. V. Triple gob mold holder arm construction, P (1) 5*e*.

Daimon, Masaki, Inoue, K., and Kondo, R. Effect of dissolved Fe oxide on CaO·Al_2O_3 hydration, (9) 214*f*.

Daimon, Masaki, and Kondo, R. Assembly of a vapor adsorption apparatus and its application to the determination of the pore size distribution of hydrated cement, (11) 266*f*. Carbonation of high Al_2O_3 cement mortar, (4) 78*f*.

Daimon, Masaki, Rhee, Kyung Hee, and Kondo, R. Hydration mechanism of $CaSO_4$ hemihydrate, (3) 73*f*.

Daimon, Masaki, Ueda, S., and Kondo, R. Morphological study on hydration of $3CaO$·SiO_2, (5) 103*f*.

Dalal, V. L., Dreeben, A. B., and Triano, A. Temp. dependence of hole velocity in *p*-GaAs, (5) 124*g*.

D'Albis, A. Research on the improvement of a glaze for hard porcelain, (2) 37*j*.

Dale, E. A. See Thomas, M. J. B.

Dale, E. A., and Thomas, M. J. B. Atomizing, spray-drying, and flame process for mfg. phosphors, P (10) 249*g*. Electrical translating device containing spheroidal phosphors, P (9) 218*i*. Process for making improved phosphate phosphors from brushite, P (7) 170*f*.

Dalmasso, C. Integrated semiconductor circuit package and method, P (10) 250*j*.

Dalton, J. J. See Quint, S. M.

Dalton, J. V., and Labuda, E. F. Diode-array target including isolating low-resistivity regions, P (10) 250*h*.

Dalton, R. H., and Riebling, E. F. GeO_2-SiO_2 glasses and method of coating, P (9) 225*j*.

Daly, F. P. Metal-oxide-metal thin-film capacitors and method of making, P (10) 251*h*.

Damen, T. C. See Leite, R. C. C.

Damjanovic, A. See Fredlein, R. A.

Dana, R. L. See Huber, W. W.

Danassy, K. See Kappelmeyer, R.

Dancy, E. A. See Deis, D. W.

Daniel, J. S. See Zikovsky, L.

Daniel, M. R., and Cracknell, A. P. Magnetic symmetry and antiferromagnetic resonance in CoO, (5) 121*e*.

Daniels, A. Thermal regenerator, P (10) 248*e*.

Daniels, A. U. Nitride-oxide refractories, P (7) 164*i*. TiC-Ni compositions, P (10) 248*e*.

Daniels, H. P. C., Van der Ven, T. J., and Tates, H. G. K. Method of connecting metal contact areas of electric components to metal conductors of flexible substrate, P (9) 226*e*.

Danielsson, L., Jonsson, O., and Wilhelmi, K. A. Micromethod for the determination of the O content of some slightly reduced transition metal oxides, (3) 74*i*.

Danilenko, L. P. See Il'yasov, I. I.

Daniluk, S. E. Semiconductor unijunction transistor device having a controlled cross-sectional area base contact region, P (3) 67*g*.

Danley, W. J., and Mulay, L. N. Magnetic studies on the Ti-O system—experimental aspects and magnetic parameters, (11) 281*e*.

Dann, J. N. See Baglio, J. A.

Danyluke, O. Vibratory or reciprocatory conveyor or screening apparatus, P (4) 92*i*.

D'Annessa, A. T., and Kranzlein, H. H., Sr. Apparatus for minimizing thermal gradient in [tensile] test specimens, P (2) 44*h*.

Dantro, H. F. Photoconductive TiO_2 composition, P (10) 252*h*.

Dapot, M. H. Apparatus for maintaining thermocouple reference junctions at a constant temp., P (4) 93*e*.

Dapples, E. C. Some concepts of cementation and lithification of sandstones, (8) 210*f*.

Darby, I. A. See Whitaker, A.

Darling, A. S., and Selman, G. L. Pt-Rh-Au alloys, P (10) 245*i*.

Darr, D. E., Edwards, G. B., Lochr, C. E., and Young, E. E. Method of preparing pigmentary TiO_2, P (5) 117*h*.

Darriet, J. See Galv, J.

Das, A. R. See Mishra, G. L.; Tiwari, A. N.

Das, C. R. H_2O attack on Na_2O-MgO-SiO_2 glasses in relation to their structure, (11) 289*i*.

Das, D., Mitra, M. N., and Chakrabarti, R. K. Capacitor microstrain gage for precise measurement of uniaxial strain, (10) 255*b*.

Das, E. S. P., and Marcinkowski, M. J. Propagation of slip across a twist boundary by means of grain-boundary twist-disclination loops, (6) 151*f*.

Das, H. A. Activation analyses and tracer techniques, (4) 92*i*.

Das, M. B. IGFETs, P (4) 88*g*. See Robinson, D. P.

D'Asaro, L. A. Curved junction laser devices, P (1) 12*f*.

Das Podder, P. K. See Mitra, N. K.

Datta, K. K. See John, P. T.

Datta, R. K. Ternary alkaline-earth pyrosilicate luminescent materials activated with divalent Eu, P (10) 253*a*.

D'Augustine, F. T. Process for screening cathode-ray tubes including salvaging of excess phosphor slurry, P (10) 245*d*.

Dauksys, R. J. High performance reinforcements for advanced structural composites, (10) 246*h*.

Daussan, H. J. Continuous slurry supply method for fabrication of mold linings, P (7) 164*c*.

Dautzenberg, S. Batch mixing in the ceramic industry with a conveyor-type electromechanical weighing machine, (1) 16*g*.

Dave, N. G., and Masood, I. Effect of time and temp. of burning of high MgO-containing limestones on the nature of the product, (11) 266*j*. Thermogravimetric method of determining unhydrated MgO contents of hydrated dolomitic limes, (11) 278*e*.

Davenport, S. T. E. See West, H. W. H.

Davey, J. E. Method of making ion implanted dielectric enclosures, P (8) 201*d*.

Davey, N. See Loasby, R. G.

Davey, N., and Loasby, R. G. Microelectronic circuits and processes for making them, P (3) 66*j*.

Davezac, J. P. Cracks in glass-metal seals obtained by hf induction heating, (10) 243*a*.

Davidge, R. W. See Evans, A. G.

Davidsohn, U. S. Method and apparatus for indicating semiconductor island thickness and for increasing isolation and decreasing capacity between islands, P (3) 65*d*.

Davidson, A. (editor). Handbook of Precision Engineering (Vol. 3) Fabrication of Nonmetals, B (9) 240*b*.

Davidson, K. V., and Schell, D. H. Production-scale formation of ultrahigh-purity carbide powders, P (9) 222*f*.

Davidson, P. See Lofberg, J. A. S.

Davies, B., and Carini, G. F. Phosphate-bonded magnesite-chrome brick, P (2) 37*b*.

Davies, B., and Henry, G. R. Basic refractory shapes, P (4) 84*g*.

Davies, E. See Cox, R. W.; Holmes, W. H.

Davies, G. Some properties of N in diamond, (4) 98*g*.

Davies, J. A. See Picraux, S. T.

Davies, J. J. See O'Mara, W. C.

Davies, J. J., Smith, S. R. P., and Wertz, J. E. EPR of tetravalent Mn ions at tetragonal and octahedral sites in MgO, (5) 120*j*.

Davies, J. M., and Peter, P. H. Calorimeter with a highly reflecting surface for measuring intense thermal radiation, (10) 255*a*.

Davies, J. M., and Zagieboylo, W. Flame spraying Al_2O_3 to make reflective coatings, P (2) 31*h*.

Davies, L. G., Powers, W. M., and Shaver, R. G. Low cost metal-matrix composite fabrication, (3) 54*g*.

Davies, M. W., and Meherali, S. G. Equilibrium solubility of N in aluminosilicate melts, (6) 147*i*.

Davies, W. Sintered aggregates, P (1) 6*d*. See Thomson, G. M.

Davis, B. C., and Singer, A. Nonwelded thermocouple junctions, P (1) 18*h*.

Davis, C. E., Ahmad, N., and Jones, R. L. Hydrothermal and dry-heat fixation of K by soil clays and the effects on C.E.C., surface area, and mineralogy, (9) 236*d*.

Davis, E. Method for connecting attachments to fiber glass rods, P (8) 193*i*.

Davis, E. A. See Cherin, P.

Davis, E. A., and Shaw, R. F. Characteristic phenomena in amorphous semiconductors, (6) 145*i*.

Davis, E. K., Hansen, K. W., and Jayachandra, Y. Black enamel glass for cathode-ray tube, P (7) 161*i*.

Davis, G. A., Joyce, I. H., and Worrall, W. E. Effect of surface characteristics of ceramic raw materials on dye adsorption, (1) 19*h*.

Davis, G. A., and Worrall, W. E. Adsorption of H_2O by clays, (2) 47*a*.

Davis, H. H., Jr., Graham, H. C., and Tripp, W. C. Vapor phase formation during high temp. oxidation, (11) 277*c*.

Davis, J. A., Talbert, S. G., Hazard, H. R., and Gibeaut, W. A. Melting of fusible materials, P (8) 206*d*.

Davis, J. E., Carithers, V. G., and Watson, D. R. Practical use of particle size distribution to predict compacting and sintering properties of calcined aluminas, (1) 11*g*.

Davis, J. P. Uninsulated in-core thermionic diode, P (10) 253*d*.

Davis, L. W., and Bradstreet, S. W. Control of thermal expansion through composite design, (1) 2*h*.

Davis, M. P., and Theobald, P. R. Au metalizing of refractory metals on ceramic substrates, P (9) 225*a*.

Davis, R. F., Aksay, I. A., and Pask, J. A. Decomposition of mullite, (3) 72*d*.

Davis, R. F., and Pask, J. A. Diffusion and reaction studies in the system Al_2O_3-SiO_2, (11) 281*e*.

Davis, T. A. See Vedam, K.

Davison, L. Shock-wave structure in porous solids, (7) 180*c*.

Davisson, J. W., and Molnar, B. Study of bias fields in ferroelectric colemanite, (2) 50*b*.

Davoine, F. See Porral, G.

Davydova, L. Ya. See Gitterman, A. K.

Daw, J. D., Nicholson, P. S., and Embury, J.

D. Inhomogeneous dehydroxylation of talc, (4) 97*g*.
Dawber, F. See Critchley, D.
Dawihl, W., Doerre, E., and Dworak, U. Application of ceramic cutting tools in machining steel and cast iron, (10) 246*e*.
Dawihl, W., and Eicke, W. Production and properties of C-containing Fe fibers and sintered fiber bodies, (10) 247*d*.
Dawson, D. K. See Barr, L. W.
Dawson, J. B. Genesis of kimberlite, (4) 77*f*.
Daxer, H. See Vogler, M.
Day, B. E. See Deits, W. C.
Day, D. E. See Abdel-Latif, A. I. A.; Fleming, J. W., Jr.; Moore, D. W.
De, S. K. See Banerjee, J. C.
Deacon, A. J., and McCullough, M. J. Gas-permeable refractory plug and method, P (2) 37*f*.
Deacon, J. S. Method and apparatus [wet type] for removing entrained dust particles from a gaseous stream, P (10) 254*e*.
Dean, G. A. Sheet handling apparatus, P (11) 270*i*. See Miller, A. H.
Dean, J. A., and Rains, T. C. (editors). Flame Emission and Atomic Absorption Spectrometry (Vol. 2) Components and Techniques, B (1) 26*j*.
Dean, P. J. See Collins, A. T.
De Angelis, W. M. Coupling for joining glass pipe sections and the like, P (10) 244*c*.
Deaton, H. W. Surface temp. indicator light for ceramic top ir radiant range, P (2) 35*a*.
Deaton, H. W., and Siegla, D. C. Ceramic top range surface temp. cutoff thermostatic device, P (3) 64*b*.
De Barrau, A. Adjuvant composition for concretes and mortars, P (8) 188*c*.
DeBaryshe, P. G. Header for a laser rod, P (2) 34*g*. See Cuff, D. W.
De Bergevin, F. See Gondrand, M.
Debever, J. M. See Benoit a la Guillaume, C.
De Bie, E. Process and apparatus for pulling single crystals of Ge, P (5) 113*j*.
De Boeck, P., Marteel, B., and Schrijvers, J. Nuclear fuel, P (9) 229*a*.
Debras-Guedon, J. See Boix, A.
De Brebisson, M. Method of mfg. a Zener diode, P (10) 251*i*.
De Bres, J. G. C. M. See Wanmaker, W. L.
De Bruin, H. J., Moodie, A. F., and Warble, C. E. Reaction welding of ceramics using transition metal intermediates, (8) 199*g*.
De Bruyne, R. See De Maayer, P.
De Bucs, E. S. See Oesterhelt, G.
De Bussy, J. M. Y. Le Clerc. See Le Clerc de Bussy, J. M. Y.
De Caro, A. R. Br-filled bipost lamp with a high-temp.-resistant glass envelope, P (6) 132*b*.
De Caro, A. R., and Rainone, N. J. Lamp combination comprising an improved envelope for W-halogen incandescible projection lamp, P (6) 133*c*.
De Cecco, A. L., Piccone, D. E., and Somos, I. Semiconductor rectifier with improved turn-on and turn-off characteristics, P (10) 252*j*.
Decius, J. C. See Frech, R.
Decker, D. L. High-pressure equation of state for NaCl, KCl, and CsCl, (6) 148*b*.
Decker, H., and Stoeckmann, H. Crusher tool for gyratory crushers, P (1) 20*c*.
Decker, J. A., Jr. Turbine engine blade pyrometer, P (3) 70*g*.
Declaye, J. See Brichard, E.
De Cremoux, B., and Leclerc, P. Light modulator, P (8) 201*a*.
De Cuir, G. L. Fractionation of SiO_2 aerosols, P (6) 144*a*. See Driscoll, R. E.
De Decker, H. K. See Houwink, R.
DeDiemar, R. B. See Archer, F. C.
Dee, P. L., Edwards, R. L., and Lee, H. R. Vibratory treatment apparatus, P (4) 91*c*.
Deeg, E. W., and Graf, R. E. Optical glasses having improved spectral transmission produced from Hg nitrate-containing glass batches, P (10) 245*h*.
Defeo, S. See Walsh, P. J.
De Ferran, E. M. See Harris, B.
De Forest, W. S., Heap, R. T., Widmont, J. C., and Zagorin, H. Method for coating metals or insulating substrates having a vitreous binder, P (9) 226*d*.
De Fouchier, A. See de Vaulchier du Deschaux, L.
Degenkolb, R. S., and Skaw, E. R. High *Q* circuits on ceramic substrates, P (10) 250*h*.
DeGroot, J. See McMurdie, H. F.
Degtyareva, E. V. See Kainarskii, I. S.
Dehlen, B. L. A. Self-supporting screens for stone, ore, and like material, P (2) 46*h*.
Deica, N. See Dragomir, C.
Deis, D. W., Dancy, E. A., and Patterson, A. Switching characteristics and the bulk properties of chalcogenide glasses, (6) 132*a*.
Deis, D. W., Gavaler, J. R., and Jones, C. K. Alternating current losses of stabilized NbN, (7) 166*d*.
Delta, W. C., and Day, B. E. Target structure for camera tubes consisting of an MgO layer supported on one side of a metal mesh, P (2) 42*i*.
De Jaeger, N. C. See Tavernier, B. H.
De Jonge, L. S. Efflorescence and firing conditions, (4) 83*f*.
De Jongh, W. K., and Mueller, P. H. New method of glass and batch sample preparation for X-ray fluorescence spectrometry, (8) 205*h*.
DeKalb, A., and Whitney, A. G. Process improvement for mfg. high-purity quartz forms, P (3) 59*d*.
De Keyser, W. L. See Robijn, P.
Dekker, P. Corrosion of enameled surfaces. New method of testing acid resistance, (6) 130*i*. Enamel expansion coeff.—relations between thermal expansion, viscosity, transformation point, and stresses, (8) 188*j*.
De Klerk, J. Method of forming thin insulating films particularly for piezoelectric transducers, P (7) 169*h*. Method [vapor deposition] of forming thin insulating films particularly for piezoelectric transducer, P (4) 89*c*.
De Kort, G. M. A. J. See Luiten, W.
De Kozak, A. Some double fluorides of Cr, (4) 98*g*.
De Kozak, A., Samouel, M., and Chretien, A. Crystalline miscibility of Ca, Sr, and Pb fluorides in CdF_2. The double fluoride $CdBaF_4$, (10) 258*g*.
Delawarde, E. See Goates, J. R.
Delepine, C. Introduction to Crystallography, B (8) 212*b*.
Delimarskii, Yu. K. See Chernov, R. V.
Delin, M. A. See Brown, T. W.
Delius, H. See Singer, H.
Dell, C. C. Laboratory studies on the removal of H_2O from clays by deep cone thickening, (1) 20*a*.
Della Porta, P., Giorgi, T. A., Kindl, B., and Zucchinelli, M. Getter device, P (3) 58*d*.
Della Porta, P., and Rabusin, E. Gettering, P (9) 219*b*.
DeLosh, R. G., Tien, Tseng-Ying, Gibbons, E. F., Zacmanidis, P. J., and Stadler, H. L. Strong quenching effects of Tb^{3+} emission by Tb-V interaction in YPO_4-YVO_4, (7) 181*c*.
Deloye, F. X. See Baron, A.
De Luca, J. P., and Leitnaker, J. M. Phase behavior in the Pu-Cr-N system, (6) 140*j*.
De Maayer, P., De Bruyne, R., and Brabers, M. J. Decomposition temp. of $Th(WO_4)_2$, (3) 72*d*.
Demareq, J. See Warzawski, B.
De Maria, G., Malaspina, L., and Piacente, V. Mass spectrometric study of the GaAs system, (5) 121*f*.
Dembovskii, S. A. See Timofeeva, N. V.
Dembovskii, S. A., Kirilenko, V. V., and Khvorostenko, A. S. System As_2Se_3-Tl_2Se, (8) 211*d*.
De Mendez, M. O., Foucard, A., and Verin, J. Sample holder for optical measurements at low temps., P (3) 70*g*.
De Menezes, L. Electron microprobe, (4) 93*c*.
Demidov, A. E. See Perel'man, F. M.
Demidovich, B. See Akulich, S.
Demirel, T. See Huang, R. J.
Demott, D. S., and Hancock, P. Na ion transport in β-Al_2O_3, (9) 238*a*.
Denayer, M. See Nagels, P.
Denda, Ryuji. See Nakata, Josuke.
Den Dulk, E. S. Electric discharge tube having at least 1 nonemitting electrode which consists at least superficially of Ni, P (2) 40*d*.
Denes, L. J., and Ward, P. C. Polarizing laser mirror, P (3) 59*c*.
Denes, P. A. Arc and spark extinguishing contacts utilizing single domain magnetic particles, P (3) 64*f*. Broad-band hf low-pass filters, P (2) 39*d*. Method of making permanent magnets, P (8) 201*e*.
DeNeufville, J. P. See Moss, S. C.
De Neve, G. M. J. See Groth, R.
Dengo, Tadao. See Suenaga, Masanobu.
Denis, J. P., and Loriers, J. Luminescent compounds of Ce phosphates activated by Tb, P (4) 88*b*.
Denis, P. M., and Guicherd, R. H. Nondestructive method for measuring states of surface and apparatus for carrying out the method, P (8) 206*a*.
Denisenko, E. I. See Potryasov, V. N.
Denison, N. E. Kiln car deck stool, P (3) 70*c*.
Denisov, Yu. V. See Dzhurinskii, B. F.
Denker, S. P. See Schoen, J. M.
Dennen, W. H., and Puckett, A. M. Chemistry and color of amethyst, (11) 280*f*.
Denning, R. Contact system for semiconductor devices, P (4) 87*b*.
Dennison, B. J., and Doutt, A. A. Treating glass sheets used in laminated safety glass windshields, P (1) 5*e*.
De Novion, C. See Guerin, Y.
Dentai, A. G. Fluorescent high Al_2O_3 ceramic substrates, (10) 249*d*.
Denton, C. I. See Shamash, M. B.
DePoorter, G. L., and Storms, E. Changes in X-ray emission spectra with compound formation—Nb *L*-spectra in Nb carbides, (4) 95*g*.
De Poorter, J. A. See Bril, A.
Deportes, C. See Dontsov, G.; Hammou, A.
Deradoorian, B. Anode array techniques, P (4) 87*c*. See Colson, W. B.
Deradoorian, B., Goodrich, G. W., and Theodorou, D. G. Method of fabricating an array of channel multipliers, P (10) 245*a*.
Dereich, J. E. Printing on substrates such as glass using epoxy resin ink compositions, P (1) 5*b*.
Derenovskaya, N. A. See Dvorina, I. A.
Dergunova, V. S. See Kilin, V. S.
De Ridder, R. See van Landuyt, J.
De Ridder, R., and Amelinckx, S. Structure of defect Mn silicides, (2) 50*a*.
Derie, R., and Kusman, L. A. Diffusion and reactions in the system MgO-Fe_2O_3, (5) 119*c*.
De Rijk, A. M. M. See Cornelissen, J.
Dernier, P. D. See Marezio, M.; Porta, P.
De Rose, K. N. Sheet handling apparatus, P (7) 162*j*.
De Rouw, H. J. Method of mfg. a glass article having a light-dispersing layer, P (6) 133*a*.
Derror, F. L. Apparatus for a system to extricate intricate ceramic shapes from multiple piece molds, P (9) 223*f*.
Derry, D. J., Lees, D. G., and Calvert, J. M. Study of O diffusion in TiO_2, (9) 238*i*.
Desai, N. C. See Odhiambo, D.
De Saint-Chamant, H. See Stiglitz, P.
Desborough, G. A., and Heidel, R. H. Improved quantitative electron microprobe analysis at low operating voltage (I) Si, Mg, and Al, (4) 93*e*.
Desborough, G. A., Heidel, R. H., and Czamanske, G. K. Improved quantitative electron microprobe analysis at low operating voltage (II) S, (4) 93*e*.
Descamps, M. See Duchateau, J.
Deschanvres, A. See Choisnet, J.; Maisseu, A.
Deschepper, P. See Brichard, E.
Descleaux, P., and Rolin, M. Al_2O_3 diffusion coeff. in cryolite-Al_2O_3 mixtures, (7) 176*f*. Viscosity of cryolite-Al_2O_3 mixtures, (7) 182*a*.
Desgardin, G., Hervieu, M., and Raveau, B. Structural study of the nonstoichiometric pyrochlore-type compound $Pb_{2-\alpha}(Ti,Ta)_2O_{7-\beta}$, (4) 98*i*.
DeShazer, L. G. See Rice, D. K.
Deshko, Yu. I. See Gusarov, A. D.
Desmond, R. J., Fronczek, E. J., and McCarthy, J. J. Machine and process for semiconductor device assembly, P (9) 225*h*.
Desmond, R. J., and Koenig, P. W. Semiconductor device with a heat sink having a foot portion, P (1) 14*j*.
Desmond, T. J., and Krumanacker, B. P. Gaseous diffusion technique, P (8) 200*f*.
Dess, H. M. See Fay, H.
Dessureault, J. M. Core for SiC furnace, P (6) 135*f*.
Desty, D. H., and Whitehead, D. M. Burner for use with fluid fuels, P (4) 93*j*.
Desvignes, F., Guiochon, P., and Pompei, J. Immersed bolometer using thin-film thermistors, P (4) 93*f*.
Detrio, J. A. Line strengths of the ^6P multiplets of Gd^{3+} in CaF_2 at cubic sites, (6) 149*d*.
Detweiler, J. R., Jr., and Tummala, R. R. Borosilicate glass composition, P (5) 107*a*.
Deulin, M. I. See Shchepetkin, A. A.
Deussner, H. Method and device for thermically treating fine-grained materials suspended in a hot gas stream, P (6) 143*b*.
Deutschbein, O. Continuous-wave fluorescent solid lasers, P (1) 12*e*.
Deutschman, A. J., Jr. See Berry, J. W.
Devalette, M. See Fava, J.
De Varda, G. Cryolitic linings in furnaces for Al smelting, P (9) 222*c*.
De Vaucelles, E. See de Vaulchier du Deschaux, L.
De Vaulchier du Deschaux, L., de Fouchier, A., de Vaucelles, E., and Facquet, L. Surface preparation of U parts, P (10) 254*b*.
Deverell, H. E. See Charpentier, A. J.
Deverell, H. E., and Muscatell, F. L. Ceramic die and method of making, P (2) 38*b*.
De Verr, S. M. See Brouwer, H. J.
Deverse, F. T. See Collins, R. H.
Devi, A. See Morrow, B. A.
De Vos, W. J., and Volger, J. Modified Fuoss-Kirkwood approach for asymmetrical dielectric loss curves, (1) 23*b*.
De Vries, A. J. See Le Page, M. A.
De Vries, J. See Blasse, G.
De Vrijer, B. See Tol, T.
DeWames, R. E., and Wolfram, T. Surface spin waves in antiferromagnetic NiO, (6) 152*f*.
De Wet, J. D. See Vail, J. W.
De Wit, M. Zeeman effect in the absorption spectrum of Cu-doped ZnS, (5) 125*j*.
DeWit, R. Relation between dislocations and disclinations, (5) 123*c*. See Simmons, J. A.
De Witt, D., Dhaka, V. A., and Oberal, A. S. Process for making metal contacts to high-speed transistors and product formed thereby, P (10) 252*a*.
De Wys, E. C. See Trueb, L. F.
Dexpert, H. See Claverie, J.
Dey, A. N. Li-metal vanadate organic electrolyte cell, P (10) 251*b*.
Dey, A. N., and Bro, P. Li-metal selenide organic electrolyte cell, P (10) 251*b*.
Dey, D. N. See Jouhari, A. K.
Deyris, E. Method of forming and regularly growing a semiconductor compound, P (6) 138*g*. Method of mfg. semiconductor compounds, P (6) 139*a*. See Le Duc, J. M.
Dgebuadze, T. P. See Krupkin, Yu. S.
Dhabanandana, S. See Grjotheim, K.
Dhaka, V. A. See De Witt, D.
Dhaka, V. A., and Kozik, A. F. Method for masking semiconductor regions for ion implantation, P (10) 251*i*.
Dhaka, V. A., Reuter, J. L., and Sandhu, J. S. Technique for fabrication of semiconductor device, P (4) 91*b*.
D'Huart, G. Ionically modified glass by electric field impaction, P (10) 244*g*.

Diamond, F. Novel semiconductor amplifier, P (5) 113*e*.
Diamond, S. Critical comparison of Hg porosimetry and capillary condensation pore size distributions of portland cement pastes, (5) 102*i*. Interactions between cement minerals and hydroxycarboxylic-acid retarders (II) tricalcium aluminate-salicylic acid reaction, (5) 103*c*; (III) ir spectral identification of the aluminosalicylate complex, (9) 214*e*. Microstructure and pore structure of impact-compacted clays, (5) 121*j*.
Dickinson, G. A. Method and apparatus for mfg. float glass, P (6) 133*h*.
Dickinson, G. A., and Nixon, F. Apparatus for mfg. float glass, P (8) 192*i*.
Dickinson, J. M. See Wagner, P.
Dickinson, S. K., Hilton, R. M., and Lipson, H. G. Czochralski synthesis and properties of rare earth-doped $Bi_4Ge_3O_{12}$, (6) 146*f*.
DiDomenico, M., Jr. See Wemple, S. H.
Diebert, M. C. Conductive C membrane electrode, P (10) 250*d*.
Dienes, E. K. See O'Brien, J. F.
Dieselman, H. D. See Olson, D. R.; Schroeder, J. B.
Dietch, L. Black-surround color picture tube, P (2) 33*e*. Etching electrodes, P (9) 225*h*.
Dietert, H. W., Graham, A. L., and Gervais, H. V. Method of determining the live clay content of foundry sand, P (1) 9*b*.
Dietert, H. W., and Steinmueller, R. E. Structure for sand testing, P (5) 110*a*.
Diettrich, H. See Lehmann, H.
Dietz, E. D., Baak, T., and Blau, H. H. Superheating of an albite feldspar, (4) 94*f*.
Dietz, J. W. Amorphous B-Si nitride materials, P (10) 247*c*. Preparation of Ti carbonitride, P (2) 37*c*.
Dietz, R. L. Multilayer dielectric compositions comprising Pb-Ba borosilicate glass and ceramic powder, P (10) 245*g*. See Trease, R. E.
Dietz, W. See Vogler, M.
Dietz, W. A. See King, W. H., Jr.
Dietzel, A. Combined chemical and mechanical corrosion, (11) 267*d*. Stress distribution in the system wall-mortar-body-glaze in fixed wall tiles (I) wall tile and relative stress in the body/enamel system; (II) calculation of stress; (III) measurement of stress in the wall; (IV) examination of fixed wall tiles, (4) 85*d*. See Oel, H. J.
Dietzel, A., and Haas, B. Influence of various oxides on the reaction of earthenware glazes with the body, (8) 197*j*.
Di Felice, A. Method of mfg. Zener diodes having improved characteristics, P (9) 226*f*.
Dill, H. G., Erb, D. M., and Toombs, T. N. Stable *n*-channel tetrode, P (4) 90*j*.
Dilliard, P. D. See Bogart, B. S.
Dillinger, J. R. See Fox, G. T.
Dillon, J. A. Disposing of solid wastes—a mountainous problem, (10) 254*d*. Monitoring SO_2, (10) 255*h*.
Dillon, J. F., Jr. See Gyorgy, E. M.
Dillon, J. F., Jr., and Garrett, C. G. B. Laser devices, P (5) 112*j*.
Dillon, J. F., Jr., and Guggenheim, H. J. Tl Fe fluoride and devices utilizing same, P (2) 43*a*.
Dills, R. L. Flat plate [glass-ceramic] surface heating unit, P (2) 34*a*.
Di Luca, H. See Fulton, T. P.
Dilworth, R. H., III. Apparatus for [dc] particle separation, P (4) 92*h*.
DiMarcello, F. V., Key, P. L., and Williams, J. C. Preferred orientation in Al_2O_3 substrates, (11) 274*e*.
Dimick, E. A. Flame-stabilizing system for power gas burners, P (6) 143*a*.
Di Mino, A. Electronic trimming of microelectronic resistors, P (3) 64*i*, P (10) 250*b*.
Dimmock, J. O. Optical properties of the Eu chalcogenides, (9) 237*f*. See Feinleib, J.; Oliver, M. R.; Pidgeon, C. R.
Dimova, D. Kh., and Piguzov, Yu. V. Improving the resistance of press mold plates, (8) 203*j*.
Dingle, R. Luminescent transitions associated with divalent Cu impurities and the green emission from semiconducting ZnO, (6) 150*c*.
Dingwall, A. G. F. Method of fabrication of photomasks, P (10) 251*d*.
Dinnie, A., and Beard, R. Reinforced brickwork silos for grain storage, (9) 221*b*.
Dinsdale, A. Data requirements in ceramics, (9) 230*g*. See Brough, R.
Dion, M., and Phan Kieu Duong. Action of lime on natural silicates of Al at 1250°C, (9) 233*d*.
Dionne, G. F. Conditions for stress-induced uniaxial anisotropy in magnetic materials of cubic symmetry, (1) 21*d*.
Dionne, G. F., and Goodenough, J. B. Effects of Co^{2+} and Mn^{3+} ion substitutions on the anisotropy and magnetostriction constants of $Y_3Fe_5O_{12}$, (11) 281*f*.
DiSalvo, F. J. See Gamble, F. R.
DiSalvo, R., Roy, D. M., and Mulay, L. N. EPR studies of radiation damage in H-impregnated glass, (11) 268*d*.
Dislich, H. Preparation of multicomponent glasses without fusion, (7) 160*a*.
Dislich, H., and Wiesner, K. H. Novel glass-plastic laminated filters, (8) 191*e*.
Dismukes, J. P. Low-temp. Si etch, P (9) 225*h*.
Dismukes, J. P., Martin, D. F., Ekstrom, L., Wang, C. C., and Coutts, M. D. Ferromagnetic CrO_2 for magnetic tape, (1) 11*f*.
Di Stefan, L. Sagger [for C], P (11) 272*f*.
Ditmars, D. A., and Douglas, T. B. Measurement of the relative enthalpy of pure α-Al_2O_3 (NBS heat capacity and enthalpy standard reference material No. 720) from 273° to 1173°K, (9) 236*f*.
Dittrich, F. J. Flame spray powder and process, P (3) 69*f*. See Longo, F. N.
Dixon, K. G. O., Gill, R. M., and Lovell, D. R. Mfg. C filaments, P (3) 61*f*.
Dixon, N. E. Capacitive ultrasonic device for nondestructively testing a sample, P (1) 18*e*.
Dixon, R. See Bramman, J. I.
Dixon, W. P., and Kendall, D. N. Semiconductor temp.-sensitive means, P (9) 227*i*.
Djabarov, N. B. BaS as an admixture to gypsum, (8) 185*i*.
Djemal, M. See Heiss, A.
Dobos, S. Bonding state of the alkali ions in the surface layer of glasses containing Na oxide, (2) 32*b*. Changes in structure of silicate skeletons during development of the surface layer of glasses containing Na oxide, (2) 32*b*.
Dobrin, M. Three-point method for determining viscosity-temp. curve for glass, (11) 269*f*.
Dobrowolsky, S. Comparative analysis of opal glass melting in gas-fired and electrical tank furnaces, (11) 268*e*.
Dobrozemsky, R. See Betz, G.
Dobrusskin, A. See Kuehl, B.
Dockerty, S. M. Controlling thickness of newly drawn glass sheet, P (11) 270*d*. Method and apparatus for feeding molten glass, P (3) 58*j*.
Dode, M. See Pialoux, A.
Dodge, F. C. W. Al_2SiO_5 minerals in rocks of the Sierra Nevada and Inyo Mountains, California, (1) 19*g*.
Doerbeck, F. H. See Ashley, K. L.
Doering, G., Kahle, K., and Schneider, D. Method for the production of mineral fiberboards containing mineral wool, P (11) 272*b*.
Doerr, F. H. Developments in cooperation of plants, management, and laboratories, (8) 189*i*.
Doerre, E. See Dawihl, W.
Dohr, H. See Konopicky, K.
Doi, Haruo. See Saito, Hajime.
Doi, Haruo, Matsushita, T., and Saito, H. Crystallization and properties of the crystallized product of Li_2O-MgO-Al_2O_3-SiO_2-F glass, (6) 131*j*. Effect of fluorine addition on crystallization of Li_2O-MgO-Al_2O_3-SiO_2 glass, (6) 131*h*. Studies on crystallization of glasses and properties of crystallized glasses of the system Li_2O-MgO-CaO-Al_2O_3-SiO_2-F, (5) 106*b*.
Doi, Hidekazu. Deformation mechanisms of WC-Co hard alloys—deformation characteristics of 2-phase alloys containing hard nonmetallic particles as a major constituent phase, (6) 134*h*.
Doi, Kazuo, Nakajima, J., Takahashi, H., and Tomokawa, H. Inorganic coating composition, P (9) 216*a*.
Doi, Kenji. See Masaki, Norio.
Doi, Kikuo. See Nanamatsu, Satoshi.
Doi, Kikuo, Takahashi, M., Nanamatsu, S., and Fujino, Y. $LiTaO_3$ piezoelectric vibrators, P (6) 138*d*.
Doi, Masaru. See Iemura, Toshio.
Dolega, U. See Schulz, E.
Dolinskaya, E. S. See Berkovich, T. M.
Dollimore, D., and Horridge, T. A. Floc sizes of kaolinite flocculated by polyacrylamide, (2) 37*h*.
Dollimore, D., and Spooner, P. Sintering studies on ZnO, (3) 75*e*.
Dolling, G. See Cowley, R. A.
Dolloff, R. T. See Mazdivasni, K. S.
Dolomont, A. A. Al welding wire electrode with an Al_2O_3 coating containing phosphate, P (10) 242*h*.
Dolzhkova, G. V. See Satarin, V. I.
Doman, R. C. See Alper, A. M.
Domey, K. E. Computer controlled growth of single-crystal ingots, (3) 62*i*.
Domicone, J. J. Surface treatment of glass-ceramics, P (9) 220*b*.
Domicone, J. J., and Ziver, G. M. Surface conditioner for glass-ceramics, P (10) 245*h*.
Donald, I. W., and McCurrie, R. A. Microstructure and indentation hardness of an MgO-Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramic, (7) 160*a*.
Donaldson, E. B. See White, Donald L.
Donaldson, W. K., Wilke, W., and Fetzer, H. Apparatus for producing coherent bodies from asbestos dispersions, P (2) 37*d*. Production of coherent bodies from asbestos dispersions, P (4) 85*a*.
Donat, R. J. See Kauffman, J. H.
Dondalski, W. J. See Charles, R. J.
Dondelinger, J. D., Kay, D. A. R., and McLean, A. Effect of Cr on the activity coeff. of S in liquid Fe-Cr-S alloys, (6) 146*h*.
Donkersloot, H. C., and van Vucht, J. H. N. Method of producing a basic powder for permanent magnets, P (10) 251*j*.
Donley, H. E. Method of forming metal oxide coatings on refractory substrates, P (8) 193*c*.
Donley, H. E., Rieser, R. G., and Wagner, W. E. Coated glass sheet and method for making, P (8) 192*c*.
Donnell, H. K. See Einthoven, W. G.
Donoghue, B. R. See Wilson, J. D.
Donohue, J. M. Cooling H_2O treatment—where do we stand? (9) 229*e*.
Donohue, J. M., and Sarno, C. V. Pollution abatement pressures influence cooling H_2O conditioning, (5) 115*g*.
Donohue, P. C. Si chalcogenides, P (2) 42*f*.
Dontsov, G., Vitter, G., and Deportes, C. Study of a fluorite-type phase in the system CeO_2-ZrO_2-CoO, (11) 282*j*.
Doquire, G. See Javaux, G.
Dore, R. F. Dry fine crusher, P (2) 44*b*.
D'Orefice, R. Tempered stemware and process of making, P (2) 35*b*.
Doremus, R. H. See Ricchezza, E. N.; Woods, K. N.
Doremus, R. H., and Turkalo, A. M. Crystallization of Li disilicate in Li silicate glasses, (9) 216*e*.
Doremus, W. See Walsh, P. J.
Dorn, L. See Podschus, E.
Dorn, L., Heinze, G., and Podschus, E. Process for the production of beadlike catalyst supports for high mechanical stressing, P (5) 117*j*.
Dornan, J. R. Molten glass shears, P (10) 245*f*.
Dornfeld, J. E., and Williams, S. B. Fusible ceramic capacitor, P (5) 112*e*.
Doroshenko, V. P. See Miroshnichenko, O. Ya.
Dorph, T. Apparatus for the hydraulic classification of solids, P (8) 203*j*.
Dorr, F. W. See Buzbee, B. L.
Dorrian, J. F. See Newnham, R. E.
Dorschner, O. See Hartmann, R.
Dorsey, J. J. See Wallis, G.
Dothan, M. See Asaro, F.
Doubrava, J., and Motycka, V. New method of connecting stoneware pipes with rubber sealing rings, (10) 246*a*.
Douglas, B. E. See Ho, Shih-Ming.
Douglas, F. C., Gregory, T. K., and Stielau, R. W. Mfg. C filaments of high strength and modulus, P (1) 9*a*.
Douglas, G. A., and Prokopec, J. C. Unscrambler for light bulb traying machine, P (7) 163*a*.
Douglas, R. W. See Burnett, D. G.
Douglas, T. B. See Ditmars, D. A.
Douglass, D. L. See Kumar, A.
Douglass, J. W. See Schroeder, J. B.
Douma, G. H. Dilatometer curve of Dutch heavy clays, (4) 83*d*. Influence of firing temp. and maturing time on the properties of the fired product, (4) 83*h*. Specific surface of Dutch heavy clays, (4) 83*g*.
Dutt, A. A. See Dennison, B. J.
Dove, D. B. See Hench, L. L.
Dowty, E. Crystal chemistry of titanian and zirconian garnet (I) review and spectral studies, (4) 95*e*.
Dozier, A. W., Wilson, L. K., Friebele, E. J., and Kinser, D. L. Correlation of structure and electrical properties of 55FeO-45P_2O_5 glass, (8) 189*d*.
Draca, C. Method for the production of abrasive brushing elements, P (9) 213*e*.
Draeger, T., and Winter, E. Determination of SiO_2 in glass, (8) 204*g*.
Dragmire, M. B. See McDonald, B. A.
Drago, G. G. Drago-Korach "sandwich" procedure for rapid firing in a walking-beam kiln, (2) 45*e*.
Dragoman, I. See Dragomir, C.
Dragomir, C., Deica, N., and Dragoman, I. Making and use of new refractory cements, (3) 60*f*.
Drake, C. F., and Amos, R. W. J. Delay line glass, P (9) 218*g*.
Drakeford, R. W., and Quinn, C. M. Stoichiometry limits in NiO and Fe_2O_3, (5) 124*g*.
Drangeid, K. E., Mohr, T. O., Statz, H. F., and von Muench, W. Schottky-barrier FET, P (2) 42*g*.
Dravnieks, F. See Smith, S. R. P.
Dreeben, A. B. See Dalal, V. L.; Southgate, P. D.
Dreger, E. A. Abrasive plumber's tool, P (5) 101*g*.
Dreher, E. J. Preformed wall section molding apparatus, P (5) 108*g*.
Dressel, W. G. See Germain, A. G.
Dresselhaus, G. See Pine, A. S.
Drew, C. J. See Bates, C. H.
Drewry, H. S. Apparatus for and method of controlling rotary kiln operation, P (6) 143*c*.
Dreyer, D. Wheaton Glass gets all new electric furnaces, (5) 106*h*.
Dreyling, A. P., and Dreyling, L. J. Refractory [cement] composition, P (8) 197*b*.
Dreyling, L. J. See Dreyling, A. P.
Drickamer, H. G. See Holzapfel, W. B.
Driessen, A. J. G. C. See Jacobs, C. A. J.
Driessens, F. C. M., Giller, H. F. J. I., and Veeneman, D. Method of mfg. a ceramic polycrystalline magnetically anisotropic spinel ferrite body, P (3) 65*i*.
Driscoll, R. E. Hydrolysis of SiF_4, P (8) 207*e*. Mfg. pigmentary SiO_2, P (8) 207*e*.
Driscoll, R. E., and De Cuir, G. L. Generation of SiF_4, P (10) 257*e*.
Drittler, K., and Luhleich, H. Method of making nuclear fuel elements, P (3) 68*e*.
Driver, M. C. Low-thermal impedance FET, P (8) 201*b*. See Page, D. J.
Driver, M. C., and Geisler, M. J. Process for producing self-aligned gate FET, P (10) 252*c*.
Drobasheva, T. I., and Bergman, A. G. System of the chlorides of K, Sr, and Pb, (5) 124*e*.

Drobot, D. V., Korshunov, B. G., and Nad, B. S. Disproportionation of $ReCl_3$ in the presence of alkali metal chlorides, (8) 208*e*.
Drofenik, M. See Kolar, D.
Drost, W. See Conde, R. M.
Drozdova, T. A. See Mamykin, P. S.
Drozdowicz, K. P., Fowler, W. R., and Averkiou, G. Low saturation resistance, low offset voltage monolithic analog switch, P (9) 225*h*.
Drummond, W. W. Glass fiber forming and supply package, P (10) 244*i*. See Irwin, W. T.
Dryden, W. G. Achieving consistent results with thick-film, (3) 62*d*.
Dryon, J. M. Device for the scoring of a glass sheet, P (1) 3*j*.
Dubaele, M. Fining and redissolving of gas bubbles in glasses, (7) 159*j*.
Dubble, R. D. Glass container test apparatus, P (3) 58*g*. See Hall, T. H., Jr.
Dubinin, M. M. See Belen'kaya, I. M.
Dubinin, M. M., Isirikyan, A. A., and Babaev, P. I. Determination of the specific area of porous solids from the immersion heat data, (2) 44*g*.
Dubinin, V. P. See Pisarenko, G. S.
Du Bois, F. M. Glass mold—how to improve its use, (7) 159*c*.
Dubois, J. See Millet, J.
Dubok, V. A., and Tyutkalo, L. I. High-temp. compatibility of refractory metals with Sc_2O_3, (10) 246*i*.
Duchateau, J., Descamps, M., and Savaete, B. Comparison of analytical results obtained by flame emission and atomic absorption, (8) 204*j*.
Dudash, J. J., and Searcy, A. W. Mp, vapor pressure, and heat of vaporization of SnF_2, (4) 97*f*.
Dudchik, G. P., Polyachenok, O. G., and Novikov, G. I. Saturated vapor pressures of the chlorides of Y, Pr, Gd, Tb, and Dy, (8) 210*b*.
Dudek, H. J. Charge transfer effects in flat glass caused by electron irradiation, (9) 216*h*.
Dudkina, N. P. See Ostrikova, N. V.
Dudrova, E., and Kubelik, J. Influence of sintering conditions on the porosity and strength of compacts, (10) 247*a*.
Duecker, H. C., and Glemza, R. Process for the preparation of fine-sized Al_2O_3, P (10) 257*c*.
Duesler, E. See Andermann, G.
Duffau, L. See Chiron, B.
Duffey, D., Wiggins, P. F., and Senftle, F. E. Mineral-detection apparatus, P (5) 116*g*.
Duffy, J. A., and Ingram, M. D. Use of Tl(I), Pb(II), and Bi(III) as spectroscopic probes for ionic-covalent interaction in glasses, (5) 106*h*.
Duffy, J. A., and Macdonald, W. J. D. Oxidation states and stereochemistries of some Pt group metals in sulfate and bisulfate melts and glasses, (2) 32*f*.
Duffy, J. J. Metal plating of substrates, P (3) 66*c*.
Duffy, J. J., and Sims, S. D. Thermometer trimming method and apparatus [laser], P (5) 107*h*.
Duffy, M. C., and Hudson, R. L. Method of determining impurity profile of a semiconductor body, P (8) 201*j*.
Duffy, M. C., Schumann, P. A., Jr., and Yeh, Tsu-Hsing. Method of making or modifying a *pn* junction by ion implantation, P (7) 169*j*.
Duffy, M. T. See Carnes, J. E.; Corish, J.
Duffy, M. T., and Revesz, A. G. Interface properties of Si-(SiO_2)-Al_2O_3 structures, (9) 236*i*.
Dufresne, J. P. See Buzzi, U.
Duga, J. J. See O'Hara, M. J.
Dugdale, R. See Habashi, Fathi.
Dugdale, R. A., and Ford, S. D. Growing of crystals using electron beam heating and annealing, P (4) 88*b*.
Dugger, C. O. Process for the synthesis of glass and single-crystal germanates of identical composition, P (10) 245*d*. Solid-state laser produced by a chemical reaction between a germanate and an oxide dopant, P (3) 67*i*.
Duguay, M. A., and Hansen, J. W. Dispersion compensation in lasers, P (10) 244*c*.
Duhart, P. See Maurel, P.
Dukai, J. See Kacsalova, L.
Duke, D. A. See Giffen, J. W.
Duke, P. J. See Helgeland, W.
Duma, G., and Lengyel, I. Calcareous mortars with vegetable fibers, (11) 265*i*.
Dumbaugh, W. H., Jr. See Giffen, J. W.
Dumbaugh, W. H., Jr., Flannery, J. E., and Hares, G. B. Opal glass compositions, P (8) 193*h*. Opal glass compositions comprising CaF_2, P (10) 245*h*.
Dumesnil, M. E., and Hewitt, R. R. Some recent developments in fused glass films on semiconductor devices, (2) 39*c*.
Dumesnil, M. E., Hewitt, R. R., and Bozarth, J. L. Low-expansion, low-melting Zn phosphovanadate glass compositions, P (7) 162*g*.
Dummann, C. Aeration system and method of fabrication, P (3) 60*c*.
Dunbar, J. D. Glass armor fabrication, P (11) 270*i*.
Duncan, D. M. Deposited Si diffusion sources, P (9) 225*b*.
Duncan, J. F. See MacKenzie, K. J. D.
Dunham, K. R. Solid state photoresist technology, (3) 63*j*.
Dunlap, G. H. Method and apparatus for joining 2 glass parts or articles, P (8) 193*i*. See Bode, W. W.
Dunlap, G. H., Kobylak, A. M., and Miller, J. E. Downdrawing method for producing very thin glass sheets, P (4) 81*f*.
Dunlap, H. L. Chemical milling of SiC, P (1) 8*j*. Method for bonding contacts to and forming alloy sites on SiC, P (7) 169*d*.
Dunlop, A. Method of carbonizing refractory molds, P (11) 272*e*. Method of making multilayer shell molds, P (3) 61*h*.
Dunn, J. W. See Smith, Roy E.
Dunn, R. S. See Canning, M. L.; Sloan, B. J., Jr.
Dunn, S. A., Rakestraw, L. F., and Cunningham, R. E. Method for forming fibers and filaments directly from melts of low viscosities, P (8) 193*j*.
Dunning, R. See Parry, R. J.
Dunstone, P. H. Comparative prices of load-bearing brickwork and concrete walling, (9) 220*e*.
Duperroy, M. See Plumat, E.
Dupeux, M. Firing of porcelain by natural gas or propane in kilns fitted with flameless-combustion burners, (2) 45*f*.
Duplex, P. See Globus, A.
Duquenoy, G. New solid-state synthesis of alkaline salts of elements in their higher valence states, (6) 150*a*.
Duran Botia, P. See Alvarez-Estrada, D.
Durand, F. Coupled growth of eutectic alloys, (8) 199*b*.
Durczewski, K. Field-dependent phase transitions of uniaxial ferromagnets, (4) 96*g*.
Durden, L. R. See Eusner, P. R.
Durgin, C. B. See Thompson, J. H.
Durham, C. T., Jr. Method for optimum mounting of piezoelectric ceramic filter elements, P (3) 66*c*.
Durham, J. J. Better finishing with coated abrasive belts, (11) 265*d*.
Durham, K. M., Jr., and Plumlee, W. W. Si resistor, P (4) 90*g*.
Durif, A. See Bagieu-Beucher, M.; Grenier, J. C.; Rakotomahanina-Rolaisoa, E.
Durinck, R., and Boussekey, B. Support for rotary furnaces, P (6) 143*d*.
Duschatko, R. W. See Bradley, J. S.
Dusek, J. T., and White, G. D. Fabrication of UO_2 helices for irradiation creep measurements, (3) 68*d*.
Dusenbery, E. B. Ancient glass in the collections of Wheaton College, (11) 265*h*.
Dusil, J. See Strnad, Z.
Dusollier, G. See Robredo, J.
Dusollier, G., and Robredo, J. Interpreting glass fiber drawing mechanism by DTA, (7) 159*d*.
Duthoit, J. Temp. control of chemical tempering of solid glass or vitrocrystalline bodies, P (4) 83*a*. See Plumat, E.
Duthion, L., and Seguela, C. J. M. Feed unit for a fuel burner, P (8) 206*c*.
Dussel, G. A. See Boer, K. W.
Duttera, R. B., and Macshane, G. H. Tubular composite self-shielded arc-welding electrodes, P (5) 105*e*.
DuVarney, R. C., Garrison, A. K., and Thorland, R. H. Electron paramagnetic and nuclear double resonance of F^+ centers in BeO single crystals, (6) 147*i*.
Duwell, E. J., and Hong, In Sun. Method of abrading Ti and Ti alloys, P (3) 53*g*.
Duyster, H. P. J. See Ryan, J. H.
Dvinin, V. I. See Shchepetkin, A. A.
Dvorina, I. A., Popova, O. I., and Derenovskaya, N. A. Preparation and some chemical properties of Mg_2Si, (3) 60*g*.
Dvorkin, L. I., Boyarshinov, E. G., and Pivovarov, V. S. Hydrophobically activated cement, (8) 186*g*.
Dworak, U. See Dawihl, W.
Dwyer, F. G. Production of synthetic faujasite, P (5) 118*a*.
D'yachkov, P. N. See Khoroshavin, L. B.
Dybwad, G. L. *c*-axis orientation of sputtered ZnO films, (7) 166*g*.
Dyczek, J. R. L. See Crennan, J. M.
Dyczek, J. R. L., and Taylor, H. F. W. Influence of additives on the autoclave reactions of β-Ca_2SiO_4 and β-Ca_3SiO_5 at 170°C, (7) 156*i*. X-ray determination of tobermorite, quartz, and α-Ca_2SiO_4 hydrate in autoclaved Ca silicate materials, (5) 116*d*.
Dyer, L. D. Production of semiconductor material, P (6) 139*h*. Production of single-crystal semiconductor material, P (6) 139*h*.
Dyla, J. F. Electroprecipitation, P (1) 16*h*.
Dymchenko, V. A. See Radomysel'skii, I. D.
Dymchuk, A. P. Additional feeding of a 4.5 x 170 m rotary kiln, (8) 185*h*.
Dyment, J. C., Paoli, T. L., and Ripper, J. E. Semiconductor lasers utilizing internal saturable absorbers, P (7) 170*b*.
Dymova, T. N., and Bakum, S. I. Thermal decomposition of K and Na hydroaluminates, (8) 211*i*.
Dyni, J. R. Process for extracting Al compounds from dawsonite and dawsonitic oil shale, P (5) 117*i*.
Dzhigit, O. M., Kiselev, A. V., Mikos, K. N., Muttik, G. G., and Rakhmanova, T. A. Heats of adsorption of H_2O vapor on X-zeolites containing Li^+, Na^+, K^+, Rb^+, and Cs^+ cations, (1) 22*b*.
Dzhurinskii, B. F., Kizel, V. A., and Denisov, Yu. V. Effect of halogens on the luminescence of rare-earth ions in borate glasses, (9) 216*i*.
Dzhus, E. V. See Govorov, A. A.
Dzierzanowski, F. J. See Haden, W. L., Jr.

Eadie, G. P. Design and effect of furnace aerodynamics on burner behavior, (7) 174*e*.
Eadie, G. P., and Halliday, W. Suspended roof for high-temp. industrial furnaces, P (3) 59*h*.
Eagan, R. J., and Bergeron, C. G. Determination of H_2O in Pb borate glasses, (2) 32*e*.
Eagles, D. M. Effective masses in Zr-doped superconducting ceramic $SrTiO_3$, (5) 120*e*. Theory of transitions from large to nearly small polarons, with application to Zr-doped superconducting $SrTiO_3$, (5) 125*a*.
Eagles, G. J. See Ingram, D. J.
Eardley, R. P. Application of direct-reading spectrometry (II) determination of the major and minor constituents of ceramics by direct-reading spectrometry, (9) 230*g*. See Bennett, H.
Earhart, C. E. See Vincent, B. T., Jr.
Eastman, C., Elyard, C. A., and Warren, D. Effect of SiO_2 additions on the semiconducting properties of doped $BaTiO_3$, (7) 166*g*.
Eastman, D. E., Holtzberg, F., and Methfessel, S. I. Photoemission studies of the electronic structure of EuO, EuS, EuSe, and GdS, (6) 150*h*. Rare earth chalcogenide thermionic emission cathodes, P (4) 90*f*.
Eastwood, H. K. See Quon, H. H.
Eaton, C. J. Spark plug with an internal resistor, P (1) 14*h*.
Eaton, D. A. See Knowles, T. J.
Eberl, E. Concentration of Ca phosphates by calcination and the material balance, (2) 40*b*.
Ebert, E. See Badami, A. V.
Eckart, D. W. See Shappirio, J. R.
Eckerlin, P. Device for determining the crystallographic directions in single crystals by X rays, P (6) 142*d*.
Eckert, G. T. K. Brazing C bodies to other bodies of temp.-resistant materials, P (2) 37*e*.
Economopoulos, P. C., and Hart, T. W., Jr. Bipolar semiconductor random access memory, P (4) 87*f*.
Economy, J., and Anderson, R. V. BN fiber mfg., P (3) 61*b*.
Economy, J., and Lin, Rucy-Yuan. High-modulus BN fibers, P (9) 222*h*.
Economy, J., and Matkovich, V. I. Refractory [BN] fibers and method of producing same, P (4) 85*a*.
Edahiro, Takao. See Waku, Shigeru.
Edelman, F. H., and Mayer, S. E. Bi titanate film capacitor and method of mfg., P (2) 39*c*.
Eden, J. S. Oxidation catalyst and process, P (4) 94*d*.
Edgar, R. F., Martzloff, F. D., and Tompkins, R. E. Magnetic latch and switch using Corare earth permanent magnets, P (9) 225*i*.
Edgecumbe, J. See James, L. W.
Edin, R. E. Evaporation filament assembly, P (2) 40*g*.
Edmond, J. T. Measurements of electrical conductivity and optical absorption in chalcogenide glasses, (3) 56*e*.
Edmonds, J. C. Apparatus for blending pulverulent material, P (10) 254*h*.
Edraos, P. See Wang, P.
Edwards, A. See Loukes, D. G.
Edwards, A., and Loukes, D. G. Coating of glass on a molten metal bath, P (10) 243*j*.
Edwards, F. J. Method of mfg. [vitreous SiO_2] extrudates, P (8) 193*f*.
Edwards, G. B. See Darr, D. E.
Edwards, G. S., and Rushby, A. N. Structure of willemite films on Si, (7) 168*d*.
Edwards, R. K. See Battles, J. E.
Edwards, R. L. See Dee, P. L.
Effenberger, F. V. Circuit for accurate tuning of a YIG filter, P (9) 224*j*.
Efimova, R. P. See Gitterman, A. K.
Egami, Harutoshi. See Ichinose, Noboru.
Egan, R. T. Wet scrubber system, P (6) 141*h*.
Egashira, Kazumichi. See Manabe, Toyotaka.
Egashira, Kazumichi, Manabe, T., and Katsuraki, H. Effects of foreign Co^{2+} and Fe^{3+} ions on the magneto-optical properties of Gd Fe garnet, (6) 147*b*. Faraday rotation in $FeBO_3$ at 77°K, (3) 73*h*.
Eger, H. Method of producing integrated circuits, P (5) 113*b*. Method of separating semiconductor chips from a semiconductor substrate, P (9) 226*i*.
Egerton, L., and Thomson, J., Jr. Preparation of high density ceramic TiO_2 having low dielectric loss at microwave frequencies, (1) 11*h*. TiO_2 ceramic composition and hot-pressing method [reducing atm] for producing, P (5) 114*d*.
Egorova, T. N., Kurlina, E. V., Novikov, V. N., and Talerchik, B. A. Material intended primarily for mfg. thermistors, P (9) 226*a*.
Eguchi, Kiyohisa. See Nakashima, Hiroshi.
Eguchi, Kiyohisa, Tabata, S., and Tarumi, S. Effect of volatilization on the rate of acid-leaching in phase-separative borosilicate glass, (3) 55*d*.
Eguchi, Shiro. See Sugahara, Yujiro.
Egunov, V. P. See Berg, K. P.; Berg, L. G.; Ganiev, R. M.
Ehle, R. S. See Galginaitis, S. V.
Ehrcke, U. See Mahler, E.
Ehrenreich, L. C. Reinforced C and graphite articles, P (10) 248*c*. See Carlson, W. H.

Ehrlich, A. C. Influence of size effect on low-temp. electrical resistivity, (5) 116*f*.
Ehrlinger, H. P., III, and Jackson, H. W. Lower Miss. river terrace sand as a commercial source of feldspar, (3) 71*d*.
Eibschuetz, M., Cohen, R. L., and West, K. W. Moessbauer effect of ^{168}Er in Er orthochromite, (5) 122*c*.
Eicke, W. See Dawihl, W.
Eiduk, O. N. See Chaporova, I. N.
Eigner, E. See Remmers, K.
Eilenberger, R. F. Creating facade forms, (2) 30*d*. Decorating with coils, (2) 30*e*. Hollow-built sculpture, (2) 30*a*. Water whistle sculpture, (2) 30*g*.
Eilenfeld, H. W. See Stilley, G. W.
Eilers, G. J. See Green, P. S.
Eilers, L. H. See Root, R. L.
Einaga, Hisahiko. See Ishii, Hajime.
Einfalt, A. C. See Birner, R. A.
Einfalt, A. C., and Osborn, R. A. Method and [laser beam] apparatus for inspecting hollow glass articles, P (11) 270*d*.
Einthoven, W. G. High-voltage transistor structure having uniform thermal characteristics, P (3) 65*d*.
Einthoven, W. G., and Donnell, H. K. Method of mfg. semiconductor devices having high planar junction breakdown voltage, P (9) 226*d*.
Einthoven, W. G., Jetter, E. S., and Wheatly, C. F., Jr. Method for making transistors including base sheet resistivity determining step, P (10) 251*h*.
Eirich, G. See Eirich, W.
Eirich, W., and Eirich, G. Mixing machine, P (10) 254*f*.
Eisbein, P. Ceramic pigments and their behavior in glazes, (1) 9*j*.
Eisenmenger, E. See Beschke, H.
Eisenmenger, E., Kuhnert, O., Kuhlmann, R., Nauroth, P., and Tuerk, G. Process for the production of organically modified silicic acids and silicates, P (1) 20*h*.
Eisler, C., Jr. Multiple-station automated control device for glass thermometers, P (1) 5*f*.
Ekstrom, L. See Dismukes, J. P.
Ekstroem, T. Formation of ternary phases of Mo_5O_{14} and $Mo_{17}O_{47}$ structure in the Mo-W-O system, (4) 96*i*. Intermediary phases in the Nb_2O_5-MoO_3 and Ta_2O_5-MoO_3 systems, (11) 281*d*.
El-Assal, K., Bateson, S., and Urban, P. Ferroelectric perovskite compositions in the system $Pb(Zn_{1/2}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$, (8) 209*c*.
El-Batal, H. A. See Abou-El-Azm, A.
Elchin, V. I. See Yavorskii, I. A.
El-Daoushy, M. F. See Arafa, A. A.
Elderfield, R. Use of C in the blast furnace, (2) 37*a*.
Elgan, D. L. See Clark, L.
Elgan, D. L., and Hays, R. G. Al diffusions, P (10) 249*e*.
Elgenstierna, R. M. Method for forming composite building elements, P (4) 83*i*.
Elger, G. W., and Stickney, W. A. Production of high-purity synthetic rutile from a domestic ilmenite concentrate, (1) 20*h*.
El Din, A. M. S. See El Hosary, A. A.
El Din, H. D. T. See El Hosary, A. A.
El Hosary, A. A., El Din, H. D. T., and El Din, A. M. S. Potentiometric study of the reaction between B_2O_3 and the carbonates of the alkali and alkaline earth metals, (2) 48*i*.
Eliseev, S. S. See Glukhov, N. A.
Elkins, P. E. See Besser, P. J.
El-Kolali, A. E. G. A., and Gad, G. Determination of free SiO_2 in ceramic raw materials, (7) 173*a*.
Elli, M. See Corsini-Mena, A.
Ellinger, F. C. Porcelain enamel cover coat milling, P (3) 54*g*.
Elliot, I. R. Method of making continuous fiber bundle, P (7) 162*d*.
Elliott, C. H., Jr., and McDaniel, C. V. Preparation of high-SiO_2 faujasite, P (5) 117*h*.
Elliott, J. F. See Yarwood, J. C.
Ellis, B., Clark-Monks, C., and Rowan, K. Characterization of adsorption onto glassy pyrogenic SiO_2 surfaces, (9) 216*g*.
Ellis, B., and McDonald, M. P. Broad-line NMR studies of α-D glucose and penta-acetate in the crystalline and glassy states, (3) 55*b*.
Ellis, C. D. See Harris, B.
El'manova, N. A. See Glukhov, N. A.
Elmgren, J. A., and Rodite, R. R. R. Sputtering apparatus having a concave source cathode, P (9) 228*b*.
Elo, A., Jr., and Broersma, F. R. Process for preparing synthetic crystalline zeolitic Na aluminosilicate, P (10) 257*e*.
El-Rafei, E. A. Reversible phase transformation in the system CaO-Cr_2O_3-O, (3) 75*b*.
El-Rafei, E. A., and Kamel, M. R. Highly refractory basic concretes (I) preparation and technological properties in relation to certain factors, (8) 195*g*.
El-Rafei, E. A., Kamel, M. R., and Gad, G. M. Preparation and properties of some highly refractory basic cements, (2) 31*a*.
El Roudi, A. M. See Hussein, M. K.
El Shami, F. A. See Fitzer, E.
Ely, R. E. Strength of TiO_2 and Al silicate under combined stresses, (8) 210*j*.
Elyard, C. A. See Eastman, C.
Emanuelson, R., and Luoma, W. L. Method of mfg. dense graphite structures, P (4) 84*e*.
Embury, J. D. See Daw, J. D.
Emeis, R., Haus, J., and Keller, W. Device for crucible-free zone melting having sealing means for a sliding member, P (7) 168*d*.
Emeis, R., and Keller, W. Apparatus for rod displacement crucible-free zone melting, P (2) 39*b*.
Emerson, R. B. See Kelly, A. C.
Emery, J. A. A., Jackson, G. N., and Priestland, C. E. D. Targets for rf sputtering apparatus, P (3) 67*j*.
Emiliani, T., Ravaglioli, A., and Missiroli, A. Pb in ceramic containers. Definition of a new hygienic-sanitary norm, (7) 165*d*.
Emiliani, T., and Vecchi, G. Modern classification of ceramics, (4) 100*a*.
Emmett, R. C., Jr., and Dahlstrom, D. A. Method for steam drying filter cake, P (10) 254*f*.
Emoto, Masayuki. See Iimura, Tsutomu.
Enache, M. See Abramovici, R.
Enari, Hideo. See Nagasima, Naoyuki.
EnDean, H. J. See Beach, H. J.
Endo, Tetsuzo. See Ishihara, Toshio.
Endo, Yasuo. See Kijima, Goro.
Engbert, R. Integrated semiconductor circuit having increased barrier layer capacitance, P (5) 112*i*. Method of producing 1 or more large integrated semiconductor circuits, P (4) 89*j*. Semiconductor circuit arrangement with integrated base leakage resistance, P (4) 90*a*.
Engebretsen, J. E. See Selte, K.
Engel, H. J. See Schat, B. R.
Engel, O., Engelmann, J., and Wilkens, K. Rotary table jarring apparatus for producing large molded C bodies, P (2) 37*f*.
Engel, W. T. Glass tube cutting machine with end polisher, P (4) 82*c*.
Engeler, W. E. Voltage-variable capacitor with controllably extendible *pn* junction region, P (2) 43*b*. See Brown, Dale M.
Engeler, W. E., and Garfinkel, M. Electromechanical filters with integral piezoresistive output and methods of making same, P (2) 40*d*. MIS device and method for storing information and providing an optical readout, P (3) 66*a*. Semiconductor fabrication technique and devices formed thereby utilizing a doped metal conductor, P (1) 14*j*.
Engelhardt, H. P. See Kuenkele, R.
Engelleitner, W. H. Pellets cut costs, improve quality, (10) 243*h*.
Engelmann, J. See Engel, O.
Engels, K. Stirring mill, P (5) 115*j*, P (7) 172*h*.
Englert, G., and Wittmann, F. Study of properties of adsorbed H_2O in hydrated Ca_3SiO_5, (8) 187*h*.
Englert, G., Wittmann, F., and Nussbaum, M. Study of the conditions relating to the combining of H_2O in hardened cement paste, (8) 187*j*.
English, A. T., and Turner, P. A. Technique for enhancing the stability of transition metal-Au thin-film composites, P (10) 253*g*.
Engmann, E. Rational process for producing tiles by continuous rapid-fire walking-beam kiln and experience during the 1st year of operation, (5) 111*a*.
Enguerrand, M. See Baudran, A.
Ensign, T. C. See Henderson, B.
Ensign, T. C., Chang, Te-Tse, and Kahn, A. H. Hyperfine and nuclear quadrupole interactions in Cu-doped TiO_2, (6) 148*e*.
Ensslin, F. H. Rf sputtering apparatus, P (10) 252*e*.
Entelis, F. S., and Nakhamkin, M. A. Study of ultrasonic treatment of plastic ceramic bodies, (8) 198*j*.
Entin, Z. B. See Kravchenko, I. V.
Entwistle, S. D. See Quon, H. H.
Enz, U., and Teale, R. W. Photomagnetic effects, (9) 237*e*.
Epik, A. P. See Karpinos, D. M.
Epp, D. See Manring, W. H.
Eppler, R. A. Composition and process for glazing ceramic ware, P (10) 248*i*. Formation of Pr-doped zircon colors in presence of halides, (1) 2*j*. Microstructure of TiO_2-opacified porcelain enamels, (1) 2*i*.
Erb, D. M. See Dill, H. G.
Erdelyi, T. See Csetenyi, J.
Erdman, W. C. Zr mask for semiconductor fabricated using alkaline etchants, P (10) 253*j*.
Erdosi, F. History of the brick industry in Southern Hungary (I), (5) 108*f*; (II, III), (6) 134*a*.
Eremeeva, A. S. See Rogozhin, Yu. V.
Eremenko, V. N., Lukashenko, G. M., and Sidorko, V. R. Thermodynamic properties of Mn silicides. Communication 3, (10) 261*d*.
Eremenko, V. N., Naidich, Yu. V., and Lavrinenko, I. A. Liquid-Phase Sintering, B (1) 25*h*.
Eremenko, V. N., and Velikanova, T. Ya. Phase equilibria in the Mo-TiC-Ti region of the ternary system Mo-Ti-C. Character of solidification of alloys and projection of the solidus surface (I), (10) 260*g*.
Eremin, N. I., and Erusalimskii, M. I. Study of thermal transformations of kaolin by a chemical method, (7) 181*i*.
Eremin, N. I., Kocherzhinskaya, V. F., and Mazel, V. A. Influence of ratio Al_2O_3:SiO_2 in raw material on physicochemical properties of self-friable aluminocalcium sinters, (7) 156*c*.
Erhard, A. E., and Allison, J. B. Process for recovery of Nb, P (5) 118*b*.
Erhard, M. See Harris, T. J.
Erickson, L. H. See Fogelberg, C. V.
Ericson, J. A. See Nadrich, J.
Eriksson, G. Thermodynamic studies of high-temp. equilibria (III) SOLGAS, a computer program for calculating the composition and heat condition of an equilibrium mixture, (11) 283*a*.
Eriksson, L. See Picraux, S. T.
Ermakov, I. S. See Meshengisser, M. Ya.
Ermel, D. See Mindrup, W.
Ermolenko, N. N. See Shalimo, Z. N.
Ermolenko, V. A. See Norkin, I. M.
Erni, H. Preparation and homogenization of raw mix, (8) 187*h*.
Ernick, F. G., New, T. C., and Walczak, D. A. Epitaxial-base high-speed *pnp* power transistor, P (6) 137*e*.
Erno, B. P. See McCurdy, K. G.
Ernst, H., Semmler, J., Vohler, O., and Rubisch, O. Hollow electrode assembly of C having dense graphite junction nipple, P (8) 196*a*.
Errey, J. R. Transverse and longitudinal correlations in H-bonded ferroelectrics, (5) 125*j*.
Erusalimskii, M. I. See Eremin, N. I.
Eryou, N. D. See Jeryan, R. A.
Esaki, Hideya. See Naomoto, Susumu.
Esaki, L. See Tsu, R.
Esaki, L., Howard, W. E., Jr., and Tsu, R. Semiconductor bulk oscillator, P (3) 67*j*.
Esaki, L., Ludeke, R., and Tsu, R. Semiconductor device with superlattice region, P (3) 67*d*.
Escaich, S. Sealing materials for glazing purposes (II) specification, (7) 160*d*.
Eschnauer, H. R., and Steine, H. T. Coating of metal powders on molds and plungers, (7) 158*i*. Use of hard alloy powders for molds and cores in the glass industry, (5) 106*g*.
Escott, G. K. See Anderson, Y. R.
Escoubes, M., Gielly, J., Quinson, J. F., and Murat, M. Microcalorimetry and dielectric measurements of adsorption of H_2O vapor on clay minerals, (9) 236*j*.
Esnoult, M. R. G., and Ayme-Jouve, M. L. Upgraded cast refractory products, P (9) 222*j*.
Estes, M. F. See Rasquin, J. R.
Estour, H. Transformations in glasses due to the electron beam of a microprobe, (11) 269*h*.
Ettinger, B. L., and Wolosin, S. M. Refractory porous [cellular] bodies, P (9) 222*g*.
Ettmayer, P. See Kieffer, R.
Ettre, K., and Castles, G. R. Pressure-fusible tapes for multilayer structures, (6) 136*j*.
Eu, B. C. See Morokuma, K.
Eusner, P. R., Durden, L. R., and Slack, L. H. Unusual electrical effects in As-Te semiconducting glasses, (2) 33*f*.
Eustacchio, C. Automatic setting of transportable stacks, (5) 108*a*. Stiff-mud pressing vs wet pressing—a comparison of economy, (5) 115*j*.
Eustache, J., and Magnan, R. Method for determining resistance of mortars to sulfate attack, (6) 129*d*.
Evans, A. G., and Davidge, R. W. Biaxial stress method for the determination of the strength of sections cut from glass containers and the size of the critical Griffith flaws, (7) 158*d*.
Evans, C. C. Furnace for mfg. ceramic whiskers, P (10) 256*f*.
Evans, D. E. See Stewart, J. E.
Evans, D. J. See Blecherman, S. S.
Evans, E. H. See Swanson, H. E.
Evans, E. L. See Thomas, J. M.
Evans, G. S. Electric discharge lamp having improved Hg-vapor control assembly, P (2) 33*j*. Hg vapor discharge lamp and pressure-regulating means therefor, P (3) 58*i*.
Evans, J. D., and Taylor, D. W. Method of annealing with an MgO separator containing a decomposable phosphate, P (2) 31*i*.
Evans, J. H. See Mahajan, S.
Evans, J. L. Trends in blast furnace refractories and design, (2) 37*a*.
Evans, J. L., and Vannorsdall, J. W. Ceramic top ir cooking assembly, P (2) 33*f*.
Evans, J. W., and Foster, R. G. Method of fabricating glass orifice plates, P (3) 59*c*.
Evans, L. W., Faria, S., Slobbe, W. W., and Williams, Lyle K. CRT screen comprising a single phosphor system, P (1) 12*c*.
Evans, W. H. See Parker, V. B.
Evans, W. J., Johnston, R. L., Scharfetter, D. L., and Seidel, T. E. Solid-state hf source, P (4) 90*i*.
Evdokimova, T. M. See Borodai, F. Ya.
Everest, D. A. See Chilton, H. T. J.
Everest, D. A., Sayce, I. G., and Selton, B. Preparation of ultrafine Al_2O_3 powders by plasma evaporation, (7) 175*e*.
Everhart, J., and Felder, J. L. Process for fast-fire ceramic tile using nepheline syenite and clay, P (7) 166*b*.
Everhart, T. E., and Hoff, P. H. Determination of kV electron energy dissipation vs penetration distance in solid materials, (7) 177*a*.
Eversdyk, M. Apparatus for forming a member from a slurry of material, P (1) 8*i*.
Evey, G. H., and Carson, J. B. Method of sealing glass to metal, P (4) 82*f*.
Evrard, O. Magnetic properties of Fe(II) oxide and of its solid solutions—importance of deviation from stoichiometry, (4) 97*c*.
Evseenko, N. K. See Yam, V. M.
Evseev, Yu. N. See Rakhmatulin, Ya.

Evseeva, V. B. See Kozachenko, E. L.
Evstrop'ev, K. S., Leshchinskii, D. A., and Medvedeva, G. V. New grinders based on synthetic plastics for fine grinding of glass, (8) 191*d*.
Evstyukhin, A. I. See Kilin, V. S.
Evtukh, V. V. See Norkin, I. M.
Evtushenko, O. V. See Burykina, A. L.
Evtushok, T. M. See Burykina, A. L.
Evtushok, T. M., and Burykina, A. L. Interaction of graphite and pyrographite with Ti, Nb, Mo, and W disilicides, (10) 259*c*.
Ewers, J. Perth Potters' Club, (4) 78*a*.
Eyring, E. M. See Schelly, Z. A.
Eyring, H. See Krausz, A. S.
Eyring, L. (editor). Advances in High Temp. Chemistry (Vol. 3), B (6) 153*f*; (Vol. 4), B (8) 212*a*.
Ezaki, Shingo. See Ito, Saburo.
Ezekiel, H. M. Method of stabilizing acrylic polymer fibers prior to graphitization, P (9) 222*b*. Preparation of graphite yarns, P (4) 84*i*.

Fabbi, B. P. Refined fusion X-ray fluorescence technique and determination of major and minor elements in silicate standards, (9) 231*i*.
Fabry, M. See Tamas, F. D.
Facey, O. E., and Sibley, W. A. Optical absorption and luminescence of irradiated MgF_2, (6) 150*d*.
Fachn, J. V. See Bernath, L.
Facquet, L. See de Vaulchier du Deschaux, L.
Fagen, E. A., and Fritzsche, H. Electrical conductivity of amorphous chalcogenide alloy films, (6) 136*h*. Optical properties of amorphous chalcogenide alloy films, (6) 136*i*.
Fagerholt, G. R. Apparatus for grinding mineral materials, P (4) 92*h*. Apparatus for making ultrafine cement, P (2) 31*d*.
Faggin, F. See Klein, T.
Fagiuoli, M. Production controls in a small or medium industry, (7) 172*g*.
Fahey, R. E. See Reed, T. B.
Fahmy, M., Park, M. J., Tomozawa, M., and MacCrone, R. K. Magnetic properties, microstructure, and ultrastructure of partially crystallized B_2O_3-BaO-Fe_2O_3 glass, (11) 268*h*.
Fahrback, D. O. E., Howat, D. D., and Jochens, P. R. Comparison of techniques for determining the resistance of refractories to slag attack, (1) 6*j*.
Failing, R. C. Method of making a sleeve-type metal to glass to metal to metal seal, P (2) 34*f*.
Fain, I. A., Kamenetskii, S. P., Rabinovich, M. A., Grigor'ev, I. V., Min'kov, D. B., and Krasotin, K. A. Production technology and pore-forming mechanism in insulating perlite-chamotte products, (8) 195*c*.
Fair, R. B. Analysis and design of ion-beam deposition apparatus, (5) 116*a*.
Fairchild, A. R. [Graphite] pallet and mask for substrates, P (10) 250*f*.
Fairfield, J. M., Joshi, M. L., and Schwuttke, G. H. [Diffusion] method for making semiconductor junction devices, P (7) 168*e*.
Fairholme, R. J., Gill, G. P., and Marsh, A. Magnetic properties of rare earth orthoferrites grown by a floating zone technique, (2) 38*i*.
Faktor, M. M., Newns, G. R., and Fiddyment, D. G. Treatment of Al_2O_3 surfaces with molten V_2O_5, P (3) 62*a*.
Falce, L. R. Method for making dielectric-to-metal joints for slow-wave structure assemblies, P (3) 65*i*.
Falce, L. R., and Scott, A. W. Slow wave circuit and method of fabricating, P (2) 42*g*.
Falicov, L. M., and Kimball, J. C. Simple model for semiconductor-metal transitions—SmB_6 and transition-metal oxides, (6) 151*e*.
Falls, J. W. Method of producing glare-reducing glass surface. P (2) 34*g*.
Fan, G. J. See Wieder, H.
Fang, F. F., and Fowler, A. B. Process for making MOSFETS, P (10) 252*b*.
Fanti, R. See Basche, M.
Faraci, J. P. See Boulogne, A. R.
Farber, M. See Srivastava, R. D.
Farber, M., Srivastava, R. D., and Uy, O. M. Mass spectrometric determination of the thermodynamic properties of the vapor species from Al_2O_3, (11) 281*e*.
Farfaletti-Casali, F. See Buzzi, U.
Faria, S. Process for preparing Sb phosphate, P (6) 144*c*. See Evans, L. W.
Faria, S., and Harrigan, D. J. Zn-Cd sulfide cathodoluminescent screen, P (7) 170*h*.
Faria, S., and Palumbo, D. T. Multiple activation of YVO_4. (2) 48*b*.
Faria, S., and Williams, Lyle K. Cathodoluminescent phosphor compositions [ZnS:CdS], P (7) 168*j*.
Farkas, P. Method of coating diamond particles with metal, P (7) 155*f*.
Farmer, A., and Bogdan, J. R. Method for producing TiO_2, P (6) 144*d*.
Farmer, F. L. Apparatus for use in the manufacture of semiconductor devices [wafer slice], P (9) 224*i*.
Farmer, V. C., and Russell, J. D. Interlayer complexes in layer silicates—structure of H_2O in lamellar ionic solutions, (3) 74*b*.
Farnum, E. H. See McVay, G. L.
Farrand, W. A. Process for producing magnetic transducer with narrow sensing tip, P (9) 227*j*.
Farrar, N. S. Influence of platen friction on the fracture of brittle materials, (7) 178*e*.
Farrar, R. T. See Morrison, C. A.
Farrell, R. Lead attachment to high-temp. devices, P (9) 225*f*.
Farrington, G. M., Treffner, W. S., and MacKenzie, G. D. Unburned basic refractory brick and method of making, P (2) 37*f*.
Fasbender, H. Tandem grinding plant for raw meal, (8) 188*d*.
Fasnacht, J. J. See Vanderbilt, B. M.
Fassett, J. R. Doped-oxide FETs, P (1) 12*h*.
Fastre, J. J. J. Ultrasonic welding device with a suction rod for treating microsemiconductor blocks, P (4) 91*b*.
Faulkner, R. A. See Henry, C. H.
Faulstich, M., and Neuroth, N. Glass having a low ultrasonic propagation time-temp. coeff., P (2) 34*f*.
Faurie, J. P., and Kohlmuller, R. Phases $MLn_4Mo_7O_{16}$ and $M'Ln_8Mo_4O_{22}$ (M=Cd, M'=Ca,Sr) with a fluorite-derived structure. Structural hypothesis for the phase $CdTm_4Mo_7O_{16}$, (4) 98*d*.
Fava, J., Le Flem, G., Devalette, M., Rabardel, L., Coutures, J. P., Foex, M., and Hagenmuller, P. Design of a high temp. furnace used in the study of ThO_2-SrO and ThO_2-BaO systems, (7) 172*j*.
Favreau, L. J. Field emission cathode with metallic [La] boride coating, P (4) 87*j*. Method for fabricating La boride cathodes, P (4) 80*c*.
Faxon, R. C. Composite thermistor temp. sensor having step-function response, P (10) 250*c*.
Faxon, R. C., and McGovern, R. T. Method for making ceramic titanate elements and materials therefor, P (5) 113*h*.
Fay, H. Electrooptic modulation of light propagating near the optic axis in $LiNbO_3$, (1) 11*e*.
Fay, H., Alford, W. J., and Dess, H. M. Linear niobate harmonic generator and method, P (5) 113*b*.
Faye, G. H. Relation between crystal-field splitting parameter, "Δ_{VI}" and M_{host}-O bond distance as an aid in the interpretation of absorption spectra of Fe^{2+}-bearing materials, (11) 278*b*.
Featherston, R. H. Continuous precipitation of Al_2O_3 hydrate, P (1) 20*b*. Precipitation of Al_2O_3 hydrate, P (6) 144*g*.
Fedelinski, K. See Laskowski, J.
Feder, F. R. Disk mill, P (3) 69*d*.
Feder, J. See Pytte, E.
Fedorenko, Yu. G. See Shpigun, A. A.
Fedoritenko, I. I. See Zapolsky, A. K.
Fedorov, N. F. Classification of and research on new binding materials, (2) 30*h*.
Fedorov, P. I., and Il'ina, N. I. Binary systems of In chloride and the chlorides of Ca, Mn, and Te(IV), (5) 118*j*.
Fedorov, P. I., and Lovetskaya, G. A. System $GaCl_2$-$InCl_2$. (8) 211*e*.
Fedorov, P. I., Lovetskaya, G. A., and Sharkadi, E. E. System $GaCl_3$-$SrCl_2$, (8) 211*e*.
Fedorov, T. F. See Sobolev, A. S.
Fedoryakin, B. F. See Syrkin, Ya. M.
Fedoseev, D. V. See Aleshin, B. N.
Fedoseeva, T. I., Sobolev, E. V., and Takher, E. A. Obtaining strong acid-resistant and wear-resistant glass-ceramic material BL (sitall) from fused basalt, (8) 191*f*.
Feenstra, R. Diamond bit, P (5) 101*f*. Diamond bits having diamonds positioned in concentric circles on the drilling face, P (1) 1*g*.
Fefferman, G. B. Method of depositing an adherent Au film on the surfaces of a suitable substrate, P (7) 169*g*. Method of depositing in situ a ceramic or glass film on the surfaces of a substrate, P (3) 65*e*. Technique for the fabrication of a photolithographically definable glass-covered Au conductor pattern, P (10) 253*g*.
Fehder, B. J. See Franklin, D. L.
Fehlner, F. P. Electrodeposition of metals in porous glass, (9) 217*g*.
Fehr, B. H. P., and Gascon, J. Process for producing basic Zr sulfate and ZrO_2 from Na silicozirconate, P (6) 144*c*.
Fehrenbacher, L. L. Stabilized ZrO_2 and HfO_2 compositions, P (4) 85*b*.
Fehrenbacher, L. L., Bailey, F. P., and McKinnon, N. A. Compressive creep of Y_2O_3 rare earth stabilized Zr storage heater refractories, (3) 60*d*.
Feige, F. Developments in raw material grinding in cement factories, (6) 128*i*.
Feige, R. Sintering properties of Al_2O_3 as a function of thermal and mechanical pretreatment, (5) 123*h*.
Feigelson, R. S. See Amzallag, E.
Feinleib, J. See Pidgeon, C. R.
Feinleib, J., Scouler, W. J., Dimmock, J. O., Hanus, J., Reed, T. B., and Pidgeon, C. R. Spin-polarized splittings in the temp.-dependent reflectance of EuO, (6) 151*j*.
Feinstein, L. G. See Margoninski, Y.
Feklichev, E. M. See Timofeeva, N. V.
Feld, I. L. See Lamont, W. E.; Stanczyk, M. H.; Tyrrell, M. E.
Felden, A. Elastic sieve bottom, P (9) 229*j*.
Felder, J. L. See Everhart, J.
Feldman, D., and Sibilia, J. T. Apparatus and method for separating scribed plates of brittle material, P (2) 39*a*.
Feldman, R. F. Factors affecting Young's modulus—porosity relation of hydrated portland cement compacts, (10) 241*j*. Flow of He into the interlayer spaces of hydrated portland cement paste, (6) 129*c*. He flow and density measurement of the hydrated Ca_3SiO_5-H_2O system, (5) 103*h*.
Feldman, R. F., and Ramachandran, V. S. Differentiation of interlayer and adsorbed H_2O in hydrated portland cement by thermal analysis, (5) 102*g*.
Feldstein, N. Method of making abrasion-resistant metal-coated [Ni-P] glass photomasks, P (9) 226*j*. Method for photodepositing smaller-size image screen areas for CRT from larger mask apertures, P (8) 201*g*.
Felice, F. T., Fisher, R. E., and Jacobs, L. J. Ladle lining refractory, P (5) 109*i*.
Fellner-Feldegg, H. See Siegbahn, K.
Felt, R. E. Process for directly reducing PuO_2 to Pu, P (3) 68*h*.
Feltham, P. See Brown, D.
Felton, C. D. Cross-sectioning techniques for scanning electron microscopy, (2) 44*f*.
Felty, E. J. See Myers, M. B.
Fendley, J. R., Jr. Double ended ion laser tube, P (2) 33*j*.
Fenish, R. G. See Mandorf, V., Jr.
Fenn, H. A. See Robinson, K. B.
Fennelly, T. J., and Reed, J. S. Compression permeability of Al_2O_3 cakes formed by pressure slip casting, (9) 223*c*. Mechanics of pressure slip casting, (6) 134*f*.
Fenner, G. E. See Galginaitis, S. V.
Fensterer, R. A. See Simkovitch, G.
Fenstermacher, J. E., and Le Blanc, J. R. Method of controlling the softening point and working temp. of soda-lime glass by regulating the H_2O content of the glassmelt, P (3) 59*b*.
Fenter, J. R. Refractory diborides as engineering materials, (3) 60*i*.
Feofanov, N. F., and Perli, S. B. Advantage of cyclone separators, (8) 185*j*.
Ferch, H. See Beschke, H.
Ferchland, H. W. Abrasive cutting tool, P (5) 101*f*.
Ferguson, D. E. See McNeese, L. E.
Ferguson, J., and Currie, K. L. Evidence of liquid immiscibility in alkaline ultrabasic dikes at Callander Bay, Ontario, (8) 209*b*.
Ferment, G. R. Induction furnace having improved susceptor for use in the continuous production of carbonaceous fibrous materials, P (8) 196*b*.
Fernandez-Moran, H. Apparatus using ultrasharp diamond edge for ultrathin sectioning, P (6) 127*g*.
Fernandez-Moran, H., Ohstuki, M., Hibino, A., and Hough, C. Electron microscopy and diffraction of layered, superconducting intercalation complexes, (4) 96*j*.
Fernandez Navarro, J. M. See Brueckner, R.; Oteo Mazo, J. L.
Ferrandis, V. Aleixandre. See Aleixandre Ferrandis, V.
Ferrante, E. See Calza Bini, A.
Ferrante, M. J. Enthalpies and entropies above 298.15°K for Cu sulfate and Cu oxysulfate, (7) 177*b*. See Pankratz, L. B.
Ferraresso, G. See Bettinali, C.
Ferrari, H. M. Internally pressurized fuel element, P (10) 253*i*.
Ferrario, B. See Giorgi, T. A.
Ferreiro, E. A., and Helmy, A. K. Partial molal vols of Ca montmorillonite, (9) 237*a*.
Ferrell, R. E., Jr. Applicability of energy-dispersive X-ray powder diffractometry to determinative mineralogy, (4) 92*j*.
Ferrero, F. See Sironi, G.
Ferrero, F., Sironi, G., and Garberi, A. Process for the recovery of V from raw TiCl, P (3) 72*a*.
Ferretti, P. Method and apparatus for the production of tempered glass articles of channeled or U cross-sectional form and article formed thereby, P (1) 4*h*.
Ferri, J. L., and Mathers, J. E. Rare earth oxide process, P (4) 90*g*.
Ferrier, A. Experimental studies of crystallization enthalpy of synthetic diopside and anorthite, (1) 22*g*.
Ferris-Prabhu, A. See Makris, J.
Ferro, A. P., and Ghandi, S. K. Properties of GaAs double-injection devices, (6) 151*g*.
Fertel, J. H., and Perry, C. H. Optical phonons in $KCl_{1-x}Br_x$ and $K_{1-x}Rb_xI$ mixed crystals, (5) 122*j*.
Fesenko, V. V. See Ryklis, E. A.; Turchanin, A. G.
Fetters, W. A. See Merz, J. P.
Fetzer, H. See Donaldson, W. K.
Feuersanger, A. E. Thin-film transistor and method of fabrication thereof, P (4) 91*d*.
Fickel, A. See Nitzsche, H. G.
Fiddyment, D. G. See Faktor, M. M.
Field, A. Abrading implement, P (7) 155*f*. Rotary abrasive tool, P (7) 155*g*.
Field, J. E., Hagan, J. T., and Schmidt, V. H. Crack-dislocation effects during cleavage, (4) 95*d*.
Fields, D. P. Preparation of alkali metal tetratitanate, P (6) 144*g*.
Fields, J. E. See Nielsen, L. E.
Fierens, P., and Verhaegen, J. P. Structure and reactivity of Cr-doped Ca_3SiO_5, (7) 157*g*.
Figg, J. See Cooper, G. A.
Figiel, F. J. Novel diamond powder dispersions and process for obtaining, P (8) 185*e*.
Filatkina, V. S., and Batsanov, S. S. Deter-

mination of the parameters of the unit cell of Tl sulfohalides, (2) 47*i*.

Filatkina, V. S., and Kustova, G. N. Crystallochemical study of sulfofluorides of rare-earth metals relating to the Sm group, (10) 258*i*.

Files, J. A. Method of manufacture of cathode-ray tubes having frit-sealed envelope assemblies, P (8) 193*e*.

Filonov, O. V. See Borisov, V. G.

Filous, J. See Zacpal, Z.

Finch, C. B. See Abraham, M. M.

Finch, C. B., and Clark, G. W. Czochralski growth of single-crystal forsterite, (7) 176*j*.

Finch, L. M., and Anthony, A. J. Hydraulic hold-down for nuclear reactor fuel assembly, P (9) 228*i*.

Finch, W. A. See Thomas, M. J. B.

Fine, M. E. Precipitation in crystalline ceramics, (7) 179*e*. See Kruse, E. W., III.

Fink, A. See Mueller, A.

Fink, R. H. Article conveyor flow control and unscrambling apparatus, P (1) 3*i*.

Fink, W. C., and Shaffer, J. W. Photoflash lamp, P (2) 35*a*.

Finkelman, R. B. See Lindholm, R. C.

Finucane, J. S., and Olander, D. R. Viscosity of U and 2 U-Cr alloys, (4) 91*j*.

Fiore, J. P. Mfg. of shadow mask color picture tube, P (10) 244*h*.

Firnhaber, M. S. Apparatus for mfg. glass fibers, P (3) 57*g*.

Fischer, A. G. Techniques for melt-growth of luminescent semiconductor crystals under pressure, (2) 39*f*.

Fischer, A. G., and Nuese, C. J. Highly refractive glasses to improve electroluminescent diode efficiencies, (2) 38*i*.

Fischer, J. J. Dispersion head for solids-liquids blender, P (4) 92*c*.

Fischer, P., and Mueller, H. A. Black cores in stoneware pipes, (11) 271*d*.

Fish, F. H., and McLaughlin, E. P. Deposition apparatus, P (7) 168*d*.

Fish, W. M. Extraction of Al_2O_3 from bauxite, P (10) 257*e*.

Fisher, D. G. Method for activating a semiconductor electron emitter, P (9) 226*b*.

Fisher, G. M. C. Method of achieving surface refractive index changes in a glass light-guide element, P (6) 133*g*.

Fisher, M. B., Schiller, C. K., and Ziemelis, O. J. Multichannel photomultiplier tube, P (9) 219*e*.

Fisher, P. C., Jr., and Shaner, K. H. Short persistence ZnS blue phosphor and method of preparing, P (9) 227*j*.

Fisher, P. D., Word, J. C., IV, and Bourg, H. J., Jr. Method and apparatus for depositing doped and undoped glassy chalcogenide films at substantially atm pressure, P (8) 201*e*.

Fisher, R. D. See Magee, J. H.

Fisher, R. E. Refractory mortar, P (6) 135*g*. See Felice, F. T.

Fisher, R. M. See Thomas, G.

Fishwick, J. H., and Yeh, W. C. T. Ceramic separators for a high temp. Li battery, (9) 230*g*.

Fismer, W. L. Filter press method and apparatus, P (4) 92*d*.

Fister, A. J. Protector for electric circuits, P (6) 136*d*.

Fitzer, E., Huettinger, K. J., and El Shami, F. A. Dilatometric study of the firing behavior of resin-bonded C bodies, (9) 221*g*.

Fitzer, E., and Kalka, J. Pyrolysis chemistry of polyphenylene and its oxides, (1) 24*i*.

Fitzer, E., and Mueller, K. Pyrolysis of acenaphthylene to soft C, (1) 24*g*.

Fitzpatrick, J. R. Ceramic gate valve, P (2) 38*c*.

Fitzpatrick, J. R., and Maghrabi, C. Radial distribution studies of amorphous As_2Te_3, (2) 49*e*.

Fitzpatrick, W. D. Refractory wall, P (1) 9*d*.

Flack, H. P., Katz, H. M., and Ashby, G. E. Process for forming uniform microspheres, P (3) 69*f*.

Flaherty, R. B. Adjustable hard ceramic underflow outlet for hydrocyclone, P (5) 111*b*.

Flanagan, T. M., and Wyatt, M. E. Radiation photoconductivity in ovonic switches, (6) 137*a*.

Flannery, J. E. Spontaneous fluoride opal glasses with thermally reversible opacity, P (9) 220*b*. See Dumbaugh, W. H., Jr.; Giffen, J. W.

Flasche, G. Method and apparatus for connecting to a Nesa layer, P (10) 251*h*.

Flautt, M. C., Moran, L. G., and McCombs, F. P. Glass fiber-reinforced elastomers, P (10) 244*j*.

Fleck, H. G. Cathode-ray tube having inert barrier between AgCl seal and photocathode, P (8) 192*b*. Tube uniting with fusion barrier, P (3) 59*i*.

Fleck, H. G., Rome, M., and Wixted, J. M. Tube uniting with end fractures, P (3) 59*i*.

Flegmann, A. W., Love, G., and Scott, V. D. Electron-optical study of the prism surfaces of kaolinite microcrystals, (9) 235*d*.

Fleischer, L. R., and Tobin, J. M. Growth of transition metal carbide single crystals by recrystallization, (I) preparation of fully dense transition metal carbide; (II) transition metal carbide recrystallization and crystal growth, (7) 177*j*.

Fleischmann, W. Refractory [casting, spraying, and ramming] bodies, (10) 247*g*.

Fleischner, P. L. Apparatus and method for continuously depositing BeO through vaporization of a basic formate, P (10) 257*b*.

Flem, Z. L., Bondar, I. Ya., and Udalov, Yu. P. New phases in the system CaO-Nd_2O_3-Al_2O_3, (2) 48*c*.

Fleming, G. R., and Ovshinsky, S. R. Method of making a current-controlling device including a VO_2 film, P (6) 138*h*.

Fleming, J. W., Jr., and Day, D. E. Relation of alkali mobility and mechanical relaxation in mixed-alkali silicate glasses, (5) 106*g*.

Fleming, S. J. Thermoluminescent authenticity testing of ancient ceramics—the effects of sampling by drilling, (5) 102*b*.

Fleming, S. J., Jucker, H., and Riederer, J. Etruscan wall paintings on terra cotta—a study in authenticity, (5) 102*b*.

Flemings, M. C. See Yarwood, J. C.

Fletcher, W. W. Combustion separation techniques in glass analysis, (8) 204*i*. Work of the Chemical Analysis Committee of the Society of Glass Technology, (8) 192*g*. See Austin, M. J.

Fleurence, A., and Lecrivain, L. Quantitative estimation of $CaAl_2O_4$ by X-ray diffraction, (7) 173*c*.

Fleurence, A., and Loisel, M. Formation of cordierite in ceramic products (I) quantitative estimation of cordierite, (2) 47*j*.

Flinchbaugh, D. A. Aperture vessel for fluid-suspension particle analyzer, P (7) 174*a*.

Flint, H. G., and Neitzel, U. E. G. Process for removing sulfate from $MgCl_2$ brines contaminated therewith, P (10) 257*g*.

Flock, W. M. High-Al_2O_3 [insulator] ceramic body and method of making, P (2) 38*a*.

Flor, L. L., and Keith, W. T. Corrosion failures revealed: Inspection of cement-lined H_2O mains, (7) 156*e*.

Florescu, V. See Tanasoiu, C.

Flori, J. F. Method and apparatus for drawing sheet glass, P (1) 4*e*.

Florinskaya, V. A. See Cherneva, E. F.

Florio, G. C. See Belt, R. F.

Floyd, J. M. See Steele, B. C. H.

Fluesmeier, A. L. Method of forming boric acid, P (11) 279*g*.

Flyagin, V. G., Rutman, D. S., and Perepelitsyn, V. A. Resistance of chamotte, dinas, and siliceous refractories to the action of basic open hearth slags, (8) 195*g*.

Foex, M. See Bonet, C.; Fava, J.; Rouanet, A.

Fogelberg, C. V., and Erickson, L. H. Method for programing parisons, P (4) 82*e*.

Fokin, V. N. See Vanyarkho, V. G.

Foley, J. C. See Sobel, J. E.

Folkmann, E., and Pammer, E. Method of precipitating layers of semiconducting or insulating material from a flowing reaction gas or from a flowing dopant gas on heated semiconductor crystals, P (8) 201*f*.

Folweiler, R. C. See Belruss, V.

Fomenko, V. S. See Lapshov, Yu. K.; Samsonov, G. V.

Fomenko, V. S., Lavrenko, V. A., Okhremchuk, L. N., Podchernyaeva, I. A., Protsenko, T. G., and Samsonov, G. V. Correlation of work function of transition metal carbides in homogeneity region with surface recombination of H atoms, (7) 176*f*.

Fomin, G. S. See Makeev, V. S.

Fomina, T. I. See Shevrina, Z. A.

Fominykh, G. V. See Taranukhin, N. A.

Fonstad, C. G., and Rediker, R. H. Electrical properties of high-quality stannic oxide crystals, (6) 147*g*.

Fontanel, A., and Grau, G. Device for measuring the diam. of fibers and threads of small thickness using a convergent coherent light beam, P (3) 70*h*.

Fontanella, J. See Andeen, C.

Foon, R. See Alderdice, D. S.

Foote, R. S. Solder preforms [Au] on a semiconductor wafer, P (1) 14*g*.

Forber, A. See Parry, R. J.

Forcier, R. E. Radial interlocking refractory tuyere block, P (5) 110*c*.

Ford, L. H. See Shennan, J. V.

Ford, S. D. See Dugdale, R. A.

Ford, W. F. See Taylor, M. I.

Ford, W. J. See Hatfield, T.

Forester, R. W. See Taylor, H. P., Jr.

Forman, I., Kreysa, K., and Vasicek, Z. Regulation of the supply of raw material to a closed-circuit grinding mill system, P (4) 92*h*.

Forman, R. A. See Blunt, R. F.; Cohen, M. I.

Forman, R. A., Piermarini, G. J., Barnett, J. D., and Block, S. Pressure measurements made by the utilization of ruby sharp-line luminescence, (8) 205*j*.

Formigoni, N. P., and Roberts, J. S. Electrical contact for SiC members, P (8) 200*j*.

Forrat, F. Apparatus for growing crystalline bodies, P (7) 168*h*.

Forst, S. M., and Reinheimer, H. A. Semiconductor target structure for image converting device comprising an array of Ag contacts having discontinuous nodular structure, P (10) 253*b*.

Forster, T., and Mohr, T. O. Process for the production of finely etched patterns, P (5) 114*a*.

Fort, A., Sharp, D., Ash, B., Papworth, K., and Reed, D. Influence of liquid environments on the strength of ferrite memory cores, (7) 167*g*.

Foss, N. A. Field-enhanced photoelectron emission from MOS structures, (5) 120*h*.

Fosshag, W. See Balzau, G.

Fossheim, K. See Berre, B.

Foster, G. F., and Stong, G. E. Glass-ceramic cements comprising SiC, P (4) 82*a*.

Foster, J. D. See Osterink, L. M.

Foster, J. R. Application of direct-reading spectrometry (I) application of direct-reading spectroscopy to the analysis of trace metals in soils and stream sediments, (9) 230*g*.

Foster, K., and Seidel, J. Bonded core structure comprising a plurality of glass-coated electrical steel sheets, P (9) 215*j*. Phosphate glass coating for electrical steel sheets, P (3) 54*f*.

Foster, L. M. See Blum, S. E.

Foster, L. M., and Scardefield, J. E. Solidus boundary in the GaP-InP pseudobinary system, (9) 238*d*.

Foster, R. G. See Evans, J. W.

Foster, T. V. Details of the new 8-section IS machine, (8) 189*g*. See Dahms, F. A.

Foster, T. V., and Nebelung, H. H. Holding and cooling device for glassware molds, P (7) 162*c*. Parison-forming unit for glassware-forming machine, P (1) 5*f*.

Fotedar, H. L., and Stoebe, T. G. Effect of temp., strain rate, and impurity content on the work-hardening characteristics of LiF single crystals, (6) 147*a*.

Fotiev, A. A. Ion-diffusion mechanism of the reactions in the system alkali metal salt-V_2O_5, (5) 121*e*.

Fotiev, A. A., and Slobodin, B. V. Chemistry of formation of the OV bronze NaV_6O_{15} in the systems V_2O_5-Na compounds, (8) 208*d*.

Foucard, A. See De Mendez, M. O.

Fourniquet, J. See Beau, R.

Fowler, A. B. See Fang, F. F.

Fowler, R. A. See Lagos, C. C.

Fowler, R. P. Electrolytic process and apparatus for recovering Ni from asbestos ore, P (10) 257*d*. Separation of Ni from asbestos ore, P (6) 144*f*.

Fowler, W. L. Method of fabricating semiconductor power devices within high resistivity isolation rings, P (3) 65*g*.

Fowler, W. R. See Drozdowicz, K. P.

Fox, G. T., Wolfmeyer, M. W., Dillinger, J. R., and Huber, D. L. Thermal conductivity of rare-earth-doped CaF_2 in magnetic fields, (5) 125*b*.

Fox, J. See Reynolds, J. A.

Foxhall, G. F., and Moline, R. A. Forming impurity regions in semiconductors, P (5) 112*e*.

Fraas, F. Electrostatic separation with photoelectric charging, (9) 229*e*.

Fraikor, F. J. See Govind, P. K.

Fraiman, L. S., and Shlionskii, Yu. S. Dependence of dusting in rotary kiln on moisture, (8) 186*f*.

Franceschini, F. Acid etching of glass, (4) 80*d*.

Francis, F. J., Russo, A. J., and Keys, L. K. Beam-lead devices for hybrid integrated circuits, (3) 62*f*.

Francis, T. L., MacZura, G., Marhanka, J. E., and Parker, H. J. White spots in 99+% Al_2O_3 ceramics, (7) 165*j*.

Frank, B., Groth, R., and Jost, R. Low-pressure Hg vapor discharge lamp, P (3) 58*f*.

Frank, C. A. Vapor treatment of containers with finish air barrier, P (3) 60*a*.

Frank, F. C. Capillary bonds between grains in moist sand, (2) 47*e*.

Frank, G. A., Kipp, K. F., and Oswald, D. R. Method for scrubbing thin, fragile slices of material [Si], P (9) 226*h*.

Frank, G. H. A. See Garbe, S.

Frank, J. N., and Robinson, W. M. Passivated semiconductor device with protective peripheral junction portion, P (4) 89*h*.

Frank, R. I., and Moberg, W. L. Reactively sputtered Si oxynitride as a dielectric material for metal-insulator-metal capacitors, (9) 224*c*. Sputtering method for deposition of Si oxynitride, P (4) 90*j*.

Frankel, R. B. See Chappert, J.

Frankenberger, R. Calculation of heat transfer in rotary cement kilns, (8) 186*a*.

Frankl, D. R. See Bartholomew, R. F.

Franklin, A. D., and Bennett, H. S. (editors). ARPA-NBS program of research on high temp. materials and laser materials, (3) 70*j*.

Franklin, A. D., and Marzullo, S. EPR study of point-defect equilibria in CaF_2 containing GdF_3, (9) 235*j*.

Franklin, D. L., and Balents, L. M. Mounting structure for high-power semiconductor devices, P (3) 66*c*.

Franklin, D. L., and Fender, B. J. Power transistors having controlled emitter impurity concentrations, P (2) 42*b*.

Frans, R. D. Heat processing of minerals, P (9) 230*c*.

Frantskevich, A. A. See Kulygin, I. P.

Frantz, H. See Najmann, K. K.

Franzblau, M. C., and Kraft, D. W. Experimental study of scattering of longitudinal elastic waves from cavities in a solid medium, (7) 177*f*.

Fraser, A. R. Process for producing battery-grade MnO_2, P (10) 257*e*.

Fraser, D. B., Maldonado, J. R., and Meitzler, A. H. Multiple element optical memory structures using fine-grain ferroelectric ceramics, P (2) 41*g*.

Frassrand, J. E. Piezoresistive miniature pressure transducer, P (3) 66*h*.

Fratzscher, H. See Bauer, D.

Frawley, F. E. See Beach, H. J.
Frazee, O. P. Fabrication of 4-layer switch with controlled breakover voltage, P (9) 225*h*.
Frech, R., and Decius, J. C. Dipolar coupling and molecular vibrations in crystals (II) rhombohedral lattices; (III) polarizabilities of molecular anions and the internal field in some rhombohedral crystals, (4) 96*d*.
Frederikse, H. P. R. Electronic transport in transition metal oxides, (9) 235*h*.
Freedman, R. W. Analysis of free SiO_2 in respirable dust, (1) 17*d*.
Fredlein, R. A., and Damjanovic, A. Electrochemical deposition and dissolution of W oxide bronzes, (8) 208*i*.
Fredrickson, D. R., Barnes, R. D., Chasanov, M. G., Nuttall, R. L., Kleb, R., and Hubbard, W. N. Enthalpy of UB_2 from 600°–1500°K by drop calorimetry, (4) 91*f*.
Freeman, M. E. See Brede, D. W.
Freeman, R. W. See Busch, R. E.
Freese, R. W., Jr. High-pressure metal halide electric discharge lamp, P (3) 58*c*.
Freiberger, E. Reciprocal latching ferrite phase shifter, P (10) 252*d*.
Freiman, D. J. Packaging protector, P (2) 34*i*.
Freiman, S. W. See Hench, L. L.
Freiman, S. W., and Hench, L. L. Effect of crystallization on the mechanical properties of Li_2O-SiO_2 glass-ceramics, (3) 55*d*.
Freiman, S. W., Onoda, G. Y., Jr., and Pincus, A. G. Controlled spherulitic crystallization in $3BaO$-$5SiO_2$ glass, (8) 189*i*.
French, K. W. Active medium for a liquid laser and method of preparation, P (3) 64*b*.
French, P. W. See Greenberg, C. B.
French, S. E., and Preston, T. K. Process for producing TeO_2 of low Fe content, P (4) 94*j*.
French, W. G. See Kim, C. K.
Frenkel, M. Ya. See Balashov, Yu. A.
Frentz, H., and Weijland, B. H. Method of mfg. a semiconductor device, P (6) 139*b*.
Frenzel, G. Cause of deterioration and disintegration of medieval stained glass [windows], (1) 1*i*.
Frese, W. See Borchert, E.
Freundlich, W. See Tabuteau, A.
Frevel, L. K., and Kressley, L. J. Removal of paramagnetic gases, P (11) 280*b*.
Frey, J. O., and Minnier, H. B. Process for preparing Cu-resistant Ag-activated ZnS phosphors, P (11) 275*b*.
Fridkin, R. Z. See Pukhlik, O. I.
Fridman, I. D. See Menchikov, L. P.
Friebele, E. J. See Dozier, A. W.
Friebele, E. J., Wilson, L. K., and Kinser, D. L. Magnetic behavior and microstructure of V phosphate glasses, (4) 80*g*.
Friedland, A. J. Fuel subassembly for nuclear reactor, P (8) 203*c*.
Friedrich, H. G. Article conveyor having ejecting means for tipped or fallen articles [bottles], P (2) 33*d*.
Friedrich, K. F. Electrical bushing having stress-grading layer disposed within solid insulation including a ground layer terminated at each end with a layer of material having a voltage-dependent resistivity, P (6) 136*b*.
Friedrichsen, W., and Goehre, O. Supported catalysts containing V_2O_5 and TiO_2 and their use for the production of carboxylic acids and carboxylic anhydrides, P (11) 280*b*.
Friele, L. F. C. Color difference and color tolerance evaluation problems and outlook, (7) 182*d*.
Fries, D. C. See Kreidler, E. R.
Frilette, V. J. Method for dehydrating moisture-containing materials using CO and a crystalline aluminosilicate catalyst, P (4) 94*i*.
Frischat, G. H. Blocking effect of ion-exchanged glass surfaces, (7) 158*f*. Cation self-diffusion in silicate glasses, (7) 158*h*. Cation transport in Al_2O_3, (6) 145*g*. Effect of K-Na ion exchange on transport phenomena in silicate glasses, (9) 217*a*. Tracer diffusion in glassy and crystalline SiO_2, (5) 106*d*.
Frischat, G. H., and Tomandl, G. Moessbauer investigation of silicate and phosphate glasses with small additions of Fe_2O_3, (7) 160*b*.
Frit, B., Jaymes, M., Perez, G., and Hagenmuller, P. System Bi_2O_3-TeO_2 at 750°C, (6) 152*i*.
Fritsch, A. A., and Hicguet, M. H. Process for roasting solids, P (3) 72*b*.
Fritsch, V., and Tauber, A. F. Possibility of geoelectrical prospecting for ceramic raw materials, (1) 20*h*.
Fritz, G. See Bagyal, P.
Fritz, L. L. Sputter etch removal rates of insulators, semiconductors, and conductors, (10) 249*a*.
Fritzinger, L. B., and Lepselter, M. P. Method of eliminating pinhole shorts in an air-isolated crossover, P (6) 138*a*.
Fritzsche, H. See Fagen, E. A.
Fritzsche, H., and Ovshinsky, S. R. Calorimetric and dilatometric studies on chalcogenide alloy glasses, (6) 131*h*. Electronic conduction in amorphous semiconductors and the physics of the switching phenomena, (6) 147*c*.
Froberg, M. L. Apparatus for conveying glass in a forehearth, P (1) 3*d*. Heating furnaces, P (4) 82*d*.
Froehling, J. Milling machines, P (7) 172*f*.
Frohman-Bentchkowsky, D. Floating gate transistor [Si] and method for charging and discharging same, P (8) 200*e*.
Frolov, A. S. See Kestner, O. E.
Fronczek, E. J. See Desmond, R. J.
Frorath, K. F. See Preisler, E.
Frost, H. J., and Ashby, M. F. Motion of a dislocation acted on by a viscous drag through an array of discrete obstacles, (7) 179*c*.
Frostling, B. H. I. See Brantte, A.
Frouin, J. C. Method of mfg. a semiconductor device comprising a Zener diode and semiconductor device manufactured by said method, P (1) 13*j*.
Frova, A. Roman glasses with brands, (11) 266*c*.
Frushour, R. H. See Roy, R.
Frydl, J. See Koller, A.
Frye, E. R. See Stoller, H. M.
Fryer, G. E. See Jordan, C. F., Jr.
Fryer, G. M. Effect of some impurities on the pressure-sintering of Al_2O_3, (1) 21*b*. Pressure-sintering of Al_2O_3, (1) 24*d*. Theory of ionic diffusion in a stress gradient, (1) 26*a*.
Fryer, G. M., and Thompson, P. Compressive creep of porous polycrystalline Al_2O_3, (11) 280*h*.
Fuchs, A. Oven installation for use in mfg. a plurality of enameled wires, P (1) 17*c*.
Fuerstenau, D. W. See Abouzeid, A. Z. M.
Fujie, Hideo. Soaking pit constructed of plastic refractories, (1) 8*a*.
Fujii, Akihiro. Method of mfg. a semiconductor photosensitive device, P (9) 266*d*.
Fujii, Atsuhiro. See Nishi, Masato.
Fujii, Junnosuke, Mori, M., and Hiyama, T. Study of safe usable temp. range for cement products, (10) 242*b*.
Fujii, Junnosuke, Mori, M., Yoshida, T., and Nishiwaki, T. Heat-, moisture-, and impact-proof panel with asbestos-cement board, (6) 129*f*.
Fujii, Kinjiro. See Kodama, Kenjiro.
Fujii, Manabu. Characteristics of deformation of lightweight concrete and steel studs, (6) 128*a*.
Fujii, Toshiro. See Tamaoki, Osamu.
Fujikawa, Kyoichiro, and Takamiya, S. Magnetically operated semiconductor device, P (9) 225*j*.
Fujiki, Yoshinori. See Mitsuhashi, Takefumi.
Fujiki, Yoshinori, Mitsuhashi, T., and Suzuki, Y. Hydrothermal growth and etching of ZrO_2 crystals, (5) 121*b*.
Fujimasu, Jiro. Calcining alkaline earth metal chlorides with cellulose and admixing with portland cement, P (4) 79*f*. Hydraulic [cement] composition, P (5) 104*h*.
Fujimori, Keizo. See Nakanuma, Sho.
Fujimoto, Isao. See Chikawa, Jun-ichi.
Fujimoto, Syoji. MOS integrated circuit semiconductor device, P (9) 227*a*.
Fujimoto, Yukiya. See Ito, Kunihiko.
Fujimoto, Yukiya, and Kurashina, I. Process for mfg. flat glass on a molten metal bath, P (6) 133*f*.
Fujimoto, Yukiya, and Matsushita, M. Float glass apparatus with longitudinal dams and metal flow control means, P (1) 4*c*.
Fujino, Yoshio. See Doi, Kikuo; Tsuya, Hideki.
Fujioka, Masami. See Okushima, Masaichi.
Fujita, Masayuki, and Uchida, Y. Study, using H_2O model, of effect of sliding valve control on coeff. of discharge of sliding nozzle, (1) 8*e*.
Fujita, Shisao. See Akazawa, Hakuichi.
Fujita, Tadao, Wake, M., and Konishi, K. Organic-inorganic silicate binder for refractory processes, P (11) 272*d*.
Fujita, Takashi. Contactless pressure-sensitive semiconductor switch, P (2) 39*i*.
Fujita, Toshiaki. See Nishi, Masato.
Fujita, Yoshio, and Nishihori, T. Deformation of reinforced concrete beams under repeated loads, (6) 128*h*.
Fujiwara, Nobuo. See Toda, Masumi.
Fujiwara, Shohei. See Kano, Goẽa.
Fujiwara, Teiichi. See Tabata, Katsuhiro.
Fujiyama, Takeshi. See Saito, Turuyoshi.
Fukai, Masakazu. See Tohi, Atsutomo.
Fukai, Yuh. See Syono, Yasuhiko.
Fukamachi, Tomoe, and Hosoya, S. Electron state of an O^{2-} atom in MgO, (4) 96*b*.
Fukao, Yoshiro. See Goshi, Yoichi.
Fukase, Yukishige. Heat resisting metallic materials for high-temp. technology, (3) 60*j*.
Fukatsu, Yukio. See Nakayama, Junn.
Fukuda, Satoshi. See Tachikawa, Kyoji.
Fukuda, Takeyi. See Tanaka, Eihachiro.
Fukuda, Tsuguo. See Uematsu, Yutaka.
Fukui, Tadaoki. Refractory materials for MHD power generation, (3) 63*e*.
Fukui, Tsunaomi, Miyadai, T., and Miyahara, S. Photoconductivity of natural pyrite (FeS_2), (4) 98*e*.
Fukuma, Naoaki. See Kodama, Kazumi.
Fukumoto, A. See Yano, T.
Fukunaga, Jiro. See Ihara, Masayoshi; Yoshimura, Takuji.
Fukunaga, Makoto. See Sato, Takeshi.
Fukuoka, Hiromi. See Ohba, Hiroshi.
Fukuoka, Tokuji. See Obuchi, Satoru.
Fukushige, Yasuo. See Shimada, Kinji.
Fukushima, Masakazu. See Okabe, Tadao.
Fukushima, Masakazu, and Kimura, K. Cathode-ray tube having a plated inner metal layer of high tensile strength, P (5) 107*b*.
Fukushima, Syoji. See Iwauchi, Kozo.
Fulk, W. F. See Klink, J. P.
Fuller, C. R. Corrosion-resistant multimetal lead contact for semiconductor devices, P (3) 64*e*. Method of forming beam leads on semiconductor devices and integrated circuits, P (7) 169*g*. Pt thin-film metalization method, P (8) 202*c*. See Carlson, H. G.; Cunningham, J. A.
Fuller, J. L. See Hayes, R. R.
Fuller, M. H. See Gunn, K. M.
Fulrath, R. M. See Holman, R. L.; Thomas, G.
Fulson, F. C. Preparation of crystalline carbonatozirconates of ammonium and K, P (2) 46*b*.
Fulton, E. See Cook, A. K.
Fulton, T. P., and Di Luca, H. Encapsulated magnetic memory element, P (5) 112*j*.
Fultz, P. Glassmelting furnace and control means for the flow of molten silicates therein, P (10) 244*b*.
Fumoto, Tsutomu. See Yamane, Sho.
Funabashi, Wataru, and Kakita, I. Coated abrasive grains (II), (3) 53*g*.
Funabashi, Wataru, Kakita, I., Kaminishi, T., and Nunome, K. Adhesive for coated abrasive (XI), (3) 53*f*.
Funabashi, Wataru, Kakita, I., and Nunome, K. Adhesive for coated abrasive (X), (3) 53*e*.
Funato, Michio. See Uchida, Shinichi.
Funk, R. E. Tubular drill shank solves dust, concentricity problems, (3) 69*b*.
Funke, V. F., Klement'ev, A. A., Kosukhin, V. V., Tyutyunnikov, A. I., and Yamskov, N. S. Deposition of carbides of refractory metals from a gaseous medium, (10) 258*d*.
Furmidge, K. F. See Weston, R. F.
Furnish, O. C. See Abboud, H. I.
Furnival, T. J. Method of fabricating a piezoelectric device, P (6) 138*c*.
Furui, Takeo. See Ishimitsu, Akitoshi.
Furukawa, Akihisa. See Sato, Chosei.
Furukawa, Motoaki. See Uchida, Teiji.
Furukawa, Yoshitaka. See Seki, Yasuo.
Furumi, Koichi. Comparison of characteristics of high-purity MgO clinker and ordinary MgO clinker, and use test results on bricks made of these clinkers, (1) 6*i*.
Furuta, Mitsuo. See Yamazaki, Yasuo.
Furuta, Tomihiko. See Berry, P. F.
Furuto, Yoshio. See Suzuki, Takuya.
Furuuchi, Shigemasa, and Aikawa, K. Heat-reflecting glass and method for mfg., P (8) 193*c*.
Furuuchi, Shigemasa, and Mukaiyama, T. Infrared-reflecting glass and method for mfg., P (3) 58*e*.
Furuya, Masaaki, Nakajima, Y., and Tanaka, T. Theoretical analysis of closed-circuit grinding system based on comminution kinetics, (2) 43*j*.
Fury, R. C. See Johnston, H. D.
Fuschillo, N. See McMaster, A. D.
Fuschillo, N., and Gimpl, M. L. Electrical and tensile properties of Cu-ThO_2, Au-ThO_2, Pt-ThO_2, and Au-Al_2O_3, Pt-Al_2O_3 alloys, (2) 38*e*.
Fussell, L. E. See Arthur, M. E.
Fuwa, Yoshikazu, Sata, Y., Ono, T., and Kato, S. Bottle-loading apparatus, P (3) 57*i*.
Fyler, N. F. Optical maser, P (2) 34*i*.

Gabadadze, T. G. See Kutateladze, K. S.
Gaboardi, M. See Kemeny, G.
Gabor, L. Method and apparatus for burning liquid fuels, P (2) 45*h*.
Gad, G. See El-Kolali, A. E. G. A.
Gad, G. M. See El-Rafei, E. A.; Khalil, A. A.
Gaddy, L. E. Vibratory apparatus for working particulate solids, P (3) 69*g*.
Gaertner, F. See Gaeth, R.
Gaeth, R., Stastny, F., Breu, R., and Gaertner, F. Thermally insulating transparent laminated glass with alkali metal silicate interlayer, P (5) 107*h*.
Gagorik, J. E., Queeney, R. A., and McKinstry, H. A. Stress distributions in Al_2O_3 bicrystal tensile specimens, (1) 25*i*.
Gailhbaud, J. Electrical resistance of electrically heated glass tank furnaces (I) furnaces with a square horizontal cross section; (II) furnaces with a hexagonal horizontal cross section, (8) 190*f*. Electrical resistance of glass-melting furnaces with horizontal electrodes not traversing the entire width of the bath, (9) 217*f*. Uniform loading of vertical electrodes in 3-phase-heated glass tank furnaces, (8) 192*b*.
Gainsbury, P. E. See Angus, H. C.
Gal, I. J., Jankovic, O., Malcic, S., Radovanov, P., and Todorovic, M. Ion-exchange equilibria of synthetic 4A zeolite with Ni^{2+}, Co^{2+}, Cd^{2+}, and Zn^{2+} ions, (1) 23*e*.
Galasso, F. S. See Basche, M.
Galasso, F. S., Kuntz, U. E., and Croft, W. J. Pyrolytic Si_3N_4, (9) 224*c*.
Galasso, F. S., and Veltri, R. D. Method of forming Si compound fibers, P (5) 107*c*.
Galdina, N. M., and Shatova, N. P. Surface changes in baddeleyite-corundum refractory under the action of high temps. and molten glass, (8) 196*d*.
Gale, A. J. Method of preventing ion channeling in crystalline materials, P (7) 169*c*.
Galginaitis, S. V., Fenner, G. E., and Ehle, R. S. Multiple color light-emitting diodes, P (2) 41*g*.
Galimov, D. G., Karapetyan, G. O., Petrovskii, G. T., Tsurikova, G. A., and Yudin, D. M. Effect of hard radiation on fluoroberyllate glasses activated by rare-earth and transition metal ions, (9) 216*j*.
Galimov, D. G., Karapetyan, G. O., and Yudin, D. M. Effect of ionizing radiation on

glasses activated by transition metals, (8) 190*c*.
Galimov, D. G., Stepanov, S. A., Tsekhomskii, V. A., and Yudin, D. M. EPR study of the action of γ-irradiation on photochromic glasses, (8) 190*h*.
Galkin, N. P., Vlasov, A. D., Birin, E. A., and Kozlov, A. M. Reaction of UO_2 and MoO_3 in a eutectic NaF-LiF melt, (1) 24*f*.
Galkin, Yu. M., Chukhlantsev, V. G., and Polezhaev, Yu. M. Preparation of stabilized cubic ZrO_2, (7) 179*g*.
Galla, R. T., and Greenhouse, H. M. Method of preparing resistive films, P (1) 13*j*.
Gallagher, P. K. See Johnson, D. W., Jr.
Gallaro, A. V., Kazuk, W. F., and Speigel, K. Luminescent screen having a separation medium therein, P (1) 12*i*. Penetration-type color tube with phosphors separated by conductive barrier layer, P (1) 14*b*.
Galli, G. See Coker, J. E.
Galli, G., and Coker, J. E. Composite structure of Zn oxide deposited epitaxially on sapphire, P (9) 225*a*.
Galloway, R. L. Electrical resistance elements, P (11) 274*f*.
Galopin, R. E., and Henry, N. F. M. Microscopic Study of Opaque Minerals, B (11) 284*c*.
Gaios, M., Kertesz, P., Kurti, I., and Marek, I. Strength testing of natural rocks, (6) 142*h*.
Galy, J. See Carpy, A.
Galy, J., Darriet, J., and Hagenmuller, P. $Li_xV_2O_5$ bronzes—structure of the β′-phase and refinement of the γ-phase structure, (6) 149*i*.
Gambale, J. R., McIntyre, G. H., Jr., and Ranney, F. J. Process for preparing basic Zr sulfates and other Zr compounds such as Zr fluosulfates and compositions containing the same, P (10) 257*d*.
Gamble, F. R., Osiecki, J. H., Cais, M., Pisharody, R., DiSalvo, F. J., and Geballe, T. H. Intercalation complexes of Lewis bases and layered sulfides—large class of new superconductors, (4) 97*h*.
Gammil, A. M., Guinn, F. K., Bird, U. S., and Householder, W. R. Metal vapor coating apparatus, P (9) 228*j*.
Gancy, A. B. High-surface-area chrysotile and method of making, P (7) 164*f*.
Gandrud, W. B. See Boyd, G. D.
Gane, N. Compressive strength of submicron diam. MgO crystals, (10) 258*e*. Microdeformation and strength of diamond, (4) 77*g*.
Ganiev, R. M., Egunov, V. P., Ilyukhin, V. V., and Belov, N. V. Synthesis and some properties of $5CaO{\cdot}2SiO_2{\cdot}H_2O$ single crystals, (9) 239*b*.
Ganiev, R. M., Kuznetsov, V. A., Lider, V. V., Ilyukhin, V. V., and Belov, N. V. Synthesis and some properties of single crystals of Ca hydrosilicates, (9) 239*c*.
Gano, B. P. See Marsh, H. N., Jr.
Gantley, F. C. Subdivided semiconductor wafer separator, P (1) 14*j*.
Garashin, V. R. See Budnikov, P. P.; Volzhenskii, A. V.
Garbe, S., and Frank, G. H. A. Activating method for Cs-activated III-V compound photocathode using rare gas bombardment, P (4) 87*c*.
Garberi, A. See Ferrero, F.
Garbett, E. S. See Austin, I. G.
Garceau, W. J. Method for sealing glass to metal, P (4) 82*g*.
Garcia, D., and Speidel, D. Reexamination of the system TiO_2-SnO_2, (7) 180*d*.
Gard, J. A. See Aggarwal, P. S.
Gardiner, S. D. See Bennett, M. C.
Gardner, E. E., Keenan, W. A., and Schumann, P. A., Jr. Measurement of carrier concentration of semiconductor material, P (3) 65*a*.
Gardner, F. M., Gervais, J. R., and Nettleton, F. S. Brazing alloy for bonding thermionic cathode to support, P (9) 218*e*.
Gardner, N. C. Diamond growth process, P (4) 77*f*. See Angus, J. C.
Garf, E. S. See Paderno, Yu. B.
Garfinkel, H. M., and Olcott, J. S. Method for [chemically] strengthening glass articles, P (4) 82*b*.
Garfinkel, H. M., Sawchuk, L. G., and Stookey, S. D. Method for strengthening photochromic glass articles, P (8) 193*a*.
Garfinkel, M. See Brown, Dale M.; Engeler, W. E.
Garlick, G. F. J., Nicholls, J. E., Prasad, C., and Oezer, A. M. ESR studies of intrinsic and impurity defects in SiO_2 and GeO_2, (2) 47*c*.
Garnache, R. R. Vapor deposition apparatus, P (1) 15*d*.
Garnache, R. R., and Kenny, D. M. Entrance-exit atm isolation device, P (6) 137*d*.
Garrett, C. G. B. See Dillon, J. F., Jr.
Garrett, D. R. Diamond implosion apparatus, P (8) 185*e*.
Garrett, J. M. Methods of mfg. semiconductor [wafer] elements and elements manufactured thereby, P (2) 41*c*. See Miles, C. V.
Garrison, A. K. See DuVarney, R. C.
Garside, B. K. See Kawasaki, B. S.
Gartner, W. J., and Clark, C. T. Structured insulating materials, P (4) 85*c*.
Garty, K. T. See Snedeker, R. H.
Garvey, F. J. Dead plate assembly for freshly formed glassware, P (1) 3*j*.
Garvie, R. C. Partially stabilized ZrO_2 refractory, P (3) 61*b*.
Garvie, R. C., and Nicholson, P. S. Phase analysis in ZrO_2 systems, (7) 179*a*. Structure and thermomechanical properties of partially stabilized ZrO_2 in the CaO-ZrO_2 system, (4) 98*j*; correction, (6) 152*c*.
Gasanaliev, A. M. See Bergman, A. G.
Gascon, J. See Fehr, B. H. P.
Gaskell, D. R. See Suito, Hideaki.
Gaskell, P. H., and Lowe, D. Detection of faults in transparent material using lasers, P (7) 161*c*.
Gasparac, R. J., and Szaj, A. P. Cone crusher feed distributor and method, P (1) 20*a*.
Gass, H., and Hintermann, H. E. Method for producing [TiC] coatings on a surface, P (5) 109*j*.
Gassaway, J. S. Magnetic memory members and methods of making, P (1) 12*j*.
Gasson, D. B. See Cockayne, B.
Gately, T. J., Quintilian, B. F., and Rodgers, C. H. Pneumatic rapper for electrostatic precipitators, P (1) 17*a*.
Gates, D. W., Zerlaut, G. A., and Rogers, F. O. Synthesis of Zn titanate pigment and coatings containing it, P (1) 3*a*.
Gates, L. E., Jr. See Lent, W. E.
Gates, L. E., Jr., and Lent, W. E. Lossy dielectric structure for dissipating electrical microwave energy, P (9) 225*g*.
Gatewood, J. R. See Maserjian, J.
Gatos, H. C. See Minagawa, Shigekazu.
Gatti, A. See Higgins, J. B.
Gatzke, H. Possible application of the rapid firing kiln in the porcelain industry, (9) 223*e*.
Gau, F. L., and Olson, R. E. Uniformity of specimens of a compacted clay, (7) 173*i*.
Gaude, J., and Lang, J. System Sr-N (I) nitriding of metallic Sr, (4) 99*b*.
Gaude, J., L'Haridon, P., Laurent, Y., and Lang, J. System Sr-N (II) new Sr-N compound, (4) 99*b*.
Gauger, R. C. Mechanism for thin-film deposition, P (3) 65*a*.
Gauster, W. B. Elastic constants and Grueneisen parameters of pyrolytic graphite, (10) 258*j*.
Gavaler, J. R. See Deis, D. W.
Gavrikov, V. S. See Menchikov, L. P.
Gavrish, A. M., Sukharevskii, B. Ya., Zoz, E. I., and Krivoruchko, P. P. X-ray study of decomposition of solid solutions based on ZrO_2, (8) 211*g*.
Gay, F. M. Multijunction thermocouples, P (9) 232*a*.
Gazza, G. E. Hot-pressing of $LiAl_5O_8$, (4) 97*a*. See Messier, D. R.
Gazza, G. E., and Messier, D. R. Cryo-coprecipitation method for preparation of ultrafine mixed metallic-oxide powders, P (10) 257*b*.
Gazzara, C. P. See Caslavsky, J. L.
Geballe, T. H. See Gamble, F. R.
Gebauer, J., and Coughlin, R. W. Preparation, properties, and corrosion resistance of composites of cement mortar and organic polymers, (5) 104*e*.
Gebauer, J., Hasselman, D. P. H., and Long, R. E. Effect of polymer impregnation on physical and mechanical behavior of ceramic tile bodies, (6) 135*j*.
Gebauer, J., Hasselman, D. P. H., and Thomas, D. A. Effect of temp. on the strength of a polymer-impregnated porous ceramic, (4) 85*e*.
Gebauer, J., Krohn, D. A., and Hasselman, D. P. H. Thermal-stress fracture of a thermomechanically strengthened aluminosilicate ceramic, (5) 125*c*.
Gebbett, J. G. Sieving, straining, and grading, (2) 43*j*.
Gebert, H., Lipka, S., and Meyer, M. Method of mfg. electrical capacitors, P (1) 13*i*.
Gebhardt, F., and Horn, H. Use of the plasma torch for analysis of glasses and raw materials, (8) 205*h*.
Gebhardt, F., and Kimmel, S. Investigation of batch analysis of Na_2O-CaO-SiO_2 glasses by X-ray fluorescence analysis, (8) 205*c*.
Gee, A. Method of treating junction diodes to prevent temp.-voltage degradation, P (3) 66*h*.
Gees, R. See Mackenzie, F. T.
Gehres, D. W. Seed holder and growth suppressor assembly for the hydrothermal synthesis of quartz, P (1) 14*i*.
Gehres, D. W., and Negley, P. L. Seed holder for use in hydrothermal synthesis of quartz, P (3) 67*i*.
Gehrig, K. Solid blank process on the IS machine, (8) 197*f*.
Gehrig, O., and Riehm, T. Process of producing alkali metal orthophosphates, P (2) 46*d*.
Geiger, A. L., Chandrasekhar, B. S., and Adler, J. G. Inelastic electron tunneling in Al-Al oxide-metal systems, (6) 148*g*.
Geirnaert, G. Study of surface layers in phase-separated industrial pressed glassware (I) general considerations; (II) comparison of the surface layers and the core of an opacified product, (11) 269*b*.
Geisler, M. J. See Driver, M. C.
Gelb, L. L. Filament structure and process comprising coated B filaments, P (10) 247*h*.
Gelb, T. See Segnit, E. R.
Gel'd, P. V. See Tskhai, V. A.
Gelezunas, V. L. See Johnston, P. A.
Gelin, R. J. Conductive mold comprising a non-conducting supporting wall and a conductive gel coat applied thereto, P (6) 132*e*.
Gell, P. A. M., and Waterworth, T. H. Furnaces for heating glass, P (11) 270*g*.
Geller, S. Crystal structure of the solid electrolyte $(C_5H_5NH)Ag_3I_4$ at −30°C, (10) 258*g*. See Colville, A. A.
Gemesi, J. Plant control of mills and rotary kilns in the cement industry by radioactive isotopes, (5) 104*c*. See Bocsi, I.
Gender, J. R., Makela, L. V., and Wolf, K. Container crown ring inspection apparatus having means disposed between lamps and crown ring for obstructing radial rays from lamps, P (4) 81*b*.
Genisson, R. R., and Thibieroz, J. P. A. Method and apparatus for forming blanks in optical-quality homogeneous glass, P (7) 162*i*.
Genser, M. Deposition of doped and undoped SiO_2 films on semiconductor surfaces, P (2) 40*a*.
Gentile, A. L., and Stafsudd, O. M. Method and apparatus for Czochralski growth of large crystals, P (9) 226*c*.
Gentry, F. E. Peripheral gate SCR with annular ballast segment for more uniform turnon, P (3) 66*e*.
George, V. J. See Thomas, J. B.
Gerdes, R. J., Chapman, A. T., and Clark, G. W. Refractory oxide-metal composites: scanning electron microscopy and X-ray diffraction of UO_2-W, (1) 16*d*.
Gerding, H. See Brinkmann, F. J.
Gereth, R. K., Hull, E. M., and Light, T. B. Flash evaporating GaAs, P (1) 12*d*.
Gerhard, A. R., and Perdick, L. P. Computerized testing of thin-film circuit conductors, (3) 62*c*.
Gerlach, G. See Holznagel, W.
Gerlich, D. See Alterovitz, S.
Germain, A. G., and Dressel, W. G. Coated graphite mold, P (11) 272*c*.
German, S. I. See Timofeev, M. M.
German, W. L., and Harding, D. A. Primary aliphatic alcohol-homoionic montmorillonite interactions, (9) 237*i*.
Gerow, J. V. See West, R.
Gerow, S. A. Silane-stabilized silicate foams, P (8) 194*a*.
Gerow, S. A., and Weidman, V. W. H_2O-insensitive bonded asbestos structures, P (8) 197*b*. H_2O-insensitive bonded perlite structures, P (8) 197*b*.
Gerson, R. See Canner, J. P.
Gerstenberg, D., and Smith, Frank T. J. Technique for the fabrication of Hf nitride resistors, P (6) 140*a*.
Gerstenberg, G., and Krochmann, J. Optical measurements of the wear of glazed tiles, (8) 198*c*.
Gerstner, D. Method of dividing a semiconductor wafer, P (10) 251*b*. Semiconductor device with compensated input and output impedances, P (2) 42*a*.
Gertz, U. Erwin Spuler (1906–1964)—exhibition at the Gallery Charlotte Hennig, Darmstadt, (5) 102*a*.
Gervais, H. V. See Dietert, H. W.
Gervais, J. R. See Gardner, F. M.
Gesing, H. See Schimmer, R.
Getman, A. F. See Shulzhenko, A. A.
Get'man, E. I. See Mokhosoev, M. V.
Getz, R. W. See Hansen, J. H.
Geulen, H. Determination of Na_2O in glass, (8) 204*g*.
Geus, J. W. Ferromagnetic material, P (7) 168*i*. Process for the preparation of acicular submicroscopic permanently magnetizable metal particles, P (10) 252*b*.
Geus, J. W., and Lemmens, J. C. Method and equipment for the preparation of catalytically active bodies, P (9) 232*i*.
Geusic, J. E., Johnson, L. F., and Van Uitert, L. G. Infrared diode-pumped visible laser, P (3) 65*e*.
Gevirzman, R., and Kozirovski, Y. Infrared spectra and spectral shifts of CO adsorbed on evaporated alkali halides (II) films of Cs salts. (3) 73*i*.
Ghandi, S. K. See Ferro, A. P.
Ghose, S. See Yin, Lo I.
Ghosh, A. K. See Lauer, R. B.
Ghosh, A. K., Wakim, F. G., and Addiss, R. R., Jr. Photoelectronic processes in rutile, (5) 122*d*.
Ghosh, D. K. See Bharadwai, S. C.
Ghosh-Tagore, R. N. Mechanism of heterogeneous deposition of thin film rutile, (9) 224*i*.
Ghosh-Tagore, R. N., and Yut, R. F. Chemical vapor deposition of dielectric thin films of rutile, P (7) 168*j*.
Giachi, A. Ceramic artists and their work—Karl and Ursula Scheid. (1) 1*j*.
Giardini, A. A. See Samara, G. A.
Giardini, D. S., Preston, G. A., and Roney, R. N. Method of severing filamentary material [glass], P (5) 107*e*.
Giallorenzi, T. G., and Tang, C. L. Effect of idler attenuation on the spontaneous parametric scattering of intense light in $LiNbO_3$ and $NH_4H_2PO_4$, (5) 120*c*.
Giammanco, F. See Paoletti, G.
Gibbon, D. L., and Hughes, E. W. What really happens in a continuous cleaning oven, (6) 131*d*.
Gibbons, E. F. See DeLosh, R. G.
Gibbons, E. F., Smith, D. E., and Tien, Tseng-

Ying. Ce-activated solid solution Y Ga oxide phosphor, P (8) 200*g*.
Gibbons, H. P. See Beninga, D. H.
Gibbs, R. J. Accuracy of particle-size analyses utilizing settling tubes, (8) 204*e*.
Gibby, R. L. Effect of Pu content on the thermal conductivity of $(U,Pu)O_2$ solid solutions, (7) 171*g*.
Gibeaut, W. A. See Davis, J. A.
Gibson, D. W. Apparatus for preparing high-modulus carbonaceous materials, P (2) 37*c*.
Gibson, F. D., Jr., Halker, B. B., and Thayer, R. L. Electrodeposition of PbO_2, P (4) 87*d*.
Gicklhorn, R. Thaddaeus Haenke's efforts to improve glassmaking in Bolivia about the end of the 18th century, (8) 185*g*.
Giddings, D. G., and Murphy, D. D. Toughening of glass, P (10) 245*h*.
Giddings, D. G., and Twist, D. Method of toughening glass in an oil bath, P (5) 107*e*.
Gidon, M. C. See Girard, R. F. V.
Gielly, J. See Escoubes, M.
Glencke, D. P. Filter material for grinding mills and the like, P (1) 16*h*.
Giersberg, J., and Reiplinger, A. Multiarticle press with hydraulically biased lower rams, P (2) 44*a*.
Giesfeldt, W. O., and Pinnow, R. L. Method for forming ohmic contacts, P (10) 251*e*.
Giess, E. A. See Burns, G.
Giess, E. A., Argyle, B. E., Calhoun, B. A., Cronemeyer, D. C., Klokholm, E., McGuire, T. R., and Plaskett, T. S. Rare earth-Y Fe-Ga garnet epitaxial films for magnetic bubble domain applications, (2) 38*g*.
Giffen, J. W. Article transfer apparatus, P (10) 254*i*.
Giffen, J. W., Duke, D. A., Dumbaugh, W. H., Jr., Flannery, J. E., MacDowell, J. F., and Megles, J. E. Glass laminated bodies comprising a tensilely stressed core and a compressively stressed surface layer fused thereto, P (10) 244*a*.
Gilbert, W. W. See Balthis, J. H., Jr.
Gilbertson, D. F., Jr. Apparatus for use in hand-working glass, P (1) 3*h*.
Gilbreath, B. Shard mosaics, (2) 30*d*.
Gildea, C. T. Falling film cooling of molten glass, P (8) 192*h*.
Giles, D. See Tench, A. J.
Gilfrich, J. V. See Brown, D. B.
Gill, G. P. See Fairholme, R. J.
Gill, R. M. See Dixon, K. G. O.
Giller, H. F. J. I. See Driessens, F. C. M.
Gillery, F. H., and Pressau, J. P. Postheating of sputtered metal oxide films, P (7) 170*d*.
Gillespie, B. E. See Busby, T. S.
Gilliam, O. R. See Breslow, R. A.
Gillooly, G. R. Preparation of halophosphate phosphors using Sb-doped $Ca_2P_2O_7$, P (5) 113*i*.
Gillooly, G. R., and Rabatin, J. G. Alkali monosulfide recrystallization of lanthanide oxysulfide luminescent material, P (6) 137*e*.
Gillott, J. E. See Ciach, T. D.
Gilman, J. J., and Tong, H. C. Quantum tunneling as an elementary fracture process, (5) 123*a*.
Gilpin, J. W. See Harrison, J. R.
Giltner, B. C. See Schroeder, D. A.
Giltrow, J. P., Kinner, G. H., and Lancaster, J. K. C fiber-filled composite materials, P (10) 247*e*.
Gimborg, E. M., and Gusev, A. I. Artificial cooling of kiln shell, (8) 185*h*.
Gimenez, G. A. Process for continuously incorporating modifiers into molten glass, P (8) 193*i*.
Gimpl, M. L. See Fuschillo, N.
Ging, D. See Preininger, E.
Ginsberg, R. N., Marszalek, D. S., and Schneidermann, N. Ultrastructure of carbonate cements in a Holocene algal reef of Bermuda, (1) 2*c*.
Gintert, D. W. See Prange, B. H.
Ginther, R. J., and Claffy, E. W. Laser-stimulated thermoluminescence in glass, (5) 106*c*.
Ginzburg, Yu. N. See Tkachev, V. V.
Giorgi, A. L. See Krikorian, N. H.
Giorgi, J. C. Apparatus for preheating separators for pulverized material, P (3) 54*d*.
Giorgi, T. A. See del'a Porta, P.
Giorgi, T. A., and Ferrario, B. Getter pump with direct resistance heating of getter strip, P (2) 34*d*.
Girard, J. R. M. Flashing electric lamp, P (10) 244*g*.
Girard, R. F. V., and Gidon, M. C. Process for treating substrates of thin magnetic films, P (9) 227*a*.
Girard, R. T. Enameled metal substrates and method of forming, P (5) 105*b*. Method of electrodepositing vitreous coatings atop a multiapertured substrate, P (10) 242*f*.
Giraskii, V. E., and Nakaryakov, A. M. Mold assembly for a continuous casting plant, P (7) 166*a*.
Gitman, E. B. See Sheiko, I. N.
Gitterman, A. K., Davydova, L. Ya., and Efimova, R. P. Selection of optimum fineness for raw-material mixtures, (8) 187*d*.
Gittins, R. See Cornell, R. C.
Giuliano, M. N., and Goins, E. W. Semiconductor switch device, P (11) 275*h*.
Gladkaya, N. V. See Kamenetskii, A. B.
Gladney, H. M., and Veillard, A. Limited-basis-set Hartree-Fock theory of NiF_6^{4-}, (5) 121*a*.
Gladu, N. D. Smoke [stack] clarifier, P (8) 204*b*.
Gladyshev, V. P. See Rakhmatulin, Ya.
Glaise, R. Semiconductor device and method of mfg., P (10) 252*h*.
Glang, R., Holmwood, R. A., Maissel, L. I., and Vergnolle, J. Cr-SiO film resistors, P (7) 168*j*.
Glaser, J. H. Lightweight transparent penetration-resistant [composite] structure, P (4) 86*b*.
Glaski, F. A., Holzl, R. A., and Kaplan, R. B. Composite hard metal product, P (5) 109*f*.
Glasner, A. See Ben-Dor, L.
Glass, A. J., and Guenther, A. H. Damage in laser glass, (5) 105*h*. (Editors) Damage in laser materials: 1971, (7) 166*i*.
Glass, H. L. X-ray double crystal topography of epitaxial magnetic bubble domain garnets, (8) 199*j*.
Glass, H. L., and Hamilton, T. N. Replication of substrate growth band and core structures by epitaxial CVD garnet films, (11) 274*i*.
Glass, W. B. Method of mfg. radiation-sensitive semiconductor devices, P (7) 169*b*.
Glasser, F. P. See Aggarwal, P. S.; Imlach, J. A.; Shahid, K. A.; West, A. R.
Glasser, L. S. D. Alkaline-earth aluminates and their hydrates, (2) 47*b*.
Glaze, J. A., and Kemp, J. C. Faraday rotation studies of an *R*-like center in neutron-irradiated MgO (I) experimental; (II) theory, (5) 120*h*.
Glazer, A. M., and Megaw, H. D. Structure of Na niobate(T_3) at 600°C, and the cubic-tetragonal transition in relation to soft-phonon modes, (10) 261*f*.
Gleim, P. S. See Bean, K. E.
Gleim, P. S., and Bean, K. E. Integrated-circuit fabrication, P (3) 65*f*.
Gleisberg, D. See Schneider-Arnoldi, A.
Gleiter, H. See Weins, M. J.
Glemza, R. See Duecker, H. C.
Glendinning, W. B., and Mark, A. Method of making an IGFE device, P (4) 89*a*.
Glendinning, W. B., and Pharo, W. B. Method of rapidly detecting contaminated semiconductor surfaces, P (10) 252*d*.
Glenk, H. Frequency accuracy specified for oscillating piezoceramic, (2) 44*j*.
Glenn, W. E., Jr. Method for making a composite back projection screen, P (10) 245*b*.
Glew, D. N., and Hames, D. A. Gypsum, disodium pentacalcium sulfate, and anhydrite solubilities in concentrated NaCl solutions, (7) 156*g*.
Glicksman, L. R. See Jeryan, R. A.
Gliemeroth, G. See Bach, H.
Glinn, T. G. J. See Sarkar, B. K.
Glinski, V. J. Monolithic integrated circuit structure, P (2) 41*e*.
Glinski, V. J., and Murphy, B. T. Method of forming monolithic semiconductor integrated circuit devices, P (7) 169*g*.
Glivicky, V. Characteristics of the heat load of the glassmakers, (3) 55*e*.
Globus, A., Duplex, P., and Vautier, R. Process and mill for grinding pulverulent materials and the materials thus ground, P (10) 254*g*.
Glover, G. H. High-field microwave permittivity of electrons in bulk GaAs, (7) 178*a*. Microwave measurement of the velocity-electric-field characteristic of inhomogeneous epitaxial GaAs with conducting substrate, (6) 150*h*.
Glukhov, N. A., Eliseev, S. S., and El'manova, N. A. Reaction of $ReCl_5$ with MoO_3, (5) 123*h*.
Glushchenko, V. I. See Borisov, V. G.
Gmelin, E. Diffusion and precipitation of He in irradiated and annealed BeO, (7) 171*d*.
Gnaedinger, J. P. Statistical study of variations in materials and compacted densities by sand-cone and nuclear methods, (7) 173*i*.
Gnecco, R. Semibaked porcelain teeth, P (3) 62*a*.
Gnesin, G. G. See Yavorskii, I. A.; Zeigarnik, V. A.
Goan, J. C. Method for improving graphite fibers for plastic reinforcement and products thereof, P (4) 84*d*.
Goates, J. R. See Ott, J. B.
Goates, J. R., Ott, J. B., and Delawarde, E. Solid-liquid phase equilibria in the K+Rb and Rb+Cs alloy systems, (6) 151*f*.
Godina, N. A., Savchenko, E. P., and Keler, E. K. Study of the systems Sm_2O_3-Nb_2O_5, Gd_2O_3-Nb_2O_5, Dy_2O_3-Nb_2O_5, and Yb_2O_3-Nb_2O_5 in the regions rich in Nb_2O_5, (2) 50*d*.
Godron, Y. G. Graphite-glass compositions and method of making, P (3) 58*a*.
Goeddel, W. V. Nuclear fuel particles, P (7) 171*i*. See Dahlberg, R. C.
Goeddel, W. V., and Luby, C. S. Process for making pyrolytic C coated nuclear fuel or poison, P (3) 68*h*.
Goehre, O. See Friedrichsen, W.
Goeller, H. Method of producing fluosilicic acid of low P content from waste gases, P (5) 117*h*.
Goelzer, W. C., Moratelli, P. A., Jr., Griffith, A. M. III, Myers, D. D., Opitz, H. E., and Procopio, J. J. Method of coating glassware, P (11) 270*d*.
Goering, C. See Riedel, W.
Goerk, H. Course of the drawing stream before and in the drawing chamber of the Fourcault process, (7) 158*c*. Method and apparatus for investigation of the layered structure of plate glass, (7) 159*j*. Properties and occurrence of layers in the layered structure of flat glass, (7) 160*b*.
Goessens, L. H. Process computer for controlling the raw materials composition for a cement kiln, (4) 79*h*.
Goetz, C. C. Surface coating compositions, P (8) 189*c*.
Goetz, J. Influence of melting conditions on the H_2O content of glass, (9) 217*j*.
Goetzinger, N. J. See Silvernail, W. L.
Goffee, J. A. Nonvolatile memory cell, P (7) 169*g*.
Goins, E. W. See Giuliano, M. N.
Gokhale, K. V. G. K. See Maiti, H. S.; Ramani, S. V.; Rao, T. C.
Goldbach, G. See Boerner, M.
Gol'dberg, I. A. See Karklit, A. K.
Goldberg, P., Hansford, J., and van Heerden, P. J. Polarization of light in suspensions of small ferrite particles in a magnetic field, (6) 151*b*.
Golde, H. J. See Toppler, B.
Goldfein, S. Impact-resistant concrete admixture, P (6) 130*f*.
Golding, I. L. S. Gas dryers, P (10) 256*h*.
Golding, R. M., Healy, P. C., and White, A. H. Temp. dependence of the magnetic moment for d^3 ions in an intermediate crystal field of octahedral symmetry, (6) 152*a*.
Goldman, J. Creative slip casting, (2) 30*e*.
Goldmann, L. S., and Liander, L. E. Chip torque testing, P (2) 39*f*.
Goldmann, W. See Ritzman, H.
Goldrick, M. R., Kerwin, R. E., and Skinner, J. G. Laminar photomask, P (10) 251*a*.
Goldstein, B. Direct measurement of diffusion length in GaAs by α particles, (4) 96*e*.
Goldstein, B., and Carlson, D. E. Determination of the composition of glass surfaces by Auger spectroscopy, (2) 32*c*.
Goldstein, C., and Pasternak, M. Internal field studies of ferromagnetic CrI_3 by the Moessbauer effect in ^{129}I, (5) 121*c*.
Goldstein, D. Prototype assembly facility for CerDip packaging, (11) 274*h*.
Goldstein, M. See Johari, G. P.
Goldstein, N. P., and Sun, K. H. Apparatus for power and breeding distribution measurements in breeder reactors, P (11) 276*c*.
Goldsworthy, W. B. Pultrusion machine, P (11) 270*h*.
Golia, M. J., McMaster, R. C., and Cooper, G. L. Ultrasonic nondestructive thickness gage, P (3) 70*g*.
Golliher, W. R., Harris, R. L., and LeDoux, R. A. Separation of Np from UF_6 containing the same, P (2) 43*f*.
Golovashkina, N. V. See Chernyavskii, K. S.
Golovaya, V. D. See Yas, D. S.
Golovkin, Yu. I. See Kestner, O. E.
Golub, A. M., Nguyen Chong Yen, and Grigorenko, F. F. Zn niobates, (9) 239*g*.
Golubtsova, R. B., Grigor'eva, S. V., and Myasnikova, K. P. Separation and study of carbidic phases formed in Ni alloys, (10) 260*i*.
Golubyak, L. S. See Kislyi, P. S.
Gomez, M. P. See Camahort, J. L.
Gomi, Shinpei. See Umeya, Kaoru.
Gon, P., and Ray, S. MgO content in portland blast furnace slag cement, (11) 266*i*.
Goncharenko, A. S. Correlation of standard oxidation-reduction potentials with crystal-chemical parameters in O compounds of some transition metals, (5) 119*a*.
Gondrand, M., Brunel, M., and De Bergevin, F. Demonstration of a new type of NaCl superstructure: structure of compositions $TNaO_2$ (T=Dy,Ho,Y,Er), (10) 258*c*.
Gontar, K. V. See Bergman, A. G.
Gonzales, J. See Lee, B. Y. S.
Gooch, D. J., and Groves, G. W. Prismatic slip in sapphire, (3) 74*h*.
Goodacre, R. Mounting devices for thyristors, P (8) 201*i*.
Goodenough, J. B. Comment on the magnetic properties of several In thiospinels, (10) 258*d*. See Dionne, G. F.
Gooding, J. E. See Jelinek, J. W.
Gooding, R. W., Abbey, W., and Parratt, N. J. Process [wet] and apparatus for classifying fibers, P (4) 92*g*.
Goodman, A. M., and Breece, J. M. Thin tunnelable layers of SiO_2 formed by oxidation of Si, (9) 239*d*.
Goodnight, H. See Zink, J. S.
Goodrich, G. W. See Deradoorian, B.
Goodrum, J. W. See Kahan, A.
Goodwin, J. W. Rheological studies on the dispersion of kaolinite suspensions, (2) 49*h*.
Goodwin, R. C. Self-acting connector for applying coolant air to glass molds, P (3) 59*f*.
Googin, J. M. See Asbury, J. J.
Goorissen, J., and Van der Werf, P. Method of vacuumtight closure of thin Be windows and X-ray tube provided with such a window, P (3) 66*h*.
Goossens, U. P. M. Gas and/or vapor discharge lamp having a U-shaped discharge tube, P (9) 219*a*. Low-pressure Na vapor discharge lamps, P (6) 133*e*.
Gorbatkina, Yu. A. See Andreevska, G. D.
Gorbenko, Yu. E. See Likhoradov, A. P.
Gordon, R. G. See Wheeler, J. C.
Gordon, R. S. See Marchant, D. D.
Gordon, R. S., and Terwilliger, G. R. Transient creep in Fe-doped polycrystalline MgO, (10) 261*d*.
Gordon, W. D., and Norman, R. S. Process for forming hermetic seal for sheathed electrical conductors, P (2) 35*a*.
Gorey, E. F. See Brack, K.

Gorsall, H. A. Endless furnace and method of utilizing same for dry process vitreous enameling, P (6) 131*b*.
Gorodetsky, G., Shtrikman, S., Tenebaum, Y., and Treves, D. Temp. dependence of the susceptibility tensor of a weak ferromagnet: $YFeO_3$, (5) 124*h*.
Goroshchenko, Ya. G. See Biryuk, L. I.
Gorshkov, V. S., Sominskii, E. A., Myagkova, M. A., and Popov, K. N. Infrared spectroscopy of glasses containing trace impurities, (9) 217*c*.
Goryachev, Yu. M., and Kutsenok, T. G. Coeff. of thermal expansion of alloyed Ce_2S_3 in the Ce_2S_3-Ce_3S_4 homogeneity region, (10) 258*d*.
Goryunova, N. A. See Borisova, Z. U.
Gosden, D. V. See Williams, Frank R.
Goshi, Yoichi, and Fukao, Y. Double-crystal X-ray spectrometer, P (5) 116*e*.
Goshokubo, Kunio. See Kodama, Kazumi.
Gosney, W. M. See Carbajal, B. G., III.
Goswami, A., and Nikam, P. S. Epitaxial growth and phase change in monoselenide of Co, (7) 177*c*.
Goswami, A. K. Switching mechanism in amorphous semiconductors, (6) 152*g*.
Gothard, E. S., and Calfee, J. D. Nylon spun bonded fabric-concrete composite, P (5) 104*i*.
Goto, Eizo. Glass brazing method, P (1) 4*f*.
Goto, K., Lodde, J., and Pluschkell, W. Ligand field absorption spectra of quenched MnO-SiO_2-base slags equilibrated with various O and S pressures, (6) 149*b*.
Goto, Kunihiro, and Matsumoto, Akira. Preparation of Ce monosulfide, (6) 143*j*.
Goto, Takenari, and Langer, D. W. Stimulated emission and excited states of the I_0 donor electron in ZnO, (7) 181*a*.
Goto, Tsuneaki, Nishimura, K., Kabashima, S., and Kawakubo, T. Relaxation process in ESR of Ti-doped VO_2, (3) 74*j*.
Goto, Yasumasa. See Takahashi, Katsuaki.
Gottardi, G. Structural features of some group silicates with chains of octahedra, (1) 25*j*.
Gottardi, V., and Bonetti, G. Discontinuity of certain properties of liquid-state glasses as a function of temp., (7) 159*c*.
Gottling, J. G. See Aponick, A. A., Jr.
Gouda, G. R. See Roy, D. M.
Gough, J. R. C., Meaden, G. W., and Price, M. S. T. Mfg. nuclear fuel elements, P (9) 228*i*.
Goullin, J. F. Epitaxial growth by vapor-phase transport, (8) 199*g*.
Goundry, P. C. See Carrell, M. A.
Goursat, P., Lortholary, P., and Billy, M. Si-O-N system (I) preparation of the oxynitride Si_2N_2O, (6) 151*e*.
Govind, P. K., and Fraikor, F. J. Electron microscope study of radiation damage in Bi ion-implanted CdS, (4) 96*j*.
Govorov, A. A., Ovramenko, N. A., and Dzhus, E. V. Hydration hardening of concentrated dispersions of the system CaO-MgO-Al_2O_3-SiO_2 under autoclave conditions, (7) 156*h*.
Goymour, C. G., and King, D. A. Field emission study of the formation and desorption of oxide layers on W surfaces, (11) 281*j*.
Gozenbuk, L. G. See Ksendzovskii, V. R.
Grabmaier, J. Method of producing epitactic layers of electrical-insulation material on a carrier body of semiconductor material, P (6) 139*f*. Method of producing epitaxic semiconductor layers on foreign substrates, P (7) 169*d*. Method of producing stoichiometric Mg-Al spinel crystals for integrated circuits, P (3) 66*e*. Thin semiconductor growth layer on Al_2O_3-deficient crucible-pulled Mg Al spinel monocrystal as well as the method for producing the layer and producing the monocrystals, P (3) 68*b*.
Grabner, H., and Konow, H. Restarting arrangement for high-pressure Hg-vapor lamp which includes metallic halide additives, P (2) 42*g*.
Grabner, L. H. Photoluminesence in $SrTiO_3$, (5) 122*d*.
Grace, M. I. Semiconductor diode hf signal generator, P (6) 140*d*.
Grady, J. J. Steel slag handling system and method for using, P (1) 3*a*.
Graebner, J. E., and Greiner, E. S. Magnetothermal oscillations and the Fermi surface of ReO_3, (6) 150*e*.
Graenicher, H. Process for the culture of large monocrystals of Li niobate, P (1) 14*d*.
Graf, R. E. See Deeg, E. W.
Graf, S. A. See Keller, J. P.
Graff, W. A., and Kohut, J. Seal glasses, P (9) 219*j*.
Graffeo, J. V., Jr., Mason, B. W., Jr., and Wells, W. O. Sputtering system, P (9) 228*c*.
Graham, A. L. See Dietert, H. W.
Graham, B. CrO_2 recording compositions stabilized with long-chain ammonium salts, P (4) 87*a*.
Graham, C. E., Lumley, R. M., and Oberholzer, D. J. Laser substrate parting, P (4) 88*i*.
Graham, G. M., and Pereira, F. N. D. D. Temp. variation of the piezoelectric effect in quartz, (5) 124*h*.
Graham, H. C. See Davis, H. H., Jr.
Graham, H. C., Tallan, N. M., and Mazdiyasni, K. S. Electrical properties of high-purity polycrystalline $BaTiO_3$, (1) 11*d*.
Graham, R. P. See Crouch, A. G.; Hryniszak, W.
Grainger, K. F. See Critchley, D.
Grakhova, S. K. See Chebukov, M. F.
Gramer, E. A. See Javorsky, B. S.
Granger, A. F. Method of mfg. unitary porous C bodies, P (8) 196*g*.
Granik, V. A., Oleinikov, N. N., Pivovarov, L. Z., and Tret'yakov, Yu. D. Physicochemical transformations in ferrites with a rectangular hysteresis loop during thermal treatment, (8) 199*f*.
Grankovskii, I. G., and Kruglitskii, N. N. Investigation of structure-formation processes in aqueous dispersions of cements, (6) 129*a*.
Grannec, J. See Ravez, J.
Grant, D. G. See Mahan, A. I.
Grant, J. M. Image intensifier with electroluminescent phosphor, P (10) 250*h*. Tubular photocell with secondary emission from internal surface, P (4) 91*a*.
Grassaud, J. See Cohen-Alloro, R.
Grau, G. See Fontanel, A.
Graulier, M. Preparation of active Al_2O_3 agglomerates of high mechanical strength, P (4) 94*f*.
Graves, G. A. See Barta, J.
Graves, R. H. W. Determination of the optical constants of anisotropic crystals, (1) 17*h*.
Graves, W. E. See Roberts, H. H.
Gray, D. N. Decorative decal with a pyrolyzable film base, P (4) 81*d*. Process for decorating a glass surface, P (8) 193*j*.
Gray, F. L. Method and apparatus for forming and drawing fused metal-oxide tubes [SiO_2], P (3) 58*j*. See Roques, R. A.
Gray, P. V. Method of making complementary FETs by single-step diffusion, P (2) 41*f*.
Grealey, M. Apparatus for acid polishing or like treatment of glass articles, P (1) 3*c*.
Greaves, E. I., and Lakin, J. R. Constitutional changes in high-Al_2O_3 bricks in arc-furnace roofs, (1) 6*i*.
Greaves, W. N. Vapor deposition of alloys, P (7) 170*h*.
Grebene, A. B. See Kleitman, D.
Grebenkina, V. G. See Samsonov, G. V.
Grebenshchikov, R. G. Relation of thermodynamic and refractometric properties of silicates, (9) 238*f*. Structural analogy, solid solutions, and electrical properties of some multicomponent silicates and germanates, (7) 181*c*.
Grebenyuk, Yu. L. See Sheinin, E. I.
Greedan, J. E., and McCarthy, G. J. Crystal chemistry and magnetic properties of Eu_2TiO_4 and $Eu_2Ti_2O_7$, (9) 234*e*.
Green, D. R. Transient thermal method and means for nondestructively testing a sample, P (10) 256*b*.
Green, G. W., and Sundberg, D. G. Fire-resistant wallboard, P (2) 31*e*.
Green, L. Q., and Light, L. L. Method for coating glass, P (9) 219*a*.
Green, M. Pinch effect laser, P (3) 66*h*.
Green, P. S., Church, J. M., and Eilers, G. J. Differential ultrasonic visualization of impact fractures in glass-reinforced plastics, (5) 105*i*.
Green, R. See Hellesland, J.
Green, T. E. Determination of metallic Al in recycled glass, (7) 158*e*.
Greenberg, C. B., and French, P. W. Passive and dynamic absorption at 1.06 μm in glass, (1) 3*g*.
Greenberg, H. J. Glass temp. measurement (I–II), (10) 243*f*.
Greenborg, J. Neutron attenuation mechanisms in concrete shielding, (5) 114*j*.
Greene, L. C., and Wilson, H. A. Edge emission bands in high-purity CdS, (5) 120*b*.
Greene, P. E. See Stringfellow, G. B.
Greener, J. W., and Waldron, B. B. Improved control of standardized china clays, (4) 94*e*.
Greenewald, H., Jr. Apparatus and methods for processing ceramic mold and core materials, P (3) 61*b*.
Greenham, A. C., and Richards, B. P. Explosive shocking of Al_2O_3 powder, (1) 22*h*.
Greenhouse, H. M. See Galla, R. T.
Greening, N. R., Copeland, L. E., and Verbeck, G. J. Modified portland cement and process, P (4) 79*h*.
Greenler, R. J. Device for trapping and removing gas bubbles from a glass mfg. chamber, P (3) 58*a*.
Greenstein, B. See Mason, D. W.
Greenstein, B., Langston, P. R., Jr., Narken, B., and Sunners, B. Method for making monolithic optoelectronic structure, P (8) 193*j*.
Grego, P., Kozlowski, T. R., and Schuyler, P. M. Decorating glass-ceramic articles, P (7) 161*b*.
Gregor, L. V., Maissel, L. I., and Standley, C. L. Apparatus and method for sputter etching, P (3) 64*e*.
Gregor, L. V., and Zuegel, M. Glass-annealing process for encapsulating and stabilizing FET devices, P (8) 200*g*.
Gregory, T. K. See Douglas, F. C.
Greig, W. J. Process for isolating semiconductor elements, P (2) 42*c*. Semiconductor device with multilevel metalization and method of making, P (3) 67*d*.
Greig, W. J., and Soden, R. R. Semiconductor device with multilevel metalization and method of making, P (9) 227*f*.
Greil, E. Method and apparatus for firing graduations, symbols, and lettering into glass articles, P (6) 133*g*.
Greiner, E. S. See Graebner, J. E.
Greiner, N. S., and Magee, J. V. Textured cementitious sheet, P (2) 31*g*.
Grenier, J. C., Martin, C., and Durif, A. New study of the $Ca(PO_3)_2$-$NaPO_3$ equilibrium diagram. Crystallographic data for $CaNa_4(PO_3)_6$ and $CaNa(PO_3)_3$, (8) 209*h*.
Grenier, P. See Combe, C.
Greskovich, C., and Lay, K. W. Grain growth in very porous Al_2O_3 compacts, (4) 96*i*.
Greskovich, C., O'Clair, C. R., and Curran, M. J. Preparation of transparent Y_2O_3-doped ThO_2, (7) 179*g*.
Grewen, O. See Majdic, A.
Grey, I. E., and Reid, A. F. Shear structure compounds $(Cr,Fe)_2$-$Ti_{n-2}O_{2n-1}$ derived from the α-PbO_2 structural type, (10) 260*j*.
Gribenyuk, Yu. N. See Shibryaev, B. F.
Griener, J. D. See Uttecht, R.
Grieve, A. [Oscillating] apparatus for the treatment of particulate solids, P (6) 141*g*.
Griffin, R. M. See Audesse, E. G.
Griffin, W. F., and Morena, A., Jr. Ceramic package, P (4) 87*j*.
Griffith, A. M., III. See Goelzer, W. C.
Griffiths, C. R., and Russell, R., Jr. Time effects in the hysteresis loop of (Pb,Sr)TiO_3, (3) 63*j*.
Griffiths, R. Mechanical properties of ceramics (I–III), (1) 17*h*.
Grigorenko, F. F. See Golub, A. M.
Grigor'ev, I. V. See Fain, I. A.
Grigor'eva, S. V. See Golubtsova, R. B.
Grigorovici, R. Short-range order in amorphous semiconductors, (3) 63*h*.
Grimes, D. M. Ferrite radar-absorbing material, P (8) 200*d*.
Grimes, N. W. Self diffusion in compounds with spinel structure, (10) 260*h*.
Grimm, A. C. See Ball, C. G.
Grimm, N., Scott, G. E., and Sibold, J. D. Infrared transmission properties of high density Al_2O_3, (1) 11*b*.
Grimm, R., and Siekbert, A. New steel for enameling, (8) 189*b*.
Grimm, R. E. See Pecoraro, G. A.
Grimshaw, R. W. Chemistry and Physics of Clays and Allied Ceramic Materials, 4th ed., rev., B (6) 153*c*. See White, I. G.
Grimvall, S. Crystal structure of $NaHSO_4 \cdot H_2O$, (11) 280*g*.
Grinberg, Ya. Kh., Zhukov, E. G., Koryazhkin, V. A., and Medvedeva, Z. S. Heterogeneous equilibria in the system BP-S, (8) 209*f*.
Grinfeld, R. See Suarez, C. B.
Grisafe, D. A. Phosphor compositions and processes for producing same, P (6) 139*j*.
Griscom, D. L., Taylor, P. C., and Bray, P. J. Reply to "Structure of trapped-hole centers in γ-irradiated borate glasses." (7) 158*j*.
Griswold, D. A., and Hotaling, R. A. Method of controlling phosphor pH in processing, P (2) 41*a*.
Grjotheim, K., Holm, J. L., Lillebuen, B., and Oeye, H. A. Densities and excess molar vols of binary and ternary melts of $MgCl_2$, $CaCl_2$, and alkali metal chloride, (5) 119*f*.
Grjotheim, K., Holm, J. L., Malinovsky, M., and Mikhael, S. A. Systems K_3AlF_6-Li_3AlF_6 and Rb_3AlF_6-Li_3AlF_6 (I) phase diagrams, (4) 99*c*.
Grjotheim, K., Holm, J. L., and Welch, B. J. Gibbs free energy of formation of liquid AlF_3, (11) 281*a*.
Grjotheim, K., Ikeuchi, H. A., Dhabanandana, S., and Krogh-Moe, J. Solution of alkaline earth metals in their molten halides (III) densities of melts in the systems Ba-$BaCl_2$, Ba-$BaBr_2$, and Sr-$SrCl_2$, (11) 282*d*.
Grjotheim, K., and Matiasovsky, K. Chemical reactions in the system Na_3AlF_6-SiO_2-Al, (7) 176*e*.
Grochowski, E. G. See Castrucci, P. P.; Collins, R. H.
Grochowski, E. G., and Lyons, V. J. Semiconductor wafer processing, P (1) 14*b*.
Grocke, D. Device for packaging piece goods on a base frame, P (3) 69*d*.
Grodkiewicz, W. H., Singh, S., and Van Uitert, L. G. GaAs junction diode-activated upconverting phosphor, P (8) 200*f*.
Grodkiewicz, W. H., and Van Uitert, L. G. Flux growth of rare earth fluorides, P (9) 232*g*.
Groenendijk, H. See Konijnendijk, W. L.
Groenewegen, P. P. M., and Huiszoon, C. Debye-Waller *B* values of some NaCl-type structures and interionic interaction, (10) 258*b*.
Grofcsik, J. Terminology problems of the ceramic industry, (7) 182*d*.
Grofcsik, J., and Boszilkov, V. Mfg. acid-resistant and wall-lining ceramics from high-Fe bauxite bedrock clays, (5) 109*j*.
Grogan, J. T. See Ryan, R. J.
Groom, B., and Chivers, M. A. Kiln furniture and refractories (II), (1) 10*d*.
Gropyanov, V. M. See Andreeva, N. A.
Gropyanov, V. M., Kuznetsova, V. L., and Laptun, V. I. Oxidation kinetics of SiC heating elements, (8) 195*a*.
Groschwitz, E. Integrated optical-electronic solid-state system having 2 superimposed circuit planes linked by optical and/or electronic and horizontal and/or vertical connections, P (4) 88*h*.
Groshev, V. I. See Nezhevenko, L. B.
Grosheva, V. M. See Karpinos, D. M.
Gross, F., and Krapf, R. Reactor core for thermionic nuclear reactor, P (11) 276*e*.
Gross, F., Kahl, P., and Mammach, P. Traveling-wave tube with a vacuumtight ceramic window, P (6) 140*c*.

Gross, H. W. See Hartmann, R.
Grosseau, A. Methods of coating surfaces and elements comprising such surfaces, P (10) 242*g*.
Grossman, D. G. Machinable glass-ceramics based on tetrasilicic mica, (10) 243*g*.
Grosso, P. F., and Heck, R. F. Method of forming phosphor screen, P (10) 245*b*.
Groth, R. See Frank, B.
Groth, R., Van Boort, H. J. J., and De Neve, G. M. J. Method of mfg. glass articles having a heat-reflecting film, P (9) 219*b*.
Grothe, W. See Brill, K.
Grotheer, M. P., and Peterson, J. A. Graphite anode treatment, P (4) 84*j*.
Grotyohann, A. G. Method and means for automating computer-controlled production of particulate materials [TiO_2], P (8) 205*j*.
Grove, A. S. See Vadacz, L. L.
Grove, F. D. See Long, G. E., III.
Grove, L. E. See Scott, K. E., Jr.
Grove, R. J., and Reeder, M. M. Radome and method of making, P (3) 59*e*.
Groves, G. W. See Gooch, D. J.
Grubba, D. C. Flame-deposited oxide coating and method of making, P (5) 105*c*.
Grubba, D. C., and Peterson, J. D. Spray coating compositions, P (3) 54*i*.
Gruber, B. A. High-strength metal-SiC article, P (7) 164*f*. Laminated [SiC] article, P (10) 247*j*.
Gruber, G. A. See Chu, Ting Li.
Grubin, H. L. See Solomon, P. R.
Grudenski, E. E. See Kolb, E. D.
Gruen, G. See Lang, F.
Gruget, A. Method of producing pads or mats of mineral fibers [glass], P (2) 34*g*.
Grundmann, W. Operation and introduction of the M-16 machine for the production of thin-walled glassware, (8) 191*h*.
Grunwald, J. J. See Rhodenizer, H. L.
Gruver, R. M. See Buessem, W. R.; Kirchner, H. P.
Gualandi, D., and Jehenson, P. Process for the production of a composite material Al-Mg-Al_2O_3-MgO, P (3) 68*i*.
Guarino, G. See Cimino, A.
Gubarev, Y. F. See Akhunov, A. M.
Gude, K. E., and Lund, B. Process for producing cement from cement slurry and a plant for carrying out the process, P (9) 215*g*.
Guenther, A. H. See Glass, A. J.
Guenther, R. A., and Weinstock, H. Effects of colloids on the thermal conductivity of γ-irradiated KCl, (5) 120*e*.
Guerga, M. Hyperfrequency dryers in the ceramic industry, (2) 45*g*.
Guerin, Y., and de Novion, C. Crystal structure of V_2C_7, (7) 176*h*.
Guerra, C. A. See Martinez, J. R.
Guertler, H. C. G. H. Asbestos fabricating process and products thereof, P (4) 84*f*.
Guetin, P., and Schreder, G. Quantitative aspects of the tunneling resistance in *n*-GaAs Schottky barriers, (7) 179*i*.
Gugel, E. See Jangg, G.; Kieffer, R.
Guger, C. E., and Manning, F. S. Kinetics of ZnO reduction with CO, (6) 149*h*.
Guggenheim, H. J. See Berglund, C. N.; Dillon, J. F., Jr.; Yasuoka, Hiroshi.
Gugger, G. See Sch'afli, H.
Guha, J. P., and Kolar, D. Indentification of $BaO{\cdot}4TiO_2{\cdot}Al_2O_3$ in the system $BaO{-}TiO_2{-}Al_2O_3$, (2) 48*f*.
Guha, S. Rate of growth and decay of high-field domain in *n*-type GaAs, (1) 11*h*.
Guicciardi, F., and Palagi, P. Process for the purification of $TiCl_4$ from traces of C compounds, P (2) 46*e*.
Guicherd, R. H. See Denis, P. M.
Guild, C. H., Jr. See Leith, F. A.
Guilland, H. F. Early American Folk Pottery, B (11) 283*i*.
Guillet, H., Jacob, L., Mouchart, J., and Sturel, B. Device for improving the homogeneity of a laser beam, P (8) 200*i*.
Guilliatt, I. F., and Brett, N. H. Crystallite size and shape relations in the product-precursor pair $MgO{-}Mg(OH)_2$, (6) 146*d*. Effect of impurities on the powder properties of $Mg(OH)_2$ decomposed in vacuo, (1) 21*i*.
Guinn, F. K. See Gammill, A. M.
Guiochon, P. See Desvignes, F.; Ledran, J. P.
Gujer, H. Band filter press, P (1) 16*j*.
Gujer, H., and Koller, K. Device for sealing off the filter press cavity between 2 filter press elements, preferably 2 revolving filter press bands or belts of a filter press, P (4) 92*c*.
Gulbransen, E. A. See Andrew, K. F.
Gulden, T. D. C thermal diffusion in the UC_2-C system, (2) 43*e*. See Kaae, J. L.
Gul'ko, N. V. See Kamenetskii, A. B.
Gullman, J. See Olofsson, O.
Gumenyuk, E. L. See Karpinos, D. M.
Gundzik, R. M. See Stern, D. R.
Gungle, W. C. See Lo, J. M.
Gunn, K. M., and Fuller, M. H. Compression resistance testing machine for pelletized material, P (2) 44*i*.
Guntersdorfer, M. Barrier-free semiconductor switching device, P (2) 39*c*. Thermal effects connected with switching in amorphous semiconducting chalcogenide films, (4) 87*a*.
Gupta, C. K. See Kamat, G. R.
Gupta, D. C. Apparatus and method for measuring the carrier concentration of semiconductor materials [Si], P (6) 142*b*. Improved methods of depositing vapor-phase homoepitaxial Si, (3) 63*b*.
Gupta, T. K. Possible correlation between density and grain size during sintering, (6) 151*e*. Sintering of MgO—densification and grain growth, (2) 49*j*. Strength behavior of thermally shocked ZnO, (9) 238*g*. Strength degradation and crack propagation in thermally shocked Al_2O_3, (6) 152*a*.
Gupton, J. A., Jr. Electrophoretic deposition of color phosphors, P (10) 244*e*. Method of producing luminescent screens by the electrophoretic process, P (10) 245*e*.
Gurev, H. S. See Black, J. R.
Gurevich, B. D. See Nezhevenko, L. B.
Gurevich, Ts. N. See Pavlushkin, N. M.
Gurgacz, S. S. Transfer mechanism, P (1) 10*i*.
Gurskii, G. L. See Pyatikop, P. D.
Gusarov, A. D., and Deshko, Yu. I. Device for determining rheological properties of raw-material slurries, (8) 204*h*.
Gusev, A. I. See Gimborg, E. M.
Gustafson, E. L., and Rand, H. B. Improve your tumbling, (3) 53*h*.
Gustavsson, K. A. G. Apparatus for cleansing flue gases, P (2) 43*h*.
Gustinetti, A. See Stella, A.
Gusynin, V. F. See Ivanov, I. P.
Gutberlet, L. C. See Bertolacini, R. J.
Guth, J. L., Collin, P., and Wey, R. Preparation and properties of a type A zeolite enriched with Si, (8) 206*i*.
Guthrie, B. M. Glass fiber forming apparatus, P (1) 4*f*.
Gutop, V. G., Kardunskii, I. I., Karnaushenko, G. A., and Zezin, M. A. Automatic oil feed through glass tank burners, (8) 206*c*.
Gutsche, B. See Herrman, R.
Gutt, W., and Osborne, G. J. System $CaO{-}2CaO{\cdot}SiO_2{-}CaF_2$, (1) 25*h*.
Gutta, J. J. See Audesse, E. G.
Guy, A. G. Introduction to Materials Science, B (2) 51*c*.
Guyader, J., and Lang, Jean. System Ca_3N_2-Ge_3N_4 (II) reactions of the ternary nitrides of Ca and Ge, (4) 99*j*.
Guyer, V. L., and Schafer, R. J. Curing of foundry molds and cores by induction heating, P (5) 109*h*.
Guzman, I. Ya., Purusova, T. N., Poluboyarinov, D. N., and Karpilovskaya, M. N. Synthesis of Si oxynitride, (8) 207*b*.
Guzowski, R. M. See Insolio, T. A.
Gyorgy, E. M., Dillon, J. F., Jr., and Remeika, J. P. Photoinduced magnetic effects in YIG (Si), (9) 237*c*.
Gyula, Z. Influence of curing temp. on structure formation of hardened portland cement, (5) 103*b*.

Haag, A. P., and Weiner, M. Particle-size control, P (3) 71*e*.
Haarbye, F. O. Ag-Cd oxide electrical contact materials, P (9) 228*a*.
Haas, B. See Dietzel, A.
Haas, E., Martin, J., Reuschel, K., Schink, N., and Vogel, C. H. Vacuum apparatus for excluding C impurities from an Si body, P (1) 15*c*.
Haas, L. A. See Khalafalla, S. E.
Haas, L. A., and Khalafalla, S. E. Removing SO_2 by CO reduction, (10) 256*c*.
Haas, L. A., McCormick, T. H., and Khalafalla, S. E. Activity patterns in the catalytic reduction of SO_2 on some transition elements in Al_2O_3, (11) 280*d*.
Haas, M. See Jonke, A. A.
Haas, P. A., and Clinton, S. D. Method for preparing oxide gel microspheres from sols, P (3) 69*d*.
Haas, W. A. Steiner tunnel furnace, (2) 44*g*.
Habashi, Fathi, Dugdale, R., and Holderreed, F. L. Refining low-grade Be ores by treatment with anhydrous SO_3, P (7) 176*a*.
Habata, Hidetsugu. See Kimura, Isao.
Haber, A. Ceramic ware deburring machine and dressing heads, P (5) 115*f*.
Haberecht, R. R. See Sivertsen, D. R.
Habrman, Z. Spectrochemical control of corrosion of Mo and oxide electrodes and of fused-cast refractories in electric glass tanks, (8) 191*g*.
Hack, P. See Bockstiegel, G. E.
Hack, P., Hass, K., and Schinke, G. Process for mfg. shaped articles of Zr-corundum, P (10) 248*h*.
Hacke, H. J. Method of forming stacked circuit boards, P (10) 251*f*.
Hackett, W. H., Jr. See Saul, R. H.
Hackett, W. H., Jr., Scharfetter, D. L., and Varnerin, L. J., Jr. Doping profile for GaP diode improved electroluminescent efficiency, P (9) 225*d*.
Hacman, D. Method for monitoring temp. variations of radiation-permeable substrates for supporting thin coatings applied by vacuum deposition, P (3) 66*b*.
Hada, Toshio. See Wasa, Kiyotaka.
Hada, Toshio, Wasa, K., and Hayakawa, S. Bistable switching of ZnO thin film diodes, (3) 62*g*.
Hadeishi, T., and McLaughlin, R. D. Hyperfine Zeeman effect atomic absorption spectrometer for Hg, (4) 93*d*.
Haden, W. L., Jr., and Dzierzanowski, F. J. Microspherical zeolitic cracking catalyst, P (8) 207*i*. Microspherical zeolitic molecular sieve composite catalyst and preparation thereof, P (6) 144*f*. Zeolitic catalyst and preparation, P (8) 207*i*.
Haefner, S. See Holmes, L.
Haerdtl, K. H. Electromechanical resonator employing piezoelectric ceramic consisting of Pb zirconate-titanate containing MnO, P (9) 225*f*. See Carl, K. F. L.
Haerdtl, K. H., and Hennings, D. Distribution of *A*-site and *B*-site vacancies in (Pb,La)$(Ti,Zr)O_3$ ceramics, (6) 136*g*.
Haering, R. R., and O'Hanlon, J. F. High-voltage thin-film transistor, P (9) 225*c*.
Haertling, G. H. Ferroelectric ceramic materials, P (9) 225*j*.
Haes, E. J., and van der Maat, A. T. Method for mfg. ceramic magnetic articles, P (4) 92*e*.
Haeusler, G., and Hohberg, G. Light scattering measurements on polished glass surfaces, (8) 205*d*.
Haewecker, M. See Riedel, W.
Hafemeister, D. See Barros, F. de S.
Hafford, B. C. See Colombo, U.
Hafner, S. S., and Raymond, M. Effect of O octupoles on the electric field gradient at the Al^{3+} sites in corundum (α-Al_2O_3), (5) 120*d*.
Hagan, J. T. See Field, J. E.
Hagdahl, E. L. Gas or liquid filter, P (7) 172*d*.
Hagedorn, E. C., and Hall, D. P. Glass colorant composition, P (3) 58*f*.
Hageman, G. Ceramic drinking horns, (2) 30*b*.
Hagen, S. H. Voltage-dependent resistors, P (9) 228*c*.
Hagenbach, R. J. Method for producing glass beads for electrostatographic developers, P (8) 193*a*.
Hagenlocher, A. K. Method and apparatus for forming an ohmic contact to high-resistivity Si, P (5) 113*d*.
Hagenmuller, P. See Claverie, J.; Fava, J.; Frit, B.; Galy, J.; Rabardel, L.; Ravez, J.
Haggerty, J. S., and Lee, D. W. Plastic deformation of ZrB_2 single crystals, (1) 24*d*.
Haggis, G. A., Jones, Michael E. B., and Knight, M. H. C-fiber-reinforced polyurethane composites, P (9) 222*b*.
Hagiwara, Tatsuo. [Conical] rotary mill, P (2) 44*a*.
Hague, J. L. See Sappenfield, K. M.
Hahn, K. F. Contribution to the development of lighter glass containers, (8) 189*h*.
Hahne, B. See Seyfarth, H. H.
Haines, R. S. Magnetic compositions of Pr-modified Cr oxide, mfg. methods, and magnetic recording media containing same, P (6) 138*g*.
Haisty, R. W. See Johnson, R. E.
Haisty, R. W., Johnson, R. E., and Mehal, E. W. Three-dimensional integrated circuits and methods of making, P (2) 43*c*.
Hajmrle, K., and Angers, R. Method of studying sintering by electron microscopy, (4) 93*f*.
Hajnal, L. Hydromechanical comminution of clay lumps in concrete aggregates, (7) 156*i*.
Hajzak, D. G. Sputtering, P (7) 172*g*.
Hakim, R. M., and Uhlmann, D. R. Electrical conductivity of alkali silicate glasses, (3) 55*e*.
Hakki, B. W. In-Al phosphide and electroluminescent device using same, P (6) 138*b*.
Halberschmidt, F., and Overath, A. Apparatus for grinding glass, P (5) 105*i*.
Halbfinger, G. P., and Kolodney, M. Activated sintering of ThO_2 and ThO_2-Y_2O_3 with NiO, (11) 280*c*.
Hale, J. W. See Nelson, R. L.
Halker, B. B. See Gibson, F. D., Jr.
Hall, A. R. Elastic moduli and internal friction of some U ceramics, (1) 15*d*.
Hall, D. P. See Hagedorn, E. C.
Hall, D. S. See Southgate, P. D.
Hall, E. H. See Blosser, E. R.
Hall, H. R. Method of bending glass sheets, P (10) 244*j*.
Hall, J. D. See Berry, P. F.
Hall, J. E. Transient electrical measurements of amorphous chalcogenide thin films, (6) 137*d*. See Branch, G. H.; Walsh, P. J.
Hall, J. W., II, and Tragert, W. E. Ohmic contact to *n*-type SiC comprising Ni-Ti-Au, P (2) 41*h*.
Hall, L. H. See Carbajal, B. G., III.
Hall, N. T. Process for production of molding compositions containing high wt% of glass, P (1) 5*d*.
Hall, R. N. Removal of acceptor impurities from high-purity Ge, P (9) 227*c*. Semiconductor chip bonder, P (3) 67*a*.
Hall, T. H., Jr., Cottrill, J. R., and Dubble, R. D. Means for vapor coating, P (8) 193*h*.
Hallam, G. C. See Kitchen, P.
Haller, J. Method of producing elongated highly densified powdered metal articles, P (9) 230*a*.
Haller, W., and Simmons, J. H. Anatomy and thermal history of laser self-focusing damage tracks in glass, (11) 267*j*.
Halliday, W. See Eadie, G. P.
Hallman, R. W. See Teeg, R. O.
Halm, L. Report on the 12th International Colloquium on refractories—converter linings, (2) 33*g*.
Halpern, J. See Zhilich, A. G.
Halsey, G. D., Jr. See Roy, N. N.
Halstead, M. B. See Henderson, S. T.
Halt, I. E. See Collins, N. E.

Halva, C. J. Plating of nonmetallics for space applications, (2) 38*d*.
Ham, F. S., Schwarz, W. M., and O'Brien, M. C. M. Jahn-Teller effects in the far-ir, EPR, and Moessbauer spectra of $MgO:Fe^{2+}$, (5) 121*f*.
Hamaguchi, Yasuo. See Imaoka, Minoru.
Hamaguchi, Yoshikazu. See Ohama, Nobuhiko.
Hamamoto, Hujio, and Noguchi, A. Outline of kneading devices based on continuous and batch systems and results of comparative study on packing quality of components kneaded by both systems for making clayey brick, (7) 172*f*.
Hamamoto, Kazuo, Matsuoka, M., and Masuyama, T. Diode comprising ZnO doped with Ga oxide used as a voltage variable resistor, P (2) 40*c*. Voltage variable resistors, P (9) 228*d*.
Hamann, O. F. Line scanning cathode-ray tube having slotted storage element, P (8) 193*f*.
Hamano, Kenya. Systematization and quantitation in ceramic materials, (4) 100*a*.
Hamano, Kenya, and Lee, E. S. Densification process in kaolin bodies, (11) 280*j*. Studies on the mechanical properties of porcelain bodies, (11) 273*c*.
Hamano, Kenya, and Watanarungsun, A. Mineralogical and ceramic properties of Ranong clay, (11) 281*g*.
Hamano, Yoshiteru. See Kinoshita, Makoto; Kose, Saburo.
Hamano, Yoshiteru, Kose, S., and Kinoshita, M. Oxide having the structural formula $(La_{1-x}Ca_x)CrO_3$, where x is 0.01–0.15 and a method for producing the same, P (4) 89*g*.
Hamerly, R. G., and Heller, M. W. Space-charge scattering and electron transport in *n*-GaAs, (7) 180*f*.
Hamert, J. M. Effects of strain on the crystallization of vitreous Se (I) strain and X-ray analysis, (11) 268*j*; (II) study of devitrification by reflection microscopy and tentative interpretation of the results, (11) 268*b*.
Hames, D. A. See Glew, D. N.
Hamid, S. A. See Bryant, F. J.
Hamilton, F. C., Jr. See Slater, T. C.
Hamilton, T. N. See Glass, H. L.; Mee, J. E.
Hamling, B. H. Metal oxide fabrics, P (8) 196*d*.
Hammel, J. J. Process for forming particles of microporous glass for tobacco smoke filters, P (4) 82*i*.
Hammel, J. J., and Mackenzie, J. D. Method of forming microporous glass fibers, P (7) 162*c*.
Hammer, F. W., and Jasinski, J. Dark amber glasses and process, P (4) 81*d*.
Hammond, D. See Siegbahn, K.
Hammond, D. L. Resonant piezoelectric acousto-optic light filter and apparatus using same, P (7) 170*i*.
Hammond, M. J., and Haynes, J. W. Method of stabilizing rare earth oxide phosphor in dichromate-sensitized coating slurry, P (10) 252*d*.
Hammond, M. J., and Herner, R. F. Cathode luminescent phosphor reclamation, P (6) 137*g*. Method of treating luminescent rare-earth oxide materials, P (11) 275*e*. Phosphor reclamation from a slurry, P (3) 66*f*. Rare earth oxide having inert layer thereon and method of making, P (3) 67*f*.
Hammou, A., Deportes, C., Robert, G., and Vitter, G. Electrical conductivity of the solid solution $(ThO_2)_{0.75}$-$(CeO_2)_{0.25}$ at high temp., (1) 11*c*.
Hamner, G. P. See Arey, W. F., Jr.
Hampl, I. See Kristek, L.
Hanada, Hiroshi. CdS-chalcogen ternary compound mixture as photoconductive material in an electrophotographic member, P (10) 249*i*.
Hanada, Hiroshi, and Kitajima, N. Method of the preparation of CdS or CdSe powder for electrophotography and method of making an electrophotographic photosensitive plate by using the powder, P (6) 139*d*.
Hanada, Hiroshi, Kitajima, N., and Masaki, T. Ge and Si additives to dual-layer electrophotographic plates, P (6) 137*g*.
Hanada, Mitsuo, and Ito, S. Studies on the hydration of synthetic melilite glass, (4) 79*e*.
Hanai, Tetsuya. See Iwauchi, Kozo.
Hanak, J. J. Method of epitaxially growing single crystal films of metal oxides, P (3) 65*f*.
Hanby, F. E. Semiconductor replacements for hot cathode vacuum and gas filled electron tube devices, P (6) 140*e*.
Hance, P. R., Strohl, R. I., and Wanesky, W. R. Method for separating selected articles from an array, P (4) 89*b*.
Hance, R. J. [Expendable] immersion temp.-responsive device, P (9) 231*g*.
Hancock, J. D., and Sharp, J. H. Method of comparing solid-state kinetic data and its application to the decomposition of kaolinite, brucite, and $BaCO_3$, (3) 74*h*.
Hancock, P. See Demott, D. S.; McGinley, C. E.
Handwerk, J. W. See Trench de Freitas, C.
Handy, R. M., Angello, S. J., Malmberg, P. R., and O'Keeffe, T. W. Electron beam fabrication system and process for use thereof, P (10) 250*b*.
Haneta, Yuichi. Field-effect semiconductor device with memory function, P (6) 137*f*. See Nakanuma, Sho.
Haneta, Yuichi, and Wada, T. Structure for rigidly mounting a semiconductor chip on a lead-out base plate, P (1) 14*j*.
Hang, K. W. See Carlson, D. E.
Hang Nam Ok, Helms, W. R., and Mullen, J. G. Properties of Co_3O_4—effects of gas adsorption and external magnetic fields, (6) 151*g*.
Hanks, C. W. Single-crystal growth [Si] and diam. control by magnetic melt agitation, P (1) 14*j*.
Hanley, B. C. See Castonguay, R. A.
Hannam, M. J. See Hardy, C. J.
Hanneman, R. E. Effects of excess vacancies in nonequilibrium solute segregation at interfaces in solids, (9) 234*i*.
Hannes, G. J. Glass fiber laminates and method, P (3) 58*h*.
Hannon, J. J., Lloyd, P., and Smith, Robert T. Low-temp.-coeff. Li tantalate resonator, P (1) 12*i*.
Hanold, R. C. F., III. See Piper, J.
Hanot, W. Forty years of recycling, (7) 159*c*.
Hanrahan, D. J. Fast switch utilizing hybrid electron beam-semiconductor devices, P (10) 250*c*.
Hansen, E. E., and Munir, Z. A. Thermodynamic properties of the free surface and equilibrium sublimations of PbS, (8) 211*c*.
Hansen, J. H., and Getz, R. W. Glass feeder made of Pt-Rh-Mo high temp.-high strength alloy, P (3) 58*h*.
Hansen, J. W. See Duguay, M. A.
Hansen, K. W. See Davis, Earl K.
Hansen, P. F. See MacKenzie, D. J.
Hansford, J. See Goldberg, P.
Hanson, C. K., and Wadsworth, M. E. Leaching Be, P (2) 46*i*.
Hantusch, G. H., Vincent, D. A., and Van Tongerloo, E. H. Heat dispersion from a semiconductor wafer by a multiplicity of unaligned minuscule heat-conductive raised dots, P (10) 250*g*.
Hanus, J. See Feinleib, J.
Hara, Ei, and Suzuki, S. Core rod stopping and releasing device in a powder material forming press, P (9) 229*h*.
Hara, Ei, and Watanabe, T. Platen locking device in powdered material compacting presses, P (4) 92*f*.
Hara, Hiroshi. See Shimizu, Takashi.
Hara, Hisashi. See Maeda, Hajime; Sato, Tai; Takeishi, Yoshiyuki.
Hara, Morihisa. See Ohta, Hironori.
Hara, Naomichi. See Matsuda, Osaku.
Harada, Shoichi. See Izumitani, Tetsuro.
Haraguchi, Takashi. See Ikeda, Takuro.
Harbison, J. E. Explosion-proof asbestos-cement shapes, P (9) 216*f*.
Harasimham, K. S. See Basu, A.
Harbur, D. R., Anderson, J. W., and Money, R. K. Crucible coating for preparation of U and Pu alloys containing Zr or Hf, P (8) 203*f*.
Harcuba, S. Apparatus for the continuous production of profile glass and plate glass in band form, P (8) 192*j*.
Harding, B. C., and Bhalla, V. K. Cd diffusion in MgO at high temps., (6) 145*d*.
Harding, B. C., Price, D. M., and Mortlock, A. J. Cation self-diffusion in single-crystal MgO, (6) 145*f*.
Harding, D. A. See German, W. L.
Harding, D. R. See Prins, J. F.
Harding, F. L. Dependence of melt O activity and H_2O retention on composition of amber glass, (8) 189*f*. Effect of base glass composition on amber color, (11) 268*i*.
Harding, F. L., and Ryder, R. J. Amber color in commercial silicate glasses, (8) 189*d*.
Hardy, C. J., Lane, E. S., and Hannam, M. J. Production of pigments, P (7) 176*a*.
Hardy, D. F. Airspeed assist, P (1) 3*j*.
Hardy, J. B. C. See Creer, M. H.
Hare, A. L. See Arkless, K.
Hares, G. B. See Dumbaugh, W. H., Jr.
Hariharan, R., and Krishnan, R. Temp. regulator, (10) 255*e*.
Harker, H., Horsley, J. B., and Robson, D. Reactivity of graphite to O—effect of impurities added after neutron irradiation, (1) 16*b*.
Harkins, P. A., Jr. Sputter etching process, P (10) 253*c*.
Harkort, D. Advantages, limitations, and the future of rapid firing, (2) 43*g*.
Harkort, D., and Hoffmann, U. Corrosion of the mold surface in ceramic slip-casting, (7) 165*c*. Experience in the industrial application of rapid firing in Germany, (2) 43*h*.
Harkulich, T. M. See Wainer, E.
Harland, G. E., Jr. See Adkinson, A. R.
Harmsworth, B. J. See Nelson, R. L.
Harned, W. L. Method of [fluid] fine grinding, P (10) 254*e*.
Harnish, M. E., and Peters, M. A. Use of refractory parting layer to aid skull removal from furnace linings, P (10) 248*e*.
Haroun, N. A. Reply to "Discussion of 'Effect of additives on sintering of CaF_2'," (7) 177*e*.
Haroun, N. A., Abdel-Azim, M. S., and Orabi, G. I. Effect of additives on sintering of CaF_2, (1) 21*h*.
Haroun, N. A., and Budworth, D. W. Effects of additions of MgO, ZnO, and NiO on grain growth in dense Al_2O_3, (1) 21*c*.
Harper, W. E. See Pflanz, H. M.
Harrach, W. Critical comparison of the composition of cast refractories, (5) 109*e*.
Harrap, V., and Carlson, H. G. Process for etching composite layered structures including a layer of fluoride-etchable Si_3N_4 and a layer of SiO_2, P (1) 14*e*.
Harries, D. A. Slurry forming apparatus, P (10) 254*i*.
Harrigan, D. J. See Faria, S.
Harrington, F. E. See Sease, J. D.
Harris, B., Beaumont, P. W. R., and de Ferran, E. M. Strength of fracture toughness of C fiber polyester composites, (7) 163*h*.
Harris, B., Varlow, J., and Ellis, C. D. Fracture behavior of fiber reinforced concrete, (10) 241*g*.
Harris, D. M. Epitaxial deposition method, P (4) 87*g*.
Harris, J. L. Apparatus for dissipating foam on molten glass, P (6) 132*a*.
Harris, R. L. See Golliher, W. R.
Harris, T. J., and Erhard, M. Multicolor laser frequency selector, P (1) 14*b*.
Harris, W. F., and Scriven, L. E. Intrinsic disclinations as dislocation sources and sinks in surface crystals, (5) 121*d*.
Harris, W. W. Method and apparatus for preparing molten material into glass fibers, P (4) 82*a*.
Harrison, D. See Chan, R. K.
Harrison, J. D. L. See Bischoff, K.
Harrison, H. F. Dual-etched refractory metalizing, P (8) 200*j*.
Harrison, J. R., and Gilpin, J. W. Method of crystal growth by vapor deposition, P (4) 88*f*.
Harrison, M. C. See Booth, F.
Harrison, R. See Brough, R.
Harsell, W. B. See Pearson, A. D.
Hart, P. A. H. Integrated semiconductor circuit comprising only low temp. processed elements, P (1) 12*g*. Vidicon target plate having a drift field region surrounding each image element, P (6) 140*d*.
Hart, P. B., Hill, C., and Wilkins, C. W. Production of vapor-deposited Nb_3Sn conductor material, P (4) 90*f*.
Hart, T. W., Jr. See Economopoulos, P. C.
Hartley, N. Rebound pug mill, P (10) 254*h*.
Hartmann, H., and Budan, G. Process for making Mg oxide or hydroxide from Mg-containing raw materials, P (10) 248*d*.
Hartmann, K. W. Zero-insertion force connector, P (9) 228*e*.
Hartmann, R., Dorschner, O., and Gross, H. W. Process and [elutriation] apparatus for separating coarse and/or heavy particles from a variable-particle-size and/or variable-particle-wt mixture of granular solids maintained in a fluidized state, P (4) 92*g*.
Harvey, K. L. Ceramic product from fly ash and method of making, P (10) 246*b*.
Harvig, H. Extended version of the regular solution model for stoichiometric phases and ionic melts, (11) 281*i*.
Harvill, M. L. Method of improving the photosensitivity of metal oxide semiconductors, P (4) 88*j*.
Harwell, C. J. See Siegfried, E. C.
Hasaba, Shigemasa, Kawamura, M., Takakuwa, J., and Saito, M. Influence of H_2O-reducing admixture on properties of concrete using crushed gravel and fine sand, (6) 129*i*.
Hasaba, Shigemasa, Sugiura, S., and Kawamura, M. Hydration of alite and belite in compacted clay-cement mixtures—the influence of types of cements (high early strength and moderate heat cement) on the clay minerals-cement interaction, (10) 241*j*.
Hasaba, Shigemasa, Sugiura, S., Kawamura, M., and Nakamura, K. Interaction between clay minerals and portland cement—role of Ca $(OH)_2$ produced by cement hydration, (6) 129*j*.
Hasegawa, Fumio. See Saito, Takeshi.
Hasegawa, Hiromasa. See Kano, Gota.
Hasegawa, Hiroshi. See Imaoka, Minoru.
Hasegawa, Katsue. See Yoshimura, Susumu.
Hasegawa, Nobuo. See Yamashita, Toshio.
Hasegawa, Nobuo, and Kamo, T. Heat-resisting insulating materials for electric parts, P (6) 135*g*.
Hasegawa, Shizushi. See Motoi, Soichiro.
Hasegawa, Shoji. See Matsushita, Toru.
Hashimoto, Masaaki. See Hishiyama, Yoshihiro.
Hashimoto, Masayuki. See Inoue, Ichiro.
Hashimoto, Norikazu. See Itoh, Yokichi; Sakurai, Yo.
Hashizume, Yutaka. See Hirosue, Hideharu.
Haskin, L. A. See Cullers, R. J.
Hass, K. See Hack, P.
Hasselman, D. P. H. See Coppola, J. A.; Gebauer, J.; Krohn, D. A.; Penty, R. A.; Steiner, C. J. P.
Hasselman, D. P. H., Coppola, J. A., Krohn, D. A., and Bradt, R. C. Nonrecoverable elastic energy and crack propagation in brittle materials, (11) 281*g*.
Hassler, E. Crystal structure of Nb_3P_3, (6) 146*b*.
Hastings, I. J., MacEwan, J. R., and Bourque, L. R. Effect of swelling on thermal conductivity and postirradiation densification of U_3Si, (6) 140*j*.
Hastings, I. J., and Stoute, R. L. Temp.-dependent swelling in irradiated U_3Si fuel elements, (1) 16*f*.
Haswell, A. B. See Latham, M.
Hatfield, T., and Richmond, C. Solubility of $CaMgSiO_4$ in Mg_2SiO_4, (1) 25*e*.
Hatfield, T., Richmond, C., Ford, W. J., and White, J. Compatibility relations between

the periclase and silicate phases in magnesite refractories at high temps., (1) 6*g*.

Hatschek, R. A. Piezoelectric accelerometer, P (4) 89*j*.

Hattori, Makoto. See Minami, Tsutomu.

Hattori, Makoto, Tsubaki, T., Murata, F., and Tanaka, M. Effect of different kinds of cations on thermal properties of condensed phosphates, (5) 120*c*.

Hattori, Takeo, and Suzuki, H. Mechanism of initial sintering of sinterable BeO powder, (6) 130*g*.

Hatzakis, M. Variable depth etching of film layers using variable exposures of photoresists, P (6) 140*d*.

Hauffe, K., and Hegedus, A. J. Effect of short wavelength light on the vaporization of ZnO, (2) 47*b*.

Haugan, K. M. Electronically controlled manipulator for the application of vitreous enamel, (5) 105*a*.

Haugsten, K. See Roest, E.

Haus, J. See Emeis, R.

Hausberger, A. L. See O'Brien, J. F.

Hausser, D. C. Sample-handling mechanism for liquid scintillation counting apparatus, P (2) 45*b*.

Havas, J. See Koepp, R. L.

Havas, J., and Lechaton, J. S. End-point detection method and apparatus for sputter etching, P (9) 225*g*.

Havel, C. J. Hot isostatic pressing using a vitreous container, P (3) 69*a*.

Hawkins, C. T., and Starr, E. W. Apparatus for conditioning glass, P (3) 57*e*.

Hawks, W. L. Test data for N. Mex. clay materials (I) Central New Mexico, (3) 71*g*.

Hawrylo, F. Z. Double epitaxial solution regrowth process and device made thereby, P (6) 137*b*.

Hay, A. E. See Loukes, D. G.

Hayakawa, Kazunobu, Namikawa, K., and Miyake, S. Exchange reflections in low energy electron diffraction from antiferromagnetic Ni oxide crystal, (4) 96*e*.

Hayakawa, M., Cohen, J. B., and Reed, T. B. Measurement of the lattice parameter of wustite at high temps., (4) 97*f*.

Hayakawa, Masashi, Ueno, K., and Yasutake, Y. Process for preparing gypsum hemihydrate, P (2) 31*f*.

Hayakawa, Shigeru. See Hada, Toshio; Matsuoka, T.; Taki, Hiromitsu; Wasa, Kiyotaka.

Hayami, Ryozo, and Wakabayashi, H. Compositional changes during electron microprobe analysis of alkali silicate glasses, (3) 55*e*.

Hayashi, Chikashi. See Kosaka, Yoshio.

Hayashi, Hiroyuki. See Obuchi, Satoru.

Hayashi, I. See Cho, A. Y.

Hayashi, Kunio, and Uei, I. Rapid determination of thermal conductivity of refractories by the hot-wire method (III) studies on automation of apparatus for determining thermal conductivity, (1) 8*e*. Simplified apparatus and method for determining thermal conductivity of refractories, (1) 8*j*.

Hayashi, Masamichi. See Yokomichi, Hideo.

Hayashi, Mineo. See Araki, Kenichi.

Hayashi, Naonori. See Akeyoshi, Kazuyuki.

Hayashi, Ryosuke. See Tomita, Kinzo.

Hayashi, Toshiya. Two-valley [*n*-type GaAs] semiconductor oscillator, P (3) 68*c*.

Hayes, C. M., Latos, E. J., and Sparks, A. K. Method of forming a filament-wound tube with an inner wall having high wear resistance, P (4) 82*c*.

Hayes, J. C., and Sobel, J. E. Making Al_2O_3 fibers from a mixture of Al_2O_3 sol and $(CH_2)_6N_4$, P (4) 86*b*.

Hayes, M. R. Apparatus for grading particles according to their sphericity, P (10) 254*h*.

Hayes, R. R., Fuller, J. L., and Stockham, J. R. Method and apparatus for forming refractory [asbestos] panels, P (9) 222*j*.

Haynes, H. L. See Morrison, A. R.

Haynes, J. W. See Hammond, M. J.

Haynes, J. W., and Shaner, K. H. Phosphate-coated rare-earth oxide compositions and a process for producing, P (1) 14*c*.

Hays, R. G. Gaseous nonpreferential etching of Si, P (10) 250*f*. See Ashton, G. L.; Elgan, D. L.

Haywood, G. L. Abrasive wheels, P (1) 1*g*.

Hazard, H. R. See Davis, J. A.

Hazelden, D. W. J. See Sterling, H. F.

Hazell, R. G. See Nielsen, B. R.

Hazen, E. J. Quartz pressure sensor, P (6) 139*i*.

Hazen, R. M., and Wones, D. R. Effect of cation substitutions on the physical properties of trioctahedral micas, (9) 234*e*.

Heacox, G. W. See Helgeland, W.

Headley, L. C., Pierce, C. I., and Wallace, W. E., Jr. Experiments on gas flow in porous media at low pressures, (6) 142*b*.

Heady, O. E., Towell, J. F., and Standifer, R. L. Pu hexafluoride reduction, P (9) 229*b*.

Heald, E. F., and Weiss, C. W. Kinetics and mechanism of the anatase/rutile transformation, as catalyzed by ferric oxide and reducing conditions, (9) 236*a*.

Heald, M. T. See Cecil, C. B.

Healy, G. W. See Schlitt, W. J.

Healy, P. C. See Golding, R. M.

Healy, R. M., and Marshall, R. Electrical resistance element with a semiconductor overlay, P (10) 250*i*.

Heap, R. T. See De Forest, W. S.

Heaps, J. F. See Isaksen, R. A.

Heath, L. J., and Jones, Ray A. Thermal-chemical alteration of sandstone to increase permeability, (7) 175*g*.

Heaton, R. A. Method of treating bottles during ribbon separation, P (5) 107*f*.

Heaton, R. A., and Sachs, M. J. Glass ribbon machine blow head mechanism, P (6) 132*i*.

Heberlein, K. Electrostatic application of glaze to porcelain and ceramic, (11) 272*i*.

Hebert, R. A., Moynihan, D. J., Paul, D. E., Petrovic, L. J., Rubel, P. A., and Seferian, R. Process and apparatus for the production of finely divided metal oxides, P (8) 207*b*.

Heck, R. F. See Grosso, P. F.

Heckmann, W. Noncellular rotary vacuum filter, P (5) 115*h*.

Heckroodt, R. O. Factors influencing the critical strain of clay materials during firing, (2) 35*f*.

Hed, A. Z. See Seltzer, M. S.

Hedler, R. A. Opaque composition for forming a windowed web in a cathode-ray tube screen structure, P (9) 227*c*.

Hedler, R. A., and Magill, M. E. Process for aluminizing a CRT screen, P (8) 202*d*.

Hedman, C. L., Jr. [Electrolytic] Au removal process, P (8) 200*a*.

Hegarty, A. Metalizing Al_2O_3 at room temp., (9) 224*j*.

Hegedus, A. J. See Hauffe, K.

Hegyi-Pako, J. Electron microscopy of dolomitized rocks, (5) 117*g*.

Hegyi-Pako, J., and Vitalis, G. Geological and material tests from carbonaceous rocks of Nagyszal Mt., (6) 143*f*.

Heide, H. See Beckmann, B.

Heidegger, P. See Pammer, E.

Heidel, R. H. See Desborough, G. A.

Heidiah, W. E. See Kunkle, G. E.

Heidt, A. Balloon pots, (2) 30*a*.

Heidweiler, A. P. L. Glass-fiber webs employing glass fibers with diams. of 3–15 μm, P (3) 58*i*.

Heilmann, T. Separation of alkali-rich dust from cement kilns, P (5) 104*j*.

Heim, R. C. See Kern, W.

Heimbach, F. See Schotten, A.

Heimke, G. Oxide ceramic housings, (11) 274*b*.

Hein, T. F. See Claessens, F. D.

Heine, J. H. D. Recent developments in ovens for continuous firing, (4) 93*j*.

Heinemann, O. Process and apparatus for determining the distribution of particle sizes in ground material, P (4) 93*f*. See Ritzman, H.

Heinle, W. Inclusion of diffusion in the space-charge theory of Kino and Robson, (7) 178*d*.

Heinrich, K. F. J., Barrett, C. S., Newkirk, J. B., and Ruud, C. O. (editors). Advances in X-Ray Analysis (Vol. 15) Proceedings of the 20th Annual Conference on Applications of X-Ray Analysis, Aug. 1971, Denver, Colo., B (9) 239*i*.

Heinrichs, F. J., and Pattyn, R. L. Method for mfg. foundry molds, P (2) 37*a*.

Heins, H. Process for the production of anti-dazzle glass filters, P (7) 162*i*.

Heinz, D. M. See Besser, P. J.; Mee, J. E.

Heinze, G. See Dorn, L.; Podschus, E.

Heiss, A., and Diemal, M. Reduction of ThO_2 by C, (7) 180*d*.

Heitz, A. J. See Rogers, L. C.

Held, W. Indirectly heated hot cathodes with pink ruby insulator, P (7) 162*d*.

Helenberg, H. W. See Baum, J. J.

Helgeland, W., Lazott, J. B., Duke, P. J., Taggart, W. J., Heacox, G. W., and Brandsma, A. Vitreous enamel resistor, P (6) 131*f*.

Heller, K. H., Wulff, C. A., and Mueller, L. Process for the production of fixed bed oxidation catalysts, P (3) 71*j*.

Heller, M. W. See Hamerly, R. G.

Hellesland, J., and Green, R. Stress and time dependent strength law for concrete, (8) 187*g*.

Hellman, W. R. See Spacil, H. S.

Helmick, J. W. Method of forming fibrous bodies with dissimilar densities and apparatus therefor, P (7) 162*c*.

Helms, W. R. See Hang Nam Ok.

Helmy, A. K. See Ferreiro, E. A.

Helvy, F. A. Method of making a multialkali photocathode with improved sensitivity to ir light and a photocathode made thereby, P (8) 193*e*.

Hemelryk, P. Fuel pollution and the clay industries, (2) 50*g*.

Hemmen, E. H. See Jordan, C. F., Jr.

Hemanth, K. H. See Nesbitt, J. D.

Hench, L. L. Semiconducting glass-ceramics, (6) 132*h*. See Freiman, S. W.; Schaake, H. F.

Hench, L. L., and Dove, D. B. (editors). Physics of Electronic Ceramics (Part A), B (2) 51*c*; (Part B), B (7) 183*g*.

Hench, L. L., and Freiman, S. W. (editors). Advances in Nucleation and Crystallization in Glasses, B (10) 261*i*.

Henderson, B. See To, Kin-Ching.

Henderson, B., Stokowski, S. E., and Ensign, T. C. Luminescence from *F* centers in CaO, (5) 121*c*.

Henderson, G. A., and Pittman, G. E. Process for the fabrication of light-emitting semiconductor diodes, P (4) 90*c*.

Henderson, S. T., Morley, D. I., and Halstead, M. B. Color discrimination tests on visitors to a scientific exhibition, (4) 85*d*.

Hendricks, C. L. See Mathewson, H. K.

Hendrickson, J. R., and Bray, P. J. Theory for the mixed-alkali effect in glass (I), (11) 269*e*.

Hendry, A. W. See Sinha, B. P.

Henery, V. A. See Michelotti, J. E.

Henisch, H. K. Controllable semiconductor switch, P (7) 168*c*.

Henker, H. Method of producing photovarnish masks for semiconductors, P (1) 13*h*.

Henmi, Yoshinori, Suzuki, H., and Kamiya, T. Process for mfg. a resin-bound abrasive grinder, P (4) 77*i*.

Hennemann, K. See Schmidt, P.

Henney, J. W., and Jones, J. W. S. Effect of controlled additions of silicate phases on the hot strength of MgO, (2) 35*j*. Reaction between $SrTiO_3$ and Zr and studies within the system SrO-TiO_2-ZrO_2, (1) 24*c*. Solid solubility of CaO and SiO_2 in MgO and its effect on the MgO-CaO-SiO_2 system at 1750°C, (1) 25*b*.

Hennicke, H. W. Temp. dependence of the elastic moduli of ceramic materials, (9) 239*b*. See Nowak, A. E.; Salge, H.

Hennicke, H. W., and Sturhahn, H. H. Transfer processes in the Al_2O_3-Cr_2O_3 system—electrical conductivity, (5) 125*e*. Transfer processes in the Al_2O_3-Cr_2O_3 system (I) miscibility of Al_2O_3 and Cr_2O_3, (1) 26*d*; (II) sintering kinetics and grain growth, (5) 125*h*.

Hennig, W. Process for production of rotary anodes for roentgen tubes, P (6) 135*e*.

Henning, O., and Kassner, B. Phase analysis of portland cement clinkers by ir spectrography, (6) 129*h*.

Henninges, K., and Schulze, B. Method of treating semiconductor elements of circular outline, P (1) 13*j*.

Hennings, D. See Haerdtl, K. H.

Henrich, V. E., and Weinreich, G. Pulsed ultrasonic studies of the acoustoelectric effect, ultrasonic attenuation, and trapping in CdS, (5) 122*j*.

Henry, C. H., Faulkner, R. A., and Nassau, K. Donor-acceptor pair lines in CdS, (5) 120*a*.

Henry, G. R. Effects of wall inertia on cylindrical magnetic domains, (5) 120*f*. See Davies, B.

Herman, H., and MacCrone, R. K. Comments on "Separation of phases by spinodal decomposition in the systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3," (2) 47*e*.

Henry, J. J. Improved capacitance gage for dimensional measurements, (11) 277*i*.

Henry, N. F. M. See Galopin, R. E.

Henry, Y. See Rakotomahanina-Rolaisoa, E.

Hensley, E. B. See Johnson, B. P.

Henstra, S., and van der Plas, L. Micromorphological changes during the firing of bricks, (9) 220*e*.

Hentzschel, H. P. K. Ohmic contact system, P (6) 139*i*.

Herbert, D. C. Magnon interactions in α-Fe_2O_3, (6) 150*e*.

Herbert, J. See Kuczynski, G. C.

Herbert, J. M. Recent advances in ferroelectrics, (7) 167*d*.

Herczog, A., and Layton, M. M. High-dielectric-constant niobate-titanate glass-ceramic articles, P (2) 34*h*.

Herczog, A., and Smith, Harold R. Method of making refractory metal carbide thin-film resistors, P (9) 226*b*.

Herendeen, R. A., and Silsbee, R. H. Paraelectric resonance of KCl:Li, (6) 150*f*.

Hermann, P. Errors in methods of testing ceramic refractory materials, (7) 173*f*.

Hermes, R. Method and apparatus for filling the die of a powder press, especially of a metal powder press, P (1) 17*a*.

Herner, R. F. See Hammond, M. J.

Heron, G. F. Treatment of asbestos, P (8) 197*a*.

Herrington, R. A. See Oelke, W. W.

Herrman, R., Neu, W., Ruediger, K., Gutsche, B., Kirchhof, H., and Trampisch, W. Method and device for the modulated sample supply in the spectrochemical analysis of a solution, P (3) 70*d*.

Herrmann, F. J., Huschka, H., and Venet, P. Fuels for high-temp. nuclear reactors, (11) 276*b*.

Herrmann, O. Method of introducing halogens into electric lamps, P (3) 59*d*.

Herron, H. M. See Sladek, K. J.

Herron, R. H. See Leonard, R. J.

Hertelendy, C. See Kozma, B.

Hervieu, M. See Desgardin, G.

Herz, J. H. Rotary kiln control apparatus and programing, P (4) 94*a*.

Herzog, A. H. Injection-luminescent diodes, P (3) 65*e*.

Herzog, A. H., Caldwell, J. F., Schmidt, J. G., and Lim, E. Ohmic contact for semiconductor devices, P (5) 113*e*.

Hespers, W. Substitute for coal dust in casting molds as lustrous C-forming additive, P (9) 222*h*.

Hessinger, P. S. Semiconductor package, P (8) 202*a*.

Hetrick, R. E., and Yeung, K. F. Effect of surface electric fields on radiative recombination in CdS, (6) 147*a*.

Heuer, A. H. See Burnett, P.

Heuner, W., Oberfeuer, B., and Koltermann, M. Significance of the refractoriness-under-load test (ISO-DFB) in investigations of foundry refractories, (1) 8*h*.

Hewaidy, I. F. See Hussein, M. K.

Hewitt, R. R. See Dumesnil, M. E.

Heyndryckx, P. Use of the ion microanalyzer and electron spectrometer in glassmaking problems, (8) 205*f*.

Heyndrickx, P., and Bonnan, D. Application of thermometry to analysis of glasses and batch materials, (8) 204*g*. Improvements in an apparatus for thermometric measurements (MOM), (11) 277*i*.

Heyne, L., and Beekmans, N. M. Electronic transport in CaO-stabilized ZrO_2, (9) 235*f*.

Heywang, W., and Sirtl, E. Method of producing semiconductor components on a magnetic substrate, P (10) 252*c*.

Heywood, K. W., and Trampier, C. R., Jr. Preparation of anatase TiO_2 pigment, P (3) 71*f*.

Hibino, Akemi. See Fernandez-Moran, H.

Hicguet, M. H. See Fritsch, A. A.

Hickenbotham, H. D. See Bryant, L. S.

Hickmott, T. W. Production and annealing of color centers in rf sputtered SiO_2 films, (4) 86*g*.

Hicks, D. G., and Varner, L. P. Grout expansion pressure meter and method for using, P (10) 255*j*.

Hicks, F. G. Comparative assessment of the thermal cycling resistance of magnesite refractories, (1) 6*g*.

Hicks, R. E. Substrate bonding bumps for large-scale arrays, P (6) 140*h*.

Hickson, D. A. See Csicsery, S. M.

Hickson, K. Electron spectroscopy—a new technique for material and structural analysis and a review of its possible applications to problems in glass research, (8) 204*i*. See Austin, M. J.

Hidaka, Toshinori. See Ono, Yoshio.

Hielscher, F. H. See Lehovec, K.

Higaki, Kazuo. See Kurumada, Norimitsu; Takashima, Saburo.

Higashi, Kazuhiro. See Uekusa, Genzo.

Higashinakagawa, Iwao. See Murakami, Yoshio.

Higgins, F. J. Tube furnace, P (5) 117*b*.

Higgins, J. A. Methods and apparatus for the distribution, deflocculation, and dispersion of fluid slurries, P (11) 277*e*.

Higgins, J. B., and Gatti, A. Formation of high-strength high-modulus coated filaments, P (9) 222*e*.

Higgins, J. J., Berejka, A. J., and Spenadel, L. Bonding glass with thermoplastic sealing compositions, P (7) 161*i*.

Higgins, T. J., Macedo, P. B., and Volterra, V. Mechanical and ionic relaxation in Na_2O·$3SiO_2$ glass, (11) 269*a*.

Higham, G. A. Optical glass compositions, P (9) 219*g*. See Parry, R. J.

Highberg, C. W. Method of polishing glass, P (10) 245*d*.

Highfield, A. Refractories, (2) 36*d*.

Higuchi, Eiichi. See Zenbutu, Sakae.

Higuchi, Kenji. See Akatsu, Ken.

Higuchi, Noboru, Ogawa, Y., and Watanabe, A. Method of mfg. porcelain for electric insulators by controlling grain size, P (10) 248*g*.

Higuchi, Shigetaka. See Makino, Yoshimi.

Hikichi, Yasuo. See Mitsuda, Takeshi.

Hilbert, R. F., Storhok, V. W., Chubb, W., and Keller, D. L. Mechanisms of swelling and gas release in UO_2, (5) 114*g*.

Hildebrand, H. Endless abrasive belt having an overlapping joint, P (6) 127*f*.

Hilgers, G., Hitzemann, G., and Kulling, A. Process for mfg. fine-particle-size TiO_2 by reacting $TiCl_4$ with O, P (6) 144*b*.

Hill, B. H. Etch-retarding oxide films as a mask for etching, P (2) 40*f*.

Hill, C. See Hart, P. B.

Hill, F. J. Corrosion-resistant binder for WC and TiC materials, P (4) 84*i*.

Hill, G. J. Ceramics for microcircuit applications, (9) 223*j*. Energy storage in high-permittivity ceramics: survey of materials based on $BaTiO_3$, (7) 167*a*. See Morse, C. T.

Hill, G. J., Strudwick, P., and Barnett, M. J. Al_2O_3 substrates with very good surface finish, (9) 223*f*.

Hill, H. G. See Wong, R.

Hill, H. W., Kaznoff, A. I., and Marlowe, M. O. Nuclear reactor fuel composition, P (10) 254*b*.

Hill, J. O. See Christensen, J. J.

Hill, R. M. Poole-Frenkel conduction in amorphous solids, (6) 151*d*.

Hill, T. Production of SiO_2 gels, P (6) 144*d*.

Hillman, H. F. Sphere grinding and polishing apparatus, P (2) 44*d*.

Hills, P. R., and McGahan, D. J. Radiation of impregnated porous material, (4) 79*b*.

Hilton, A. R. Optical properties of chalcogenide glasses, (6) 132*c*.

Hilton, R. M. See Dickinson, S. K.

Himmelberg, G. R. See Loney, R. A.

Hinch, H. H. See Bradley, J. S.

Hinchey, J. F. Method of encapsulating coplanar microelectronic system, P (8) 201*a*.

Hingorany, A. R. Semiconductor device package having improved compatibility properties, P (4) 90*d*.

Hintenberger, K. Vacuum furnace, P (5) 117*b*.

Hintermann, H. E. See Gass, H.

Hinz, W. Silicates—Fundamentals of Silicate Science and Silicate Technology (Vol. I) Silicates and the Methods to Investigate Them, B (5) 126*f*. (Vol. II) Silicate Systems and Technical Silicates, B (8) 212*f*.

Hipp, J. C., and Schmidt, J. A. Method of metalizing a ceramic member, P (3) 66*b*.

Hira, Isao. See Suzuki, Kazutaka.

Hirabayashi, Takakuni. See Sakaguchi, Masakazu.

Hiraga, Tomoaki. See Kemi, Torao.

Hiragushi, Keisuke. See Ohba, Hiroshi.

Hirai, Hidefumi. See Makishima, Shoji.

Hirai, Masahiro. See Saitou, Masashi.

Hirai, Masaki. See Yoshioka, Yasuhiko.

Hirai, Toshio. See Aoki, Koichi.

Hirano, Jiro. See Miyauchi, Tsuneshige.

Hirano, Masahiro, and Shionoya, S. Effect of internal magnetic field on the optical spectra of Sm^{3+} ion in $TbPO_4$ and YPO_4 and their mixed crystals, (3) 72*h*.

Hirano, Shinichi. See Miyagawa, Saburo; Somiya, Shigeyuki; Sugai, Mikio.

Hirano, Tomiyoshi. See Ohmae, Kenji.

Hiraoka, Teruyoshi, Sano, N., and Matsushita, Y. Electrochemical measurement of the standard free energies of formation of Nb oxides, (1) 21*i*.

Hirasawa, Ikuo. See Okada, Kiyoshi.

Hirashima, Hiroshi, and Yoshida, T. Electrical conductivity and structure of the molten oxide system PbO-B_2O_3-Fe_2O_3, (6) 147*f*.

Hirashima, Masaki. Apparatus for direct generation of electricity, P (4) 81*h*.

Hirata, Kentaro. See Namikata, Takeshi.

Hiratsuka, Toshio, Kanemaru, T., and Yamazoe, H. Method of making a metal-impregnated C product [seal], P (3) 61*h*.

Hirose, Koyo. See Kato, Akihisa.

Hirose, Kozabro. See Tanaka, Sadao.

Hirose, Masami. Growth of ZnO single crystals by vapor phase reaction, (3) 73*e*.

Hirosue, Hideharu, Matsuda, O., Koga, Y., and Hashizume, Y. Production and properties of perlite from Shirasu, (6) 143*g*.

Hirota, Eiichi. See Kawamata, Tadashi.

Hirsch, P. Method for heating, melting, or softening glass in dispersed form, P (1) 4*j*.

Hirschfeld, T. Total reflection fluorescence spectroscopy, P (1) 18*j*.

Hirschhorn, L. Porcelain bonding dental Au alloy, P (10) 248*h*.

Hirshon, J. M., and Warner, P. D. Semiconductor device and method of making, P (10) 252*h*.

Hirth, J. P. See Nishioka, Kazumi.

Hishikari, Isao. Radiation thermometer, P (2) 45*a*.

Hishiyama, Yoshihiro, Ono, A., and Hashimoto, M. Field dependence of magnetoresistance in no-binder soft carbons at 77°K, (3) 73*i*.

Hissong, G. E., Jr., and Rice, W. Epitaxial deposition reactor, P (3) 64*j*.

Hita, Toshiharu. See Tsumagari, Akira.

Hitchcock, R. D. Schottky-emission thin-film varistor diode formed of Al/Al oxide/Mn/Mn oxide/Pb and a method of fabricating the diode, P (4) 90*a*.

Hitomi, Teiichi, Kotera, N., and Sakamoto, H. Thermoluminescent materials, P (11) 276*a*.

Hitotsuya, Koretoshi. See Saito, Turuyoshi; Yamane, Sho.

Hittmair, P. See Nitzsche, S.

Hitzemann, G. See Hilgers, G.

Hiyama, Teturo. See Fujii, Junnosuke.

Hiyama, Yutaka. See Somiya, Shigeyuki.

Hjorth, L., and Lauren, K. G. Belite in portland cement, (4) 78*e*.

Hlavac, J. See Matousek, J.

Hloch, A., Medic, N., and Kohlhaas, R. Process for mfg. condensed Al phosphates, P (7) 175*h*.

Ho, I. T. See Chang, J. J.

Ho, Shih-Ming, and Douglas, B. E. Structures of the elements in the PTOT system, (7) 181*g*.

Hobden, M. V., Rich, G. J., and Robertson, D. S. Piezoelectric device utilizing Li germanate, P (9) 227*g*.

Hock, H., and Braetsch, P. Suitability and behavior of coked tar-dolomite bricks with increased C content and their preparation, (6) 134*i*.

Hockey, J. A. See Jones, P.; Tyler, A. J.

Hoda, Tokiti, Inagaki, M., and Yamada, S. Glass-like carbons, (3) 60*i*.

Hodby, J. W. Quantum-limit phenomena in the magnetoconductivity of the K halides, (6) 151*h*.

Hodgkinson, H. R. See West, H. W. H.

Hodgson, B. P. See McMillan, P. W.

Hodkin, E. N. See Nicholas, M. G.

Hodson, P. T. A., and Richardson, H. M. Mineralogical examination of refractory linings of Kaldo vessels, (1) 7*i*.

Hoefgen, H. See Schwiete, H. E.

Hoefler, H. See Peter, E.

Hoeh, F. W. U-shaped fluorescent lamp with improved envelope-bracing means, P (1) 5*f*.

Hoekje, H. H., Strain, F., and Wilson, W. L. Process for preparing pigmentary metal oxide, P (5) 117*i*.

Hoekstra, J. P. See Blum, J. M.

Hoelscher, M. W., and Strubhar, P. D. Method for metalizing a ceramic body, P (3) 66*b*.

Hoeltje, G. Pressure measurement on impact spindle presses in the ceramic industry, (5) 115*h*.

Hoens, M. F. A. Hot water tank enameling, (4) 79*j*.

Hofer, A. See Steffen, J.

Hofer, F., and Schueler, C. Method for producing intermetallic compound permanent magnet material, P (11) 275*d*.

Hoff, G. C. Porosity-strength considerations for cellular concrete, (5) 104*d*.

Hoff, P. H. See Everhart, T. E.

Hoffman, C. Pottery from Crete, (5) 102*c*.

Hoffman, C. G. See Benz, R.

Hoffman, E. R. Importance of binders in spray dried pressbodies, (4) 92*f*.

Hoffman, L. C. Bismuthate glass-ceramic precursor compositions, P (11) 274*d*. Glass-ceramic precursors, P (8) 192*j*. See Amin, R. B.

Hoffman, L. C., and Nakayama, T. High dielectric constant ceramic bodies and compositions for producing same comprising Fe oxide, P (9) 225*b*.

Hoffman, M. V. Divalent Eu-activated alkaline earth AlF_3 luminescent materials and process, P (4) 87*c*. Fluorescence and energy transfer in $SrZnP_2O_7$:UO_2^{2+}, (2) 47*h*. Uranyl-activated Sr Zn pyrophosphate phosphors, P (9) 228*c*.

Hoffman, W. D., and Larson, A. E. Foundry mold process and pattern composition, P (7) 164*d*.

Hoffmann, H. Characterization of the thermal behavior of bloating minerals in the hot-stage microscope, (6) 134*f*.

Hoffmann, H., and Thurnay, K. Eqs. of state for the nuclear fuels UC and PuC, (5) 114*j*.

Hoffmann, U. Testing of plaster molds in the ceramic laboratory, (5) 116*c*. See Harkort, D.

Hofmann, D., Kuehl, B., and Rasch, E. Low-pressure Hg vapor discharge lamp containing [In-Hg] amalgam, P (4) 82*f*.

Hofmann, H., and Katz, H. Dispenser cathode structure, P (10) 244*c*.

Hofstein, S. R. Electronic storage tube utilizing a target comprising both Si and SiO_2 areas, P (4) 87*f*. Image-transducing storage tube, P (6) 138*b*. Self-scanned phototransistor array employing common substrate, P (3) 67*j*.

Hogan, W. M. See McDonald, W. N.

Hoge, J. H. See Albert, R. J.

Hogeboom, J. G. Etched Schottky-barrier MOSFETs, (1) 11*e*.

Hohberg, G. See Haeusler, G.

Hohlfeld, H. See Schuller, W.

Hohlwein, H. R. Electronic data processing in the ceramic industry—installation of a computer for body preparation in the porcelain industry, (11) 276*j*.

Hokinoue, Yoshikazu. See Tsuboi, Tatsuaki.

Holcomb, R. H. See Levand, V. A., Jr.

Holcombe, C. E., Jr., and Horne, O. J., Jr. Method for preparing B suboxide, P (8) 203*c*. Preparation of B_2O, (3) 68*e*.

Holden, C. B., and Wilson, W. L. Preparation of TiC, P (8) 196*h*.

Holderreed, F. L. See Habashi, Fathi.

Holdridge, D. A. See Taylor, W. A.; Walker, E. G.

Hollan, L. See Boucher, A.

Holland, A. E. See Segnit, E. R.; Stevens, T. J.

Hollander, E. F., Jr. Method for making graphite whiskers, P (9) 222*a*.

Hollingsworth, W. W. Hanging bosh construction with means allowing for thermal expansion, P (11) 272*c*.

Holloway, H. Vacuum deposition, P (6) 140*c*.

Holloway, W. W., Jr., and Kestigian, M. Lu-Nd-doped YAG, P (4) 88*c*. Optical properties of Ce-activated garnet crystals, (1) 11*g*.

Hollox, G. E., Novak, D. L., Huntington, R. D., and Slattery, P. W. Slip systems in VC-TiC alloys, (2) 49*b*.

Hollox, G. E., Precht, W., Lye, R. G., and Westwood, A. R. C. High-temp. TiC-VC structural materials, P (8) 196*a*.

Holm, B. L. Apparatus utilizing sonic vibrations to facilitate the movement of particulate material along a sloping surface [bin], P (5) 115*e*.

Holm, J. L. See Grjotheim, K.

Holm, R. L., and Ashford, J. W. Ceramic-ball-insulated depressed collector for a microwave tube, P (10) 249*j*.

Holman, R. L., and Fulrath, R. M. Intrinsic nonstoichiometry in single-phase $Pb(Zr_{0.8}Ti_{0.2})O_3$, (5) 121*e*.

Holmes, L., Sherwood, R. C., Van Uitert, L. G., and Haefner, S. Paramagnetic anisotropy and crystal-field splittings in $EuAlO_3$, (5) 122*a*.

Holmes, L. M. See Wood, D. L.

Holmes, W. H. See Cox, R. W.

Holmes, W. H., Cox, R. W., Davies, E., and Salt, D. L. British Ceramic Research Assn. quickfire kiln, (9) 232*c*, (11) 279*a*.

Holmstrom, F. R. Shielded-cathode mode bulk effect devices, P (2) 42*f*.

Holmwood, R. A. See Glang, R.

Holroyd, P. Laminated structures, P (11) 270*b*.

Holscher, H. H. Glass Primer, B (11) 283*i*.

Holseth, H., Kjekshus, A., and Andresen, A. F. Compounds with the marcasite-type crystal structure (VI) neutron diffraction studies of $CrSb_2$ and $FeSb_2$, (5) 118*h*.

Holst, P. See Tolksdorf, W.

Holt, S. L. See Simo, C.

Holt, W. C., Jr. See Youtsey, K. J.

Holton, W. C. Information storage by changing the valence state of a semiconductor crystal, P (11) 274*j*. $^2S_{1/2}$ impurity maser, P (10) 252*e*.

Holtzberg, F. See Eastman, D. E.

Holzapfel, W. B., and Drickamer, H. G. Effect of pressure on the Néel temp. of CoO, (5) 120*d*.

Holzl, R. A. See Glaski, F. A.

Holznagel, W., Hund, F., and Gerlach, G.

Production of temp.-stable Fe-Mn oxide black pigment, P (2) 46*g*.
Hondros, E. D. See McLean, M.
Honeiser, V. P. See Brand, J. S.
Hong, In Sun. See Duwell, E. J.
Honig, J. M., Van Zandt, L. L., Reed, T. B., and Sohn, J. Negative-magnetoresistance effects in Ti_2O_3, (5) 122*g*.
Hoogendoorn, C., Moody, M., and Schwuttke, G. H. Method of fabricating semiconductor structures with reduced crystallographic defects, P (6) 138*e*.
Hoogendoorn, H. M., Liberman, H. E., Narken, B., and Sunners, B. Method of mounting a ferrite head, P (5) 113*a*.
Hoogendoorn, H. M., Narken, B., Roeder, P. J., and Sunners, B. Air bearing magnetic head with glass slider body, P (10) 249*e*.
Hooker, J. R. Nuclear fuel body and process for making [with thermosetting resin], P (6) 140*j*.
Hooper, R. C. See Cunningham, J. A.
Hoover, J. M. See Arnett, C. J.
Hope, B. B. See Manning, D. G.
Hopkins, R. H. See Melamed, N. T.; Roland, G. W.
Hopkins, R. H., Roland, G. W., Partlow, W. D., and Steinbruegge, K. B. Ca Y silicate oxyapatite laser material containing Nd or Er ion, P (4) 87*g*.
Hopkins, R. H., Roland, G. W., Steinbruegge, K. B., and Partlow, W. D. Ca-containing silicate oxyapatite laser materials, P (10) 249*h*.
Hoppe, R., and Schwedes, B. Crystal structure of $LiBiO_2$, (6) 146*a*.
Hoppe, W. Apparatus for holding and orienting a crystal in X-ray instruments measuring the microstructure thereof, P (4) 93*d*.
Hori, Hiroo. See Nakagawa, Takashi.
Hori, Hiroo, Tsuji, S., and Kiuchi, Y. Method of preparing photoconductive layers on substrates, P (1) 13*e*.
Hori, Hiroo, and Tsutsumi, T. Experimental Si Vidicon target without mosaic structure, (3) 73*g*.
Hori, Shoichiro, Murakami, K., and Tanaka, H. Method of producing $CaSO_4$ dihydrate, P (4) 79*g*.
Horibe, Toshiyasu, Katto, S., and Kuwabara, S. Ti-containing precipitates in the corundum phase of brown aluminous abrasives after heat treatment in air, (3) 53*e*.
Horibe, Toshiyasu, and Kuwabara, S. Rate of Ti^{3+} exolution from brown abrasive corundum heated in air, (3) 74*j*.
Horiguchi, Hiroshi. See Yamamoto, Zensaku.
Horii, Kazuo. See Ueoka, Hisayoshi.
Horikawa, Kohsuke. See Kimura, Shigeo.
Horikawa, Shoichi. See Nakayama, Toshio.
Horikawa, Susumu, and Nakagawa, K. Transparent crystallized glass, P (10) 245*i*.
Horio, Yasuo. Apparatus for fracturing hot gobs of glass, P (1) 3*e*.
Horiuchi, Masatada. See Morita, Tadahisa; Tokuyama, Takashi.
Horiuchi, Takashi. See Yamamoto, Hirotaka.
Horn, F. H. Method for forming epitaxial crystals or wafers in selected regions of substrates, P (4) 88*h*.
Horn, H. See Gebhardt, F.
Horne, O. J., Jr. See Holcombe, C. E., Jr.
Horoszko, J. See Kedzior, A.
Horridge, T. A. See Dollimore, D.
Horrocks, S. Method of heat transfer, P (8) 206*f*.
Horsley, G. W., and Burnett, R. C. Mfg. ceramic artifacts having pores, P (5) 115*b*.
Horsley, J. B. See Harker, H.
Horsman, W. H. See Scott, B. A.
Horton, R. C. See Marzocchi, A.
Horvath, E. Method of mfg. an extruded catalyst composition, P (8) 207*g*.
Horvath, T., and Nagy, K. Simultaneous preparation of sintered magnesite and H_2SO_4 by use of SO_2 content of flue gases, (11) 279*i*.
Horwath, R. S., and Sadagopan, V. Transparent fabrication masks utilizing masking material selected from the group consisting of spinels, perovskites, garnets, fluorides, and oxyfluorides, P (8) 202*i*.
Hosegood, S. B. See Rennie, C. A.
Hoshina, Teruhiko, and Kuboniwa, S. 4*f*–5*d* transition of Tb^{3+} and Ce^{3+} in MPO_4 (M= Sc, Y, and Lu), (3) 73*a*.
Hoshino, Masahiro. Effect of clay and dolomite additions on $BaTiO_3$ ceramics crystal structure and sinterability, (11) 273*i*.
Hoshino, Yoshio. See Akimoto, Yasumasa; Utsunomiya, Taizo.
Hosokawa, Masuo, Yokoyama, T., and Nakagawa, F. Powder classifier, P (9) 230*b*.
Hosokawa, Masuo, Yokoyama, T., and Urayama, K. Device for measuring fluid characteristics of powdered or granular materials, P (9) 231*f*.
Hosotani, Shigeyoshi, and Matsubara, A. Relation between heat of hydration of cement and adiabatic temp. rise of concrete in the early stage of hydration, (9) 215*c*.
Hosoya, Sukeaki. See Fukamachi, Tomoe.
Hossain, D., and Brett, N. H. Phase equilibria in ternary systems containing ZrO_2 and SiO_2 (III) system MgO-ZrO_2-SiO_2, (1) 23*f*.
Hotaling, R. A. See Griswold, D. A.
Hou, K. C. Vapor phase B deposition by pulse discharge, P (10) 253*d*.
Houck, C. W. See Canonico, D. A.
Hough, A. J. Process for [epoxy] encapsulating electronic components, P (1) 14*d*.
Hough, C. See Fernandez-Moran, H.
Houldsworth, J. Cylindrical grinding machines, P (8) 203*h*.
Houseknecht, T. M. Shrinkage-compensating cement, P (6) 130*h*.
Houseman, D. H. See Singh, B. N.
Housholder, W. R. See Gammill, A. M.
Houska, C. R. See Carpenter, J. A.
Houwink, R., and de Decker, H. K. (editors). Elasticity, Plasticity, and Structure of Matter, B (3) 76*h*.
Hovasse, C. See Bonnel, B.
Howard, C. R. See Bye, G. C.
Howard, G. T. See Nichols, C. E., Jr.
Howard, J. K., and Smith, P. J. Analysis of defect distribution in transistor structures with reflection and transition X-ray topography, (9) 233*g*.
Howard, J. W. Hydraulic cement compositions, P (2) 31*f*.
Howard, R. T. Methods for visual characterization of trimmed thick-film resistors, (3) 63*g*.
Howard, W. E., Jr. See Esaki, L.
Howard, W. E., Jr., Ludeke, R., and Stiles, P. J. Gated metal-semiconductor transition device, P (6) 137*g*.
Howat, D. D. See Fahrback, D. O. E.
Howatt, G. N. Method of eliminating voids in ceramic bodies, P (4) 88*h*.
Howe, A. C. S. Low-density concretes and their manufacture, P (10) 242*d*.
Howell, B. F. Anomalous H_2O—fact or figment, (4) 95*d*.
Howell, C. M., and Anand, Y. High burnout resistance Schottky barrier diode, P (6) 137*j*.
Howell, J. D., and Krasienko, S. L. Capacitor having a glass-to-metal seal and an elastomeric seal, P (3) 64*j*.
Howell, J. R. See Siegel, R.
Howse, T. K. G., Kent, R., and Rawson, H. Determination of glass-mold heat fluxes from mold temp. measurements, (2) 32*c*.
Hozumi, Syoichi. See Kajii, Motohiko.
Hrapka-Wojnarovitsne, I. See Kocsis, G.
Hritz, G. G., Royer, D. J., and Ziegenhain, W. C. H_2O-dispersible α-Al_2O_3 monohydrate, P (10) 257*j*.
Hrma, P. Relation between rate of isothermal corrosion and composition of glass, (10) 243*i*.
Hryniszak, W., and Graham, R. P. High-temp. [composite] seals, P (4) 84*a*.
Hsieh, C. See Thomson, R.
Hu, King Lau. Alloy diode characteristics control method, P (8) 200*a*.
Hu, Shih Ming. Correlation factor of impurity diffusion in diamond lattice, (5) 119*a*.
Huang, I-Der, and Sonn, M. Computer control of batch processes, (11) 276*h*.
Huang, P. M. See Kozak, L. M.
Huang, R. J., Demirel, T., and McGee, T. D. Adsorption of H_2O vapor on E-glass, (9) 216*b*.
Huang, Y. K. Shock-wave behavior and properties of solids, (5) 123*f*.
Hubbard, W. N. See Fredrickson, D. R.
Hubble, D. H. See Kappmeyer, K. K.
Huber, D. L. See Fox, G. T.
Huber, W. W., and Dana, R. L. Method for dry-pressing ceramic tile, P (9) 223*c*.
Huber-Panu, J. Research into the kinetic processes in pulverization, (5) 115*i*.
Hubert, P. W. See Rode, J. A.
Huckabee, M. L., and Palmour, H., III. Rate controlled sintering of fine-grained Al_2O_3, (8) 195*d*.
Hudson, R. L. See Duffy, M. C.
Hudson, R. O. (editor). Proceedings of the Australasian Vitreous Enamellers' Institute Convention, 1970 (Vol. 2), B (2) 52*a*.
Hudson, W. G. See Snellman, D. L.
Huebotter, P. R., and Bump, T. R. Fuel assembly for a liquid-metal-cooled fast breeder reactor, P (10) 253*h*.
Huelsenberg, D. Relations between the structure and deformation of fireclay at high temps., (11) 271*g*.
Huenlich, H. W. Of what significance to the brick and ore industries engineers are the problems of environmental protection, (9) 239*h*.
Huetter, J. See Stich, H.
Huettinger, K. J. Intermediate liquid-crystalline phases during thermal degradation of aromatics yielding graphitic C, (1) 22*j*. See Fitzer, E.
Huff, R. G. Apparatus for sensing temp., P (9) 231*d*.
Huffman, T. R. See Coleman, M. G.
Hufnagel, R. E. High-power laser including means for providing power output, P (2) 40*b*.
Huggins, R. A., Bube, R. H., and Roberts, R. W. (editors). Annual Review of Materials Science (Vol. 1, 1971), B (2) 50*h*.
Hughes, B. P. See Lowe, I. R. G.
Hughes, E. W. See Gibbon, D. L.
Hughes, G. See Bickerdike, R. L.
Hughes, I. F., and Page, E. W. Influence of Mn and C on plastic anisotropy, grain size, and ductility in pure Fe, (6) 148*j*.
Hughes, J. J. See Napoli, L. S.
Hughes, R. E. See Bless, P. W.
Hughes, W., and Williams, F. R. Process of beneficiation, P (4) 94*f*.
Hughey, V. V. Process for improving the hydration resistance of dead-burned MgO, P (10) 248*d*.
Hugli, H. W. Welded pressure transducer, P (1) 15*b*.
Hugo, G. Implications of glazing, (11) 266*a*.
Hugot, A. A. Hg vapor lamp, P (9) 219*h*.
Huheey, C. L. See Huheey, J. E.
Huheey, J. E., and Huheey, C. L. Anomalous properties of elements that follow "long periods" of elements, (8) 207*j*.
Huiskens, J. C. See Reber, R. L.
Huiszoon, C. See Groenewegen, P. P. M.
Huizinga, F. See van der Giessen, A. A.
Hu, King Lau. Method for fabricating an alloyed semiconductor device, P (1) 13*c*.
Hujii, Toshisada. See Suzuki, Kazutaka.
Hukui, Hideo. See Suzuki, Kazutaka.
Hulbert, R. W. See Nies, N. P.
Hulbert, S. F., Wilson, H. H., and Venkatu, D. A. Kinetics of the reaction between MgO and Fe_2O_3 in powder compacts, (1) 23*h*.
Hull, C. J. See Wagner, W.
Hull, E. M. See Gereth, R. K.
Hulley, B. J. Method and apparatus for product sampling, P (9) 231*j*.
Hulse, C. O. Process of casting Ni-base alloys using H_2O-soluble CaO cores, P (6) 135*b*.
Huml, J. O., and Layne, G. S. Method for preparing AlN and metal fluoride single crystals, P (1) 9*c*. Production of polymeric fibers or coherent thin deposit of an Si and O compound, P (10) 257*h*.
Hummel, F. A. See Craig, D. F.; Richerson, D. W.
Humphery, T. See Wright, J. W. T.
Humphrey, J. R. See Christie, J. H.
Humphrey, W. E. Lens surface grinding method and apparatus, P (1) 4*j*.
Hums, D., and Brueckner, R. Development of different coagulation mechanisms and the action of ultrasonic radiation on dilute kaolin suspensions, (6) 146*a*. Mechano-optical investigations on coagulation and dispersion in kaolin suspensions, (7) 178*e*.
Hund, F. CrO_2 catalyst, P (9) 232*f*. See Holznagel, W.
Hung, J. J. See Tchalenko, J. S.
Hunsperger, R. G., and Marsh, O. J. Method of forming an ohmic contact region in a thin semiconductor layer, P (9) 226*h*. Method for making *n*-type layers in GaAs at room temp., P (6) 138*i*.
Hunter, D. Air dryer/filtration unit, P (7) 172*i*.
Hunter, O., Jr. See Branscomb, T. M.; Manning, W. R.
Hunter, R. I. See Sagmuller, J. R.
Huntington, R. D. See Hollox, G. E.
Hurlbut, M. R., and Lane, J. W. Method and apparatus for cement kiln control, P (1) 2*e*.
Hurley, E. B. Reduction of dustiness and abrading of soft porous low-density hydrated $CaSiO_3$ products, P (8) 207*g*.
Hurley, G. F. Process for coating an α-Al_2O_3 body with an epoxy resin, P (3) 62*c*.
Hurst, V. J. Continuous hydrothermal apparatus and process, P (1) 20*b*.
Hurt, J. C. See Rawal, B. S.
Huruhashi, Isao. See Suzuki, Kazutaka.
Huschka, H. See Herrmann, F. J.
Huska, G. Rapid microscope method for quantitative determination of fine sands and similar materials, (10) 255*c*.
Huska, P. A., Meissner, H. P., and Lamb, T. J. Method and apparatus for converting Al nitrate solutions to α-Al_2O_3, P (6) 144*b*.
Husni, S. Y. Method of connecting semiconductor device to terminals of package, P (9) 226*e*.
Hussein, A. T. See Khalil, A. A.
Hussein, M. K., Kolta, G. A., Hewaidy, I. F., and El Roudi, A. M. Solid-state reduction of chromite ores by H, (6) 151*g*.
Hust, J. G. See Sparks, L. L.
Hutchinson, R. W., and Stein, F. P. Laboratory apparatus for the classification of very fine, irregularly shaped, difficult-to-handle particles, (3) 69*h*.
Huth, G. C. Si device having a Pb silicate thereon and method of forming, P (9) 227*i*.
Hutson, J. L. Process for glass passivating Si semiconductor junctions, P (4) 90*d*. Semiconductor device manufacture with junction passivation, P (2) 42*i*. Semiconductor magnetic device, P (11) 275*h*.
Hutton, W. L. Filter press plate process and apparatus, (9) 230*b*.
Huxtable, J. See Zimmerman, D. W.
Hwang, C. J. Doping dependence of hole lifetime in *n*-type GaAs, (6) 146*f*.
Hwang, Paul Y. Co-doped γ-ferric oxide, P (9) 224*i*.
Hyde, B. G. Crystallographic shear relations between the structure types α-UO_3, CaF_2, La_2O_3, and NaCl and a correlation of some lanthanide and actinide oxide structures, (9) 234*f*. See Bursill, L. A.
Hyde, G. R. Dielectric properties of sintered Y_2O_3, (1) 11*b*.
Hyland, J. W., Jr., and Bengtson, R. H. Siliceous fiber for reinforcement and method of mfg., P (3) 59*g*.
Hymore, F. J. See Ritter, G. F., Jr.
Hynd, W. C. Glassmelting furnaces having hinged floor insulation, P (7) 161*j*.

Iacaccia, L. C. Heating apparatus, P (2) 45*g*.
Iannicelli, J. See Whitley, J. B.

Iannicelli, J., Kunkle, A. C., and Maynard, R. N. Method of brightening kaolin clay by removing organic contaminants, P (8) 207*f*.

Iberg, R. Contribution to the thermal chemistry of brick clay, (1) 5*h*.

Ichida, Atsuyoshi, and Miyata, Y. Method of mfg. color picture tube, P (9) 219*b*.

Ichikawa, Hirohiko. See Shirai, Yoshihiro.

Ichikawa, Kazuhiko, Okubo, T., and Shimoji, M. Electrical conductivities of molten I_2+Te solutions, (6) 147*e*.

Ichikawa, Osamu. See Yoshida, Kenji.

Ichikawa, Yuji. See Namikata, Takeshi.

Ichimura, Nobuyoshi. See Suzuki, Yoshiro.

Ichinose, Noboru, Egami, H., Yokoyama, K., and Tanno, Y. Oxide piezoelectric material, P (8) 202*a*.

Ichinose, Noboru, Egami, H., Yokoyama, K., and Yamashita, Y. Piezoelectric oxide materials, P (11) 275*j*.

Ichinose, Noboru, Takahashi, T., and Yokomizo, Y. Crystal growth of $Pb(Cd_{1/3}Nb_{2/3})O_3$ and its dielectric properties, (4) 95*g*.

Ichinose, Noboru, Yokoyama, K., Egami, H., and Tanno, Y. Piezoelectric ceramic compositions, P (6) 139*a*.

Ichinose, Noboru, Yokoyama, K., and Nishikawa, H. Ceramic resonators, P (10) 250*a*.

Iden, R. B. See Blosser, E. R.

Idorn, G. M. Research and development in the cement and concrete industry, (2) 31*b*.

Ieda, Bunichiro. See Saito, Shuntaro.

Ieda, Masayuki, Sawa, G., and Kato, S. Poole-Frenkel effect on electric conduction in insulators, (5) 122*e*.

Iehisa, Masatoshi. See Watanabe, Shigeo.

Iemura, Toshio, Doi, M., and Shimizu, Y. Magnetic transducer heads, P (10) 251*e*.

Iga, Takeo. See Kato, Shuzo.

Igarashi, Osamu. Crystallographic orientations and interfacial mismatches of single-crystal CdS films deposited on various faces of Zn blende-type materials, (6) 145*f*.

Igarashi, Ryo. See Nakanuma, Sho; Wada, Toshio.

Igarashi, Yukio. Semiconductor-controlled rectifying device, P (6) 140*b*.

Ignat'ev, O. S. See Roi, V. A.

Ignatius, R. H. Starch-coated fibers having improved drying characteristics, P (2) 35*c*.

Ignatova, T. S. See Buldakov, A. A.

Ihara, Masayoshi. Crystal structure of Li_2O-B_2O_3-$2GeO_2$, (5) 119*b*. See Yoshimura, Takuji.

Ihara, Masayoshi, and Fukunaga, J. Consideration of the concept of partial molar vol for nonideal solutions such as glass, and a method to idealize vol-composition relations of nonideal solutions, (6) 131*i*.

Ihochi, Takahiko. High-power integrated-circuit ceramic package with metallic heat-conducting body, P (6) 137*j*. See Kawakatsu, Fumimaro.

Ihrig, A. C., and Rahe, V. Forehearth surface glass separation and removal, P (4) 81*j*.

Ihrig, A. C., and Wilson, R. W. Radiation target structure and use to cool molten glass, P (6) 133*f*.

Iida, Seishi, and Unno, Y. Semiconductor laser, P (8) 202*a*.

Iida, Shinya, Sato, H., and Takeda, Y. Bond-type diode utilizing Sn-doped GaAs, P (8) 200*e*.

Iida, Shuichi. See Mizushima, Koichi.

Iida, Yoshio. See Masuyama, Takeshi; Matsuoka, Michio; Nakata, Koreaki.

Iijima, Sunio. High-resolution electron microscopy of crystal lattice of Ti-Nb oxide, (7) 178*b*.

Iimura, Tsutomu, Kurokawa, S., and Emoto, M. Li-Zn ferrite composition with As oxide or Bi oxide additive, P (5) 113*b*.

IIT Research Institute. See U.S. Bureau of Mines.

Iizuka, Hiroshi. See Siire, Toyokazu.

Ikeda, Akio. See Nishikawa, Tomozo.

Ikeda, Isoroku. See Akatsu, Ken; Miyairi, Hidehiko.

Ikeda, Ko. See Tashiro, Chuichi.

Ikeda, Koji. See Kushihashi, Akira.

Ikeda, Masaru. See Suzuki, Takuya.

Ikeda, Masayoshi. See Kanazawa, Takafumi.

Ikeda, T. See Brandt, W. W.

Ikeda, Takahide. See Morita, Tadahisa; Tokuyama, Takashi.

Ikeda, Takuro, Haraguchi, T., Onodera, Y., and Saito, T. Some compounds of W-bronze type $A_xB_{10}O_{30}$ (B=Nb,Ti or Nb,W), (3) 75*i*.

Ikeda, Yoshiro. See Kitano, Ichiro.

Ikegami, Takayasu. See Matsuda, Shinichi.

Ikenaga, Hirotake. See Oshima, Hisaji.

Ikesawa, Hiroshi. See Watanabe, Osamu.

Ikeuchi, H. A. See Griotheim, K.

Ikushima, Y. See Tsuiide, Tohru.

Il'chenko, L. N. See Berezhnoi, A. I.

Iler, R. K. Method of producing colloidal SiO_2 by electrodialysis of a silicate, P (9) 233*a*. See Chay, Dong M.

Iler, R. K., and Palmer, A. B. Ti and/or Zr nitride based articles of jewelry, P (9) 222*i*.

Iler, R. K., and Rigby, E. B. Heterogeneous Co-bonded W carbide, P (8) 196*j*.

Iles, G. S. See Casale, M. E. A.

Iles, P. A. Method of coating solar cell with borosilicate glass and resultant product, P (7) 169*f*.

Il'ina, N. I. See Fedorov, P. I.

Il'ina, N. V. See Skoblo, L. I.

Il'yasov, I. I., and Barsegov, D. G. Complex formation in the system of the chlorides of Cs, Tl, and Pb, (5) 118*h*. System K,Cs‖Cl,I, (5) 124*f*.

Il'yasov, I. I., Barsegov, D. G., Berikashvili, I. G., and Danilenko, L. P. X-ray phase study of melts of binary salts of the halides of mono- and bivalent metals and Tl, (5) 125*i*.

Ilyukhin, V. V. See Butt, Yu. M.; Ganiev, R. M.

Ilyushchenko, A. I. See Ostrikova, N. V.

Imagawa, Hiroshi. ESR studies on ns^1 centers in glass (I) Au atom in photosensitive glass; (II) Ag atom in mixed alkali silicate glass; (III) the s-character of Cd^+ and the basicity of the host glasses, (3) 55*h*,*j*.

Imahori, Yutaka. See Kamegaya, Takeo.

Imai, Atsuo. See Sugaike, Suezo.

Imamura, Hitoshi, and Katakura, K. Color TV tube having shadow mask support studs unequally spaced from screen, P (8) 192*e*.

Imamutdinova, K. Kh. See Akhunov, A. M.

Imanaka, Osamu. Recent progress in abrasive machining of glass and ceramics, (3) 53*i*.

Imaoka, Minoru. See Suzuki, Suguru.

Imaoka, Minoru, Hasegawa, H., Hamaguchi, Y., and Kurotaki, Y. Chemical composition and tensile strength of glasses in the B_2O_3-PbO and B_2O_3-SiO_2-Na_2O systems, (5) 105*g*.

Imaoka, Minoru, Konagaya, Y., and Hasegawa, H. Studies on $ZnCl_2$ glass, (5) 106*b*.

Imashev, M. K. See Butt, Yu. M.

Imbusch, G. F. See Berggren, M. J.; Chang, Tung Symon.

Imlach, J. A., and Glasser, F. P. Subsolidus phase relations in the system CaO-Al_2O_3-Fe-Fe_2O_3, (2) 50*e*.

Imler, V. R. See Johnson, R. S.

Immel, W. Electrolytic pretreatment before single-coat enameling, (8) 188*i*.

Imoto, Yonezo. Thermal expansion characteristics of limestone-containing green bodies for earthenware, (5) 111*e*.

Imperato, L. G., Jr. Methods and composition for mfg. portland cement, P (1) 2*e*.

Inaba, Ritsuo, Ishiguro, T., and Mikoshiba, N. Preparation and properties of rf sputtered films of ZnO as an ultrasonic transducer, (3) 63*c*.

Inaba, Ritsuo, Kajimura, K., and Mikoshiba, N. Generation and detection of elastic surface waves with ZnO film transducers, (3) 63*a*.

Inagaki, Michio. See Hoda, Tokiti; Naka, Shigeharu.

Inagawa, Konosuke, Kamigaki, K., and Miura, S. Spin flopping in CoO crystal in the pulsed intense magnetic field, (4) 98*h*.

Inal, O. T. See Murr, L. E.

Ingles, T. A. Porcelain for high-voltage applications, (7) 165*f*.

Ingram, D. J., and Eagles, G. J. Brick-handling apparatus, P (3) 60*b*.

Ingram, M. D. See Duffy, J. A.

Ingulli, C. A litt'e FFFFFFFFFT goes a long way, (5) 101*e*.

Inkinen, Osmo. See Togawa, Senichi.

Innes, W. P. See Rhodenizer, H. L.

Inomata, Hiroshi. See Yasuda, Kazuo.

Inomata, Yoshizo. Thermal stability of the wurtzite and sphalerite structures, (3) 76*a*. See Mitorro, Mamoru.

Inomata, Yoshizo, and Inoue, Z. Wurtzite-type SiC whiskers obtained by the sublimation method and the thermal stability of the basic polytypes of SiC, (3) 61*a*.

Inomata, Yoshizo, Inoue, Z., and Mitomo, M. Platelike α-SiC single crystals grown from an Si melt in a graphite crucible, (6) 150*j*.

Inomata, Yoshizo, and Matsumoto, S. Formation of β-SiC during the initial growth stage of SiC crystals, (5) 120*i*.

Inomata, Yoshizo, and Tanaka, H. Growth of SiC single crystals, (6) 148*a*. Inclusion of small C particles in SiC crystals prepared by the sublimation method, (3) 73*g*.

Inoue, Eiichi. See Nakayama, Takao.

Inoue, Hiroshi. See Komeya, Katsutoshi.

Inoue, Ichiro, Mori, Y., and Hashimoto, M. Bond strength of super-rapid-hardening portland cement concrete, (10) 241*g*.

Inoue, Keiji. Piezoelectric transducer elements, P (8) 202*c*. See Sakurai, Yasunobu.

Inoue, Ken. See Daimon, Masaki.

Inoue, Masaharu. See Washio, Shigeaki.

Inoue, Morio. Semiconductor device having a TiO_2-SiO_2 composite oxide layer, P (2) 42*i*.

Inoue, Noboru. See Koshiishi, Kuniaki.

Inoue, Noboru, and Wada, M. Glass bulb blowing machine, P (6) 132*g*.

Inoue, Norihiro. See Matsuda, Osaku.

Inoue, Taiichi, and Ueda, T. Ce and Si substituted Mn activated Mg gallate phosphor, P (9) 225*a*. Si and/or Ge dioxide substituted Mn activated Mg aluminate gallate phosphor, P (9) 227*i*.

Inoue, Touru, and Tachibana, M. Preparation of glass containing Se, P (4) 82*h*.

Inoue, Touru, Yamada, T., and Noguchi, S. Method for production of fused energy-conducting structure, P (9) 219*d*.

Inoue, Yoshiki. See Asano, Shunkichi.

Inoue, Yoshiki, Asano, S., and Yamagiwa, Y. Carbonation of cement pastes using several curing methods, (9) 213*i*.

Inoue, Zenzaburo. See Inomata, Yoshizo.

Insartseva, S. A. See Budnikov, P. P.

Insley, L. F. Vitrified clay pipes, (2) 35*f*.

Insolio, T. A., Guzowski, R. M., and Steinkamp, R. A. Glass cutter, P (11) 270*i*.

Institut du Verre, Paris. Scientific and Technical Communications of the 9th International Congress on Glass, B (7) 184*c*. Compte Rendu des Travaux, 9th International Congress on Glass, B (11) 283*e*.

Into, Masakazu. See Kimura, Morihiro.

Inukai, Kiyo. See Kumagai, Yasuji.

Ipat'eva, V. V., Borisova, Z. U., and Molchanov, V. C. Observance of additivity principle of electroconductivity of 2-alkali glasses, (7) 160*i*.

Ippolitov, A. G. See Zhigarnovskii, B. M.

Iqbal, M., and Baker, E. H. Measurements of total ac conductivity of ThO_2-YO_2 solid solutions at high O pressures, (9) 236*h*.

Irie, Toshiaki, Sato, K., and Nanko, Y. Transistor device with plateau emitter and method for making, P (9) 228*b*.

Irish, D. E. See Brooker, M. H.

Irvin, J. C. Method of making semiconductor device components, P (7) 169*a*.

Irving, B. F. See Chapman, R. P.

Irving, S. M. Plasma oxidation process for removing photoresist films, (3) 63*a*.

Irving, S. M., Lemons, K. E., and Bobos, G. E. Gas plasma vapor etching process, P (2) 40*i*.

Irwin, G. W. Blowhead-operating mechanism, P (4) 81*a*.

Irwin, W. T., and Drummond, W. W. Expanded fiber glass strand, P (1) 4*a*.

Isaacs, T. J. See Riedel, E. P.

Isaacson, R. A. See Calvo, R.

Isaksen, R. A., Williams, C. R., Heaps, J. F., and Clark, R. J. Laser light scattering for determination of agglomeration in dispersed systems, (1) 17*f*.

Isaksson, S. E. Method of mfg. rods or tubes from powder, P (1) 17*b*.

Isard, J. O. Mixed alkali effect in glass, (3) 56*f*. See Topping, J. A.

Ischenko, A. Ya., and Sinchuk, A. G. Flux for welding light alloys, P (4) 80*c*.

Ise, Yukihiko, and Kaname, Y. Switching device employing a piezoelectric ceramic resonator, P (2) 42*i*.

Ise, Yukihiko, Kaname, Y., and Wada, K. Piezoelectric ceramic band-pass filter, P (3) 66*g*.

Iseki, Takayoshi, and Tagai, H. Shift of Al$K\alpha$ peak in Ca aluminates, (6) 151*d*.

Isherwood, T. H. Bonding high purity aggregates with inorganic polymeric compounds, (4) 83*j*.

Ishibashi, Michio. See Nagata, Takashi.

Ishibashi, Yoshihiro, and Takagi, Y. Force constants in $BaTiO_3$ and $SrTiO_3$, (4) 96*h*.

Ishida, Tomio. See Sato, Kunio.

Ishida, Toru. See Nishikawa, Tomozo.

Ishigaki, Eiichi. Filter press, P (6) 141*e*.

Ishiguri, Hachiro. Optical glass having a high refractive index and a low dispersion, P (10) 245*h*.

Ishiguro, Takehiko. See Inaba, Ritsuo.

Ishihara, Shoichi. See Asano, Shunkichi.

Ishihara, Toshio, Okazaki, T., Endo, T., Koichi, T., and Nakajima, S. Process for the production of phosphoric acid at a high concentration and a gypsum by-product of improved quality, P (7) 175*i*.

Ishii, Eiichi. See Tabata, Hideyo.

Ishii, Hajime. Consecutive spectrophotometric determination of Fe, Ti, and Al in cement and its raw materials using Calcichrome as a common reagent, (4) 78*g*.

Ishii, Hajime, and Einaga, H. Rapid chelatometric determination of Ca and Mg in cements, (9) 215*b*.

Ishii, Katsuyuki. Semiconductor electromechanical transducer element having a *pnp* or *npn* amplifying junction integrally associated with a strain-sensitive region, P (8) 202*i*.

Ishii, Shiro. See Kawano, Toshio.

Ishii, T. K. Microwave ferrite acceleration sensor, P (5) 113*c*.

Ishii, Teruji. Apparatus and method for automatic quantitative analysis of substances by slight enthalpimetric difference, P (6) 142*b*.

Ishikawa, Iwao. See Saito, Teruyoshi.

Ishikawa, Masaoki. See Shinoda, Daizaburo.

Ishikawa, Masaoki, and Shinoda, D. Laminated electrode for a semiconductor device, P (8) 201*a*.

Ishikawa, Tatsuo. See Tokumitsu, Yoshiharu.

Ishikawa, Toshikatsu, and Teranishi, H. Method for mfg. heat-resistant carbonaceous products having low permeability, P (4) 84*f*.

Ishikawa, Yoshikazu. See Syono, Yasuhiko.

Ishikawa, Yoshikazu, Sato, S., and Syono, Y. Neutron and magnetic studies of a single crystal of Fe_2TiO_4, (3) 74*c*.

Ishikawa, Yoshikazu, and Syono, Y. Giant magnetostriction and magnetic anisotropy of Fe_2TiO_4, (3) 73*b*.

Ishimitsu, Akitoshi, Furui, T., Sato, K., and Sawamura, Y. Process for producing a Ca ferrite for making steels, P (6) 135*d*.

Ishimura, Susumu. See Kawano, Toshio.

Ishiyama, Masahiko. Glass laser materials, P (10) 244*b*.

Ishizuka, Hiroshi. Method for preparing $ZrCl_4$ and $HfCl_4$, P (9) 232*j*.

Isirikyan, A. A. See Dubinin, M. M.

Iskra, J. See Laskowski, J.

Ismatov, A. A. See Kolesova, V. A.; Toropov, N. A.

Isobe, Seishiro. See Kadotani, Makoto.

Isphording, W. C. Analysis of variance applied to measures of central tendency and dispersion in sediments, (8) 204*g*.

Isserlis, M. D. Ferrite powder and method of preparing it, P (4) 87*i*.
Isupova, L. A. See Anoshina, N. P.
Itai, Akira. See Yoshida, Hideo.
Itakura, Kiyoshi, and Noguchi, S. Float glass apparatus with flow control dams, P (1) 4*c*.
Itakura, Masayuki. Electrooptic switch using rotated Y-plate of $LiNbO_3$, (3) 62*i*.
Ito, Kunihiko. See Kita, Hideo.
Ito, Kunihiko, Fujimoto, Y., Obsato, N., and Akashi, N. Apparatus for mfg. glass ribbon by float process, P (8) 192*j*.
Ito, Kunimoto. See Miyake, Yasutomo.
Ito, Saburo, and Ezaki, S. Metal halide discharge lamp containing Be, P (2) 34*a*. Metal halide discharge lamps, P (4) 82*h*.
Ito, Sadatoshi. See Hanada, Mitsuo.
Ito, Shiro, and Iwaya, S. Ceramic condensers, P (3) 64*j*.
Ito, Suketoshi. See Naka, Shigeharu.
Ito, Tomizo. See Tsuboi, Tatsuaki.
Ito, Toshiji. See Kobayashi, Kazusuke.
Ito, Yukio. See Matsuyama, Shigeru.
Itoh, Hideaki. See Takahashi, Takehiko.
Itoh, Tadatsugu, and Kushiro, Y. Arsenic and Cd implantations into *n*-type GaAs, (7) 176*h*.
Itoh, Teruo. See Moriki, Juichi.
Itoh, Yokichi, and Hashimoto, N. Semiconductor surface-barrier diode of Schottky type and method of making, P (5) 114*a*.
Itoh, Yokichi, Shirasaka, N., and Tauchi, S. Method of mfg. semiconductor devices, P (8) 201*f*.
Itoh, Yoshio, and Iwasaki, H. W bronze field in the pseudoternary system $NaNbO_3$-$BaTiO_3$-$BaNb_2O_6$, (10) 261*e*.
Ivanov, G. I. See Kulygin, I. P.
Ivanov, I. P., and Gusynin, V. F. Stability of paragonite in the system SiO_2-$NaAlSi_2O_6$-Al_2O_3-H_2O, (5) 124*e*.
Ivanov, O. A. See Zaborovskii, V. I.
Ivanova, G. M. See Turchinova, L. N.
Ivanova, M. P. See Makarychev, A. R.
Ivanova, V. A. See Pevzner, B. Z.
Ivanov-Emin, B. N. See Zaitsev, B. E.
Ivensen, V. A. See Chaporova, I. N.
Iwabuchi, Toshitsugu. Supplemental study on a grinding aid [diethylene glycol] for cement, (9) 215*g*. See Tanemura, Tadashi.
Iwabuchi, Toshitsugu, Okaue, H., and Sanami, T. Effect of grinding aid of cement on the technical properties of concrete, (6) 128*c*.
Iwabuchi, Toshitsugu, Shimobayashi, S., and Suzuki, M. Effect of diethylene glycol as a grinding aid or an admixture on the various properties of cement, (4) 78*f*.
Iwai, Shinichi. See Moori, Takahiko; Watanabe, Tetsuo.
Iwai, Shinichi, Ossaka, J., and Morikawa, H. Impurities and micropores of agate, (5) 117*h*.
Iwai, Shinichi, Ossaka, J., Morikawa, H., and Watanabe, T. Study on agate (II) X-ray line broadening in agate, (3) 75*e*.
Iwasa, Hitoo. See Teramoto, Iwao; Yokozawa, Masami.
Iwasa, Minetaka. Surface barrier junction diode, P (6) 140*i*.
Iwasaki, Hiroshi. Equilibrium concentration of vacancies in TiO under high pressure, (3) 73*e*. See Itoh, Yoshio; Miyazawa, Shintaro; Uchida, Naoya.
Iwata, Tadao, and Nihira, T. Atomic displacements by electron irradiation in pyrolytic graphite, (4) 95*d*.
Iwauchi, Kozo. Dielectric properties of fine particles of Fe_3O_4 and some ferrites, (3) 62*d*.
Iwauchi, Kozo, Yamamoto, S., Bando, Y., Hanai, T., Koizumi, N., Takada, T., and Fukushima, S. Dielectric properties of the mixtures of α-Fe_2O_3, TiO_2, and Fe_2TiO_5, (3) 62*d*.
Iwaya, Shoichi. See Ito, Shiro.
Izatt, R. M. See Christensen, J. J.
Izen, E. H. See Kemp, J. C.
Izumi, Isao. See Okumura, Akihiro.
Izumitani, Tetsuro. See Asahara, Yoshiyuki.
Izumitani, Tetsuro, and Harada, S. Polishing mechanism of optical glasses, (3) 57*a*.
Izumitani, Tetsuro, and Namiki, K. Optical glass with a high refractive index and a high dispersing ability, P (8) 193*h*.
Izumitani, Tetsuro, and Toda, S. Stable fluorophosphate optical glass, P (8) 194*b*.

Jaccarino, V. See Yasuoka, Hiroshi.
Jackson, B. L. J., Metcalfe, A., and Wilcock, R. J. Adsorption hysteresis on disordered kaolinite, (2) 46*j*.
Jackson, C. T. Apparatus for producing fiber glass articles, P (10) 243*g*.
Jackson, G. N. See Emery, J. A. A.
Jackson, H. W. See Ehrlinger, H. P., III.
Jackson, R. C. Method for assembling groups of flat modular pieces [tile], P (8) 198*f*.
Jackson, S. R. Depressible beam collector structure for electron tubes, P (10) 250*g*.
Jackson, W. B. See Adamski, J. A.
Jackson, W. H., and Robison, B. J. Rf sputtering system with the anode enclosing the target, P (8) 202*f*.
Jacob, C. J., and Lawton, G. W. Method of making electrical connections to a glass-encapsulated semiconductor device, P (9) 226*a*.
Jacob, H. See Bauer, R.
Jacob, L. See Guillet, H.
Jacobi, R. Conservation of medieval glass windows by a method based on the safety-glass technique, (1) 1*j*.
Jacobs, C. A. J., Beijer, L. B., and Driessen, A. J. G. C. High-pressure Hg vapor iodide discharge lamp, P (5) 107*i*.
Jacobs, D. A. See Cecil, T. A.
Jacobs, L. J. See Felice, F. T.
Jacobs, R. B. Fluid flow measurement systems, P (10) 255*j*.
Jacobson, H. W. SiO_2-deficient mullite fiber and a process for its production, P (1) 9*d*.
Jacqmarcq, M. See Levandowsky, L.
Jaeger, Eginhard. Improvement in container mold cooling, (8) 190*c*. See Nebelung, H. H.
Jaeger, Erwin. Means for preventing the adhesion of mineral fibers to the walls of a forming chamber, P (5) 107*a*.
Jaeger, H. See Caillag, A.
Jaenich, H. J. Apparatus for purifying dust-loaded [furnace] waste gases, P (10) 254*i*.
Jaep, W. F. Role of interactions in magnetic tapes, (5) 123*d*.
Jaffe, B., Cook, W. R., Jr., and Jaffe, H. Piezoelectric Ceramics, B (7) 184*a*.
Jaffe, H. See Jaffe, B.
Jaffe, J. See Csicsery, S. M.
Jaffe, P. M. Photoluminescence of Eu(II)-activated $EuAlO_3$, (9) 237*e*.
Jagdt, R., and Kloss, I. Optical mirror [telescopic], P (6) 133*d*.
Jagodzinski, R. F., and Mansur, F. E. Glass and glass-ceramic treating process, P (2) 34*e*.
Jagodzinski, R. F., and Spanoudis, I. Decorating process, P (2) 33*h*.
Jahn, P. F. Use of Al_2O_3 alone or with SiO_2 as sintering aid for B_4C, P (4) 85*a*.
Jain, L. C. Prevention of lime blowing in bricks by the addition of NaCl, (2) 35*d*.
Jain, S. C., and Chadderton, L. T. (editors). Nonmetallic Crystals, B (10) 263*h*.
Jakas, R. P., and Mullin, J. V. Fiber-aligning apparatus, P (3) 61*e*.
Jaklik, J., Jr. See Silver, R. S.
Jambor, J. Effect of phase composition of hardened binding material pastes on their strength, (2) 30*i*.
James, D. L. See Bodnar, R. E.
James, D. P. Refractory compositions containing C, P (6) 135*f*.
James, D. R., and Carpenter, S. H. Relation between acoustic emission and dislocation kinetics in crystalline solids, (7) 180*f*.
James, G. S. Method of forming metal-coated diamond abrasive wheels, P (3) 53*h*. See Prins, J. F.
James, L. W., Antypas, G. A., Edgecumbe, J., Moon, R. L., and Bell, R. L. Dependence on crystalline face of the band bending in Cs_2O-activated GaAs, (7) 177*a*.
James, O. B. Origin and emplacement of the ultramafic rocks of the Emigrant Gap area, Calif., (8) 206*j*.
James, R. J. See Tauber, E.
James, T. L. Photoelectron spectroscopy, (4) 93*g*.
James, W. J. See Canner, J. P.
Jamison, W. E. See Kjekshus, A.; Selte, K.
Janakirama-Rao, B. V. Heat-absorbing blue Na_2O-CaO-SiO_2 glass, P (7) 162*b*.
Jandeleit, O. Measuring the thickness of superficial layers deposited on glass. Investigation of their composition and structure (I) measurement of thickness of superficial layers; (II) composition and structure of thin layers of metallic oxides, (7) 159*g*.
Janetos, N. S., Marzocchi, A., and Leary, D. E. Method for treating and impregnating glass fiber bundles for reinforcement of elastomeric materials and product, P (3) 59*h*.
Jang, Sung Do, and Condrate, R. A., Sr. Infrared spectra of α-alanine adsorbed on Cu montmorillonite, (11) 281*b*. Infrared spectra of glycine adsorbed on various cation-substituted montmorillonites, (11) 281*b*.
Jangg, G., Kieffer, R., Gugel, E., Kollwentz, W., and Jicinsky, G. Use of the infiltration technique for mfg. cermets, (1) 8*f*.
Janicot, C. Centerless diamond grinding of ceramics, (1) 1*f*.
Janke, G. J. Foundry sand article forming machine with pivotal blow reservoir, P (2) 37*f*.
Janko, A. Rapid determination of gypsum in cement, (5) 104*i*.
Jankovic, O. See Gal, I. J.
Jankowsky, E. J. See Viglione, J.
Janning, J. L. Method of accurately doping a semiconductor material layer, P (3) 65*b*.
Janowski, K. R. See Rossi, R. C.
Janssen, J. F. M. See Van Esdonk, J.
Janssen, P. J. M. Fiber-optical plate coupling a luminescent screen for the display of an image to a photoconductive PbO target of a TV camera tube, P (5) 112*c*.
Jansson, R. A., and Rau, F. J. [Electric] welding glass sheets, P (4) 81*g*.
Janus, A. See Shirn, G. A.
Jarczyk, H. Luminescent screen and method of making, P (5) 113*b*.
Jarrett, Q. T. See Maguire, C. F.
Jarry, R. L. See Jonke, A. A.
Jaschiski, K. See Zirngibl, H.
Jasinski, J. See Hammer, F. W.
Jaskolski, S. V., and Seitz, M. A. ZnO crystal bulk effect oscillator and method of preparing, P (9) 233*d*.
Jaupain, M. See Brichard, E.
Javaux, G. Float glass apparatus with lateral guides, P (3) 58*c*. Refractory block furnace wall, P (7) 162*j*. Tank furnace for the treatment of glass by the float process, P (7) 163*b*.
Javaux, G., Doquire, G., and Bodart, M. Method and apparatus for mfg. flat glass on a bath of molten metal, P (4) 82*j*.
Javed, N. A. Phase relations in the U-C-O system at 1573°K, (1) 15*g*.
Javorsky, B. S., and Gramer, E. A. Apparatus for separating dust from a gas, P (3) 69*c*.
Jaworski, J. M., and Makolagwa, S. Formation of an Mn-Zn ferrite from Fe oxides produced by different methods, (10) 249*c*.
Jayachandra, Y. See Davis, E. K.
Jayaraman, A. See Berglund, C. N.; Wemple, S. H.
Jaymes, M. See Frit, B.
Jean, A. J. See Costello, R. C.
Jeanmaire, M. Study of opalescent Na borosilicate by low-angle X-ray diffraction and electron microscopy, (7) 160*e*.
Jeannot, C. See Perrot, P.
Jeans, C. V. Neoformation of clay minerals in brackish and marine environments, (9) 237*c*.
Jeansonne, G. E. See Canning, M. L.
Jebsen-Marwedel, H. Phenomenological relations between enameling and lacquering, (1) 2*i*.
Jeffers, P. E. Another step forward for the quick set panel, (9) 220*b*. Antique process for profit, (11) 271*a*. Atkinson Brick Company—a picture plant, (9) 220*c*. Backbone for brick walls, (2) 35*d*. Brick panel factory multiplies mason productivity, (9) 220*c*. Brick panel gains in California, (9) 220*d*. Brick panels go hi-rise, (9) 220*d*. Canadian brick panel—ready for production, (9) 220*e*. Clay pipe industry—where it stands and where it is going, (2) 35*f*. Custom aggregate fills refractory needs, (11) 271*g*. Epoxy branching of clay pipe pays off, (9) 220*g*. From processed clay to white brick at Kings Mountain Brick, (2) 35*g*. How lightweight aggregate is made from fly ash, (9) 220*c*. How to start a 300,000 brick per week plant, (9) 220*d*. Kaiser consolidates research in new $25 million lab, (9) 221*g*. Large clay pipe swings into action, (9) 220*d*. Lightweight aggregate in brick—Port Costa makes it work, (9) 220*d*. Machine de-hacking streamlines production at Southern Brick, (2) 35*h*. New plant upgrades ladle brick production, (2) 36*j*. "One-high" kiln in 1972, (9) 220*f*. Panel progress "down under," (1) 6*e*. Quick set—new method for making brick walls, (2) 35*e*. Red River brick and tile—a new $2 million plant built in Manitoba, Canada, (9) 221*b*.
Jehenson, P. See Gualandi, D.
Jeitschko, W., and Sleight, A. W. Re-O system at high pressure—structure and characterization of a new Re oxide, (10) 260*f*.
Jelenic, I. See Bezjak, A.
Jelinek, J. W., Kozlowski, J. J., and Gooding, J. E. Glass conductivity and temp. probe, P (8) 192*j*.
Jelli, A. See Wollast, R.
Jen, D. P., Slocum, R. A., and Valentino, C. R. Programed digital-computer-controlled system for automatic growth of semiconductor crystals, P (3) 67*e*.
Jendrisak, J. E., and McKelvey, H. E. Glass [sheet] cutting apparatus, P (10) 244*c*.
Jenkins, A. See Cornell, R. C.
Jenkins, K. L. Mineral aggregate insulation board, P (3) 61*a*.
Jenkins, R., Mead, C. A., and McCaldin, J. Ohmic contact to ZnS devices, P (2) 41*i*.
Jenkins, R. T., and Wilson, G. H. Schottky-barrier diode process and devices, P (3) 67*h*.
Jenkins, S. E. See Caveney, R. J.
Jenkinson, D. A. See Carr-Brion, K. G.
Jenks, H. R. Method for making prestressed laminated fiber glass structures, P (5) 107*c*.
Jenness, R. C. Trunnion liner assembly for rotary grinding mill or the like, P (1) 20*j*.
Jensen, A. O. See Campbell, A. E., Jr.
Jensen, H. A. See Barnett, A. M.
Jensen, T. H. Method and device for forming glass fibers, P (3) 59*c*.
Jensen, T. H., and Bennett, H. M. Method and apparatus for controlling the diam. of glass fibers, P (7) 162*h*.
Jeryan, R. A., Eryou, N. D., and Glicksman, L. R. Optical method of measuring temp. in hot glass, (3) 56*j*.
Jeschar, R. See Schroeder, U.
Jetter, E. S. See Einthoven, W. G.
Jewell, R. C. Containers for molten glass, P (7) 161*a*.
Jicinsky, G. See Jangg, G.
Jimbo, Genji. Recent trends in the research of powder technology, (6) 141*g*.
Jinbo, Kazumi. See Kawano, Toshio.
Jirkowsky, J., Obst, M., and Simon, L. New method for determining K_2O in feldspars by means of radioisotope ^{40}K, (8) 205*g*.
Jirku, J. See Ryba, J.
Jitsugiri, Yukio. See Noshiro, Makoto.
Joannes, G. See Sluse, G.
Jochens, P. R. See Fahrback, D. O. E.
Joehlin, S. W. See McMaster, R. G.
Johansen, V. Solid solution of Cr in Ca_3SiO_5, (5) 104*a*.
Johanson, V. G. Method of fusion sealing wire grid in tube, P (3) 59*d*.
Johansson, N. G. E. See Picraux, S. T.
Johari, G. P., and Goldstein, M. Viscous liquids and the glass transition (II) secondary relaxations in glasses of rigid molecules, (7) 161*d*.

John, P. T., and Datta, K. K. Industrial applications of particle size, pore size, and surface area measurements, (11) 277*j*.

John, W. New photoelectrically controlled automatic machine for profiling the bore of an [high voltage] insulator, (11) 272*h*.

Johnson, A. A. Fluent material [continuous] weighing system, P (10) 254*j*.

Johnson, A. B., Crabtree, J. O., McVay, T. L., and Bennett, P. E. Beneficiation of high-clay potash ores by flotation, (3) 70*j*.

Johnson, A. D. CRT faceplate having diverse optical means therein, P (9) 218*f*.

Johnson, A. F. Process for mfg. Al_2O_3, P (4) 94*g*.

Johnson, A. L. Process of melting glass, P (1) 5*d*.

Johnson, A. L., and Robertson, L. F. Method of adding colorant to molten glass, P (4) 82*i*.

Johnson, B. C. See Amzallag, E.

Johnson, B. P., and Hensley, E. B. Additive coloration of Sr oxide, (5) 118*e*.

Johnson, C. A. Method of housing semiconductors, P (8) 201*b*.

Johnson, D. L. Discussion of "Effect of additives on sintering of CaF_2," (7) 177*e*. See Venkatu, D. A.

Johnson, D. W., Jr., and Gallagher, P. K. Kinetics of the thermal decomposition of $BeSO_4$, (6) 149*h*.

Johnson, E. W. Covered welding electrode, P (6) 131*a*.

Johnson, H. See Wiederhorn, S. M.

Johnson, J. N. High-temp. seal, P (9) 222*h*.

Johnson, J. R. See Sowman, H. G.

Johnson, J. W. See Whitney, I.

Johnson, J. W., and Cubicciotti, D. Critical temp., orthobaric densities, and vol change on fusion of $NbCl_5$, (8) 208*h*.

Johnson, J. W., Salva, W. J., and Cubicciotti, D. Vapor pressure of molten $NbCl_5$ and the thermodynamics of vaporization to the critical point, (8) 211*f*.

Johnson, J. Y. Patched tank cools it, (11) 271*e*.

Johnson, K. E. See Boxall, L. G.

Johnson, K. L. Method for improving the properties of hydraulic cementitious mixtures, P (5) 104*i*.

Johnson, L. F. See Geusic, J. E.

Johnson, N. E. See Alper, A. M.

Johnson, P. D., and Poran, H. A. Al_2O_3-metal sealed lamp apparatus, P (8) 200*b*.

Johnson, R. Vitreous china refire dunting (I–III), (4) 85*f*.

Johnson, Robert. Slab pots from block forms, (2) 30*d*.

Johnson, R. C. See Crowley, M. S.

Johnson, R. E. See Haisty, R. W.

Johnson, R. E., and Haisty, R. W. Three-terminal active glass memory element, P (2) 43*c*.

Johnson, R. E., and Mehal, E. W. Method of making doped group III-V compound semiconductor material, P (8) 201*d*.

Johnson, R. S., and Imler, V. R. Apparatus for press bending glass sheets, P (11) 270*a*.

Johnson, R. T., Jr., and Kenna, B. T. Radioactive decay and associated electrical changes in fast-neutron-irradiated CdS, (5) 123*c*.

Johnson, S. E. See Sakurai, Katsumi.

Johnston, A. R. Dispersion of electrooptic effects in $BaTiO_3$, (5) 119*h*.

Johnston, H. D., and Fury, R. C. Producing H by contact of steam with Fe oxide promoted with Zn ferrite, P (11) 280*a*.

Johnston, J. D. See Sanders, R. N.

Johnston, N., and Latker, M. Apparatus for the dry separation of granular materials, P (9) 229*g*.

Johnston, P. A., and Gelezunas, V. L. Beta particle detection in thin nuclear detectors, P (3) 68*h*.

Johnston, R. L. See Evans, W. J.

Johnston, W. D. Process for burning a combustible liquid employing a particulate C-coated cellular ceramic nodule, P (8) 198*g*. Process for burning a combustible liquid using cellular ceramic nodules, P (8) 198*g*.

Johnston, W. D., Jr. Characteristics of optically pumped platelet lasers of ZnO, CdS, CdSe, and $CdSe_xSe_{1-x}$ between 300° and 80°K, (5) 111*i*.

Johnstone, J. K. See Stacy, D. W.

Jolley, G. B., and Roberts, D. T., Jr. SiO_2-Al_2O_3-NiO catalyst and its preparation, P (5) 118*a*.

Jolliffe, K. H. See Crouch, A. G.

Joly, J. See Borgne, R.

Joly, R. See Szente, P. A.

Jones, C. K. See Deis, D. W.

Jones, Cecil M., II. Method for producing α-Al_2O_3 crystals from Al_2O_3 containing CaO, P (2) 29*h*.

Jones, Cecil M., II, and Amero, J. J. Method for producing α-Al_2O_3 crystals from Al_2O_3, P (2) 29*g*.

Jones, Clifton P., and Martyny, W. C. Fluorescent panel lamp, P (6) 132*g*.

Jones, Charles T. See Thorp, W.

Jones, David. Float glass method and apparatus for supplying modifying material to the glass surface, P (4) 81*i*. See Lawrenson, J.

Jones, Donald C. Method for producing a unitary composite ophthalmic lens, P (3) 59*g*.

Jones, D. G., and Melford, D. A. Comparison of the high-temp. constitution of sea-water magnesites with that of natural Greek material, (1) 19*j*.

Jones, D. R. H. Determination of the kinetics of ice-brine interfaces from data on temp.-gradient zone migration, (10) 258*f*.

Jones, D. W. See Cockayne, B.

Jones, G. J., and Trivedi, R. K. Lateral growth in solid-solid phase transformations, (6) 149*a*.

Jones, H. K. Process for mfg. articles from slate, P (9) 230*c*.

Jones, Isaac P., McCartan, D. A., Kies, J. R., and Seymour, M. W. Molded fibrous [glass] surfacing unit, P (2) 34*h*.

Jones, I. Wynn. See Miles, L. J.

Jones, I. Wynn, and Miles, L. J. Production of β-Al_2O_3 electrolyte, (9) 237*j*.

Jones, J. H. See Christensen, L. L.

Jones, Joseph R. Automatic system for controlling the temp. of a series of glass molds, P (2) 33*d*.

Jones, J. T. See Bell, H.

Jones, J. T., and Berard, M. F. Ceramics: Industrial Processing and Testing, B (10) 262*c*.

Jones, J. W. S. See Henney, J. W.

Jones, Michael E. B. See Haggis, G. A.

Jones, P., and Hockey, J. A. Infrared studies of rutile surfaces (I); (II) hydroxylation, hydration, and structure of rutile surfaces, (3) 73*j*.

Jones, Peter A. See Barrow, R. F.

Jones, Peter M. See Stern, D. R.

Jones, Ray A. See Heath, L. J.

Jones, R. L. See Davis, C. E.

Jones, Robert R., Jr. Recirculatory system for the granulation of molten slag, P (2) 35*b*.

Jones, Shannon. Sb-activated Ca halophosphate containing B, P (8) 200*b*.

Jones, S. P. Factors that affect the glass-forming process, (8) 190*j*.

Jones, Thomas B., Perry, M. P., and Melcher, J. R. Dielectric siphons, (4) 93*a*.

Jones, Weston C. See Belue, J. C.

Jones, W. J. D. See Lee, G. M. C.

Jones, William P. Oxidation-resistant graphite and C shapes, P (9) 222*c*.

Jones, W. R. See Pedinoff, M. E.

Jonke, A. A., Carls, E. L., Vogel, G. J., Anastasia, L. J., Jarry, R. L., and Haas, M. Reducing pollution from fossil fuel combustion, (1) 19*a*.

Jonker, G. H. Nature of aging in ferroelectric ceramics, (2) 38*j*.

Jonscher, A. K., and Ansari, A. A. Photocurrents in SiO films, (6) 150*h*.

Jonsson, F. L., Trolle, S., and von Platen, B. C. High-pressure apparatus, P (10) 254*d*.

Jonsson, K. O. See Sjoedin, B.

Jonsson, O. See Danielsson, L.

Joo, L. A., and Snodgrass, F. E. Process for mfg. filamentary C products, P (1) 9*g*.

Jope, E. C. Shaft furnaces, P (1) 19*f*.

Jordan, A. S. Liquidus surfaces of ternary systems involving compound semiconductors (I) general thermodynamic analysis; (II) calculation of the liquidus isotherms and component partial pressures in the Ga-As-Zn and Ga-P-Zn systems, (6) 149*e*.

Jordan, C. F., Jr., Fryer, G. E., and Hemmen, E. H. Size analysis of silt and clay by hydrophotometer, (1) 18*i*.

Jordan, L. L. Varactor diode, P (2) 43*b*.

Jorgensen, L. L. See Kerr, J. T.

Jorgensen, P. Automation and rational use of computers in plant and design departments, (11) 276*f*.

Jorgensen, P. J. Transparent ThO_2-base ceramics and method for producing, P (2) 38*c*.

Joshi, M. L. See Fairfield, J. M.; Lin, S. C. H.; Makris, J.

Joshi, M. L., Masters, B. J., Viva, O. R., and Yeh, Tsu-Hsing. Method of reducing carrier lifetime in semiconductor structures, P (3) 66*g*.

Joshi, M. L., Platt, A., and Wajda, E. S. Method for making a semiconductor device having a shallow, flat front diffusion layer, P (6) 138*j*.

Joshi, S. G. See Van den Heuvel, A. P.

Jost, E. M. See Purdes, A. J.

Jost, R. See Frank, B.

Jouhari, A. K., and Dey, D. N. Cooling of granular materials in beds, (7) 175*a*.

Joyce, I. H. See Davis, G. A.

Joyce, I. H., and Worrall, W. E. Adsorption of polyanions by clays and its effect on their physical properties, (1) 9*h*.

Joyce, R. R., and Richards, P. L. Far-ir spectra of Al_2O_3 doped with Ti, V, and Cr, (5) 120*f*.

Joynson, R. E. See Burgess, J. F.

Juchem, F. J. See Lang, F.

Jucker, H. See Fleming, S. J.

Juel, L. H. Method and apparatus for controlling orientation of needlelike C particles in extruded C stock, P (10) 247*j*.

Juels, R. J. See Staffin, R.

Jugovics, L. Hungarian basalt quarrying and its development, (5) 117*h*.

Juillerat, H. Grinding wheel and lubricant arrangement, P (1) 1*h*.

Julietti, R. J. Atomic absorption spectroscopy, (9) 230*j*.

Jumentier, C., and Bonnet, A. Manufacture of plates or shaped sheets having a base of mineral fibers, particularly glass fibers, P (2) 34*a*.

Jumentier, C., Bonnet, A., and Boiteau, C. Aggregates of mineral fibers and thermoplastic materials useful particularly as underlayers for structural sheathings for acoustic insulation, P (8) 192*h*.

Jun, Cho'l K. See Shaffer, P. T. B.

Jung, H. Roman clay lamp in the form of an Egyptian mummy, (11) 266*b*. Sensational finds from a pre-Christian grave displayed in the Luxemburg State Museum, (1) 2*a*.

Jung, L. Furnace [electric] for making fused quartz hollow slugs, P (7) 161*g*, P (10) 244*h*.

Junge, A. E., Thimons, A. J., and Wenkhous, D. R. Strengthened glass article and [ion exchange] process for making, P (2) 35*c*.

Jungquist, G. E. See Ownby, P. D.

Juo, A. S. R., and White, J. L. Orientation of the dipole moments of hydroxyl groups in oxidized and unoxidized biotite, (1) 23*e*.

Juteau, L. Baie Comeau (Quebec) quartzite deposite and its importance as an industrial mineral reserve, (11) 279*e*.

Juzvuk, D. I., and Saparov, V. V. Granular ceramic heat carrier and method of manufacture, P (9) 222*g*.

Kaae, J. L. Structure and mechanical properties of isotropic pyrolytic C deposited below 1600°C, (5) 115*b*.

Kaae, J. L., and Gulden, T. D. Structure and mechanical properties of codeposited pyrolytic C-SiC alloys, (1) 25*a*.

Kabakova, I. I. See Kainarskii, I. S.

Kabanova, O. N. See Bering, B. P.

Kabashima, Shigeharu. See Goto, Tsuneaki.

Kabdebon, I. See Bocsi, I.

Kaboth, D. See Abratis, H.

Kacsalova, L., and Dukai, J. Preparation of transparent polycrystalline Al_2O_3, (7) 165*f*.

Kadota, Kazuya, Saito, S., and Sakaino, T. Stress relaxation of B_2O_3 glass, (6) 132*j*.

Kadotani, Makoto, and Isobe, S. Method of improving the quality of synthetic cryolite, P (2) 46*a*. Process for the production of high-quality synthetic cryolite, P (8) 207*e*.

Kaes, H. H. Changes in the dispersion of glasses by introduction of additional absorption centers, (9) 216*e*. Fluorescence of Dy^{3+}, Eu^{3+}, Sm^{3+}, and UO_2^{2+} in Na borate glasses, (7) 159*b*.

Kaes, K. See Classen, F.

Kafalas, J. A., and Longo, J. M. High-pressure synthesis of (ABX_3)-$(AX)_n$ compounds, (8) 209*f*.

Kafri, A. See Kiro, D.

Kagan, A. S. See Lidorenko, N. S.

Kagawa, Hiroyuki. See Matsuno, Akira.

Kagawa, Ichiro. See Yamazaki, Shumpei.

Kahan, A., Goodrum, J. W., Singh, R. S., and Mitra, S. S. Polarized reflectivity spectra of tetragonal GeO_2, (6) 151*c*.

Kahl, P. See Gross, F.

Kahle, K. See Doering, G.

Kahn, A. H. See Blunt, R. F.; Ensign, T. C.

Kahn, F. J., Pershan, P. S., and Remeika, J. P. Ultraviolet magneto-optical properties of single-crystal orthoferrites, garnets, and other ferric oxide compounds, (6) 152*i*.

Kahn-Harari, A. Structural and chemical properties of some double oxides $MTiO_4$ and MTi_2O_6, (1) 25*i*.

Kahng, Dawon, and Nicollian, E. H. Monolithic semiconductor apparatus adapted for sequential charge transfer, P (7) 169*f*. Semiconductor memory apparatus with multilayer insulator contacting the semiconductor, P (1) 14*a*.

Kai, Juniiro. See Awazu, Kenzo.

Kainarskii, I. S., Degtyareva, E. V., and Kabakova, I. I. Effect of some technical parameters on the properties of corundum refractories, (8) 195*d*.

Kainarskii, I. S., Orlova, I. G., and Natsenko, A. I. Thermal stability of vacuum-dense corundum ceramics, (9) 221*j*.

Kaino, Yoku. Laminated glass stem and method of making, P (5) 107*i*.

Kaiser, H. D., Pakulski, F. J., and Schmeckenbecher, A. F. Fabrication technique for multilayer ceramic modules, (11) 273*f*.

Kaiser, K. See Carlson, K. D.

Kaiser, R. Method of producing a [control] transistor, P (10) 252*a*.

Kaiser, W. See Nitzsche, S.

Kaitna, W. Hollow brick mold box, P (7) 163*e*.

Kali, Keiji. See Akazawa, Hakuichi.

Kajii, Motohiko, Hozumi, S., Nakata, T., and Nakano, S. Acceleration method of concrete hardening with ir lamps, (6) 127*j*. Properties of fresh concrete with artificial lightweight aggregate, (10) 242*b*.

Kajimura, Koji. See Inaba, Ritsuo.

Kajita, Koji, and Masumi, T. Transient photoconductivity and magnetoresistance of ferromagnetic semiconductor EuS, (3) 76*a*.

Kajiura, Hiroshi, and Watanabe, K. Impact flowmeter for powdery and granular materials, P (2) 45*a*.

Kakehi, Toshihiro. See Naito, Kiyoshi.

Kakita, Isamu. See Funabashi, Wataru.

Kakuta, Yoshio. See Yokomichi, Hideo.

Kalabinski, B., and Wasilewski, Z. Method for measuring the values of plastic shrinkage of cement mix, (9) 214*i*.

Kalashnikov, Ya. A. See Timofeeva, N. V.

Kalbfleisch, F. See Krall, F.

Kalff, P. J., and Alkemade, C. Th. J. Determination of the dissociation energy of BaO in a CO/N_2O flame, (5) 119*h*.

Kalinichenko, A. M. See Biryuk, L. I.

Kalishchuk, G. I. See Satarin, V. I.

Kaliski, S. Method of generation of spontaneous elastic spin oscillations in ferromagneto-piezosemiconductor circuits, P (9) 226*i*.

Kalita, Z. A. See Bukhovets, V. G.

Kalka, J. See Fitzer, E.
Kalnajs, J. See Belruss, V.
Kalousek, G. L., and Kopanda, J. E. Approach to fundamentals of concrete strength, (4) 78*d*.
Kal'yanova, V. N. See Potryasov, V. N.
Kamada, Eiji. See Koh, Yoshiro.
Kamada, Osamu, Takizawa, T., and Sakurai, T. High-temp. X-ray diffractometer using a solar furnace, (3) 69*j*.
Kamat, G. R., and Gupta, C. K. Open aluminothermic reduction of Nb_2O_5 and purification of the reduced metal, (6) 143*f*.
Kamatani, Yukinori. See Asano, Shunkichi.
Kamath, G. S. Method of making SiC junction diodes, P (8) 201*e*. Process for fabricating SiC junction diodes by liquid phase epitaxial growth, P (6) 139*f*.
Kamdar, M. H., and Mueller, J. I. Diffraction from 3 interatomic spacings observed in α-Al_2O_3 ceramics, (11) 281*c*.
Kamegaya, Takeo, Imahori, Y., Ohta, A., Kanoh, T., and Ohara, A. Metal vapor discharge lamp, P (9) 219*h*.
Kamei, Ichizo. See Arita, Shigeru.
Kamei, Shuichi. See Matsuda, Osaku.
Kamei, Taketo, and Miyazaki, K. Glow discharge starter tube with hydrocarbon-rare gas fill, P (10) 244*d*.
Kamel, M. R. See El-Rafei, E. A.
Kamenetskii, A. B., Gul'ko, N. V., and Gladkaya, N. V. Electric-insulating material for thermoelectrodes operating in vacuum, (8) 199*e*.
Kamenetskii, S. P. See Fain, I. A.
Kamentsky, L. A., and Klinger, I. Photo-optical particle analysis method and apparatus, P (8) 206*a*.
Kameshima, Noriaki. See Shikami, Gunji.
Kamibayashi, Tetsusaburo. See Oshima, Shintaro.
Kamigaito, Osami. See Oyama, Yoichi.
Kamigaki, Kazuo. See Inagawa, Konosuke.
Kamin, G. J. See Chiola, V.
Kaminishi, Tokishi. See Funabashi, Wataru.
Kamins, T. I. See Oberlin, D. W.
Kamiya, Iwao. See Makino, Yoshimi.
Kamiya, Tadao. See Henmi, Yoshinori; Yoshikawa, Takayuki.
Kamiyama, Susumu, and Suzuki, H. Property of cement paste and concrete using expansive agent, (10) 242*c*.
Kamiyama, Takamitsu, and Maki, M. Method for fabricating a semiconductor integrated circuit, P (6) 138*d*.
Kamiyama, Yukio. See Murata, Jiro.
Kammer, E. W. Nondestructive measuring system, P (6) 133*c*.
Kammlott, G. W. Observation of ferromagnetic domains with the SEM, (7) 179*g*.
Kamo, Takahiro. See Hasegawa, Nobuo.
Kamoshida, Mototaka. Method of fabricating a semiconductor, P (9) 226*g*. See Mitchell, I. V.
Kamoshida, Mototaka, and Nakanuma, S. Complementary enhancement and depletion MOSFETs with common gate and channel region, the depletion MOSFET also being a JFET, P (5) 112*h*.
Kamp, C. A. Tile, P (9) 223*e*.
Kampf, L. Brick treatment, P (10) 246*b*.
Kamphues, H., and Rosengarten, H. J. Method and means for stacking molded articles in groups, P (9) 221*c*.
Kampmann, F. W. See Schneider-Arnoldi, A.
Kan, Hung-Kuen A. See Champetier, R. J.
Kanai, Eizo. Method and apparatus for mfg. flat glass, P (10) 244*i*.
Kaname, Yuichi. See Ise, Yukihiko.
Kaname, Yuichi, and Wada, K. Piezoelectric ceramic ring resonator, P (2) 42*a*.
Kanatani, Keiichi. See Yazaki, Takehito.
Kanazawa, Takafumi, Kawazoe, H., and Ikeda, M. Some properties of Ca silicophosphate and Mg silicophosphate glasses, (3) 57*h*.
Kanazawa, Takafumi, Kawazoe, H., and Yamamoto, I. Crystals formed by devitrification of glasses in the system CaO-MgO-P_2O_5, (5) 105*h*.
Kanbayashi, Akio, Miyadai, T., Kondo, H., and Miyahara, S. Magnetic properties of the diluted ferromagnetic system xSrRuO$_3$·(1-x)LaRhO$_3$, (3) 74*f*.
Kanda, Mamoru, and Suzuki, O. Abrasion resistance of artificial lightweight aggregate concrete, (6) 127*i*.
Kandler, J. See Schneider-Arnoldi, A.
Kane, E. O. Strain effects on optical critical-point structure in diamond-type crystals, (5) 124*g*.
Kane, R. M. See Werner, L. C.
Kaneko, Isao. See Nakao, Tatsuhide.
Kaneko, Kunio, and Watanabe, N. Method for the preparation of groups III-V single-crystal semiconductors, P (2) 41*i*.
Kaneko, Masahiko. See Tomii, Kaoru.
Kaneko, Tadataka. See Naomoto, Susumu.
Kanemaru, Toyonosuke. See Hiratsuka, Toshio.
Kaneoya, Ryoichi, and Nagata, M. Method of mfg. thin-film resistor elements, P (1) 13*c*.
Kanev, S. See Konstantinova, E.
Kang, K. D. Method of forming an Si_3N_4 diffusion mask, P (2) 41*e*.
Kanij, J. B. W., and Noothout, A. J. Method for the preparation of spherical particles, P (9) 229*a*.
Kano, Gota, Yokozawa, M., Kawasaki, T., Fujiwara, S., and Hasegawa, H. Method for mfg. pressure-sensitive semiconductor device, P (4) 89*e*.
Kano, Ryosuke. See Nameda, Naoyoshi.
Kano, Tsuyoshi, Otomo, Y., and Yamamoto, H. Phosphors, P (7) 169*j*.
Kanoh, Tadao. See Kamegaya, Takeo.
Kanomata, Ichiro. See Yamazaki, Hisashi.
Kao, K. C. See Card, A. C.
Kao, R., Perrone, N., and Capps, W. Large-deflection solution of the coaxial-ring–circular-glass-plate flexure problem, (1) 3*f*.
Kapany, N. S. See Sawatari, T.
Kaplan, R. B. See Glaski, F. A.
Kaplan, S. H. Color picture tube screen with phosphor dots overlapping portions of a partial light-transmissive black-surround material, P (2) 33*h*. Mfg. a color picture tube, P (10) 244*h*. Process of screening a shadow mask color tube, P (9) 227*a*. Screening a black-surround color CRT, P (10) 252*f*.
Kappelmeyer, R. See Widmann, D.
Kappelmeyer, R., Kellerbauer, M. H., and Danassy, K. Crystal seed following a hypercycloid path in melt, P (2) 39*i*.
Kappmeyer, K. K., and Hubble, D. H. Steel-plant refractories in the 70's, (8) 196*b*.
Kapral, G. A. Molten glass shears, P (1) 5*e*.
Kar, B. C. Preparation of fluoboric acid from low-grade fluorspar and its purification by ion exchange, (7) 175*e*.
Karapetyan, G. O. See Galimov, D. G.
Karasev, A. P., Krasnikov, V. I., and Seifullin, R. S. Electrochemical activity of sulfides, (5) 120*h*.
Kardunskii, I. I. See Gutop, V. G.
Karkhanavala, M. D. See Momin, A. C.
Karklit, A. K. See Likhoradov, A. P.
Karklit, A. K., Gol'dberg, I. A., and Bernshtein, R. S. Mechanization and automation of the refractories industry, (8) 195*j*.
Karklit, A. K., Krasotkina, N. I., Pil'dish, V. G., and Malinovskii, S. V. Burner lining for high-pressure steam boiler, (8) 194*g*.
Karnaushenko, G. A. See Gutop, V. G.
Karpenko, N. V. See Sevast'yanova, T. N.
Karpilovskaya, M. N. See Guzman, I. Ya.
Karpinos, D. M., Grosheva, V. M., Gumenyuk, E. L., and Zil'berberg, V. G. Improving the thermal-shock and impact resistance of ZrO_2 ceramics, (8) 195*h*.
Karpinos, D. M., Zil'berberg, V. G., Epik, A. P., Batalin, G. I., and Beloborodova, E. A. Diffusion and plasma coatings for increasing the durability of electrodes in molten Al, (10) 246*i*.
Karplus, M. See Morokuma, K.
Karr, G. H. See Smolen, L. E.
Kasai, Junichi. See Tsuyuki, Naomitsu.
Kasai, Masami. See Yamamura, Katsumi.
Kasai, Noboru, See Uchikawa, Hiroshi.
Kasai, Yoshio. Considerations of setting and hardening of concrete, (6) 128*d*.
Kasai, Yoshio, Yokoyama, K., and Shibata, O. Initial frost damage of green concrete used in various kinds of lightweight aggregates, (6) 129*j*.
Kasakawa, Tatsuo. See Teramoto, Hideo.
Kasami, Akinobu. See Naito, Makoto.
Kasano, Hiroyuki, and Kawamura, M. Solid state electronic device utilizing difference in effective mass, P (10) 253*c*.
Kashyap, S. C. See Sharma, S. D.
Kasori, Mitsuo. See Ooka, Kazuo.
Kasperkovitz, W. G. Semiconductor device having a bistable circuit element, P (3) 67*a*. Semiconductor device for producing or amplifying electric oscillations and circuit arrangement comprising such a device, P (9) 227*f*.
Kassner, B. See Henning, O.
Kastner, J., and Oltman, B. G. Neutron dosimeter including a step wedge formed of an α-attenuating material, P (1) 16*c*.
Kasuga, Masanobu. See Ogawa, Hiroshi.
Kas'yanova, G. N. See Sychev, M. M.
Katakura, Keiji. See Imamura, Hitoshi.
Kataoka, Kohji. See Yumoto, Tetsuo.
Kataoka, S. See Tomizawa, K.
Katase, Denji, and Okuma, T. Comparative study of 2 systems for charging press components, 1 by vol and 1 by wt, (7) 172*a*.
Katayama, Yoshifumi. See Kotera, Nobuo.
Katnack, F. L. Semiconductor device employing 2-metal contact and polycrystalline isolation means, P (9) 227*e*.
Kato, Akihisa, and Hirose, K. Factors in cement grinding process affecting strength of cement, (4) 78*i*.
Kato, Akio. See Nagano, Masamitsu.
Kato, Akio, and Anju, Y. Expansion of Ag_2O lattice by annealing, (2) 47*g*.
Kato, Akio, Nishihashi, R., Nagano, M., and Mochida, I. Relative activity of O ions in molten Na phosphate as determined from the solubility of SO_3, (5) 123*c*.
Kato, Etsuzo. See Choshi, Isamu; Takashima, Hiroo.
Kato, Hajime. See Ono, Yoshio.
Kato, Haruo. Discussion of "Creep behavior of Ni-Zn ferrites," (6) 146*d*.
Kato, Hiroshi. See Sato, Kogo.
Kato, Minoru. See Kijima, Goro.
Kato, Nobuyuki. See Saito, Hajime.
Kato, Shiro. See Fuwa, Yoshikazu.
Kato, Shohichi. See Nishi, Masato.
Kato, Shuzo, and Iga, T. Grain growth during vacuum sintering of Al_2O_3 obtained by thermal decomposition of Al sulfate, (3) 73*b*.
Kato, Sousuke. See Ieda, Masayuki.
Kato, Takahiro. See Maeda, Minoru.
Kato, Tsutomu. See Tamura, Takaaki.
Katona, I. Composition and style problems of art ceramics in Hungary during the end of the 19th century, (5) 101*j*.
Kator, W. G. See Burroughs, J. E.
Kats, M. E., and Kvyatkovskaya, K. K. Low-temp. fluxes for cast ceramic tile production, (8) 197*f*.
Katsuki, Kazuo. Theory of glass transition of Na disilicate glass—calculation of thermal expansion, (3) 57*b*.
Katsuki, Kazuo, and Aoki, K. Theory of glass transition of Na disilicate glass—electronic state between 2 nonbridging oxygens, (3) 57*b*.
Katsumata, Takuma, and Kishigami, H. Method and device for inspecting bottle by radiant energy, P (1) 4*i*.
Katsura, Akihiko. See Nagao, Kazuyoshi.
Katsuraki, Hisao. See Egashira, Kazumichi.
Katsuta, Morio, and Ouchiyama, T. Observation of *pn* junction by SEM, (11) 274*b*.
Katsuta, Yukio, Akahane, R., and Yahagi, K. Electrical properties of rutile thin film, (3) 62*f*.
Katto, Hisao, Kobayashi, K., Koga, Y., and Koyama, M. Method of mfg. a metallic oxide film on a substrate, P (9) 226*c*.
Katto, Shigeru. See Horibe, Toshiyasu.
Katz, H. See Hofmann, H.
Katz, H. M. See Flack, H. P.
Katz, I. See Kristianpoller, N.
Kauffman, J. H., and Donat, R. J. Modular plow system for [pan-type] mixers and the like, P (4) 92*f*.
Kaufmann, M., and Shultz, B. R. Method of making and using diced single-crystal impurity source, P (9) 226*c*.
Kaufmann, P., and Liepert, R. Flash lamp and apparatus for making, P (4) 81*i*.
Kaufmann, R. A. Glass goes on offense in 70's, (10) 243*e*.
Kaul, B. K. Specific gravity of clay minerals, (11) 282*d*.
Kauppila, J. E. Passivated wire bonded semiconductor device, P (4) 89*i*.
Kaveggia, F. S. Chemical lapping of Y Al, P (4) 87*j*.
Kawabata, Kunio, and Noda, M. Influence of increase of vol of air blast through Sturtevant separator on separating efficiency, (4) 78*j*.
Kawabuchi, Katsuhiro, and Suzuki, T. Variations in orientation of etch pits on (100) and (111) surfaces of Ag, (7) 182*a*.
Kawachi, Masao. See Abe, Masanori.
Kawachi, Masaru. See Naito, Makoto.
Kawachi, Youji. See Ono, Minoru.
Kawada, Takehiko. High-voltage source devices utilizing piezoelectric elements, P (4) 88*f*.
Kawagoe, Hiroto, and Kubo, M. Method of mfg. a field-effect semiconductor device, P (3) 65*j*.
Kawaguchi, Yukiyoshi. Apparatus for continuous measuring of the moisture content in a high-temp. chamber at atmospheric pressure, P (1) 18*c*.
Kawahara, Sei. See Kito, Masao.
Kawaji, Akira. See Yonezu, Hiroo.
Kawakami, Akira, and Nagahara, M. Use of ceramic fiber in annealing furnace, (2) 37*b*.
Kawakami, Hidehiko. See Uno, Yoshihiro.
Kawakatsu, Fumimaro, Ibochi, T., and Okabe, T. Laminated ceramic structure for containing a semiconductor element, P (3) 65*i*.
Kawakita, Hitoshi. See Kubota, Takehiro.
Kawakubo, Tatsuyuki. See Goto, Tsuneaki.
Kawamata, Tadashi, Hirota, E., Mihara, T., and Terada, Y. Te-Fe-modified CrO_2, P (5) 114*b*.
Kawamoto, Yoji, and Tsuchihashi, S. Properties and structure of sulfide glasses (V) properties and structure of glasses in the system As_2S_3-Sb_2S_3-S, (6) 132*e*. Thermal expansion of As-S glasses, (3) 57*b*.
Kawamura, Masao. See Kasano, Hiroyuki.
Kawamura, Mitsunori. See Hasaba, Shigemasa.
Kawamura, Nobuo. See Shinoda, Daizaburo.
Kawamura, Shigeo, and Mizukami, K. Influence of quartz and feldspar on the burning process of cement clinker, (4) 79*a*.
Kawamura, Susumu, and Yamaguchi, F. Glass solder, P (6) 132*i*.
Kawamura, Takao. See Takemoto, Takeo.
Kawanishi, Nobuo, Kuratani, S., and Moriwaki, S. Origin of black stones included in dark green glass, (3) 56*j*.
Kawano, Toshio, Ishii, S., and Jinbo, K. Investigation of initial efflorescence-preventing agents in portland cement mortar, (9) 214*f*.
Kawano, Toshio, and Ishimura, S. Ready-mixed concrete based on white portland cement, (10) 242*c*.
Kawasaki, B. S., Shewchun, J., and Garside, B. K. Relation between wavelength tuning and lasing threshold in electron-beam pumped GaAs lasers, (7) 167*f*.
Kawasaki, Junko. See Shimada, Kinji.
Kawasaki, Tatsuo. See Kano, Gota.
Kawashima, Kinichi. Apparatus for producing bundles of optical fiber, P (1) 3*g*.
Kawashima, M. See Tomizawa, K.
Kawasumi, Kenichi. See Yamane, Mikiya.
Kawazoe, Hiroshi. See Kanazawa, Takafumi.
Kawazu, Satoru. MIS-type variable capacitance semiconductor device, P (2) 41*d*.
Kay, D. A. R. See Dondelinger, J. D.; Sommerville, I. D.

Kay, D. B. High effective absorption coeff. solid state laser rods, P (11) 274*i*.

Kay, E., and Sawatzky, E. Epitaxial garnet films, P (1) 12*a*.

Kay, J., and Blumenthal, E. Manufacture of Na_2CO_3, P (9) 232*h*.

Kay, R. Whole-crystal micron diamond improves productivity, finish, (2) 29*j*.

Kay, S. E., and Pickard, J. Manufacture of curved glass, P (11) 270*c*.

Kayser, W. W. O. G. Magnetic film array, P (2) 40*i*.

Kazan, B., and Pennebaker, W. B. Display devices based on low-voltage excitation of ZnO in a gas plasma, (4) 86*e*.

Kazanbekov, R. G. See Belyaev, I. N.

Kazanskii, V. L. See Nekrasov, N. N.

Kazimir, J. Influence of gypsum variety on strength of plaster, (3) 53*j*.

Kaznoff, A. I. See Hill, H. W.

Kazuk, W. F. See Gallaro, A. V.

Kazumata, Yukio. See Miyako, Yoshihito.

Kearby, K. K. Metal halide containing zeolites and method for their preparation, P (6) 144*a*.

Kearley, R. A. Separation of K phosphate and Al_2O_3, P (6) 144*f*.

Keast, R. R. See Corliss, D. S.

Keck, D. Apparatus for the removal of clay web wastes in a clay-shaping machine, P (6) 134*c*. Apparatus for setting green bricks in gapped rows, P (3) 69*d*. Equipment for forming a stack of bricks or other articles and for interleaving successive layers with thermoplastic film material, P (9) 221*a*. See Shaefer, K.

Keddeinis, H., Lenz, A., Bleh, O., and Termin, E. SiO_2 gel-containing MgO insulating composition, P (11) 272*f*.

Kedzior, A., Horoszko, J., Olszowski, T., Romaniec, E., and Zaremba, S. Method of continuous and controlled preparation of liquid self-hardening molding sand and the installation for its application, P (11) 272*e*.

Keefe, J. E., Jr. Laser structure with a segmented laser rod, P (2) 34*j*.

Keeling, R. A., and Priest, J. G. Method of applying transfers to fiber glass articles, P (8) 193*b*.

Keenan, W. A. See Gardner, E. E.

Keesom, P. H. See Sandin, T. R.

Kegel, K. See Reichelt, B.

Kegelman, T. D. Photosensitive device comprising photoconductive and photovoltaic layers, P (9) 227*e*.

Kehoe, T. J. Instrumentation—the key to environmental control, (9) 231*e*.

Keib, H. Method and apparatus for producing filaments from vitreous material, P (3) 59*a*.

Keig, G. A., Smith, James C., and Watts, J. M. J. Asteriated synthetic corundum gemstones and method and apparatus for their production, P (7) 175*j*.

Keiser, J. E., and Krieger, E. Method of producing porcelain enamel coatings, P (6) 131*d*.

Keiser, W. E. See Alpert, N. L.

Keister, F. Z., and Smolker, G. S. Self-destruct Al-WO_3 films, P (10) 252*f*.

Keith, H. D., Padden, F. J., Jr., and Vadimsky, R. G. Intercrystalline links—critical evaluation, (7) 178*j*.

Keith, T. E. See Coleman, R. G.

Keith, W. T. See Flor, L. L.

Keler, E. K. See Godina, N. A.

Kell, R. C. See Bates, C. H.

Kelland, D. R. See Abeshouse, D. J.

Kellar, A. A. Electrode joint cement, P (8) 196*h*.

Keller, D. L. See Chubb, W.; Hilbert, R. F.

Keller, J. P., and Graf, S. A. Ac line operation of monolithic circuit, P (6) 137*e*.

Keller, R. H. Glass gob shaping and delivering means, P (10) 244*a*. Mold spray apparatus, P (3) 59*i*.

Keller, W. Adjustable heating device for crucible-free zone melting a crystalline rod, P (3) 64*b*. Apparatus for crucible-free zone melting of crystalline rods, P (8) 200*b*. Apparatus for producing a monocrystalline rod, particularly of semiconductor material, P (1) 12*c*. Apparatus for producing rod-shaped members of crystalline material, P (3) 64*f*. Device for crucible-free floating-zone melting a crystalline rod, P (9) 225*b*. Device for crucible-free floating-zone melting a crystalline rod, especially a semiconductor rod, P (1) 12*g*. Device for heater movement in crucible-free zone melting a crystalline rod, P (4) 92*b*. Method for crucible-free floating-zone melting a crystalline rod, especially of semicrystalline material, P (8) 201*e*. Method and device for crucible-free floating-zone melting using a variable-diam. heating coil, P (1) 13*b*. Method and device for crucible-free zone-melting a crystalline rod, P (6) 138*a*. Method for producing a monocrystalline rod by crucible-free floating-zone melting, P (3) 66*d*. See Emeis, R.; Longo, H. E.

Keller, W., and Berger, G. Method of crucible-free zone melting crystalline rods, especially of semiconductor material, P (8) 201*j*.

Kellerbauer, M. H. See Kappelmeyer, R.

Kelley, E. A. See Kelley, J. C.

Kelley, J. C. See Parish, W. R.

Kelley, J. C., and Kelley, E. A. Introduction to the Ceramics of the Chalchihuites Culture of Zacatecas and Durango, Mexico (1) Decorated Wares, B (1) 27*g*.

Kelley, J. K. See Mashikian, M. S.

Kelly, A. C., Barsotti, L. R., and Emerson, R. B. Process for producing fine-particle-size Al_2O_3 hydrates [η structure], P (3) 71*i*.

Kelly, D. H., and Bruen, C. P. Process for producing Al_2O_3 of low residual nitrate content from basic Al nitrates, P (3) 71*i*.

Kelsey, R. H. Continuous production of Al_2O_3 whiskers, P (8) 196*h*.

Kemeny, G., Gaboardi, M., Santini, A., Testori, M., Reinhardt, P. D., Simoleit, H., and Walter, L. Method for the production of Ba hydroxide, P (7) 175*d*.

Kemeny, I. Capacity increase in ceramic body preparation by the Beacedis machine, (11) 276*g*.

Kemi, Torao, and Hiraga, T. Initial properties of concrete using superhigh early-strength portland cement, (9) 214*d*. Quality of artificial lightweight aggregate concrete in situ, (6) 130*b*.

Kemlage, B. M. See Badami, A. V.

Kemmerer, R. P., Jr. See Shapiro, W. A.

Kemp, J. C. See Glaze, J. A.

Kemp, J. C., Cheng, Jack C., Izen, E. H., and Modine, F. A. Magnetooptical structure of the MgO *F* band, (5) 121*e*.

Kemp, J. L., and Moulson, A. J. Effect of Fe additions on the electrical properties of Al_2O_3 ceramics, (7) 166*e*.

Kemper, D. M. See Scott, K. E., Jr.

Kempis, E. B. See Pope, N. C.

Kenawy, M. E. See Arafa, A. A.

Kendall, D. N. See Dixon, W. P.

Kendall, L. F., Jr., and Bredt, J. H. Diffusion barriers for semiconductive thermoelectric generator elements, P (7) 168*d*. *n*-Type PbTe, P (7) 169*h*.

Kenmoku, Yoshihiro. See Sugano, Izuru.

Kenna, B. T. See Johnson, R. T., Jr.

Kennedy, A. B., Jr. Handling apparatus for particulate dry product, P (8) 203*i*.

Kennedy, D. P., Perri, J. A., and Riseman, J. Junction transistor using a thin layer of semiconductor material on a diffusion-proof substrate, P (3) 65*h*.

Kennedy, G. C. Method for mfg. diamonds in an H-free environment, P (10) 241*f*.

Kennedy, R. W. Passivated semiconductor device with protective peripheral junction portion, P (4) 89*h*.

Kennedy, T. N., and Mackenzie, J. D. Suppression of the semiconductor-metal transition in V oxides, (3) 57*j*.

Kennison, M. C. Treatment of small semiconductor wafers with etchant, P (2) 43*a*.

Kenny, D. M. See Garnache, R. R.

Kent, A. P. See Marks, A. M.

Kent, J. A. Active circuit trimming with abrasives, (3) 62*d*.

Kent, R. See Howse, T. K. G.

Kent, R., and Rawson, H. Experimental and theoretical investigation of glass pressing, (3) 56*a*.

Kenworthy, H. See Barnard, P. G.

Kepper, H. Method of thermally bloating clay pellets using a fluidized bed, P (3) 60*c*.

Kerbe, F. G. See Budnikov, P. P.

Kerber, E. W. See Collins, N. E.

Kerkmeester, H. B. See Baas, W.

Kern, W. Semiconductor surface contamination investigated by radioactive tracer techniques (I, II), (11) 274*a*.

Kern, W., and Heim, R. C. Chemical vapor deposition of silicate glasses for use with Si devices (I) deposition techniques; (II) film properties, (9) 216*i*.

Kerr, G. T. Zeolite esters, P (11) 280*c*.

Kerr, J. A. See Robinson, D. P.

Kerr, J. M., and Larson, G. C. Nuclear fuel rod, P (3) 68*f*.

Kerr, J. T. Current-voltage characteristics of chalcogenide glass films, (6) 131*h*.

Kerr, J. T., and Jorgensen, L. L. Oxidic semiconducting glass continuous dynode electron multipliers, (6) 132*c*.

Kerr, R. E. Spring flip-top mount support for Hg vapor discharge lamp, P (3) 59*g*.

Kershner, C. J. See Lonadier, F. D.

Kerstner, K. H. Experiences with glazes for dry-press glazing process, (8) 194*e*.

Kertesz, P. See Galos, M.

Kerwin, R. E. See Goldrick, M. R.

Kesarev, V. V. See Balyaev, I. N.

Kesavan, R., and Singh, M. N. Deposition of P-doped SiO_2 films, (11) 273*g*.

Keshelava, B. F. See Andreeva, E. P.

Keskar, K. S., Yamashita, T., and Onodera, Y. Superconducting transition temps. of rf sputtered NbN films, (3) 63*j*.

Keski, J. R. Bi_2O_3 ceramics, (7) 171*a*.

Kessler, W. Microwave plasma burner as a light source for emission spectrum analysis—fundamentals and applications, (8) 205*f*.

Kesterke, D. G. Electrowinning of O from silicate rocks, (7) 175*a*.

Kestigian, M. See Holloway, W. W., Jr.

Kestner, O. E., Frolov, A. S., Vinokurov, V. I., Trofimov, M. G., Kostechko, R. F., Pyanov, V. N., Golovkin, Yu. I., Abakumov, V. B., Shagurin, A. A., Lotarev, V. A., Yakovlev, A. A., Popov, V. S., and Nagorskaya, Z. S. Ni-base metalloceramic sealing material, P (11) 272*c*.

Ketcham, S. J. See Viglione, J.

Ketchum, W. C., Jr. Pottery and Porcelain Collector's Handbook—a Guide to Early American Ceramics from Maine to Calif., B (7) 184*f*.

Key, P. L. See DiMarcello, F. V.

Keyes, R. W., and Weiser, K. Method of fabricating solid-state devices, P (5) 113*g*.

Keys, D. L. See Broderick, J. P.

Keys, L. K. See Francis, F. J.

Keyser, D. R. Optimized thermocouple calibration, (1) 19*f*.

Khalafalla, S. E. See Haas, L. A.; Shah, I. D.

Khalafalla, S. E., and Haas, L. A. Carbothermal reduction of siliceous minerals in vacuum, (8) 206*i*. Kinetics of carbothermal reduction of quartz under vacuum, (9) 236*c*.

Khalil, A. A., and Hussein, A. T. Wt loss as a method of the assessment of gypsum plasters, (11) 266*j*.

Khalil, A. A., Hussein, A. T., and Gad, G. M. Thermochemistry of gypsum, (5) 104*e*.

Khalizeva, O. N. See Pukhlik, O. I.

Khan, A. A., and Baur, W. H. Eight-membered cyclosilicate rings in muirite, (1) 21*g*.

Khan, B. Kh., Bykov, I. I., Burovskii, N. I., and Malyavin, A. G. Effect of structure and temp. on the mechanical and elastic properties of cast stone, (8) 195*e*.

Khan, G. A. Method of screening a color CRT, P (4) 89*a*.

Khandros, E. L. See Biryuk, L. I.

Khanna, S. L. See Srivastava, K. K.

Khanov, V. M. See Morozov, V. I.

Kharakhorin, F. F., and Boyarintsev, P. K. Semiconductor properties of Mg_2Pb, (9) 238*h*.

Kharbash, A. Kh. Plugs and nozzles for intermediate continuous steel casting ladles with automatic jet regulation, (8) 195*c*.

Kharinskaya, M. A., and Obraztsov, A. I. Ferrite and method of mfg., P (4) 87*h*.

Kharitonov, F. Ya. See Budnikov, P. P.; Surkov, M. E.

Kharitonov, V. I., and Shamrai, F. I. Ternary system Mo-W-B, (10) 261*c*.

Kharitonov, Yu. Ya., Molodkin, A. K., and Balakaeva, T. A. Study of some Th carbonate complexes by ir spectroscopy, (8) 211*a*.

Khashkovskaya, A. P. See Chistyakova, A. A.

Khatchoian, A. V. See Polak, L. S.

Khaustova, Z. N. See Afinogenov, Yu. P.

Khigerovich, M. I. See Budnikov, P. P.

Khitarov, N. I. See Pugin, V. A.

Khlebnikov, A. L. See Brumberg, R. M.

Khoroshavin, L. B. See Budnikov, P. P.

Khoroshavin, L. B., D'yachkov, P. N., Purgin, A. K., Pisarenko, N. K., Kosolapova, E. P., Pivnik, L. Ya., Bogatikova, V. K., and Latysheva, A. K. Properties of aluminosilicate concretes in various grades of orthophosphoric acid, (8) 187*j*.

Khoroshavin, L. B., Ust'yantsev, V. M., Taksis, G. A., Bogatikova, V. K., and Kosolapova, E. P. Phase transformations of Mg phosphates during heating, (8) 210*c*.

Khosla, R. P. Electrical properties of semiconducting CdF_2:Y, (5) 120*h*.

Khotimchenko, V. S. See Toropov, N. A.

Khvorostenko, A. S. See Dembovskii, S. A.

Kiba, W. M. Transparent mask and method for making, P (3) 59*i*.

Kidde, G. E. Process for the production of $(NH_4)_3AlF_6$, P (4) 94*j*.

Kido, Yasunori. See Shiraiwa, Toshio.

Kieburtz, R. B. Multiaperture ferrite residue arithmetic unit, P (2) 41*f*.

Kieffer, R. See Jangg, G.

Kieffer, R., Gugel, E., Leimer, G., and Ettmayer, P. System B-C, (5) 124*b*. System B-C-Si, (11) 283*b*.

Kiehl, J. P., and Valentin, G. High-density refractory shapes and method for production, P (7) 164*e*.

Kiel, R. H. High temp. curing thermosetting decorative composition, P (9) 219*e*.

Kienel, G. Method [vacuum] of coating a transparent synthetic polymer substrate with B_2O_3-SiO_2 glass, P (6) 133*b*.

Kienow, S. Calculation from chemical analyses of the accretion or removal of brick or slag components, (6) 134*e*.

Kies, J. R. See Jones, Isaac P.

Kiess, R. J. See Scott, K. E., Jr.

Kiewit, D. A. PbS ion implantation mask, P (1) 12*h*.

Kijima, Goro, Yamazaki, M., Ueda, M., Kato, M., and Endo, Y. Emergency construction in the hot season, using Al_2O_3 cement concrete, (6) 128*g*.

Kiiima, Katsumi. See Ohno, Masao.

Kikuchi, Sadao. See Maruyama, Mitsuhiro.

Kikuchi, Sakae. Semiconductor device and method of mfg., P (2) 42*j*.

Kikukawa, Hirozi. See Murata, Jiro.

Kikumoto, Yukio, and Miwa, H. Studies on fundamental properties of crushed stone concrete, (6) 130*f*.

Kilby, J. St. C. Semiconductor device, P (5) 114*c*.

Kilgren, A. W. Method of heating O-containing gases for the production of TiO_2 pigment, P (4) 94*i*.

Kilin, V. S., Evstyukhin, A. I., and Dergunova, V. S. Properties and microstructure of C-TiC alloys obtained by precipitation from the gaseous phase, (10) 260*c*.

Kim, C. K., Voris, S. S., and French, W. G. Simultaneous determination of Co, Cu, and Mn in high-purity optical glass by thermal neutron activation, (3) 57*g*.

Kim, Man Jin. Complementary MISFET devices and method of fabrication, P (6) 137*i*.

Kim, Y. M. See Rexford, D. G.

Kim, Y. M., and Bray, P. J. ESR studies of γ-irradiated alkali titanate glasses, (7) 159*e*.
Kimball, J. C. See Falicov, L. M.
Kimball, L. W. See Schreurs, W. P.
Kimball, S. F. W halogen lamp having improved seal of Mo aluminide, P (9) 220*a*. See Palmer, L. H., III.
Kimball, S. F., and Bonazoli, R. P. Explosion-proof quartz-halogen lamp, P (1) 4*a*.
Kimmel, S. See Gebhardt, F.
Kimura, Akihiro. Schottky barrier semiconductor device, P (4) 90*j*. Semiconductor device and method of making, P (5) 114*d*.
Kimura, Isao. Rheology of cement plaster, (9) 215*e*.
Kimura, Isao, and Habata, Hidetsugu. Method of producing C fibers, P (5) 109*j*.
Kimura, Isao, and Setaka, R. Flow measuring devices of cement mortars—approach to the problem of evaluation of plasticity of cement plasters, (4) 78*i*.
Kimura, Katuhiro. See Fukushima, Masakazu.
Kimura, Morihiro, Nagao, I., and Into, M. Refractories for the Mitsubishi-Metacon ladle valve system, (2) 36*f*.
Kimura, Shigeo, and Horikawa, K. Durability of lightweight aggregate concrete, (6) 128*a*.
Kimura, Shigeo, and Nozaki, S. Superdry mix concrete—strength, shrinkage, and creep, (6) 130*f*.
Kimura, Shigeyuki, and Muan, A. Phase relations in the system CaO-Fe oxide-TiO_2 in air, (1) 23*i*. Phase relations in the system CaO-Fe oxide-Ti oxide under strongly reducing conditions, (1) 24*a*.
Kimura, Shiushichi. See Yasuda, Eiichi.
Kind, G., Schroeder, K. H., and Busse, R. Separating device for separating metallic matter from nonmetallic matter, P (7) 172*g*.
Kind, H. See Verheyden, L.
Kindig, J. K. See Coltrinari, E. L.
Kindl, B. See della Porta, P.
King, C. Y., and Webb, W. W. Internal fracture of glass under triaxial tension induced by thermal shock, (4) 80*e*.
King, D. A. See Goymour, C. G.
King, E. F. See Cheney, G. T.
King, G., Rayner, J. W. F., and Powell, A. C. Ohmic contacts for GaAs, P (6) 139*i*.
King, G. A. See Ridge, M. J.
King, L. C., Yearsley, G. A., Adams, A. L., Simmons, M. I., Altenburger, E. G., and Yager, B. P. Automated method and system for fabricating semiconductor devices, P (3) 64*g*.
King, R. B. See Lundquist, J. R.
King, W. H., Jr., and Dietz, W. A. Method for preconditioning piezoelectric sorption detectors, P (10) 251*i*.
King, W. J., and Martin, F. W. Buried-layer semiconductor device for detecting and measuring the energy and atomic number of impinging atomic particles, P (2) 39*d*. Method for making a buried-layer semiconductor device, P (3) 65*h*.
Kingsley, J. D. See Ludwig, G. W.; Prener, J. S.
Kingsley, J. D., and Ludwig, G. W. Efficiency of cathode-ray phosphors (II) correlation with other properties, (9) 224*c*.
Kingsley, J. D., and Prener, J. S. Electron-energy-sensitive phosphors for multicolor CRT, P (9) 225*f*.
Kinner, G. H. See Giltrow, J. P.
Kinoshita, Gyoku. See Kobayashi, Masaki; Kokubu, Masatane.
Kinoshita, Joshyo, and Stein, W. W. Method for growing Sn-doped *n*-type epitaxial GaAs from the liquid state, P (1) 13*e*.
Kinoshita, Koichi. See Oishi, Kenichi.
Kinoshita, Makoto. See Hamano, Yoshiteru; Kose, Saburo.
Kinoshita, Makoto, Kose, S., and Hamano, Y. Hot-pressing of ZrB_2-$MoSi_2$ mixtures, (2) 48*f*.
Kinser, D. L. Structure and electrical properties of FeO-P_2O_5 glasses, (9) 218*i*. See Dozier, A. W.; Friebele, E. J.
Kinsey, L. R. Metal chimney with ceramic lining, P (4) 84*c*.
Kiovsky, J. R., and Bart, R. K. Bonded low-Al_2O_3 mordenite, P (5) 117*e*.
Kiparisov, S. S., Paisov, I. V., and Narva, V. K. Heat treatment of sintered TiC base materials, (10) 246*h*.
Kiplinger, D. V. See Beatty, R. L.
Kipp, K. F. See Frank, G. A.
Kira, Kimihiro, Kobayashi, H., and Yamamoto, K. Electrical oscillation in a microhole made on a thin glass wall, (3) 55*g*.
Kirch, W. See Aboutboul, H. A.; Krekeler, J. H.
Kirchhof, H. See Herrman, R.
Kirchner, H. O. K., and Chadwick, G. A. Calorimetric study of eutectic solid-solid interfacial energies, (7) 176*c*.
Kirchner, H. P. Method of chemically machining Al_2O_3, P (4) 86*c*.
Kirchner, H. P., Gruver, R. M., and Walker, R. E. Strengthening of polycrystalline Al_2O_3 by crystalline surface layers, (2) 49*h*.
Kirchner, H. P., Walker, R. E., and Platts, D. R. Strengthening Al_2O_3 by quenching in various media, (5) 111*c*.
Kireev, P. S. See Aleshin, B. N.
Kirgintsev, A. N., and Aloi, A. S. Possibility of separation of K and Rb nitrates and K and Ce nitrates by zone melting in ammonium nitrate, (3) 71*e*.
Kirgintsev, A. N., Shklovskaya, R. M., and Arkhipov, S. M. Solubility in the systems $KClO_4$-$RbClO_4$-H_2O, $KBrO_3$-$RbBrO_3$-H_2O, KIO_3-$CsIO_3$-H_2O, $RbClO_4$-$CsClO_4$-H_2O, $RbBrO_3$-$CsBrO_3$-H_2O, $RbIO_3$-$CsIO_3$-H_2O at 25°, (3) 75*h*.
Kirichenko, S. P. See Nekrasov, N. N.
Kirichenko, T. P. See Turchinova, L. N.
Kirichenko, Yu. E. Control of batchers and feeders of loose materials, (8) 203*i*.
Kirilenko, V. V. See Dembovskii, S. A.
Kirk, D. L., Phillips, D. C., and Pratt, P. L. Ionic conductivity, ionic thermocurrents, dielectric absorption, and internal friction in impure NaCl, (9) 236*i*.
Kirkendale, G. A. (editor). Analytical Methods for Materials Investigation, B (3) 76*d*.
Kirkpatrick, M. E., and Mendelson, R. A. Alloy capacitor porous anodes, P (9) 224*h*. Apparatus for forming powder compacts of uniform interconnected porosity, P (7) 172*i*.
Kiro, D., Low, W., and Kafri, A. Comparison of electron-nuclear double resonance spectra of Ce^{3+}-H^- and Ce^{3+}-F^- in CaF_2, (6) 145*a*.
Kirschner, J. G. Ceramic capacitor with counterelectrode, P (1) 12*d*.
Kiryukhina, N. A. See Borisova, I. I.
Kiselev, A. V. See Dzhigit, O. M.
Kishi, Isao. See Nakao, Tatsuhide.
Kishigami, Hiromu. Mixing character of a glass-melting tank for container mfg., (5) 106*e*.
Kishigami, Hisao. See Katsumata, Takuma.
Kishii, Toru. See Ooka, Kazuo.
Kishimoto, Shigeki. See Muguruma, Hiroshi.
Kishitani, Koichi. Corrosion of Fe in reinforced concrete—protective effect of Ca lignosulfonate for corrosion by chloride, (4) 78*h*.
Kishore, K., and Singh, L. P. Role of SiO_2 sand in the preparation of various mixes used for steel castings, (9) 221*h*.
Kisliuk, P., Chang, Nai-Chien, Scott, P. L., and Pryce, M. H. L. Energy levels of Cr ion pairs in ruby, (5) 120*b*.
Kislyi, P. S. See Badyan, A. Kh.
Kislyi, P. S., and Golubyak, L. S. Sintering of TiC during continuous heating under the influence of ultrasonic vibrations, (10) 261*a*.
Kislyi, P. S., and Kuzenkova, M. A. Evaluation of the surface energy of some metals and refractory compounds, (10) 259*d*.
Kiss, Z. J. See Alig, R. C.
Kita, Hideo. Float glass method and apparatus with gas extraction means, P (2) 34*b*.
Kita, Hideo, and Ito, K. Process for mfg. and sizing float glass, P (5) 107*g*.
Kitagawa, Yasuo, and Watanabe, Y. Preparation of dioctahedral vermiculite from muscovite, (6) 143*e*.
Kitaigorodskii, I. I. Method of mfg. crystalline glass articles, P (10) 245*c*.
Kitajima, Nobuo. See Hanada, Hiroshi.
Kitamura, Saburo. See Yamashita, Toshio.
Kitamura, Toshinori, Ajichi, Y., Miyata, I., and Ono, M. Ceramic capacitor, P (11) 274*d*.
Kitano, Ichiro. See Uchida, Teiji.
Kitano, Ichiro, Koizumi, K., Ikeda, Y., and Matsumura, H. Light-conducting glass structure having a peripheral light-absorbent layer, P (7) 162*f*.
Kitano, Ichiro, and Matsumura, H. Spherical lens structures, P (9) 220*a*.
Kitano, Yukio. Method for mfg. cryolite with high purity, P (9) 232*i*.
Kitchen, P., and Hallam, G. C. Moessbauer measurements in the compensated ferrite $Li_{0.5}Fe_{2}Cr_{2.5-\delta}O_4$, (7) 178*j*.
Kito, Masao, Kawahara, S., Sakai, T., and Sugiyama, S. Effect of addition of petroleum coke on the solid reaction between $BaCO_3$ and TiO_2, (6) 146*g*.
Kitta, Kenichi. See Kumada, Akio.
Kitto, A. D. See Craik, D. J.
Kittrell, J. R. Hydrocracking catalyst comprising an amorphous aluminosilicate component, a group VIII component, and Re and process using the catalyst, P (3) 71*j*.
Kiuchi, Yuji. See Hori, Hiroo.
Kivela, W. C. See Woerner, L. M.
Kiyomitsu, Eto. See Nishi, Seiya.
Kizawa, Kyubei. See Ohgishi, Sakichi.
Kizel, V. A. See Dzhurinskii, B. F.
Kizer, D. E., Smith, Roy, A., and Speidel, E. O. Method of making a nuclear reactor fuel element of UN in a refractory metal matrix, P (8) 203*d*.
Kizu, Humio. See Matsuno, Akira.
Kjekshus, A. Properties of binary compounds with the $CoSb_2$-type crystal structure, (6) 151*f*. See Bjerkelund, E.; Brattas, L.; Brostigen, G.; Holseth, H.; Selte, K.
Kjekshus, A., and Jamison, W. E. Magnetic properties of $CrAs_{1-x}Se_x$, (4) 97*b*.
Kjekshus, A., and Nicholson, D. G. Significance of π back-bonding in compounds with pyrite-, marcasite-, and arsenopyrite-type structures, (3) 75*d*.
Klaeboe, P. See Oeye, H. A.
Klahr, C. N. Wide aperture electrooptic modulator, P (2) 43*c*.
Klama, S., and Klinger, M. I. Influence of electron-spin exchange interaction in ferromagnetic semiconductors on dynamics and transport of charge carriers, (6) 148*g*.
Klar, R. See Trattner, H.
Klasse, F. See Mahler, E.
Klassen, A. N. See Luginina, I. G.
Klassen, V. K. See Luginina, I. G.
Klauz, M. See Patka, M.
Kleb, R. See Fredrickson, D. R.
Klein, A. Ceramic centers in Italy (V) modern ceramic museums in Italy, (9) 213*h*. Did the Siegburg stoneware potters know about the Chinese porcelain? (7) 155*g*.
Klein, G. P. Continuous [film] forming of metal oxides, P (5) 112*i*.
Klein, K. See Verheyden, L.
Klein, L. See Cooper, A. R.
Klein, M. V. See Moore, G. E., Jr.; Rosenbaum, R. L.
Klein, M. V., and Porto, S. P. S. Multiple-phonon-resonance Raman effect in CdS, (6) 150*i*.
Klein, N. See Berglund, C. N.
Klein, T. Conductor-insulator-semiconductor FET with semiconductor layer embedded in dielectric underneath interconnection layer, P (1) 12*e*.
Klein, T., and Faggin, F. Doped semiconductor electrodes for MOS-type devices, P (10) 250*h*.
Kleinteich, R., and Bauder, U. Installation of windows in glass apparatus, (1) 3*e*.
Kleitman, D., Russell, L. K., and Grebene, A. B. Method for integrated circuit mask fabrication and assembly used therewith, P (9) 226*j*.
Klement, K., and Krutsky, N. Trace elements in limestone and their significance, (9) 232*j*.
Klement'ev, A. A. See Funke, V. F.
Klemm, W. A., and Berger, R. L. Calcination and cementing properties of $CaCO_3$-SiO_2 mixtures, (11) 266*h*.
Klemperer, W. A. See Raymonda, J. W.
Kleppa, O. J. See Oestvold, T.
Klerk, J., and Stijntjes, T. G. W. Magnet core built up from Ti-containing Mn-Zn-ferrous ferrite and method of mfg., P (6) 138*f*.
Kleshchev, G. V. See Bryzgalov, A. N.
Klesper, H. See Busse, O.
Klimisch, R. L. Catalyst for N oxide reduction, P (10) 257*c*.
Klimmek, N. Lightweight ballistic armor, P (2) 38*b*.
Klimov, V. V. See Volkov, V. I.
Klinge, J. L. Temp.-resistant coating and method, P (8) 189*c*.
Klinger, I. See Kamentsky, L. A.
Klinger, M. I. See Klama, S.
Klink, J. P., and Fulk, W. F. Apparatus for severing linear material, P (6) 132*b*.
Klink, J. P., and Morrison, C. R. Method of making, supplying, and applying chemical treatment to glass fibers, P (3) 59*f*.
Klochkov, L. A. See Samsonov, G. V.
Klokholm, E. See Giess, E. A.; Matthews, J. W.
Klomp, C. J. See van der Giessen, A. A.
Klomp, J. T. Adhesion bonding of ceramics to metals, (4) 79*i*. Bonding of metals to ceramics and glasses, (10) 242*f*. Recent developments for bonding ceramics to metals (I,II), (10) 247*f*.
Klose, G. R. See Abratis, H.
Klose, P. H. Electrical properties of MnO_2 and Mn_2O_3, (9) 235*c*.
Kloss, I. See Jagdt, R.
Klotins, E. E. See Bergmanis, K. A.
Klotz, J. M. See Phelps, F. L., Jr.
Klumb, R. H. Core plug for nuclear reactor and method of operating reactor, P (9) 228*g*.
Klyucharov, Ya. V., and Strakhov, V. I. Effect of gaseous atm. on reaction between ZrO_2 and CeO_2 and properties of the fired material, (8) 195*c*.
Kmecak, R. A. See Kovach, S. M.
Knauf, A. N. Removing H_2O from Ca sulfate, P (3) 54*d*.
Knauff, K. G. Fe_4N as a material for magnetic recording and method of mfg., P (10) 250*j*.
Knerr, R. H., and Thibault, D. J. Y-junction circulator with common arm capacitor, P (1) 15*b*.
Knight, M. H. See Haggis, G. A.
Knippenberg, W. F. See Bootsma, G. A.; Veldkamp, J. D. B.
Knippenberg, W. F., and Moore, A. W. Method of mfg. SiC crystals, P (2) 41*i*.
Knippenberg, W. F., and Verspui, G. Method of mfg. AlN crystals for semiconductor devices, P (4) 89*d*. Method of securing diamond by brazing, P (10) 241*f*.
Knippenberg, W. F., Verspui, G., and Basart, J. C. M. Crystals, in particular crystal whiskers, and objects comprising such crystals, P (4) 92*i*.
Knochel, W. J., and Werner, L. C. Method of seasoning crystalline ceramic discharge lamps, P (11) 270*f*.
Knop, O. See Barker, W. W.
Knowles, T. J., and Eaton, D. A. Method and apparatus for applying a film to a substrate surface by diode sputtering, P (9) 226*c*.
Knudson, G. E., and Langhus, D. Constant flow device for automatic titration, (1) 17*g*.
Knyazeva, T. P. See Zamyatin, S. R.
Kobayashi, Hiroo, and Oyama, T. Rate of thermal dissociation and reassociation of zircon, (7) 179*j*.
Kobayashi, Hiroshi. See Kira, Kimihiro.
Kobayashi, Isamu. Integrated complementary transistor circuit chip with polycrystalline contact to buried collector regions, P (6) 138*c*. Integrated transistor with a polycrystalline contact to a buried collector region, P (3) 65*f*. Semiconductor device including a polycrystalline diode, P (7) 170*a*. Semiconductor device [transistor] and method of

making, P (10) 252*i*. Semiconductor integrated circuit, P (3) 67*e*.
Kobayashi, Katuei. See Osoegawa, Hideru.
Kobayashi, Kazunari. See Katto, Hisao.
Kobayashi, Kazuo. Method of making a junction-type FET, P (6) 138*i*. See Ohama, Fumihiko.
Kobayashi, Kazusuke, Ito T., Mori, T., and Nishiyama, K. H_2O-reducing admixture composed mainly of the salt of hydroxy carbonic acid, (6) 130*b*.
Kobayashi, Keiji. Optical and ESR studies on the interactions of Ag^+ and Cu^+ ions diffusing into glass with multivalent elements Fe, As, and Sb, (3) 56*j*.
Kobayashi, Masaki. Studies of test methods for concrete subjected to freezing and thawing, (6) 130*f*. See Kokubu, Masatane.
Kobayashi, Masaki, and Kinoshita, G. Influence of fly ash on properties of high-Al_2O_3 cement concrete, (6) 129*h*.
Kobayashi, Norio. See Omichi, Hiromu.
Kobayashi, Shoichi. See Niwa, Yoshiji.
Kobayashi, Takehiko. See Suenaga, Masanobu.
Kobayashi, Toshihiko. See Oshima, Shintaro.
Kober, H. See Abeck, W.
Kobylak, A. M. See Bode, W. W.; Dunlap, G. H.
Kobylarz, T. J. Several circuit applications of amorphous semiconductors, (6) 137*b*.
Kobylko, V. S. See Pyatikop, P. D.
Kocharov, A. G. See Spiridonov, F. M.
Kochergin, V. P. See Shevrina, Z. A.
Kochergin, V. P., Bochkareva, N. N., and Mlynskaya, T. P. Electrical conductivity and density of $CaCl_2$-NaCl and $ZnCl_2$-NaCl melts in the presence of KCl, (5) 120*g*.
Kochergin, V. P., and Ulanova, M. S. Solubility of TiO_2 in halide-phosphate melts, (8) 210*f*.
Kocherzhinskaya, V. F. See Eremin, N. I.
Kochkin, G. M. See Meshengisser, M. Ya.
Kocsis, G., and Wojnarovits-Hrapka, I. Examination of basalt systems for the production of mineral wool, (11) 271*h*. Relation between viscosity and structure formed during cooling of basalt melts, (6) 151*j*.
Kocsis, J., and Cauge, T. P. Surface-controlled avalanche semiconductor device, P (10) 253*f*.
Koda, Kiyoyasu. See Kudo, Tetsuo.
Kodaira, K., Shimada, M., Kume, S., and Koizumi, M. Hot isostatic pressing of glass-sealed BeO, (9) 236*c*.
Kodama, Kazumi, Fukuma, N., and Goshokubo, K. Effect of various H_2O-reducing admixtures on steam-cured concrete, (6) 128*d*.
Kodama, Kenjiro, Otake, T., Osada, K., and Fujii, K. Influence of [firing] atm on the bloating of artificial lightweight aggregate prepared from fly ash and pulp waste liquor, (2) 31*d*.
Kodama, Takezo. Variation of strength of concrete with the direction of testing load other than that of the direction of placing concrete into mold, (6) 130*b*.
Kodzoeva, S. M. See Kopylov, N. I.
Koechner, W. Method and means for compensating birefringence in laser systems, P (8) 193*i*. Method and means for sealing laser rods, P (9) 226*f*.
Koehret, B. See Riffaud, J. B.
Koella, C. G. Composite abrasive finishing tool, P (3) 53*f*.
Koelmans, H. Image display device comprising an auxiliary light source, P (5) 112*h*.
Koenig, H. R. Rf sputtering apparatus for promoting resputtering of film during deposition, P (8) 202*f*.
Koenig, J. L. See Tuinstra, F.
Koenig, P. W. See Desmond, R. J.
Koepp, R. L., and Havas, J. Method of insulating multilevel conductors, P (8) 201*b*.
Koester, D. W. See Cornelius, E. B.
Kofstad, P. Nonstoichiometry, Diffusion, and Electrical Conductivity in Binary Metal Oxides, B (10) 263*i*.
Koga, Yasumasa. See Kuroki, Hayashi.
Koga, Yasushi. See Katto, Hisao.
Koga, Yasushi, Kozuka, H., and Tauchi, S. Method of vapor growth of a semiconductor crystal, P (11) 275*e*.
Koga, Yoshiyuki. See Hirosue, Hideharu.
Koh, Yoshiro, Kamada, E., and Tabata, M. Frost resistance of autoclaved lightweight concretes, (6) 129*d*.
Kohashi, Tadao. See Nakamura, Tadao; Tanaka, Kazunobu.
Kohashi, Tadao, and Tanaka, Kazunobu. Semiconductive elements, P (9) 227*d*.
Kohler, G. Thermal behavior of natural rocks, (11) 283*a*.
Kohlhaas, R. See Hloch, A.
Kohlmuller, R. See Faurie, J. P.
Kohno, Kiyoshi. See Araki, Kenichi.
Kohut, J. F-containing borate glass compositions, P (2) 34*c*. See Graff, W. A.
Koichi, Tanizawa. See Ishihara, Toshio.
Koike, Yujiro. See Uno, Yoshihiro.
Koikeda, Toshiaki. See Kumagai, Shun.
Koizumi, Ken. See Kitano, Ichiro; Uchida, Teiji.
Koizumi, M. See Kodaira, K.
Koizumi, Naokazu. See Iwauchi, Kozo.
Kojima, Fumiko. See Nomura, Shoichiro.
Kojima, Takayuki. See Nishibayashi, Shinzo.
Kojima, Yasushi. Measurements of surface tension of CaO-SiO_2 and CaO-SiO_2-Al_2O_3 slags containing S, (3) 74*f*.
Kokado, Hiroshi. See Nakayama, Takao.
Kokosa, R. A. Controlled rectifier and triac with laterally offset gate and auxiliary segments for accelerated turn on, P (10) 250*e*.
Kokot, I. F. See Brekhunets, A. G.
Kokotailo, G. T., and Lawton, S. L. Method of decreasing the K content of K-containing zeolites, P (5) 117*g*.
Kokubo, Tadashi, and Tashiro, M. Thick-film capacitors made from glass-ceramics containing PbO and TiO_2, (2) 39*f*.
Kokubu, Katsuro. Fundamental studies of bond behavior between reinforcement and concrete under static load and repeated load, (6) 129*e*.
Kokubu, Masatane, Kobayashi, M., and Kinoshita, G. Studies of long-term strength of high-Al_2O_3 cement concrete, (10) 242*a*.
Kokuta, Hiroshi. Quick setting and quick hardening cement and method for producing, P (9) 215*i*.
Kolakowski, R. L. Electric lamp structure, P (2) 33*j*.
Kolar, D. See Guha, J. P.
Kolar, D., and Drofenik, M. Influence of Bi_2O_3 additions on the sintering and the magnetic properties of Sr ferrite, (7) 167*e*.
Kolar, D., and Trontelj, M. Final-stage sintering of active CaF_2 and analysis of microstructure, (2) 47*g*.
Kolarik, R. V. Composite armor, P (9) 218*f*.
Kolb, E. D., Caporaso, A. J., and Laudise, R. A. Hydrothermal growth of Li metagallate, (7) 178*c*.
Kolb, E. D., Pinnow, D. A., Rich, T. C., Laudise, R. A., Tynes, A. R., Lias, N. C., and Grudenski, E. E. Low-optical-loss synthetic quartz, (8) 190*j*.
Kolb, W. P., Jr., and Crane, D. E. Gas laser with adjustable mirror, P (2) 34*c*.
Kolesnichenko, G. A. See Naidich, Yu. V.
Kolesnik, L. N. See Borisov, V. G.
Kolesnikova, I. A. See Sazhin, V. S.
Kolesova, V. A. Infrared absorption spectra of silicate glasses containing BeO, (9) 217*a*.
Kolesova, V. A., Ismatov, A. A., and Toropov, N. A. Infrared absorption spectra of some silicates with the akermanite-type lattice, (8) 190*h*.
Kolfertz, E. Heating rods, P (7) 174*e*.
Koller, A., Frydl, J., and Antonin, V. Use of ceramic semiconductors, (9) 224*f*.
Koller, K. See Gujer, H.
Kollwentz, W. See Jangg, G.
Kolm, H. H. Process for magnetic separation, P (10) 254*g*.
Kolodney, M. See Halbfinger, G. P.
Kolomaznik, K., Zapletal, V., Soukup, J., and Ruzicka, V. Use of electronic microbalances in gravimetric thermal analysis, (10) 255*f*.
Kolomytsev, P. T., Moskaleva, N. V., and Snetkov, A. Ya. Phase composition and some properties of Mo-Cr-B alloys, (10) 260*f*.
Kolopus, J. L. See Chen, Yok.
Kolosovskaya, V. M. See Tolochkova, M. G.
Kolostori, J. Nomograph for the determination of significant characteristics of closed-circuit ball mills, (5) 115*f*.
Kolotii, I. I. See Budnikov, P. P.
Kolotii, P. V. Decorating pottery by silk screening, (8) 197*f*.
Kolpakov, S. V. See Likhoradov, A. P.
Kolta, G. A. See Hussein, M. K.
Koltermann, M. See Heuner, W.
Komac, M. See Sharp, A. R.
Komaki, Takashi. See Shimada, Kinji.
Komatsu, Wazo. See Morivoshi, Yusuke.
Komatsubara, Kiichi. See Tsuchimoto, Takashi.
Komazawa, Yoshihisa. See Oshima, Shintaro.
Komeya, Katsutoshi, and Inoue, H. Influence of fibrous AlN on the strength of sintered AlN-Y_2O_3, (2) 48*h*. Method for mfg. AlN fibers, P (7) 164*g*.
Komeya, Katsutoshi, Tsuge, A., Inoue, H., and Murata, H. Study of sintered AlN-Y_2O_3 with fibrous structure, (6) 152*d*.
Komine, Noboru. Wear of diamond wheels in grinding ceramics, (3) 53*e*.
Komissarova, L. N. See Anoshina, N. P.; Spiridonov, F. M.
Komlev, V. G. See Svchev, M. M.
Komljenovic, R. See Ocepek, D.
Kompanichenko, N. M. See Chaus, I. S.
Komuro, Keigo. See Oshima, Shintaro.
Konagaya, Yasuhei. See Imaoka, Minoru.
Kondo, Akihiro. Solid-state microwave oscillator with ceramic capacitance temp. compensating element, P (9) 228*a*.
Kondo, Hiromitsu. See Kanbayashi, Akio.
Kondo, Renichi. See Choi, Sangheul; Daimon, Masaki.
Kondo, Renichi, and Choi, S. Formation reaction in portland cement clinker, (2) 31*c*.
Kondo, Renichi, and Yoshida, K. Effects of the pore structure in paste on the rate of hydration and mortar strength of C_3S, alite, and their solid solutions, (4) 78*h*.
Kondo, Yojiro. See Nanamatsu, Satoshi.
Kondratov, I. Ya. See Samsonov, G. V.
Konev, V. A. See Shemyakin, V. K.
Koninendijk, W. L., and Groenendijk, H. Wet-chemical preparation of homogeneous glass systems, (9) 218*a*.
Konik, L. P. See Korobka, L. A.
Konishi, Kunihiko. See Fujita, Tadao.
Kono, Hisashi. See Suzukawa, Yuichi.
Kono, Motomi, and Ohtomi, H. Method and apparatus for separating particles from particle-laden fluid, P (11) 277*e*.
Kononchuk, O. P. See Borisov, V. G.
Konopicky, K. Use of X-ray fluorescence analysis for refractory raw materials and products, (8) 205*i*.
Konopicky, K., Patzak, I., and Dohr, H. Chemical and mineralogical changes in the constituents accompanying SiC (influence of temp. gradient on block from the furnace) (II) acid solubility and oxidation resistance of various modifications of polytypes of SiC —problem of SiC analysis, (10) 246*f*.
Konopicky, K., and Routschka, G. Investigation of the requirements in refractory materials for use at high temp. for long periods, (5) 109*g*.
Konorova, E. A. See Kozlov, S. F.
Konov, A. V. See Safonov, V. V.
Konow, H. See Grabner, H.
Konstantinova, E., and Kanev, S. Photovoltaic cells from ceramic CdS treated in a solution containing Bi ions, (7) 167*c*.
Koo, R. C., and Shurgan, J. Filament-protecting device and shock-resistant lamp, P (3) 58*b*.
Kooi, E. Method of mfg. a semiconductor device and device manufactured by the method [epitaxial growth], P (1) 13*a*. Method of mfg. a semiconductor device and device manufactured by the method [oxidation], P (1) 13*a*. Semiconductor device comprising an IGFET and method of mfg., P (10) 252*h*. Semiconductor device having a semiconductor body of which a surface is at least locally covered with an oxide film and method of mfg. a planar semiconductor device, P (6) 140*c*. See Tulp, T. J.
Koons, E. R. Metal-to-glass-to-ceramic seal, P (5) 107*a*.
Koopmans, G. See Chedaille, J.
Koos, J. Experiments with portland cement-plastics combinations, (6) 128*j*.
Kopanda, J. E. See Kalousek, G. L.; Nickelsen, H. O.
Kopelman, B. See Beare, G. K.
Kopko, P. Method of reconstituting unfired cast Al_2O_3 scrap, P (4) 86*a*.
Kopylev, B. A. See Tokarev, G. I.
Kopylov, K. I. See Menchikov, L. P.
Kopylov, N. I. System PbS-Cu_2S-FeS-Na_2S, (5) 124*g*.
Kopylov, N. I., and Kodzoeva, S. M. System ZnS-Na_2S, (8) 211*h*.
Kor, G. J. W. See Turkdogan, E. T.
Kor, G. J. W., and Turkdogan, E. T. Sulfides and oxides in Fe-Mn alloys (II) precipitation of solid sulfides and liquid oxysulfides during oxidation of Fe alloys, (6) 152*e*.
Korab, O. See Ryba, J.
Korach, M. Recent developments in ceramic firing, (2) 43*j*.
Korchak, I. I. See Spitsyn, V. I.
Koren, M. G., Oksman, A. M., Raginskaya, P. I., Rivlin, N. I., Tishkevich, Yu. B., and Likhachev, G. M. Continuous method of dehydrating porcelain slip, (8) 197*d*.
Korkh, L. M., Pugina, L. I., and Mamykin, E. T. Effect of some technological factors on the strength and antifriction properties of sulfidized Fe-graphite materials (II) Effect of porosity and structure, (10) 246*e*.
Kornblit, A. See Lipsicas, M.
Korneev, V. I. See Sychev, M. M.
Korobka, L. A., Tret'yak, Z. A., and Konik, L. P. Differential photometric method for determining Zr content in refractories, (8) 195*a*.
Koroleva, L. N. See Bondar, I. A.
Korotin, B. A. See Nemirovskii, B. V.
Korotkova, R. F. See Chaporova, I. N.
Korshunov, B. G. See Drobot, D. V.; Safonov, V. V.
Koryazhkin, V. A. See Grinberg, Ya. Kh.
Kosaka, Yoshio. See Oota, Fukuo.
Kosaka, Yoshio, Tanigawa, Y., and Hayashi, C. Effect of end condition of concrete specimen on stress distribution under uniaxial compression, (6) 128*b*.
Kosar, J. See Varga, J.
Kosarev, V. S. See Lidorenko, N. S.
Kose, Saburo. See Hamano, Yoshiteru; Kinoshita, Makoto; Nakamura, Tetsuro.
Kose, Saburo, Kinoshita, M., and Hamano, Y. Densification and electrical conductivity of hot-pressed ZrO_2-CeO_2 mixtures, (3) 72*e*.
Koshiishi, Kuniaki, and Inoue, N. Blow head link of glass blow molding apparatus, P (2) 33*e*.
Kosinskaya, I. Ya. See Tret'yakov, Yu. D.
Kosinskaya, I. Ya., and Tret'yakov, Yu. D. Density and structure of ferrites after sintering of ferrite powders, (9) 223*h*.
Kosolapova, E. P. See Budnikov, P. P.; Khoroshavin, L. B.
Kosolapova, T. Ya., and Kutysheva, E. V. Reaction between ZrC and Si powders, (10) 260*d*.
Kossivas, T. G. Amine formate accelerator additives for portland cement compositions, P (3) 54*d*.
Kostechko, R. F. See Kestner, O. E.
Kostenko, A. S. See Zapolsky, A. K.
Kostic, E. See Boskovic, S.
Kostikov, V. I. See Zubarev, Yu. V.
Kostin, N. D. See Yas, D. S.
Kostiner, E. See Bless, P. W.; Robertson, B.
Kostyukov, N. S. See Budnikov, P. P.
Kosukhin, V. V. See Funke, V. F.
Kota, S. See Kozar, L.
Kotera, Noboru. See Hitomi, Teiichi.
Kotera, Nobuo, and Katayama, Y. MOSFET ir detector, P (9) 227*a*.

Koto, Kichiro. See Morimoto, Nobuo.
Kotova, T. V. See Volkov, G. M.
Koudelka, J. Indirect measurement of the surface temp. of a glass ribbon with a radiation pyrometer, (8) 190*d*.
Koupal, B. See Riffaud, J. B.
Kourtesis, J. G., and Marcoux, L. Contact system for electrically conductive ceramic-like material, P (10) 250*e*.
Kouwenhoven, H. W., and Van Beem, M. J. L. Process for the preparation of mordenite, P (2) 46*c*.
Kouzova, N. I. See Borisova, Z. U.
Kovach, S. M., and Kmecak, R. A. Alkyl transfer of alkyl aromatics with group VIII metals on B_2O_3-Al_2O_3, P (1) 20*j*.
Kovacs, R. Connection between structure and properties of cements containing fly ash, (2) 30*j*. Data on the application of power plant fly ashes, (2) 30*j*.
Koval'chenko, M. S. See Bezykornov, A. I.; Ogorodnikov, V. V.; Samsonov, G. V.
Koval'chenko, M. S., and Sereda, N. N. Sintering of TiC base cermets, (10) 247*j*.
Kovaleva, I. S., Luzhnaya, N. P., and Martikyan, S. B. Interaction of components in the system Ga-In-As, (8) 209*b*.
Koval'skii, A. E. See Lidorenko, N. S.
Kovalyk, D. A. See Kuz'ma, Yu. B.
Kovarik, J. F., and Vossos, P. H. Process for making SiO_2 organosols, P (8) 196*i*.
Kovba, L. M. See Spitsyn, V. I.; Velikodnyi, Yu. A.
Koyama, Machiko. See Katto, Hisao.
Koyama, Yasujiro. See Shimada, Noburo.
Koyanagi, Wataru. See Niwa, Yoshiji.
Koyanagi, Wataru, Mishima, H., Usui, Y., and Otoi, T. Mechanical properties of mortar with various sand-cement ratios, (6) 129*c*.
Kozachenko, E. L., Bergman, A. G., and Evseeva, V. B. Ternary system Na fluoride, pyrophosphate, and tetraborate, (5) 124*i*.
Kozak, L. M., and Huang, P. M. Adsorption of hydroxy-Al by certain phyllosilicates and its relation to K/Ca cation exchange selectivity, (5) 118*f*.
Kozak, O. R. Infrared-sensitive ZnS luminophor, P (1) 12*g*.
Kozar, L., Toth, M., Uveges, J., Pataki, E., and Kota, S. Process for increasing the strength and electrical conductivity of graphite or C articles and/or for bonding such articles to each other, to ceramic articles, or to metals, P (2) 37*c*.
Kozik, A. F. See Dhaka, V. A.
Kozirovski, Y. See Gevirzman, R.
Kozlov, A. M. See Galkin, N. P.
Kozlov, S. F. Nuclear radiation detection device utilizing diamond detector with injecting and blocking contacts, P (9) 229*a*.
Kozlov, S. F., and Konorova, E. A. Diamond nuclear radiation detector, P (9) 228*h*.
Kozlovskii, L. V. See Andreeva, N. A.
Kozlowski, J. Creatures made from collapsed pots, (2) 30*e*.
Kozlowski, J. J. See Jelinek, J. W.
Kozlowski, T. R. See Grego, P.
Kozma, B., and Hertelendy, C. Hardness measurement of green porcelain bodies, (9) 231*b*.
Kozmin, M. I. Device for mfg. pipes from glass metal, P (4) 81*d*. Glass tank furnace, P (4) 82*c*. See Bondarev, K. T.
Kozuka, Hirotsugu. See Koga, Yasushi.
Kracklauer, A. C. Method and apparatus for retaining and dislodging filter cake, P (7) 172*e*.
Kraemer, S., Seidl, A., and Seger, M. Method of producing lightweight heat-insulating construction elements from lime and silicate and products thereof, P (7) 157*d*.
Kraft, D. W. See Franzblau, M. C.
Kraft, G. Advances in modern wet chemical analysis of Na_2O-CaO-SiO_2 glasses, (8) 204*e*.
Krahl, P. See Bogenschuetz, A. F.
Krsinil, A. G. See Ogorodnikov, V. V.
Krajewski, J. J. See Lang, W. J.
Krall, F., and Kalbfleisch, F. Push-through furnace with graphite rod heating, P (2) 45*i*.
Krambeck, R. H., Panousis, P. T., and Strain, R. J. Electronic switch utilizing a semiconductor with deep impurity levels, P (7) 168*g*.
Kramer, J. O. See Tate, G. L.
Kramer, W. E. Method of activating Pb glass microchannel plates, P (4) 82*h*.
Kramer, W. W. Refractory grid [shape], P (3) 61*e*.
Kranzlein, H. H., Sr. See D'Annessa, A. T.
Krapf, R. See Gross, F.
Krasienko, S. L. See Howell, J. D.
Krasnikov, V. I. See Karasev, A. P.
Krasnov, A. N., and Burikina, A. L. Diffusion saturation of spherical refractory metal powders with C and B, (1) 7*d*.
Krasotin, K. A. See Fain, I. A.
Krasotkina, N. I. See Karklit, A. K.; Yam, V. M.
Krauer, W., Martinelli, A. A., and Oehme, F. Titration potential measurement, P (9) 232*a*.
Kraus, T. Apparatus [vacuum furnace] for determining the gas content of samples, P (11) 278*h*.
Krause, G. Abrasion-resistant recording head, P (11) 274*c*.
Krause, J. T. Variables affecting the acoustic loss and velocity of vitreous SiO_2 at 4°–300°K, (5) 125*c*. Zero temp. coeff. ultrasonic transmission medium having temporal stability, P (7) 163*a*.
Krause, J. T., and Kurkjian, C. R. Acousto-optic and ultrasonic devices using Ge-containing chalcogenide glasses, P (7) 168*g*.
Krause, J. T., and O'Bryan, H. M., Jr. Acoustic detection of ferroelectric phase transitions in PLZT ceramics, (11) 273*e*.
Krausz, A. S., and Eyring, H. Chemical kinetics of plastic deformation, (4) 95*h*.
Krauth, A., and Telwes, H. J. Apparatus for vapor-free melting of U carbide or Pu carbide, P (9) 228*j*.
Kravchenko, I. V. See Potryasov, V. N.
Kravchenko, I. V., Entin, Z. B., and Oleinikova, N. I. Improvement of existing standards for cements, (8) 186*h*.
Kravitz, B. L. Method of producing air-isolated integrated circuits, P (10) 251*j*.
Krawiec, D. M. Nuclear reactor spring ferrule spacer grid, P (9) 229*b*.
Kreider, J. F. Specimen alignment reference apparatus for back-reflection X-ray camera, P (4) 93*g*.
Kreidl, N. J. What's happening in glass? (3) 57*c*, (10) 243*c*.
Kreidler, E. R. Phase equilibria in the system CaO-BaO-WO_3, (11) 281*j*.
Kreidler, E. R., Meehan, J. P., Wilson, E. J., and Fries, D. C. Crystal growth and properties of Mn_2PO_4Cl, (2) 47*g*.
Kreiselmaier, K. W. See Marek, D. A.
Kreitz, W. Monolithic integrable crystal oscillator circuit, P (11) 275*f*.
Krekeler, J. H. See Aboutboul, H. A.
Krekeler, J. H., Aboutboul, H. A., and Kirch, W. Preparation of SiO_2 gels, P (7) 175*e*.
Kressel, H., and Pankove, J. I. Semiconductor electron emitter, P (9) 227*g*.
Kressley, L. J. See Frevel, L. K.
Kreysa, K. See Forman, I.
Krieg, H. C., Jr. See Burk, M.
Kriegel, W. W., and Palmour, H., III (editors). Ceramics in Severe Environments, B (8) 212*f*.
Krieger, E. See Keiser, J. E.
Krigman, A. Energy, fuel, and the environment, (10) 256*e*. Laser machining—specialized but versatile, (3) 63*e*. S problem, (5) 117*a*.
Krikorian, N. H., Bowman, A. L., Krupka, M. C., and Arnold, G. P. Preparation and crystal structure of Sc_4C_3, (4) 98*a*.
Krikorian, N. H., Giorgi, A. L., Szklarz, E. G., and Krupka, M. C. Preparation of a superconducting Sc-C phase, P (1) 9*g*.
Krikunenko, A. F. See Nekrasov, N. N.
Kripitser, A. M. See Satarin, V. I.
Krishan, I. See Srivastava, K. K.
Krishnamachari, V. See Bell, H.
Krishnan, R. See Hariharan, R.
Krishnan, R. S. Raman spectrum of B_2O_3 glass, (11) 269*g*.
Krishtofori, I. I. See Belen'kaya, I. M.
Kristek, L., Svizela, A., and Hampl, I. Arrangement for classifving liquid suspensions and solid materials, P (3) 71*h*.
Kristensen, K. Electronic bistable semiconductor switching element and method of making, P (4) 87*f*.
Kristianpoller, N., and Katz, I. Optical properties of various types of fused SiO_2, (8) 191*j*.
Krivenyuk, V. V. See Pisarenko, G. S.
Krivonosov, L. B., Krylov, E. I., and Zavol'skii, V. A. Synthesis and some properties of Er orthotantalate, (2) 50*a*.
Krivoruchko, P. P. See Gavrish, A. M.
Krivovyazov, E. L., and Voskresenskaya, N. K. Surface tension of melts of the system $Zn(PO_3)_2$-ZnO, (9) 239*a*.
Kriwanek, F. F. Keramos—the Teaching of Pottery, B (1) 28*c*. Victor Spinski, (4) 78*a*.
Krochmann, J. See Gerstenberg, G.
Kroder, E. A. Diamond tool and method of making, P (8) 185*e*.
Kroeger, D. M. See Reimann, D. K.
Kroell, K. E. See Badami, A. V.
Kroger, H. High-frequency diode energy transducer and method of mfg., P (11) 274*i*.
Krogh-Moe, J. Structure of vitreous and liquid B oxide, (3) 75*c*. See Griotheim, K.
Krohn, D. A. See Coppola, J. A.; Gebauer, J.; Hasselman, D. P. H.
Krohn, D. A., and Hasselman, D. P. H. Static and cyclic fatigue behavior of a polycrystalline Al_2O_3, (5) 124*e*.
Krokhina, A. G., and Morozov, I. S. Reactions in the system $TaCl_5$-UCl_4-KCl, (5) 123*j*.
Krolikowski, W. F. MOS semiconductor device operable with a positive or negative voltage on the gate electrode and method therefor, P (4) 89*e*.
Krolla, G. As_2O_3 glass compositions, P (2) 33*c*.
Krostewitz, W. Method for measuring rate of fluid absorption of plaster molds, P (9) 231*j*.
Krouskop, N. C. See Castellucci, N. T.
Krueger, J. Thermal properties of Na silicate glasses at low temps., (9) 218*j*.
Kruglitskii, N. N. See Borzunov, E. E.; Grankovskii, I. G.
Kruglitskii, N. N., and Orobchenko, V. I. Neutron irradiation of argillaceous minerals with various crystal structures, (7) 179*g*.
Kruglitskii, N. N., Sposobnyi, V. V., and Voronkova, R. M. Structure formation in the consolidated fireclay masses, (2) 50*b*.
Krumanacker, B. P. See Desmond, T. J.
Kruntorad, V. See Chromecek, R.
Krupka, M. C. See Krikorian, N. H.
Krupkin, Yu. S., and Dgebuadze, T. P. Dielectric properties of glasses in systems M_2O-GeO_2 and M_2O-B_2O_3-GeO_2, (8) 189*j*.
Krupnick, A. C. Inorganic thermal control coatings, P (3) 54*f*.
Kruppa, R. W., and Ward, E. S. Dielectric film thickness monitoring and control system and method, P (2) 40*c*.
Kruse, E. W., III, and Fine, M. E. Precipitation strengthening of MgO by $MgFe_2O_4$, (2) 49*a*.
Krutnev, I. M. Partial replacement of slag with quartzite in raw-material mixture, (8) 187*h*.
Krutsky, N. See Klement, K.
Krylov, E. I. See Bazuev, G. V.; Krivonosov, L. B.
Krylov, V. S., Popkov, I. N., Magunov, R. L., Puring, M. N., Bagdasarov, Kh. S., Tsagina, R. F., and Popov, V. I. Method of producing orthovanadates of rare-earth metals, P (9) 233*b*.
Krynock, R. A., and Ruhe, R. W., Jr. Vibrating screen for fine screening of liquids, P (9) 230*e*.
Krystyniak, C. W. Free-flowing plasma spray powder, P (6) 131*c*.
Kryzhanovskaya, I. A. See Satarin, V. I.
Kryzhanovskaya, I. A., Zdorov, A. I., Lobasenko, I. G., and Lipovskaya, A. G. Intensification of the process of averaging slurries, (8) 187*b*.
Krzyzanowski, E. See Wittmoser, A.
Ksendzovskii, V. R., Gozenbuk, L. G., and Shal'man, L. M. Automatic control system for firing material in a rotary kiln, (8) 206*b*.
Ksendzovskii, V. R., Gozenbuk, L. G., and Skusnov, L. I. Automatic control system for the heating cycle in tunnel kilns, (8) 206*c*.
Kubelik, J. See Dudrova, E.
Kublik, P. S. Method for fabricating ferrite core plug-in devices, P (7) 169*d*.
Kubo, Kazuhiko. Molding materials of Ca silicate hydrate and shaped products thereof, P (10) 242*e*.
Kubo, Kazuhiko, Minoura, T., Takahashi, A., and Tamura, H. Influence of pyrophyllite on the hydrothermal synthesis of Al-containing tobermorite, (5) 117*i*.
Kubo, Masaharu. See Kawagoe, Hiroto; Makimoto, Tsugio.
Kuboniwa, Shigeo. See Hoshina, Teruhiko.
Kubota, Kanji. See Murayama, Keiichi.
Kubota, Takehiro. Progress and present condition of work on expansion of blooming soaking pit walls using plastic refractories, (1) 8*d*.
Kubota, Takehiro, and Kawakita, H. Spalling test results obtained on zircon sleeve brick and high-SiO_2 sleeve brick, (1) 8*b*.
Kubota, Tsutomu. Method of forming fluorescent screens, P (6) 138*e*.
Kucera, W. J. See Costello, R. C.
Kucher, E. Auxiliary equipment on [edge-runner] wet-pan and roller mills, (9) 229*c*.
Kuchmas, J. See Walsh, P. J.
Kuczynski, G. C., and Herbert, J. Surface cracking of opacified glasses, (7) 160*h*.
Kudintseva, G. A., Kuznetsova, G. M., Bondarenko, V. P., Selivanova, N. F., and Shlyuko, V. Ya. Preparation and emissive properties of some Y and Gd borides, (10) 260*j*.
Kudo, Atsushi. See Murata, Takao.
Kudo, Koji. See Maeda, Teizo.
Kudo, Tetsuichi. See Makishima, Shoji.
Kudo, Tetsuo, Nakatani, K., and Koda, K. Method and apparatus for mfg. tubular optical glass, P (10) 244*i*.
Kudrna, J. Exhalation of harmful substances from brickwork kilns, (10) 246*a*.
Kudrzycki, R. M. See Augustin, E. H.
Kuebel, E., Lambrecht, J., Linke, A., and Stadlmann, G. Installation for removing a stopper rod from a ladle, applying a new covering to the rod, and reinserting the rod into the ladle, P (4) 84*b*.
Kuehl, B. See Hofmann, D.
Kuehl, B., and Dobrusskin, A. High-pressure Hg vapor discharge lamp with metal halide additive, P (7) 162*c*. High-pressure saturated metal vapor, preferably Na or metal halide vapor, discharge lamp, P (8) 193*e*.
Kuehl, D. K., and Smart, R. C. Low-twist tensioning of B filament, P (4) 84*c*.
Kuehr, J. See Singer, H.
Kuenkele, R., Engelhardt, H. P., and Chaudhuri, S. Different types of bricks and their behavior in vacuum metallurgy, (5) 109*f*.
Kugler, T., and Silbiger, J. Preparation of finely particulate Si oxides, P (6) 144*h*.
Kuhlmann, R. See Eisenmenger, E.
Kuhlmann-Wilsdorf, D. See Moore, J. T.
Kuhn, M., and Schumaker, N. E. Electroluminescent semiconductor display apparatus, P (9) 225*e*.
Kuhn, P. See Bol, J.
Kuhnert, O. See Eisenmenger, E.
Kuiper, L. L. Semiconductor devices with lines and electrodes which contain 2–3% Si with the remainder Al, P (2) 42*a*.
Kukolev, G. V. Chemistry of Silicon and the Physical Chemistry of the Silicates (Vols. 1–3), B (5) 126*b*.
Kukolev, G. V., Nemets, I. I., and Semchenko, G. D. Methods of intensifying the vitrification of kaolinitic clays, (8) 209*g*.
Kukuruznyak, I. S. See Borisov, V. G.
Kukusheva, M., and Radkova, A. Nepheline as a structural element of semivitreous porcelain, (5) 110*j*.
Kuleshova, V. D. See Ostrikova, N. V.
Kulicke, F. W., Jr., and Lepone, J. J. Aiming device for semiconductor bonding apparatus, P (8) 200*a*.
Kulikov, A. A. See Nekrasov, N. N.
Kulkarni, A. K., Thiagarajan, K., Upadhyaya,

D. D., and Moorthy, V. K. Development of $BaTiO_3$ with consistent dielectric properties, (11) 273*h*.
Kulling, A. See Hilgers, G.
Kulygin, I. P., Cherep, I. L., Ivanov, G. I., and Frantskevich, A. A. Efficient construction of hanging fireproof chains, (8) 186*a*.
Kumada, Akio. Ferroelectric storage device using Gd molybdate, P (3) 65*a*.
Kumada, Akio, Suzuki, K., and Kitta, K. Switching condenser element for switching an alternating current, P (9) 228*d*.
Kumagai, Shun, and Koikeda, T. Method [sputtering] of producing Ta nitride film resistors, P (8) 201*h*, P (9) 226*i*.
Kumagai, Yasuji, Inukai, K., and Suzuki, Y. Tunnel current through a thin Al_2O_3 film with nonuniform thickness, (5) 112*d*.
Kumanomido, Mahito. See Mitomo, Mamoru.
Kumar, A. See Srivastava, G. P.
Kumar, A., Rajdev, D., and Douglass, D. L. Effect of oxide defect structure on the electrical properties of ZrO_2, (10) 258*i*.
Kumbhare, P. R., Tedrow, P. M., and Lee, D. M. Electron tunneling in superconducting Cd-Al_2O_3-Al junctions, (5) 120*b*.
Kume, Makoto. See Suzuki, Joji.
Kume, S. See Kodaira, K.
Kumia, Shoji. See Tanaka, Eihachiro.
Kummer, G. L., Jr., Straw, R. A., and Wendt, J. A. Ultrasonic thickness measuring system, P (1) 18*j*.
Kummer, J. T., and Tien, Tseng-Ying. Solid state energy storage device, P (1) 14*h*.
Kummerle, H. F. Method of making SiO_2 [bead] particles, P (8) 207*g*.
Kummerlehr, H. See Mechel, F.
Kumon, Osamu. Terminal device for piezoelectric ceramic transformer, P (3) 68*a*. See Osada, Mitsuo.
Kun, Zoltan K., and Robinson, R. J. *Pn* junctions in ZnSe, ZnS, or ZnS/ZnSe and semiconductor devices comprising such junctions, P (9) 227*h*.
Kunert, A., and Oesterhelt, G. Solder for contacting a semiconductor body and method for its production, P (1) 14*g*.
Kunes, K. See Spicak, K.
Kung, J. K. See Mitchell, I. V.
Kunihiro, Etsuji. See Tamaoki, Osamu.
Kunimoto, Kozui. See Sugiura, Kozo.
Kunin, V. Ya., Tsikin, A. N., and Shakirov, A. Electrical conductivity and volt-ampere characteristics of Ti-containing dielectrics during aging, (8) 199*e*.
Kunkle, A. C. See Iannicelli, J.
Kunkle, G. E. Glassmelting furnace, P (8) 193*b*.
Kunkle, G. E., and Heidish, W. E. Process and apparatus for separating foam from a molten body of glass, P (9) 219*h*.
Kunnen, H. M. J. J. See Piesslinger, G. A. A.
Kuntsevich, O. V. Conditions which conserve the air phase in concentrated cement suspensions, (7) 156*e*.
Kuntz, U. E. See Basche, M.; Galasso, F. S.
Kunvari, A. Open questions in the perspective technical development of the silicate industries, (2) 50*g*.
Kunz, H. J. Electroluminescent diode configuration and method of forming, P (9) 225*e*.
Kunz, W., and Breckheimer, W. Process for the production of Pb oxides, P (3) 72*a*.
Kupka, L. Kerkortan—an organic liquefying agent of ceramic materials, (10) 248*g*.
Kuramoto, Yoshio. See Yamazaki, Yasuo.
Kurashina, Isao. See Fujimoto, Yukiya.
Kuratani, Sadamitsu. See Kawanishi, Nobuo.
Kuratomi, Tatsuo. Method of mfg. diamond crystals, P (1) 1*f*, P (7) 155*f*. Process for production of an Si-coated diamond powder, P (3) 67*d*. Ultrahigh pressure-temp. apparatus, P (6) 141*h*.
Kurczyk, H. G. See Wuhrer, J.
Kuribayashi, Shunsuke. See Setoguchi, Masahiro.
Kurita, Kenichiro. Apparatus for automatically shaking filter cake in a filter press, P (3) 69*c*. Device for releasing filter cake in filter press, P (9) 229*j*.
Kurita, Toshio. See Tomizuka, Isao.
Kurkjian, C. R. See Krause, J. T.
Kurlina, E. V. See Egorova, T. N.
Kurokawa, Akitsugu, and Maezawa, Shigeru. Slurry-pumping [diaphragm-type] means, P (5) 115*i*.
Kurokawa, Hideo. See Yukami, Noboru.
Kurokawa, Susumu. See Iimura, Tsutomu.
Kurokawa, Takaaki. Cooling device in a glass bulb blowing apparatus, P (4) 81*j*. Glass bulb blow-molding apparatus, P (4) 81*i*.
Kurokawa, Takaaki, Yamada, J., and Wada, M. Apparatus for blow molding glass bulbs, P (9) 218*c*.
Kuroki, Hayashi, and Koga, Y. B_2O_3 anomaly in NaF-Na_2O-B_2O_3 glasses, (11) 268*d*.
Kuroki, Hisataka. See Moriki, Juichi.
Kurosaki, Hideaki. See Sugahara, Yujiro.
Kurotaki, Yuko. See Imaoka, Minoru.
Kurti, I. See Galos, M.
Kurtzig, A. J. Faraday rotation in birefringent crystals, (5) 120*f*.
Kurtzig, A. J., LeCraw, R. C., and Wolfe, R. $FeBO_3$ devices, P (3) 65*g*.
Kurumada, Katsuhiko, Shikama, S., and Satoh, H. Transistors for C-60M system line repeaters, (11) 274*b*.
Kurumada, Norimitsu. See Nagano, Ranzo.
Kurumada, Norimitsu, and Higaki, K. Some studies on flash setting admixture, (9) 215*h*.
Kuschell, W. N. Process of producing an array of integrated circuits on semiconductor substrate, P (2) 42*d*.
Kuse, D. Influence of magnetic ordering on the Faraday effect in $CdCr_2Se_4$, (9) 236*h*.
Kushihashi, Akira, and Ikeda, K. Process and apparatus for forming a metal oxide coating on flat glass, P (10) 245*a*.
Kushiro, Yukitoshi. See Itoh, Tadatsugu.
Kusman, L. A. See Derie, R.
Kustova, G. N. See Filatkina, V. S.
Kutateladze, K. S., Gabadadze, T. G., and Suladze, I. Sh. Alunite additions reduce setting times and increase the strength of concrete, (8) 185*h*.
Kutateladze, K. S., and Verulashvili, R. D. New compositions for reduction glazes, (8) 198*b*.
Kutsenok, T. G. See Goryachev, Yu. M.
Kutysheva, E. V. See Kosolapova, T. Ya.
Kuwabara, Makoto, and Yanagida, H. Two-step anomalous increase of resistance in $La_{0.002}Ba_{0.998}TiO_3$-$Bi_2O_3$ composite ceramics, (3) 76*a*.
Kuwabara, Senzo. See Horibe, Toshiyasu.
Kuwano, Yasuhiko, and Shiroki, K. Preparation of $Nd(OH)_3$ by vapor-phase reaction, (8) 210*i*.
Kuzenkova, M. A. See Kislyi, P. S.
Kuz'ma, Yu. B. See Sobolev, A. S.; Telegus, V. S.; Voroshilov, Yu. V.
Kuz'ma, Yu. B., and Chepiga, M. V. X-ray diffraction investigation of the systems Ti-Ni-B, Mo-Ni-B, and W-Ni-B, (10) 261*g*.
Kuz'ma, Yu. B., Telegus, V. S., and Kovalyk, D. A. X-ray diffraction investigation of the ternary systems V-Cr-B, Nb-Cr-B, and Mo-Cr-B, (10) 261*h*.
Kuzmicheva, N. V. See Rabodzei, N. V.
Kuznetsov, A. F. See Bryzgalov, A. N.
Kuznetsov, V. A. See Ganiev, R. M.
Kuznetsov, V. G. See Tananaev, I. V.
Kuznetsov, V. G., Petushkova, S. M., and Tananaev, I. V. X-ray study of neutral and basic phosphates of Pr, Sm, and Yb, (8) 210*i*.
Kuznetsov, V. G., and Popova, Z. V. X-ray study of simple and mixed ferrocyanides of In with K, Rb, and Cs, (8) 211*j*.
Kuznetsova, G. M. See Kudintseva, G. A.
Kuznetsova, V. L. See Gropyanov, V. M.
Kuznietz, M., Lander, G. H., and Baskin, Y. Cryogenic sensing device using U monophosphide-U monosulfide, P (6) 140*j*.
Kvyatkovskaya, K. K. See Kats, M. E.
Kwak, T. A. P. Compositions of natural sillimanites from volcanic inclusions and metamorphic rocks, (4) 94*b*.
Kwast, G. M. Template for use in marking firebrick preparatory to cutting for fireboxes of fireplaces and similar structures, P (8) 197*a*.
Kweller, E. R., Staats, W. R., and Rosenberg, R. B. Self-igniting burners, P (10) 256*i*.
Kwestroo, W., van den Broek, J., and Netten, A. Photoconductive layer comprising mixed crystals of PbO and SnO, P (2) 34*j*.
Kwiecien, M., and Lachowicz, H. Magnetoelastic sensitivity of thin-film memory elements, (10) 249*d*.
Kynatov, P. B. See Butt, Yu. M.

LaBelle, H. E., Jr., and Mlavsky, A. I. Method and apparatus for growing inorganic filaments and ribbons from the melt, P (7) 172*d*.
Labrot, G. See Classen F.
Labuda, E. F. See Dalton, J. V.
Lach, V. See Sauman, Z.
Lach, V., and Sauman, Z. Morphology of the microstructure of stoneware bodies and the crystal structure of mullite, (6) 135*j*.
Lachowicz, H. See Kwiecien, M.
LaCombe, D. J., and Babcock, G. L. Composite integrated circuits including semiconductor chips mounted on a common substrate with connections made through a dielectric encapsulator, P (10) 250*b*.
Laconich, R. L., and Schoijett, H. N. Process for decorating pottery, P (5) 111*e*.
Lacourrege, M. Batch material for vitreous manufactures, P (11) 270*b*.
Ladany, I. Liquid phase double epitaxial process for mfg. light-emitting GaP devices, P (6) 138*d*.
Ladik, J., and Biczo, G. Some developments in the semiempirical theories of molecular crystals (IV) σ-π (CNDO) bands, (2) 49*e*.
Lado, E. A. Production of refractory materials, P (6) 143*c*.
Ladygin, F. F. See Satarin, V. I.
Lafer, L. I. See Shikunov, B. I.
Lagarde, Y. See Caillet, M.
Lagervall, E. See Wilhelmi, K. A.
Lagos, C. C. Luminescence of divalent Eu in Ba-Ca, Ba-Sr, and Ca-Sr orthophosphate and pyrophosphate compositions, (9) 236*d*. Phosphor and method of making, P (6) 139*a*.
Lagos, C. C., Fowler, R. A., and Thomas, M. J. B. Process for reclaiming Y orthovanadate phosphors, P (9) 227*a*.
Lagrange, A., Nicolas, J., and Sroussi, R. Magnetic garnets, P (8) 201*c*.
La Grouw, C. M. Glass for TV display CRT, P (4) 81*a*, P (8) 193*a*.
Lahav, N. Particle geometry and optical density of clay suspensions, (5) 122*b*.
Lahiri, D. See Basu, R. K.
Lainer, Yu. A. See Chizhikov, D. M.
Laing, A. M. Magnetic particle core mfg. process, P (9) 225*j*. Process of magnetic particle preparation, P (1) 14*e*.
Laing, W. R. See Leitnaker, J. M.
Lajza, J. J., Jr., See Couture, R. A.
Lake, W. H. Highly loaded fluorescent lamp particularly for dc operation, P (3) 58*d*. Voltage doubler starting circuit for discharge lamp, P (4) 83*b*.
Lake, W. H., and Medendorp, N. W. Internally resistively ballasted discharge lamp containing bridge rectifier, P (10) 244*f*.
Lakin, J. R. See Greaves, E. L.; Payne, G.
Lam, Hung-Kei H. See Bell, N.
Lamb, F. E. See Bourne, D. J.
Lamb, T. J. See Huska, P. A.
Lambdin, F., and Cook, J. L. Fabrication of C-C composites using electrostatic fiber deposition (flocking), (3) 54*f*.
Lambe, K. A. D. See Bowen, D. H.
Lambrecht, J. See Kuebel, E.
Laming, J. Raw materials and refractories performance, (2) 36*c*.
Lamont, W. E., Spruiell, C. E., Jr., Brooks, D. R., and Feld, I. L. Laboratory flotation studies of Tenn. phosphates in the presence of slimes, (7) 175*c*.
Lamp, W. F. See Weisselberg, E. B.
Lanaspeze, P. See Tannenberger, H.
Lancaster, J. K. See Giltrow, J. P.
Lancucki, C. J. See Cole, W. F.
Land, N. S. Feasibility study of a technique for sorting particles by shape, (1) 17*i*.
Landa, T., Syvakari, P., and Westman, E. Pressure chamber for treating material with high pressure, such as isostatic compression of powder bodies, P (2) 44*c*.
Landa, Ya. A. See Litovskii, E. Ya.
Lander, G. H. See Kuznietz, M.
Landry, R. J., and Marino, A. D. End fusion of glass laser rods of dissimilar chemistry, P (2) 34*a*.
Landry, R. J., and Snitzer, E. Sensitizing luminescence of Er with Mo [laser], P (10) 245*g*.
Landry, R. J., Snitzer, E., and Bartram, R. H. Ultraviolet-induced transient and stable color centers in self-*Q*-switching laser glass, (5) 106*f*.
Landsman, A. P. See Lidorenko, N. S.
Lane, A. M. See Weisselberg, E. B.
Lane, E. S. See Hardy, C. J.
Lane, J. W. See Hurlbut, M. R.
Lane, M. K. Method of making dried gypsum articles having improved strength-to-density ratio, P (9) 215*g*. Retarded gypsum plaster for use in long-set aggregated mortar applications, P (7) 157*g*.
Lane, R., Mack, D. L., and Brown, K. R. Dielectric, piezoelectric, and pyroelectric properties of the $PbNb_2O_6$-$BaNb_2O_6$ system, (11) 281*b*.
Lane, R. L. Abrasive cutting element, P (4) 77*h*.
Lang, A. G., Jr. Preformed multiple track magnetic head assembly, P (7) 170*d*.
Lang, A. R. See Moore, M.
Lang, F., Gruen, G., Schwalm, K., and Juchem, F. J. Method and apparatus for treating powdery or granular materials with gaseous, liquid, or solid agents or stabilizers, P (1) 17*a*.
Lang, Jean. See Gaude, J.; Guyader, J.
Lang, Johann. See Schulz, E.
Lang, L. W. Fast breeder reactor, P (8) 203*f*.
Lang, W. J., and Krajewski, J. J. Foundry sand compositions containing graft copolymers of acrylic acid with H_2O-soluble polyhydroxy polymeric compounds, P (6) 135*g*.
Langdon, J. L. Construction of monolithic chip and method of distributing power therein for individual electronic devices constructed thereon, P (7) 168*b*.
Langdon, T. G. Creep mechanisms in stoichiometric UO_2, (5) 114*g*. Grain-boundary sliding in ceramics, (9) 235*h*.
Lange, F. F. Fracture energy and strength behavior of an Na borosilicate glass-Al_2O_3 composite system, (1) 3*d*.
Lange, M. R. Nonclogging impact crusher, P (2) 46*a*.
Langer, D. W. See Goto, Takenari.
Langer, H. G. DTA cell assembly, P (3) 70*a*. Furnace assembly for thermal analysis use, P (4) 93*e*.
Langer, K. Synthesis and properties of Ga-bearing cordierite, $Mg_2(Al_{4-x}Ga_xSi_5O_{18})$, (4) 99*h*.
Langhus, D. See Knudson, G. E.
Langlois, R. E. Bonded mat of strands of continuous glass fibers, P (2) 33*e*.
Langston, P. R., Jr. See Greenstein, B.
Lankard, D. R. Low-temp. sintering phenomenon in heated portland cement pastes, (7) 157*b*.
Lankard, D. R., and Sheets, H. D., Jr. Composition for marking hot metal, P (5) 105*a*.
Lanza, F., and Marengo, G. Graphite impregnated with Bi-Ni alloy, P (9) 228*h*.
Lao, B. Y., and Litvak, M. M. Far-ir mixing in high-purity GaAs, (6) 148*e*.
Lapshov, Yu. K., Podchernyaeva, I. A., Samsonov, G. V., Terekhov, V. P., and Fomenko, V. S. Investigation of the preparation conditions and several physical properties of alloys of the WB-LaB_6 system, (10) 259*e*.
Laptun, V. I. See Gropyanov, V. M.
Larionova, T. N., and Pustyl'nik, T. M. Thermal study of the system InCl-TlCl-$AlCl_3$, (8) 211*b*.
Larkin, M. W. See O'Keeffe, T. W.
Larsen, F. K. See Coppens, P.

Larsen, F. K., Lehmann, M. S., and Soetofte, I. Neutron diffraction study of H_2SeO_3, (3) 74*b*.
Larsen, H. L. See Christensen, L. L.
Larson, A. E. See Hoffman, W. D.
Larson, D. A. See Young, R. G.
Larson, G. C. See Kerr, J. M.
Larson, G. L. See Stewart, J. E.
Larson, J. F., and Polashenski, W. A. Method and apparatus for the manufacture of color CRT screens, P (5) 113*d*, P (8) 200*d*.
Larson, R. I., Jr. See Smollen, L. E.
Larson, S. B. Induction furnace lining materials and installation, (10) 246*i*.
Laskowski, J., Lupa, Z., Fedelinski, K., and Iskra, J. Effect of dressing chromite ores on the quality of refractories, (9) 221*j*.
Lass, J. L., Ross, W. T., and Venier, D. A. Nuclear reactor fuel element spacer, P (7) 171*j*.
Lasser, M. E. Coherent far-ir generator, P (2) 39*g*.
Lassman, B. Solid press molding apparatus, P (10) 254*j*.
Latham, M., and Haswell, A. B. Apparatus for heat-treating elongated tubular material, P (1) 3*f*.
Latker, M. See Johnston, N.
Latos, E. J. See Hayes, C. M.
Latysheva, A. K. See Khoroshavin, L. B.
Laub, L. W. See Childs, P. E.
Laudise, R. A. See Kolb, E. D.
Lauer, J. L. Apparatus for removing SO_2 from stack gases, P (10) 256*d*.
Lauer, O. Fine grinding and air sifting of raw materials for the ceramic industry, (9) 229*g*.
Lauer, R. B., Addiss, R. R., Jr., and Ghosh, A. K. Properties of the room-temp. electron trap in rutile, (5) 122*h*.
Lauer, R. B., and Williams, Ferd. Vapor growth of graded composition crystals of (Zn,Cd)S and (Zn,Cd)Te, (7) 182*c*.
Launay-Mondet, S. Crystal chemistry of the nonstoichiometric phases identified in the systems V-W-O and Li-V-W-O, (6) 145*h*.
Lauren, K. G. See Hjorth, L.
Laurent, Y. See Gaude, J.
Lauritzen, J. I., Jr., and Zwanzig, R. Exact calculation of the partition function for a generalized model of 2-dimensional polymer crystallization by chain folding, (5) 120*c*.
Laurs, A. Pb release of glazes and the earthenware industry, (9) 223*d*. Pb solubility and industrial earthenware production, (7) 165*d*.
Lavenberg, S. S. See Wieder, H.
Lavrenko, V. A. See Fomenko, V. S.
Lavrinenko, I. A. See Eremenko, V. N.
Law, H. B., and Lee, R. H. C. Method of producing a color kinescope, P (4) 89*i*.
Lawless, W. N. Apparatus for [hot] compressing materials, P (1) 16*j*. Capacitive cryogenic thermometer, P (6) 137*g*. Technique for flux growth of $BaTiO_3$ single crystals, P (10) 253*a*.
Lawn, B. R. See Mikosza, A. G.
Lawrence, H., and Schaefer, P. C. Three masking step process for fabricating an IGFET, P (9) 228*a*.
Lawrence, P., Majumdar, A. J., and Nurse, R. W. Application of the Mackenzie model to the mechanical properties of cements, (4) 78*b*.
Lawrence, W. G., and Coffin, L. B. Method of making a permeable ceramic mold used as a substitute for plaster molds, P (5) 111*c*.
Lawrenson, J. Float glass method and apparatus for supplying modifying material to the glass surface, P (4) 81*i*. See Loukes, D. G.; Robinson, A. S.
Lawrenson, J., and Jones, David. Float glass apparatus with adjustable surface modification means, P (2) 34*a*. Method and apparatus for float glass mfg., P (8) 193*h*.
Lawrenson, J., and Morrison, E. Float glass apparatus with adjustable surface modification means, P (2) 34*a*.
Lawrenson, J., and Robinson, A. S. Method and apparatus for float glass mfg., P (8) 193*h*.
Laws, W. R., and Winkworth, D. A. Ceramic recuperators, P (2) 37*e*.
Lawson, A. W. See Ryden, W. D.
Lawton, G. W. See Jacob, C. J.
Lawton, S. L. See Kokotailo, G. T.
Lay, K. W. See Greskovich, C.
Layman, H. D., and Taylor, R. E. Production of Ca halophosphate phosphors, P (7) 170*g*.
Layne, G. S. See Huml, J. O.
Layton, M. M. See Borrelli, N. F.; Herczog, A.
Lazarev, A. N. Vibrational Spectra and Structure of Silicates, B (11) 284*g*.
Lazaridis, L. J. Glass furnace with heat pipe melting, P (1) 4*g*.
Lazor, D. K. See Wallick, C. R., Jr.
Lazott, J. B. See Helgeland, W.
Lea, F. M. Chemistry of Cement and Concrete (3d ed.), B (10) 263*a*.
Lea, P. G. Low-depth CRT, P (11) 275*a*.
Leach, C. E. See Allen, C. H.
Learn, A. J. See Scott-Monck, J. A.
Learned, A. W., III. See Alliegro, R. A.
Leary, D. E. See Janetos, N. S.
Le Blanc, J. R. See Fenstermacher, J. E.
Leblond, M. See Barton, J. L.
Le Bras, L. R. See Christenson, R. M.
Le Bras, L. R., and Ostrowski, J. S. Treatment of electrodeposition bath, P (8) 194*d*.
Le Bras, L. R., and Zwack, R. R. Combined electrodialysis and ultrafiltration of an electrodeposition bath, P (8) 192*e*.
Le Can, C. J. P. F., and Steinmaier, W. Semiconductor devices with more than one semiconductor circuit element in one body, P (2) 42*b*.
Le Cars, Y., Thery, J., and Collongues, R. Range of existence and stability of β- and β''-Al_2O_3 in the system Al_2O_3-Na_2O. Study by *X* rays and electron microscopy, (11) 282*a*.
Lechaton, J. S. See Havas, J.
Leclerc, P. See de Cremoux, B.
Le Clerc de Bussy, J. M. Y. Electrical high-temp. melting furnace, P (8) 192*g*.
Lecocq-Robert, A. See van Lierde, W.
LeCraw, R. C. See Kurtzig, A. J.
Lecrivain, L. See Fleurence, A.
Ledbetter, J. O. Air Pollution: Part A, Analysis, B (8) 212*e*.
Le Doussal, H. Comparative interlaboratory tests on thermal conductivity of refractories, (7) 172*j*. European interlaboratory tests of thermal expansion of electrofused Al_2O_3, (2) 44*i*. Interlaboratory tests of mechanical strength of firebricks, (2) 36*c*. Tests of after-variations in dimensions of a dense refractory, (2) 36*j*.
LeDoux, R. A. See Golliher, W. R.
Ledran, J. P., and Guiochon, P. Negative-temp.-coeff. resistors in the form of thin [SiC] layers and method of mfg., P (3) 66*d*.
Le Duc, J. M. See Andre, E.
Le Duc, J. M., and Deyris, E. Method of mfg. a crystalline compound, P (4) 89*d*.
Lee, A. E. Glancing incidence diffraction studies of TiC single-crystal surfaces in ultrahigh-vacuum environment, (10) 259*i*.
Lee, B. Y. S., and Gonzales, J. Process for neutralization of amorphous B, P (8) 204*a*.
Lee, D. B. Methods of etching semiconductor body surfaces, P (6) 139*g*.
Lee, D. M. See Kumbhare, P. R.
Lee, D. W. See Haggerty, J. S.
Lee, Eung Sang. See Hamano, Kenya.
Lee, G. M. C., and Jones, W. J. D. Fatigue properties of vitreous enameled Armco iron, (5) 105*b*.
Lee, Hanju, and Chi, Dongsuk. Ultrastable 3 Å molecular sieve, P (10) 257*j*.
Lee, H. A., Jr., and Rapp, C. F. Er_2O_3/Yb_2O_3-doped glass lasers, P (8) 192*g*. Li_2O-SiO_2 glass laser containing various other alkali oxides, P (5) 107*j*. Li_2O-SiO_2 glass laser containing various alkaline earth oxides, P (5) 107*j*.
Lee, H. M., and Alcock, C. B. Cation diffusion in UO_2-based solid solutions as a function of stoichiometry, (9) 228*f*.
Lee, H. R. See Dee, P. L.
Lee, K. EuO films with enhanced magnetic exchange, P (10) 250*b*. See Coburn, J. W.; Suits, J. C.
Lee, R. H. C. See Law, H. B.
Lee, Sung Ki. See Cooke, V. F. G.
Lee, W. S. Porcelain enamels for self-cleaning cooking oven, P (9) 216*a*.
Leece, J. Corrosion of Armourplate glass windows by high-pressure demineralized H_2O, (11) 268*f*.
Leech, R. J. See Austin, M. J.
Leedy, H. M., Jr. See Portnoy, W. M.
Leedy, H. M., Jr., and Tolar, N. J. Ti-W-Au contacts for semiconductor devices, P (1) 15*b*.
Leers, K. J. Application of nondestructive mechanical vibration testing to nonmetallic inorganic industrial materials, (9) 230*h*.
Lees, D. G. See Derry, D. J.
Lefever, R. A. (editor). Preparation and Properties of Solid State Materials (Vol. 1) Aspects of Crystal Growth, B (2) 52*i*. See Baughman, R. J.
Leff, J., and Roberts, A. A. Reliability of Al and Al alloy lands, P (3) 67*f*.
Lefkowitz, I. See Cowley, R. A.
Le Flem, G. See Fava, J.
Leger, L. F. See Plumat, E.
Leger, L. F. and Lelong, J. Coating method for [compressive] strengthening vitreous and vitrocrystalline bodies, P (4) 35*j*.
Legg, J. B. System means for controlling the fuel supply to burners of a glassware burn-off machine, P (2) 35*a*.
Le Hair, J. P. Determination of textural parameters using gas adsorption isotherms, (7) 173*b*.
Leheny, R. F., and Shay, J. L. Near-ir detector employing $CdSnP_2$, P (4) 89*f*.
Lehman, H. S. See Barson, F.
Lehmann, H. Innovations in testing of ceramic materials, (7) 173*i*. See Salge, H.
Lehmann, H., and Dietrich, H. Determination of bloating properties of ceramic raw materials, (5) 116*b*.
Lehmann, H., Ohnemueller, W., and Solf, A. Production and properties of synthetic wollastonite for use in ceramic bodies, (1) 10*h*.
Lehmann, H., and Probst, R. Determination of the adhesive strength of the combination tile-mortar-concrete, (5) 110*g*.
Lehmann, M. S. See Larsen, F. K.
Lehmann, W. Method for stabilizing alkaline-earth metal sulfide phosphors, P (3) 66*g*.
Lehmann, W., and Ryan, F. M. Cathodoluminescent CaS compositions with improved fast decay characteristic, P (10) 249*i*.
Lehnigk, S. H. See Steverding, B.
Lehovec, K. Array comprising row of electro-optical elements and associated row of semiconducting microcircuits located on adjoining faces of a parallelepipedal slab, P (4) 87*e*. Diffractive image-forming means integrated into semiconducting devices, P (6) 137*b*. Electrooptical microtransducer comprising diffractive element monolithically integrated with photoelectric device, P (9) 225*g*.
Lehovec, K., Hielscher, F. H., and Preier, H. M. Solid-state vidicon structure, P (9) 228*b*.
Lehrer, W. I. Process of forming an As sulfide mask, P (3) 66*j*.
Leibenzeder, S. See Merkel, H.
Leibowitz, H. A. Method and apparatus for removal of bubbles from sheet glass overflow forming surfaces, P (1) 4*h*.
Leimer, G. See Kieffer, R.
Leinkram, C. Z. Process for bonding chip devices to hybrid circuitry, P (10) 252*j*.
Leinkram, C. Z., and Prom, R. L. Microelectronic interconnection substrate, P (1) 13*j*.
Leirvik, R. M. Nuclear fuel rod, P (10) 254*b*.
Leite, R. C. C., Scott, J. F., and Damen, T. C. Multiple-phonon resonant Raman scattering in CdS, (6) 150*j*.
Leith, F. A., and Guild, C. H., Jr. Diode having a voltage variable capacitance characteristic and method of making, P (4) 87*b*.
Leitnaker, J. M. See De Luca, J. P.; Spear, K. E.
Leitnaker, J. M., Potter, R. A., Spear, K. E., and Laing, W. R. Lattice parameter of U(C,N) as a function of composition, (4) 91*g*.
Leitner, K. See Remmers, K.
Leitz, E., Broemer, H., and Meinert, N. La borosilicate optical glass, P (2) 34*j*.
Leliaert, R. M., and Snyder, C. A. Apparatus for filtering suspended solids from gaseous medium and for removal of filter cake from filter elements, P (1) 16*i*.
Lell, E. See Stroud, J. S.
Lelong, J. See Leger, L. F.
Lemeshev, V. G. See Poluboyarinov, D. N.
Lemmens, J. C. See Geus, J. W.
Lemons, K. E. See Irving, S. M.
Lenel, F. V. See Nayar, H. S.
Lengersdorff, N. Problems in the direct [open] firing of sanitary ware, (7) 165*h*.
Lengyel, I. See Duma, G.
Lennertz, H. E. Flow investigations of glass in a model tank with special consideration of the transport flow (I) experimental procedure and thermal effect of the batch blanket; (II) influence of a barrier, the throughput, and the throat width, (7) 159*j*.
Lent, W. E. See Gates, L. E., Jr.
Lent, W. E., and Gates, L. E., Jr. SiO_2-clay tooling material for welding and brazing operations, P (4) 80*b*.
Lenz, A. See Keddeinis, H.
Lenzing, J. R. See Causey, D. R.
Lenzlinger, M. Reachthrough or punchthrough breakdown for gate protection in MOS devices, P (6) 139*j*.
Leon, A. See Wilcox, W. R.
Leonard, D. A. Using lasers to monitor stack emissions, (11) 277*c*.
Leonard, R. B., and Searcy, A. W. Variation of vaporization rates with orientation for basal planes of ZnO and CdS, (6) 152*j*.
Leonard, R. J., and Herron, R. H. Significance of redox reactions in BOF refractories, (2) 36*g*.
Leonard, R. J., and Ulmer, G. C. Impregnated fired refractory shape and method of producing, P (9) 222*h*.
Leonesio, R. B. Fracture and healing effects in mica crystals, (10) 259*h*.
Leonova, E. N. See Pirogov, A. A.
Le Page, M. A., and de Vries, A. J. Chromatographic separation with porous SiO_2, P (10) 255*h*.
Lepeshova, V. I. See Budnikov, P. P.
Lepomaa, L. A., and Roisko, T. O. Method of preparing CaF_2 and soluble phosphate from F-containing phosphate rock, P (11) 279*h*.
Lepone, J. J. See Kulicke, F. W., Jr.
Lepper, H. A., Jr., and Rodgers, R. B. Nuclear methods for determining the H_2O content and unit wt of fresh concrete, (7) 157*d*.
Lepselter, M. P. Method of fabricating semiconductor contacts, P (5) 113*f*. Modifying barrier layer devices, P (9) 226*j*. Passivated semiconductor devices, P (3) 202*a*. See Berglund, C. N.; Byrnes, P. A., Jr.; Fritzinger, L. B.
Lepselter, M. P., and Ligenza, J. R. Barrier layer devices and methods for their manufacture, P (2) 39*c*.
Lepselter, M. P., and MacRae, A. U. Fabrication of an IGFET involving ion implantation, P (7) 168*h*. High-frequency transistors with shallow emitters, P (1) 12*f*.
Lepselter, M. P., and Waggener, H. A. Method for producing passivated *pn* junctions by ion beam implantation, P (2) 41*a*, P (3) 66*d*.
Lerner, M. L. Process of etching a shadow mask, P (9) 227*i*.
Lertes, K. Oxidizing method and apparatus, P (7) 169*i*.
Leschinskii, D. A. See Evstrop'ev, K. S.
Lesemann, G. Method and instrument for determining the moisture content and/or temp. of moving material, P (3) 70*d*.
Lessoff, H. Comments on "Influence of liquid environments on the strength of ferrite memory cores," (7) 167*g*.
Lester, W. C., Nuccio, C., and Ward, E. S. Cathode-target assembly for rf sputtering

apparatus, P (4) 87*i*. Continuous vacuum process apparatus, P (7) 168*b*.

Le Sueur, J. T. See Chapman, G. C.

Leung, A. F. See Stafsudd, O. M.

Leung, A. F., and Wong, E. Y. Absorption spectrum of NpO_2^{2+} in $CsUO_2(NO_3)_3$, (6) 144*i*. EPR of NpO_2^{2+} in $Cs_2UO_2Cl_4$ and $CsUO_2(NO_3)_3$, (5) 120*j*.

Leusden, C. O. P. Influence of molding on the properties of bricks and tiles, (4) 83*i*.

Leuthold, C., and Leuthold, F. Protective brick against radioactive radiations [design], P (2) 37*e*.

Leuthold, F. See Leuthold, C.

Levand, V. A., Jr., Thomasson, G. I., and Holcomb, R. H. Sb borate glass compositions, P (7) 161*e*.

Levandowsky, L., and Jacqmareq, M. Review of methods for testing wear of refractories by molten metals, (7) 173*e*.

Levelink, H. G. See van den Berg, H.

Levenberg, N. E. See Timofeev, M. M.

Levi, C. A. Method of producing semiconductor devices, P (9) 226*g*, P (10) 252*c*.

Levin, D. I. See Nikulina, L. N.

Levin, D. I., and Basin, E. V. Measuring the whiteness of porcelain, (8) 197*i*.

Levin, N. D. Method of assembling electron discharge devices having sensitive components housed in a glass envelope, P (2) 34*b*.

Levin, S. See Wiener, E.

Levine, P. A., and Liu, Shing-Gong. Compact high-power, high-efficiency Si avalanche diode L-band oscillator, P (5) 112*g*.

Levinskaya, M. Kh. See Portnoi, K. I.

Levinskii, Yu. V., Arabei, B. G., and Prokof'ev S. A. Kinetics of boriding and its effect on the mechanical properties of Ni, (10) 259*i*.

Levinson, A. A. See Bavliss, P.

Levinstein, H. J., Robbins, M., and Capio, C. Crystallographic study of the system $FeCr_2O_4$-Fe_3O_4($Fe^{2+}Fe_x^{3+}Cr_{2-x}O_4$), (4) 95*j*.

Levitt, S. R., Blakeslee, K. C., and Condrate, R. A., Sr. Infrared spectra and laser-Raman spectra of several apatites, (7) 178*f*.

Levy, H. M. See Bruce, J. A. G.

Levy, N., Jr. See Rettew, R. R.

Lewey, S. See Mason, G. W.

Lewicki, S. Prefabricated and prestressed modular furnace units, P (9) 232*e*.

Lewiner, J., Meijer, P. H. E., and Wigmore, J. K. Detection of Al_2O_3:Fe^{2+} by acoustic paramagnetic resonance, (5) 119*g*.

Lewinson, L. J. Color TV picture tube with metallic film coating on funnel portion, P (3) 57*j*.

Lewis, B. H. Portable electric kiln for use with enameling kits, P (11) 266*e*.

Lewis, D. See Bailey, J. E.

Lewis, D. W. Properties of AlN derived from $AlCl_3$-NH_3, (9) 238*c*.

Lewis, M. H. See Billingham, J.

Lewis, R. M. See Alper, A. M.

Lewis, T. W., II. See Nell, D. J.

L'Haridon, P. See Gaude, J.

Li, J. C. M. See Liu, G. C. T.

Li, J. H., and Uhlmann, D. R. Note on the largest viscosity measurable in finite experimental times, (3) 56*g*.

Li, Pei-Ching. See Ali, M. A.

Liander, L. E. See Goldmann, L. S.

Lias, N. C. See Kolb, E. D.

Libby, C. C., and McDaniel, R. C. Method and apparatus for controlling frequency of piezoelectric transducers, P (10) 251*i*.

Libera, J. J., and Puetz, E. J. Preparation of TiO_2 pigment having the crystal structure of anatase, P (2) 46*b*, P (3) 71*f*.

Liberman, H. E. See Hoogendoorn, H. M.

Liberman, I. A. Method for preparing a rare-earth phosphor, P (7) 169*e*.

Librant, Z. M. See Bailey, J. E.

Lichte, C. L. SiC seal for an earth-boring bit, P (1) 20*j*.

Lichte, N. Holder for electric lamps with a glass base cap, P (10) 244*e*.

Lichtenberger, G. J., and Addison, J. R. F- and X-band spectroscopy on Fe^{3+} in rutile, (5) 120*e*.

Lider, V. V. See Ganiev, R. M.

Lidorenko, N. S., Kagan, A. S., Chizhik, S. P., Koval'skii, A. E., Prokoshina, S. M., and Sokolov, O. V. "Packing" texture of brittle materials, (10) 247*c*.

Lidorenko, N. S., Landsman, A. P., Strekkov, D. S., Zaitseva, A. K., Zadde, V. V., and Kosarev, V. S. Semiconductor photoelectric generator, P (7) 170*c*.

Lieberman, M. L. Amorphous Bi oxide-containing coatings, P (10) 243*e*.

Liebl, H. Ion lens to provide a focused ion, or ion and electron beam at a target, particularly for ion microprobe apparatus, P (3) 70*b*.

Liebowitz, H. (editor). Fracture—An Advanced Treatise (Vol. 3) Engineering Fundamentals and Environmental Effects, B (3) 76*e*.

Liepert, R. See Kaufmann, P.

Ligenza, J. R. See Lepselter, M. P.

Light, L. L. See Green, L. Q.

Light, T. B. See Gereth, R. K.

Lightowlers, E. C. See Collins, A. T.; Williams, A. W. S.

Ligorati, F. See Barilli, F.

Likhachev, G. M. See Koren, M. G.

Likhoradov, A. P., Teder, L. I., Chigral, I. D., Kolpakov, S. V., Pozhivanov, A. M., Ustalov, V. E., Gorbenko, Yu. E., Matveev, E. V., Ryazantsev, V. D., Balaban, G. I., Karklit, A. K., Borisov, V. G., Andryushchenko, A. I., and Shapiro, E. Ya. Experience with increasing lining life of O converters, (8) 195*f*.

Lilburne, M. T. Development of the bubble technique for the measurement of the surface energy of solids, (5) 119*h*; reply to comments on, (5) 119*j*.

Liljeholm, S. Arrangement for delivering predetermined quantities of liquid and solid material, P (9) 229*g*.

Lillebuen, B. See Grjotheim, K.

Lim, E. See Herzog, A. H.; Schmidt, J. G.

Limar, T. F., Maldukova, T. P., Mudrolyubova, L. P., and Prokhvatilov, V. G. Formation of solid solutions in the system $LaAlO_3$-$CaTiO_3$ and their electrical properties, (9) 235*d*.

Limberis, N. A. Interior plaster coating composition, P (3) 54*b*.

Liminga, R. See Tellgren, R.

Lin, Chinyueh, Chow, L., and Miller, K. J. Vapor phase etching of GaAs in the H_2-H_2O flow system, (9) 239*d*.

Lin, H. C., and Yu, K. K. Semiconductor integrated circuit having MIS and bipolar transistor elements, P (2) 42*c*.

Lin, I. J. See Somasundaran, P.

Lin, Ruey-Yuan. See Economy, J.

Lin, S. C. H., and Joshi, M. L. Structure of SiO, (2) 50*b*.

Lincoln, J., and Tettenhorst, R. Freeze-dried and thawed clays, (5) 120*j*.

Lincoln, R. L. Method and apparatus for cooling cement clinker, P (9) 215*g*.

Lind, E. L. See Cherin, P.

Lind, R., and Price, N. Graphite moderator structures for nuclear reactors, P (1) 16*c*.

Lind, R. S. Indium alloy seal and CRT envelope employing such seal, P (4) 82*e*.

Lindberg, J. D., and Snyder, D. G. Diffuse reflectance spectra of several clay minerals, (9) 234*i*.

Lindblom, R. O. Vapor phase metal plating process, P (6) 135*h*.

Linderer, T. B. See Spear, K. E.

Lindeqvist, P. T. Fiber optic output faceplate assembly system, P (4) 87*j*.

Lindgren, P. H. See Brantte, A.

Lindholm, R. C., and Finkelman, R. B. Calcite staining—semiquantitative determination of ferrous Fe, (8) 204*h*.

Lindow, R. Natural gas in competition on the energy market, (8) 206*e*.

Lindqvist, O. Crystal structure of $Te(OH)_6$ (monoclinic), (5) 119*d*. Crystal structures of $CuTeO_3$ and $CuTe_2O_5$, (1) 21*f*. See Philippot, E.

Lindsay, J. The potter as demiurge, (11) 266*d*.

Lindsay, J. G. Calcined bauxite, (2) 46*a*.

Lindsley, J. F., and Sanborn, W. E. Process for preparing Al_2O_3-coated SiO_2 catalyst material and the material so prepared, P (4) 94*i*.

Lindstrom, C. E. Method of mfg. synthetic diamonds, P (7) 155*f*.

Lines, M. E. Statistical theory for displacement ferroelectrics (I); (II) specific heat and soft-mode-frequency calculations; (III) comparison with experiment for Li tantalate, (5) 124*f*.

Lingl, H. M. L., Jr. Method for unloading and blending layered stacks of bricks or similar articles, P (1) 6*c*.

Lingl, J. Apparatus for producing [cutting and stacking] bricks, P (1) 6*c*. Method and apparatus for positioning material such as brick blanks in stacks, P (3) 60*b*.

Linke, A. See Knebel, E.

Linnett, J. W. See Rahman, M. L.

Linnett, J. W., and Rahman, M. L. Recombination of atoms at surfaces (XIII) O atoms on $Zn_xFe_{3-x}O_4$ and $Ni_xFe_{3-x}O_4$, (1) 24*j*.

Linson, D. H. Molded epoxy resin electrical insulating body containing Al_2O_3 and SiO_2, P (6) 136*c*.

Linstedt, H., and Bellon, S. Process for providing contacts on a semiconductor body, P (4) 90*e*.

Linstrom, R. E. See Winget, J. O.

Lint, P. J. Glazing of building brick, (4) 83*g*.

Linz, A. See Belruss, V.; Yamada, Yoshito.

Linzer, F. D. Apparatus for simultaneously supporting, cooling, and shaping glass sheets and the like, P (9) 218*d*.

Liou, J. G. *P-T* stabilities of laumontite, wairakite, lawsonite, and related minerals in the system $CaAl_2Si_2O_8$-SiO_2-H_2O, (1) 24*f*.

Lipetz, N. See Agrios, J. P.

Lipinski, D. See Schwiete, H. E.

Lipka, S. See Gebert, H.

Lipovskaya, A. G. See Kryzhanovskaya, I. A.

Lipp, G. D., Rahe, V., and Roberts, L. B. Apparatus for and method of orienting cords in a molten glass downdraw bowl, P (8) 192*i*.

Lippert, W. See Reichelt, B.

Lipsicas, M., Mattis, D. C., Lord, E., and Kornblit, A. Negative resistance and modulation in metal oxides ("Moxies"), (6) 150*j*.

Lipson, H. G. See Dickinson, S. K.

Liptay, G. (editor). Atlas of Thermoanalytical Curves (Vol. 1), B (6) 153*i*.

Lishanskii, B. A., Mikhailov, N. V., and Rebinder, P. A. Rheological properties of disperse systems during vibration, (7) 180*g*.

Liskowitz, J. W. Measuring the concentration of solid particles suspended in various regions in a fluid using polarized light, P (5) 116*f*. Particle-size-distribution measurement using polarized light of a plurality of wavelengths, P (7) 174*a*. Suspended particle concentration determination using polarized light, P (2) 45*b*.

Lisovaya, E. D. See Livson, Z. A.

Lisovskaya, N. B. See Babich, M. M.

Lisovskii, A. F. See Babich, M. M.

Lissant, K. J. Method of transporting bulk solids, P (3) 60*d*.

List, F., and Alfs, H. Process of improving formed SiO_2 gels, P (1) 20*g*.

Litovskii, E. Ya., Landa, Ya. A., and Mil'shenko, R. S. Thermal conductivity factors of aluminosilicate refractories at 200°–1600°C, (8) 196*e*.

Litt, M. H., and Aharoni, S. M. Fe carbides—preparation from C-rich matrix, (1) 7*a*.

Littell, H. E., Jr. Integral transparent safety glass armor unit, P (9) 219*f*.

Little, C. M., and Murie, R. A. Preparation of AlN, P (1) 9*e*.

Little, E. L., Jr., and Wolf, J. D. Process for making ferromagnetic metal powders, P (8) 202*e*.

Littler, E. S. See Binns, D. B.

Littleton, H. K. Glassblowing—a Search for Form, B (7) 183*j*.

Littlewood, P. A. Introduction to metal enameling, (1) 2*b*.

Litvak, M. M. See Lao, B. Y.

Litvan, G. G. Phase transitions of adsorbates (III)—heat effects and dimensional changes in nonequilibrium temp. cycles; (IV) mechanism of frost action in hardened cement paste, (2) 48*g*.

Litvinova, E. I. See Pevzner, B. Z.

Liu, G. C. T., and Li, J. C. M. Strain energies of disclination loops, (5) 124*h*.

Liu, Lingun. Dense modification of BaO and its crystal structure, (5) 119*d*.

Liu, Shing-Gong. See Levine, P. A.

Livezey, J. P., and Rosser, D. B. Unitary high-power semiconductor subassembly suitable for mounting on a separable heat sink, P (7) 170*h*.

Livshits, L. I., and Smushkov, I. V. Optical aging of LiF crystal ceramics, (8) 191*i*.

Livson, Z. A., and Lisovaya, E. D. Effect of additives on the strength of kaolin briquet, (8) 197*c*.

Llubimov, E. M. See Rabodzei, N. V.

Lloyd, A. J. Plunger for bottle-making machine, P (9) 219*h*.

Lloyd, M. K. See Conlev, R. F.

Lloyd, P. See Hannon, J. J.

Lloyd, R. H. F. Integrated circuit having lightly doped epitaxial collector layer surrounding base and emitter elements and heavily doped buried collector layer in contact with the base element, P (5) 112*i*. Integrated clamping circuit, P (7) 169*a*.

Lloyd, R. R. Method of producing anhydrous Mg chloride, P (1) 9*d*.

Lo, J. M., Gungle, W. C., and Waymouth, J. F. Arc discharge lamp including means for cooling envelope surrounding an arc tube, P (3) 57*g*.

Loasby, R. G. See Davey, N.

Loasby, R. G., Davey, N., and Barlow, H. Enhanced-property thick-film conductor pastes, (11) 273*f*.

Lobachev, A. N. (editor). Hydrothermal Synthesis of Crystals, B (1) 27*a*.

Lobasenko, I. G. See Kryzhanovskaya, I. A.

Lobb, D. R. See West, R. N.

Loch, W. See Striebel, W. K.

Locher, F. W., and von Seebach, H. M. Influence of adsorption on industrial grinding, (7) 156*j*.

Locke, R., Jr. Power control for crystal growing, P (3) 66*i*.

Lockett, G. E. See Rennie, C. A.

Lockwood, F. P. Estimation of furnace structural heat losses—correction, (2) 45*e*.

Locsei, B. Corrosion resistance of crucibles made of mullite, (5) 109*b*. Molten Silicates and Their Properties, B (2) 51*j*.

Lodde, J. See Goto, K.

Loeff, A. Semiconductor wafer air slide with controlled wafer motion, P (1) 14*b*.

Loeffler, F. Compression and deaeration of powders, P (4) 92*h*.

Loeffler, K. H. Thermionic cathode for electron beam apparatus, P (4) 9*c*.

Loefgren, P. Crystal structure of $Rb_2Cr_2O_7$ ($P2_1/n$), (6) 146*c*.

Loefgren, P., and Waltersson, K. Crystal structure of $Rb_2Cr_2O_7$($C2/c$), (6) 146*b*.

Loehr, C. E. See Darr, D. E.

Loepfe, E. Method and apparatus for detecting a relative movement between 2 bodies being in frictional contact with each other, P (10) 251*i*.

Loescher, J. See Seyfarth, H. H.

Lofberg, J. A. S., and Davidson, P. Bottom brick for ingot molds, P (11) 272*b*.

Loftus, L. T., Jr. See Pick, E. G.

Logan, J. S. Rf sputtering method and apparatus for producing insulating films of varied physical properties, P (8) 67*g*. See Collins, R. H.

Logan, R. A., Rosenzweig, W., and Wiegmann, W. Electroluminescent junction semiconductor with controllable combination colors, P (1) 12*j*.

Logan, R. A., White, H. G., and Wiegmann, W. Electroluminescent *pn* junction diodes with nonuniform distribution of isoelectronic traps, P (6) 137*c*.

Loher, R. T. See Swanson, A. B.
Lohner, E. Automation in the brick and tile industry, (2) 35*d*.
Loichenko, V. Ya. See Sheiko, I. N.
Loisel, M. See Fleurence, A.
Lommel, J. M. See Chen, Arthur C. M.
Lonadier, F. D., and Kershner, C. J. Radioactive heat source, P (10) 254*a*.
Loney, R. A., Himmelberg, G. R., and Coleman, R. G. Structure and petrology of the Alpine-type peridotite at Burro Mountain, Calif., (1) 20*i*.
Long, B. Forming glass sheets in a mold, (11) 268*d*. Method and apparatus for heat-treating glass sheets on molten metal, P (6) 133*h*.
Long, D. M. Method for drying glass fiber forming packages, P (2) 34*c*.
Long, G. C content analysis, P (10) 255*h*.
Long, G. E., III, Grove, F. D., and Bartch, D. W. Li silicate glare-reducing coating and method of fabrication on a glass surface, P (4) 82*f*.
Long, J. V. High-efficiency materials, (2) 36*b*.
Long, R. E. See Gebauer, J.
Long, S. A., and Blumenthal, R. N. Ti-rich nonstoichiometric $BaTiO_3$ (II) analysis of defect structure, (1) 12*a*.
Longo, F. N., and Dittrich, F. J. Flame spray powders and process with Al_2O_3 having TiO_2 bonded to the surface thereof, P (1) 3*b*.
Longo, F. N., and Patel, M. S. Ceramic clad flame spray powder, P (7) 157*j*.
Longo, H. E., Keller, W., and Vogel, C. H. Method of growing rod-shaped dislocation-free monocrystals, particularly of Si, by crucible-free floating-zone melting, P (7) 169*i*.
Longo, J. M. See Kafalas, J. A.
Longo, V., and Podda, L. CeO_2-ZrO_2-CaO system—solid state phase relations and related structures, (4) 95*e*. CeO_2-ZrO_2-MgO system—solid state phase relations and related structures, (4) 95*f*. Solid state phase relations in the system CeO_2-ZrO_2-Al_2O_3, (4) 98*f*.
Longo, V., and Roitti, S. Solid state phase relations in the system CeO_2-ZrO_2, (4) 98*d*.
Look, D. C. NMR determination of the conduction-electron hyperfine interaction in crystalline CdO, (5) 122*h*.
Loop, F. M. Treatment of electrodeposition bath, P (8) 194*d*.
Loop, F. M., and Bosworth, F. C. Treatment of an ultrafiltrate derived from an electrodeposition process by reverse osmosis, P (8) 194*c*.
Loose, G. H. Fused-substrate resistor, P (3) 65*a*. Method for forming an electroconductive coating resistor, P (2) 41*d*.
Loosjes, R. New type of a silk-screen machine to decorate arbitrarily shaped articles, (4) 85*i*.
Lopatnikova, L. Ya. See Blonskaya, V. M.
Lopker, E. B. Method for filtration of slurries, P (2) 44*d*.
Lorbach, H., and Salares, R. Radiometric assay of U ores based on their high energy γ spectrum, (3) 68*j*.
Lord, E. See Lipsicas, M.
Lord, J. S. Automatic 100% line adjustment of spectrophotometers, P (6) 142*d*.
Lorenz, M. R. Liquid epitaxy method of fabricating controlled band gap GaAlAs electroluminescent devices, P (10) 251*a*.
Lorenz, M. R., and Nethercot, A. H., Jr. Semiconductor recombination radiation device, P (2) 42*e*.
Loriers, J. See Denis, J. P.
Lortholary, P. See Goursat, P.
Losee, D. L., and Wolf, E. L. Tunneling spectroscopy of CdS Schottky-barrier junctions, (6) 152*g*.
Lotarev, V. A. See Kestner, O. E.
Lothe, J. See Nishioka, Kazumi.
Louderback, A. W., and Zook, M. A., Jr. Antireflection coatings, P (1) 3*c*.
Loughnan, F. C. Refractory flint clays of the Sydney basin, (8) 206*i*.
Loughridge, F. A. See Anderson, J. W.
Loughridge, F. A., Matheson, W. G., and Passmore, E. M. Seal arrangements for lamps, P (10) 245*f*.
Loughridge, F. A., and Ziebell, R. J. Mfg. striation-free quartz tubing, P (1) 4*b*.
Loukes, D. G. Method of reshaping and ion-exchanging glass, P (5) 107*e*. See Edwards, A.; Robinson, A. S.
Loukes, D. G., and Edwards, A. Coating of glass in float glass method and apparatus, P (8) 192*d*. Float glass mfg. apparatus, P (8) 192*h*. Production of float glass having an oxidized metal-modified surface, P (10) 245*e*.
Loukes, D. G., and Hay, A. E. Method and apparatus for producing float glass by oxidizing glass-forming elements, P (1) 4*g*.
Loukes, D. G., and Lawrenson, J. [Electrolytic] treatment of hollow glass articles, P (11) 270*e*.
Loukes, D. G., and Maltman, W. R. Method and apparatus for producing coated flat glass, P (3) 59*a*. Method and apparatus for producing glass having a metallic surface finish, P (4) 82*a*.
Loukes, D. G., Robinson, A. S., and Lawrenson, J. Method and apparatus for producing coated flat glass, P (3) 59*a*.
Loup, J. P. See Odier, P.
Louvrier, J. See Baron, A.
Lovatt, W. J. Supporting structures for use in firing pottery, P (11) 272*g*.
Love, G. See Flegmann, A. W.
Lovelace, B. K. See Waters, W. P.
Lovelace, J. B. See Nalley, C. E.
Lovell, D. R. See Dixon, K. G. O.
Lovelock, J. E., and Simmonds, P. G. Atmospheric sampling devices, P (8) 205*j*.
Lovetskaya, G. A. See Fedorov, P. I.
Lovygin, B. A. See Voronchikhina, T. P.
Low, G. M. Atmospheric sampling devices, P (8) 205*j*. Preparation of high-purity CuF_2, P (1) 20*f*.
Low, N. M. P. Grain growth in polycrystalline YIG, (8) 209*d*.
Low, N. M. P., and Major, A. L. Methods of preparation of rare-earth trifluoride up-conversion phosphors, (6) 136*i*.
Low, W. See Kiro, D.
Lowe, D. See Gaskell, P. H.
Lowe, I. J. See Magee, J. H.
Lowe, I. R. G., Hughes, B. P., and Walker, J. Diffusion of H_2O in concrete at 30°C, (5) 102*h*.
Lowrison, G. C. Design and application of crushers (9) 232*h*. Intensive mixing, (9) 229*i*.
Loxley, T. A., Webb, J. M., and Barber, W. G. Process for redrawing SiO_2 glass rods, P (7) 162*i*. Wafer boat, P (5) 107*i*.
Loye, N. Li ferrite composition for magnetic memory elements and mfg. process, P (2) 40*g*.
Lubart, N. D., and Vora, M. B. Semiconductor resistor with uniform current distribution at its contact surface, P (4) 90*f*.
Luby, C. S. See Chin, J.; Goeddel, W. V.
Lucas, J. M. See Luff, P. P.; Simpson, A. W.
Lucas, J. W. (editor). Heat Transfer and Spacecraft Thermal Control, B (1) 27*j*.
Lucas, R., and Miller, J. P. Rotor for a roll crusher, P (6) 144*e*.
Luce, J. W., and Morrette, R. A. Automatic sheet stacker, P (4) 81*j*.
Luckey, G. W. Mixed alkaline earth sulfate phosphor compositions, P (7) 169*e*. Preparation of phosphors by precipitation from solution, P (9) 227*h*.
Luckie, P. T. See Austin, L. G.
Ludeke, R. See Esaki, L.; Howard, W. E., Jr.; Tsu, R.
Ludwig, G. W. See Kingsley, J. D.
Ludwig, G. W., and Kingsley, J. D. Efficiency of cathode-ray phosphors (I) measurement, (9) 224*c*.
Luedeman, R. T. See Busch, R. E.
Lueneberg, H. See Zagar, L.
Luethi, B. See Moran, T. J.
Lufcy, G. H. Composition and method for the production of ceramicly bonded basic refractories, P (4) 84*h*.
Luff, P. P., and Brosselard, E. Thickness dependence of surface coercivity in polished magnetic oxide platelets, (5) 125*d*.
Luff, P. P., and Lucas, J. M. Cylindrical magnetic domain propagation in $Sm_{0.85}TbO_{0.45}FeO_3$ platelets possessing high surface coercivity, (7) 176*i*.
Luginina, I. G. Ca carbonate-silicate in calcination products and rotary kiln coatings, (8) 185*j*.
Luginina, I. G., Klassen, V. K., and Klassen, A. N. Thermal analysis of cement kiln samples with simultaneous determination of their electrical conductivity, (8) 188*f*.
Luhleich, H. See Drittler, K.
Luhr, H. P. Effect of ignition loss of fly ash on the quality of ash cements, (2) 30*h*.
Luiten, W., Westendorp, F. F., and de Kort, G. M. A. J. Method of densifying magnetically anisotropic powders, P (2) 41*b*.
Lukashenko, G. M. See Eremenko, V. N.
Lukatskaya, L. A. See Butt, Yu. M.
Lukes, F. Optical constants of GaAs, (8) 209*i*.
Lukes, J. A. See Ryan, J. H.
Lukics, G. Connection between specific energy consumption and kiln output with various vols. of air drawn from the cooling zone of tunnel kilns, (11) 279*c*. Relation of specific energy consumption to kiln output, (2) 45*e*.
Lukin, E. S. See Andrianov, N. T.
Lumley, R. M. See Graham, C. E.
Lund, B. See Gude, K. E.
Lund, D. F. See Allen, C. A.
Lund, G. E. MOS integrated circuit driver system, P (10) 252*e*.
Lundberg, M. Crystal structure of $LiNb_3O_8$, (11) 280*e*.
Lundquist, D., and Widakowich, M. Semiconductor element [for heat pump], P (2) 42*c*.
Lundquist, J. R., and King, R. B. Preparation of high-purity CuF_2, P (1) 20*f*.
Lundstrom, H. Furnace for heat-treating objects under high pressure, P (1) 19*d*, P (4) 93*i*.
Lundy, T. S. See Reimann, D. K.
Lunghofer, E. P. See Cross, L. E.
Luoma, W. L. See Emanuelson, R.
Lupa, Z. See Laskowski, J.
Lupanov, A. F. See Yas, D. S.
Luscombe, G. A. Machine for comminuting glassware and the like [recycle], P (7) 162*h*.
Lush, J. S. Crack-off apparatus for glass articles, P (7) 161*a*.
Lushpaeva, P. P. Colored active additives in decorative cements, (8) 186*c*.
Lussow, R. O., and Wirtz, L. H. Electroless Ni plating on nonconductive substrates, P (5) 112*j*.
Luthi, B., and Pollina, R. J. Sound propagation near the magnetic phase transition in EuO, (6) 151*h*.
Luthi, O. Rotary drum filter, P (10) 254*h*.
Lutz, C. W. Phosphate glass bodies, P (5) 107*f*.
Luxon, J. T., Montgomery, D. J., and Summitt, R. Effect of particle size and shape on the ir absorption of MgO powders, (6) 146*j*.
Luzhnaya, N. P. See Kovaleva, I. S.
L'vova, G. G. See Ponomarenko, N. E.
Lyashkevich, I. M., and Beinard, G. S. Relaxation and polarization characteristics of the H_2O-cement system in a magnetic field, (3) 54*b*.
Lye, R. G. See Hollox, G. E.
Lykova, L. N., and Afonskii, N. S. Investigation of the phase composition of the system Y_2O_3-Ta_2O_5, (1) 23*b*.
Lynch, C. S. Glass-ceramic bodies, and method by B_2O_3 treatment, P (7) 161*h*.
Lynch, G. F., Sayer, M., Segel, S. L., and Rosenblatt, G. Electron and nuclear magnetic resonance in semiconducting phosphate glasses, (5) 105*j*.
Lynch, J. E. Composite ceramic package breakaway notch, P (1) 10*c*. Leadless ceramic package for integrated circuits, P (5) 113*a*.
Lynch, R. W., and Morosin, B. Thermal expansion, compressibility, and polymorphism in Hf and Zr titanates, (9) 239*c*.
Lynd, L. E., Nilsen, A. N., and MacCardle, L. E. Process for beneficiating ilmenite ore, P (10) 257*b*.
Lynskey, P. J. See Stern, D. R.
Lyon, G. See Czeck, J. J.
Lyon, J. K. Antifriction liner for ceramic valve plates of single-handle mixing valve, P (8) 198*d*.
Lyons, S. C. Kaolin product and method of producing, P (4) 94*h*.
Lyons, V. J. See Grochowski, E. G.
Lysenko, A. P. See Vil'f, F. Zh.
Lysenko, L. I. See Shemyakin, V. K.
Lythe, T. W., and Ashworth, E. A. Basic refractories, P (5) 109*f*.
Lyu, S. See Moser, F.
Lyutenko, A. P. Pottery industry (USSR) in the 9th 5-year period, (8) 198*f*.

Maartense, I., and Searle, C. W. Domain wall and magnetoelastic resonances in hematite, (4) 96*e*.
Maas, K. See Schildknecht, H.
McAlister, C. G. See Miller, C. O.
McAllister, P. V., and Cutler, I. B. Thermal grooving of MgO and Al_2O_3, (8) 211*a*.
McAllister, W. A. Ca gallate [luminescent] composition activated by Mn and method of preparation, P (4) 87*g*.
McAllister, W. A., and Sausville, J. W. Zn-Mg silicogermanate phosphor composition and method of preparing, P (6) 140*e*.
McAndrew, J. Differential dispersion measurement of refraction index, (9) 231*a*. Low angle microdiffraction with a 57.3 mm diam. X-ray powder camera, (9) 231*h*.
Macarus, D. P., Upson, L. L., and Wood, R. T. Synthesis of Na faujasite, P (5) 118*b*.
McBride, J. P., McCorkle, K. H., and Pattison, W. L. Production of predominantly crystalline sol of urania, P (4) 91*j*.
McBride, L. E., Jr. Electrothermal time proportioning temp. control, P (1) 18*f*.
McCafferty, W. E. Tamping material, P (9) 228*d*.
McCaldin, J. See Jenkins, R.
McCaldin, J. O. See Mead, C. A.
McCandless, L. C., and Withers, J. C. High-strength high-modulus low-density B silicide monofilaments and method of making, P (1) 9*a*.
MacCardle, L. E. See Lynd, L. E.
McCartan, D. A. See Jones, Isaac P.
McCarthy, G. J. See Greedan, J. E.; Takamori, Takeshi.
McCarthy, G. J., and Roy, R. Gel route to homogeneous glass preparation (II) gelling and desiccation, (1) 3*e*.
McCarthy, G. J., Roy, R., and McKay, J. M. Preliminary study of low-temp. "glass" fabrication from noncrystalline silicas, (1) 3*g*.
McCarthy, J. F. Hot top liner and refractory ring combination for use with metal casing that is hot, P (8) 196*b*. Hot top liner and refractory ring combination for use with metal hot top casing, P (8) 196*b*.
McCarthy, J. J. See Desmond, R. J.
McCauley, J. W., and Newnham, R. E. Origin and prediction of ditrigonal distortions in micas, (4) 98*a*.
MacChesney, J. B. See Cox, D. E.
McClellan, J. R. See Allington, T. R.
McClellan, W., and Stiles, A. B. Heat-treated Bi molybdate and phosphomolybdate-on-TiO_2 catalysts, P (5) 117*f*.
McClure, D. S. See Alig, R. C.
McColm, I. J. See Steadman, R.
McCombs, F. P. See Flautt, M. C.
McCombs, F. P., and Sullivan, J. C. Glass fiber product bonded with terpolymer comprising phenol-formaldehyde–urea-formaldehyde condensation product, P (2) 34*d*.
McConnell, J. D. C. Microstructure and properties of the bonding medium in set cement: restudy of the natural hydrogel, (2) 31*f*.
McConnell, L. W. Method for selectively pro-

jecting refractory material against the lining of basic O furnaces, P (8) 190*e*.
McCorkle, K. H. See McBride, J. P.
McCormack, J. F. See Stahl, F. T.
McCormick, T. H. See Haas, L. A.
MacCragh, A. Extraction of fission product noble metals from spent nuclear fuels, P (10) 253*j*.
McCreary, J. R., Rassoul, S. A., and Thorn, R. J. Enthalpy and entropy of sublimation of $MnCl_2$—entropy and dissociation energy of gaseous $MnCl_2$. Correlation of $\Delta S°$ and $\Delta H°$, (4) 96*c*.
McCreary, W. J., and Court, D. B. Apparatus for coating microspheres with pyrolytic C, P (5) 115*a*.
MacCrone, R. K. See Fahmy, M.; Herman, H.
McCullough, M. J. See Deacon, A. J.
McCurdy, K. G., and Erno, B. P. Kinetics of hydration of Ca_3SiO_4, (7) 156*j*.
McCurrie, R. A. See Donald, I. W.
McCusker, J. H. See Perlman, S. S.
McDaniel, C. L. Phase relations in the CaO-Pt system in air, (9) 237*c*.
McDaniel, C. L., and Schneider, S. J. Phase relations in the CaO-IrO_2-Ir system in air, (10) 260*h*.
McDaniel, C. V. See Elliott, C. H., Jr.; Maher, P. K.
McDaniel, C. V., Baker, R. W., and Rundell, C. A. Cation and thermal stabilization of a faujasite-type zeolite, P (1) 20*a*.
McDaniel, C. V., Maher, P. K., and Pilato, J. M. Process for preparing binderless molecular sieve aggregates, P (7) 175*g*.
McDaniel, R. C. See Libby, C. C.
McDermott, P. S. See Carpenter, D. R.
McDevitt, N. T. Infrared lattice spectra of rare-earth Al, Ga, and Fe garnets, (1) 22*h*.
MacDonald, A. C. X-ray collimator having a fiber optic light source therein for alignment purposes, P (4) 83*b*.
McDonald, B. A., and Dragmire, M. B. Nitride passivation of mesa transistors by phosphovapox lifting, P (4) 89*f*.
McDonald, D. Cooler for rotary kiln, P (6) 143*d*.
McDonald, D. P. Corrosion resisting materials and their applications, (2) 35*i*.
McDonald, J. L. Electrically insulating compositions of dielectric polymer, mica flakes, and silicone resin, P (7) 168*f*.
McDonald, M. P. See Ellis, B.
McDonald, P. F. Ultrasonic paramagnetic resonance of U^{4+} in CaF_2, (5) 125*a*. See Bowden, C. M.
Macdonald, W. J. D. See Duffy, J. A.
McDonald, W. N., and Hogan, W. M. Fiber band regulator for fiber glass pipe winder, P (1) 4*a*.
McDonough, M. S. See Chen, J. H.
McDonough, T. B. See Brown, S. V.
McDougall, J. D. Complementary metal-insulator-silicon transistor pairs, P (8) 200*g*. Ion implantation equipment and processes for semiconductor device mfg., (3) 63*d*.
MacDowell, J. F. See Giffen, J. W.
MacDowell, J. F., and Rittler, H. L. SiO_2-free Ca aluminate glass-ceramic articles, P (4) 83*c*.
Macedo, P. B. See Aggarwal, I. D.; Higgins, T. J.; Provenzano, V.; Simmons, J. H.
McElfresh, P. M. See Parsons, M. L.
McElroy, J. T. Focused piezoelectric transducer and method of making, P (10) 250*e*.
McEntee, J. F. A. See Abbott, C. E.
MacEwan, J. R. See Hastings, I. J.
Macey, A. M. See Prestinini, P.
Macey, J. G. Method for making anhydrous $MgCl_2$, P (6) 144*b*.
Macey, R. G. See Prestinini, P.
McFadden, N. E., Perry, W. M., and Ramge, D. L. Glassmelting pot, P (3) 58*j*.
McFadin, L. W. Pt resistance thermometer circuit, P (2) 45*d*.
Macfarlane, R. M. See Allen, J. W.
McGahan, D. J. See Hills, P. R.
McGee, T. D. See Huang, R. J.
McGee, T. D., and Wirkus, C. D. Mullitization of aluminosilicate gels, (8) 195*a*.
McGibbon, R. C. See Marinace, J. C.
McGinley, C. E., and Hancock, P. Effect of measuring frequency on the electrical conductivity of thoria-based oxides at high temp., (7) 177*i*.
McGovern, R. T. See Faxon, R. C.
McGregor, J. D. See Berger, R. L.
McGrew, G. M. Piezoelectric crystal assembly, P (3) 66*h*.
McGroddy, J. C. High-frequency bulk semiconductor amplifiers and oscillators, P (1) 12*e*.
McGuire, T. R. See Giess, E. A.
Mach, L., and Machova, H. A-fiber, a partial substitution of asbestos in asbestos-cement concrete, (10) 241*g*.
McHargue, C. J. See Yust, C. S.
Machida, Jitsuro, and Tanaka, T. Composite circuit member including an electrostrictive element and condenser, P (3) 64*c*.
Machii, Tetsuo. See Suenaga, Masanobu.
Machlan, G. R., and Thom, C. L. Method and apparatus for mfg. glass films, P (3) 58*j*.
Machova, H. See Mach. L.
McHugh, J. F. Stacked mica capacitors, P (7) 170*d*.
MacInnis, C. See Beaudoin, J. J.
McIntosh, J. D. Specifying the quality of bedding mortars, (9) 221*c*.
McIntyre, G. H., Jr. See Gambale, J. R.
McIntyre, J. E., Piccone, D. E., and Somos, I. SCR with amplified emitter gate, P (3) 67*h*.
MacIntyre, J. S. See Wiesler, M.
MacIver, B. A. Hybrid solid-state voltage-variable tuning capacitor, P (6) 138*a*.
MacIver, B. A., and McKinnon, M. C. MIS voltage variable capacitor with controlled resistivity dielectric, P (3) 65*b*.
Mack, D. L. See Lane, R.
Mack, J. M. See Podiak, R. S.
McKay, J. M. See McCarthy, G. J.
McKearin, H. Notes on stopping, bottling, and binning, (11) 266*d*.
McKee, R. L. Al_2O_3 alloy improves hard-steel grinding, (2) 29*f*.
McKelvey, H. E. See Jendrisak, J. E.
McKenney, R. L., Jr., and Block, J. Process for preparing improved carbide microspheres from ion exchange resins, P (10) 248*e*.
McKenzie, D. H. Laminated transparent bullet-resisting structure, P (3) 58*e*.
MacKenzie, D. J., Accettura, F., and Hansen, P. F. Reinforced thermocouple junction, P (3) 70*f*.
Mackenzie, D. W. See Baird, T.
Mackenzie, F. T., and Gees, R. Quartz—synthesis at earth-surface conditions, (1) 24*j*.
MacKenzie, G. D. See Farrington, G. M.
Mackenzie, J. D. Electronic conduction in noncrystalline solids, (6) 147*c*. See Hammel, J. J.; Kennedy, T. N.; Sakka, Sumio.
MacKenzie, K. J. D. Influence of ac and dc electric fields on the high-temp. reactions of aluminosilicates. A comparative study, (9) 236*f*. Infrared frequency calculations for ideal mullite ($3Al_2O_3$-$2SiO_2$), (3) 73*h*.
MacKenzie, K. J. D., and Duncan, J. F. Calculation of the theoretical disorder entropies of the intermediate phases formed during thermal transformations of aluminosilicate minerals, (2) 47*c*.
Mackenzie, R. C. DTA, (9) 231*b*.
Mackey, H. J. See Stephens, A. E.
McKibben, B. M. See Powell, B. E.
McKinnis, C. L. See Thom, C. L.
McKinnis, C. L., and Cohen, C. I. Semipermeable membranes, P (4) 83*b*.
McKinnon, M. C. See MacIver, B. A.
McKinnon, N. A. See Fehrenbacher, L. L.
McKinstry, H. A. See Gagorik, J. E.
McKinstry, R. G. Glass [vapor] treating tunnel, P (8) 193*c*.
Mackintosh, W. D. See Thompson, D. A.
McKnight, H. G. See Carman, J. N.
McKyes, E., and Yong, R. N. Three techniques for fabric viewing as applied to shear distortion of a clay, (5) 117*c*.
McLaren, R. J. Composite mold and method of making, P (6) 135*e*.
McLary, S. M. Methods and apparatus for applying oxide coating to glass containers, P (2) 37*h*.
McLaughlin, E. P. See Fish, F. H.
McLaughlin, R. D. See Hadeishi, T.
McLean, A. See Dondelinger, J. D.
McLean, D. Grain boundary dislocations—their effect on vacancies and sliding, (6) 148*h*.
McLean, M., and Hondros, E. D. Study of grain-boundary grooving at the Pt/Al_2O_3 interface, (2) 50*c*.
McMahan, W. H. Laser guide construction, P (9) 225*f*. Method of forming a laser tube, P (9) 226*h*. Method of gas ion laser action, P (9) 226*i*.
McMarlin, R. M. Glass composition, P (3) 58*f*.
McMaster, A. D., and Fuschillo, N. Semiconductor behavior in amorphous Au-SiO thin films, (6) 137*a*.
McMaster, H. A. Apparatus for conveying glass sheets through adjacent bending and tempering stations, P (1) 3*e*. Apparatus for cutting and grinding glass, P (10) 243*e*. Method and apparatus for reshaping glass sheets, P (1) 4*i*.
McMaster, R. C. See Golis, M. J.
McMaster, R. G., and Joehlin, S. W. Method and apparatus for heat-treating sheets of glass, P (1) 4*f*.
McMeekin, J. H. Container wall thickness detection [electrical capacitance], P (11) 270*d*.
McMillan, P. W. See Phillips, S. V.
McMillan, P. W., and Partridge, G. Glass-ceramics, P (6) 132*h*.
McMillan, P. W., Hodgson, B. P., and Crozier, D. S. Devitrifiable glasses and glass-ceramics, P (2) 33*i*.
McMillan, P. W., Partridge, G., and Ward, F. R. Insulating coating on Si, P (5) 112*h*.
McMurdie, H. F. See Swanson, H. E.
McMurdie, H. F., Morris, M. C., deGroot, J., and Swanson, H. E. Crystallography of some double sulfates and chromates, (9) 234*h*.
McMurray, W. C. See Mashikian, M. S.
McMurtry, C. H. Protected thermocouple and protection tube, P (6) 142*h*.
McNab, I. R. Electrical brush structure, P (9) 225*d*.
McNally, R. N. See Alper, A. M.
McNally, R. N., and Patrick, R. F. Mfg. fused cast basic refractory, P (3) 61*f*.
McNatt, J. L. Electroreflectance study of NiO, (6) 147*e*.
McNeese, L. E., and Ferguson, D. E. Method for reprocessing spent molten salt reactor fuels, P (10) 253*j*.
McNeil, W. H. Method of applying a radiation shield to a second anode button, P (9) 219*j*.
McNeill, K. E. See Carrell, M. A.
McNeilly, C. E. See Chikalla, T. D.
McNish, T. G. Improvements in or relating to fibrous insulating materials, P (6) 135*i*.
McNulty, R. H. Common beverage bottles—their production, use, and forms in 17th and 18th century Netherlands (I), (11) 265*h*.
McPhee, A. D., and Brown, Norman L. Power consumption in solid-liquid slurries, (2) 43*i*.
McPherson, R. See Cutter, I. A.
McQuaid, G. J. Control systems, P (4) 81*c*.
MacRae, A. U. See Lepselter, M. P.
McRae, R. C. Envelope structure for high-intensity 3-electrode arc lamps incorporating heat shielding means, P (8) 200*b*. Housing for a sealed beam arc lamp, P (6) 133*b*.
Macshane, G. H. See Duttera, R. B.
McVay, G. L., and Farnum, E. H. Atm effects on Na diffusion in glass, (6) 131*h*. Specific activity effects on diffusion coeffs. in glass, (1) 3*i*.
McVay, T. L. See Johnson, A. B.
McWhan, D. B. Pressure variable in materials research, (10) 260*c*.
McWhan, D. B., and Rice, T. M. Critical pressure for the metal-semiconductor transition in V_2O_3, (6) 145*g*.
McWhan, D. B., Rice, T. M., and Remeika, J. P. Mott transition in Cr-doped V_2O_3, (6) 150*i*.
McWhinnie, A. D. Exercise in management at Spode, (1) 9*j*.
MacZura, G. See Francis, T. L.
MacZura, G., and Pearson, A. Production of low-soda Al_2O_3, P (7) 176*a*.
Madden, L. P. Method of obtaining low concentration impurity predeposition on a semiconductive wafer, P (1) 13*d*. See Moyle, K. J.
Madonna, L. A. Glass processing system—a diffusional network, (4) 80*j*.
Maeda, Hajime. See Takeishi, Yoshiyuki.
Maeda, Hajime, Takeishi, Y., Sato, T., Hara, H., and Okamoto, Y. Semiconductor device, P (4) 90*b*.
Maeda, Haruo. See Uno, Yoshihoro.
Maeda, Katsusuke. See Akatsu, Ken.
Maeda, Minoru, Shibayama, N., and Kato, T. Hydration of electrically fused MgO—dispersion of hydration values by autoclave test, (3) 60*d*.
Maeda, Teizo, and Kudo, K. Method for making metal oxide film resistors, P (4) 89*b*.
Maeda, Yojin. See Moriki, Juichi.
Maekawa, Hideyuki, Sakamoto, T., and Sagawa, Y. Rotary press-molding apparatus, P (8) 204*a*.
Maekawa, Shizuo. See Yokomichi, Hideo.
Maeno, Masahiro. See Sugahara, Yujiro.
Maezawa, Shigeru. See Kurokawa, Akitsugu.
Magee, J. H., Morton, V., Fisher, R. D., and Lowe, I. J. Relation between Fe_2O_3 particle size, spinel particle size, and magnetic properties of Mn Zn Fe_2O_4 materials, (1) 11*i*.
Magee, J. V. See Greiner, N. S.
Maghrabi, C. See Fitzpatrick, J. R.
Magidson, W. H. See Protzman, T. F.
Magill, M. E. See Hedler, R. A.
Magnan, R. See Eustache, J.
Magnante, P. C. Frequency-doubled Nd-doped glass laser utilizing an Li niobate crystal, P (9) 225*j*.
Maguire, C. F., Jarrett, Q. T., and Bartholomew, C. Y. Si_3N_4 improvement of reliability of mass produced transistors, (11) 274*a*.
Magunov, R. L. See Krylov, V. S.
Mah, A. D. See Pankratz, L. B.
Mahajan, S., Evans, J. H., and Wilyman, P. Stacking faults and twins in nonstoichiometric MoC, (4) 98*i*.
Mahan, A. I., Bitterli, C., Cannon, S. M., and Grant, D. G. Ruby as a macroscopic fluorescing and laser material, (1) 11*j*.
Mahe, C. See Warzawski, B.
Maher, G. H. Low-temp.-fired glass-bonded dielectric ceramic body and method, P (3) 65*j*. Low-temp.-fired rare earth-titanate ceramic body and method of making, P (11) 275*a*.
Maher, P. K. See McDaniel, C. V.; Park, C. S.
Maher, P. K., Albers, E. W., and McDaniel, C. V. Preparation of high-SiO_2 synthetic faujasite, P (9) 233*d*.
Maher, R. D. See Adamski, J. A.
Maher, S. W. Barite resources of Tenn., (1) 19*i*.
Mahlendorf, H. Special mechanical presses for the compaction of powdered materials, (11) 277*a*.
Mahler, E. Magnesite refractory materials, P (10) 247*j*.
Mahler, E., Becker, E., Czapla, H. U., Klasse, F., and Ehrcke, U. SiO_2 refractory material, P (3) 61*e*.
Mahler, R. J. Nominal $\Delta_m = \pm 1,2,3,4,5$ magnetic nuclear transition probabilities in ruby, (6) 150*b*.
Maidukova, T. P. See Limar, T. F.
Maines, J. D. See Crabb, J. C.
Maissel, L. I. See Glang, R.; Gregor, L. V.
Maisseu, A., Montfort, Y., Allais, G., and Deschanvres, A. System Nb-N-O near the solid solution α-Nb, (6) 152*j*.
Maiti, H. S., Gokhale, K. V. G. K., and Sub-

barao, E. C. Kinetics and burst phenomenon in ZrO_2 transformation, (7) 178*b*.
Maiti, J. N., and Basu, J. Effect of glass wall on the determination of plasma conductivity by rf external probes, (3) 69*i*.
Majdic, A., Grewen, O., and Nowak, A. E. Use of isostatic pressing in the shaping of refractory components, (6) 135*a*.
Majdic, A., and Routschka, G. Refractories for blast furnace regenerators—a review, (6) 134*g*.
Major, A. L. See Low, N. M. P.
Majumdar, A. J. See Ali, M. A.; Lawrence, P.; Speakman, K.
Makabe, Hirokuni. Measuring combined electrode, P (9) 231*h*.
Makarov, E. M. See Nekrasov, N. N.
Makarova, T. S. See Poluboyarinov, D. N.
Makaruk, A. F., and Starosel'skii, G. L. Adjusting and operating the automatic control of clinker firing, (8) 185*i*.
Makarychev, A. R., Pesina, N. M., and Ivanova, M. P. Testing ladle brick made by different [Soviet] factories, (8) 196*d*.
Makeev, V. S. See Pilyugin, A. N.
Makeev, V. S., Pilyugin, A. N., Poltoratskii, N. I., and Fomin, G. S. Electric furnace for sintering articles of refractory compounds, (10) 256*e*.
Makela, L. V. See Gender, J. R.
Maki, Hironobu. See Yoshikawa, Takayuki.
Maki, Iwao. Orthorhombic modifications of tricalcium aluminate in portland cement clinker, (6) 129*h*. So-called prismatic phase in portland cement clinker, (9) 215*f*. Systems between $2CaO \cdot SiO_2$ and its analogs containing alkalis, (4) 79*f*.
Maki, Iwao, Nishi, M., and Sugimura, T. Structural changes in the orthorhombic modification of $Ca_3Al_2O_6$, (6) 152*a*.
Maki, Iwao, and Sugimura, T. Cubic metasilicate $Na_4CaSi_3O_9$ and its relation to $Ca_3Al_2O_6$, (3) 72*d*.
Maki, Michiyoshi. See Kamiyama, Takamitsu; Makimoto, Tsugio.
Makimoto, Tsugio, and Maki, M. Method of fabricating a semiconductor integrated-circuit device, P (2) 41*d*.
Makimoto, Tsugio, Nagata, M., Masaki, A., and Kubo, M. Method of fabricating LSI circuits, P (3) 65*g*.
Makino, Ichiro. Gas chromatographic analysis of bubbles in glass, (6) 132*a*.
Makino, Yoshimi, Higuchi, S., Kamiya, I., and Masuya, Y. Co ferrite magnetic powder for tape recording, P (7) 168*a*.
Makishima, Shoji, Hirai, H., Tomiie, K., and Kudo, T. Fuel cell with electrodes having spinel crystal structure, P (11) 274*h*.
Makolagwa, S. See Jaworski, J. M.
Makoldi, M. Optimization of heat economy in ceramic tunnel kilns, (2) 45*g*.
Makris, J., Ferris-Prabhu, A., and Joshi, M. L. Effect of extremely thin nitrogenous surface films on P-impurity profiles in Si, (9) 223*j*.
Malandrino, Q. Dilatometric data of majolica wall tiles (I), (7) 165*g*.
Malaspina, L. See De Maria, G.
Malathi, N., and Puri, S. P. Moessbauer studies of adsorption and thermal treatment of Fe^{3+} ions on SiO_2 gel, Al_2O_3, and natrolite, (4) 97*g*.
Malcic, S. See Gal, I. J.
Malcolm, E. W. Adding cationic material to silicic acid sorbent chromatographic sheet for improved performance, P (6) 143*h*.
Malden, P. J. Bleaching of clays, P (10) 257*c*. Treatment [bleaching] of minerals, P (9) 233*d*. Treatment of clay, P (4) 95*a*.
Maldonado, J. R. See Fraser, D. B.
Maldonado, J. R., and Meitzler, A. H. Fine-grain polycrystalline ferroelectric ceramic optical shutter, P (2) 40*h*. Strain-biased fine-grain electrooptic ceramic device for controlling optical phase retardation, P (8) 202*e*. Strain-biased fine-grain ferroelectric ceramic devices for optical image storage and display systems, P (8) 202*e*.
Malek, R. I. A. See Mikhail, R. S.
Malesak, J. Method and apparatus for continuously mfg. foam glass, P (1) 4*d*.
Malhotra, D. See Rao, T. C.
Malhotra, L. K. See Sharma, S. D.
Mali, M. See Blinc, R.
Malinovskii, S. V. See Karklit, A. K.
Malinovsky, M. See Grjotheim, K.
Mallahan, F. J. See Castonguay, R. A.
Mallener, H. Gas reactions during enameling of sheet steel, (8) 188*h*.
Mallory, J. D., and Wallington, F. L. Method and apparatus for assembling bulb-shaped glass containers having cylindrical base elements, P (4) 82*i*.
Malloy, J. F., Curry, N. A., and Olton, D. J. Coated abrasive belt joint, P (9) 213*f*.
Malloy, J. F., and Seiler, C. J. Coated abrasive belt overlap joint, P (5) 101*e*.
Malmberg, P. R. See Handy, R. M.
Malone, J. G. Method of forming creased fiber glass blanket, P (2) 34*d*.
Maloney, B. A. See Stewart, D. A.
Maltman, W. R. See Loukes, D. G.
Mal'tsev, M. V., and Nikolaev, A. N. External friction of cermet powders in the low-pressure region, (10) 246*g*.
Maluck, W. A. Masonry cutting apparatus, P (3) 69*a*.
Malyavin, A. G. See Khan, B. Kh.
Mamantov, G. See Braunstein, J.
Mammach, P. See Gross, F.
Mamykin, E. T. See Korkh, L. M.
Mamykin, P. S. See Zamyatin, S. R.
Mamykin, P. S., and Drozdova, T. A. Effect of boric oxide on electrical conductivity of polycrystalline MgO, (8) 208*g*.
Man, C. Y. Process for electrodepositing metal-silicate coatings, P (4) 80*b*.
Manabe, Toyotaka. See Egashira, Kazumichi.
Manabe, Toyotaka, and Egashira, K. Crystal growth and optical properties of Gd Al garnet, (2) 47*f*.
Manasevit, H. M. Composite, method for growth of IIB-VIA compounds on substrates, and process for making composition for the compounds, P (9) 225*a*. See Thorsen, A. C.
Manasevit, H. M., and Simpson, W. I. Use of metal-organics in the preparation of semiconductor materials (I) epitaxial Ga(V) compounds, (2) 39*i*.
Mancewicz, T. A. See Spridco, J. P.
Mandineau, D. P. H., Mourey, M. Y. C., Pizzini, G. P. H., and Poulain, J. C. W boride-containing articles and production thereof, P (9) 222*j*.
Mandorf, V., Jr., and Fenish, R. G. Use of expanded anisotropic graphite as multicavity mold for hot-pressing, P (4) 85*b*.
Mandorf, V., Jr., and Montgomery, L. C. Composite article containing high-purity hot-pressed BN, P (10) 247*j*. High-purity hot-pressed BN, P (8) 193*j*.
Manevy, G., and Matcheret, G. Process for processing [decanning] canned irradiated ceramic fuel elements, P (6) 141*a*.
Manghnani, M. H. Pressure and temp. dependence of the elastic moduli of Na_2O-TiO_2-SiO_2 glasses, (8) 191*d*.
Mangum, B. W. See Blunt, R. F.
Mank, V. V. See Brekhunets, A. G.
Mankin, C. J. See Bucke, D. P., Jr.
Manley, B. W., Schagen, P., and Adams, J. Image intensifier with channel-type secondary emission multiplier, P (1) 12*f*.
Manley, G. W. See Carpenter, D. R.
Mann, G. R. See Riley, G. S.
Manninen, Seppo. See Togawa, Senichi.
Manning, D. G., and Hope, B. B. Effect of porosity on the compressive strength and elastic modulus of polymer impregnated concrete, (5) 103*a*.
Manning, F. S. See Guger, C. E.
Manning, W. R., Hunter, O., Jr., Calderwood, F. W., and Stacy, D. W. Thermal expansion of Nb_2O_5, (8) 211*a*.
Manring, W. H. Melting particulate glass batch, P (1) 4*b*.
Manring, W. H., and Epp, D. How to study reboil with a hot-stage microscope, (3) 56*a*.
Mansingh, A. See Sayer, M.
Mansmann, M. See Zirngibl, H.
Mansur, F. E. See Jagodzinski, R. F.
Mao, H. K., and Bell, P. M. Electrical conductivity and the red shift of absorption in olivine and spinel at high pressure, (10) 258*j*.
Mar, J. Method of monitoring semiconductor device fabrication, P (7) 169*b*.
Maradudin, A. A. See Tong, S. Y.
Maravilla, S. Oil-well cement and method of making, P (7) 157*d*.
Marboe, E. C., and Weyl, W. A. Photoluminescent glass and method of making, P (5) 107*f*.
Marcdargent, S. Physicochemical study of synthetic monocalcium silicate used in ceramics—hot-pressing, (2) 48*h*.
Marchal, M. See Cantagrel, M.; Combe, C.
Marchand, E. W. Ray tracing in gradient-index media, (8) 205*b*.
Marchant, D. D., and Gordon, R. S. Grain size distributions and grain growth in MgO and MgO-Fe_2O_3 solid solutions, (2) 48*b*.
Marchese, B. See Collepardi, M.
Marchese, B., Mascolo, G., and Sersale, R. Relation of composition of hydrogarnet to resistance to sulfate attack, (4) 79*b*.
Marchesi, C. M. Clay area heater, P (10) 247*f*.
Marcialis, A. See Collepardi, M.
Marcinkowski, M. J. See Das, E. S. P.
Marconato, R., and Anderson, R. L. Partial recovery of GaAs tunnel diodes after stress-induced degradation, (5) 112*a*.
Marcoux, L. See Kourtesis, J. G.
Marcus, S. M., and Blther, T. A. Measurement of the de Haas-van Alphen effect in perovskite-type Mo bronzes, A_2MoO_3, (6) 150*f*.
Mare, A. Refractory brick having oblique surface, P (4) 85*a*.
Marek, B. A., Sukhikh, L. L., and Teodorovich, O. K. Metal-ceramic reinforced electrical contacts, (10) 249*e*.
Marek, D. A., Kreiselmaier, K. W., and Van Tassel, J. H. Electron beam evaporated quartz insulating material process, P (3) 64*i*.
Marek, I. See Galos, M.
Marengo, G. See Lanza, F.
Maret, G. Radiation detectors having lateral photovoltage and method of mfg., P (3) 67*e*.
Marezio, M. See Matthias, B. T.; Porta, P.
Marezio, M., Dernier, P. D., and Remeika, J. P. Crystal structures of orthorhombic $SmAlO_3$ and of trigonal $NdAlO_3$, (8) 208*a*.
Margoninski, Y., and Feinstein, L. G. Low-energy electron-diffraction and surface conductance studies of surface reaction of Ge with O, (6) 149*i*.
Margrave, J. L. See Charlu, T. V.
Marhanka, J. E. See Francis, T. L.
Mari, C. See Pizzini, S.
Marinace, J. C., and McGibbon, R. C. Semiconductor laser device with improved operating efficiency, P (2) 42*d*.
Marinenko, G. See Sappenfield, K. M.
Marinenko, G., and Champion, C. E. High-precision coulometric titrations of boric acid, (9) 231*d*.
Marino, A. D. See Landry, R. J.
Marino, G. P. Porosity correction factor for the thermal conductivity of ceramic fuels, (7) 171*b*.
Marioge, J. P. See Warzawski, B.
Mark, A. See Glendinning, W. B.
Markov, V. E. See Menchikov, L. P.
Markovskii, L. Ya., Vekshina, N. V., Bezruk, E. T., Sukhareva, G. E., and Voevodskaya, T. K. Magnesiothermic method for producing metal borides, (3) 60*d*.
Marks, A. M., Marks, M. M., and Kent, A. P. Nonglare coating for surfaces of TV tubes and such coated surfaces, P (10) 245*g*.
Marks, L. M., Jr. See Young, R. G.
Marks, M. M. See Marks, A. M.
Marler, J. V. See Mills, L.
Marlowe, M. O. Simulation of gaseous fission products in UO_2, (8) 203*e*. See Hill, H. W.
Marotta, A. See Buri, A.
Marotta, A., Buri, A., and Orsini, P. G. Crystallization of glass materials (III) calculation of the activation energy from DTA data, (4) 80*f*.
Marquis, J. E. Pb in glazes—benefits and safety precautions, (1) 10*e*.
Marr, R. J., and Treffner, W. S. Microstructure of periclase and C in BOF refractories, (8) 195*a*.
Marsden, C. P. Tabulation of data on semiconductor amplifiers and oscillators at microwave frequencies, (7) 168*f*.
Marsh, A. See Fairholme, R. J.
Marsh, H. N., Jr., and Gano, B. P. Composite articles including bonded fibrous glass with said articles having density gradients, P (5) 107*d*.
Marsh, O. J. See Hunsperger, R. G.
Marshall, A. See Schnaus, U. E.
Marshall, D. W., and Pett, E. A. Method of making fragmented crystalline material, P (6) 127*f*.
Marshall, J. See Williams, Frank R.
Marshall, K. See Roberts, W.
Marshall, L. J. Conveying apparatus for splitting a single stream of roofing tiles on pallets into 2 streams, P (1) 6*c*.
Marshall, R. See Healy, R. M.
Marshall, R. C. See Quickenden, T. I.
Marszalek, D. S. See Ginsberg, R. N.
Marteel, B. See De Boeck, P.
Martens, K. P. See Van der Tas, J. C.
Martikyan, S. B. See Kovaleva, I. S.
Martin, B. M. See Sloan, B. J., Jr.
Martin, C. See Grenier, J. C.
Martin, C. H. Arrangement for connecting concrete or clay bricks, blocks, panels, and slabs, P (10) 246*a*.
Martin, D. F. See Dismukes, J. P.
Martin, D. L. Sintered Co-rare earth intermetallic product [Sm and Ce] and permanent magnets produced therefrom, P (11) 275*i*. Sintered Co-rare earth intermetallic product [Sm and La] and permanent magnets produced therefrom, P (11) 275*i*. Sintered Co-rare earth intermetallic product [Sm and Pr] and permanent magnets produced therefrom, P (11) 275*i*. See Benz, M. G.
Martin, D. L., and Benz, M. G. Sintered Co-rare earth intermetallic product [Sm and Ce misch metal] and permanent magnets produced therefrom, P (11) 275*j*. Superconductors containing flux traps, P (10) 253*f*.
Martin, F. W. High-durability $PbTiO_3$-containing enamel for glass-ceramics, P (8) 193*d*. See Beall, G. H.; King, W. J.
Martin, J. Ribbon conductor press seal structure, P (10) 245*e*. See Haas, E.
Martin, J. C., and Thompson, W. L. Si pressure transducer circuit, P (6) 140*f*.
Martin, J. S., Jr. See Royce, M. R.
Martin, J. W. Strong Materials, B (11) 284*a*.
Martin, M. Method for vertical suspension of glass sheets during thermal treatment, P (10) 245*e*.
Martin, R. C. Aqueous hydraulic cement composition having improved retardation to set and use thereof in high-temp. environments, P (8) 188*d*.
Martin, R. M. Dielectric screening model for lattice vibrations of diamond-structure crystals, (6) 146*c*.
Martin, W. S. See Almasi, J. C.
Martine, J. L. See Miller, F. E.
Martinelli, A. A. See Krauer, W.
Martinet, A. See Nava, R.
Martinez, C. Building block and structure made therewith, P (6) 134*c*.
Martinez, J. R., Serrano, F. A., Sardina, M. M., and Guerra, C. A. Factors affecting oriented crystallizations on phyllosilicates, (10) 259*f*.
Martinsen, W. E. See Cordone, L. G.
Martiros, P. Multifocal lens mfg. process and apparatus, P (3) 59*j*.
Martlew, D. See Cable, M.
Martner, J. G. See Cornelius, W. L.
Martyn, L. G. Piezoelectric crystal device including loading elements having the shape of chordal sections, P (11) 275*i*.
Martynova, I. F. See Raichenko, A. I.
Martyny, W. C. See Jones, Clifton P.

Martzloff, F. D. See Edgar, R. F.
Maruyama, Mitsuhiro, Mizuno, O., and Kikuchi, S. Vapor growth process for GaAs, P (8) 203*a*.
Marx, F. See Becherescu, D.
Maryon, H. Metalwork and Enamelling, B (7) 183*j*.
Marzocchi, A. Apparatus and method of removing excess liquid coating from glass filaments, P (10) 243*e*. Glass fiber-reinforced elastomers, P (10) 244*j*. Glass fibers impregnated with polymers containing an unsaturated silane, P (7) 161*i*. Method of making [glass] reinforcement for tires, P (4) 82*d*. Method of producing a coated glass fiber strand, P (10) 245*d*. Method for treating glass fibers, P (11) 270*g*. See Janetos, N. S.
Marzocchi, A., and Horton, R. C. Glass fibers coated with vinyl polymers containing an amine, P (7) 161*i*.
Marzullo, S. See Franklin, A. D.
Masaki, Akira. See Makimoto, Tsugio; Sakai, Kaname.
Masaki, Norio, and Doi, K. Analysis of the superstructure of U_4O_9 by neutron diffraction, (10) 253*h*.
Masaki, Tatsuo. See Hanada, Hiroshi.
Mascolo, G. See Marchese, B.
Maserjian, J., and Gatewood, J. R. Thin-film temp. sensor and method of making, P (10) 256*b*.
Mash, D. H. Mfg. semiconductor devices, P (6) 138*i*.
Mashbane, A., and Vilardi, F. Electrophoresis testing apparatus, P (10) 255*i*.
Mashikian, M. S., Kelley, J. K., and McMurray, W. C. Capacitively graded modular pothead for H-V cable, P (10) 248*i*.
Maslennikova, G. N. See Surkov, M. E.
Mason, B. W., Jr. See Graffeo, J. V., Jr.
Mason, D. W. High *K* dielectric materials, P (10) 250*g*.
Mason, D. W., Greenstein, B., and Woulbroun, J. M. Resistors, compositions, pastes, and method of making and using, P (10) 252*d*.
Mason, F. P., and Waren, F. A. O. Magnetic powder conveyance arrangement, P (4) 92*e*.
Mason, G. W., Lewey, S., Bollmeier, A. F., and Peppard, D. F. Process of separating Y from lanthanide rare earths, P (2) 46*f*.
Mason, I. M., and Ash, E. A. Acoustic surface-wave beam diffraction on anisotropic substrates, (7) 166*c*.
Mason, R. B. See Arey, W. F., Jr.
Mason, W. P. Monolithic crystal filter with auxiliary filter shorting tabs, P (10) 252*e*.
Masood, I. See Dave, N. G.
Massard, P., Bernier, J. C., and Michel, A. Jahn-Teller effect in the system Ta_2CrO_6-$TaCrO_4$, (10) 259*h*.
Massonne, J., and Becher, W. Method for removing SO_2 from BF, P (3) 71*d*.
Masters, B. J. See Joshi, M. L.
Masuda, Isao. Glass for laser, P (4) 81*j*.
Masuda, Senichi. Electrodynamic behavior of charged dust particles, (6) 141*e*.
Masumi, Taizo. See Kajita, Koji.
Masuya, Yoshikazu. See Makino, Yoshimi.
Masuyama, Takeshi. See Hamamoto, Kazuo; Matsuoka, Michio.
Masuyama, Takeshi, Amemiya, T., and Iida, Y. Voltage variable resistors, P (9) 228*d*.
Masuyama, Takeshi, Matsuoka, M., and Iida, Y. Nonlinear resistor and nonlinear resistor composition, P (8) 201*j*.
Masuyama, Takeshi, Matsuoka, M., and Nishi, T. Nonlinear resistors of bulk type, P (8) 201*j*.
Masuyama, Takeshi, Matsuura, M., Iida, Y., and Amemiya, T. Voltage variable resistor, P (5) 114*e*.
Matcheret, G. See Manevy, G.
Mather, J. Apparatus for use in mfg. flat glass, P (11) 270*a*.
Mathers, J. E. See Ferri, J. L.
Mathers, J. E., and Mikus, F. F. Process for producing phosphors, P (5) 113*j*.
Mathers, J. E., Mikus, F. F., and Mehalchick, E. J. Process for producing Eu-activated Y vanadate phosphors, P (4) 80*d*.
Mathers, J. E., Mikus, F. F., and Yale, R. L. Production of ammonium metavanadate, P (7) 170*g*.
Mathers, J. E., and Toma, S. Z. Phosphor compositions and process for upgrading Y orthovanadate phosphors, P (6) 139*j*.
Matheson, W. G. See Loughridge, F. A.
Mathews, J. R. See Beadle, W. E.
Mathews, M. D. See Momin, A. C.
Mathews, T. C. Apparatus and method for separating solid articles, P (10) 254*h*.
Mathewson, H. K., and Hendricks, C. L. B polyimide composite development, (11) 271*f*.
Mathey, R. G. See Clifton, J. R.
Mathis, P. Process for the solubilization of Ca borate present in B minerals, P (7) 175*j*.
Mathisen, E. S. Automatic holographic wafer positioning system and method, P (2) 39*b*.
Mathur, N. M., Rao, M. R. K., and Sen, P. C. Microstructure and properties of chrome-magnesite refractories made from indigenous raw materials, (11) 271*d*.
Mathur, P. C. See Srivastava, G. P.
Matiasovsky, K. See Grjotheim, K.
Matis, I. G. See Bergmanis, K. A.
Matkovich, V. I. See Economy, J.
Matoba, Tamuro, and Nakayama, T. Machine for planting a refractory piece in a sheet-like thermoplastic mass, P (4) 82*g*.
Matousek, J., and Hlavac, J. Study of the volatilization of Pb glass, (2) 32*j*.
Matricon, M. Method of mfg. hollow superconducting bodies, P (5) 113*i*.
Matrosova, V. A., and Bergman, A. G. Investigation of the ternary system of the sulfate, metaphosphate, and metaborate of Na, (1) 23*c*.
Matrosovich, A. N. See Budnikov, P. P.
Matsera, V. E. Heat-resisting fibers and their use in mfg. composite materials, (10) 246*g*.
Matson, C. B. Sensing device for determining the unbalance of a grinding wheel, P (1) 1*h*.
Matsubara, Atsushi. See Hosotani, Shigeyoshi.
Matsubara, Tetsujin. Infrared stimulable phosphor YOF:Yb, Er, (3) 63*d*. See Sugano, Izuru.
Matsuda, Osaku. See Hirosue, Hideharu.
Matsuda, Osaku, Hara, N., Inoue, N., and Kamei, S. Shirasu-lime autoclaved lightweight concrete by pretreatment in hot H_2O, (6) 130*c*.
Matsuda, Shinichi, Ikegami, T., and Suzuki, H. Synthesis and thermal decomposition of Be sulfates, (6) 152*g*.
Matsui, Hideki. See Nomura, Kazuhumi.
Matsui, Masatoshi. Thermal change detector of the linear thermopile type, P (6) 140*b*.
Matsukura, Yasuo, Ohta, K., and Wada, T. Semiconductor device [NOT circuit] employing Gunn effect elements, P (1) 14*j*.
Matsukura, Yasuo, Wada, T., and Ohta, K. Semiconductor logic device employing a Gunn effect element, P (7) 170*c*.
Matsumoto, Akira. See Goto, Kunihiro.
Matsumoto, Fumio. See Nakao, Tatsuhide.
Matsumoto, Katsuyoshi. See Yamane, Mikiya.
Matsumoto, Keiji. See Sato, Tomi.
Matsumoto, Seiichiro. See Inomata, Yoshizo.
Matsumoto, Tadao. See Nishibayashi, Shinzo.
Matsumoto, Zenji. See Shirai, Yoshihiro.
Matsumura, Hiroyoshi. See Kitano, Ichiro.
Matsunaga, Kazu. See Awazu, Kenzo.
Matsunaka, Kazuto. See Nakamura, Atsushi; Tsukayama, Ryuichi.
Matsunami, Hiroyuki, Tazaki, M., and Tanaka, T. Cracks observed on the chalcogenide glass surfaces after switching, (3) 55*i*.
Matsuno, Akira, Sasame, T., Shimizu, I., Kizu, H., and Kagawa, H. Method of preparing corrosion-resistant metallic articles, P (8) 189*b*.
Matsuo, Akira. See Yoshida, Hideo.
Matsuo, Masao, and Tomiwa, H. Method of mfg. chip-shaped passive electronic components, P (3) 65*j*. Solid-state electrolytic capacitor and method of making, P (6) 140*g*.
Matsuo, Takeshi. See Tsutsumi, Tadashi.
Matsuo, Yoshihiro. Growth of single crystals of $Pb(Zn_{1/3}Nb_{2/3})O_3$ and its properties, (3) 73*d*. Synthesis of the perovskite-type oxide $Pb(Zn_{1/3}Nb_{2/3})O_3$, (2) 50*a*. See Matsuoka, T.; Sasaki, Hiromu.
Matsuoka, Kouji. See Uto, Yashimitsu.
Matsuoka, Michio. Nonohmic properties of ZnO ceramics, (3) 74*c*. See Hamamoto, Kazuo; Masuyama, Takeshi.
Matsuoka, Michio, Masuyama, T., and Iida, Y. Ba-modified ZnO voltage variable resistor, P (4) 88*i*. Pb-modified ZnO voltage variable resistor, P (4) 88*i*. Sr-modified ZnO voltage variable resistor, P (4) 88*i*. Voltage-dependent resistors of bulk type, P (11) 276*a*.
Matsuoka, T., Matsuo, Y., Sasaki, H., and Hayakawa, S. Preparation and characterization of Cd_2TiWO_7, (3) 63*c*. PTCR behavior of $BaTiO_3$ with Nb_2O_5 and MnO_2 additives, (3) 63*d*.
Matsuoka, Tohru. Microwave circuit utilizing a semiconductor impedance element, P (4) 89*d*.
Matsushima, Katsuo. Sputtering apparatus, P (6) 140*h*.
Matsushita, Masanari. Process and apparatus for production of glass ribbon on molten metal bath, P (11) 270*h*. See Fujimoto, Yukiya.
Matsushita, Tatsuhiko, Yamagami, T., and Okuda, M. Compositional dependency of the filamentary paths formed on the surface of the chalcogenide glasses, (3) 55*f*. Formation of a high current density path on the surface of the chalcogenide glass, (3) 56*d*.
Matsushita, Toru. See Doi, Haruo; Saito, Hajime.
Matsushita, Toru, Suzuki, K., and Hasegawa, S. Method of applying coating of metal oxides on substrates, P (6) 138*j*.
Matsushita, Yukio. See Hiraoka, Teruyoshi.
Matsuura, Mikio. See Masuyama, Takeshi.
Matsuura, Shigeo. Method for mfg. a variable capacitance diode, P (5) 113*i*.
Matsuyama, G. See Petersen, A. J.
Matsuyama, Shigeru, and Ito, Y. Antipiping compound and process for retaining heat of hot top surface, P (2) 37*c*.
Matsuzaki, Yasuhiro. See Tsuboi, Tatsuaki.
Matsuzawa, Takayoshi. See Takashio, Haruo.
Matthelss, L. F. Band structure and Fermi surface of ReO_3, (5) 118*i*.
Matteudi, G. See Porral, G.
Matthews, J. R. See Temple, C. S.
Matthews, J. W., and Klokholm, E. Fracture of brittle epitaxial films under the influence of misfit stress, (6) 136*j*.
Matthews, R. K. See Benson, L. V.
Matthias, B. T., Marezio, M., Corenzwit, E., Cooper, A. S., and Barz, H. E. High-temp. superconductors, the first ternary system, (8) 209*g*.
Mattingley, N. J. See Bowen, D. H.
Mattis, D. C. Optical shutter for laser or maser modulation, P (9) 219*g*. See Lipsicas, M.
Mattox, W. J. See Arey, W. F., Jr.
Matumura, On. See Okamoto, Yasunori.
Matusov, I. A. See Avgustinik, A. I.
Matveev, E. V. See Likhoradov, A. P.
Matweecha, D. M. Blending apparatus, P (6) 141*d*.
Matyash, I. V. See Sil'chenko, V. A.
Matz, D. See Moser, F.
Maupin, F. M. Planning center cuts downtime, boosts productivity at A. P. Green, (2) 36*b*.
Maurel, P., and Duhart, P. Process for the acid treatment of aluminous ores for the recovery of Al_2O_3, P (3) 71*f*.
Maurer, R. D., and Schultz, P. C. Fused SiO_2 optical wave guide, P (8) 192*i*.
Maurin, A. F. See Rutman, D. S.
Maurin, M. See Philippot, E.
Mavroudis, M. Air-cushion (Hover-) kiln—a new fast firing method, (1) 19*b*. Research with a model into the movement of bulk material in shaft furnaces with interior fittings, (8) 187*b*.
Maxsted, M. D. See Miller, J. P.
Maxutov, R. See Akhunov, A. M.
Maxwell, E. See Abeshouse, D. J.
May, J. E. W barrier electrical connection, P (2) 43*a*.
May, R. E. Glass fiber fabric for drapery, P (2) 34*d*.
Mayaux, P., and Nisol, M. Use of automatic X-ray fluorescence apparatus for control of glasses and batch material, (8) 192*b*.
Mayeda, Toshiko K. See O'Neil, J. R.
Mayer, J. W. See Mitchell, I. V.; Picraux, S. T.
Mayer, R. M. See Cooper, G. A.
Mayer, R. P., Thompson, I. M., and Zbojniewicz, W. P. Production of high-density dead-burned MgO in a shaft kiln, P (5) 110*b*.
Mayer, S. E. See Edelman, F. H.
Mayers, C. C. Glass polishing machinery, P (10) 244*c*.
Maynard, R. N. See Iannicelli, J.
Mayo, J. W. Observations of some overseas enameling plants, (5) 105*e*.
Mazaeva, O. L., Pikashov, V. S., and Rozhanskii, A. I. Effect of burner design on gas combustion and heat exchange in glass furnaces, (8) 190*a*.
Mazdiyasni, K. S. See Graham, H. C.
Mazdiyasni, K. S., and Brown, L. M. Microstructure and electrical properties of Sc_2O_3-doped, rare-earth-oxide-doped, and undoped $BaTiO_3$, (1) 11*d*.
Mazdiyasni, K. S., Dolloff, R. T., and Smith, Jonathan S., II. Process for producing high-purity submicron Ba and Sr titanate powders, P (6) 139*g*.
Mazel, V. A. See Eremin, N. I.
Mazelsky, R. See Ohlmann, R. C.
Mazelsky, R., and Ohlmann, R. C. Laser containing Nd-doped Ca fluoroapatite laser crystal, P (3) 65*h*.
Mazo, J. L. Oteo. See Oteo Mazo, J. L.
Mazur, R. G. Apparatus for automatically determining spreading resistance, resistivity, and impurity concentration in semiconductor bodies, P (4) 87*d*.
Mazzoni, R. J. See Bowser, G. H.; Stewart, J. L.
Mchedlov-Petrosyan, O. P., and Chernyavskii, V. L. Thermokinetic studies of portland cement hydration in dilute electrolyte solutions, (8) 188*f*.
Mchedlov-Petrosyan, O. P., Ol'ginskii, A. G., Uginchus, D. A., and Chernyavskii, V. L. Significance of temp. factor in hardening of cement with mineral additives, (8) 187*e*.
Mead, C. A. See Jenkins, R.
Mead, C. A., and McCaldin, J. O. Method for processing semiconductors, P (7) 169*f*.
Meadca, G. W. See Gough, J. R. C.
Meadowcroft, D. B. High-temp. insulation, (7) 165*b*.
Meadows, F. W. See Bradshaw, A.
Meadows, G. W. Anisodimensional WC platelets bonded with Co, P (6) 135*d*.
Means, J. A. Device for testing semiconductors, P (8) 200*i*.
Mechel, F., and Kummermehr, H. Mineral wool made from silicate glass containing Fe oxides, P (10) 245*f*.
Mechel, J. R. Machine for uniting glass parts, (3) 58*g*.
Mechler, I. See Opoczky, L.
Mecholsky, J. J. See Aggarwal, I. D.
Medaris, L. G., Jr. See Cullers, R. J.
Medders, J. B. See Pick, E. G.
Medendorp, N. W. See Lake, W. H.
Medic, N. See Hloch, A.
Medvecky, B. P., Oberai, A. S., and Platt, A. Method for producing high performance semiconductor device, P (10) 252*b*.
Medvedeva, G. V. See Evstrop'ev, K. S.
Medvedeva, Z. S. See Grinberg, Ya. Kh.; Toropov, N. A.
Medvedovskaya, E. I. See Budnikov, P. P.
Medvedovskaya, Z. I. See Bulavin, I. A.
Mee, J. E. See Besser, P. J.
Mee, J. E., Heinz, D. M., Hamilton, T. N., Besser, P. J., and Pulliam, G. R. Method

of forming multiple-layer structures including magnetic domains, P (6) 138*f*.
Meehan, J. P. See Kreidler, E. R.
Meek, R. L. Fabrication of integrated semiconductor devices by electrochemical etching, P (8) 200*c*. Method of preparing slices of a semiconductor material having discrete doped regions, P (5) 113*a*.
Megaw, H. D. Crystal structures and thermal expansion, (2) 47*h*. See Glazer, A. M.
Megles, J. E. Nepheline-feldspar glass-ceramics, P (7) 162*e*. Strengthened laminated glass bodies, P (6) 133*h*. See Giffen, J. W.
Mehal, E. W. See Allen, H. A.; Haisty, R. W.; Johnson, R. E.
Mehalchick, E. J. See Mathers, J. E.
Meherali, S. G. See Davies, M. W.
Mehta, P. K. Stability of ettringite on heating, (2) 31*c*. See Tewari, R. P.
Mehta, R. R. See Chapman, D. W.
Meijer, P. H. E. See Lewiner, J.
Meijer, R. A. J. M. See van Bakel, H. A.
Meijer, R. A. J. M., and Pennekamp, J. C. Pinch-base electric lamp with transversely arranged supply wires, P (3) 59*c*.
Meikleham, V. F. See Barnett, A. M.
Meiling, G. S. Photochromic glass, P (2) 34*j*.
Meille, E. See Picon, M.
Meinert, N. See Broemer, H.; Leitz, E.
Meinhold, L. See Chromecek, R.
Meissner, H. P. See Huska, P. A.
Meitzler, A. H. See Fraser, D. B.; Maldonado, J. R.; O'Bryan, H. M., Jr.
Meitzler, A. H., and O'Bryan, H. M., Jr. La dependence of elastic and piezoelectric properties of PLZT ceramics with a Zr/Ti ratio of 65/35, (11) 273*i*.
Melamed, N. T. See Roland, G. W.
Melamed, N. T., Roland, G. W., and Hopkins, R. H. Ca Y silicate oxyapatite laser material containing Ho and Cr ions, P (4) 87*g*. Laser material, P (8) 201*a*.
Melcher, J. R. See Jones, Thomas B.
Melcher, R. L., and Bolef, D. I. Ultrasonic propagation in $RbMnF_3$ (II) magnetoelastic properties, (6) 152*h*.
Melford, D. A. See Jones, D. G.
Melillo, M. B., and Vlachos, D. P. Method of plating a uniform Cu layer on an apertured printed circuit board, P (4) 89*g*.
Melin, K. A. Apparatus for controlling the temp. of a sample during the [X-ray] examination thereof, P (6) 142*a*.
Mellen, E. J., Jr. Process for redrawing SiO_2 glass rods, P (7) 162*i*. Wafer boat, P (5) 107*i*.
Mellen, E. J., Jr., Baker, E. M., and Webb, J. M. Porcupine shell molds and method of making, P (7) 164*a*.
Melroy, D. O., Orr, W. H., Pelletier, F. P., and Yocom, W. H. Method for the fabrication of discrete RC structure, P (1) 13*c*.
Melville, T. See Bail, C. G.
Menchikov, L. P., Kopylov, K. I., Okun, E. L., Smirnov, V. M., Gavrikov, V. S., Fridman, I. D., Markov, V. E., and Sopin, A. A. Installation for casting microwire in glass insulation, P (7) 162*e*.
Mendel, E. Method for polishing magnetic oxide materials, P (8) 201*g*.
Mendelson, R. A. See Kirkpatrick, M. E.
Menelly, R. A. Arc discharge lamp having a thin continuous film of In oxide on the inner surface thereof, P (10) 243*i*.
Menessy, I. See Becherescu, D.
Menezes, R. A. See Coghlan, W. A.
Menis, O. See Shultz, J. I.
Menzel, G. Apparatus for grinding the corners of flat glass plates such as glass slides, P (4) 81*h*. Machine for grinding edges of glass articles, P (5) 107*j*.
Mercade, V. V. Method for improving the brightness of gray sedimentary kaolin clay, P (7) 175*d*. Recovery of CaF_2 from fluorspar ore, P (8) 207*f*.
Mercade, V. V., and Weir, S. R. Method for treating floated solids, P (4) 94*c*.
Mergerian, D. See Bozanic, D. A.
Merkel, H., and Leibenzeder, S. Method for producing highly pure GaAs, P (8) 201*h*.
Merkin, A. P. See Budnikov, P. P.
Mermelstein, S. Endless belt seed crystal gripping and pulling means, P (1) 12*a*.
Merriam, M. F. Electronic ceramics—opportunity area for small scale mfg., (2) 38*g*. See Subbarao, E. C.
Merrill, R. C. See Wright, A. N.
Merrin, S. IGFE device having glass gate insulator, P (10) 250*j*.
Merwin, B. W. Ceramic dinnerware surveillance program, (1) 9*j*.
Merz, J. P., Wong, Yeng P., and Fetters, W. A. Bonding with a glass frit coating applied by a knurled roller, P (1) 12*c*.
Meshengisser, M. Ya., Ermakov, I. S., Kochkin, G. M., Stankun, A. V., Shakhov, F. N., Velednitskii, I. P., and Yagodin, P. P. Filter press, P (2) 44*b*.
Mesley, N. N. Method of preparing [printed circuit] glass masters, P (5) 107*d*.
Mesri, G. Mechanisms controlling the permeability of clays, (5) 121*h*.
Mesrobian, G., Rolin, M., and Pham, H. Study under pressure of NaF-AlF mixtures rich in AlF, (11) 283*a*.
Messier, D. R. See Gazza, G. E.; Wong, Philip.
Messier, D. R., and Gazza, G. E. Preparation of ultrafine mixed metallic-oxide powders, P (10) 257*b*. Synthesis of $MgAl_2O_4$ and $Y_3Al_5O_{12}$ by thermal decomposition of hydrated nitrate mixtures, (10) 249*a*.
Metcalfe, A. See Jackson, B. L. J.
Metcalfe, A. G., and Schmitz, G. K. Mechanism of stress corrosion in E glass filaments, (9) 217*h*.
Methfessel, S. See Ahn, Kie Y.
Methfessel, S. I. See Eastman, D. E.
Metzger, L. H., and Miller, H. C. Rotary grinding wheel, P (9) 213*j*.
Meuleman, J. Radiation detector having a clamped crystal, P (6) 139*i*. Radiation detector having a semiconductor crystal, P (6) 139*i*. See Cacheux, J. A.
Meulemans, C. C. E. See Van der Tas, J. C.
Meulemans, D. R. See Bilous, O.
Meunier, G., Michaud, H., and Souchet, R. Apparatus for pneumatically supporting flexible ribbons and sheets out of contact with solids, P (1) 3*g*.
Meunier, H. G. Measuring the permeability of granular material, P (2) 45*b*.
Meyer, A. Apparatus for stacking bricks and other articles, P (2) 35*g*.
Meyer, E. Apparatus for forming a composite metal-ceramic article, P (1) 12*b*. Electrical contact material and method of making and utilizing, P (3) 64*g*. Method of preparing a metal part to be sealed in a glass-ceramic composite, P (9) 226*g*.
Meyer, H. C. See Bowden, C. M.
Meyer, M. See Gebert, H.
Meyer, P. B. Dust in the ceramic industry, (5) 126*a*.
Meyer, R. T., and Nelson, L. S. Role of N in the formation of microbubbles during the explosive combustion of Zr droplets in N_2/O_2 mixture, (8) 210*b*.
Meyer-Simon, E. See Schwarz, R.
Miale, J. N. Mn silicate-containing minerals in the form of nodules and their use in hydrocarbon conversion, P (10) 257*f*.
Michael, J. F. See Corth, R.
Michaelsen, J. D. See Chapman, D. W.
Michal, J. Chromatography in Inorganic Analysis, B (7) 183*g*.
Michalik, E. R., and Misson, G. W. Method and apparatus having sealing means and gaseous takeoff for float glass, P (2) 34*b*.
Michaud, H. See Meunier, G.
Michel, A. See Bernigaud, G.; Massard, P.
Michel, H. See Schulten, R.
Micheletti, F. B., Norris, P. E., Schlesier, K. M., and Shaw, J. M. Pyrohydrolytic Al_2O_3 for MOS applications, (10) 249*i*.
Micheli, A. See Cimino, A.
Micheli, A. L. Method of coprecipitating hexagonal ferrites, P (4) 88*e*. Method of preparing an Li-containing ferrite composition, P (5) 113*a*.
Michelotti, J. E., and Henery, V. A. Apparatus for coating hot glass, P (7) 161*f*.
Michieli, R. E. Triangularly shaped concrete seat with tile covering, P (5) 111*g*.
Middelhoek, S., and Sasso, G. Procedure for making semiconductor devices of small dimensions, P (9) 227*i*.
Middleton, A. J. See White, Donald L.
Middleton, R. M. See Caslavsky, J. L.
Midgley, H. G. Indexing of powder X-ray diffraction data for Ca_2SiO_4, (2) 48*g*.
Midgley, H. G., and Pettifer, K. Electron optical study of hydrated high-Al_2O_3 cement pastes, (11) 266*f*. Microstructure of hydrated supersulfated cement, (4) 79*e*.
Mieher, R. L. See Chu, Yuan Hou.
Migitaka, Masatoshi. See Takahashi, Susumu.
Mihalik, V., Zatko, S., and Butkovic, P. Possibilities of the treatment of fine raw perlite, (10) 257*a*.
Mihara, Toshihiro. See Kawamata, Tadashi.
Mikhael, S. A. See Grjotheim, K.
Mikhail, R. S. See Yudenfreund, M.
Mikhail, R. S., and Abd-El-Enein, S. A. H_2O and N adsorption on hardened cement pastes (I) development of surface in low porosity pastes, (10) 242*c*.
Mikhail, R. S., Abd-El-Enien, S. A., and Abd-El-Khalik, M. Determination of pore structure and specific surface of Ca silicate hydrates by H_2O adsorption, (9) 213*j*.
Mikhail, R. S., and Malek, R. I. A. Microstructure of hardened gypsum pastes, (5) 103*d*.
Mikhailov, N. V. See Lishanskii, B. A.; Ur'ev, N. B.
Mikhailova, G. A. See Bystrova, V. I.
Mikheeva, V. I. See Sterlyadkina, Z. K.
Mikheichev, M. Ya. Semiautomatic spraying machine for porcelain decoration, (8) 198*i*.
Mikol'skii, Yu. N., and Zelenyi, I. T. Accuracy of methods for checking rectilinearity of the axis of kiln rotation, (8) 185*g*.
Mikos, K. N. See Dzhigit, O. M.
Mikoshiba, Nobuo. See Inaba, Ritsuo.
Mikoza, A. G., and Lawn, B. R. Section-and-etch study of Hertzian fracture mechanics, (7) 160*d*.
Mikoteit, F., and Tennstedt, H. J. Hydraulic mortar or cement composition, P (6) 130*e*.
Mikus, F. F. See Mathers, J. E.
Miles, C. V., and Garrett, J. M. Semiconductor devices, P (4) 90*d*.
Miles, G. C. Umayyad and Abbasid glass weights and measure stamps in the Corning Museum, (11) 266*d*.
Miles, L. J. See Jones, I. Wynn.
Miles, L. J., and Jones, I. Wynn. Na transport through β-Al_2O_3 membranes, (9) 237*a*.
Milewski, J. V. See Shyne, J. J.
Milgram, A. A. Process of producing conductive Au patterns, P (11) 277*f*.
Miller, A. H., and Dean, G. A. Method and apparatus for handling sheet material, P (10) 244*i*.
Miller, C. C. Making bamboo handles, (2) 30*a*.
Miller, C. G. Depressurization of arc lamps, P (3) 57*j*.
Miller, C. O., and McAlister, C. G. Oxyhalogenation catalysts, P (4) 94*d*.
Miller, E. C. See Thompson, B. A.
Miller, F. E., and Martine, J. L. Preparation of Al_2O_3 of improved purity by Fe removal, P (1) 20*f*.
Miller, F. M. See Bredzs, N.; Tabikh, A. A.
Miller, H. C. See Metzger, L. H.
Miller, I. N. See Chemodanov, D. I.
Miller, J. E. See Dunlap, G. H.
Miller, J. P. See Lucas, R.
Miller, J. P., and Maxsted, M. D. Screen support, P (3) 69*g*.
Miller, K. J. Introduction to semiconductor surfaces as catalysts, (1) 11*b*. See Lin, Chinyueh.
Miller, L. J. Treated C cloth for the preparation of composite structures and method of treatment, P (5) 110*b*.
Miller, N. C. Antisublimation coating and method for thermoelectric materials, P (3) 64*d*. Mechanical mounting for a thermoelectric couple, P (9) 231*i*.
Miller, R. C. Glass sheet press bending mold, P (4) 82*b*.
Miller, R. C., Nordland, W. A., and Bridenbaugh, P. M. Dependence of 2nd-harmonic-generation coeffs. of $LiNbO_3$ on melt composition, (6) 146*h*.
Miller, R. G., and Cavitt, R. L. Electroless process for forming thin metal films, P (9) 218*j*.
Miller, R. W. Sealing technique for transparent lids on integrated circuit packages, P (3) 67*i*.
Millet, J. See Baron, A.
Millet, J., Benezech, G., Dubois, J., Canale, P., and Provost, G. Refractory rare-earth tungstate ceramics, (7) 180*e*.
Millis, W. T. Cathode construction, P (8) 192*b*.
Mills, A. L., and Vivers, R. W. J. Processing of irradiated nuclear fuels, P (10) 254*a*.
Mills, H., and Woods, L. Method and apparatus for inspecting a glass surface, P (9) 219*i*.
Mills, L., Marler, J. V., and Buntz, B. J. Methods, apparatus, and products for handling brittle materials [UO_2], P (10) 253*j*.
Mills, M. Changes in raw materials processing, (11) 276*h*.
Mills, R. G. See Chin, Jack.
Milly, G. H. Method of prospecting for mineral deposits having radioactive gaseous decay products [U,Th], P (2) 43*f*.
Milochevitch, A., and Roulot, M. Method of sealing metal in a vitreous enclosure, P (1) 5*c*.
Milovidova, L. V. See Arav, R. I.
Mil'shenko, R. S. See Litovskii, E. Ya.
Milsted, J. H. Bricks, (2) 35*e*.
Milyukov, E. M. See Shteinberg, Yu. G.
Mimkes, J. Diffusion along grain boundaries and dislocations, (5) 119*a*.
Mimura, Yoshiaki. Decrease in pinhole density by improving photoresist coating conditions, (11) 273*g*.
Minagawa, Katsuji. See Tanaka, Shigezo.
Minagawa, Shigekazu. Kinetics of growth of Al_2O_3 whiskers, (3) 74*d*.
Minagawa, Shigekazu, and Gatos, H. C. Equilibrium computation for the growth of α-SiC from silane and propane in the presence of H or an inert gas, (3) 73*e*.
Minakov, A. G. See Bondarev, K. T.
Minami, Tsutomu, Hattori, M., and Tanaka, M. Thermal expansion and its related properties of As-S-Te glasses, (3) 57*c*.
Minami, Tsutomu, Yoshida, A., and Tanaka, M. Electrical conduction in vitreous semiconductors in the system As-Se-Te, (3) 62*e*.
Minar, S., and Ruzicka, A. Glass grinding with tools with bonded synthetic diamonds, (3) 56*h*.
Minarik, R. W. See Bozanic, D. A.
Minchenko, A. V. See Sheinin, E. I.
Mindrup, W., and Ermel, D. Isostatic pressing by the Quintus process, (5) 115*e*.
Mindt, W. F. H., and Parisi, G. I. Technique for the fabrication of thin-film capacitor including PbO_2 conductive films, P (3) 67*j*.
Minegishi, Keiichi. See Mori, Hitoaki.
Minegishi, S. Method and apparatus for melting glassy materials by a rotary kiln, P (11) 270*d*.
Mineo, Takaji. See Okamura, Hajime.
Miner, J. E. See Trent, P. E.
Minin, V. I. See Bondarev, K. T.
Min'kov, D. B. See Fain, I. A.; Poluboyarinov, D. N.
Minneman, L. C. Glass shaping, P (9) 219*d*.
Minnick, L. J. Method of purifying hydrates of calcined dolomite and magnesite, P (10) 257*j*. MgO-containing refractory products and methods of making, P (3) 61*e*. Sulfopozzolanicly active fly ash and composition, P (4) 79*i*.
Minnick, W. J. Slagging in basic steelmaking process and compositions therefor, P (6) 135*g*.
Minnier, H. B. See Frey, J. O.
Minomura, Shigeru. See Okuyama, Naoki.
Minoura, Nachio, and Conley, C. D. Technique

for impregnating porous rock samples with low-viscosity epoxy resin, (3) 70*e*.
Minoura, Tatsuya. See Kubo, Kazuhiko.
Minshull, J. A. Nomogram for the calculation of shear stress, rate of shear, and viscosity from sliding plate microviscometer data, (5) 116*a*. Note on the geometry of the sliding plate microviscometer, (5) 116*b*.
Minz, F. R., and Zirngiebl, E. Preparation of Na_2CO_3, P (6) 144*a*.
Minzenberger, T. C. Process of back etching a perforated metal mask for color TV tubes, P (10) 245*c*.
Mirak'yan, M. M. See Pirogov, A. A.
Miranda, V. E. V. Spectrophotometric test apparatus and method employing retroflective means, P (4) 93*h*.
Miroshnichenko, O. Ya., and Doroshenko, V. P. Glass formation and properties of B-Mo glasses containing oxides of alkaline and alkaline-earth elements, (6) 132*b*.
Miroshnik, Z. A. See Ostrikova, N. V.
Misicka, M. Separation and determination of Pb and Ba oxides in glass analysis, (8) 205*d*.
Misetich, A. A. See Chappert, J.
Mishima, Haruo. See Koyanagi, Wataru.
Mishima, Kiyotaka. Strength characteristics of hardened Al_2O_3 cement, (6) 130*e*.
Mishin, I. V. See Shikunov, B. I.
Mishler, R. E. Apparatus for simultaneously applying a plurality of coatings to a substrate, P (6) 137*f*. Apparatus for successively applying a plurality of coatings to a substrate, P (6) 137*f*.
Mishra, G. L., Das, A. R., and Seshadri, V. Sintering kinetics, microstructure development, and grain growth in pure and SiO_2-doped hematite, (3) 75*e*.
Missiroli, A. See Emiliani, T.; Ravaglioli, A.
Missiroli, A., and Mosca, V. Apparatus for the determination of tensile adhesive strength [of ceramic wall tiles], (7) 164*i*.
Misson, G. W. Gas hearth with particular gas-supply channels [glass support], P (11) 270*h*. See Michalik, E. R.
Mistler, R. E. Strengthening Al_2O_3 substrates by incorporating grain growth inhibitor in surface and promoter in interior, P (7) 170*d*.
Misu, Sadayuki. Vacuum bottle, P (5) 107*i*.
Mita, Yoh. Optical probing of acoustic flux associated with moving high-field domains in semiconducting CdS crystals, (6) 150*f*.
Mitarai, Hajime, Nelson, C. E., and Youmans, A. P. Method for determining depth of lapping of dielectrically isolated integrated circuits, P (3) 65*e*.
Mitchell, A., and Cameron, J. Electrical conductivity of some liquids in the system CaF_2+CaO+Al_2O_3, (6) 147*f*.
Mitchell, D. F. See Sewell, P. B.
Mitchell, I. V., Kamoshida, M., and Mayer, J. W. Channeling-effect analysis of thin films on $Si:Al_2O_3$, (5) 111*h*.
Mitchell, I. V., Mayer, J. W., Kung, J. K., and Spitzer, W. G. Investigation of Te-doped GaAs annealing effects by optical- and channeling-effect measurements, (6) 149*b*.
Mitchell, J. E. See Alms, E. E.
Mitchell, J. K. See Wang, Mian-Chang.
Mitchell, M. J. See Munir, Z. A.
Mitchell, P. W. D. Chemical method for preparing $MgAl_2O_4$ spinel, (10) 258*c*.
Mitchell, R. F. Piezoelectric transducers having variable sensitivity between the boundaries of the piezoelectric crystal, P (9) 227*g*.
Mitin, B. S. See Zubarev, Yu. V.
Mitjunin, V. A. See Nemiorvskii, B. V.
Mitkevich, G. I. See Bondarev, K. T.
Mitoff, S. P. See Charles, R. J.; Tedmon, C. S., Jr.
Mitomo, Mamoru. Thermal etch patterns on SiC crystals, (3) 76*a*. See Inomata, Yoshizo.
Mitomo, Mamoru, Inomata, Y., and Kumanomido, M. Effect of doped Al on the thermal stability of 4H- and 6H-SiC, (3) 72*g*.
Mitra, M. N. See Das, D.
Mitra, N. K., Mukherjee, M., Vasistha, S. R., and Das Podder, P. K. Acid leaching characteristics of some nucleated borosilicate glasses on progressive heat treatment, (11) 267*h*.
Mitra, N. K., and Sarkar, A. K. Stability of alkali aluminosilicate hydrogel on progressive heat treatment, (11) 282*g*.
Mitra, N. K., Vasistha, S. R., Mukherjee, M., and Basumajumder, A. Effect of heat treatment on leaching characteristics of CaO-Al_2O_3-SiO_2 glasses, (2) 32*e*.
Mitra, S. S. See Kahan, A.; Vetelino, J. F.
Mitsche, R. T. Preparation of a crystalline aluminosilicate-Al_2O_3 catalyst composition, P (6) 144*h*.
Mitsuda, Takeshi, Hikichi, Y., and Murachi, M. Low-temp. synthesis of Al tobermorite, (9) 214*g*.
Mitsuda, Takeshi, and Murachi, M. Hydrothermal reactions between lime and zeolite, (9) 214*b*.
Mitsuhashi, Takefumi. See Chiba, Toshinobu; Fujiki, Yoshinori; Noguchi, Masayasu.
Mitsuhashi, Takefumi, Fujiki, Y., Tsukioka, M., and Tsuda, N. Crystalline transformation of ZrO_2, (3) 72*c*.
Mitsui, Yoshiaki. See Saito, Shuntaro.
Miura, Shigeto. See Inagawa, Konosuke.
Miura, Takeshi. See Suzuki, Takuya.
Miwa, Hisakatsu. See Kikumoto, Yukio.
Miyadai, Tomonao. See Fukui, Tsunaomi; Kanbayashi, Akio.
Miyagawa, Saburo, Hirano, S., and Somiya, S. Phase relations in the system MgO-B_2O_3, (11) 282*b*.
Miyahara, Syohei. See Fukui, Tsunaomi; Kanbayashi, Akio.
Miyahara, Yoshikazu, and Takajo, S. NMR in $Ga_xFe_{3-x}O_4$ and $GaNiFeO_4$, (3) 74*d*.
Miyai, Yukio. See Teramoto, Iwao.
Miyairi, Hidehiko, and Ikeda, I. Effect of basic ratio of the granulated blast-furnace slag on cement mortar strength, (4) 78*e*.
Miyaji, Akihiko. See Niwa, Yoshiji.
Miyaji, Hideo. See Tsukayama, Ryuichi.
Miyaji, Naoki, Tsuno, F., and Nakajima, K. Early estimation of compressive strength of concrete containing a large excess of H_2O-reducing admixture, (6) 128*b*.
Miyake, Shigenobu. Method for directly electrochemically extracting Ga from a circulating aluminate solution in the Bayer process by eliminating impurities, P (10) 257*h*.
Miyake, Shizuo. See Hayakawa, Kazunobu.
Miyake, Yasutomo, Shinada, T., and Ito, K. Transistor crystal oscillator operable at a subharmonic frequency of the crystal, P (2) 43*d*.
Miyako, Yoshihito. Observation of the substitutional Co^{2+} ions combined with the interstitial Ti^{4+} ions in rutile, (4) 97*j*.
Miyako, Yoshihito, and Kazumata, Y. ESR on rutile (TiO_2) with Co ions combined with O vacancies, (4) 96*b*.
Miyama, Hiroshi. See Tomii, Kaoru.
Miyamichi, Kazuo. Process for carbonized cellulose fiber or the products thereof, P (5) 110*b*.
Miyashiro, Shoichi. Photosensitive semiconductor device, P (9) 227*f*.
Miyashita, Meiji. See Takaku, Tetsuo.
Miyata, Itaru. See Kitamura, Toshinori.
Miyata, Takeo. Alloy junction transistor and a method of making, P (3) 64*c*.
Miyata, Yoshihiko. See Takemoto, Takeo; Uchida, Atsuyoshi.
Miyatani, Kazuo. See Okamoto, Fumio.
Miyauchi, Tsuneshige, Hirano, J., Ueki, A., Tatsumi, R., Mukai, K., and Yoshikawa, S. Stereoscopic microscope with graded index fiber objective lenses, P (7) 163*a*.
Miyazaki, Eiichi. See Tomii, Kaoru.
Miyazaki, Kouichi. See Kamei, Taketo.
Miyazaki, Masayoshi. Method of making semiconductor wafer, P (1) 13*g*.
Miyazaki, Takao. See Morita, Tadahisa; Tokuyama, Takashi.
Miyazawa, Kokichi. See Yamada, Shigeki.
Miyazawa, Shintaro. See Uchida, Naoya.
Miyazawa, Shintaro, and Iwasaki, H. Single-crystal growth of Pb_2MoO_5, (7) 180*f*.
Miyazawa, Toshihiko. See Nitta, Tsuneharu.
Miyoshi, Akimasa. See Tsukayama, Ryuichi.
Miyoshi, Kimio. See Nakanishi, Syosuke.
Mize, J. P. See Broce, M. E.
Mizuguchi, Hiroyuki. See Araki, Kenichi.
Mizukami, Kunio. See Kawamura, Shigeo.
Mizuno, Masao. See Noguchi, Tetsuo.
Mizuno, Osamu. See Maruyama, Mitsuhiro.
Mizunuma, Mamoru. X-ray stress-measuring apparatus, P (5) 116*h*.
Mizunuma, Tsutomu, and Azumi, T. Cement additive comprising Ca sulfoaluminate, an organic adhesive, a foaming agent, and a dispersing agent, P (8) 188*d*.
Mizushima, Koichi, and Iida, S. Photoconductivity spectra of Fe-doped TiO_2, (3) 74*f*.
Mizushima, Yoshihiko, and Sudo, T. Semiconductor switching element, P (8) 202*c*.
Mizushima, Yoshihiko, Takagi, T., Ochi, O., and Seki, M. Se-Te transducer employing piezoresistance effect, P (3) 67*i*.
Mlavsky, A. I. See LaBelle, H. E., Jr.
Mlynskaya, T. P. See Kochergin, V. P.
Mobarak, A. See Saada, M. Y.
Moberg, W. L. See Frank, R. I.
Mochida, Isao. See Kato, Akio; Nagano, Masamitsu.
Mochizuki, Masatoshi. See Uno, Tatujiro.
Mochizuki, Mitsuaki. Method of making sensing elements for resistance temp. probes, P (5) 116*g*.
Mod, W. A., and Caldwell, D. L. Source composition for alkali metal oxides and alkaline earth metal oxides, P (4) 95*b*.
Modine, F. A. See Kemp, J. C.
Moebus, G. Gas burner control apparatus for operating a piezoelectric ignition system in conjunction with the gas valves, P (10) 253*h*.
Moegenbier, J. Screening a color CRT, P (1) 14*h*.
Moehring, H. Enamel—more than just a protection against corrosion, (6) 131*a*.
Moelgaard, J., and Smeltzer, W. W. Thermal conductivity of magnetite and hematite, (5) 125*b*.
Moeller, A., and Straarup, O. Atomizer wheel with wear-resistant sintered bushings [spray dryer], P (5) 115*e*.
Moeller, E. C. Pneumatic drive means for grinding apparatus, P (2) 46*a*.
Moertl, G. L. Refractory fired MgO brick, P (10) 248*b*.
Moglestue, K. T. Spin waves in $Ga_xFe_{3-x}O_4$ [Ga-substituted magnetite], (5) 124*e*.
Mohapatra, S. K. See Ramani, S. V.
Mohr, R. K. See Scharf, K.
Mohr, T. O. See Drangeid, K. E.; Forster, T.
Mohr, W. C. H_2O absorption test methods, (1) 18*c*.
Moiseeva, V. P. See Borisova, I. I.
Mokhosoev, M. V. See Brekhunets, A. G.
Mokhosoev, M. V., Get'man, E. I., and Alekseev, F. P. Double molybdates of Rb and the rare-earth elements of composition $RbLn(MoO_4)_2$, (8) 208*f*.
Molchanov, V. C. See Ipat'eva, V. V.
Moldvai, R. Relations between structure and technical properties of Li Al silicates, (11) 282*b*.
Moline, R. A. See Foxhall, G. F.
Molineux, K. J. Glass as a material of construction, (4) 80*j*. Glass as a material of construction for chemical plant, (2) 32*g*.
Mol'kov, V. V. See Morozova, G. P.
Mollard, P. Fluidized bed process for obtaining granulated boric oxide, P (3) 71*j*.
Mollenkorf, H. Some solutions to mixing problems, (9) 229*e*.
Moller, W. M. See Tauber, A.
Molnar, B. See Davisson, J. W.
Molnar, L. Up-to-date pottery exhibited at the 38th International Ceramic Fair, Faenza (Italy), (2) 30*f*.
Molodkin, A. K. See Kharitonov, Yu. Ya.
Moltzan, H. J., and Walker, J. Production of metal oxides, P (5) 118*c*.
Momin, A. C., Mathews, M. D., and Karkhanavala, M. D. Studies in the system UO_2-ThO_2-O_2 (III) dilatometric and high-temp. X-ray diffractometric studies of U oxides, (11) 276*e*.
Momoi, Toshimitu. See Ono, Minoru.
Monaldi, R. See Cesca, T.
Monchamp, R. R., Weber, M. J., and Bass, M. Laser with a monocrystalline $YAlO_3$:Nd^{3+} active medium, P (2) 40*g*.
Moncunill de Ferran, E. See De Ferran, E. M.
Mondin, L. Ya. Effect of heat treatment on the magnetic properties of Ba ferrite powders (1) effect of the height of the layer of Ba ferrite powder during ferritization on its magnetic properties, (10) 249*b*.
Money, R. K. See Harbur, D. R.
Monneraye, M. Reducible vitreous material, P (4) 83*a*.
Montfort, Y. See Maisseu, A.
Montgomery, D. J. See Luxon, J. T.
Montgomery, E. C. Bath temp. control in float glass apparatus, P (5) 106*j*. Movable restrictor tiles in float glass apparatus and method of regulating glass ribbon, P (9) 219*e*.
Montgomery, H. C. Method for measuring electrical resistivity of anisotropic materials, (5) 116*a*.
Montgomery, L. C. See Mandorf, V., Jr.
Montgomery, R. M., and Young, E. H., Jr. Light diffraction by an acoustic surface wave in fused quartz, (5) 121*j*.
Montierth, M. R. See Beall, G. H.
Montorsi, M. See Brisi, C.
Moodie, A. F. See de Bruin, H. J.
Moody, J. W., and Reid, F. J. Infrared detecting materials, P (4) 88*f*.
Moody, M. See Hoogendoorn, C.
Mooi, J. See Sanford, R. A.
Mookherji, T. Origin of diamagnetism in MgO and CdO, (9) 237*h*.
Moon, Je Kil. See Tokumitsu, Yoshiharu.
Moon, R. L. See James, L. W.
Moore, A. W. See Knippenberg, W. F.
Moore, D. R., Ross, S. E., and Tesoro, G. C. Process for carbonizing cellulosic fibrous substrates, P (3) 61*c*.
Moore, D. W., and Day, D. E. Temp. variation in distribution of relaxation times in aluminosilicate glasses, (2) 33*c*.
Moore, E. B. See Comstock, R. L.
Moore, E. P., Jr. Process for preparing stable positively charged Al_2O_3-coated SiO_2 sols, P (3) 71*h*.
Moore, F. L. Isolation and purification of Am from other 5*f* and 4*f* elements by extraction chromatography, P (2) 43*e*.
Moore, G. E. Resistor for integrated circuit, P (4) 90*j*.
Moore, G. E., Jr., and Klein, M. V. Thermal conductivity of doped and pure CdS, (5) 125*a*.
Moore, H. Changing color in continuous furnaces, (3) 55*d*.
Moore, J. T., and Kuhlmann-Wilsdorf, D. Theory of dislocation cells (III) simple cells constructable from multipoles; (IV) hybrid cells, (5) 124*j*.
Moore, M., and Lang, A. R. X-ray topographic study of impurity platelet distribution and size in an inhomogeneous diamond, (10) 261*h*.
Moore, M. M. See Spangler, E. G.
Moore, P. J. Wet chemical methods, (9) 231*c*.
Moore, R. E. See Ainsworth, J. H.; Smith, Peter C.
Moore, R. L. See Chiao, T. T.
Moore, R. M. Heterojunction semiconductor transducer having a region which is piezoelectric, P (3) 65*c*.
Moore, R. M., and Busanovich, C. J. Device employing Se semiconductor heterojunction, P (3) 64*f*.
Moore, V. D., and Thompson, J. D. Sputtering of transparent conductive oxide films, P (4) 90*j*.
Moore, W. J. See Bishop, S. G.
Moorer, H. H., and Anderegg, C. M. Cement

grinding aid and pack set inhibitor, P (2) 31*e*.

Morrey, P. R. S. Authenticity of vessels and figurines in the Hacılar style (I) origins of the Oxford inquiry and the archeological background, (5) 101*h*.

Moorey, P. R. S., and Ucko, P. J. Authenticity of vessels and figurines in the Hacılar style (III) list of objects tested, (5) 101*h*.

Moori, Takahiko, Morikawa, H., Iwai, S., and Tagai, H. X-ray radial distribution function of high-Al_2O_3 glass, (3) 57*d*.

Moorthy, V. K. See Kulkarni, A. K.

Morachevskii, A. G., and Berdichevskii, N. I. Equilibria involving alkali metals and their compounds (VI) solubility of Na and K in melts of the systems NaOH-KOH, NaCl-KCl, and NaOH-KOH-NaCl-KCl, (7) 177*c*.

Moran, L. G. See Flautt, M. C.

Moran, T. J., and Luethi, B. Elastic and magnetoelastic effects in magnetite, (6) 147*c*.

Moratelli, P. A., Jr. See Goelzer, W. C.

Moratis, C. J., and Bratton, R. J. Resistivity behavior of semiconducting $YBaZrTiO_3$, (3) 63*e*.

Moreau, C. Process for the fabrication of nuclear fuel elements, P (9) 229*c*.

Moreau, J. Advantages of a study of crystalline inclusions in glass by reflection microscopy, (11) 267*i*.

Moreau, W. M., and Rottmann, H. R. Optical mask with integral spacers and method of making, P (10) 252*g*.

Morelock, C. R. Borocarbon-coated filaments, P (3) 61*b*.

Moren, R. E., and Ydren, N. E. Additive for concrete and mortar, P (8) 188*c*.

Morena, A., Jr. See Griffin, W. F.

Morgan, A. C. High combustion rate burner, P (2) 45*h*.

Morgan, C. Point contact semiconductor device, P (8) 202*c*.

Morgan, I. H. Method of providing integrated diffused emitter ballast resistors for improved power capabilities of semiconductor devices, P (3) 66*f*.

Morgan, P. E., and Roberts, R. W. Method of making a warp sheet comprising C filaments, P (8) 196*f*.

Morgan, P. E. D. Method of making dense MgO-Mg chromite spinel bodies, P (1) 9*c*. Pressure calcintering, P (10) 254*g*.

Mori, Hitoaki, Minegishi, K., and Ohta, T. Early hydration of $3CaO \cdot SiO_2$ in the presence of alkali, (4) 78*c*.

Mori, Hitoaki, Minegishi, K., Ohta, T., and Akiba, T. Effect of alkali carbonate on earlier stage of hydration of $3CaO \cdot SiO_2$, (9) 214*d*.

Mori, Makoto. See Fujii, Junnosuke.

Mori, Minoru. See Fujii, Junnosuke.

Mori, Takaaki. See Tokuyama, Takashi.

Mori, Tokiaki. See Kobayashi, Kazusuke.

Mori, U. CIER Ceramica Italiana SpA plant at Cagliari, (7) 165*b*.

Mori, Yasuhito. See Inoue, Ichiro.

Moriizumi, T. See Takahashi, K.

Morikawa, Hideki. See Iwai, Shinichi; Moori, Takahiko; Watanabe, Tetsuo.

Moriki, Juichi, Itoh, T., Shiosaki, M., Maeda, Y., Kuroki, H., Sumi, K., and Shimura, H. High-voltage piezoelectric transformer housed with diodes, P (8) 200*h*.

Morimoto, Nobuo, Tokonami, M., Koto, K., and Nakajima, S. Crystal structures of the high-pressure polymorphs of Mn_2GeO_4, (9) 234*e*.

Morinaga, Michio, and Yamamoto, M. Physical properties of portland cement plaster with plastering admixtures, (4) 79*g*.

Morinaud, P. C. Electrical lead-in tubular socket member for electronic tubes, P (9) 218*i*.

Morita, Keiichi. See Takahashi, Kazusaburo.

Morita, Shiro. Limitation of allowable steel stress for crack width control in reinforced concrete beams, (6) 129*b*.

Morita, Tadahisa. See Tokuyama, Takashi.

Morita, Tadahisa, Tokuyama, T., Tsuchimoto, T., Miyazaki, T., Nishimatsu, S., Ikeda, T., Sano, H., and Horiuchi, M. Method for fabricating semiconductor devices by ion implantation, P (2) 41*c*.

Morita, Tomijiro. See Shibata, Hiroshi.

Morita, Toshio. See Yamaguchi, Goro.

Moriwaki, Shogo. See Kawanishi, Nobuo.

Moriya, Yoshiro. Effects of components, other than the alkalis, on the phase separation of alkali silicate glasses, (3) 55*e*.

Moriyama, Tsunenori. Test results on cordierite chamotte made of "Omura" clay, (1) 8*f*.

Moriyoshi, Yusuke, and Komatsu, W. Kinetics of sintering at a constant rate of heating, (6) 149*g*.

Morkowski, J. See Schmidt, W.

Morley, D. I. See Henderson, S. T.

Mornon, J. P. Present tendencies in crystal-structure determinative methods, (8) 205*j*.

Morokuma, K., Eu, B. C., and Karplus, M. Collision dynamics and the statistical theories of chemical reactions (I) avg cross section from transition-state theory, (4) 95*c*.

Morosin, B. See Lynch, R. W.

Moroz, A. L. See Boiko, P. A.

Moroz, I. Kh. See Budnikov, P. P.

Morozov, I. S. See Korkhina, A. G.; Pham Ngok Thien.

Morozov, I. S., Avaliani, A. Sh., and Chatova, V. L. System In,Mg,K‖Cl, (5) 124*f*.

Morozov, V. I., Prygunov, V. F., and Khanov, V. M. Disk extruder, P (8) 203*i*.

Morozova, G. P., Tumanov, S. G., Mol'kov, V. V., and Vizir, L. A. Dulevo (USSR) Color Factory increases output, (8) 197*f*.

Morrette, R. A. See Luce, J. W.

Morris, D. E., and Bhargava, A. K. Development and production of ferrites by powder metallurgy in India, (12) 38*d*.

Morris, E. E. Performance of glass-filament-wound presure vessels with metal liners at cryogenic temps., (5) 106*f*.

Morris, F. J. See Arthur, J. R., Jr.

Morris, H. H., Olivier, J. P., and Ross, S. Separation of discolorants from clay, P (8) 207*g*.

Morris, J. R. See O'Keeffe, T. W.

Morris, M. C. See McMurdie, H. F.; Swanson, H. E.

Morris, M. L., Jr., Pope, H. L., Jr., and Ruggiero, E. M. Integrated heater element array and drive matrix, P (4) 88*h*.

Morris, R. C., Christopher, J. E., and Coleman, R. V. Conduction phenomena in thin layers of Fe oxide, (5) 118*j*.

Morris, R. W. Method of mfg. storage target for CRT, P (2) 34*f*.

Morris, W. G. See Charles, R. J.

Morrison, A. R., and Haynes, H. L. Size for fibers and glass fibers coated therewith, P (9) 220*a*.

Morrison, C. A., Wortman, D. E., and Farrar, R. T. Nuclear charged self-sustaining laser, P (9) 227*b*.

Morrison, C. R. See Klink, J. P.

Morison, E. See Lawrenson, J.

Morrow, B. A., and Devi, A. Adsorption of H_2O and ^{18}O exchange of surface hydroxyl groups on SiO_2, (7) 176*c*.

Morse, C. T., and Hill, G. J. Electric strength of Al_2O_3—the effect of porosity, (7) 165*j*.

Mortlock, A. J. See Harding, B. C.

Morton, P. H., and Barber, A. C. Method of fabricating a tubular superconductor assembly, P (3) 65*g*.

Morton, V. See Magee, J. H.

Mosca, V. See Missiroli, A.

Moscou, L. Reduction of the alkali metal content of crystalline aluminosilicates of the faujasite type, P (4) 95*b*.

Mosebach, W., and Piper, C. P. Solid electrolytic capacitors having an additional insulated layer formed on the dielectric layer, P (2) 42*g*.

Moser, C. See Carlson, K. D.

Moser, F., Matz, D., and Lyu, S. Infrared optical absorption in semiconducting CdF_2:Y crystals, (5) 121*c*.

Moser, M. Microhardness measurements and electron probe microanalysis studies of bond development between abrasive grains and binding material in grinding tools, (11) 265*e*.

Moshkina, M. K. See Sazhin, V. S.

Moskaleva, N. V. See Kolomytsev, P. T.

Moss, G., and Richard, G. P. Production of lime, P (3) 54*c*.

Moss, M., Cyrus, W. L., and Schuster, D. M. Properties of filament-reinforced plasma-sprayed Al_2O_3, (3) 54*h*.

Moss, S. C., and deNeufville, J. P. Thermal crystallization of selected thin films of Te-based memory glasses, (8) 192*a*.

Mostetzky, H. Movement of liquids in polycapillary materials when the supply of liquid is impeded (I) theory of movement of liquids in a single capillary and its experimental verification, (5) 122*d*.

Motai, Hirokazu. Dazzle-preventing and heat-locking glass sheet, P (7) 161*a*.

Motizuki, Kazuko. See Akion, Toshiro.

Motoi, Soichiro, Urushibara, K., and Hasegawa, S. Influence of SO_3 on the hydration of aluminous cement, (6) 129*i*.

Motoyuki, Inoue. Method of mfg. low-thermal-expansion porcelain, P (7) 166*a*.

Mott, J. H. Methods of making thin film patterns, P (3) 66*i*.

Mott, L. W. See Wiehe, A. E.

Mott, N. F. Conduction in glasses containing transition metal ions, (3) 55*f*. Conduction in noncrystalline systems (VII) nonohmic behavior and switching, (6) 145*c*.

Mottier, F., and Von Willisen, F. K. Arrangement for interferometric measurement of 2 lengths, P (2) 44*h*.

Motycka, V. See Doubrava, J.

Mouchart, J. See Guillet, H.

Moulson, A. J. See Kemp, J. L.

Mount, R. L. Precision wide-belt grinding saves material, (2) 29*g*.

Mountvala, A. J. Effect of surface moisture on dielectric behavior of ultrafine $BaTiO_3$ particulates, (1) 11*c*. See Bratschun, W. R.

Mourey, M. Y. C. See Mandineau, D. P. H.

Mourros, R. See Rivoire, C. L.

Moyant, D. A. Explosively activated glass valve, P (9) 218*j*.

Moyer, H. P. Self-rimming porcelain enameled sink, P (2) 32*a*.

Moyle, K. J., and Madden, L. P. High-voltage MOS transistor method and apparatus, P (4) 88*e*.

Moynihan, C. T. See Aggarwal, I. D.; Provenzano, V.; Schnaus, U. E.

Moynihan, D. J. See Hebert, R. A.

Mozley, R. H. See Muller, L. D.

Mras, R. J. See Dahlman, F. A.

Muan, A. See Kimura, Shigeyuki.

Mudrolyubova, L. P. See Limar, T. F.

Mueller, A. Device for heat treatment of Si disks, P (1) 12*h*.

Mueller, A., and Fink, A. Superconductive alloy and production thereof, P (10) 253*e*.

Mueller, A. P. Corrosion-inhibiting [perlite] thermal insulation for stainless steel, P (5) 109*g*.

Mueller, D. See Arndt, H. H.

Mueller, E., and Weimann, K. Semiconductor element for switching purposes, P (5) 114*e*.

Mueller, G. See Bachinski, S. W.

Mueller, H. A. See Fischer, P.

Mueller, J. Analyze abrasive performance and improve productivity, (2) 29*f*.

Mueller, J. I. See Kamdar, M. H.

Mueller, K. See Fitzer, E.

Mueller, K. A. See Axe, J. D.

Mueller, L. Thermal stresses in glass-to-metal seals of cylindrical bodies, (7) 160*j*. See Heller, K. H.

Mueller, P. H. See de Jongh, W. K.

Mueller, R. A. Fuel element bundle for nuclear reactors, P (8) 203*b*.

Mueller, R. O. Spectrochemical Analysis by X-ray Fluorescence, B (9) 240*f*.

Mueller, R. S. Reflection and refraction of plane waves from plane ferrite surfaces, (4) 86*i*.

Muenter, J. S. See Raymonda, J. W.

Muguruma, Hiroshi, and Kishimoto, S. Min. tensile reinforcement of reinforced concrete flexural member, (6) 129*e*.

Muguruma, Hiroshi, Tominaga, M., and Takaya, Y. Effects of reinforcements on the behavior of simply supported prestressed lightweight concrete beams under load history, (6) 128*f*.

Muguruma, Hiroshi, Tominaga, M., Takaya, Y., and Chung, Il-Yong. Inelastic behavior of statically indeterminate prestressed concrete structures assembled with precast units, (6) 129*g*.

Muguruma, Hiroshi, and Tomita, K. Deformation capability of jointed prestressed concrete piles, (6) 128*g*.

Muguruma, Hiroshi, and Watanabe, F. Ductility of eccentrically loaded reinforced concrete columns, (6) 128*a*.

Muhler, J. C. Dental amalgam polishing composition comprising $SnSiO_3$, P (2) 29*f*.

Muhler, J. C., and Stookey, G. K. Brush with abrasive-impregnated bristles, P (2) 29*j*.

Muirhead, J. Electrostatic glaze application, (4) 85*e*.

Mukai, Kunihiro. See Miyauchi, Tsuneshige.

Mukaiyama, Takashi. See Furuuchi, Shigemasa.

Mukerji, J. Behavior of Ru in glass, (10) 242*j*. Vaporization of Cs from Cs metaborate, Cs silicate, Cs borosilicate, and mixtures of Cs nitrate, boric oxide, and SiO_2, (11) 283*b*.

Mukerji, J., and Biswas, S. R. Oxidation states of Ru in glasses, (2) 32*e*.

Mukherjee, K. P., and Sarkar, B. Physicochemical properties of Indian magnetites, (11) 282*f*.

Mukherjee, M. See Mitra, N. K.

Mulay, L. N. See Danley, W. J.; DiSalvo, R.

Mulder, C. See Schmitz, A.

Mulfinger, H. O. Analysis of the contents of gas bubbles in glasses, (8) 204*f*.

Mullen, J. G. See Hang Nam Ok.

Muller, K. A. See Berre, B.

Muller, K. A., Berlinger, W., and Rubins, R. S. Observation of 2 charged states of an Ni-O vacancy pair in $SrTiO_3$ by paramagnetic resonance, (6) 150*d*.

Muller, L. D., Sayles, C. P., and Mozley, R. H. Gravity separation of granular materials, P (10) 254*j*.

Muller, M. Charging devices and balances for the ceramic industry, (6) 141*c*.

Muller, O. See Wilhelmi, K. A.

Mullin, J. V. See Jakas, R. P.

Mullot, M. See Warzawski, B.

Mulvaney, J. M. See Villers, P.

Mumford, E. H. Glass-forming machine, P (3) 58*i*.

Mund, K., and Schulte, R. W. Method of producing a WC-containing electrode for fuel elements, P (11) 272*b*.

Munekata, Mutuo. See Yamaguchi, Goro.

Munir, Z. A. Sublimation of IIB-VIA compounds (II) dependence of the sublimation pressure of CdS on crystalline orientation, (4) 99*d*. See Hansen, E. E.

Munir, Z. A., and Mitchell, M. J. Sublimation of IIB-VIA compounds (I) sublimation coeff. and activation energy for sublimation of single crystalline ZnS, (4) 99*c*.

Munoz, J. L. Hydrothermal stability relations of synthetic lepidolite, (4) 97*c*.

Muoio, E. L. Process for cleaning hard [sanitary ware] surfaces, P (10) 242*g*.

Murabayashi, Mineo, and Shirai, H. Crystal structure and particle shape of the carbonates for oxide-coated cathodes, (11) 273*e*.

Murachi, Mikio. See Mitsuda, Takeshi.

Murahashi, Kinjiro. See Nogi, Takaji.

Murakami, Hideaki. See Yamashita, Toshio.

Murakami, Keiichi. See Hori, Shoichiro.

Murakami, Kunio. See Obuchi, Satoru.

Murakami, Toshiaki. See Waku, Shigeru.

Murakami, Yoshio, Higashinakagawa, I., Yasuda, N., and Sato, M. Flat-type magnetic thin-film memory, P (7) 168*i*.

Murakami, Yoshio, Higashinakagawa, I., Yasuda, N., and Takeno, S. Method for mfg. magnetic thin-film element, P (9) 226*c*.

Murat, M. See Escoubes, M.

Murata, Fumitori. See Hattori, Makoto.

Murata, Hiroyuki. See Komeya, Katsutoshi.

Murata, Jiro, and Kamiyama, Y. Properties of aged gunite, (6) 129*j*. Strengthening of reinforced concrete slabs by bonding of steel plate with epoxy resin, (6) 130*e*.

Murata, Jiro, Otsuka, S., and Kikukawa, H. Solidification of radioactive waste, (10) 242*a*.

Murata, Takao, and Kudo, A. Foundry sand composition for cores and molds, P (9) 222*e*.

Murav'eva, I. A. See Spitsyn, V. I.

Murayama, Kazuo. See Yamane, Mikiya.

Murayama, Keiichi, and Kubota, K. Temp. dependence of optical harmonic generation in crystalline quartz, (3) 75*i*.

Murie, R. A. See Little, C. M.

Murphy, B. T. Method of fabricating semiconductor devices, P (6) 138*d*. See Glinaki, V. J.

Murphy, D. D. See Giddings, D. G.

Murphy, E. J. See Beebe, R. R.

Murphy, S. L. See Siegfried, E. C.

Murphy, T. Photocathodes for electronic discharge tubes, P (9) 227*d*.

Murr, L. E. Fossilization of electrical corona streamers from Si_3N_4 crystals in the electron microscope, (10) 255*d*.

Murr, L. E., and Inal, O. T. Field ion microscopy of graphite fibers, (5) 116*d*.

Murray, J. J., and Pear, C. B., Jr. Long-wearing magnetic head, P (9) 225*g*.

Murray, M. J. See Tauber, E.

Murray, R. W. See Welty, J. M.

Murray, T. P. Method and apparatus for estimating errors in pyrometer readings, P (2) 45*b*.

Murrmann, H. Method for producing metal structures on semiconductor surfaces, P (1) 13*h*.

Murthi, K. S. See Chan, R. K.

Murthy, G. K., and Caley, R. H. Electroconductive glaze and method for preparation, P (1) 12*j*.

Murthy, N. S. S., Natera, M. G., Youssef, S. I., Begum, R. J., and Srivastava, C. M. Yafet-Kittel angles in Zn-Ni ferrites, (5) 125*i*.

Muscatell, F. L. See Deverell, H. E.

Muschalla, B., and Simhan, R. Monitoring of forehearth temp. through a deviation controller, (8) 191*c*.

Mushran, S. P. See Verma, J. R.

Muta, Hiroki. See Shinoda, Daizaburo.

Mutaftschiev, B. Crystal-melt interface, (8) 199*c*.

Muto, Hideaki. See Satou, Sumio.

Muto, Katsutoshi. See Awazu, Kenzo.

Muto, Tadao. See Tomii, Kaoru.

Muto, Yuhei. See Yokota, Ryosuke.

Muttik, G. G. See Dzhigit, O. M.

Muxart, R. See Vernois, J.

Muzzin, L., and Peymirat, G. Apparatus for the rapid measurement of specific surface areas of powders by N desorption, (9) 230*f*.

Myagkova, M. A. See Gorshkov, V. S.

Myasnikova, K. P. See Golubtsova, R. B.

Myers, C. F. Integrated-circuit bipolar memory cell, P (4) 88*g*.

Myers, D. D. See Goelzer, W. C.

Myers, M. B., and Felty, E. J. Heats of fusion of the $A_2^{V}B_3^{VI}$ compounds As_2S_3, As_2Se_3, As_2Te_3, and Sb_2S_3, (9) 235*i*.

Myreen, B. Method and device for measuring the temp. of material in a rotary furnace, P (10) 256*a*.

Mysels, K. J. See Rix, C. E.

Myuller, R. L. Electrical Conductivity of Vitreous Substances, B (6) 153*i*.

Naber, C. T. Method of controllably oxidizing an Si wafer, P (6) 138*j*.

Nad, B. S. See Drobot, D. V.

Nada, Naohiro, and Yamashita, T. Phosphor for thermoluminescent radiation dosimeter, P (5) 113*h*.

Nadeau, J. S. See Carter, R. E.

Nadeau, J. S., Carter, R. E., and Rosolowski, J. H. Morphology of migrating bubbles in KCl crystals, (4) 97*h*.

Nadobnikov, M. N. See Rabodzei, N. V.

Nadrich, J., and Ericson, J. A. Closure for a bottom pour metallurgical ladle, P (10) 247*f*.

Nafziger, R. H., and Riazance, N. Alkaline-earth-fluoride-LaF_3 systems with implications for electroslag melting, (4) 95*c*.

Nagahara, Masayoshi. See Kawakami, Akira.

Nagahara, Shigehiro. See Suzuki, Yoshiro.

Nagai, Osamu. See Yamaguchi, Masafumi.

Nagano, Masamitsu. See Kato, Akio.

Nagano, Masamitsu, Kato, A., Mochida, I., and Seiyama, T. Effect of acid-base properties on the redox equilibrium of V in the molten V_2O_5-M_2O and V_2O_5-MPO_3 systems, (3) 72*f*.

Nagano, Masamitsu, Mochida, I., Kato, A., and Seiyama, T. ESR study of the structure of V in V_2O_5-Na_2PO_4 glasses, (6) 131*j*.

Nagano, Ranzo, and Kurumada, N. Influence of gypsum in portland cement on the properties of concrete, (6) 129*h*.

Nagao, Ishihiro. See Kimura, Morihiro.

Nagao, Kazuyoshi, and Katsura, A. Apparatus for producing bundles of optical fiber, P (1) 3*g*. Method of making fused bundles of light-conducting fibers, P (3) 59*e*.

Nagao, Shuichi. See Saito, Hajime.

Nagaoka, Hirotada. See Toda, Masumi.

Nagaoka, Kinnosuke. Electric melting of glasses—today and tomorrow, (6) 131*i*.

Nagarajan, A. Ultrasonic study of elasticity-porosity relation in polycrystalline Al_2O_3, (5) 125*a*.

Nagasawa, Koichi. Crystal growth of V_nO_{2n-1} by the chemical transport reaction and electrical properties, (1) 11*a*.

Nagasawa, Masahiro. Negative resistance device, P (10) 252*f*.

Nagasawa, Masahiro, and Shionoya, S. Electrical and optical properties of reduced SnO_2 crystals, (3) 72*j*. Electrical conductivity of SnO_2 single crystals at very low temps., (3) 72*i*. Properties of oxidized SnO_2 single crystals, (3) 74*i*. Temp. dependence of the fundamental optical absorption edge in SnO_2, (3) 75*h*.

Nagase, Kaneomi. See Taki, Hiromitsu.

Nagase, Tatsuo. See Tomita, Kinzo.

Nagashima, Y. See Takahashi, K.

Nagasima, Naoyuki. Contamination of SiO_2 films with Na atoms due to thermal oxidation of Si, (3) 72*h*.

Nagasima, Naoyuki, and Enari, H. Local crystallization of thermal oxide film of Si, (3) 63*e*.

Nagata, Minoru. Optoelectronic display panel, P (8) 201*j*. Probe header for testing integrated circuits, P (2) 42*c*. See Kaneoya, Ryoichi; Makimoto, Tsugio.

Nagata, Minoru, and Sato, K. Method for mfg. a semiconductor device, P (7) 169*e*.

Nagata, Takashi, Ishibashi, M., and Nakajima, Y. Piezoelectric ceramic resonator and mounting, P (3) 66*g*.

Nagata, Yuzihiro. See Suzuki, Takuya.

Nagato, Saburyo. See Obuchi, Satoru.

Nagatomo, Hiroto. See Yamada, Eiichi.

Nagatuka, Kotaro. See Uchida, Shinichi.

Nagels, P., Denayer, M., and Callaerts, R. Hall mobility in vitreous As_2Se_3, (2) 48*e*.

Nagibin, Yu. A. See Zubarev, Yu. V.

Nagorskaya, Z. S. See Kestner, O. E.

Naguib, A. G. E. Process for beneficiating ilmenite, P (8) 207*b*.

Nagy, K. See Horvath, T.

Nagy, K., Csurgay, I., and Terenyi, G. Experiments for the production of heat accumulating ceramic materials, (6) 134*i*.

Nagy, R. Lamp envelope with a thin transparent buffer film on its inner surface, P (3) 58*f*.

Naidenova, G. A. See Budnikov, P. P.

Naidich, Yu. V. See Eremenko, V. N.

Naidich, Yu. V., and Kolesnichenko, G. A. Investigation of the wetting of diamond and graphite by molten metals and alloys (V) carbide-formation kinetics at the graphite/metallic melt interface, (10) 259*f*.

Naidich, Yu. V., and Nevodnik, G. M. Wettability of the surface of SiC single crystals by metallic melts, (9) 239*e*.

Naiditch, S. Method of producing crystalline materials, P (2) 44*a*.

Naito, Kiyoshi, Toda, M., and Kakehi, T. Refractories for recent ammonia equipments, (2) 36*f*.

Naito, Makoto, Kasami, A., and Kawachi, M. Method of mfg. GaP electroluminescent diodes, P (3) 66*a*.

Naito, Ryuichi. See Sugai, Mikio.

Najmann, K. K., and Frantz, H. Monolithic integrated circuit having inversely operated transistors, P (4) 89*e*.

Naka, Hideaki. See Yamada, Shigeki.

Naka, Shigeharu, Ito, S., and Inagaki, M. Effect of shear on the quartz-coesite transitions, (7) 177*i*.

Nakagawa, Fumio. See Hosokawa, Masuo.

Nakagawa, Kenshi. See Horikawa, Susumu.

Nakagawa, Koji. See Niwa, Yoshiji.

Nakagawa, Kozi. Process for the production of cement expansive additives, P (9) 215*h*.

Nakagawa, Masuo. See Okada, Moritami.

Nakagawa, Takashi, Tsutsumi, T., and Hori, H. Semiconductor photosensitive device with a rare earth oxide compound forming a rectifying junction, P (9) 227*h*.

Nakahara, Nobuo. Method and apparatus for making spherical granules, P (3) 69*b*.

Nakai, Tetsuzo. See Suenaga, Masanobu.

Nakajima, Hisaaki. See Nishikawa, Tomozo.

Nakajima, Jun. See Doi, Kazuo.

Nakajima, Koji. See Miyaji, Naoki.

Nakajima, Rokuro. See Tabata, Hisanobu.

Nakajima, Saburo. See Yokota, Ryosuke.

Nakajima, Sataro. See Ishihara, Toshio.

Nakajima, Shigeo. See Morimoto, Nobuo.

Nakajima, Yasuo. See Nagata, Takashi.

Nakajima, Yoji. See Furuya, Masaaki.

Nakakuki, Yoshikazu. See Saito, Turuyoshi.

Nakamura, Atsushi, Takahashi, Y., and Matsunaga, K. Experiments on the properties of white portland cement concrete, (10) 241*i*.

Nakamura, Kazuyoshi. See Hasaba, Shigemasa.

Nakamura, Shigeaki. See Nakamura, Tadao.

Nakamura, Tadao, Nakamura, S., and Kohashi, T. Photoconductive ternary alloy of Cd, Se, and Hg, P (9) 227*e*. Photoelectric device with enhanced photoconductive sensitivity and storage effect of input radiation, P (1) 14*c*. Signal memory device, P (1) 14*c*. Solid-state image-converting device, P (6) 140*g*.

Nakamura, Tadashi. CRTs having row and column electrodes attached to opposite sides of insulating substrate, P (10) 243*i*.

Nakamura, Takanori. See Sudoh, Giichi.

Nakamura, Tetsuji. Magnetosensitive semiconductor switching device, P (2) 40*i*.

Nakamura, Tetsuro, Kose, S., and Sata, T. Paramagnetism and semiconductivity in a triclinic perovskite $BaBiO_3$, (4) 98*d*.

Nakamura, Tetsuro, and Sata, T. Moessbauer effect and magnetic susceptibility in ordered perovskite $(SrLa)(FeTa)O_6$, (3) 74*b*. Structural, magnetic, optical, and electrical properties in the perovskite system $BaCeO_3$-$Ba_2(CeTa)O_6$, (11) 282*g*.

Nakamura, Toshio, and Ozeki, H. Method of mfg. [tar-bonded] carbonaceous refractory products, P (11) 272*a*.

Nakamura, Yasusi. See Ueda, Tadao.

Nakamura, Yoshihiko. See Shimizu, Yasuhiro.

Nakanishi, Syosuke, and Miyoshi, K. Determination of Ge in Au-Ge alloys by atomic absorption spectrophotometry, (11) 277*i*.

Nakano, Mitsuko. See Yamaguchi, Goro.

Nakano, Mitsuko, Yamaguchi, G., and Saito, K. Analysis of ^{18}O in solid oxides by spark source mass spectrometry, (5) 118*h*. Role of O in the formation of spinel from MgO and Al_2O_3, (5) 123*e*. Thickness ratio of 2 spinel layers formed by solid-state reaction, (5) 125*d*.

Nakano, Saburo. See Tanemura, Tadashi.

Nakano, Satoshi. See Shibata, Hiroshi.

Nakano, Shigeki. See Kajii, Motohiko.

Nakanuma, Sho. See Kamoshida, M.; Tsujide, Tohru; Wada, Toshio.

Nakanuma, Sho, Haneta, Y., Fujimori, K., and Wada, T. Vapor deposition apparatus, P (5) 114*e*.

Nakanuma, Sho, Haneta, Y., and Wada, T. Integrated circuit having complementary FETs, P (3) 65*f*.

Nakanuma, Sho, Tsujide, T., and Wada, T. MIS-type semiconductor read-only memory device and method of mfg., P (8) 201*h*.

Nakanuma, Sho, Tsujide, T., Wada, T., Igarashi, R., and Onoda, K. Memory matrix using MIS semiconductor element, P (9) 226*a*.

Nakao, Tatsuhide, Kishi, I., Matsumoto, F., and Kaneko, I. Joint test planned by the Cement Assoc. of Japan for a portland cement sample, (6) 129*a*.

Nakao, Tatsuhide, Kishi, I., Nogi, K., and Kaneko, I. Test results of the 69-OC cement joint test in 1969, (10) 242*b*.

Nakaryakov, A. M. See Girskii, V. E.

Nakashima, Hiroshi, Tsuchihashi, S., and Eguchi, K. Study on the coordination number of B in borosilicate glasses by ir absorption spectroscopy, (5) 103*c*.

Nakashima, Hisao. See Takahashi, Susumu.

Nakata, Josuke. Thyristor with degenerate semiconductive region, P (5) 114*c*.

Nakata, Josuke, and Denda, R. Semiconductor controlled rectifier including 2 emitter regions, P (9) 227*d*.

Nakata, Koreaki, and Iida, Y. Solid electrolytic capacitor having a Ti-Zr alloy electrode, P (6) 140*f*.

Nakata, Roy, and Oppel, J. A. High-voltage ceramic capacitor assembly, P (9) 225*c*.

Nakata, Ryohei. See Zenbutu, Sakae.

Nakata, Teruo. See Kajii, Motohiko.

Nakatani, Kozo. See Kudo, Tetsuo.

Nakayama, Junn, and Fukatsu, Y. Introducing N gas into the melt to improve fused-cast refractories, P (9) 222*i*.

Nakayama, Niro. Pneumatic mill for extra-fine powder, P (1) 17*c*.

Nakayama, Takao, Kokado, H., and Inoue, E. Anomalous photoresponse on tetrazolium-ZnO system, (3) 72*e*.

Nakayama, Takashi. See Bacher, R. J.; Hoffman, L. C.

Nakayama, Toshio. Method for molding hollow and bottomed glass articles, P (8) 193*a*. See Matoba, Tamuro.

Nakayama, Toshio, and Horikawa, S. Method and apparatus for shaping the ends of glass tubes, P (7) 162*a*.

Nakazato, Kunio. See Nomura, Kazuhumi.

Nakhamkin, M. A. See Entelis, F. S.

Nalley, C. E., and Lovelace, J. B. Glass fiber size, P (7) 161*h*.

Nameda, Naoyoshi, and Kano, T. Fog lamp, P (3) 58*d*. Illuminating lamp having concave segments on exterior bulb surface, P (7) 162*d*.

Nameishi, Naoyuki. Mineralogical studies on corrosion by slag of MgO-CaO refractories used in lining of basic O steelmaking furnace, (I) physical properties and chemical compositions of the used refractories, (7) 163*h*.

Namikata, Takeshi, Hirata, K., and Ichikawa, Y. Method of mfg. solid capacitors, P (1) 13*b*.

Namikawa, Kazumichi. See Hayakawa, Kazunobu.

Namiki, Kazuo. See Izumitani, Tetsuro.

Nanamatsu, Satoshi. See Doi, Kikuo.

Nanamatsu, Satoshi, Sugiyama, H., Doi, K., and Kondo, Y. Ferroelectricity in $Pb_2Ge_3O_{11}$, (3) 73*h*.

Nanba, Kazuhiko. See Suzuki, Ichizo.

Nandi, D. N. See Banerjee, J. C.

Nanko, Yoshiyuki. See Irie, Toshiaki; Noguchi, Shozo.

Nann, R. G. See Shaffer, P. T. B.

Naoe, Masahiko, and Yamanaka, S. Vacuum-arc evaporation of ferrites and compositions of the deposits, (3) 64*a*.

Naomoto, Susumu, Kaneko, T., and Esaki, H. Planar *pn* junction with mesh field electrode to avoid pinhole shorts, P (10) 252*i*.

Napoli, L. S. Strip-type directional coupler having elongated aperture in ground plane opposite coupling region, P (8) 202*f*.

Napoli, L. S., and Hughes, J. J. Semiconductor device with plurality of small area contacts, P (7) 170*a*.
Napolitano, A. See Simmons, J. H.
Nara, Jiyuichi. Apparatus for fluidizing and drying pulverant materials, P (2) 43*i*.
Narasimhamurty, T. S. Photoelastic constants of α-quartz, (1) 24*d*.
Narayan, S. Y. See Collard, J. R.
Narayanaswamy, O. S. Model of structural relaxation in glass—correction, (1) 3*f*.
Naredi, R. G. F. J. Lifting members in wear lining for rotary drums, P (5) 115*h*.
Narita, Koziro. See Aiki, Kunio.
Narken, B. See Greenstein, B.; Hoogendoorn, H. M.
Naruse, Akira, Abe, Y., and Takami, A. Role of Al ion in the structure of alkaline earth aluminoborate glasses, (6) 132*g*.
Narva, V. K. See Kiparisov, S. S.
Naschke, J. H., and Taylor, R. L. Clarification of H_3PO_4, P (6) 143*j*.
Nash, F. R. See Bridenbaugh, P. M.
Nassau, K. See Henry, C. H.
Natera, M. G. See Murthy, N. S. S.
Nath, D. K. Al_2O_3 in the glassy and $3CaO{\cdot}Al_2O_3$ phases of a portland cement clinker in the system $CaO{-}Al_2O_3{-}SiO_2$, (1) 2*c*.
Nathanson, H. C., and Wickstrom, R. A. Conductor elements spaced from microelectronic component surface and methods of making, P (10) 250*d*.
Natola, F., and Touzain, P. K_2O and the $K{-}K_2O$ phase diagram, (7) 179*c*.
Natsenko, A. I. See Kainarskii, I. S.
Naudin, F. See Zarzycki, J.
Naugler, W. E., Jr. Semiconductor structures having improved hf response and power dissipation capabilities, P (4) 90*g*.
Nauroth, P. See Eisenmenger, E.
Nauta, C. J. Device for mixing, kneading, or drying substances, P (2) 44*a*. Device for stirring material or drying slurries or sludges, P (1) 16*g*. Device for treating one or more substances in a vessel provided with at least one rotatable stirring member, P (8) 203*h*. Lower bearing assembly for a mixing screw, P (2) 44*c*.
Nava, R., Callarotti, R., Ceva, H., and Martinet, A. Hypersonic attenuation by low-frequency optical phonons in $SrTiO_3$ crystals, (6) 148*e*. Microwave sound absorption by anharmonic 3-phonon interactions in TiO_2, (6) 150*h*.
Navarro, Jose M. Fernandez. See Fernandez Navarro, J. M.
Navazio, G. See Raccanelli, A.
Nayar, H. S., Lenel, F. V., and Ansell, G. S. Creep of dispersions of ultrafine amorphous SiO_2 in ice, (6) 145*f*.
Nayar, P. S. Semiconductor thermoelectric generators, (11) 274*a*.
Nayar, R. K. See Srivastava, K. K.
Naylor, W. A. Vitrified clay pipes, (2) 35*f*.
Nazarova, T. I. See Buldakov, A. A.
Neale, R. G. Amorphous electrode or electrode surface, P (2) 39*j*. Coplanar semiconductor switch structure, P (3) 64*e*. Device structures and fabrication techniques for amorphous semiconductor switching devices, (6) 136*g*. Film-deposited semiconductor devices, P (10) 250*d*.
Neale, R. G., and Ovshinsky, S. R. Method of selective wiring of integrated electronic circuits and the article formed thereby, P (4) 89*a*.
Nebelung, H. H. See Foster, T. V.
Nebelung, H. H., and Jaeger, E. Mold holder with thermostatically controlled mold, P (9) 219*e*.
Nebenzahl, I., and Weger, M. Band structure and lattice distortion in V_2O_3, (5) 118*i*.
Nebesar, B. Specialized instruments for the determination of S by the combustion method (I), (4) 93*c*; (III), (7) 173*h*.
Neddenriep, R. J. Zeolite agglomerate, P (4) 95*b*.
Nedeljkovic, A. I., and Cook, R. L. Thermal expansion of porcelain enamels containing Ce oxide, (1) 3*a*.
Neel, E. E. See Clement, C.
Neff, W. S. Flexible insulating sheet containing BN fibers and method for forming, P (10) 247*h*.
Negishi, Katuo. See Oi, Kazuo.
Negley, P. L. See Gehres, D. W.
Negro, A. See Amato, I.
Negus, R. W. See Carruth, W. L.
Neidhardt, M., and Schneider, J. Electrical heating element with fused MgO insulation, P (3) 61*d*.
Neis, D. A. Process for forming luminescent screens, P (6) 139*g*.
Neitzel, U. E. G. See Flint, H. G.; Ryan, J. H.
Nekrasov, N. N., Blinchikov, A. L., Kazanskii, V. L., Besedin, A. F., Krikunenko, A. F., Makarov, E. M., Zemskov, A. L., Afinogenov, F. I., Kirichenko, S. P., and Kulikov, A. A. Gas burner, P (10) 256*g*.
Nell, D. J., and Lewis, T. W., II. Impregnating porous ceramics with noncolloidal solids, P (9) 230*d*.
Nelson, C. E. See Mitarai, Haiime.
Nelson, C. E., Camenzind, H. R., and Youmans, A. P. Method for fabricating pinched resistor semiconductor structure, P (11) 275*c*.
Nelson, F. W., and Beer, L. N. Electrocoating of porcelain enamels, (3) 54*f*.
Nelson, G. V. See O'Keefe, W. H.
Nelson, J. A. See Wurst, J. C.
Nelson, K. E. Resistor [ZnO_2], P (4) 90*j*.
Nelson, L. S. See Meyer, R. T.
Nelson, P. A., and Wenz, D. A. Reprocessing a PuO_2-Mo fuel, P (6) 141*a*.
Nelson, R. L., Hale, J. W., and Harmsworth, B. J. Energy transfer in oxides (I) adsorption of O on MgO during γ-irradiation, (1) 21*j*.
Nelson, R. S. Magnifying devices for observing crystal lattice structures, P (1) 18*g*. See Rowse, R. A.
Nelson, W. F. See Barber, S. W.
Nemecek, P. See Zacpal, Z.
Nemeth, B. J., and Boeckeler, B. C. Piston construction for high-pressure apparatus, P (2) 44*b*.
Nemeth, J. See Blickle, T.
Nemeth, J., Youdelis, W. V., and Parr, J. G. High-temp. creep behavior of polycrystalline $SrZrO_3$, (4) 96*j*.
Nemets, I. I. See Kukolev, G. V.
Nemilov, S. V. Viscosity of glasses of systems $Na_2O{-}K_2O{-}SiO_2$ and $Li_2O{-}K_2O{-}SiO_2$ in the region of softening points, (7) 161*c*.
Nemilov, S. V., and Romanova, N. V. Viscosity of glasses of the system $PbO{-}B_2O_3$ in the region of the softening point and annealing temp., (8) 192*e*.
Nemirovskii, B. V., Korotin, B. A., Shatalin, B. S., and Mitjunin, V. A. Device for remote checking of operation and sensitivity of radiation monitors, P (10) 255*i*.
Nemoto, Kuniharu. See Tateno, Hideo.
Nepela, D. A. See Comstock, R. L.
Neronov, V. A. Phase diagram of the system Al-B, (5) 122*c*.
Nesbitt, E. A., Scaff, J. H., and Theuerer, H. C. Sputtered magnetic films, P (2) 42*h*.
Nesbitt, J. D., and Hemsath, K. H. Gas-treating apparatus, P (1) 19*d*.
Nesterova, A. L. See Borisov, V. G.
Nesteruk, E. K. Metal oxide coatings on glass, P (6) 133*f*.
Nethercot, A. H., Jr. See Lorenz, M. R.
Netherwood, P. H. Multilayer beam-lead wiring for [ceramic] semiconductor packages, P (11) 275*g*.
Netten, A. See Kwestroo, W.
Nettleton, F. S. See Gardner, F. M.
Neu, W. See Herrman, R.
Neubauer, H. Operating experiences with the Roirant S-10 machine, (8) 191*h*.
Neuberger, M. Handbook of Electronic Materials (Vol. 2) III-V Semiconducting Compounds, B (1) 27*f*; (Vol. 5) Group IV Semiconducting Materials, B (6) 154*c*.
Neugebauer, C. A. See Burgess, J. F.
Neumann, B. S. Synthetic claylike minerals of the smectite type and method of preparation, P (9) 233*c*.
Neumann, B. S., and Sansom, K. G. Composition and process for making stable aqueous sol of synthetic silicate, P (7) 175*b*. Rheological properties of dispersions of laponite, a synthetic hectorite-like clay, in electrolyte solutions, (9) 238*g*.
Neumann-Venevere, P. Natural and controlled bloating of clays for the production of lightweight aggregates, (5) 108*c*.
Neuroth, N. See Faulstich, M.
Neville, R. R. See Collins, N. E.
Nevodnik, G. M. See Naidich, Yu. V.
New, T. C. See Ernick, F. G.
Newkirk, J. B. See Barrett, C. S.; Heinrich, K. F. J.
Newman, R. L. Prediction of thermal-shock resistance during heating at very high rates, (10) 255*j*.
Newnham, R. E. See McCauley, J. W.
Newnham, R. E., Wolfe, R. W., and Dorrian, J. F. Structural basis of ferroelasticity in the Bi titanate family, (2) 39*d*.
Newns, G. R. See Faktor, M. M.
Newton, R. G. Enigma of the layered crusts on some weathered glasses, a chronological account of the investigations, (5) 101*j*. Possible indicator of furnace profitability, (9) 218*a*. Preliminary examination of a suggestion that pieces of strongly colored glass were articles of trade in the Iron Age in Britain, (5) 102*a*. Stereoscan views of weathering layers on a piece of ancient glass, (11) 269*j*.
Nezhevenko, L. B., Gurevich, B. D., Groshev, V. I., and Bokov, O. V. Influence of the density of ZrC compacts on the density of sintered specimens, (10) 247*b*.
Ng, D. M., and Rehkope, C. H. Optical system for forming a windowed web in a color cathode-ray tube screen structure, P (9) 227*d*.
Nguyen Chong Yen. See Golub, A. M.
Nguyen Van Tran and Shah, J. C. Broad-band optically pumped semiconductive lasers, P (10) 249*h*.
Ngwe, Tin. See Yasuoka, Hiroshi.
Nicholas, M. G., and Hodkin, E. N. Grain-boundary grooving of UC, (7) 171*i*.
Nicholls, G. D. Developments in spark-source mass spectrographic analysis of silicate and allied materials, (9) 230*j*.
Nicholls, J. E. See Garlick, G. F. J.
Nichols, C. E., Jr., and Howard, G. T. Concrete block or the like with multiple brick facing and method of making, P (8) 194*e*.
Nichols, G. E., Jr. Coated screens, P (10) 105*f*. Slurry screen and process of making, P (9) 230*e*.
Nichols, R. A. Method and means for constructing and erecting building structures formed of bricks or the like, P (8) 194*f*.
Nicholson, D. G. See Kjekshus, A.
Nicholson, P. S. See Burte, A. S.; Daw, J. D.; Garvie, R. C.; Shelley, R.
Nickelsen, H. O., Kopanda, J. E., and Piasecki, F. J. Method of making cement clinkers, P (10) 242*e*.
Nicki, J. Method of producing filamentary monocrystals, P (1) 13*g*.
Nickle, S. Ceramic necklaces, (2) 30*b*.
Nicklin, T., Clack, J., and Burgess, K. H. U oxide catalyst, P (4) 95*b*.
Nicol, A. W., and Roy, R. Growth of oxide single crystals by topotactic reaction, (2) 48*c*.
Nicol, J. P. Novel lightweight asbestos-containing cementitious material and process for producing, P (8) 196*h*.
Nicol, W. S. Vapor deposition apparatus, P (1) 15*a*.
Nicolai, V. O. Optical windows [GaSb] for lasers, P (2) 41*i*.
Nicolaides, R. See Walsh, P. J.
Nicolas, J. See Lagrange, A.
Nicoll, F. H. Electron beam excited laser, P (8) 200*a*.
Nicollian, E. H. See Kahng, Dawon.
Nicollian, E. H., Berglund, C. N., Schmidt, P. F., and Andrews, J. M. Electrochemical charging of thermal SiO_2 films by injected electron currents, (7) 166*i*.
Nidorf, P. X. Stoneware medallions, (2) 30*e*.
Nieda, Tamotsu. See Yoshioka, Yasuhiko.
Niedermiller, H. C. See Colson, W. B.
Niedrach, L. W. Fuel cell electrode, P (1) 12*d*.
Nielsen, A. Oil atomization burner, P (7) 174*g*.
Nielsen, B. R., Hazell, R. G., and Rasmussen, S. E. Crystal structure of $BaTeO_3{\cdot}H_2O$, (11) 280*e*.
Nielsen, L. E., and Fields, J. E. B-reinforced composite, P (7) 164*b*.
Niemitz, G. Process and apparatus for preheating limestone and the like, P (1) 2*g*.
Niemyskii, T. See Paderno, Yu. B.
Nienhuis, R. J. IGFET with integrated safety diode, P (6) 138*b*. See Sangster, F. L.
Nienhuis, W. F., Spanhoff, G. A., Willem, J., and Bocke, K. Method of mfg. an implosion-free display tube, P (1) 5*a*.
Nier, J. Method of assembling a semiconductor device, P (2) 40*j*.
Nies, N. P., and Hulbert, R. W. Zn borate of low hydration and method of preparing, P (6) 144*h*; P (10) 258*a*.
Niesel, K., and Schimmelwitz, P. Hardening and weathering processes of dolomite lime mortars, (5) 103*f*.
Niesz, D. E., Bennett, R. B., and Snyder, M. J. Strength characterization of powder aggregates, (10) 248*h*.
Niffka, H. Automatic plate manufacture on a high-capacity production line, (5) 110*e*.
Nigam, A. K. See Argon, A. S.
Nihira, Takeshi. See Iwata, Tadao.
Niizeki, Nobukazu. See Yamada, Tomoaki; Uchida, Naoya.
Nikam, P. S. See Goswami, A.
Nikiforov, L. V. See Chizhikov, D. M.
Nikirk, R. G. See Rogers, L. C.
Niklas, L. Programed ultrasonic pulse-echo apparatus for flaw size indication in materials testing, P (6) 142*g*.
Nikles, F., and Oguey, H. T. Assembly comprising an adjustable capacitor and a printed circuit, P (7) 168*i*.
Nikolaev, A. N. See Mal'tsev, M. V.
Nikolaev, R. K. See Nisel'son, L. A.
Nikulina, L. N., and Levin, D. I. Effect of quartz genesis on the nature of its solution during porcelain firing, (8) 197*g*.
Nilsen, A. N. See Lynd, L. E.
Nilsen, W. G. Raman spectrum of cubic ZnS, (5) 123*d*.
Nink, H. Piezoceramic transformer, (11) 274*d*.
Ninomiya, Kiyosha, and Ohara, H. Friction material [Fe_3O_4], P (8) 196*i*.
Ninomiya, Mitsuo, Ohta, H., Nozaki, Y., and Wakao, Y. Fluid sand mold using H_2O glass and slag, (3) 60*i*.
Nisbet, J. L., and Woodall, H. C., Jr. Finished glass textile materials and method of forming, P (7) 161*e*.
Nisel'son, L. A., Nikolaev, R. K., Vasilevskaya, I. I., and Vasil'eva, A. G. Some properties of Re_2O_7, (1) 25*f*.
Nishcheta, V. V. See Zubarev, Yu. V.
Nishi, Gosaburo. See Ojima, Teruhiko.
Nishi, Masaaki. See Maki, Iwao.
Nishi, Masato, Fujita, T., Fujii, A., and Kato, S. "Mirror" spectrum of 572 nm band in reactor-irradiated CaO, (3) 74*a*.
Nishi, Seiya, Oshio, A., and Kiyomitsu, E. Method of producing high-strength mortar or concrete, P (10) 242*e*.
Nishi, Tsuyoshi. See Masuyama, Takeshi.
Nishibashi, Reiko. See Kato, Akio.
Nishibayashi, Shinzo, Kojima, T., and Matsumoto, T. Experimental studies on properties of the concrete using crushed stone coarse aggregate, (6) 128*i*.
Nishida, Masamitsu, and Ouchi, H. Piezoelectric ceramic compositions, P (5) 113*i*; P (6) 139*b*; P (7) 170*a*; P (9) 227*f*.
Nishida, Shinichi. See Sunano, Naomasa.
Nishida, Shinji, and Tabata, K. Outline of tar-dolomite plant in Romania, (2) 36*a*.
Nishihori, Tadanobu. See Fujita, Yoshio.
Nishikawa, Hisashi. See Ichinose, Noboru.
Nishikawa, Tomozo, Abe, H., and Umeya, K.

Temp. dependence of internal friction of Ni-Zn ferrite, (6) 152*j*.

Nishikawa, Tomozo, and Ikeda, A. Abrasion and temp. dependence of the internal friction of some polycrystalline ferrites, (3) 62*c*.

Nishikawa, Tomozo, Nakajima, H., Ishida, T., and Umeya, K. Creep behavior of Ni-Zn ferrites, (5) 111*i*.

Nishimatsu, Shigeru. See Morita, Tadahisa; Tokuyama, Takashi.

Nishimoto, Tatsuya. See Osada, Mitsuo.

Nishimura, Akio. See Waku, Shigeru.

Nishimura, Hiroshi. See Tamaoki, Osamu.

Nishimura, Katsuyuki. See Goto, Tsuneaki.

Nishimura, Kazuhira. See Toda, Masumi.

Nishinaga, Tatau. See Ogawa, Hiroshi.

Nishio, Shinji. Recent development of ceramic and cement cutting tools, (3) 53*i*.

Nishioka, Kazumi, Pound, G. M., Lothe, J., and Hirth, J. P. Comments on homogeneous nucleation theory, (5) 118*f*.

Nishiwaki, Takeshi. See Fujii, Junnosuke.

Nishiyama, Keijiro. See Kobayashi, Kazusuke.

Nishizawa, Jun-ichi. See Okuno, Yasuo.

Nishizawa, Jun-ichi, and Sukegawa, T. Electroluminescent *pn* junction semiconductor device for use at higher frequencies, P (4) 87*e*.

Nishizawa, Masahiro. Method of making phosphor screen for color CRT, P (10) 251*g*.

Nisol, M. See Mayaux, P.

Nitta, Tsuneharu, and Miyazawa, T. X-ray and thermal-expansion study of an $(Na_{0.88}Li_{0.12})NbO_3$+6 mol% Li_2O ceramic, (1) 26*d*.

Nitzsche, H. G., and Fickel, A. Ceranox materials—preparation, properties, and applications, (9) 221*e*.

Nitzsche, S., Kaiser, W., Wohlfarth, E., and Hittmair, P. Method for preparing hydrophobic SiO_2, P (10) 257*i*.

Niwa, Hisao. Planning of powder processing equipment—incidental facility, (6) 141*f*.

Niwa, Shohei. Refractories for continuous casting of steel, (6) 134*h*.

Niwa, Yoshiji, Kobayashi, S., Koyanagi, W., and Nakagawa, K. Microcracks of concrete under triaxial compression, (6) 129*d*.

Niwa, Yoshiji, Kobayashi, S., and Miyaji, A. Considerations on fracture criteria of cement mortar subjected to multiaxial compression, (6) 128*d*.

Nix, W. D. See Coghlan, W. A.

Nixon, D. See Saull, R. C.

Nixon, F. Apparatus for use in the mfg. of flat glass, P (11) 270*a*. See Dickinson, G. A.

Nobes, M. J. See Carter, G.

Nobes, M. J., Colligon, J. S., and Carter, G. Equilibrium topography of sputtered amorphous solids (I), (2) 47*d*.

Nobili, A. See Calza Bini, A.

Noble, F. R. Clay, P (10) 257*d*. Disorder in kaolinite, (6) 146*d*.

Noble, L. A. Method of producing neutron source tube with coated target, P (5) 115*c*.

Noda, Minoru. See Kawabata, Kunio; Onuma, Eiichi.

Noe, R. J. Photoconductive recording member utilizing a mixture of ZnO and CdS-CdSe, P (8) 202*a*.

Noel, S. See Palavit, G.

Noerlund Christensen, A. Hydrothermal preparation and low-temp. magnetic properties of TbOOH, DyOOH, HoOOH, ErOOH, and YbOOH, (8) 209*j*.

Noerlund Christensen, A., and Ollivier, G. Hydrothermal and high-pressure preparation of some $BaMnO_3$ modifications and low-temp. magnetic properties of $BaMnO_3(2H)$, (8) 209*h*.

Nogi, Koji. See Nakao, Tatsuhide.

Nogi, Takaji, Murahashi, K., and Suzuki, T. Effects of curing temp. on the strength of cement, (6) 128*e*.

Noguchi, Akio. See Hamamoto, Hujio.

Noguchi, Masahiko. See Taga, Koji.

Noguchi, Masayasu. See Chiba, Toshinobu.

Noguchi, Masayasu, Chiba, T., Mitsuhashi, T., and Tsuda, N. Positron life time in ReO_3, (3) 74*g*.

Noguchi, Seizo. See Inoue, Touru; Itakura, Kiyoshi.

Noguchi, Shozo, and Nanko, Y. Hermetically sealed semiconductor device, P (8) 200*g*.

Noguchi, Tetsuo, and Mizuno, M. Liquidus curve measurements in the ZrO_2-MgO system with the solar furnace, (3) 74*d*.

Noguchi, Tetsuo, Mizuno, M., and Yamada, T. Liquidus curve of the ZrO_2-Y_2O_3 system as measured by a solar furnace, (3) 74*e*.

Nomura, Kazuhumi, Nakazato, K., and Matsui, H. Method for separating alcohols and hydrated Al_2O_3 from hydrolysis products of Al alkoxides, P (6) 144*e*.

Nomura, Setsuo, and Sugata, E. Field desorption of Cs from a Cs covered oxygenated W surface, (3) 73*i*.

Nomura, Shoichiro. See Abe, Masanori; Yoshimoto, Jiichiro.

Nomura, Shoichiro, and Kojima, F. Preparation and dielectric properties of K Bi Zn niobate, (4) 98*b*.

Nonomura, Takuo, and Yamamoto, K. Charge distribution and thermally released current in γ-irradiated Ce glass, (3) 55*e*.

Noothout, A. J. See Kanij, J. B. W.

Nordland, W. A. See Cohen, E.; Miller, R. C.

Nordquist, L. E. See Piper, J.

Nordyke, J. S. Pb in glazes—introductory remarks, (1) 10*e*.

Norin, R. Crystal structures of $Nb_{39}O_{147}F$ and $Nb_{32}O_{101}F_3$, (6) 146*d*.

Norin, R., and Rappinger, B. Phase composition of the NiO-Nb_2O_5 system, (11) 281*i*.

Norkin, I. M., Ermolenko, V. A., and Evtukh, V. V. Selection of distance between points of measurement during mine surveys, (8) 207*a*.

Norman, R. S. See Gordon, W. D.

Noro, Masaharu. See Saito, Turuyoshi.

Norris, P. E. Method of detecting the completion of plasma anodization of a metal on a semiconductor body, P (8) 201*j*. See Micheletti, F. B.

Norsworthy, R. G. H_2O slide-off decals, (3) 57*c*.

North, W. D. See Castrucci, P. P.; Collins, R. H.

Northover, W. R. See Bagley, B. G.

Norton, C. L., Jr. See Wallace, R. W.

Norton, F. H. Fiber optic bundle fusion, P (3) 58*a*.

Norton, W. J. [Pneumatic] classifying system, P (2) 44*c*.

Nosch, E. Method of producing semiconductor devices, P (1) 13*i*.

Noshiro, Makoto, and Jitsugiri, Y. Rapid analysis of F in glass by the use of fluoride-ion-sensitive electrode, (11) 278*a*.

Notarius, H. Dark forsterite ceramic composition, P (6) 137*j*.

Notelteirs, V. R. Electric incandescent lamp with an improved pinch seal, P (10) 244*d*.

Nouveau, H. Linings for ingot molds and foundry molds, P (8) 196*c*.

Novak, D. L. See Hollox, G. E.

Novak, E. J. Spark plug with single-piece ceramic insulator with tubular portion extending into scavenging chamber, P (1) 14*i*.

Novak, J., Vrestalova, M., and Stefkova, V. Application of digital computers in the assessment of thermal engineering data in cement factories, (5) 102*d*.

Novak, J. P. Method of treating an alloy steel for enameling, P (9) 216*a*.

Novikov, G. I. See Dudchik, G. P.

Novikov, V. I. See Paderno, Yu. B.

Novikov, V. N. See Egorova, T. N.

Novokhatskii, I. A., and Pavlov, V. G. Behavior of a proton in oxide glasses, (9) 216*b*.

Novoselova, A. V. See Vanyarkho, V. G.

Novoselova, A. V., Odin, I. N., and Popovkin, B. A. Interaction of the chalcogenides and halides of Pb, (8) 209*b*.

Novosel'skii, L. G. See Syrkin, Ya. M.

Nowak, A. E. See Majdic, A.

Nowak, A. E., Brueckner, R., and Hennicke, H. W. Comparative investigations defining chemical attack of enamel surfaces, (11) 267*d*. Comparative investigations defining mechanical attack of enamel surfaces, (11) 267*e*.

Nowick, A. S. Study of defect reactions in crystals by means of anelastic and dielectric relaxation, (7) 181*h*.

Nowick, A. S., and Berry, B. S. Anelastic Relaxation in Crystalline Solids, B (10) 262*g*.

Nozaki, Hiroshi. See Yamazaki, Masaki.

Nozaki, Ken. Development of materials for energy, (6) 136*f*.

Nozaki, Sadasumi. See Kimura, Shigeo.

Nozaki, Yoshihiko. See Ninomiya, Mitsuo.

Nuccio, C. See Lester, W. C.

Nuese, C. J. See Fischer, A. G.

Nunn, H. R. Antipollution chamber, P (9) 229*f*.

Nunome, Keichi. See Funabashi, Wataru.

Nurse, R. W. See Lawrence, P.

Nussbaum, M. See Englert, G.

Nuttall, R. L. See Fredrickson, D. R.

Nyankovskaya, R. N. System of the fluorides, iodides, and carbonates of Na and K, (5) 124*e*.

Nybo, S. A. Device for detection and location of failed nuclear fuel elements, P (9) 228*g*.

Nye, J. D. System for feeding grinding media to continuous attrition mill, P (10) 254*j*.

Nyitray, I. See Vasadi, F.

Nyunt, Kan. and Soe, K. Complexometric determination of lime and MgO in calcite, dolomite, gypsum, and other silicate rocks, (3) 69*h*.

Oakley, R. See Ropp, R. C.

Oates, W. A. See Shaw, J. G.

Obata, Shuichi. See Oda, Fujio.

Obayashi, Seiichi. See Oishi, Kenichi.

Oberai, A. S. Semiconductor device having high switching speed and method of making, P (3) 67*b*. See De Witt, D.; Medvecky, B. P.

Oberfeuer, B. See Heuner, W.

Oberholzer, D. J. See Graham, C. E.

Oberli, R. Specimen-analyzing apparatus, P (4) 93*h*.

Oberlin, D. W., and Kamins, T. I. Complementary *npn/pnp* structure for monolithic integrated circuits, P (2) 39*g*.

Oberly, J. E., Coless, T. L., and Rimer, K. W. Welding flux composition, P (8) 189*d*.

Obidina, S. P., and Bush, A. N. Glass for mfg. glass-coated microwire, P (2) 34*g*.

Obolonchik, V. A. See Semenov-Kobzar, A. A.

Oborn, P. See Bruce, J. A. G.

Obraztsov, A. I. See Kharinskaya, M. A.

O'Brian, C. D. See Corish, J.

O'Brien, J. F., Dienes, E. K., and Hausberger, A. L. Low-temp. Cu-Zn shift reaction catalysts and methods for preparing, P (2) 46*i*.

O'Brien, M. C. M. See Ham, F. S.

O'Brien, N. R. Fabric of kaolinite and illite floccules, (6) 148*c*.

O'Brien, T. E. Low-voltage pulser circuit for driving row-column conductor arrays of a gas discharge display capable of being made in integrated circuit form, P (10) 251*d*.

O'Bryan, H. M., Jr. See Krause, J. T.; Meitzler, A. H.

O'Bryan, H. M., Jr., and Meitzler, A. H. Enhanced ordering of ferroelectric domains in PLZT ceramics, (6) 136*i*.

Obst, M. See Jirkowsky, J.

Obuchi, Satoru, Fukuoka, T., Nagato, S., Murakami, K., Shigeta, T., and Hayashi, H. Process for pretreating glass fibers for reinforcing rubber articles, P (11) 270*h*.

Ocepek, D., and Komljenovic, R. Coagulation and flocculation of kaolin suspensions, (2) 46*a*.

O'Cheskey, T. H. Adjustable knife blade for dry filter cake discharge, P (6) 141*g*.

Ochi, Osamu. See Mizushima, Yoshihiko.

O'Clair, C. R. See Greskovich, C.

O'Connell, T. B. See Oelke, W. W.

O'Connor, J. J. See Armington, A. F.

Oda, Fujio, and Obata, S. Semiconductor stress transducer, P (10) 253*a*.

Odajima, Akira. See Ueno, Tokihiro.

Odake, Kimio. See Okada, Kiyoshi.

Oden, L. L. See Pankratz, L. B.

Odent, G., and Annabi, F. Cryoscopic study of various germanates of trivalent elements, (6) 145*g*.

Odhiambo, D., and Desai, N. C. Sorption of benzene by Kenya diatomite, (5) 117*j*.

Odier, P., Loup, J. P., and Anthony, A. M. Use of thermal electron emission to study point defects in Y_2O_3, (7) 182*c*.

Odin, I. N. See Novoselova, A. V.

Odler, I. Properties of low-porosity alite pastes, (5) 104*g*. See Brunauer, S.; Skalny, J.; Yudenfreund, M.

Odler, I., Yudenfreund, M., Skalny, J., and Brunauer, S. Hardened portland cement pastes of low porosity (III) degree of hydration. Expansion of paste. Total porosity, (10) 241*i*.

Odom, I. E. Clay and shale resources of Madison, Monroe, and St. Clair counties, Ill., (3) 71*b*.

O'Donovan, K. H. J. See Pope, N. C.

Oeffinger, T. R. See Braginski, A. I.

Oehlschlegel, G. Binary partial system BaO·$2SiO_2$-2BaO·$3SiO_2$, (8) 189*f*.

Oehme, F. See Krauer, W.

Oel, H. J., and Dietzel, A. Stress distribution in the system wall-mortar-body-glaze in fixed wall tiles (II), calculation of stress, (4) 85*d*.

Oelke, W. W., Carson, F. J., and Badger, A. E. Method and apparatus for bending and tempering glass sheets, P (4) 82*j*.

Oelke, W. W., O'Connell, T. B., and Herrington, R. A. Method and apparatus for heat-treating glass sheets, P (5) 107*b*.

Oesterhelt, G. See Kunert, A.

Oesterhelt, G., and de Bucs, E. S. Method for mfg. homogeneous bodies from semiconductor alloys, P (10) 251*h*.

Oestvold, T. Enthalpies of mixing in the ternary systems $CaCl_2$-MCl-MBr-$CaBr_2$ where M is Na, K, and Rb, (11) 281*i*. See Szczygiel, Z.

Oestvold, T., and Kleppa, O. J. Enthalpies of mixing in binary liquid alkali sulfate mixtures, (3) 73*c*.

Oeye, H. A. See Grjotheim, K.

Oeye, H. A., Rytter, E., Klaeboe, P., and Cyvin, S. J. Raman spectra of KCl-$AlCl_3$ melts and normal coordinate analysis of $Al_2Cl_7^-$, (6) 151*i*.

Oezer, A. M. See Garlick, G. F. J.

Offenbacher, W. See Peeters, J. M.

Oganesov, V. N. See Tkachev, V. V.

Ogasawara, Takayuki. See Ogawa, Yutaka.

Ogawa, Hiroshi, Nishinaga, T., Kasuga, M., and Arizumi, T. Selective epitaxial growth of Si by using Si_3N_4 film as a mask, (4) 86*j*.

Ogawa, Tadashi. See Tomita, Kinzo.

Ogawa, Takuzo. See Ura, Mitsuru.

Ogawa, Yutaka. See Higuchi, Noboru.

Ogawa, Yutaka, Ogasawara, T., and Seike, S. Method for producing semiconducting glaze compositions for electric insulators, P (8) 198*f*.

Ogden, J. S., and Ricks, M. J. Matrix isolation studies of group IV oxides (II) ir spectra and structures of GeO, Ge_2O_2, Ge_3O_3, and Ge_4O_4; (III) ir spectra and structures of SnO, Sn_2O_2, Sn_3O_3, and Sn_4O_4, (7) 178*e*.

Ogg, N. R. See Crabb, J. C.

Ogland, J. W. Fusion method for spaced conductive element window, P (7) 161*g*. Optical maser, P (5) 113*e*.

Ogorodnikov, V. V., Koval'chenko, M. S., and Krainii, A. G. Effect of neutron irradiation on the electrical resistance and color of high-melting compounds, (10) 258*i*.

Ogren, C. W. See Anderson, W. G.

Ogren, J. R. See Carroll, D. F.

Oguey, H. T. See Nikles, F.

Ogura, S. See Viswanathan, C. R.

Oguri, Takeo. See Yamazaki, Hisashi.

Oguro, Kyoji. See Sakaguchi, Masakazu.

Ohama, Fumihiko, and Kobayashi, K. Behavior of the composite prestressed concrete beams, (6) 127*j*.

Ohama, Fumihiko, and Tauchi, M. Basic study of mortar for grouting in the prepacked con-

crete works—grouting mortar having high flowability, (6) 127*j*.

Ohama, Nobuhiko. See Okamoto, Yasunori.

Ohama, Nobuhiko, and Hamaguchi, Yoshikazu. Determination of the exchange integrals in β-MnO_2, (3) 72*e*.

O'Hanlon, H. Ferrite-cored kicker magnets, (9) 224*c*.

O'Hanlon, J. F. See Haering, R. R.

Ohara, Akio. See Kamegaya, Takeo.

Ohara, Hideaki. See Ninomiya, Kiyosha.

O'Hara, M. J. Catalyst and method of preparation, P (5) 117*e*. See Sheets, H. D., Jr.

O'Hara, M. J., and Biggar, G. M. Phase equilibria aspects of the performance of basic refractories, (1) 8*b*.

O'Hara, M. J., Duga, J. J., and Sheets, H. D., Jr. Studies in phosphate bonding, (8) 196*c*.

O'Haver, T. C. Chemical instrumentation (LXII) lock-in amplifiers, Pt. 1, (8) 204*i*.

Ohba, Hiroshi, and Fukuoka, H. Materials and data concerning spalling tests on sleeve brick obtained from 16 sources, (1) 7*a*.

Ohba, Hiroshi, Hiragushi, K., and Okada, Y. Conditions for using plastic refractories, especially with respect to effects of moisture content and packing density on their characteristics after completion of furnace, (1) 6*h*.

Ohba, Hiroshi, Sugita, K., and Fukuoka, H. Crystallization and its effect on property changes in fused SiO_2 refractories during heating (I), (1) 7*b*.

Ohba, Hiroshi, Sugita, K., and Shimada, K. Method of producing highly gas-permeable refractory material having open pores, P (3) 61*a*.

Ohgishi, Sakichi, Kizawa, K., and Tanahashi, I. Mechanical properties of mortar and concrete with polypropylene fiber dispersed in them, (6) 129*c*.

Ohgishi, Sakichi, and Ukai, M. Mechanical properties of cement mortar dispersed with steel fiber, (6) 129*b*.

Ohlmann, R. C. See Mazelsky, R.

Ohlmann, R. C., and Mazelsky, R. Fluoroapatite laser material doped with Ho or Tm and Cr, P (4) 88*a*.

Ohmachi, Yoshiro. See Uchida, Naoya.

Ohmachi, Yoshiro, and Uchida, N. Acoustic and acousto-optical properties of TeO_2 single crystal, (11) 273*d*.

Ohmae, Kenji, Hirano, T., and Akaishi, T. Reflector-type incandescent lamps, P (8) 193*j*.

Ohmann, H. See Schreiner, H.

Ohmori, Takashi. See Sugano, Keiichi.

Ohnemueller, W. See Lehmann, H.

Ohnishi, Norio. Ordered structure on the (111) face of highly B-doped Si crystals, (3) 74*e*.

Ohnishi, Shinji. See Sato, Kogo.

Ohno, Masao, and Kijima, Katsumi. Uv ray cutting pink glass for color photography, P (9) 220*b*.

Ohno, Tomeji, Takahashi, M., Akashi, T., and Tsubouchi, N. Piezoelectric ceramics, P (4) 90*a*; P (7) 170*b*.

O'Horo, M. P., and White, William B. Phase equilibria in the systems CdF_2-CaF_2, CdF_2-PbF_2, and CdF_2-ZnF_2, (1) 23*e*.

Ohring, M. Electromigration damage in thin films due to grain boundary grooving processes, (5) 111*j*. See Rosenberg, R.

Ohsato, Nobuyoshi. See Ito, Kunihiko.

Ohshita, Masahide, and Tsukagoshi, T. Mfg. process for an InSb thin-film semiconductor element, P (10) 251*e*.

Ohstuki, Mitsuo. See Fernandez-Moran, H.

Ohta, Akira. See Kamegaya, Takeo.

Ohta, Hideaki. See Ninomiya, Mitsuo.

Ohta, Hironori, and Hara, M. Ion exchange in sheet glass by electrolysis, (3) 56*c*.

Ohta, Kuniichi. Spin-orbit effects in crossed electric and magnetic fields: Γ_7 band of wurtzite-type crystals, (5) 124*d*. See Matsukura, Yasuo.

Ohta, Masaya. Method of mfg. a semiconductor device and a semiconductor device obtained thereby, P (4) 89*f*.

Ohta, Takahiro. See Utsugi, Mikio.

Ohta, Takeshi. See Mori, Hitoaki.

Ohta, Toshitaka. See Yokomichi, Hideo.

Ohtani, Tadao. See Yamashita, Toshio.

Ohtomi, Hiroshi. See Kono, Motomi.

Oi, Kazuo, and Negishi, K. Method and apparatus for [dry] centrifugal classification, P (9) 230*e*.

Oi, Kyoko. See Awazu, Kenzo.

Oi, Yoshiro. Progress of reconstruction work on ignition furnace of sintering plant and selective test on refractories, (1) 8*d*.

Oikado, Taizo. Gas-filled discharge tube with gas-refilling means, P (5) 107*f*.

Oikawa, Mitsuru. See Okabe, Tadao.

Oishi, Kenichi, Obayashi, S., and Kinoshita K. Compaction of concrete by vibration, (6) 128*b*.

Oishi, Yasumichi. See Shirasaki, Shinichi.

Oizumi, Chihiro. See Tabata, Yoneho.

Ojima, Teruhiko, and Nishi, G. Oxide magnets, P (5) 113*g*.

Okabe, Jiro. See Yamada, Masatoshi.

Okabe, Tadao, Tanaka, M., Tamura, S., Fukushima, M., and Oikawa, M. Shadow mask having focusing function and method of making, P (9) 219*j*.

Okabe, Takahiro. See Kawakatsu, Fumimaro.

Okada, Akira. See Oshima, Shintaro.

Okada, Kiyoshi, Sakata, K., and Odake, K. Creep rupture of concrete and mortar, (6) 128*f*.

Okada, Kiyoshi, Yamura, K., and Sakai, K. Deflections of 2-span continuous reinforced concrete beams, (6) 128*g*.

Okada, Kiyoshi, Yoneda, S., and Hirasawa, I. Ultimate strength of square and rectangular columns under biaxially eccentric loads, (6) 130*a*.

Okada, Masahiro. See Tsuboi, Tatsuaki.

Okada, Moritami, Nakagawa, M., Atobe, K., and Shibata, T. Color centers in MgO:Ni induced by neutron irradiation, (3) 72*f*.

Okada, Takashi. See Takamizawa, Hideo.

Okada, Yoshisada. See Ohba, Hiroshi.

Okai, Bin. See Yoshimoto, Jiichiro.

Okai, Bin, and Yoshimoto, Jiichiro. Shear strength of pyrophyllite up to 80 kbars, (3) 75*c*.

Okajima, T. Mechanical properties of particulate composites under static compression, (8) 187*e*.

Okamato, Fumio, Wada, Y., and Miyatani, K. Magnetic compositions, P (10) 251*d*.

Okamoto, Naomichi. Reciprocity of electromagnetic waves scattered by anisotropic composite obstacles, (7) 180*c*.

Okamoto, Yasunori, Ohama, N., and Matumura, O. Thermal emittance study of MgO films, (3) 75*j*.

Okamoto, Yoshihiko. See Maeda, Hajime; Sato, Tai; Takeishi, Yoshiyuki.

Okamura, Hajime, and Mineo, T. Fundamental studies on the arrangement of bars in reinforced concrete beams, (6) 129*f*.

O'Kane, D. F. See Burns, G.

Okano, K. See Sakata, H.

Okaue, Hiromitsu. See Iwabuchi, Toshitsugu; Tanemura, Tadashi.

Okazaki, Takayoshi. See Ishihara, Toshio.

O'Keefe, M. Extended defects and their possible role in mass transport, (9) 235*b*.

O'Keefe, W. H., Colvert, J. H., Nelson, G. V., and Youngblood, D. J. Stabilized amorphous SiO_2-Al_2O_3 catalytic cracking catalysts, P (9) 233*c*.

O'Keeffe, T. W. See Handy, R. M.

O'Keeffe, T. W., and Larkin, M. W. Fabrication of semiconductor devices utilizing bombardment-enhanced etching of insulating layers, P (2) 40*g*.

O'Keeffe, T. W., and Morris, J. R. Masked photocathode and method of making, P (10) 251*f*.

Okhremchuk, L. N. See Fomenko, V. S.

Okikawa, Shinji, Somiya, S., and Saito, S. Effect of TiO_2 on the grain growth of sintered CeO_2, (6) 147*a*.

Okol'chishena, N. E. See Bukhalova, G. A.

Oksman, A. M. See Koren, M. G.

Okubo, Tsutomu. See Ichikawa, Kazuhiko.

Okuda, Hiroshi. See Tabata, Hideyo.

Okuda, Kensuke, Yoshida, T., and Sugawara, K. Method of preparing carbonaceous nonwoven fabric, P (11) 272*a*.

Okuda, Masahiro. See Matsushita, Tatsuhiko.

Okuda, Taneaki. See Akashi, Tsuneo; Sugano, Izuru.

Okuma, Takeshi. See Katase, Denii.

Okumura, Akihiro, and Izumi, I. Glassware cooling and transfer apparatus, P (7) 162*a*.

Okumura, Tomisaburo. See Arita, Shigeru.

Okun, E. L. See Menchikov, L. P.

Okuno, Yasuo, Suto, K., and Nishizawa, J. Growth of $In_{1-x}Ga_xP$ crystals from solution, (3) 73*d*.

Okushima, Masaichi, Suzuki, K., and Fujioka, M. Effect of reinforcement on the initial cracking moment of reinforced concrete and prestressed concrete member, (6) 128*c*.

Okuyama, Naoki, Yasunaga, H., Minomura, S., and Takeya, K. Dependence of the resistance on pressure in the *c* direction of pyrolytic and natural graphite, (4) 96*a*.

Olander, D. R. See Finucane, J. S.

Olcott, E. L. Shaped pyrolytic graphite articles, P (4) 83*b*.

Olcott, J. S. See Garfinkel, H. M.

Oleinik, G. S. See Yavorskii, I. A.

Oleinik, V. T. See Yam, V. M.

Oleinikov, N. N. See Granik, V. A.

Oleinikova, N. I. See Kravchenko, I. V.

Olesov, N. A. Action of alkaline naphthenate (soap substitute) on the properties of process dust, (8) 203*g*.

Olesov, N. A., and Yudin, N. M. Centralized removal of industrial dust, (8) 203*h*.

Olewinski, E. W. Stable aqueous $NaAlO_2$ solutions, P (8) 207*h*.

Ol'ginskii, A. G. See Mchedlov-Petrosyan, O. P.

Oliver, D. W. See Slack, G. A.

Oliver, J., and Waye, B. E. Dielectric strength of electrical porcelain, (1) 11*b*.

Oliver, M. R., Dimmock, J. O., and Reed, T. B. Temp. and magnetic field dependence of the conductivity of EuO, (9) 239*a*.

Olivier, J. P. See Morris, H. H.

Olivotto, V. Apparatus for collecting glass tubes at the end of a production line, P (9) 218*c*.

Ollivier, G. See Noerlund Christensen, A.

Olmsted, L. E., Puetz, E. J., Rodgers, W., and Trampier, C. R., Jr. Preparation of finely divided $CaSiO_3$, P (8) 207*a*.

Olofsson, O., and Gullman, J. Crystal structure of TlP_5, (3) 72*h*.

Olsen, T. W. Screen printing machine for round and flat articles, P (8) 194*a*.

Olson, A. W. Glazing unit, P (8) 193*c*.

Olson, D. R., Dieselman, H. D., and Schroeder, J. B. Radiation-induced changes in refractive index and absorption coeff. for several optical materials, (8) 191*d*.

Olson, E. J. See Pile, F. L.

Olson, R. E. See Gau, F. L.

Olstowski, F. Forms of graphite, P (4) 84*j*. Process for producing anisotropic graphite-metal composites, P (9) 222*e*.

Olszowski, T. See Kedzior, A.

Oltman, B. G. See Kastner, J.

Olton, D. J. See Malloy, J. F.

O'Malley, A. J. Overview of photomasking technology in the past decade, (3) 63*a*.

Omar, A. A., and Salman, S. M. A. Crystallization of silicate glasses based on granite and dolomite mixtures, (11) 268*h*.

O'Mara, W. C., Davies, J. J., and Wertz, J. E. Structure of the F-containing trapped-hole center in MgO, (5) 124*i*.

Omel'chenko, V. V. Sulfate-slag cement production, (8) 188*b*.

Omichi, Hiromu, and Kobayashi, N. Piezoelectric ceramics, P (7) 170*a*.

Omori, Hirao. See Tabata, Katsuhiro.

Omori, Yasuo. See Aratani, Fukuo; Tanizake, Mikio.

Ondracek, G., and Schulz, B. Conductivity of cermets and other multiphase materials (I) theoretical considerations of the electrical resistivity as a function of concentration and stereometry; (II) derivation of the electrical resistivity as a function of concentration and stereometry of the phases on the basis of the field equation, (8) 199*a*.

Ondracek, G., and Splichal, K. Cermets in phase diagrams, (5) 108*i*.

O'Neil, J. R., Clayton, R. N., and Mayeda, T. K. O isotope fractionation in divalent metal carbonates, (4) 98*c*.

O'Neill, J. S. Strength and elastic modulus relations in BeO-SiC bodies, (1) 25*g*.

O'Nions, R. K., and Smith, D. G. W. Investigations of the $L_{II, III}$ X-ray emission spectra of Fe by electron microprobe (II) Fe $L_{II, III}$ spectra of Fe and Fe-Ti oxides, (1) 23*d*.

Ono, Akio. See Hishiyama, Yoshihiro.

Ono, Kaoru. See Yokomichi, Hideo.

Ono, Kohei. See Saito, Hajime.

Ono, Masayoshi. See Kitamura, Toshinori.

Ono, Minoru, and Momoi, T. Method for mfg. a semiconductor device, P (6) 139*b*.

Ono, Minoru, Momoi, T., and Kawachi, Y. Semiconductor devices, P (5) 114*d*.

Ono, Shujiro. See Yamamoto, Zensaku.

Ono, Tadaaki. See Fuwa, Yoshikazu.

Ono, Yoshio. Chemistry of super-high early-strength cement, (6) 128*b*.

Ono, Yoshio, Hidaka, T., and Shirasaka, M. Influence of Na_2O, K_2O, and MgO on the development of strength of portland cement mortar, (4) 79*a*.

Ono, Yoshio, and Kato, H. Microstructure of cement paste—drying behavior of cement paste, (4) 79*e*.

Onoda, G. Y., Jr. See Freiman, S. W.

Onoda, Katsuhiro. See Nakanuma, Sho; Wada, Toshio.

Onodera, Natsuo, Suga, H., and Seki, S. Glass transition in amorphous precipitates, (3) 56*i*.

Onodera, Yasuhiko. See Ikeda, Takuro.

Onodera, Yutaka. See Keskar, K. S.; Oya, Ginichiro; Tanaka, Eihachiro.

Onodo, Yoshihiro. See Akashi, Tsuneo.

Onstott, E. I. Separation of rare earths by electrolysis with porous C electrodes, P (2) 46*i*.

Onuma, Eiichi, and Noda, M. Investigation on the testing method of work index test of cement raw materials, (4) 79*b*.

Ooi, Takakazu. Tests for determining sp gr and H_2O absorption of lightweight aggregate, (6) 130*h*.

Ooka, Kazuo, and Kishii, T. Changes of electrical properties in glass caused by uv irradiation, (3) 55*c*.

Ooka, Kazuo, Kishii, T., and Kasori, M. Effects of small additives on the stress buildup in glass by uv radiation—rare earth oxides, (3) 55*e*.

Oomen, J. A. F. Piezoelectric-driven variable capacitor, P (6) 139*c*.

Oosting, M. Chemical attack of enamel surfaces, (4) 79*j*.

Oota, Fukuo, Kosaka, Y., and Tanigawa, Y. Effect of bond between mortar matrix and aggregate and aggregate strength on the splitting strength of concrete, (10) 241*h*.

Ootsuka, Motoya. See Yasuda, Eiichi.

Openshaw, I. K. Collimator for an X-ray analyzer, P (2) 44*i*.

Opitz, H. E. See Goelzer, W. C.

Opoczky, L., and Bocs, A. Corrosion of asbestos fibers, (6) 128*e*.

Opoczky, L., Szatura, L., and Mechler, I. Corrosion of artificial fibers in asbestos cement products, (11) 266*h*.

Oppel, J. A. See Nakata, Roy.

Opresko, S. T. See Stoller, A. I.

Opresko, S. T., and Pinch, H. L. Control of product phases in the chemical vapor deposition of garnet films, (10) 248*j*.

Orabi, G. I. See Haroun, N. A.

Orban, N. See Rocher, G.

Ord, G. See Cowlard, F. C.

Orecchia, L. Method and apparatus for setting up a temp. gradient, P (10) 253*i*.

O'Reilly, B. E. See Palilla, F. C.

Orel, M. Caustic MgO and MgO cements, (5) 102*g*.

Orlemann, J. K. Process for producing synthetic hectorite-type clays, P (9) 233*b*.
Orlita, F. Solution of a crystalline or pulverulent mass, P (11) 277*g*.
Orlova, E. M. See Bogdanova, G. S.
Orlova, I. G. See Kainarskii, I. S.
Orlova, T. M. See Tkachev, V. V.
Orobchenko, V. I. See Kruglitskii, N. N.
O'Rourke, J. A. See Wagner, P.
Orr, C. D. See Cunningham, J. A.
Orr, L. Practical anaiysis of fractures in glass windows, (9) 218*b*.
Orr, W. H. Thin film distributed RC structure, P (9) 228*a*. See Melroy, D. O.
Orsini, P. G. See Buri, A.; Marotta, A.
Ortelli, G. Technology and statistics, (7) 182*d*. See Ravaglioli, A.; Vincenzini, P.
Osada, Kiyoshi. See Kodama, Kenjiro.
Osada, Mitsuo, Kumon, O., and Nishimoto, T. Ferroelectric and piezoelectric composition, P (4) 87*i*.
Osawa, Junichi. See Tanaka, Sadao.
Osborn, R. A. See Einfalt, A. C.
Osborne, G. J. See Gutt, W.
Oshchipko, I. S., and Burykina, A. L. Study of the reactions between BC_2N_2 and refractory metals and compounds, (10) 261*a*.
Oshima, Hisaji, and Ikenaga, H. Shrinkage and creep of high-strength medium consistency concrete made with artificial lightweight aggregate, (6) 130*c*.
Oshima, Shintaro, Kobayashi, T., and Kamibayashi, T. Method of fabricating memory matrix planes using ferromagnetic thin film, P (8) 201*b*.
Oshima, Shintaro, Kobayashi, T., Kamibayashi, T., Okada, A., Komazawa, Y., and Komuro, K. Method for fabricating a memory strip array, P (9) 226*f*.
Oshio, Akira. See Nishi, Seiya.
Osial, T. A., and Ravas, R. J. System for providing continuously variable pump pulses, P (9) 228*d*.
Osiecki, J. H. See Gamble, F. R.
Osinova, T. A. See Abrikosov, N. Kh.
Osmanov, E. O. See Borisova, Z. U.
Osment, H. E., and Williams, R. L. Method of making a foamed Al_2O_3 shape or catalyst support, P (1) 20*e*.
Osmer, J. A., and Chase, A. B. Crystallization of BeO, Be_2SiO_4, and SiO_2 from Li_2MoO_4-MoO_3, (7) 176*h*.
Osoegawa, Hideru, and Kobayashi, K. Method for fitting semiconductor pellet on metal body, P (5) 113*g*. Semiconductor pellet fitted on a metal body, P (10) 252*j*.
Osovitz, E. E. See Zysk, E. D.
Ossaka, Joyo. See Iwai, Shinichi; Urabe, Kazuyori.
Ostberg, J. E. Electrodes for electric arc furnaces, P (8) 206*b*.
Osterink, L. M., and Foster, J. D. Mode-locked laser modulated by a train of stabilized nondamped relaxation pulses, P (2) 41*e*.
Ostermayer, F. W., Jr. High-efficiency diode-pumped lasers, P (8) 193*d*.
Ostrikova, N. V., Miroshnik, Z. A., Kuleshova, V. D., Dudkina, N. P., and Ilyushchenko, A. I. System $GaCl_3$-$AlCl_3$-RbCl, (5) 124*e*.
Ostrikova, N. V., and Zhuravlev, E. F. System of the chlorides of Ga, Al, and K, (5) 124*d*.
Ostroski, J. W. See Chang, Hung-Chi.
Ostrowski, J. S. See Le Bras, L. R.
Oswald, D. R. See Frank, G. A.
Oswald, L. A. Apparatus for advancing glass fibers, P (9) 218*b*.
Ota, Tadashi. Method and apparatus for automatically determining characteristic parameters, P (8) 201*d*.
Otake, Takeshi. See Kodama, Kenjiro.
Otani, Hiroshi. See Yukami, Noboru.
Otani, Sugio. Production of C filaments from low-priced pitches, P (4) 84*j*. See Tabata, Yoneho.
Oteo Mazo, J. L., and Fernandez Navarro, J. M. Effects of dissolved N on the properties of alkali borophosphate glass, (4) 80*g*.
Otoi, Tomozo. See Koyanagi, Wataru.
Otomo, Yoshiro. See Kano, Tsuyoshi.
Otoupalova, J. See Chromecek, R.
Otsuka, Michio. Semiconductor [3 layer] with improved connection to control electrode region, P (3) 67*c*.
Otsuka, Sigeo. See Murata, Jiro.
Ott, D. B. See Rupprecht, D.
Ott, J. B. See Goates, J. R.
Ott, J. B., Goates, J. R., and Oyler, D. E. Solid-liquid phase equilibrium in the Na-Cs alloy system, (5) 124*a*.
Ott, W. See Schilling, W.
Ottenheym, A. See Wuhrer, J.
Otto, J. L. M. See Boucher, R. C. E.
Ouchi, Hiromu. See Nishida, Masamitsu.
Ouchiyama, Takeshi. See Katsuta, Morio.
Oulton, R. J. Preheating glass batch material by melting the batch core area, P (5) 107*g*.
Overath, A. See Halberschmidt, F.
Overbeek, J. T. G. See Rouweler, G. C. J.
Ovramenko, N. A. See Govorov, A. A.
Ovshinsky, S. R. Display screen using variable resistance memory semiconductor, P (6) 137*b*. Introduction to ovonic research, (6) 136*g*. See Bienenstock, A.; Fleming, G. R.; Fritzsche, H.; Neale, R. G.
Owa, Masaaki. Method of mfg. flat glass on molten metal and apparatus therefor, P (4) 82*e*.
Owen, A. E., and Robertson, J. M. Electronic properties of some simple chalcogenide glasses, (6) 131*j*.
Owen, L. B. Rapid sample preparation method for powder diffraction cameras, (4) 93*h*.
Owen, R. B. See van den Heuvel, A. P.
Owens, E. B. See Wolfe, C. M.
Owens, F. See Breslow, R. A.
Ownby, P. D., and Jungquist, G. E. Final sintering of Cr_2O_3, (10) 259*g*.
Oya, Ginichiro, and Onodera, Y. Preparation of single-crystal NbN and Nb_4N_5 films, (3) 74*h*.
Oyama, Takeji. See Kobayashi, Hiroo.
Oyama, Yoichi, and Kamigaito, O. Solid solubility of some oxides in Si_3N_4, (4) 98*d*.
Oyler, D. E. See Ott, J. B.
Ozaki, Yoshinori. See Urata, Toshio.
Ozdemir, F. S., and Schwartz, R. J. Formation of thin layers of mixed titanates by solid-solid reactions, (6) 136*i*.
Ozeki, Hidekichi. See Nakamura, Toshio.
Ozretic, V., and Tahirbegovic, T. Use of Kamex M-15 and Nitrol I for mass blasting in the Perun quarry of Ivan L. Lavcevic, Split, (2) 46*f*.

Paczkowski, J. P. See Collard, J. R.
Padalko, O. V. See Pilyugin, A. N.
Padawer, G. E. See Argon, A. S.
Padden, F. J., Jr. See Keith, H. D.
Paderno, Yu. B., Garf, E. S., Niemyskii, T., and Pracka, I. Electrophysical properties of fused hexaborides of the alkaline- and rare-earth metals, (10) 259*c*.
Paderno, Yu. B., Novikov, V. I., and Garf, E. S. Electrical properties of hexaborides of the alkaline- and rare-earth metals at low temps., (10) 259*b*.
Pafomov, N. N. See Sil'chenko, V. A.
Pagano, M. Measurement of strains in ceramic materials using rosette gages and shaped polyester gages, (7) 173*j*.
Page, D. J. Schottky barrier power rectifier, P (7) 170*i*. See Brody, T. P.
Page, D. J., and Brody, T. P. Thin-film power FET, P (7) 170*g*.
Page, D. J., and Driver, M. C. Method of producing thin-film transistors, P (9) 226*h*.
Page, E. W. See Hughes, I. F.
Page, J. B., Jr. Theory of the electric field from phonons perturbed by substitutional impurities in ionic crystals, (5) 124*j*.
Page, J. S. See Brent, J. T., Jr.
Pages, M. See Tabuteau, A.
Paige, J. I. See Russell, J. H.
Paine, T. O. Method for determining presence of OH in MgO, P (1) 18*h*. Method of producing crystalline materials, P (2) 44*a*. Uninsulated in-core thermionic diode, P (10) 253*d*.
Painter, F. F., and Seymour, S. L. Glass gripping tongs, P (1) 4*g*.
Paisov, I. V. See Kiparisov, S. S.
Pajean, G. Determination of B_2O_3 in glasses by atomic absorption, (10) 243*b*.
Pakswer, S., and Stevens, M. T. Secondary electron emission from thin-film Au-metal oxide cermets, (7) 167*i*.
Pakulski, F. J. See Kaiser, H. D.
Pakutka, W. M., Cerulli, N. F., and Scanlon, G. T. Refractory metal brazing with Nb_2O_5 flux, P (4) 90*h*.
Pal, D. Using fluidics to control continuous blending, (10) 254*g*.
Palac, K. Method of depositing vitreous material on a faceplate panel, P (10) 244*j*.
Palagi, P. See Guicciardi, F.
Palavit, G., and Noel, S. Disulfates of Mn and Ni, (4) 96*e*.
Palecek, M. Determination of B_2O_3 in commercial glasses, (8) 204*d*.
Palfi, T. L. See Castrucci, P. P.
Palilla, F. C., O'Reilly, B. E., and Abbruscato, V. J. Fluorescence properties of alkaline earth oxyanions activated by divalent Yb, (2) 47*i*.
Palin, F. T., and Richardson, H. M. Study of the oxidation temp. and amount of residual C in coked tarred magnesite and dolomite, (11) 271*i*.
Palini, O. Sensing transducer, P (1) 14*b*.
Palka, F. M. See Strenglein, H. F.
Pallmann, W. Comminuting particles [impact mill], P (11) 277*f*.
Palmer, A. B. Method of securing dense metal-bonded refractory nitride bodies to steel and product, P (9) 222*a*. See Iler, R. K.
Palmer, F. R. Means for [spray] marking glass and the like, P (3) 58*h*. Portable means for marking glass and the like, P (11) 270*g*.
Palmer, G. G. Method of embedding semiconductor chip within a dielectric layer flush with surface, P (2) 41*c*.
Palmer, L. H., III, and Kimball, S. F. W halogen lamp having improved filament support, P (4) 83*b*.
Palmour, H., III. See Huckabee, M. L.; Kriegel, W. W.
Palmquist, R. L. See August, R. R.
Palotas, L. Approximate determination of the shrinkage of concrete, (5) 102*e*. Evaluation of the inherent stresses in concrete, (6) 128*h*.
Palumbo, D. T. See Faria, S.; Toma, S. Z.
Palumbo, D. T., and Brown, Jesse J., Jr. Electronic states of Mn^{2+}-activated phosphors (I) green-emitting phosphors, (9) 235*f*.
Palumbo, F. J., Stanczyk, M. H., and Sullivan, P. M. Electronic color sorting of glass from urban waste, (7) 159*f*.
Palyi, L. Two-stage hammer mill, P (6) 144*h*.
Pammer, E. Method for producing an insulating layer on the surface of a semiconductor crystal, P (8) 201*h*. See Folkmann, E.
Pammer, E., and Heidegger, P. Method of producing a protective layer of SiO_2 on the surface of a semiconductor wafer, P (10) 252*b*.
Pammer, E., and Panholzer, H. Method of producing Ga diffused regions in semiconductor crystals, P (5) 113*b*.
Panchuk, I. E. See Belotskii, D. P.
Panchuk, O. E. See Belotskii, D. P.
Panholzer, H. See Pammer, E.
Panish, M. B. Liquidus isotherms in the Ga-In-As system, (9) 236*d*.
Panish, M. B., and Sumski, S. Crystal growth apparatus, P (10) 250*f*.
Panizza, G. A. See Agarwal, B. D.
Pankeeva, N. E. See Sazhin, V. S.
Pankove, J. I. Electroluminescent semiconductor device of GaN, P (11) 274*g*. See Kressel, H.
Pankratov, V. L. See Blonskaya, V. M.
Pankratz, L. B., and Ferrante, M. J. Thermodynamic properties of 4 crystalline Na borates, (2) 50*c*.
Pankratz, L. B., Stuve, J. M., Poppleton, H. O., Oden, L. L., and Mah, A. D. Enthalpy and free energy of formation of $VN_{0.463}$, 298°–1800°K, (6) 147*h*.
Panlener, R. J., and Blumenthal, R. N. Ti-rich nonstoichiometric $BaTiO_3$ (III) high-temp. thermodynamic and X-ray diffraction measurements, (1) 12*a*.
Panousis, P. T. See Krambeck, R. H.
Pansare, R. M. Tracer study of the reaction between perchlorate ions and iodide ions in fused alkali nitrate media, (8) 211*d*.
Panteleimonov, V. M. See Ryss, Yu. S.
Pantell, R. H. See Amzallag, E.
Panther, R. H., and Purser, C. R. Spherical halogen Geiger tube, P (6) 133*h*.
Pao, Yoh-Han. Controllable magneto-optical devices employing magnetically ordered materials, P (9) 218*g*.
Paola, C. R. See Bergh, A. A.
Paoletti, G., and Giammanco, F. Study of nucleation and crystal growth in opal glasses, based on spectrophotometric measurements, (7) 160*e*.
Paoli, T. L. See Dyment, J. C.
Paoli, T. L., and Ripper, J. E. Dynamic AM control of the transverse modes of a self-pulsing semiconductor laser, P (10) 250*i*. Method and apparatus for pulse position modulating spontaneously pulsing semiconductor lasers, P (4) 88*d*. Method for modulating semiconductor lasers, P (2) 41*i*. Method for pulse-width-modulating semiconductor lasers, P (3) 66*f*.
Paorici, C. See Corsini-Mena, A.
Pape, H. See Classen, F.
Papke, K. G. Montmorillonite, bentonite, and fuller's earth deposits in Nevada, (3) 71*e*.
Papkova, L. P., Shamaeva, A. A., and Sivokon, V. I. Use of complex kaolin-quartz-feldspar raw material for porcelain production, (8) 198*b*.
Pappadis, N. P. Integrated shadow mask structure [color tube], P (1) 4*i*.
Papst, K., and Zednicek, W. Basic bricks in vacuum [steel-] degassing furnaces, (5) 108*g*.
Papworth, K. See Fort, A.
Paradis, H. J. Variations in form and technique, (2) 30*f*.
Parascandola, L. J. See Thorington, L.
Paretzkin, B. See Swanson, H. E.
Parfitt, G. D., Ramsbotham, J., and Rochester, C. H. Infrared study of ammonia adsorption on rutile surfaces, (1) 22*h*. Infrared study of the reactions of Si, Ti, and Sn tetrachloride with rutile, (11) 281*c*.
Parillo, E. V. See Thomasson, G. I.
Parish, W. R., and Kelley, J. C. Concentrating fluosilicic acid, P (6) 143*j*.
Parisi, G. I. See Mindt, W. F. H.
Park, C. S., and Maher, P. K. Method of producing small particle size Z-14 zeolite, P (3) 71*d*.
Park, K. C. See Ahn, Kie Y.
Park, K. C., and Basavaiah, S. Bistable switching in Zr-ZrO_2-Au junctions, (6) 145*c*.
Park, M. J. See Fahmy, M.
Park, M. J., and Bray, P. J. ^{11}B NMR studies of Sr borate glasses and compounds, (11) 268*a*.
Parke, S., and Cole, E. Sensitization and energy transfer in the systems Mn-Nd, Mn-Ho, and Mn-Er in glasses, (3) 57*e*.
Parkell, E. F. Apparatus for the transfer of articles, P (10) 243*h*.
Parker, C. J., and Popov, W. A. Experimental determination of the effect of temp. on refractive index and optical path length of glass, (10) 243*d*.
Parker, G. W. See Bittmann, C. A.
Parker, H. J. See Francis, T. L.
Parker, H. S. See Brower, W. S., Jr.
Parker, S. G. Growth of crystals at a uniform and constant rate, P (4) 88*c*.
Parker, S. G., and Pinnell, J. E. Flux growth of cubic CuCl crystal using a small thermal gradient, (2) 47*i*. Light emission from ZnSe-GaAs diodes, (5) 111*h*.
Parker, V. B., Wagman, D. D., and Evans, W. H. Selected values of chemical thermodynamic properties, (3) 70*b*.
Parnet, B. Handling and transferring device for plane objects, particularly glass sheets, P (9) 219*e*.

Parr, J. G. See Nemeth, J.
Parr, N. L., and Brown, R. L. Spray deposition of Si powder structures, P (9) 222*h*.
Parratt, N. J. See Gooding, R. W.
Parry, R. J., Dunning, R., Forber, A., and Higham, G. A. Th-free La borate optical glass, P (2) 35*b*.
Parsons, M. L., and McElfresh, P. M. Flame Spectroscopy—Atlas of Spectral Lines, B (1) 27*e*.
Partiot, M. Infrared burners and high-efficiency radiant plates, P (11) 272*d*.
Partlow, W. D. See Hopkins, R. H.
Partridge, G. See McMillan, P. W.
Partridge, T. J. Refractories involved in the large scale degassing of steel, (2) 36*e*.
Pask, J. A. See Davis, R. F.
Passmore, E. M. Apparatus for metal vaporization comprising a heater and a refractory vessel, P (4) 87*e*. See Loughridge, F. A.
Passmore, E. M., and Wilde, D. P. Electrically conductive refractory bodies, P (1) 12*j*.
Pasternak, M. See Goldstein, C.
Pataki, E. See Kozar, L.
Patel, A. R., and Agarwal, B. P. Whisker growth and etching on K bromide single crystals, (7) 182*b*.
Patel, A. R., and Sangwal, K. Growth and etching of PbS whiskers from the vapor phase, (7) 177*h*.
Patel, C. K. N. Spin-flip light scattering and Gunn effect-type oscillations in multivalley semiconductors subject to a magnetic field, P (8) 202*d*.
Patel, M. S. See Longo, F. N.
Patka, M., and Klauz, M. Heat transfer between glass and mold during pressing of small glass articles, (8) 190*b*.
Patrat, G. Study of spinel phases in the systems $(1-x)Al_2LiO_4$-$xGeAlLiO_4$; $(1-x)Fe_2LiO_4$-x "$GeFeLiO_4$"; x"$Ge_2Li_4O_{12}$"-$GeZn_2O_4$, (8) 211*a*.
Patrick, G. S. Method and apparatus for applying a glass collet to a CRT, P (1) 4*c*.
Patrick, L. See Choyke, W. J.
Patrick, L., and Choyke, W. J. Optical absorption in *n*-type cubic SiC, (6) 150*e*.
Patrick, R. F. See McNally, R. N.
Patterson, A. See Deis, D. W.
Patterson, M. M. "Organization chart" for abrasive engineering terminology and editorial, (9) 213*e*.
Pattison, W. L. See McBride, J. P.
Pattyn, R. L. See Heinrichs, F. J.
Patzak, I. See Konopicky, K.
Pauchard, G. AGA and the laser reflector—Apollo XI, (7) 158*b*.
Paul, B. Semiconductor-type radiation detector, P (10) 253*b*.
Paul, D. E. See Hebert, R. A.
Paulson, D. L. See Russell, J. H.
Pauthenet, R. See Claverie, J.
Pavlica, S. R. See Wallace, R. W.
Pavlik, N. M. Nonreactive refractory separating coatings for electrical steels, P (9) 222*c*.
Pavlov, V. F. See Rokhvarger, E. L.
Pavlov, V. G. See Novokhatskii, I. A.
Pavlovskii, V. K., Tunimanova, I. V., and Tsekhomskii, V. A. Use of radioactive isotopes to determine Ag losses during glass melting, (8) 192*d*.
Pavlushkin, N. M., Gurevich, Ts. N., and Petunina, A. Ya. Influence of some oxides on the content of sulfide S in slag glass, (8) 190*h*.
Pavlushkin, N. M., Zhuravlev, A. K., and Zhabotinskii, V. A. Interrelation between the glass-forming tendency of a material and its ferroelectric activity, (8) 190*i*.
Pawley, G. S. See Cowley, R. A.
Paymal, J. Continuous production of composite [ceramic-faced] panels, particularly for buildings, P (9) 218*g*. Method and apparatus for production of fibers from thermoplastic materials, particularly glass fibers, P (4) 82*b*.
Payne, G., and Lakin, J. R. Behavior of refractories at high temps. in vacuum, (5) 108*j*.
Payrissat, M. See Wurm, J. G.
Pazin, A. V., and Borisova, Z. U. Electrical conductivity of glasses in the system Sb-Ge-Se, (9) 217*e*.
Peacock, R. D. Spectral intensities of the trivalent lanthanides (II) assessment of the vibronic contribution, (11) 282*e*.
Pear, C. B., Jr. See Murray, J. J.
Pearlman, D. See Carnall, E.
Pearne, F. J. See Pearne, F. S.
Pearne, F. J., Pearne, F. S., and Robson, F. G. Unloader blender [for bricks], P (1) 6*e*.
Pearne, F. S. See Pearne, F. J.
Pearne, F. S., and Pearne, F. J. Brick handling and stacking machine, P (8) 194*e*.
Pearson, A. Mfg. of semiconductor elements, P (3) 65*j*. See MacZura, G.
Pearson, A. D. Memory and switching in semiconducting glasses—a review, (6) 132*c*.
Pearson, A. D., and Harsell, W. B. Ion beam polishing of glass, (9) 217*e*.
Pearson, A. W. See Wilkes, A.
Pearson, G. L. See Ting, C. H.
Pearson, J. R. A. See Shah, Y. T.
Pearson, L. E. Glass fiber container and method of construction, P (10) 244*i*.
Pearson, M. J. Al_2O_3 desiccant for drying unsaturated organic gaseous compounds, P (3) 71*h*.
Peck, D. B., and Schroeder, W. W. Coulometric device with nonconductive inorganic electrode substrate, P (1) 12*f*.
Peck, W. F. Apparatus for making monofilament fiber optic ribbons for coherent fiberscopes, P (1) 3*f*.
Peco, G. Ceramic products in contact with foodstuffs. Harmonization of legislation in the field of health, (7) 165*a*.
Pecorado, R. P. See Bilous, O.
Pecoraro, G. A., and Grimm, R. E. Service test of zircons for pavers, (5) 106*j*.
Pedersen, N. E. Resonant cavity photon sensor comprising semiconductor materials sandwiched between 2 layers of dielectric, P (2) 42*f*.
Pederson, W. E. See Bell, B. B.
Pedinoff, M. E., Waldner, M., and Jones, W. R. Refraction and reflection of surface acoustic waves at boundaries of layered anisotropic substrates—Au on Li niobate, (5) 123*b*.
Pechs, M., and Wendler, F. Method of densification of porous layers, P (3) 68*d*.
Peeters, J. M., and Offenbacher, W. Apparatus for drawing glass sheets, P (2) 33*b*.
Peirce, L. H. Preparation and growth of $CsNiCl_3$ and $RbNiCl_3$, (7) 179*e*.
Pelah, I. See Wiener, E.
Peletskii, V. E. See Zeigarnik, V. A.
Pellechia, V. J. See Sheppard, J. E.
Pelletier, F. P. See Melroy, D. O.
Peloschek, H. P., and Perduljn, D. J. Method of mfg. a sintered oxidic ferromagnetic body, P (9) 226*e*.
Pelosini, L. See Corsini Mena, A.
Pelsmackers, J. See van Lierde, W.
Peltzer, D. L. Method of fabricating integrated circuits with oxidized isolation and the resulting structure, P (6) 138*b*.
Penberthy, L. Method and apparatus for preheating glass batch, P (1) 4*g*.
Penczek, E. S. Electrical contact structure for a switch reed comprising Au and Pd layers, P (9) 225*e*.
Penicaud, L., and Bilaine, J. Kiln furniture for rapid firing, (2) 36*d*.
Pennachetti, J. T., and Boux, J. F. Process for the treatment of fly ash and product, P (9) 230*d*.
Pennebaker, W. B. See Kazan, B.
Pennekamp, J. C. See Meijer, R. A. J. M.
Pennell, R. C. See Ashton, C. L.
Penny, J. See Casselton, R. E. W.
Penrod, O. R. See Brandt, I. L.
Penty, R. A., Hasselman, D. P. H., and Spriggs, R. M. Young's modulus of high-density polycrystalline mullite, (4) 99*j*.
Peppard, D. F. See Mason, G. W.
Peray, K., and Waddell, J. J. Rotary Cement Kiln, B (6) 154*e*.
Percival, J. O. Semiconductor chip bonding method, P (9) 227*g*. Semiconductor flip-chip soldering method, P (9) 227*g*.
Perdick, L. P. See Gerhard, A. R.
Perduljn, D. J. See Peloschek, H. P.
Perduljn, D. J., Varekamp, R. R. P., and Verjans, H. C. Continuous hot-pressing of K-Na niobate, (9) 223*g*.
Pereira, E. See Thomas, H. J.
Pereira, F. N. D. D. See Graham, G. M.
Perel'man, F. M., and Babievskaya, I. Z. Calculation of the liquidus diagram of the system $ZrCl_4$-$AlCl_3$-$FeCl_3$-NaCl-KCl, (5) 118*j*.
Perel'man, F. M., and Demidov, A. E. Calculation of mp of refractory compositions of the system SiO_2-Al_2O_3-CaO-MgO, (9) 233*j*.
Perepelitsyn, V. A. See Budnikov, P. P.; Flyagin, V. G.
Perez, G. See Frit, B.
Perli, S. B. See Feofanov, N. F.
Perlman, I. See Asaro, F.
Perlman, S. S., and McCusker, J. H. Ferroelectric transformers with means to suppress or limit resonant vibrations, P (11) 274*g*.
Pernicone, N. See Traina, F.
Perri, G., and Aquili, G. Process for the flotation of fluorite, P (3) 71*g*.
Perri, J. A. See Kennedy, D. P.
Perrone, N. See Kao, R.
Perrot, P., and Jeannot, C. Activity-composition relations in the Ag_2S-Cu_2S solid solutions, (4) 95*c*.
Perry, C. H. See Fertel, J. H.
Perry, G. S. Effects of impurities on the high-temp. X-band dielectric properties of sintered Al_2O_3, (1) 21*e*.
Perry, M. P. See Jones, Thomas B.
Perry, W. M. Glassmelting pot, P (8) 193*b*. See McFadden, N. E.
Pershan, P. S. See Kahn, F. J.
Persick, R. S. Wedging board pots, (2) 30*g*.
Perusek, R. J. Traveling solvent method of growing SiC crystals and junctions utilizing Y as the solvent, P (9) 288*b*. See Addamiano, A.
Perusek, R. J., and Potter, R. M. [Y] electrical contact to SiC, P (4) 91*c*.
Pescarolo, B. See Cesca, T.
Pesina, N. M. See Makarychev, A. R.
Pestie, J. P., and Belmas, J. Method of mfg. semiconductor components, P (4) 89*e*.
Peter, E. Quantitative determination of clinker minerals using a diffractometer, (4) 79*a*. See Tamas, F.
Peter, E., and Hoefler, H. Designing automatic electrostatic powder spray systems, (7) 172*a*.
Peter, P. H. See Davies, J. M.
Petermann, J. P., Slagle, R. J., Wilson, R. W., and Steffensen, L. M. Spray booth, P (1) 17*c*.
Peters, E. R., and Rutherford, W. H. Floating glass plug for stopcock assembly, P (8) 192*h*.
Peters, F. G., Sinclair, W. R., and Sullivan, M. V. Technique for the preparation of Fe oxide films by cathodic sputtering, P (7) 170*e*, P (9) 228*e*.
Peters, M. A. See Harnish, M. E.
Peters, T. E. Alkaline earth thiogallate phosphors, P (5) 112*e*.
Petersen, A. J., and Matsuyama, G. Solid-state glass electrode, P (6) 133*h*.
Petersen, J. H., and Sturlason, L. V. Atomizing nozzle, particularly for oil burners, P (9) 232*c*.
Petersen, L. E. See Royse, C. F., Jr.
Peterson, D. E. See Smith, P. K.
Peterson, E. C. See Blatchford, J. K.
Peterson, G. E. See Schempp, E.
Peterson, G. E., Carruthers, J. R., and Carnevale, A. ^{93}Nb NMR study of the $LiNbO_3$-$LiTaO_3$ solid-solution system, (7) 179*d*.
Peterson, J. A. See Grotheer, M. P.
Peterson, J. D. See Grubba, D. C.
Peterson, J. R. See Baybarz, R. D.
Peterson, N. L. See Chen, Wei-Kong.
Peterson, T. D. Indicator tube having means for separating leads, P (3) 58*d*.
Pethica, B. A. See Tyler, A. J.
Petrak, D. R. See Rankin, D. T.
Petrasek, D. W., Signorelli, R. A., Weeton, J. W., and Beremand, G. B. Method of making fiber composites, P (7) 164*h*.
Petro, J., and Rively, C. M. Method of decorating a glazed article utilizing a beam of corpuscular energy, P (8) 204*a*.
Petri, L. See Szabo, A.
Petrov, V. A., Chekhovskoi, V. Ya., and Sheindlin, A. E. Emissive power and electrical resistance of TiC at high temp., (8) 199*f*.
Petrova, A. A. See Tret'yakov, Yu. D.
Petrova, E. M., Shcherban, N. I., and Sleptsov, V. M. Elastic aftereffect in the cold-pressing of metal-carbide mixtures, (10) 246*f*.
Petrova, M. A. See Bondar, I. A.
Petrovic, L. J. See Hebert, R. A.
Petrovskii, G. T. See Galimov, D. G.
Pett, E. A. See Marshall, D. W.
Petterson, R. Harrison McIntosh—portfolio, (2) 30*g*.
Petticrew, R. W. New thermally crystallizable glasses and low-expansion transparent, translucent, and opaque ceramics made therefrom, P (3) 59*j*.
Pettifer, K. See Midgley, H. G.
Petty, A. J. See Bawa, M. S.
Petty, M. A., and Weymouth, J. H. Slide holder for the making of polished thin sections in vibratory polishers, (4) 93*a*.
Petunina, A. Ya. See Pavlushkin, N. M.
Petushkova, S. M. See Kuznetsov, V. G.; Tananaev, I. V.
Petzi, F. Modern rotary kilns for presintering ferrites, (10) 249*f*, 256*g*.
Petzold, J., and Scheidler, H. Glass convertible to transparent glass-ceramics containing AlPO, P (5) 107*g*.
Pevzner, B. Z., Litvinova, E. I., and Ivanova, V. A. Effect on enamel quality of chemical methods of preparing 08KP steel surfaces, (8) 188*h*.
Peymirat, G. See Muzzin, L.
Pezzanite, L. V. See Rose, E. T.
Pfaender, L. V. See Bode, W. W.
Pfeiffer, H. Generalization of Wallace's statistical perturbation method and its application to uniaxial ferromagnets with field, (6) 148*f*. Ground state and low-temp. weak-field thermodynamics of a uniaxial ferromagnet with transverse magnetic field, (6) 148*i*.
Pflanz, H. M., and Harper, W. E. Vacuum-type electrical device, P (3) 62*b*.
Pfleger, H. See Beschke, H.
Pfluger, R. Process and apparatus for the continuous manufacture of profiled glass bars, P (8) 193*i*.
Pham, H. See Mesrobian, G.
Pham Ngok Thien, and Morozov, I. S. Reaction of rare earth oxychlorides with their chlorides in a melt, (5) 123*g*. Reaction of YCl_3 with the chlorides of Rb, Ba, Nd, and Gd, (5) 123*i*.
Phan Kieu Duong. See Dion, M.
Phaneuf, R. A. Method of making optical fibers for image-transfer devices, P (2) 34*f*. See Strack, R. R.
Pharo, W. B. See Glendinning, W. B.
Phelan, R. J., Jr. Semiconductor device for producing radiation in response to incident radiation, P (6) 140*c*.
Phelps, F. L., Jr., and Klotz, J. M. Coating composition, P (8) 189*a*.
Phelps, G. W., and Silwanowicz, A. Role of nonclay particle size in whiteware slip casting, (8) 198*g*.
Philippot, E., and Lindqvist, O. Crystal structure of Ca_2CS_3·H_2O, (6) 145*j*. Crystal structure of $KH_5(PO_4)_2$, (6) 145*j*.
Philippot, E., Ribes, M., and Lindqvist, O. Crystal structure of $Na_4Ge_4S_{10}$, (6) 146*a*.
Philippot, E., Ribes, M., and Maurin, M. Crystal structure of Sr orthothiogermanate. Structural evolution of Ca_2GeS_4, Sr_3GeS_4, and Ba_2GeS_4, (4) 95*i*.
Philipps, T. E. Glass fiber coating method, P (6) 132*h*.
Philips, G. Measuring surface temp. with thermocouples, (3) 69*i*.
Phillips, B. L. See Wallis, G.
Phillips, D. C. See Kirk, D. L.

Phillips, L. N. Continuous C fiber tapes, P (9) 222*c*.
Phillips, R. J. See Steingiser, S.
Phillips, S. V., Booth, R. E., and McMillan, P. W. Structure and electrical properties of chalcogenide glasses, (9) 218*g*.
Phillips, V. A. Modern Metallographic Techniques and Their Applications, B (8) 212*c*.
Phillips, W. Doped CaF_2 and SrF_2 photochromic compositions, P (11) 274*e*.
Phy, W. S. Face-bonded photoarray package, P (3) 65*a*.
Piacente, V. See De Maria, G.
Pialoux, A., and Dode, M. Research on reactions between C and refractory oxides with X rays at high temps., (6) 142*f*.
Piasecki, F. J. See Nickelsen, H. O.
Piatek, Z. Strength and rheological properties of structural expanded clay concrete, (9) 215*b*.
Piatkowski, A. Effect of a polyvinyl acetate latex additive on certain properties of cement mortars, (9) 214*c*.
Piazza, J. R., and Steele, T. G. Positional deviations of preformed holes in substrates, (7) 167*d*.
Piccone, D. E. See De Cecco, A. L.; McIntyre, J. E.
Pick, E. G., Medders, J. B., and Loftus, L. T., Jr. Device for breaking scribed slices of semiconductor material, P (1) 12*g*.
Pickard, J. See Kay, S. E.
Picken, R. N. Performance of walls built of wirecut bricks with and without perforations (IV) photoelastic investigations of the stress distribution in perforated sections, (9) 220*j*.
Pickert, P. E. Process for preparing supersiliceous zeolites, P (5) 117*j*.
Picon, M., Vichy, M., and Meille, E. Composition of Lezoux, Lyon, and Arezzo Samian ware, (5) 101*i*.
Picquendar, J. E. See Cahen, O.
Picraux, S. T., Davies, J. A., Eriksson, L., Johansson, N. G. E., and Mayer, J. W. Channeling studies in diamond-type lattices, (5) 118*f*.
Pidgeon, C. R. See Feinleib, J.
Pidgeon, C. R., Feinleib, J., Scouler, W. J., Dimmock, J. O., and Reed, T. B. Optical reflectance study of magnetic ordering effects in EuO, EuS, EuSe, and EuTe, (9) 237*g*.
Pierce, C. I. See Headley, L. C.
Pierce, R. D. See Walsh, W. J.
Pierfederici, O. Gas burners for top-heated ovens, P (7) 174*d*.
Piermarini, G. J. See Forman, R. A.
Pierpont, W. H., Jr. Method of forming fiber glass pipe with integral joint thread, P (8) 193*c*.
Pierre-Dit-Mery, J. M. Process and apparatus for tempering of glass by electrochemical ion exchange, P (10) 245*b*.
Pierson, H. G. W. Selection of liquid-solid separation systems, (11) 276*h*.
Piesslinger, G. See Cornelissen, J.
Piesslinger, G. A. A., and Kunnen, H. M. J. J. La borate fiber optic glass, P (2) 34*j*.
Pietmann, N. Isostatic press, P (3) 69*a*.
Pietras, R. Basic properties of fibrous glass fabric as reinforcing in concrete, (9) 213*j*.
Pigurov, Yu. V. See Dimova, D. Kh.
Pikashov, V. S. See Mazaeva, O. L.
Pike, E. G. Diffusion coating of ferrous articles, P (3) 54*i*.
Pikorz, W. See Borchert, E.
Pilato, J. M. See McDaniel, C. V.
Pil'dish, V. G. See Karklit, A. K.
Pile, F. L., and Olson, E. J. Flat glass shipping case, P (7) 161*f*.
Pilyugin, A. N. See Makeev, V. S.
Pilyugin, A. N., Makeev, V. S., and Padalko, O. V. Laboratory hot-pressing installation, (10) 255*e*.
Pim, K. A. See Berlincourt, D. A.
Pinch, H. L. See Opresko, S. T.
Pincus, A. G. Soviet building with slag sitall (I), (5) 106*a*; (II), (10) 243*j*. See Ali, M. A.; Bratschun, W. R.; Freiman, S. W.
Pine, A. S. Brillouin scattering study of acoustic attenuation in fused quartz, (6) 145*c*.
Pine, A. S., and Dresselhaus, G. Linear wavevector shifts in the Raman spectrum of α-quartz and ir optical activity, (6) 149*d*.
Pinero, G., and Quiroz, R. Kinetics of solid state reactions governed by diffusion, (10) 259*j*.
Pinnell, J. E. See Parker, S. G.
Pinnow, D. A. See Coquin, G. A.; Kolb, E. D.
Pinnow, D. A., and Van Uitert, L. G. Acoustooptic devices using $PbMoO_4$ and related compounds, P (3) 64*a*.
Pinnow, R. L. See Giesfeldt, W. O.
Pintar, M. M. See Sharp, A. R.
Piper, C. P. See Mosebach, W.
Piper, J., Nordquist, L. E., and Hanold, R. C. F., III. Multilayer ceramic capacitor and process, P (2) 41*f*.
Piper, J., and Raschiotto, R. J. Hermetically sealed solid electrolytic capacitor, P (2) 40*a*.
Piper, R. D. Method for thermally refining precipitated haloapatites, P (5) 113*b*. Process for precipitating luminescent alkaline-earth haloapatites, P (9) 227*j*.
Piper, T. E. Apparatus for preventing C diffusion in electric discharge sintering, P (9) 228*i*.
Piquard, G. See Tardif, A.
Pircher, G. See Cahen, O.
Piringer, F. Method and devices for the determination of colors and color tolerances in a visual manner in any kind of artificial light or sunlight, P (7) 174*c*, P (10) 256*b*.
Pirlet, R. A. Method and apparatus for measuring thickness, P (3) 70*c*.
Pirogov, A. A., Mirak'yan, M. M., Leonova, E. N., and Primachenko, V. V. Effect of fluoride mineralizers on Al_2O_3 sintering, (8) 195*c*.
Pirogov, A. A., Rakina, V. P., Mirak'yan, M. M., and Volkov, N. V. Anorthite insulating refractories, (8) 194*j*.
Pirogov, Yu. A. See Pyatikop, P. D.
Pirogov, Yu. A., Prokopenko, M. I., and Prokopets, G. D. Equipment for determining bonding strength of guncrete coatings on refractories, (8) 195*f*.
Pirooz, P. P. Methods of making opal glass articles, P (6) 133*b*. Opalizable borosilicate glass compositions, P (6) 133*d*.
Pisarenko, G. S., Krivenyuk, V. V., and Dubinin, V. P. Selection of a rational heater design for testing high-melting-point cermets, (10) 247*i*.
Pisarenko, N. K. See Khoroshavin, L. B.
Pisharody, R. See Gamble, F. R.
Pitak, N. V., and Anslmova, T. A. Ramming bodies for soaking pits, (8) 195*d*.
Pitetti, R. C., and Zuber, T. W., Jr. Electrochemical etching technique for charting and curing defects in thin-film capacitors, P (6) 137*c*.
Pitha, J. J. Resistance material and method of making, P (1) 14*g*.
Pither, L. F., and Sauv[illegible], P. J. F opal glasses, P (3) 58*c*.
Pitt, R. E. Method for coating and forming high-strength glass fiber mat, P (3) 59*b*.
Pittinger, D. S. Solid neutron-moderating core structures for nuclear reactors, P (4) 92*a*.
Pittman, E. D. Microporosity in carbonate rocks, (3) 71*d*.
Pittman, G. E. See Henderson, G. A.
Pittman, R. R. Surge-modifying lightning arrester construction, P (4) 91*b*.
Pitzer, D. C., Braddock, W. B., Swann, R. C. G., and Pyne, A. E. Dielectric structure for semiconductor device, P (6) 137*a*.
Pivnik, L. Ya. See Khoroshavin, L. B.
Pivovarov, L. E. See Chaporova, I. N.
Pivovarov, L. Z. See Granik, V. A.
Pivovarov, V. S. See Dvorkin, L. I.
Pizzini, G. P. H. See Mandineau, D. P. H.
Pizzini, S., Buzzanca, G., Mari, C., Rossi, L., and Torchio, S. Preparation, structure, and electrical properties of thick RuO_2 films, (8) 199*g*.
Place, H. See Cheshire, A. G.
Placek, E. W. Method and apparatus for [gas-fired] ir heating, P (10) 256*i*.
Plankenhorn, W. J. See Schneider, H. E.
Plaskett, T. S. Synthesis of bulk GaP from Ga solutions, (2) 39*f*. See Blum, S. E.; Giess, E. A.
Platt, A. See Joshi, M. L.; Medvecky, B. P.
Platts, D. R. See Kirchner, H. P.
Pleass, C. M. Method for making electrooptic dipoles, P (6) 138*h*. See Brandes, R. G.
Plendl, J. N. Damping of lattice vibrations in solids, (8) 208*d*.
Plenier, A. See Chakraverty, B. K.
Pless, U. Etchant for selectively etching patterns in thin SiO_2 layers and method of preparing such an etchant, P (9) 225*g*.
Ploeger, F., and Vietzke, H. Apparatus for separating U from an aqueous solution, P (10) 253*i*.
Plotnikov, L. A. Computer experimental method for determining the thermal shock resistance of refractories, (8) 204*d*.
Plovnick, R. H., and Schmidt, G. E. Purification and crystal growth of $KReO_4$, (7) 179*i*.
Plsek, J. See Pospisil, J.
Plumat, E. Chemical tempering process for glass by spraying, P (10) 243*j*. Chemical treatments for modifying physical properties of various materials, P (7) 161*j*. Production of chemically strengthened curved glass bodies, P (4) 82*j*. See Brichard, E.
Plumat, E., and Duperroy, M. Method [drawing] and apparatus for sheet glass fabrication, P (4) 82*c*.
Plumat, E., Duthoit, J., Toussaint, F., and Van Laethem, R. Process for enhancing the effectiveness of chemical tempering of vitreous material, P (4) 82*i*.
Plumat, E., and Leger, L. F. Diffusion treatments of selected [glass] body surface portions by electric arc, P (6) 132*e*.
Plumat, E., and Toussaint, F. Ion exchange of glass with use of CO_2, P (10) 244*f*.
Plumat, E., Toussaint, F., and Schottey, J. [Chemically tempered] glass articles having improved breakage characteristics, P (5) 107*c*.
Plumat, E., and Van Laethem, R. Physically strengthening bodies made of at least partly vitreous material, P (10) 245*j*.
Plumlee, W. W. See Durham, K. M., Jr.
Pluschkell, W. See Goto, K.
Plyushch, G. V. See Samsonov, G. V.
Podchernyaeva, I. A. See Fomenko, V. S.; Lapshov, Yu. K.; Samsonov, G. V.
Podda, L. See Longo, V.
Podlak, R. S., Mack, J. M., and Bretsch, M. A. Spark plug seat, P (9) 228*b*.
Podschus, E. See Dorn, L.
Podschus, E., Dorn, L., and Heinze, G. Process for the production of highly porous bead-form SiO_2 catalyst supports, P (10) 257*f*.
Podzorov, B. N. See Vasil'kova, I. V.
Poeschmann, H. Ground-coat enamel which suppresses gas reactions, (8) 188*j*.
Poferl, G. See Truppe, M.
Pogge, H. B. See Badami, A. V.
Poggi, L. A. TINI hollow block works at Monterotondo (Italy), (2) 35*f*.
Pohanka, R. C. See Cross, L. E.
Poignet, J. C., and Barbier, M. J. Development of a capillary viscometer usable for low viscosity melted salts, (7) 173*c*.
Pointon, A. J. See Saull, R. C.
Poirier, R. See Szydlo, N.
Pokrovskii, A. N., Rybakov, V. K., and Trunov, V. K. X-ray study of Y oxytungstate and the oxytungstates of the lanthanides, (8) 211*j*.
Polak, L. S., and Khatchoian, A. V. Rate coeff. (constant) of nonequilibrium chemical reactions, (6) 151*j*.
Polashenski, W. A. See Larson, J. F.
Polezhaev, Yu. M. See Galkin, Yu. M.
Polezhaev, Yu. M., and Chukhlantsev, V. G. Ternary compounds of the system K_2O-ZrO_2-SiO_2, (9) 239*b*.
Politis, C., Thuemmler, F., and Wedemeyer, H. UN-Mo and UN-W systems at high temp., (7) 171*d*.
Pollack, G. P. See Trivich, D.
Pollak, I., and Roth, J. Automation in the crushed rock industry, (2) 46*a*.
Pollak, M. Frequency dependence of conductivity in amorphous solids, (6) 148*f*.
Pollard, E. R. See Reed, T. B.
Pollina, R. J. See Luthi, B.
Pollitzer, E. L. Process for preparing an SiO_2-Al_2O_3 supported Pt group metal hydrocracking catalyst, P (11) 279*j*.
Pollman, E. W. Casting with glass, (2) 30*b*.
Poltoratskii, N. I. See Makeev, V. S.
Poluboyarinov, D. N. Relation between the deformation properties of some high Al_2O_3 refractories and the impurity concentrations, (8) 195*g*. See Andrianov, N. T.; Guzman, I. Ya.
Poluboyarinov, D. N., Balkevich, V. L., Lemeshev, V. G., Min'kov, D. B., Makarova, T. S., and Binogradova, L. V. Production technology and properties of oxide refractories with a granular structure, (8) 195*c*.
Polyachenok, O. G. See Dudchik, G. P.
Polyakov, V. A. See Antsiferov, V. N.
Polyakova, N. L. See Bystrova, V. I.
Polye, W. R. Capacitance-type pressure transducer, P (4) 87*h*.
Polysius, J., and Ritzmann, H. Apparatus for preheating fine granular material, P (8) 206*g*.
Pompei, J. See Desvignes, F.
Poncet, P. [Screw] mixers, P (1) 17*b*.
Pond, C. W. Composite crystal filter circuit, P (2) 39*h*. Crystal ladder network having improved passband attenuation characteristic, P (2) 39*j*.
Ponomarenko, N. E., Pugina, L. I., and L'vova, G. G. Effect of B on the friction of porous Ni at high velocities and temps., (10) 258*h*.
Pontonnier, L., Caillet, M., and Aleonard, S. System Rb_2BeF_4-Na_2BeF_4, (11) 283*d*.
Poola, J. V. Method and apparatus for making glass windshields, P (5) 107*b*.
Poole, A. B. Application of X-ray fluorescence to silicate analysis, (9) 230*i*.
Poole, J. P., Snyder, H. C., and Boschini, M. A. Tripotassium phosphate treatment for strengthening glass, P (1) 5*f*.
Pope, H. L., Jr. See Morris, M. L., Jr.
Pope, N. C., Kempis, E. B., and O'Donovan, K. H. J. High-pressure device, P (5) 115*g*.
Popkov, I. N. See Krylov, V. S.
Popov, K. N. See Gorshkov, V. S.
Popov, N. I. See Timofeev, M. M.
Popov, O. N. Rational use of Bakor refractories for high-temp. glassmelting, (8) 195*e*.
Popov, V. I. See Krylov, V. S.
Popov, V. S. See Kestner, O. E.
Popov, W. A. See Parker, C. J.
Popova, O. I. See Biryukova, R. S.; Dvorina, I. A.
Popova, Z. V. See Kuznetsov, V. G.
Popovkin, B. A. See Novoselova, A. V.
Popowich, M. J. Resistor compositions containing pyrochlore-related oxides and Pt, P (4) 90*j*.
Popper, P. (editor). Special Ceramics: Vol. 5, B (11) 284*f*.
Poppi, M. Muffle kiln for the firing of glazed ceramic tiles, P (5) 117*a*.
Poppleton, H. O. See Pankratz, L. B.
Popplewell, J. M. See Pryor, M. J.
Pora, N. Two-stage hammer mill, P (6) 144*h*.
Porai-Koshits, E. A., and Averjanov, V. I. Primary and secondary phase separation of Na_2O-SiO_2 glasses, (3) 57*c*.
Poran, H. A. See Johnson, P. D.
Poretskaya, L. V. See Abrikosov, N. Kh.
Porral, G., Matteudi, G., and Davoine, F. Application of the conductive properties of stabilized ZrO_2 to the preparation of thermal probes, (7) 172*i*.
Porta, della P. See della Porta, P.
Porta, P., Marezio, M., Remeika, J. P., and Dernier, P. D. CrO_2—high pressure synthesis and bond lengths, (5) 117*d*.
Porter, D. L. Multiple-contact glass-sealed dry reed switching device, P (2) 34*i*.
Porter, I. T. See Calow, C. A.

Porter, L. J. See Bailey, J. E.
Porter, R. A. Removal of B and P-containing glasses from Si surfaces, P (9) 227*b*. Technique for masking Si_3N_4 during phosphoric acid etching, P (8) 202*g*.
Portier, V. R., White, William B., and Roy, R. Optical spectra of the intermediate oxides of Ti, V, Mo, and W, (10) 260*d*.
Portier, J. See Claverie, J.; Ravez, J.
Portnoi, K. I., Levinskaya, M. Kh., and Romashov, V. M. Constitution diagram of the system Fe-B, (10) 258*f*.
Portnoi, K. I., and Romashov, V. M. Phase diagram of the system Re-B, (10) 260*f*.
Portnoy, W. M., and Leedy, H. M., Jr. Ti-Si rectifying junction, P (3) 68*b*.
Portnoy, W. M., Waters, W. P., and Wisman, E. C. Method of forming epitaxial region of predetermined thickness and article of manufacture, P (2) 41*d*.
Porto, S. P. S. See Arguello, C. A.; Klein, M. V.
Pospisil, J., and Pisek, J. Method for adjustment of the heat-generating process in a rotary kiln with a heat exchanger, P (8) 206*f*.
Poss, S. M. ZnS phosphors, P (8) 203*a*.
Post, R. C. See Carrell, M. A.; Stroup, R. F.
Potryasov, V. N., Antoshchenko, S. Ya., Trusov, V. V., Denisenko, E. I., Kravchenko, I. V., Vlasova, M. T., Yudovich, B. E., and Kal'yanova, V. N. Production of high-strength portland cement, (8) 187*i*.
Potter, C. Pipe stopper for bell and spigot type of tile, P (10) 246*c*.
Potter, P. E. See Bischoff, K.
Potter, R. A. See Leitnaker, J. M.
Potter, R. M. See Perusek, R. J.
Potthoff, I. Scraper to recover bulk material from storage, P (8) 204*b*.
Potvin, A. See Quon, H. H.
Pouchard, M. See Rabardel, L.
Poulain, J. C. See Mandineau, D. P. H.
Poulton, D. J., and Smeltzer, W. W. O diffusion in monoclinic ZrO_2, (9) 237*i*.
Pound, G. M. See Nishioka, Kazumi.
Povysheva, L. G. See Chistyakova, A. A.
Powel, W. S. Apparatus for advancing pallets for making tiles, P (10) 248*i*.
Powell, A. C. Rotary kiln nose ring, P (11) 279*c*. See King, G.
Powell, B. E., and McKibben, B. M. Alkali halide filamentary crystals, (7) 176*d*.
Powell, D. A. See Cole, W. F.
Powell, R. L. See Sparks, L. L.
Powell, R. J., and Berglund, C. N. Photoinjection studies of charge distributions in oxides of MOS structures, (6) 150*i*.
Powers, P. Spark-type ion source and downstream deflector for mass spectrometer, P (1) 18*i*.
Powers, W. M. See Davies, L. G.
Pozhivanov, A. M. See Likhoradov, A. P.
Pracka, I. See Paderno, Yu. B.
Prager, H. J. See Chang, Kern K. N.
Prange, B. H., and Gintert, D. W. Method and apparatus for silk-screening a pattern on an underlying [glass] substrate, P (5) 107*b*.
Prasad, C. See Garlick, G. F. J.
Pratt, P. L. See Kirk, D. L.
Prazak, C. J. Screening of black-surround color picture tubes, P (7) 170*j*.
Precht, W. See Hollox, G. E.
Preier, H. M. See Lehovec, K.
Preininger, E., and Ging, D. Inorganic white pigments containing optical brighteners and process for their mfg., P (9) 232*h*.
Preisler, E., Frorath, K. F., and Strauss, G. Process for the electrolytic production of MnO_2, P (4) 94*g*.
Prendergast, I. D., Budworth, D. W., and Brett, N. H. Densification and grain size control in Al_2O_3, (11) 280*h*.
Prener, J. S. See Kingsley, J. D.
Prener, J. S., and Kingsley, J. D. Rare earth activated Ag and Cu sensitized Zn and Cd sulfide phosphors, P (1) 14*g*.
Pressau, J. P. See Gillery, F. H.
Pressley, H. Some effects of attack on refractories by the oxides of Na, S, and V, (1) 8*a*.
Pressley, R. J. See Burke, W. J.
Prestinini, P., Macey, R. G., and Macey, A. M. Method for making anhydrous $MgCl_2$, P (6) 144*b*.
Preston, G. A. See Giardini, D. S.
Preston, J. P. See Alpert, M. B.
Preston, T. K. See French, S. E.
Prete, J. A., and Raudat, J. L. Apparatus for simultaneously loading groups of articles into packing cases, P (10) 243*h*.
Preuss, H. J. See Broemer, H.
Previte, R. W. Some insights on the mechanism of saccharide set retardation of portland cement, (5) 104*b*.
Prible, G. V. Preassembled insulating panels for high-temp. furnaces, P (1) 9*d*.
Pribylov, K. P. See Berg, L. G.
Price, D. M. See Harding, B. C.
Price, J. B., and Wagner, J. B., Jr. Diffusion of Mn in single crystalline manganous oxide, (2) 47*j*.
Price, J. W. See Bell, N.
Price, M. S. T. See Gough, J. R. C.
Price, N. See Lind, R.
Price, T. F., and Walton, R. R. Roller hearth furnace with roll oscillation controller, P (1) 19*e*.
Priest, E. H., and Priest, G. M. Apparatus and method for melting a solid, P (8) 206*f*.
Priest, G. M. See Priest, E. H.
Priest, J. G. See Keeling, R. A.
Priestland, C. R. D. See Emery, J. A. A.
Prijn, C., and Benedetti, F. Electric lamp comprising a lamp base of a synthetic material, P (10) 244*d*.
Primachenko, V. V. See Pirogov, A. A.
Prins, J. F., Harding, D. R., and James, G. S. Apparatus for testing single diamond particles under simulated working conditions, (4) 77*e*.
Prislan, G. Apparatus for the drawing of continuous sheets of glass including glassmelt heating and cooling means, P (8) 192*a*. Process for the production of float glass with even edges, P (4) 82*j*.
Probst, R. See Lehmann, H.
Procopio, J. J. See Goelzer, W. C.
Proctor, T. M., Jr. Sound speed measurements in solids—absolute accuracy of an improved transient pulse method, (4) 93*a*.
Prod'homme, L. Phase separation in some glasses by transmission measurements, (11) 269*d*.
Prod'homme, M. Some properties of Na borosilicate glasses liable to demixing, (10) 243*j*.
Prokhvatilov, V. G. See Limar, T. F.
Prokof'ev, S. A. See Levinskii, Yu. V.
Prokopec, J. C. See Douglas, G. A.
Prokopenko, M. I. See Pirogov, Yu. A.
Prokopets, G. D. See Pirogov, Yu. A.
Prokoshina, S. M. See Lidorenko, N. S.
Prom, R. L. See Leinkram, C. Z.
Proper, J. See Albrecht, C.
Prost, R. See Calvet, R.
Protsenko, T. G. See Fomenko, V. S.
Protzman, T. F., and Magidson, W. H. Color TV tube [coating] fabrication, P (10) 244*a*.
Provenzano, V., Boesch, L. P., Volterra, V., Moynihan, C. T., and Macedo, P. B. Electrical relaxation in $Na_2O{\cdot}3SiO_2$ glass, (11) 268*c*.
Provost, G. See Millet, J.
Proxmire, H. J. Method of producing a brush track for an adjustable sliding brush transformer, P (3) 53*h*.
Pruniaux, B. R. Transport properties of the Au Ge GaAs metal semiconductor system, (5) 112*d*.
Prussog, D. Determination of the degree of burning of lime by X-ray diffraction analysis, (5) 102*e*. High temp. X-ray diffraction technique for the measurement of thermal expansion, (7) 173*g*.
Pryadka, G. A. See Samsonov, G. V.
Pryce, M. H. L. See Kisliuk, P.
Prygunov, V. F. See Morozov, V. I.
Pryor, J. N. Process for preparing alkalized Al_2O_3, P (4) 94*i*.
Pryor, M. J. Method of making a glass or ceramic-to-composite metal seal, P (3) 59*e*.
Pryor, M. J., and Popplewell, J. M. Composites of glass or ceramic-to-metal seals and method of making, P (10) 244*b*.
Prytkov, E. F. Tubular incandescent lamp, P (10) 245*i*.
Puckett, A. M. See Dennen, W. H.
Puetz, E. J. See Libera, J. J.; Olmsted, L. E.
Pugin, V. A., and Khitarov, N. I. Equilibria in the Al_2O_3-SiO_2 system, (1) 22*b*.
Pugina, L. I. Sintered antifriction materials, (10) 247*i*. See Korkh, L. M.; Ponomarenko, N. E.
Pukhlik, O. I., Boguslavskii, I. A., Fridkin, R. Z., and Khalizeva, O. N. Calculating the optimum heating cycles for glass during hardening, (8) 189*g*.
Pull, B. T. See Ronzio, A. R.
Pulliam, G. R. See Mee, J. E.
Purdes, A. J., and Jost, E. M. Method of modifying electrical resistivity characteristics of dielectric substrates [$BaTiO_3$], P (5) 113*j*.
Purgin, A. K. See Khoroshavin, L. B.
Puri, S. P. See Malathi, N.
Puring, M. N. See Krylov, V. S.
Purnanandam, M. See Rao, T. S.
Purser, C. R. See Panther, R. H.
Purton, M. J., and Coldrey, J. M. Effect of autoclaving conditions on the constitution and properties of Ca silicate brick specimens, (1) 5*j*.
Purusova, T. N. See Guzman, I. Ya.
Pustyl'nik, T. M. See Larionova, T. N.
Puthoff, H. E. See Amzallag, E.
P'yachev, V. A. See Chebukov, M. F.
Pyanov, V. N. See Kestner, O. E.
Pyatikop, P. D., Pirogov, Yu. A., Boltyanskii, A. V., Gurskii, G. L., and Kobylko, V. S. Phase composition of magnesite-chromite refractories with guncrete coatings after use in an open-hearth roof, (8) 195*b*.
Pyne, A. E. See Pitzer, D. C.
Pytte, E., and Feder, J. Theory of a structural phase transition in perovskite-type crystals, (6) 152*b*.
Pyzewski, S. J. See Bowser, G. H.

Quaal, G. J. See Woerner, L. M.
Quaas, J. F. Welding electrode, P (4) 80*c*.
Quandt, H. C. Graphite crucibles for use in producing high-quality quartz, P (7) 162*b*.
Queeney, R. A. See Gagorik, J. E.; Stinchcomb, W. W.
Queisser, H. J. Sign of Hall coeff. in a relaxation-case semiconductor, (7) 180*d*.
Quickenden, T. I., and Marshall, R. C. Magnetochemistry in SI [International System] units, (7) 182*e*.
Quincy, R. B., Jr. See Sturm, B. J.
Quinn, C. M. See Drakeford, R. W.
Quinn, T. J., and Chandler, T. R. D. Pt metal thermocouples. New international reference tables, (10) 255*i*.
Quinson, J. F. See Escoubes, M.
Quint, S. M., and Dalton, J. J. Coating for H_2O-containing hydraulic cement articles, P (10) 242*d*.
Quintilian, B. F. See Gately, T. J.
Quiroz, R. See Pinero, G.
Quon, H. H., Eastwood, H. K., and Potvin, A. J. Crystal growth in the system $NiFe_2O_4$-BaO-B_2O_3, (8) 208*h*.
Quon, H. H., and Potvin, A. J. Growth of single crystal rare earth garnet films by liquid phase epitaxy, (8) 199*h*.
Quon, H. H., Potvin, A. J., and Entwistle, S. D. Growth of orthoferrite single crystals from flux melts, (2) 48*b*.
Qureshi, A. H. See Saleh, N.

Ra, O. Vibrational contributions to the thermodynamics of imperfect crystals. A propagator viewpoint, (11) 283*c*.
Rabardel, L. See Fava, J.
Rabardel, L., Pouchard, M., and Hagenmuller, P. Precise determination of specific mass (of powders) by hydrostatic pressure, (3) 70*a*.
Rabatin, J. G. See Gillooly, G. R.
Rabatin, J. G., and Bradshaw, E. Tb-activated rare-earth oxyhalide phosphors containing Yb for reduced afterglow, P (9) 228*e*.
Rabatin, J. G., and Sieger, R. A. X-ray image convertors utilizing La and Gd oxyhalide luminescent materials activated with Tb, P (3) 68*b*.
Rabinovich, M. A. See Fain, I. A.
Rabodzei, N. V., Astrin, V. A., Kuzmicheva, N. V., Shidlovskii, G. V., Ljubimov, E. M., and Nadobnikov, M. N. X-ray television microscope, P (2) 45*c*.
Rabusin, E. See della Porta, P.
Raccanelli, A., Navazio, G., and Scorzon, L. Effects of spray-drying processes on the characteristics of some clays, (4) 94*d*.
Radielovic, D. See Wanmaker, W. L.
Radkova, A. See Kukusheva, M.
Rado, G. T. See Schelleng, J. H.
Rado, P. Strange case of hard porcelain, (2) 37*j*.
Radomysel'skii, I. D. See Vlasyuk, R. Z.
Radomysel'skii, I. D., and Dymchenko, V. A. Investigation of the vol changes occurring during the sintering of Fe-Cr carbide composite materials, (10) 259*f*.
Radomysel'skii, I. D., and Shcherban, N. I. Ejection force in the cold pressing of metal-glass materials, (10) 243*c*.
Radovanov, P. See Gal, I. J.
Raevskii, G. V. Operation of welded rotary kiln shell, (8) 187*g*.
Raffy, J. See Budin, J. P.
Raghavan, K. S. See Uttecht, R.
Raghavan, V. See Subbarao, E. C.
Raginskaya, P. I. See Koren, M. G.
Rahe, V. See Ihrig, A. C.; Lipp, G. D.
Rahman, M. L. See Linnett, J. W.
Rahman, M. L., and Linnett, J. W. Recombination of atoms at surfaces (XI) N atoms at some acid, base, and salt surfaces, (1) 24*i*.
Rahmanova, T. A. See Dzhigit, O. M.
Rahnke, C. J. Ceramic turbine wheel, P (9) 222*c*.
Raholison, C. See Rakotomahanina-Rolaisoa, E.
Raichenko, A. I., Martynova, I. F., and Skorik, L. I. Effect of heat treatment on the brightness coeffs. of Fe-Cr cermet alloys, (10) 246*j*.
Rai-Choudhury, P. Epitaxial GaAs from trimethyl Ga and arsine, (2) 38*g*.
Rainone, N. J. Lamp to eliminate single frame curtain, P (5) 107*i*. See De Caro, A. R.
Rains, T. C. See Dean, J. A.; Shultz, J. I.
Rairden, J. R., III. Refractory metal/refractory metal nitride resistor films, P (7) 164*f*.
Raithel, K. Method of joining a body of semiconductor material to a contact or support member, P (9) 226*j*.
Raithel, K., and Rosenheinrich, R. Pressure-biased semiconductor component free from damage to semiconductor body, P (4) 90*b*.
Rajdev, D. See Kumar, A.
Raju, T. A. See Soellner, A. M.
Rakestraw, L. F. See Dunn, S. A.
Rakhmatulin, Ya., Gladyshev, V. P., and Evseev, Yu. N. Synthesis of Ta phosphate, (2) 50*b*.
Rakina, V. P. See Pirogov, A. A.
Rakotomahanina-Rolaisoa, E., Henry, Y., Durif, A., and Raholison, C. Systems $TlPO_3$-$Co(PO_3)_2$, $TlPO_3$-$Mg(PO_3)_2$, and $TlPO_3$-$Ca(PO_3)_2$, (8) 211*h*.
Ralston, P. H. Compositions [binders] for use in refractories, P (8) 196*h*.
Ram, M. J. Graphitization process, P (8) 196*j*.
Ram, M. J., Riggs, J. P., and Clarke, C. M. Process for the carbonization of a stabilized acrylic fibrous material, P (10) 248*e*.
Ramachandran, V. S. Interaction of Ca lignosulfonate with Ca_3SiO_5, hydrated Ca_3SiO_5, and Ca hydroxide, (7) 156*e*. See Feldman, R. F.
Ramakrishna, J. See Rangarajan, G.
Ramani, S. V., Mohapatra, S. K., Gokhale, K. V. G. K., and Subbarao, E. C. Zircon—a review, (11) 279*e*.
Ramankulov, M. R. See Butt, Yu. M.

Ramdas, S. See Rao, G. V. S.
Ramesam, K. See Banerjee, J. C.
Ramge, D. L. See McFadden, N. E.
Ramisch, E. Electric condenser with a flat tubular dielectric, P (10) 250*j*.
Ramisch, E., and Schwan, W. Sintered cold-conductor resistor body and method for its production, P (5) 114*a*.
Ramsbotham, J. See Parfitt, G. D.
Ramsey, H. J. Apparatus for bonding semiconductor elements, P (4) 87*d*.
Ramsey, T. H. Use of DTA in controlling behavior of solder-glass seals in ceramic packages, (11) 274*c*.
Ramseyer, J. A. Elastomeric composition containing SiC for use as an ablative coating, P (3) 61*c*.
Rana, V. See Thomson, R.
Ranallo, H. U. See Wiltshire, A. J.
Rand, H. B. See Gustafson, E. L.
Randels, R. B. Electronic image device with mesh electrode for reducing moire patterns, P (2) 40*e*.
Randolph, D. R. Recovery of F and P_2O_5 from dilute aqueous acidic phosphatic solutions, P (3) 72*b*.
Rangarajan, G., and Ramakrishna, J. NMR study of internal motions in certain Fe group fluosilicates, (4) 97*j*.
Rankin, D. T., Stiglich, J. J., Petrak, D. R., and Ruh, R. Reply to "Discussion of 'Hot-pressing and mechanical properties of Al_2O_3 with an Mo-dispersed phase'," (1) 21*h*.
Ranney, F. J. See Gambale, J. R.
Ranon, U. See Rosenthal, J.
Ranze, W. Process control requirements in the initial stage of cement factory design, (11) 266*j*.
Rao, C. N. R. See Rao, G. V. S.
Rao, D. B. See Cyvin, B. N.
Rao, G. V. S., Ramdas, S., Tomar, M. S., and Rao, C. N. R. Electrical conduction in binary oxide systems of the type $M'O_2$-M''_2O_3, (11) 281*h*.
Rao, J. B. V. See Janakirama-Rao, B. V.
Rao, K. S. See Rao, K. V.
Rao, K. V., and Rao, K. S. Effect of O impurity on the electrical conductivity and dielectric properties of CoO and NiO single crystals, (6) 146*i*.
Rao, M. R. K. See Mathur, N. M.
Rao, R., and Bradshaw, R. I. Etchants, the treatment of monocrystalline semiconductor wafers therewith, and semiconductor devices incorporating such wafers, P (1) 12*b*.
Rao, R. P. Method for insolubilizing Na silicate foam, P (8) 207*f*.
Rao, T. C., Gokhale, K. V. G. K., and Malhotra, D. Thermal studies on pyrophyllite diaspore minerals, (11) 283*a*.
Rao, T. S., Revathi, B., and Purnanandam, M. Elastic moduli of some polycrystalline ferrites, (11) 281*f*.
Rao, V. D. Ceramic crossarm seal for gas turbine regenerators, P (1) 8*j*.
Rao, V. D., Telang, Y. P., and White, J. E. Bearing member for high-temp. applications, P (10) 247*c*.
Rao, V. V. V. N. S. R., and Abraham, K. P. Kinetics of oxidation of Cu_2S, (6) 149*e*.
Rao, W. R., and Cutler, I. B. Initial sintering and surface diffusion in Al_2O_3, (4) 97*g*.
Rapp, C. F. See Lee, H. A., Jr.
Rapp, J. E. See Busdiecker, R. A.
Rappinger, B. See Norin, R.
Rasch, E. See Hofmann, D.
Raschiotto, R. J. See Piper, J.
Rash, C. D. Junior high students can throw big pots, (2) 30*a*.
Rasmussen, A. L. See West, E. D.
Rasmussen, J. J. Surface tension, density, and vol change on melting of Al_2O_3 systems, Cr_2O_3, and Sm_2O_3, (7) 181*b*.
Rasmussen, P. D., and Schulze, R. E. Potter's wheel with variable speed drive arrangement, P (1) 17*a*.
Rasmussen, S. E. See Nielsen, B. R.
Rasmussen, S. T., and Cutler, I. B. Sintering of feldspar, (11) 282*b*.
Rasquin, J. R., and Estes, M. F. Apparatus for making diamonds, P (4) 77*i*.
Rassoul, S. A. See McCreary, J. R.
Ratcliff, P. S. Effective evaluation of refractory performance in electric arc furnaces, (2) 36*a*.
Ratcliffe, E. G. Production of Fe oxide pigments, P (3) 72*b*.
Rau, C. A., Jr. See Swenson, D. O.
Rau, F. J. See Jansson, R. A.
Raudat, J. L. See Prete, J. A.
Rausch, W., von der Decken, C. B., and Bachus, K. P. Method of measuring the nuclear physical behavior of bodies, P (7) 171*h*.
Rausell-Colom, J. A., and Salvador, P. S. Gelling of vermiculite in solutions of γ-aminobutyric acid, (9) 235*f*. Vermiculite-amino acid complexes, (6) 153*a*.
Ravaglioli, A. See Emiliani, T.
Ravaglioli, A., Missiroli, A., and Ortelli, G. Method for the determination of Pb in micro-quantities in the presence of other cations, (10) 255*h*.
Ravas, R. J. See Osial, T. A.
Raveau, B. See Choisnet, J.; Desgardin, G.
Ravez, J., Grannec, J., and Portier, J. Systems MF_2-TlF_3 (M=Ca,Sr), (4) 99*d*.
Ravez, J., Tourneur, D., and Hagenmuller, P. Primary phases of ferroelectric oxyfluorides of the type "tetragonal W bronze," (8) 210*i*.
Rawal, B. S., and Hurt, J. C. Discussion of "Determination of axial stress in clad glass fibers," (1) 3*c*.
Rawson, H. See Howse, T. K. G.; Kent, R.
Ray, A. E., and Strnat, K. Permanent magnet, P (10) 252*h*.
Ray, H. S. See Bandyopadhyay, G. K.
Ray, J. D., Steingiser, S., and Cass, R. A. Treatment of C or graphite fibers and yarns for use in fiber-reinforced composites, P (9) 222*i*.
Ray, R. A., and Sternberg, J. C. Temp.-controlled discrete sample analyzer, P (2) 45*b*.
Ray, R. L. See Chu, Ting Li.
Ray, S. See Gon, P.
Rayburn, C. C. Monolithic capacitor components and process for producing, P (3) 66*a*.
Raygor, P. O. See Brody, T. P.
Rayment, D. L. See Ali, M. A.
Raymond, M. See Hafner, S. S.
Raymonda, J. W., Muenter, J. S., and Klemperer, W. A. Electric dipole moment of SiO and GeO, (5) 120*g*.
Rayner, J. W. F. See King, G.
Rea, R. F. Method of making a [mill lining] brick with wear indicator, P (3) 62*b*.
Rea, S. N. See Wakefield, G.
Reade, F. G., and Smith, Tazzell. Method of making a ferrite head, P (3) 65*i*.
Reade, R. F. Tb-activated radioluminescent silicate glasses, P (7) 163*c*.
Reader, A. M. See Steuetz, D. E.
Reber, R. L., and Huiskens, J. C. Method and apparatus for etching fine line patterns in metal on semiconductive devices, P (10) 251*j*.
Rebinder, P. A. See Andreeva, E. P.; Lishanskii, B. A.
Rechberger, F. F. Grinding wheel package and method of packaging, P (4) 77*g*.
Rechter, H. L. See Bortz, S. A.
Reddy, J. See Volpe, M. L.
Reder, H. See Schiekel, M.
Rediker, R. H. Method of and apparatus for enhancing radiation from indirect-gap semiconductors, P (4) 88*d*. See Fonstad, C. G.
Redwantz, J. O. Semiconductor interconnecting system using conductive patterns bonded to thin flexible insulating films, P (8) 202*j*.
Redwine, D. J. MOS circuit with bipolar emitter-follower output, P (1) 14*a*.
Redwine, D. J., and Worstell, E. M., Jr. MOSIC with protection against voltage surges, P (1) 14*a*.
Reed, D. See Fort, A.
Reed, J. S. See Cooley, R. F.; Fennelly, T. J.
Reed, M. W., Jr., and Schwemer, W. C. Method of making a porous C material, P (6) 135*a*.
Reed, R. A. See Bennett, H.
Reed, R. D. See Zink, J. S.
Reed, R. D., and Zink, J. S. Pressurized fuel burner, P (11) 279*c*.
Reed, T. B. See Feinleib, J.; Hayakawa, M.; Honig, J. M.; Oliver, M. R.; Pidgeon, C. R.
Reed, T. B., and Fahey, R. E. Growth of EuO, EuS, EuSe, and EuTe single crystals, (7) 177*i*.
Reed, T. B., and Pollard, E. R. Method and structure for growing crystals, P (3) 66*h*.
Reeder, M. M. See Grove, R. J.
Rees, J. M. See Coaton, J. R.
Reeves, W. T. See Chen, Wei-Kong.
Regh, J., and Silvey, G. A. Method for polishing an Si surface, P (2) 41*j*.
Reginato, L. L. See Smith, Bob H.
Reh, L., Schmidt, W. H., and Rosenthal, K. Fluidized-bed cooler and method of cooling particulate solid material, P (10) 256*f*.
Rehfeld, G., and Schwiete, H. E. Recent results on the melting behavior of mullite, (1) 24*g*.
Rehkope, C. H. See Ng, D. M.
Rehmet, M., and Begemann, J. High-pressure compact arc lamp with electrodes containing TaC, P (3) 58*b*.
Reich, A. R. See Wilkins, B. J. S.
Reichard, T. E. Apparatus for measuring film thickness, P (1) 18*d*.
Reichelt, B., Lippert, W., Zoellner, D., and Kegel, K. Special [graphite] electrodes for light arc furnaces, P (11) 272*g*.
Reichelt, W., Ruthardt, K., and Speidel, H. Low current electrical contact comprising a layer of Fe-Ni alloy and a layer of Ru, P (10) 251*c*.
Reichert, K. O. Method of grooving semiconductor wafer for the dividing thereof, P (10) 251*j*.
Reid, A. F. See Grey, I. E.
Reid, A. F., and Ward, J. C. Solid solution in the $FeTi_2O_5$-Ti_3O_5 system, (3) 75*h*.
Reid, D. M. Apparatus for supplying granular material, P (9) 229*g*.
Reid, E. D. Composite wear-resistant material and method of making, P (10) 242*i*.
Reid, F. J. See Moody, J. W.
Reimann, D. K., Kroeger, D. M., and Lundy, T. S. Cation self-diffusion in UN_{1+x}, (7) 171*b*.
Rein, H. M., and Conze, P. Methods of producing diffusion regions in semiconductor bodies, P (9) 226*g*.
Reinhall, R. B. Grinding apparatus [with disks], P (11) 277*a*.
Reinhardt, P. D. See Kemeny, G.
Reinhart, F. Protective coatings on ceramic bodies, (5) 110*j*.
Reinheimer, H. A. See Forst, S. M.
Reiplinger, A. See Giersberg, J.
Reisner, W., and Rothe, M. v. E. Bins and Bunkers for Handling Bulk Materials—Practical Design and Techniques, B (3) 76*h*.
Reiss, S. E. Method for fabricating multilayer magnetic devices, P (10) 251*c*.
Reitmayer, F., and Schuster, E. Homogeneity of optical glasses, (10) 243*f*.
Remeika, J. P. See Gyorgy, E. M.; Kahn, F. J.; Marezio, M.; McWhan, D. B.; Porta, P.; Van Landuyt, J.; Wood, D. L.
Remmers, K., Bertoldi, G., Leitner, K., and Eigner, E. Process for calcining gypsum in a current of heating gas, P (6) 130*g*.
Renaud, R. Conductimetric and cryoscopic investigations in molten V_2O_5—reactions with various oxides, (6) 145*b*.
Renfordt, U. Plant experiences with electrostatic enamel application, (8) 189*c*.
Renke, A. See Vassilevsky, A. N.
Rennie, C. A., Lockett, G. E., and Hosegood, S. B. Pentagonal core blocks for gas-cooled nuclear reactors, P (10) 254*b*.
Repik, A. J. See Ball, F. J.
Rettew, R. R., Wirth, D. G., Jr., and Levy, N., Jr. Process for the preparation of Al_2O_3 and Mg aluminate bodies, P (7) 164*b*.
Reuschel, K. See Haas, E.
Reuss, A. Preliminary homogenization of raw materials in the cement industry, (9) 215*a*.
Reusser, R. E. See Czeck, J. J.
Reuter, J. L. See Dhaka, V. A.
Reuter, J. L., and Sandhu, J. S. Fabrication method for semiconductor devices, P (4) 87*h*. Ion-free insulating layers, P (9) 225*e*.
Revathi, B. See Rao, T. S.
Revay, M., and Szijj, F. Connection between quicklime quality and burning parameters, (6) 128*c*.
Revcolevschi, A. See Saurat, M.
Revesz, A. G. See Duffy, M. T.
Revesz, R. N. See Sitek, G. J.
Revitz, M., and Turene, F. E. Semiconductor device with β-Ta-Au composite conductor metallurgy, P (5) 114*c*.
Rexford, D. G., Kim, Y. M., and Story, H. S. ESR studies of Cr^{3+} in $LiNbO_3$, (5) 120*a*.
Reyes, J. M. See Sayer, M.
Reynolds, D. C., and Collins, T. C. Donor-acceptor pair recombination spectra in CdS crystals, (6) 146*e*. Excited terminal states of a bound exciton-donor complex in ZnO, (6) 148*a*.
Reynolds, J. A. Analysis and control of glass and raw materials, (8) 189*e*.
Reynolds, J. A., and Fox, J. Experiences with electron beam analysis with particular regard to Na and F, (8) 205*a*.
Reynolds, M. J. See Casselton, R. E. W.
Reynolds, R. C., Jr. See Tettenhorst, R.
Reynolds, R. W. See Abraham, M. M.
Reynolds, W. E. See Bortz, S. A.
Rhee, C., and Bray, P. J. Effect of ionic motion on the ^{133}Cs NMR in glass-y and crystalline Cs borates, (7) 159*d*. NMR studies of the structure of Cs borate glasses and crystalline compounds, (7) 160*g*.
Rhee, Kyung Hee. See Daimon, Masaki.
Rhee, S. K. Critical surface energies of Al_2O_3 and graphite, (7) 157*h*. Wetting of TaC by liquid Cu and liquid Ag, (4) 80*a*.
Rhodenizer, H. L., Grunwald, J. J., and Innes, W. P. Method of making additive printed circuit boards and product thereof, P (9) 226*a*.
Riazance, N. See Nafziger, R. H.
Ribes, M. See Philippot, E.
Ricchezza, E. N., and Doremus, R. H. Protective coating and method of making, P (3) 54*h*.
Ricci, R. J. See Staffin, R.
Rice, D. K., and DeShazer, L. G. Spectra of Eu in monoclinic Gd sesquioxide, (5) 124*b*.
Rice, E. J. Method for fabricating semiconductor junctions, P (10) 251*c*. See Crishal, J. M.
Rice, M. J., and Roth, W. L. Ionic transport in super ionic conductors—a theoretical model, (10) 259*g*.
Rice, R. R. Pulse shape of a mode-locked frequency-doubled Nd:YAG laser, (6) 151*h*.
Rice, R. W. Deformation, recrystallization, strength, and fracture of press-forged ceramic crystals, (3) 72*e*. See Schneider, S. J., Jr.
Rice, S. B., Jr. Preparation of welding surfaces on semiconductors, P (6) 139*d*.
Rice, T. M. See McWhan, D. B.
Rice, W. See Hissong, G. E., Jr.
Rich, G. J. See Hobden, M. V.
Rich, T. C. See Kolb, E. D.
Richard, G. P. See Moss, G.
Richards, B. P. See Greenham, A. C.
Richards, C. W. See Sellevold, E. J.
Richards, P. L. See Joyce, R. R.
Richards, R. Bricks, (2) 35*e*.
Richards, R. See Bode, W. W.
Richardson, C. D. Method and apparatus for fiberizing molten mineral materials, P (9) 219*i*.
Richardson, H. L., and Craig, R. C. Electrostatic precipitator, P (9) 230*a*.
Richardson, H. M. See Hodson, P. T. A.; Palin, F. T.
Richardson, J. H. Optical Microscopy for the Materials Sciences, B (5) 125*d*.
Richerson, D. W., and Hummel, F. A. Synthesis and thermal expansion of polycrystalline Cs minerals, (6) 152*h*.

Richmond, C. See Hatfield, T.
Richter, R. W. See Van der Heuvel, A. P.
Richter, V. Automation in the whitewares industry, (2) 37*h*
Rickey, C. J. See Culbreth, W. K., Jr.
Ricks, H. E. Fuel-element coating containing burnable poison, P (3) 68*h*.
Ricks, M. J. See Ogden, J. S.
Riddel, J. W. Thermistor composition, P (7) 170*f*.
Ride, C. Study of heat exchange during firing of ceramic products and its application to firing time, (2) 45*e*.
Rideout, A. J. Integrated lateral transistor having increased β and bandwidth, P (7) 169*a*. Passive elements for solid-state integrated circuits, P (2) 41*j*.
Ridge, M. J. See Beretka, J.
Ridge, M. J., and King, G. A. Comments on use of reduced time in plotting kinetic data, (3) 53*j*.
Riebling, E. F. See Dalton, R. H.
Riebling, E. F., Blaszyk, P. E., and Smith, Dennis W. Fluoride glasses containing Xe, P (7) 161*f*.
Ried, E. A., Jr. Infrared burner and method of increasing the heat flux radiated therefrom, P (4) 93*j*.
Riedel, E. P., and Isaacs, T. J. Orange–red-emitting Eu-activated Y stannate phosphor for warm-white blends, P (5) 113*f*.
Riedel, R. Heating zone of the tunnel kiln and its problems, (4) 93*i*.
Riedel, W., Binberg, R., Haewecker, M., and Goering, C. Influence of cement minerals on corrosion resistance of portland cements in Mg salt solutions, (8) 186*i*.
Riederer, J. See Fleming, S. J.
Riedner, R. J., and Cartz, L. Thermal-expansion characteristics of $CrVO_4$ by X-ray diffraction, (7) 181*d*.
Riehm, T. See Gehrig, O.
Ries, H. B. Mfg. ferrites with special reference to preparation, (6) 136*g*.
Rieser, R. G. See Donley, H. E.
Riffaud, J. B., Koehret, B., and Koupal, B. Modeling and simulation of an Al_2O_3 kiln, (9) 232*d*.
Rigby, E. B. See Iler, R. K.
Rigby, G. R. Mechanical properties of basic bricks (I) survey of the MgO-chrome system; (II) effect of chrome ore sizing, (1) 7*b*; (III) role of the silicate phases, (2) 36*d*. Mechanical properties of high-Al_2O_3 refractories utilizing various bonding agents, (2) 36*g*.
Rigge, R. J. See Bell, N.
Riggs, J. P. See Ram, M. J.
Rigney, J. A. See Arey, W. F., Jr.
Rigterink, M. D. Advances in technology of the cryochemical process, (3) 62*f*.
Rijken, A. J. Recent investigations on frost resistance of roofing tiles, (4) 83*e*.
Rijnbeek, A. G. See Westendorp, F. F.
Rijnders, J. Halogen filament lamp for vehicle headlight with screen partly surrounding antiglare filament, P (6) 133*b*.
Riley, G. S., and Mann, G. R. Effects of particle shape on angles of repose and bulk densities of a granular solid, (5) 117*e*.
Riley, J. F. See Clawson, C. D.
Riley, R. F. See Rosenthal, J.
Riley, R. J. See Carpenter, D. R.
Riley, R. R. See Whitehouse, W. E.
Rimer, K. W. See Oberly, J. E.
Rimkus, H. Method for producing metal-to-ceramic junctions, P (10) 252*b*.
Rindner, W., and Roth, H. Gunn-type solid-state devices, P (9) 225*b*.
Rine, J. C. See Caserta, R. T.
Riotti, S. See Longo, V.
Ripper, J. E. See Dyment, J. C.; Paoli, T. L.
Risberg, L. A. See Cohen, E.
Riseman, J. See Kennedy, D. P.
Riseman, J., and Totta, P. A. Composite metallurgy stripe for semiconductor devices, P (3) 64*d*.
Risse, M. See Baudran, A.
Ristic, M. M. See Boskovic, S.
Ritchey, R. A. See Barnard, P. G.
Ritchie, F. S. See Seeley, J. S.
Riter, J. R., Jr. Interpretation of diamond and graphite compressibility data using molecular force constants, (6) 149*a*.
Ritter, G. F., Jr. Bending and tempering glass sheets, P (11) 270*b*. Glass sheet bending and tempering apparatus, P (10) 244*c*. Glass sheet [press] bending method and apparatus, P (3) 58*a*. Loading and unloading apparatus, P (1) 4*a*. Method and apparatus for bending glass sheets, P (4) 82*j*.
Ritter, G. F., Jr., and Hymore, F. J. Apparatus for tempering flat sheets or plates of glass, P (10) 243*h*.
Ritter, J. E., Jr., and Sherburne, C. L. Dynamic and static fatigue of silicate glasses, (1) 3*c*.
Rittler, H. L. See MacDowell, J. F.
Ritzmann, H. Apparatus for heat treatment of fine material, P (1) 19*d*. See Polysius, J.
Ritzmann, H., Heinemann, O., and Goldmann, W. Method of cooling fired or sintered material, P (9) 232*d*.
Rively, C. M. See Petro, J.
Rivers, A. D. See Copley, G. J.
Rivlin, N. I. See Koren, M. G.
Rivoire, C. L., and Mourros, R. Mfg. superwhite cements, P (3) 54*b*.
Rix, C. E., and Mysels, K. J. Method of treating glass fibers, P (11) 270*g*.
Roach, H. C. See Roberts, J. R.
Roaper, R. B., II. See Weaver, H., Jr.
Robbins, M. Magnetic compositions, P (10) 251*d*. See Levinstein, H. J.
Robbins, M., Wertheim, G. K., Storm, A. R., and Buchanan, D. N. E. Preparation of polycrystalline rare earth orthoferrites and garnets via hydroxide precipitation, (6) 136*j*.
Robbins, M., and Wolfe, R. Ferrimagnetic semiconducting material and devices made therefrom, P (5) 112*b*.
Roberson, H. E., and Towe, K. M. Montmorillonite—electron diffraction from 2-dimensional single crystals, (10) 260*b*.
Robert, G. See Hammou, A.
Roberts, A. A. See Leff, J.
Roberts, B. W. Properties of selected superconductive materials, (10) 249*g*.
Roberts, C. A. Ground glass in the garden, (5) 106*a*.
Roberts, D. T., Jr. See Jolley, G. B.
Roberts, F. P. See Chikalla, T. D.
Roberts, H. H., and Graves, W. E. Thermoluminescence—a tool for the environmental analysis of recent sediment cores, (8) 205*f*.
Roberts, J. Family pottery, (2) 30*f*.
Roberts, J. R., and Roach, H. C. High-temp. insulation block, P (11) 272*d*.
Roberts, J. S. See Formigoni, N. P.
Roberts, J. T. Assemblies of semiconductor devices having mounting pillars as circuit connections, P (10) 249*g*.
Roberts, J. T. A. Nature of the activation volstress dependence in the high-temp. plasticity of UO_2, (5) 114*i*.
Roberts, J. T. A., and Ueda, Y. Influence of porosity on deformation and fracture of UO_2, (4) 91*g*.
Roberts, L. B. See Lipp, G. D.
Roberts, R. W. See Huggins, R. A.; Morgan, P. E.
Roberts, S. See Slack, G. A.
Roberts, W., and Marshall, K. Glaze-body reactions—electrochemical studies, (1) 10*a*.
Robertson, B., and Kostiner, E. Crystal structure and Moessbauer effect investigation of $FeVO_4$, (8) 208*i*.
Robertson, D. D., and Wheeler, W. R. High-vacuum gettering pump, P (9) 219*f*.
Robertson, D. S. See Hobden, M. V.
Robertson, J. M. Surface treatment of porous bodies, P (1) 10*h*. See Owen, A. E.
Robertson, L. F. See Johnson, A. L.
Robijn, P. Simple methods for detecting crystalline plasticity of periclase grains in basic bricks, (1) 18*h*.
Robijn, P., and de Keyser, W. L. Changes in basic checker bricks of glass furnaces due to the heavy elements of fuel, (1) 6*f*.
Robinder, R. C., Rowe, W. A., and Schwartz, J. W. Process of mfg. screens for shadow-mask tubes, P (10) 245*c*.
Robinson, A. S. Control system for modifying the surface of float glass, P (1) 5*c*. Method for mfg. float glass, P (6) 133*j*. Mfg. of flat glass, P (11) 270*c*. See Lawrenson, J.; Loukes, D. G.
Robinson, A. S., and Lawrenson, J. Method and apparatus for modification of article surface characteristics in a float glass process, P (4) 82*a*. Mfg. of flat glass, P (7) 162*h*.
Robinson, A. S., Loukes, D. G., and Lawrenson, J. Process and apparatus for surface modification of glass, P (1) 5*b*.
Robinson, C. C., and Snitzer, E. Photochromic glass, P (9) 219*g*.
Robinson, D. P. Methods of mfg. semiconductor devices, P (7) 169*d*.
Robinson, D. P., Beale, J. R. A., Shannon, J. M., Kerr, J. A., and Das, M. B. Method of making semiconductor devices [IGFETS], P (7) 169*a*.
Robinson, H. J. See Chase, E. W.
Robinson, K. B. See Stanyon, H. E.
Robinson, K. B., and Fenn, H. A. W-halogen lamps, P (3) 59*j*.
Robinson, M., and Cripe, D. M. Method for preparing high-quality rare earth and alkaline earth fluoride single crystals, P (6) 139*d*.
Robinson, P. Electrolytic device employing semiconductor oxide electrolyte, P (4) 87*e*. Some practical aspects of processing in the technical ceramic industry in Australia, (9) 239*h*.
Robinson, R. J. See Kun, Zoltan K.
Robinson, W. M. See Frank, J. N.
Robison, B. J. See Jackson, W. H.
Robredo, J. See Dusollier, G.
Robredo, J., Calvo, M. L., and Dusollier, G. Mechanism of formation of microhardness impressions in glass, (7) 159*i*. Tests on microhardness of glass, (4) 81*d*.
Robson, D. See Harker, H.
Robson, F. G. See Pearne, F. J.
Robson, H. E. Process for preparing a synthetic crystalline zeolite, P (10) 257*d*.
Rocher, G. Nozzle for a pouring ladle, P (7) 164*a*.
Rocher, G., and Orban, N. Hot tops, P (10) 247*i*.
Rochester, C. H. See Parfitt, G. D.
Rochus, W. See Ziechmann, W.
Rockstad, H. K. Hopping conduction and optical properties of amorphous chalcogenide films, (6) 136*f*.
Rode, J. A., and Hubert, P. W. Carrier for U oxide pellets, P (4) 91*f*.
Rodgers, C. H. See Gately, T. J.
Rodgers, R. B. See Lepper, H. A., Jr.
Rodgers, W. See Olmsted, L. E.
Rodgol'ts, Yu. S. See Borisov, V. G.
Rodlte, R. R. R. See Elmgren, J. A.
Roe, G. D. See Youngman, C. A.
Roe, J. L. See Bentley, G. I.
Roeder, M. See Vogler, M.
Roeder, P. J. See Hoogendoorn, H. M.
Roehrig, F. K., and Wright, T. R. Carbide synthesis by freeze-drying, (2) 47*e*.
Roelandt, B. See Berton, J. F.
Roenkov, N. D. See Borshchevskii, A. S.
Roest, E., and Haugsten, K. Crystal structure of $Ni_{0.85}Se_2$, (11) 280*g*.
Rogachev, D. L. See Roi, V. A.
Rogers, B. C., and Wakely, W. T. Diaphragm-connected leadless package for semiconductor devices, P (3) 64*f*.
Rogers, E. S. See Sanford, R. A.
Rogers, F. O. See Gates, D. W.
Rogers, L. C., Nikirk, R. G., and Heitz, A. J. Method [etching] for producing high-purity monocrystalline Si, P (10) 251*j*.
Rogozhin, Yu. V., Zaionts, L. A., and Eremeeva, A. S. Dependence of chemical stability of sitalls on heat treatment conditions, (9) 216*f*.
Rohde, T. L. Method of sealing reed switches using ir energy, P (8) 193*f*.
Roi, V. A., Ignat'ev, O. S., and Rogachev, D. L. Solid phases in the system Na_2O-CaO-Al_2O_3-SiO_2-H_2O at 300°C, (8) 210*c*.
Roisko, T. O. See Lepomaa, L. A.
Rokhvarger, E. L., and Pavlov, V. F. Advantages of slip method of preparing press powders in floor tile production, (8) 197*d*.
Rokitansky, K., and Solt, G. Rotary filtering device and process of operating, P (3) 69*g*.
Roland, G. W. See Hopkins, R. H.; Melamed, N. T.
Roland, G. W., Hopkins, R. H., and Melamed, N. T. Oxyapatite laser materials, P (4) 89*h*.
Rolin, M. Density of mixtures based on melted cryolite—systems NaF-AlF_3, AlF_3Na_3-Al_2O_3, and AlF_3Na_3-CaF_2, (6) 146*h*. See Desclaux, P.; Mesrobian, G.
Romaniec, E. See Kedzior, A.
Romanova, N. V. See Nemilov, S. V.
Romashov, V. M. See Portnoi, K. I.
Rombaux, J. P. M. See Van Impe, J.
Romberg, H. Effect of the type of cement on the pore size distribution in hardened cement mixes, (1) 2*d*.
Rome, M. See Fleck, H. G.
Romig, J. R. Cement raw mix control apparatus and programing, P (1) 2*d*.
Roney, R. N. See Giardini, D. S.
Ronning, R. L. Method and apparatus for enhancing the separation of particulate material from effluent stream, P (6) 141*f*.
Ronzio, A. R., and Pull, B. T. Composition for eliminating efflorescence in portland cement products, P (6) 130*d*.
Rooksby, H. P. See Creer, M. H.
Roos, J., and Boone, S. Electroacoustic transducer having a diaphragm made of at least one layer of piezoelectric material, P (11) 274*g*.
Root, R. L., and Eilers, L. H. Alum-containing aluminous cements, P (3) 54*c*.
Rooymans, C. J. M. Chemical reactions and reactivity under high pressure, (4) 95*j*.
Ropp, R. C. Method of preparing rare earth metal phosphate-vanadate luminescent compositions having acicular crystal habit, P (8) 201*g*. Process for coating lehring-sensitive phosphor onto lamp envelope, P (10) 245*c*.
Ropp, R. C., and Oakley, R. Method of preparing rare earth metal orthovanadate phosphor, P (4) 89*h*.
Roques, R. A., and Gray, F. L. Use of vapor phase deposition to make fused SiO_2 articles having TiO_2 in the surface layer, P (6) 140*c*.
Rosback, D. H. Method for preparing Cu-exchanged type X zeolite, P (6) 144*c*. Method for preparing Cu-exchanged type Y zeolite, P (6) 144*c*.
Roscher, A. M. Mfg. of elastomer-coated glass fibers, P (3) 58*g*.
Rose, D. J. See Schuck, J. F.
Rose, E. T., and Pezzanite, L. V. Structural carbonaceous materials having improved surface erosion characteristics, P (5) 110*a*.
Rose, J. A. Means for supporting core in open-ended shell mold, P (8) 196*d*.
Rose, J. W. Masking to prevent autodoping of epitaxial deposits, P (8) 201*d*.
Rose, P. G. Method of mfg. C fiber, P (8) 196*g*.
Rose, S. H. See Wainer, E.
Rosen, A. See Assour, J. M.
Rosen, E., and Tegman, R. Preparative and X-ray powder diffraction study of the polysulfides Na_2S_2, Na_2S_4, and Na_2S_5, (11) 282*i*.
Rosenbauer, C. H. Mfg. of multifocal ophthalmic lens molds, P (6) 133*f*.
Rosenbaum, R. L., Chau, Cheuk-Kin, and Klein, M. V. Thermal conductivity of alkali halide crystals containing the hydroxide ion, (6) 152*b*.
Rosenberg, M. See Tanasoiu, C.
Rosenberg, P. E. Compositional variations in synthetic topaz, (9) 233*j*.
Rosenberg, R., and Ohring, M. Void formation and growth during electromigration in thin films, (7) 168*f*.
Rosenberg, R. B. See Kweller, E. R.
Rosenberger, R. D. Method of making a grid layout for printed circuitry, P (2) 41*f*.
Rosenblatt, G. See Lynch, G. F.; Sayer, M.
Rosencwaig, A. Domain-wall energies in ortho-

ferrites, (7) 177*e*. Double exchange and the metal-nonmetal transition in magnetite, (5) 120*a*.
Rosengarten, H. J. See Kamphues, H.
Rosenheinrich, R. See Raithel, K.
Rosenqvist, T., and Tunkesvik, K. Thermodynamics of Si sulfides and ZnS, (4) 99*h*.
Rosenthal, J., Riley, R. F., and Ranon, U. EPR of Gd^{3+} in zircon structures (II) YVO_4, YPO_4, $YAsO_4$, (5) 120*i*.
Rosenthal, K. See Reh, L.
Rosenzweig, W. See Logan, R. A.
Roshchupkin, V. I. Determination of equilibrium conditions of heat treatment of Mn ferrite in controlled gas medium, (9) 234*i*.
Rosiaux, E. See Borgne, R.
Rosinski, E. J. Explosive fragmentation of porous solids [zeolites], P (3) 71*i*.
Roskovec, V. See Sestak, J.
Rosolowski, J. H. See Carter, R. E.; Nadeau, J. S.
Ross, C. W. Feed rate control in a cement kiln incorporating dust return, P (4) 79*g*.
Ross, D. P. See Craik, D. J.
Ross, J. Fluid energy steam mill collection system, P (3) 69*g*.
Ross, M. Semiconductor pumped laser [YAG], P (3) 67*g*.
Ross, S. E. See Moore, D. R.
Ross, S. See Morris, H. H.
Ross, S. E. Process for producing carbonized fibrous products, P (8) 196*i*.
Ross, W. T. See Lass, J. L.
Rosser, D. B. See Livezey, J. P.
Rossi, E. F. Gas delivery manifold and processed material discharge assembly for rotary kiln, P (8) 206*c*.
Rossi, L. See Pizzini, S.
Rossi, R. C., Cost, J. R., and Janowski, K. R. Influence of the shape of dispersed particles on the elastic behavior of composite materials, (6) 148*j*.
Rossmann, P. F. Apparatus and method for pressurizing materials, P (4) 77*f*.
Rostoker, D. See Cowan, J. H., Jr
Roth, H. See Rindner, W.
Roth, H. A. See Scola, D. A.
Roth, J. See Pollak, I.
Roth, R. S., and Schneider, S. J., Jr. (editors) Solid State Chemistry, B (10) 264*c*.
Roth, W. L. Stoichiometry and structure of the super ionic conductor Ag β-Al_2O_3, (8) 210*i*. See Rice, M. J.
Rothe, M. v. E. See Reisner, W.
Rothenberg, P. Combining enameled Cu and wood, (2) 30*c*. Enameled stones, (2) 30*f*. Found objects as stencils, (2) 30*g*. Mary Sharp, (4) 77*j*. Mary Sharp demonstrates cloisonne techniques, (2) 30*b*.
Rothermel, D. L., and Stookey, S. D. Dealkalization of glass surfaces, P (7) 161*b*.
Rothwell, E., and Teo, T. K. Preparation of electrically conducting films by impregnating porous ceramics, (2) 38*e*.
Rothwell, R., and Branwood, A. Domain configurations in PZT ceramic, (9) 223*i*.
Rotoloni, P. L. See Calza Bini, A.
Rotter, H. W. Stretchable creped mica foil and method therefor, P (8) 202*f*.
Rottmann, H. R. See Moreau, W. M.
Rouanet, A. Study of the systems Zr-lanthanide oxides close to the mp, (6) 152*d*.
Rouanet, A., Coutures, J., and Foex, M. High temp. phase diagram study of the La(III) oxide-Yb(III) oxide system, (10) 259*a*.
Rouf, M. A., Cooper, A. R., and Bell, H. B. Study of phase equilibria in the system CaO-MgO-TiO_2, (1) 25*c*.
Roulot, M. See Milochevitch, A.
Rousseau, D. L. See Arguello, C. A.
Rousselet, C. Pressure filtration or centrifugal filtration, (4) 92*f*.
Routschka, G. See Konopicky, K.; Majdic, A.
Rouweler, G. C. J., and Overbeek, J. T. G. Dispersion forces between fused SiO_2 objects at distances between 25 and 350 nm, (2) 47*a*.
Rowan, K. See Ellis, B.
Rowden, E. Acid corrosion and smut emission by kiln exhaust gases, (1) 19*a*.
Rowe, D. M. Graphical method for estimating phonon- and impurity-scattering contributions in heavily doped semiconductors, (7) 167*c*.
Rowe, W. A. See Robinder, R. C.
Rowse, R. A., and Nelson, R. S. Thermoset-resin-impregnated high-speed vitreous grinding wheel, P (2) 29*j*.
Roy, D. M. See DiSalvo, R.
Roy, D. M., Gouda, G. R., and Bobrowsky, A. Very high strength cement pastes prepared by hot-pressing and other high pressure techniques, (8) 188*a*.
Roy, H. Particle size distribution and surface area of some ceramic clays in finer size range, (11) 281*i*.
Roy, N. N., and Halsey, G. D., Jr. Structure relaxation at liquid-solid interfaces, (7) 181*f*.
Roy, R. See McCarthy, G. J.; Nicol, A. W.; Porter, V. R.; Strickler, D. W.; Takamori, Takeshi; Wood, C.
Roy, R., and Frusbour, R. H. Reexamination of the quartz-coesite transition in anvil apparatus, (1) 18*e*.
Roy, S. B., and Chakravorty, S. K. Li in ceramics—a review, (11) 279*f*.
Roy, S. K. See Sinha, B. C.
Roy, Salil K. Measurement of pore size and porosity, P (11) 278*i*.
Royce, M. R. Phosphor screen comprising 2 kinds of particles, each having phosphor core and phosphor coating, P (3) 66*f*. Visible-emitting Ce-activated Ca Al oxide phosphor, P (8) 203*a*.
Royce, M. R., and Martin, J. S., Jr. Very short luminescent decay-time phosphor, P (3) 68*a*.
Royer, B. R. See Corson, B. L.
Royer, D. J. See Hritz, G. G.
Royse, C. F., Jr., Wadell, J. S., and Petersen, L. E. X-ray determination of calcite-dolomite—an evaluation, (1) 26*c*.
Rozanov, I. A. See Berul, S. I.
Rozhanskii, A. I. See Mazaeva, O. L.
Rozlovskii, A. A. See Buldakov, A. A.
Rubel, P. A. See Hebert, R. A.
Rubin, A. G. Method of producing concentrated phosphoric acid compounds from phosphate rock, P (4) 94*b*.
Rubins, R. S. See Mueller, K. A.
Rubinstein, A. M. See Shikunov, B. I.
Rubisch, O. See Ernst, H.
Rublack, W. D. In-line plural-beam CRT with an aspherical aperture mask, P (4) 88*f*.
Ruckensteiner, K. See Stich, H.
Rudd, M. J. Measurement of particle sizes, P (10) 256*a*.
Ruddle, R. W., and Yendrek, M. R. Exothermic hot tops, P (3) 61*d*.
Rudin, W. See Brungraber, L. E.
Rue, C. V. [Bossed] abrasive cutting wheels, P (4) 77*f*. Method for the production of bonded abrasive disk wheels, P (3) 53*i*.
Rueb, F. Burners for ceramic kilns, (10) 256*c*. Cloth filters for stringent requirements in dust extraction plants, (5) 115*d*.
Ruediger, K. See Herrman, R.
Ruegg, H. W. Semiconductor device having a lateral transistor, P (9) 227*e*.
Ruehle, M. See Borgstedt, H. U.
Ruettiger, K., Zahs, G., and Stolte, G. Behavior of refractories in DH vacuum vessels, (5) 108*h*.
Rugg, J. M. Complementary MOS gate protection diode, P (9) 224*j*.
Ruggiero, E. M. Technique for depositing SiO_2 from silane and O, P (1) 15*a*. See Morris, M. L., Jr.
Ruh, R. See Rankin, D. T.
Ruhe, R. W., Jr. See Krynock, R. A.
Ruini, G. Use of nonshaped refractory materials in ceramics, (4) 84*d*.
Rumyantsev, V. N., and Rumyantseva, G. V. Solubility of slightly soluble compounds in H_2O at high pressures and temps., (5) 124*a*.
Rumyantseva, G. V. See Rumyantsev, V. N.
Rundell, C. A. See McDaniel, C. V.
Rundqvist, S. See Carlsson, B.
Rupert, G. N. See Benz, R.
Rupert, R. E., and Anderson, N. C. Thin-film planar resistor, P (6) 133*i*.
Rupprecht, C. F., and Wiker, F. Glass handling and cutting system, P (9) 219*c*.
Rupprecht, D., and Ott, D. B. BN as a diffusion source, (11) 273*e*.
Rushby, A. N. See Edwards, G. S.
Russ, M. J. Liquid encapsulated Czochralski growth of GaAs and GaP, (11) 273*i*.
Russell, E. A. Connection [brazing] of metals to ceramics, P (4) 85*j*.
Russell, J. D. See Farmer, V. C.
Russell, J. H., Paige, J. I., and Paulson, D. L. Evaluation of some solid oxides as sorbents of SO_2, (6) 143*a*.
Russell, L. K. See Kleitman, D.
Russell, R., Jr. See Bailey, J. T.; Griffiths, C. R.
Russell, R. G. Apparatus having rotating bushing for forming fibers, P (4) 81*j*. Method and apparatus for producing filaments by centrifugal forces, P (6) 133*i*. Method of coating glass fibers, P (10) 244*j*.
Russell, R. S. See Ashton, W. H.
Russell-Rayner, A. P. See Branch, G. H.
Russo, A. J. See Francis, F. J.
Russo, M. E. See Bertsch, H. C.
Russo, R. J. See Benedict, R. P.
Rustan, B. Process for the preparation of fiber-containing plaster products, P (11) 267*c*.
Ruszczyk, J. F., and Secrist, D. R. Air bearing magnetic head with glass slider body, P (9) 224*h*. Method of mfg. ferrite recording heads with a multipurpose devitrifiable glass, P (10) 245*c*.
Ruthardt, K. See Reichelt, W.
Rutherford, D. Poets, prophets, and potters, (4) 78*a*.
Rutherford, W. H. See Peters, E. R.
Rutledge, J. L. See Saltich, J. L.
Rutman, D. S. See Flyagin, V. G.
Rutman, D. S., Maurin, A. F., Taksis, G. A., and Toropov, Yu. S. Relation between the electrical resistance of zircon ceramics and porosity, (8) 199*i*.
Rutt, T. C. Ceramic capacitors, P (10) 249*j*.
Ruud, C. O. See Barrett, C. S.; Heinrich, K. F. J.
Ruzicka, A. See Minar, S.
Ruzicka, J. Ultradisintegration and agglomeration of minerals such as mica, products therefrom, and apparatus therefor, P (2) 46*i*.
Ruzicka, V. See Kolomaznik, K.
Ryabov, V. A. See Aleshin, B. N.
Ryan, F. M. See Lehmann, W.
Ryan, F. W. See Schottmiller, J. C.
Ryan, J. H., Lukes, J. A., Neitzel, U. E. G., and Duyster, H. P. J. Method for the production of K sulfate from K-containing double salts of $MgSO_4$, P (4) 94*b*.
Ryan, R. J., Burtis, S. F., and Grogan, J. T. Process for forming a conductive coating on a substrate, P (11) 275*a*.
Ryan, W. Deflocculation of a blue ball clay (II) Na silicate and Na oxalate, (1) 9*h*. Ion exchange in clays (III-V), (1) 19*j*. Ion exchange in clays (VI), (4) 85*h*.
Ryan, W. H. Method and apparatus [laser] for measuring interferometer fringe patterns, P (6) 142*g*.
Ryantsev, V. D. See Likhoradov, A. P.
Ryba, J., Korab, O., and Jirku, J. Influence of P_2O_5 on portland cement clinker, (3) 53*j*.
Rybailo, O. I. See Belotskii, D. P.
Rybakov, V. K. See Pokrovskii, A. N.
Ryden, W. D., and Lawson, A. W. Magnetic susceptibility of IrO_2 and RuO_2, (6) 150*c*.
Ryder, R. J. See Harding, F. L.
Ryklis, E. A., Bolgar, A. S., and Fesenko, V. V. Vaporization rate and thermodynamic properties of TiN, (10) 261*g*.
Rymas, F. Cemented carbide composition [WC-Co] and method of preparation, P (10) 247*e*.
Rynowiecki, K. Audible signal having glass reed relay, P (2) 39*b*.
Ryss, Yu. S., Bakhtin, Yu. G., Panteleimonov, V. M., and Alexeev, A. I. Device for determining the mineral composition, size, and location of ore deposits, P (8) 207*d*.
Rytter, E. See Oeye, H. A.
Rzucidlo, A. G. See Ueltz, H. F. G.

Saada, M. Y., and Mobarak, A. Fiber formation from a melt by centrifugation, (4) 80*i*.
Saalfeld, H. Stabilization of verneuil boules consisting of Ca_2SiO_4 by $Ca_3(PO_4)_2$ and V_2O_5, (6) 132*h*.
Sabaski, R. E. End liner assembly for rotary mill, P (1) 20*c*. Trunnion liner assembly for rotary grinding mill, P (1) 20*j*.
Sabirov, I. M. See Akhunov, A. M.
Sacadura, J. F. O. Thermal radiation characteristics of dielectric materials, (6) 134*j*.
Sacerdote, R. See Sironi, G.
Sach, R. S., and Bromley, J. Oxidative heat treatment of C fibers, P (5) 110*a*.
Sachs, M. J. See Heaton, R. A.
Sack, E. A. Semiconductor integrated circuit with isolated elements and power transistor utilizing substrate for low collector resistance, P (3) 67*f*.
Sack, W. Sealing glass having high absorption of ir radiation, P (10) 245*f*.
Sack, W., and Scheidler, H. Glass batches for the production of transparent glass-ceramics containing solid solutions of β-eucryptite, P (3) 58*e*.
Sadagopan, V. Preparation of single-crystal films of Li niobate by rf sputtering, P (6) 139*d*. See Horwath, R. S.
Sadkov, V. I. See Chistyakova, A. A.
Sadler, A. G. See Bateson, S.; Westwood, W. D.
Sadran, G. H. Aluminous cement Ca_3SiO_5 binders, P (6) 130*c*. See Stiglitz, P.
Sadran, G. H., and Assaud, L. M. Highly refractory aluminous cement and process for mfg., P (3) 54*a*.
Safonov, V. V., Konov, A. V., and Korshunov, B. G. Phase diagrams of $TeCl_4$-$TiCl_4$ and $TeCl_4$-$SbCl_5$, (8) 209*j*. Reactions of $TeCl_4$ with the chlorides of the alkali metals and ammonium, (8) 210*a*.
Sagawa, Yoshihisa. See Maekawa, Hideyuki.
Sagiya, Ippei. See Tomita, Kinzo.
Sagmuller, J. R., and Hunter, R. I. Slip casting [cermets], P (10) 248*d*.
Saha, P. Elastic properties of dislocations, (11) 281*g*. Geometry of dislocations, (11) 281*j*.
Sahni, R. J. Process of producing an array of integrated circuits on semiconductor substrate, P (2) 42*d*. See Agusta, B.
St. Clair, H. W., and Brown, Raymond E. Experimental study of particle size and size distribution of minerals crushed by impact, (7) 172*c*.
St-Jacques, R. G., and Chaklader, A. C. D. Creep and shrinkage of compacts of colloidal boehmite during dehydroxylation, (11) 280*j*.
St. John, D. F. Pneumatic doctoring of solid ink particles from intaglio plate, P (4) 82*h*.
Saito, Akira. See Yamane, Mikiya.
Saito, Hajime. See Doi, Haruo; Takashima, Hiroo; Takusagawa, Nobuo; Ushio, Masumi.
Saito, Hajime, Doi, H., Yamai, I., and Matsushita, T. Studies on precipitated crystals from glasses of the system Li_2O-MgO-CaO-Al_2O_3-SiO_2-F, (3) 57*i*.
Saito, Hajime, Ushio, M., and Nagao, S. Synthesis of cubic BN, (2) 36*h*.
Saito, Hajime, and Yamai, I. Synthesis of chrysotile (IV) synthesis of chrysotile with addition of alkali halides, especially K and Mg bromides under hydrothermal conditions, (1) 25*e*; (VI) synthesis of chrysotile fibers with the addition of Mg iodide by a hydrothermal-dehydration process; (VII) effect of Fe ions on the formation of chrysotile by the hydrothermal-dehydration process, (1) 25*f*.
Saito, Hajime, Yamai, I., and Kato, N. Synthesis of chrysotile (V) conditions of synthesis of chrysotile fibers by the hydrothermal-dehydration process, (1) 25*f*.
Saito, Hajime, Yamai, I., and Ono, K. Synthesis of chrysotile (III) synthesis of chrysotile containing OH or F in alkaline solutions under high pressure and at high temp., (1) 25*e*.
Saito, Kazuya. See Nakano, Mitsuko.

Saito, Mitsuru. See Hasaba, Shigemasa.
Saito, Muneki. See Suzukawa, Yuichi.
Saito, Shinroku. See Okikawa, Shinji; Suzuki, Takeyuki; Watanabe, Tetsuo.
Saito, Shogo. See Arai, Kazuo; Kadota, Kazuya.
Saito, Shuntaro, Mitsui, Y., and Ieda, B. Comparative test results on metal wire and welded metal net as reinforcing metals for furnace lining by dry cold-gunning method, (7) 163*g*.
Saito, Takeshi, and Hasegawa, F. GaAs semiconductor device, P (2) 40*h*.
Saito, Tetsuo. See Tanaka, Eihachiro.
Saito, Tsutomu. See Ikeda, Takuro.
Saito, Turuyoshi, Hitotsuya, K., Fujiyama, T., and Nakakuki, Y. Properties of H_2O-permeability, abrasion resistance, and freezing and thawing of vacuum concrete mixed with shrinkage-reducing material containing gypsum anhydrite, (6) 130*a*.
Saito, Turuyoshi, Hitotsuya, K., Noro, M., Ishikawa, I., and Watanuki, T. Properties of strength and shrinkage of vacuum concrete mixed with shrinkage-reducing admixture containing gypsum anhydrite, (6) 130*a*.
Saitou, Masashi, Yanagi, M., and Hirai, M. Properties of cement, consisting of alite, Casulfoaluminate, and Ca sulfate, (4) 79*i*.
Sakaguchi, Masakazu, Hirabayashi, T., and Oguro, K. Role of firing atm during ZnS phosphor preparation (VI) effect of firing atms on the diffusion of sulfide ion in ZnS crystals, (7) 180*h*.
Sakaguchi, Mitsuhito. See Uchida, Teiji.
Sakai, Kaname, and Masaki, A. High-frequency integrated-circuit device providing impedance matching through its external leads, P (4) 88*e*.
Sakai, Kenji. See Okada, Kiyoshi.
Sakai, Kunio. See Tohi, Atsutomo.
Sakai, Masao. See Banno, Hisao.
Sakai, Takeshi. See Kito, Masao.
Sakai, Tetsushi. See Watanabe, Yoshio.
Sakaino, Teruo. See Kadota, Kazuya.
Sakakura, Mitsuo. See Yamaguchi, Akira.
Sakamoto, Chiaki. See Setoguchi, Masahiro.
Sakamoto, Hitoshi. See Hitomi, Teiichi.
Sakamoto, Kazuyoshi. See Tamura, Takaaki.
Sakamoto, Makoto. Method for sealing [metal cap] a semiconductor element, P (2) 41*b*.
Sakamoto, Sadao. See Yazaki, Takehito.
Sakamoto, Teruo. See Maekawa, Hideyuki.
Sakamura, Hiroyasu. See Suzuki, Suguru.
Sakata, H., and Okano, K. Effect of electrolytes on the efficiency of the polishing of glass, (7) 159*d*.
Sakata, Kenji. See Okada, Kiyoshi.
Sakata, Makoto. See Terada, Michiko.
Sakharov, G. P. See Budnikov, P. P.
Sakka, Sumio. Discussion of "X-ray radial distribution function of high-Al_2O_3 glass," (5) 105*j*. Phototropic glass-ceramic articles containing Bi-doped Ca tungstate crystals, P (1) 5*a*. See Yamamoto, Tokuji.
Sakka, Sumio, and Mackenzie, J. D. High pressure effects on glass, (3) 56*j*. Phototropic articles containing thallous halide, P (2) 35*a*.
Sakoda, Hiroshi. See Uchida, Shinichi.
Sakurai, Katsumi, Johnson, S. E., and Broida, H. P. Laser-induced fluorescence of BaO, (5) 121*g*.
Sakurai, Takemaro. See Kamada, Osamu.
Sakurai, Takeshi, and Tani, Z. Method of making a *pn* junction device, P (10) 251*h*.
Sakurai, Yasunobu, Sato, H., Shimizu, M., and Inoue, K. Supporting means for piezoelectric transformers, P (8) 202*f*.
Sakurai, Yo, Tamura, T., and Hashimoto, N. Process for producing magnetic head, P (8) 202*e*.
Salama, C. A. T. Rf sputtered Al_2O_3 films on Si, (9) 224*e*.
Salares, R. See Lorbach, H.
Salee, J. E. See Bazinet, W. P., Jr.
Saldick, J. Production of NiF_2, P (1) 20*i*.
Saleh, N., and Qureshi, A. H. Conductivity tensor and Hall effect in magnetic semiconductors, (6) 145*c*.
Salge, H. Investigation of the structure of nonmetallic inorganic material using a new electronic apparatus, (9) 231*f*.
Salge, H., Lehmann, H., and Hennicke, H. W. Electron probe microanalysis of inorganic nonmetallic raw materials, (2) 44*h*.
Salinger, R. M. Preparation of SiC from methylchlorosilanes in a plasma torch, (10) 247*c*.
Salman, S. M. A. See Omar, A. A.
Salt, D. L. See Holmes, W. H.
Saltich, J. L., and Rutledge, J. L. Hot carrier *pn* diode, P (9) 225*d*.
Salva, W. J. See Johnson, J. W.
Salvador, P. S. See Rausell-Colom, J. A.
Salvan, F. See Benoit a la Guillaume, C.
Samara, G. A. See Beattie, A. G.
Samara, G. A., and Giardini, A. A. Effect of pressure on the Néel temp. of magnetite, (6) 146*i*.
Sambell, R. A. J. See Bowen, D. H.
Samdani, S. G., Chary, M. N., and Ali, Abde. Studies on densification behavior and phase changes in TiO_2-ZrO_2 and TiO_2-Al_2O_3 composites fired under oxidizing and reducing atms, (11) 282*i*.
Samouel, M. Crystallization equilibria in 11 binary systems of simple fluorides. Synthesis in the solid state and crystallographic identification of the double fluorides discovered, (6) 146*e*. See de Kozak, A.
Samsonov, G. V. (editor). Chemical Properties and Analysis of Refractory Compounds, B (10) 262*e*. Protective Coatings on Metals (Vol. 3), B (4) 100*h*. See Fomenko, V. S.; Lapshov, Yu. K.
Samsonov, G. V., and Bozhko, S. A. Recrystallization during the sintering of Nb and Ti carbide powders, (10) 260*e*.
Samsonov, G. V., and Grebenkina, V. G. Temp. coeff. of electroresistance of some high-melting compounds, (10) 261*b*.
Samsonov, G. V., and Kondratov, I. Ya. Cermet alloys of Re with Y hexaboride, (10) 246*f*.
Samsonov, G. V., Koval'chenko, M. S., and Tkachenko, Yu. G. Investigation into the external friction of Nb and Ta carbides at high temps. in vacuum, (10) 259*d*.
Samsonov, G. V., Plyushch, G. V., and Pryadka, G. A. Rheological properties of hard-alloy mixtures plasticized with paraffin, (10) 247*h*.
Samsonov, G. V., Podchernyaeva, I. A., and Fomenko, V. S. Emission coeffs. of high-melting compounds, (3) 73*a*.
Samsonov, G. V., Timofeeva, I. I., and Klochkov, L. A. Substructure of deformed carbides of the transition metals in their homogeneity regions, (10) 261*a*.
Samsonov, G. V., and Upadkhaya, G. Sh. Physical properties of the monocarbides of the transition metals in their homogeneity regions (I) TiC_{1-x} and NbC_{1-x}, (3) 74*f*.
Sanami, Tetsuo. See Iwabuchi, Toshitsugu.
Sanbongi, Koji. See Aratani, Fukuo.
Sanborn, W. E. See Lindsley, J. F.
Sanchez, M. G. See Triggiani, L. V.
Sandbank, C. P. Solid-state scanning by detecting the relief profile of a semiconductor body, P (8) 202*d*.
Sandera, J. Glass-coated semiconductor, P (4) 88*a*.
Sanders, D. See Wortman, D. E.
Sanders, R. N., and Johnston, J. D. Minerals separation process, P (9) 233*c*.
Sandhu, J. S. See Dhaka, V. A.; Reuter, J. L.
Sandin, T. R., and Keesom, P. H. Specific heat and paramagnetic susceptibility of stoichiometric and reduced rutile (TiO_2) from 0.3°–20°K, (5) 124*b*.
Sands, A. E. Method for increasing the strength of C foam, P (4) 84*e*.
Sandstrom, D. B., and Sawyer, D. E. Fabrication of single-crystal film semiconductor devices, P (3) 64*j*.
Sandvoss, W. E. See Bruce, H. W.
Sanford, R. A., Mool, J., and Rogers, E. S. Extruded Al_2O_3 catalyst support and the preparation thereof, P (10) 257*e*.
Sangster, F. L., and Nienhuis, R. J. IGFET with opposite-type gate connected region inset in source or drain, P (3) 65*e*.
Sangwal, K. See Patel, A. R.
Sano, Hisumi. See Morita, Tadahisa; Tokuyama, Takashi.
Sano, Nobuo. See Hiraoka, Teruyoshi.
Sano, Yoichi. See Sato, Chosei.
Sanogawa, Tatsuru. See Somiya, Shigeyuki.
Sansom, K. G. See Neumann, B. S.
Sansom, K. G., and White, D. Aggregation and dispersion in clays with particular reference to the montmorillonites, (2) 37*i*.
Santini, A. See Kemeny, G.
Santry, G. J., and Wacenske, H. R. Gripping and sealing system for slab facing materials, P (10) 244*d*.
Sanzharov, A. S. See Bergman, A. G.
Sanzharov, A. S., and Bergman, A. G. System $K\|CO_3,SO_4,CrO_4$, (8) 211*g*.
Saparov, V. V. See Juzvuk, D. I.
Sappenfield, K. M., Marinenko, G., and Hague, J. L. Standard reference materials—comparison of redox standards, (11) 278*b*.
Sara, R. V. Sn-C fiber composites, P (3) 61*f*.
Sardina, M. M. See Martinez, J. R.
Sarkar, A. K. See Mitra, N. K.
Sarkar, B. See Mukherjee, K. P.
Sarkar, B. K., and Glinn, T. G. J. Fatigue behavior of high-Al_2O_3 ceramics, (1) 22*i*.
Sarkar, B. K., and Towner, J. M. X-ray line broadening and electron microscopy study of the effects of milling and subsequent annealing of Al_2O_3 powders, (5) 125*g*.
Sarkar, S. K. See Cooper, A. R.
Sarno, C. V. See Donohue, J. M.
Sarvary, G. J. Mechanized palletized storage systems, P (3) 69*a*.
Sasaki, Hiromu. Chemical preparation of raw powders for electroceramics, (3) 62*h*. See Matsuoka, T.
Sasaki, Hiromu, and Matsuo, Y. Oxidation-reduction phenomena in the $PbTiO_3$-$La_{2/3}TiO_3$ system, (3) 63*a*.
Sasaki, Isao. See Takeishi, Yoshiyuki.
Sasaki, Kiyoshi, and Watanabe, S. Method of sealing display cathodes in a glass envelope, P (4) 82*f*.
Sasaki, Seiya. Method for producing MnO_2 containing less K, P (9) 233*a*.
Sasaki, Takeshi. See Takahashi, Kazusaburo.
Sasame, Takao. See Matsuno, Akira.
Sasamoto, Tadashi, and Sata, T. Vaporization of chromic oxide over Al_2O_3-Cr_2O_3 solid solutions (I), (11) 283*b*. Vaporization of $LaCrO_3$ at high temps. in vacuum, (6) 152*i*.
Sass, E. Microphotometric determination of preferred orientation in undeformed dolomites, (1) 23*b*.
Sasai, G. Air pollution in ceramic industries, (7) 182*c*.
Sasso, G. See Middelhoek, S.
Sata, Toshiyuki. See Nakamura, Tetsuro; Sasamoto, Tadashi; Yoshimura, Masahiro.
Sata, Toshiyuki, and Takahashi, Tatsuo. Measurement of the mp of Al_2O_3 by means of DTA, (5) 121*g*.
Sata, Toshiyuki, and Uchida, Y. Vaporization process of CaO from CaO-stabilized ZrO_2, (5) 109*d*.
Sata, Toshiyuki, and Urano, T. Reactions between refractory metals and insulating nitrides at high temps., (2) 49*f*.
Sata, Yoshio. See Fuwa, Yoshikazu.
Satarin, A. V. See Ved, E. I.
Satarin, V. I., Syrkin, Ya. M., Kryzhanovskaya, I. A., Dolzhkova, G. V., Ladygin, F. F., Kriptser, A. M., and Kalishchuk, G. I. Fast-setting slag portland cement with high sulfate resistance, (8) 186*c*.
Sato, Chosei, Furukawa, A., and Sano, Y. Method for removing impurities in the Bayer process, P (6) 144*e*.
Sato, Hideo. See Sakurai, Yasunobu.
Sato, Hiroshi. See Yamamoto, Zensaku.
Sato, Hisashi. See Yoshioka, Tsunehiko.
Sato, Hitoshi. See Iida, Shinya.
Sato, Katsuhiko. See Ishimitsu, Akitoshi.
Sato, Katsuo. See Irie, Toshiaki.
Sato, Kenji. See Ueda, Tadao.
Sato, Kenzo. S-shift curve characteristics of Si-O stretching band of amorphous SiO_2, (9) 238*e*.
Sato, Kogo, Kato, H., and Ohnishi, S. Method of forming the electrode of a semiconductor device, P (10) 251*d*.
Sato, Kozi. See Nagata, Minoru.
Sato, Kunio, Sugihara, K., Wakabayashi, T., and Ishida, T. Method for making molded C composition resistors, P (10) 251*f*.
Sato, Masao. See Akimoto, Yasumasa; Utsunomiya, Taizo.
Sato, Motoharu. See Murakami, Yoshio.
Sato, Shoichi. See Ishikawa, Yoshikazu.
Sato, Sumio. Review of crystal systems and crystallographic point groups, (1) 8*h*.
Sato, Susumu. See Yamamoto, Zensaku.
Sato, Tai. See Maeda, Hajime; Takeishi, Yoshiyuki.
Sato, Tai, Takeishi, Y., Okamoto, Y., and Hara, H. Complementary FET semiconductor device, P (1) 12*d*.
Sato, Takeshi, and Fukunaga, M. Lattice strain in $3CaO{\cdot}SiO_2$ solid solution, (9) 214*f*.
Sato, Tomi, and Matsumoto, K. Method for making semiconductor devices, P (4) 89*c*.
Satoh, Hidekichi. See Kurumada, Katsuhiko.
Satou, Minoru. See Akimoto, Yasumasa.
Satou, Sumio, and Tamura, T. Studies on the extracted ferrite phase—vitrification, (4) 79*e*.
Satou, Sumio, Tamura, T., Takahashi, Y., and Muto, H. Studies on the ferrite phase separated chemically from industrial cement clinkers, (9) 215*d*.
Sattler, G., and Weimann, K. Process for making a beveled cavity in a semiconductor element, P (4) 90*d*.
Sauar, T. O. Shroud for a fuel assembly in a nuclear reactor, P (8) 203*f*.
Saul, R. H., and Hackett, W. H., Jr. Distribution of impurities in Zn, O-doped GaP liquid phase epitaxy layers, (9) 234*e*.
Saull, R. C., Pointon, A. J., Nixon, D., and Batho, C. J. Kinetics of the formation of $CuFe_2O_4$, (7) 178*c*.
Saulnier, T. A. Photographic method for producing a CRT screen structure, P (3) 66*f*.
Sauman, Z. See Lach, V.
Sauman, Z., and Lach, V. Long-term carbonization of the phases $3CaO{\cdot}Al_2O_3{\cdot}6H_2O$ and $3CaO{\cdot}Al_2O_3{\cdot}SiO_2{\cdot}4H_2O$, (10) 242*a*.
Saurat, M., and Revcolevschi, A. Preparation by the floating zone method of refractory oxide monocrystals, in particular of Ga oxide, and study of some of their properties, (7) 179*e*.
Sausville, J. W. Precipitation method of preparing alkaline-earth metal fluorochlorophosphate phosphor, P (8) 202*c*. See McAllister, W. A.; Thornton, W. A.
Sauve, P. J. See Pither, L. F.
Savaete, B. See Duchateau, J.
Savage, H. K. See Arrowsmith, J.
Savchenko, E. P. See Godina, N. A.
Savchenko, L. T. See Chernov, R. V.
Savenkov, A. N. See Zaborovskii, V. I.
Savenkov, M. I. See Turchinova, L. N.
Savi, C., and Zamorani, E. Investigation in the Am oxide system, (1) 15*f*.
Savitskii, E. M., and Baron, V. V. (editors). Physics and Metallurgy of Superconductors, B (2) 51*i*.
Sawa, Goro. See Ieda, Masayuki.
Sawabini, C. T., Chilingar, G. V., and Allen, D. R. Design and operation of a triaxial, high-temp., high-pressure compaction apparatus, (3) 68*j*.
Sawamura, Yasumasa. See Ishimitsu, Akitoshi.
Sawano, Takahiro. See Suenaga, Masanobu.
Sawatari, T., and Kapany, N. S. Wave propagation along hollow dielectric wave guides, (8) 192*f*.
Sawatzky, E. See Kay, E.
Sawbridge, P. T., and Sykes, E. C. Dislocation glide in UO_2 single crystals at 1600°K, (6) 140*i*.
Sawchuk, L. G. See Garfinkel, H. M.
Sawyer, D. E. Semiconductor-ferroelectric memory device, P (3) 67*d*. See Sandstrom, D. B.
Saxman, R. L. See Corliss, D. S.

Sayce, I. G. Production of F or volatile F compounds using plasma jet anode, P (11) 280*b*. See Chilton, H. T. J.; Everest, D. A.
Sayer, M. See Lynch, G. F.
Sayer, M., Mansingh, A., Reyes, J. M., and Rosenblatt, G. Polaronic hopping conduction in V phosphate glasses, (5) 106*g*.
Sayles, C. P. See Muller, L. D.
Sazhin, V. S. See Bukhovets, V. G.; Shpigun, A. A.; Zapolsky, A. K.
Sazhin, V. S., Moshkina, M. K., Pankeeva, N. E., and Kolesnikova, I. A. Partial sections in the system Na_2O-CaO-SiO_2-H_2O, (6) 150*f*.
Scacciati, G. See Colombo, U.
Scace, R. I., and Slack, G. A. Semiconductor device with thermally conductive dielectric barrier [AlN], P (2) 42*a*.
Scaff, J. H. See Nesbitt, E. A.
Scaffidi, F. Upper liner for crushers, P (6) 144*h*.
Scalise, S. J. High-efficiency laser cavity, P (11) 270*b*.
Scanlon, G. T. See Pakutka, W. M.
Scardefield, J. E. See Foster, L. M.
Scarfe, F. Mixed melters, super boosters, (4) 80*g*.
Scarlett, R. M. High frequency transistor structure having an impedance transforming network incorporated on the semiconductor chip, P (9) 225*c*.
Schaake, H. F., and Hench, L. L. Polaronic effects in KV phosphate glasses, (6) 132*d*.
Schabert, H. P. Collecting device for cooling reactor core fragments in a fast breeder reactor, P (10) 253*j*.
Schachner, H., and Tannenberger, H. Vapor phase deposition of layers of Al_2O_3 on Al by hydrolysis of $AlCl_3$, (10) 249*b*.
Schade, J. See Wittmoser, A.
Schaedel, J. See Arndt, H. H.
Schaefer, D. L. Method of forming group III-V compound photoemitters having a high quantum efficiency and long wavelength response, P (10) 251*e*.
Schaefer, D. L., and Wilson, R. H. Method of forming a camera tube diode array target by masking and diffusion, P (9) 226*h*.
Schaefer, H. Semiconductor rectifying arrangement, P (10) 253*a*.
Schaefer, H., Stoermann, J., and Weber, R. A. Processes occurring during the wear of refractory linings in vacuum vessels of recirculatory type, (5) 109*c*.
Schaefer, P. C. See Lawrence, H.
Schaefer, S. C. Free energy of formation of In oxide by emf measurements, (2) 48*a*.
Schaetz, K. Cements and adhesives applied in ceramic technology, (2) 43*g*.
Schafer, R. J. See Guyer, V. L.
Schaffner, G. J., Jr. Method of making an abrasive belt, P (8) 185*f*.
Schafft, H. W. High reliability ceramic bender, P (3) 65*c*. Piezoelectric bender bilayer with flexible corrugated center vane, P (4) 89*j*.
Schagen, P. See Manley, B. W.
Scharf, K., and Mohr, R. K. Temp. dependence of photocurrents produced by X and γ rays in Si radiation detectors, (6) 137*b*.
Scharfetter, D. L. See Evans, W. J.; Hackett, W. H., Jr.
Schaschel, E. T. Reaction product of SiO and acetylenes, P (8) 198*h*. Reaction products of SiO and organic compounds having active H atoms and methods of making, P (8) 198*h*. Reaction products of SiO and organic halides, P (8) 198*h*.
Schat, B. R., and Engel, H. J. Calendering as a method of forming thin ceramic sheets, (9) 223*g*.
Schaumburg, G. Method for treating a hot-rolled metal body, P (6) 131*e*.
Schaun, W. E. Dental ceramic firing ovens, P (7) 174*j*.
Schawlow, A. L. See Stokowski, S. E.
Scheel, H. J., and Schulz-Dubois, E. O. Flux growth of large crystals by accelerated crucible-rotation technique, (7) 172*e*.
Scheidler, H. See Petzold, J.; Sack, W.
Schell, D. H. See Davidson, K. V.
Schellenberg, J. M. See Buck, D. C.
Schelleng, J. H., and Rado, G. T. Direct measurements of anisotropy energy and anisotropic magnetization in Ga Fe oxide, (5) 119*f*.
Schelly, Z. A. See Brandt, W. W.
Schelly, Z. A., and Eyring, E. M. Topics in chemical instrumentation (LX) step perturbation relaxation techniques, (4) 93*d*.
Schembs, W. Method of producing electronic planar-type devices applicable for hf Ge planar transistors, P (10) 252*a*.
Schempp, E., Peterson, G. E., and Carruthers, J. R. ^{93}Nb nuclear quadrupole resonance investigation of $LiNbO_3$, (7) 179*e*.
Scherenberg, H. O. [Self-cleaning] spark plug for internal combustion engines, P (10) 248*h*.
Scherer, H. Running of the HP 350 press, (7) 172*g*.
Schernthaner, M. See Truppe, M.
Scherzer, J., and Albers, E. W. Rare earth-H exchanged zeolites, P (10) 257*i*.
Schickel, A. Electrostatic separation method and apparatus, P (3) 69*e*.
Schickle, G. Controlled Gunn effect device, P (3) 64*d*.
Schickel, M., and Reder, H. Method for making a [gas discharge] tube, P (11) 270*e*.
Schildknecht, H., and Maas, K. Method for the transportation of crystals and melt, P (4) 89*e*.
Schile, R. D. See Basche, M.
Schiller, C. K. See Fisher, M. B.
Schiller, K. K. Strength of porous materials, (5) 104*c*.
Schilling, W., and Ott, W. Flashbulb with percussion ignition and preformed ignition tube, P (9) 218*j*.
Schilp, W. H., Jr. See Stoller, A. I.
Schimmelwitz, P. See Niesel, K.
Schimmer, R., and Gesing, H. Method of dividing semiconductor wafers, P (4) 88*g*.
Schink, N. See Haas, E.
Schinke, G. See Hack, P.
Schipke, F. Cement for nipple junctions of C electrodes, P (3) 61*c*.
Schipper, D. J., van Doorn, C. Z., and Bolwijn, P. T. Preparation of cathodochromic sodalites, (6) 151*e*.
Schirm, H. T., and Zeigler, R. O. Apparatus for feeding glass having multiple outlets, P (3) 57*f*.
Schlafli, H., and Gugger, G. Method for boring workpieces by laser pulses, P (1) 17*b*.
Schlapp, W. See Schmidt-Bruecken, H.
Schlegel, H. Dust removal with cloth filters, (5) 115*d*.
Schlein, W. S., and Wold, A. Preparation and properties of several In thiospinels, (10) 260*a*.
Schlesier, K. M. See Micheletti, F. B.
Schlesinger, M., and Whippey, P. W. Optical study of CaF_2:Ho^{2+}, (5) 122*a*.
Schlitt, W. J., and Healy, G. W. Kinetics of lime dissolution in CaO-FeO-SiO_2 slags, (1) 2*c*.
Schluderberg, D. C. Vapor suppressing means for a nuclear reactor, P (9) 229*b*.
Schlueter, K. See Widmann, D.
Schmalzried, H. See Borchardt, G.
Schmeckenbecher, A. F. See Kaiser, H. D.
Schmid, R. Ferromagnetic storage cores and process of making, P (5) 112*c*.
Schmidt, A. Process for the preparation of pure AlF_3, P (8) 207*d*.
Schmidt, B. H., Jr. Complementary MOS exclusive NOR gate, P (11) 274*e*. Complementary MOS exclusive OR gate, P (9) 224*j*.
Schmidt, G. E. See Plovnick, R. H.
Schmidt, H., Jr. Filter leaf core, P (3) 69*e*.
Schmidt, J. A. See Hipp, J. C.
Schmidt, J. G. Semiconductor doping compositions, P (8) 202*i*. Semiconductor [SiO_2-based] doping compositions, P (8) 202*a*. See Herzog, A. H.
Schmidt, J. G., and Lim, E. Method for fabricating monolithic light-emitting semiconductor diodes and arrays thereof, P (5) 113*f*.
Schmidt, L. B. See West, E. D.
Schmidt, P., and Hennemann, K. Method of producing welding flux, P (4) 80*a*.
Schmidt, P. F. See Nicollian, E. H.
Schmidt, P. H. See Bobeck, A. H.
Schmidt, V. H. See Field, J. E.
Schmidt, W., and Morkowski, J. Relaxation of magnons on dislocations in uniaxial ferromagnets, (6) 151*c*.
Schmidt, W. H. See Reh, L.
Schmidt-Bruecken, H., and Schlapp, W. New process for bonding metals to ceramics (I), (1) 11*d*; (II), (8) 199*c*.
Schmitt, C. R. Method for producing fibrous C structures, P (1) 9*d*.
Schmitt, C. R., and Schreyer, J. M. C composite structures and method for making, P (4) 84*h*.
Schmitz, A. Method of mfg. a [double-diffused] transistor and transistor manufactured by this method, P (1) 13*h*.
Schmitz, A., Mulder, C., and Slob, A. Semiconductor device with complementary transistors, P (3) 67*c*.
Schmitz, G. K. See Metcalfe, A. G.
Schnable, G. L. Depletion-type IGFET having high-conductivity *n*-type channel, P (3) 64*e*.
Schnaus, U. E., Marshall, A., and Moynihan, C. T. Heat capacities of glasses and liquids in the pseudobinary system $Ge_2As_{40-x}S_{60}$, (5) 106*b*.
Schneble, F. W., Jr. See Stahl, F. T.
Schneegans, M. New method for correction of matrix effects in X-ray fluorescence analysis (I) theoretical investigation, (7) 173*a*; (II) experimental investigation of a continuous background of X-ray fluorescence spectra; (III) application of the method to the determination of elements, (11) 278*a*. Use of glass in lasers, (7) 161*a*.
Schneider, D. See Doering, G.
Schneider, H. E., and Plankenhorn, W. J. Method and apparatus for melting vitreous-type materials, P (4) 93*j*.
Schneider, I. *F* centers in additively colored KCl:NaCl crystals, (5) 120*e*.
Schneider, J. See Beckmann, R.; Neidhardt, M.
Schneider, R. A. Transducer head with laminated pole tips for wide-band transducer system, P (8) 202*i*.
Schneider, S. J., Jr. See McDaniel, C. L.; Roth, R. S.
Schneider, S. J., Jr., and Rice, R. W. (editors). Science of Ceramic Machining and Surface Finishing, B (10) 264*j*.
Schneider, W. C. Method of making a lateral transistor, P (2) 41*f*.
Schneider, W. C., and Vedam, K. Piezo-optic properties of amorphous Se at a wavelength of 1.15 μm, (8) 191*b*.
Schneider-Arnoldi, A., Kampmann, F. W., Thiel, H. D., Kandler, J., and Gleisberg, D. Sand-lime brick and process for making, P (10) 248*c*.
Schneidermann, N. See Ginsberg, R. N.
Schnur, J. M. Compositions for sand core mold elements, P (5) 109*g*.
Schoen, J. M., and Denker, S. P. Band structure, physical properties, and stability of TiO by the augmented-plane-wave virtual-crystal approximation, (5) 118*j*.
Schoen, K. Conductivity cell for particle counting apparatus, P (9) 231*f*. Particle counting apparatus, P (2) 45*d*.
Schoen, O. W., Jr. Dew point condensate detector, (9) 231*a*.
Schoenlaub, R. A. Apparatus for thermal analysis, P (9) 231*e*.
Schoijett, H. N. See Laconich, R. L.
Scholl, R. F. See Bleha, W. P., Jr.
Schorr, A. J. Measurement of thermal conductivity of hard crystalline bodies, P (2) 45*a*.
Schorsch, H. Assigning tolerances to the finish-surface marks according to DIN 3140, (7) 158*c*.
Schott, C. E. See Shiple, T. J.
Schott, L. A. Apparatus for making foamed glass panels, P (4) 81*i*.
Schotten, A., and Heimbach, F. Filter element for upright filter press, P (7) 172*c*.
Schottey, J. See Plumat, E.
Schottmiller, J. C. See Wood, C.
Schottmiller, J. C., Ryan, F. W., and Wood, C. Composition and method, P (4) 87*a*.
Schrader, R. L. Vacuum coating apparatus, P (5) 114*e*.
Schreder, G. See Guetin, P.
Schreiner, H., and Ohmann, H. Composite contact structure for vacuum-type circuit interrupters, P (2) 39*g*.
Schreurs, W. P. Polyspectral fluorescent lamp, P (10) 245*a*.
Schreurs, W. P., and Kimball, L. W. Method of making fluorescent lamps, P (10) 245*c*.
Schrewelius, N. G. Furnace for the production of glass fibers, P (10) 244*h*. Method of mfg. electrical resistance elements [$MoSi_2$] and elements manufactured by the method, P (1) 13*j*.
Schreyer, J. M. See Schmitt, C. R.
Schrijvers, J. See De Boeck, P.
Schroeder, D. A., Weiss, A. D., and Giltner, B. C. Resistance material and resistance elements made therefrom, P (3) 67*g*.
Schroeder, J. B. See Olson, D. R.
Schroeder, J. B., Dieselman, H. D., and Douglass, J. W. Technical feasibility of figuring optical surfaces by ion polishing, (8) 191*j*.
Schroeder, K. Booster for glassmelting tanks, (11) 268*b*.
Schroeder, K. H. See Kind, G.
Schroeder, T. F. See Brown, Sherman D.
Schroeder, U., and Jeschar, R. Model experiments on pressure losses and heat transfer in lattice-type checkerwork settings in tunnel kilns, (10) 256*f*.
Schroeder, W. W. See Peck, D. B.
Schroll, E., and Stepan, E. Quantitative analysis of mineral phases with X-ray diffraction, (1) 18*e*.
Schubel, J. R. See Swift, D. J. P.
Schuck, J. F., Rose, D. J., and Wang, C. H. Decal metalization of ceramic substrates, P (2) 39*j*.
Schuele, D. See Andeen, C.
Schueler, C. See Hofer, F.
Schueller, K. H. Surface finish of treated Al_2O_3 ceramics, (2) 29*h*. Texture of ceramic materials, (7) 182*e*.
Schuller, W., and Hohlfeld, H. Process and apparatus for making glass fiber structures including coating before and after attenuation, P (10) 245*b*.
Schuller, W. H. W. Glass staple fiber body, P (11) 270*b*. Method and apparatus for producing filaments from vitreous material, P (3) 59*a*.
Schulte, R. W. See Mund, K.
Schulten, R., and Michel, H. Apparatus for etching semiconductor bodies, P (10) 249*f*.
Schultes, B., and Troegel, G. Microscopy of enamels and its application, (1) 17*j*.
Schultz, A. H., and Stubican, V. S. Reply to comments on "Separation of phases by spinodal decomposition in the systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3," (2) 47*e*.
Schultz, P. C. Pb ferrite glass-ceramic articles and method of making, P (4) 82*e*. See Maurer, R. D.
Schulz, B. See Ondracek, G.
Schulz, E., Dolega, U., and Lang, J. Semiconductor device showing at least 3 successive zones of alternate opposite conductivity type, P (11) 275*e*.
Schulz-Dubois, E. O. See Scheel, H. J.
Schulze, B. See Henninges, K.
Schulze, E. Operating experience with the 8-section IS machine, (8) 191*g*.
Schulze, R. E. See Rasmussen, P. D.
Schulze, W. A. See Biggers, J. V.
Schumacher, H. Thick-film networks with printed capacitors, (2) 39*g*.
Schumaker, N. E. See Kuhn, M.
Schuman, L. J. See Archer, F. C.
Schumann, P. A., Jr. See Duffy, M. C.; Gardner, E. E.
Schuster, D. M. See Moss, M.
Schuster, E. See Reitmayer, F.
Schutrum, L. F. See Stewart, J. L.

Schutt, J. B. K silicate-Zn coatings, P (3) 54*g*.
Schuyler, P. M. See Grego, P.
Schwaerzler, G. Ceramic artists and their work—Heinz H. Engler, (1) 1*j*.
Schwalm, K. See Lang, F.
Schwan, W. See Ramisch, E.
Schwandner, G. Dynamic asymmetry. Work of Hans Joachim Wagner, (11) 265*i*.
Schwartz, A. B. See Sherry, H. S.
Schwartz, I. M. Asbestos processing apparatus, P (4) 94*g*.
Schwartz, J. W. See Robinder, R. C.
Schwartz, M. A. High-temp. materials, (2) 36*c*. See Ali, M. A.
Schwartz, R. J. See Ozdemir, F. S.
Schwarz, F. High-sensitivity long-time-constant thermistor bolometer, P (11) 274*j*.
Schwarz, R., and Meyer-Simon, E. Method of making Si halides, P (10) 257*i*.
Schwarz, W. M. See Ham, F. S.
Schwarzbach, J. Glass-ceramic dielectrics for thick-film capacitors of integrated circuits, (11) 273*g*.
Schwedes, B. See Hoppe, R.
Schweiker, M. A., and Watson, W. C. Tile edge grinding machine, P (4) 86*b*.
Schwemer, W. C. See Reed, M. W., Jr.
Schwiete, H. E. See Rehfeld, G.; Wierich, H.
Schwiete, H. E., Hoefgen, H., and Bleckmann, H. Use of blast furnace slag as a raw material in the ceramic industry, (1) 6*a*.
Schwiete, H. E., and Lipinski, D. Measuring thermal conductivity under vacuum at high temps., (5) 109*b*.
Schwiete, H. E., Lipinski, D., and von Chiari, B. Influence of the specimen shape and size on refractoriness under load of refractories, (6) 134*j*.
Schwinger, J. Magnetic model of matter, (1) 15*h*.
Schwuttke, G. H. See Brack, K.; Fairfield, J. M.; Hoogendoorn, C.
Schwyn, R. E., and Berg, M. Metalizing process for glass-free ceramic bodies, P (5) 113*d*.
Scola, D. A., and Roth, H. A. Treatment of C fibers, P (8) 197*b*.
Scorzon, L. See Raccanelli, A.
Scott, A. W. See Falce, L. R.
Scott, B. A., and Burns, G. Crystal growth and observation of the ferroelectric phase of $PbZrO_3$, (8) 199*b*. Determination of stoichiometry variations in $LiNbO_3$ and $LiTaO_3$ by Raman powder spectroscopy, (6) 146*i*.
Scott, B. A., and Horsman, W. H. Structural changes during the production of corundum by calcination of gibbsite and their influence on fabrication, (1) 8*b*.
Scott, B. F. See Beresford, M. P.
Scott, G. E. See Grimm, N.
Scott, J. F. Raman spectrum of SnO_2, (7) 179*j*. See Leite, R. C. C.
Scott, J. H. See Burns, J. R.
Scott, K. E., Jr., Kemper, D. M., Grove, L. E., and Kiess, R. J. Method of making piezoelectric crystal units, P (8) 201*e*.
Scott, M. W., and Stelzer, E. L. Multicolor photovoltaic device, P (5) 113*c*.
Scott, P. L. See Berggren, M. J.; Kisliuk, P.
Scott, R. K. Process for making refractory molds, P (1) 9*g*.
Scott, R. O. Applications of spectrography, (9) 230*i*.
Scott, V. D. See Flegmann, A. W.
Scotter, D. G. Effect of nonmagnetic inclusions on the spin-wave linewidth in polycrystalline YIG, (6) 146*i*.
Scott-Monck, J. A., and Learn, A. J. Method for producing improved semiconductive diodes, P (8) 201*h*.
Scouler, W. J. See Feinleib, J.; Pidgeon, C. R.
Scoville, R. D. See Brown, T. W.
Scriven, L. E. See Harris, W. F.
Sender, J. D. Reduction of char depth in ablative composites, P (7) 164*c*.
Seal, M. Use of diamond as a heat sink for solid state microwave devices, (4) 87*b*.
Searcy, A. W. See Dudash, J. J.; Leonard, R. B.
Searle, C. W. See Maartense, I.
Sease, J. D., and Harrington, F. E. Method of vibratory loading nuclear fuel elements, P (11) 276*d*.
Sechak, R. P. Trilayered Se-doped photoreceptor, P (7) 170*g*.
Secrist, D. R. See Ruszczyk, J. F.
Secrist, D. R., and Turk, H. L. Magnetic recording head having a nonmagnetic ferrite gap, P (5) 113*c*.
Seddon, R. I. Durable first surface Ag high reflector, P (1) 3*j*.
Sedlacek, Z. Device for instantaneously disconnecting a sorption apparatus from the source of vacuum, (7) 173*e*.
Seeger, D. E. See Beare, G. K.
Seeley, J. S., Smith, Stanley D., and Ritchie, F. S. Cs iodide interference filter with moisture-resistant layer, P (2) 33*g*.
Seely, J. H., and Chu, Richard C. Heat Transfer in Microelectronic Equipment—a Practical Guide. B (9) 240*d*.
Seferian, R. See Hebert, R. A.
Sefl, V. Rationalization of drying for structural ceramics, (7) 174*f*.
Segel, S. L. See Lynch, G. F.
Seger, M. See Kraemer, S.
Segerson, E. E. Multiple lead integrated circuit device and frame member for the fabrication thereof, P (2) 41*h*.
Seglin, L., and Winnicki, H. S. Production of Na_2CO_3, P (7) 176*a*.
Segnit, E. R., Anderson, C. A., and Holland, A. E. Scanning electron microscopy of clinochlore-kaolinite bodies, (9) 223*e*.
Segnit, E. R., Gelb, T., and Holland, A. E. Reaction of Fe, Co, and Ni oxides with kaolinite at 750°–1100°C, (9) 238*d*.
Segnit, E. R., and Holland, A. E. Formation of cordierite from clinochlore and kaolinite, (8) 197*i*.
Segre, J. P. Symmetrically pumped slab laser, P (6) 133*i*. 2-slab laser system with compensation for lens power, P (4) 91*b*.
Segrove, H. D. Purification of sand, P (4) 95*a*.
Seguelong, C. J. M. See Duthion, L.
Sehman, B. A. See Boksjo, C. I.
Seidel, B. See Abeck, W.
Seidel, G. Filtering apparatus, P (5) 115*g*.
Seidel, J. See Foster, K.
Seidel, T. E. See Evans, W. J.
Seidl, A. See Kraemer, S.
Seifullin, R. S. See Karasev, A. P.
Seike, Shoji. See Ogawa, Yutaka.
Seiler, C. J. See Malloy, J. F.
Seitelman, M. See Brody, S. B.
Seiter, H. See Sirtl, E.
Seitz, M. A. See Jaskolski, S. V.
Seiyama, Tetsuro. See Nagano, Masamitsu.
Sekerka, R. F. Aspects of morphological stability, (8) 207*j*.
Seki, Masahiro. See Mizushima, Yoshihiko.
Seki, Syuzo. See Onodera, Natsuo.
Seki, Yasuo, and Furukawa, Y. Effect of Dy^{3+} on the efficiency of ir-to-visible conversion phosphor Y_2OCl_2:Yb^{3+},Er^{3+}, (3) 72*g*. Effect of Dy^{3+} on the luminescence of Y_2OCl_2:Yb^{3+}, Er^{3+}, (3) 72*h*. Improved conversion efficiency of ir stimulable phosphor $(Y_{0.8-x}La_x)_2OCl_2$:Yb^{3+},Er^{3+}, (3) 73*g*. Infrared stimulable phosphor matched with YAG:Nd laser, (3) 63*d*.
Sekiya, Shinji. Resinoid pocketed cutoff and grinding wheel and method of making, P (8) 185*e*.
Selby, M. C. See Bilous, O.
Self, P. G. X-ray detection of Cr_2O_3 and V_2O_5 in Cr_2O_3-V_2O_5 mixtures, (9) 239*f*.
Selivanova, N. F. See Kudintseva, G. A.
Sell, D. D. Optical spectrometer with transparent refracting chopper, P (9) 232*a*.
Sellevold, E. J., and Richards, C. W. Short-time creep transition for hardened cement paste, (7) 157*f*.
Sellors, J., Jr., and Shular, H. E. Excess air burner, P (10) 258*e*.
Selman, G. L. See Darling, A. S.
Selman, M., Wamser, C. A., and Wilkalis, J. E. Process for preparing α-ammonium uranous pentafluoride, P (10) 254*c*.
Selte, K., and Kjekshus, A. Structural and magnetic properties of CoAs, (11) 282*g*.
Selte, K., Kjekshus, A., Jamison, W. E., Andresen, A. F., and Engebretsen, J. E. Magnetic structure and properties of CrAs, (4) 97*d*.
Selton, B. See Everest, D. A.
Seltzer, M. S., and Hed, A. Z. Analysis of the high-temp. electrical properties of wustite, (9) 233*h*.
Semchenko, G. D. See Kukolev, G. V.
Semchenko, I. A. Influence of physicochemical properties of slurries on the selection of efficient conditions of kiln operation, (8) 187*a*.
Semenov-Kobzar, A. A., Obolonchik, V. A., and Akinina, Z. S. Stability of transition metal carbides under anodic polarization conditions, (3) 75*b*.
Sementsova, D. V. See Bukhalova, G. A.
Semmler, J. See Ernst, H.
Semperowitsch, D. Quality assurance in regard to ceramic technology, (2) 37*i*.
Sen, P. C. See Mathur, N. M.
Senda, Masatoshi. See Sudoh, Giichi.
Sendt, A. Glassmaking tool and method of use, P (6) 132*j*. Method and apparatus for processing vitreous melt, P (5) 117*a*.
Senft, S. P. Mfg. of interior-coated bulbs for high-temp. glass lamps, P (10) 244*h*.
Senftle, F. E. See Duffey, D.
Serafin, F. G. Mineral grinding aids, P (1) 2*f*.
Serebrennikov, V. V. See Yakunina, G. M.
Sereda, N. N. See Koval'chenko, M. S.
Sereda, P. J. See Ciach, T. D.
Serlin, I. Method of testing and selecting glass cloth for use in polyimide composites, P (1) 5*d*. Treatment of glass cloth, P (8) 194*d*.
Serna, J. Twist grain boundaries in alkali halides [surface decoration], (10) 261*e*.
Serpinskii, V. V. See Bering, B. P.
Serrano, F. A. See Martinez, J. R.
Sersale, R. See Marchese, B.
Sese, Kiyoaki. Method for mfg. $Mg(OH)_2$, P (8) 207*f*.
Seshadri, V. See Mishra, G. L.
Sessler, G. M., and West, J. E. Method for producing permanent electret charges in dielectric materials, P (6) 139*f*.
Sestak, J., Zaveta, K., Roskovec, V., and Zounova, F. Preparation and magnetic properties of the glassy system MnO-Fe_2O_3-B_2O_3, (11) 269*f*.
Sestrich, D. E. Pyrolytic deposition of Si_3N_4 films, P (5) 114*a*.
Setaka, Nobuo, and Ajiri, K. Influence of vapor-phase composition on morphology of SiC single crystals, (11) 281*a*.
Setaka, Ryusuke. See Kimura, Isao.
Setoguchi, Masahiro, Sakamoto, C., and Kuribayashi, S. Crystal growth of $2CaSiO_4$-$CaCl_2$ by the flux method, (3) 72*h*.
Seuffert, A. J. Method for producing a Cr-W coating on W for protection against oxidation at elevated temps., P (4) 80*a*.
Sevast'yanova, T. N., and Karpenko, N. V. Thermographic and X-ray study of the systems SnI_2-MI(M=K,Rb,Cs), (8) 211*d*.
Sewell, P. B., and Mitchell, D. F. Quantitative X-ray emission analysis of thin oxide films on Ta, (7) 179*i*.
Seyfarth, H. H., and Hahne, B. Microscopic phase analysis of mixtures of solids by means of light refraction measurements, (3) 69*i*.
Seyfarth, H. H., Hahne, B., and Loescher, J. Microscopic identification of secondary and trace ingredients in mixtures of solids, (3) 69*i*.
Seymour, M. W. See Jones, Isaac P.
Seymour, S. L. See Painter, F. F.
Sha, G. T. See Chou, Y. T.
Shabaker, H. A. Thermal treatment of powder, P (4) 95*a*.
Shackleford, W. L. See Beder, E. C.
Shacklette, L. W., and Williams, W. S. Scattering of electrons by vacancies through an order-disorder transition of VC, (7) 180*j*.
Shadel, J. S. Documented use of cup plates in the 19th century, (11) 265*i*.
Shadrina, M. N. See Skoblo, L. I.
Shaefer, K., and Keck, D. Unstacking and sorting of bricks, P (8) 194*f*.
Shaffer, F. N. Yb-activated Sr phosphate phosphors, P (2) 43*c*.
Shaffer, J. W. Photoflash lamp, P (3) 59*a*, P (10) 245*i*. Photoflash lamp and method of preparing and applying fulminating material, P (6) 133*d*. See Brown, S. V.; Fink, W. C.
Shaffer, P. T. B., and Jun, Choll K. Elastic modulus of dense polycrystalline SiC, (4) 96*g*.
Shaffer, P. T. B., and Nanni, R. G. Refractive index and dispersion of β-SiC, (1) 25*a*.
Shaffer, R. E. Frangible glass grenade, P (11) 270*g*.
Shagurin, A. A. See Kestner, O. E.
Shah, I. D., and Khalafalla, S. E. Kinetics and mechanism of the conversion of covellite (CuS) to digenite ($Cu_{1.8}S$), (6) 149*d*.
Shah, I. S. Thermal conversion of Mg sulfite to Mg oxide, P (10) 257*i*.
Shah, J. C. See Nguyen Van Tran.
Shah, Y. T. See Bodman, S. W.
Shah, Y. T., and Pearson, J. R. A. Stability of nonisothermal fiber spinning, (9) 218*d*. Stability of nonisothermal fiber spinning—general case, (9) 218*e*.
Shaha, J. P. Use of Indian glasses for fiber optics, (7) 161*a*.
Shahid, K. A., and Glasser, F. P. Phase equilibria in the glass forming region of the system Na_2O-CaO-MgO-SiO_2, (11) 269*c*.
Shakhov, F. N. See Meshengisser, M. Ya.
Shakirov, A. See Kunin, V. Ya.
Shalchin, V. S. See Budnikov, P. P.
Shalimo, Z. N., and Ermolenko, N. N. Influence of precrystallization heat treatment on the crystallization of glasses in the system SiO_2-Al_2O_3-CaO-Na_2O, (8) 190*g*.
Shal'man, L. M. See Ksendzovskii, V. R.
Shamaeva, A. A. See Papkova, L. P.
Shamash, M. B., Staley, W. W., Denton, C. I., and Walton, F. D. Microcircuit modular package, P (11) 275*f*.
Shamrai, F. I. See Kharitonov, V. I.
Shanefield, D. J. See Crosby, G. E.
Shaner, K. H. See Fisher, P. C., Jr.; Haynes, J. W.
Shank, H. C., Jr. Method for protecting glassware and the article produced thereby, P (1) 5*c*.
Shannon, J. M. See Bulthuis, K.; Robinson, D. P.
Shannon, R. D. Electrical resistors comprising rhombohedral Pt Co oxides, P (4) 87*d*. Orthorhombic Pt-metal oxides of type Pt_3MO_6, P (8) 207*a*.
Shannon, R. F. Method of producing siliceous fiber corrosion-inhibiting composites, P (8) 193*f*.
Shapira, Y. Ultrasonic behavior near the spin-flop transition of Cr_2O_3, (6) 152*h*. Ultrasonic behavior near the spin-flop transitions of hematite, (5) 125*a*.
Shapiro, E. Ya. See Likhoradov, A. P.
Shapiro, L. Rotary press, P (10) 254*i*.
Shapiro, W. A., and Kemmerer, R. P., Jr. Solid-state ring laser, P (8) 202*c*.
Shapkin, P. S. See Vasil'kova, I. V.
Shapland, J. T. Refractory closure member for bottom-pour vessels, P (3) 61*d*.
Shappirio, J. R., Eckart, D. W., and Cook, C. F., Jr. Chemical and structural characterization of amorphous semiconducting materials in the system Ga-As-Te-Ge, (6) 145*j*.
Sharan, H. N. Control system for a multiplicity of muffle burners, P (6) 143*d*. Turbulence muffle burner, P (2) 45*i*.
Shardlow, L. R. See Baker, L. K.
Sharkadi, E. E. See Fedorov, P. I.
Sharma, R. A. Liquidus and eutectic phase equilibria in the systems CaI_2-$CaCl_2$, CaI_2-CaF_2, and CaI_2-$MgCl_2$, (4) 97*a*.
Sharma, S. D., and Kashyap, S. C. Growth of ZnO whiskers, platelets, and dendrites, (7) 167*d*.

Sharma, S. D., and Malhotra, L. K. Growth of hollow crystals of CdS, (7) 177*i*.
Sharp, A. R., Pintar, M. M., and Komac, M. Proton spin-lattice relaxation in paramagnetic solid $UO_2{\cdot}xH_2O$, (6) 151*h*.
Sharp, D. See Fort, A.
Sharp, D. J., and Sutch, R. D. Anodizable cermet film components and their manufacture, P (6) 137*f*.
Sharp, J. H. See Hancock, J. D.
Sharpe, R. M. See Bramman, J. I.
Shatalin, B. S. See Nemirovskii, B. V.
Shatokhina, L. P. See Syrkin, Ya. M.
Shatova, N. P. See Galdina, N. M.
Shatskii, V. M. See Anoshina, N. P.
Shaulov, A. See Simhony, M.
Shaunfield, W. N., Jr. See Barelli, A. E.
Shaver, R. G. See Davies, L. G.
Shaw, D. W. Epitaxial GaAs kinetic studies: [001] orientation, (9) 235*i*. Method of depositing semiconductor material, P (4) 88*f*.
Shaw, E. J., and Stetka, D. G. Method of making a planar segmented memory unit, P (2) 41*g*.
Shaw, H. E., Jr. See Bricker, J. A.
Shaw, J. G., and Oates, W. A. Thermomigration of C in metals, (6) 152*f*.
Shaw, J. M. See Micheletti, F. B.
Shaw, J. M., and Amick, J. A. Vapor-deposited W for Si devices, (10) 249*b*.
Shaw, K. Kiln firing in craft pottery, (1) 10*d*. New thinking in glaze research and technology, (1) 10*e*. Soviet high-strength perforated bricks, (10) 246*b*. Updating clay product drying processes; rapid drying in existing driers; rapid conveyor and automatic drying; new ceramics drying methods in Russia, (3) 70*i*.
Shaw, M. C. Segmented grinding wheel, P (5) 101*g*.
Shaw, M. J. Some experiments on fast firing of aluminous refractories, (2) 36*h*.
Shaw, M. P. See Solomon, P. R.
Shaw, R. F. See Davis, E. A.
Shaw, R. G. See West, R. N.
Shaw, R. R. Polyimide and polyamide-polyimide as a semiconductor surface passivator and protectant coating, P (2) 42*b*.
Shaw, R. R., and Breedis, J. F. Secondary phase separation in Pb borate glasses, (9) 218*c*.
Shay, J. L. See Leheny, R. F.
Shchavelev, O. S., and Babkina, V. A. Dependence of temp. coeff. of linear thermal expansion of silicate glasses on their chemical composition, (9) 216*g*.
Shchepetkin, A. A., Antonov, V. K., Dvinin, V. I., and Chufarov, G. I. Crystal-chemical transformations during dissociation of spinel solid solutions in the system Mg-Ti-Fe-O under equilibrium conditions, (5) 119*b*.
Shchepetkin, A. A., Dvinin, V. I., Zakharov, R. G., and Chufarov, G. I. Synthesis and crystal structure of spinel-like solid solutions in the systems Mg-Ti-Fe-O and Mn-Ti-Fe-O, (1) 25*g*.
Shchepetkin, A. A., Zinovik, M. A., Deulin, M. I., and Chufarov, G. I. Effect of heat treatment on the crystal structure and properties of Mg-Mn ferrites, (8) 208*h*.
Shcherbakov, V. A. See Baidakov, L. A.
Shcherban, N. I. See Petrova, E. M.; Radomysel'skii, I. D.
Sheehan, G. M. TiO_2 pigment, P (5) 118*c*.
Sheets, H. D., Jr. See Lankard, D. R.; O'Hara, M. J.
Sheets, H. D., Jr., and O'Hara, M. J. Phosphate-bonded grinding wheel, P (3) 53*i*.
Sheiko, I. N., Gitman, E. B., and Loichenko, V. Ya. Solubility of Be oxide in melted chloride and fluoride systems, in tetraborate, and Na phosphate, (8) 210*e*.
Sheindlin, A. E. See Petrov, V. A.
Sheinin, E. I., Belostotskaya, N. S., Minchenko, A. V., and Grebenyuk, Yu. L. Method and equipment for hydrostatic pressing of washbasins, (8) 197*i*.
Sheka, I. A. See Chaus, I. S.
Shelby, J. E. He migration in natural and synthetic vitreous SiO_2, (3) 56*j*. He migration in TiO_2-SiO_2 glasses, (5) 106*b*.
Sheldon, E. E. Devices of fiber optic and vacuum tube construction, P (10) 244*c*. Improvements in CRT of TV type for X-ray protection, P (2) 34*h*.
Sheldon, G. S. Semiconductor passivating process, P (5) 114*f*. Semiconductor passivating process and product, P (6) 140*d*.
Sheldon, R. W. See Swift, D. J. P.
Shelley, D. P. Development and use of the air-cushion kiln (Hover-kiln), (2) 45*e*.
Shelley, R., and Nicholson, P. S. Macroscopic densification and homogeneity in hot-pressing, (1) 16*h*.
Shemyakin, V. K., Chernyshev, A. N., Konev, V. A., and Lysenko, L. I. Interference method for measuring the slurry level in vertical slurry basins, (8) 187*d*.
Sheng, H. P., and Wooten, F. T. Method for the continuous doping of semiconductor materials, P (2) 41*a*.
Shennan, J. V., and Ford, L. H. Nuclear reactor fuel elements, P (3) 68*g*.
Shepherd, F. D., Jr., Vickers, V. E., and Yang, A. C. Schottky barrier photodiode with a degenerate semiconductor active region, P (1) 14*h*.
Shepherd, G. Method of forming welded multiple glazing units, P (8) 193*d*.
Sheppard, J. E., and Pellechia, V. J. Method for bonding with deposited particulate glass, P (9) 219*j*.
Sheppard, R. S., and Wilson, W. L. Preparation of TiC, P (8) 196*h*.
Sherburne, C. L. See Ritter, J. E., Jr.
Sherry, H. S., and Schwartz, A. B. Low temp.-high temp. 2-stage ion exchange of zeolites, P (10) 257*f*.
Sherwood, R. C. See Bobeck, A. H.; Cohen, E.; Holmes, L.
Shestakov, A. I., Zemskov, G. V., and Smekh, E. V. Diffusion chromizing of graphite powders in a closed reaction vol, (10) 246*j*.
Shesternenkov, V. I. Detonation coating, (10) 246*i*.
Shevlin, T. S. Integral heating elements, P (5) 105*c*.
Shevrina, Z. A., Kochergin, V. P., and Fomina, T. I. Solubility of Fe oxide in phosphate-halogenide melts of alkali metals, (1) 25*c*.
Shewchun, J. See Kawasaki, B. S.
Shibata, Hiroshi, Morita, T., and Nakano, S. Production of Na_2CO_3, P (7) 176*b*.
Shibata, Osami. See Kasai, Yoshio.
Shibata, Toshikazu. See Okada, Moritami.
Shibayama, Naoyuki. See Maeda, Minoru.
Shibryaev, B. F., Gribenyuk, Yu. N., and Shuvalova, T. A. Boriding of sintered parts, (10) 246*f*.
Shibuya, Hideo. See Yamamoto, Masavuki.
Shick, L. K., and Von Neida, A. R. Growth of crystalline chalcogenide spinels, P (4) 88*b*.
Shidlovskii, G. V. See Rabodzei, N. V.
Shifrin, G. A. See Bower, R. W.
Shiga, Kazumasa. Semiconductor oscillating-resonance circuit device, P (4) 90*e*.
Shigehara, Hiroshi. See Yanagida, Hiroaki.
Shigeta, Tamikazu. See Obuchi, Satoru.
Shih, K. K. Epitaxial growth of $GaAs_zP_{1-z}$ from the liquid phase, (9) 235*i*.
Shikama, Sukejiro. See Kurumada, Katsuhiko.
Shikami, Gunji, and Kameshima, N. Sedimentation vol of portland cement in organic liquid, (4) 79*c*.
Shikunov, B. I., Lafer, L. I., Yakerson, V. I., Mishin, I. V., and Rubinstein, A. M. Infrared spectra of some zeolites, (6) 149*a*.
Shiloff, J. C. Boric acid production, P (7) 175*a*.
Shilov, S. A. See Belyaev, I. N.
Shima, Makoto. Fission track dating of ancient glasses, (4) 77*i*.
Shimada, Kinji, Komaki, T., Kawasaki, J., and Fukushige, Y. Wollastonite deposit at Kiura, Oita prefecture, Japan, (6) 143*g*.
Shimada, Kohei. See Ohba, Hiroshi.
Shimada, M. See Kodaira, K.
Shimada, Noburo, and Koyama, Y. Nondrying-blow-in of blast furnace, (1) 8*b*.
Shimada, Sugao. See Yamamoto, Yasuhiko.
Shimakura, Keiichi, Yamamoto, H., and Shiraishi, M. Semiconductor integrated-circuit device, P (2) 42*c*.
Shimizu, Ikuzo. See Matsuno, Akira.
Shimizu, Masao. See Sakurai, Yasunobu.
Shimizu, Takashi, and Hara, H. Oxidation of CO on La_2O_3-doped $BaTiO_3$, (11) 274*b*.
Shimizu, Yasuhiro, and Nakamura, Y. High-pressure discharge lamp of the cooled electrode type, P (1) 4*h*.
Shimizu, Yoshiaki. See Iemura, Toshio.
Shimobayashi, Seiichi. See Iwabuchi, Toshitsugu.
Shimoda, Takashi. See Akai, Shinichi.
Shimohira, Takajiro. Mechanism of densification during final stage of hot-pressing, (5) 121*h*. Two-dimensional shape of polycrystalline grains, (6) 152*g*.
Shimoji, Mitsuo. See Ichikawa, Kazuhiko.
Shimura, Hidekazu. See Moriki, Juichi.
Shimura, Yoshihiro. X-ray stress-measuring apparatus, P (5) 116*h*.
Shinada, Toshio. See Miyake, Yasutomo.
Shindel'man, Yu. I., and Akulova, G. I. Low-pressure Hg-vapor gas-discharge fluorescent lamp with amalgam, P (11) 270*c*.
Shinn, W. A. See Battles, J. E.
Shinoda, Daizaburo. See Ishikawa, Masaoki.
Shinoda, Daizaburo, Ishikawa, M., Muta, H., Asanabe, S., and Kawamura, N. MOS device with a metal silicide gate, P (3) 66*b*.
Shinohara, Kunio, Shoji, K., and Tamaka, T. Mechanism of size segregation of particles in filling a hopper, (11) 276*g*.
Shinskey, G. Blending system start up and shut down, (10) 254*c*.
Shintani, Yoshihiro. See Tada, Osamu.
Shioiri, Teruhumi. See Tamaoki, Osamu.
Shionoya, Shigeo. See Hirano, Masahiro; Nagasawa, Masahiro; Yamada, Naoto.
Shiosaki, Masaharu. See Moriki, Juichi.
Shiota, P. See Welty, J. M.
Shiota, Takeshi. See Watanabe, Osamu.
Shiple, T. J., and Schott, C. E. Application of dense media separation to reclaim a glass raw material from municipal solid wastes, (4) 92*b*.
Shirai, Hisao. See Murabayashi, Mineo.
Shirai, Yoshihiro, Ichikawa, H., Yoshida, A., Uchida, N., Tsuji, M., and Matsumoto, Z. Method for mfg. activated C and apparatus therefor, P (10) 248*b*.
Shiraishi, Masamichi. See Shimakura, Keiichi; Yamamoto, Hirohiko.
Shiraishi, T. See Yamaguchi, T.
Shiraiwa, Toshio, Yamaguchi, H., and Kido, Y. Precooling apparatus for continuous automatic ultrasonic inspection, P (8) 206*a*.
Shirane, Gen. See Axe, J. D.; Cox, D. E.; Yamada, Yoshito.
Shirane, Gen, and Yamada, Y. Lattice-dynamical study of the 110°K phase transition in $SrTiO_3$, (5) 121*g*.
Shirasaka, Masaru. See Ono, Yoshio.
Shirasaka, Nobuhiko. See Itoh, Yokichi.
Shirasaki, Shin-ichi, and Oishi, Y. Role of grain boundaries in O self-diffusion in polycrystalline MgO, (3) 75*c*.
Shirasuka, Kouhei. See Yamaguchi, Goro.
Shirk, B. T. Production of Ba ferrite, P (4) 90*e*.
Shirley, D. A. Automatic control for glass drawing process, P (3) 57*h*.
Shirn, G. A., and Janus, A. Sputtering process for making a film of SiO_2 and Si_3N_4, P (1) 14*i*.
Shiroki, Ken-ichi. See Kuwano, Yasuhiko.
Shirouzu, Shunji. See Tsuji, Shigeo.
Shishkin, L. S. See Artamonov, A. Ya.
Shishkov, N. V. See Budnikov, P. P.
Shively, J. H., and Archer, E. D. Selected adsorption with a silanized crystalline aluminosilicate, P (8) 207*g*.
Shklovskaya, R. M. See Kirgintsev, A. N.
Shlionskii, Yu. S. See Fraiman, L. S.
Shlyuko, V. Ya. See Kudintseva, G. A.
Shoji, Kazunori. See Shinohara, Kunio.
Shonebarger, F. J. Ion exchange strengthening of glasses with Li vapor, P (2) 34*i*.
Shook, W. B. See Barta, J.
Shoop, V. A. See Bowser, G. H.
Shor, O. I. See Bukhovets, V. G.; Shpigun, A. A.
Short, O. A. Thermistor compositions and thermistors made therefrom, P (10) 253*b*.
Shortes, S. R. Phosphor screen fabrication, P (5) 113*h*.
Shoup, R. D. Silicate bodies containing coprecipitated oxides, P (10) 245*g*.
Shousha, A. H. M. Negative differential conductivity due to electrothermal instabilities in thin amorphous films, (7) 160*c*.
Shpigun, A. A., Sazhin, V. S., Fedorenko, Yu. G., and Shor, O. I. Phase transitions during the hydrochemical decomposition of nepheline, (7) 179*b*.
Shrader, R. L. Apparatus for supporting a substrate holder, P (8) 200*c*. Vacuum coating apparatus, P (8) 202*j*.
Shteinberg, Yu. G., and Milyukov, E. M. Mechanism of liquation in the pseudobinary section of $SrSiO_3$-$ZnSiO_3$, (9) 217*g*.
Shtrikman, S. See Gorodetsky, G.
Shubin, V. I. See Budnikov, P. P.; Skoblo, L. I.
Shukhnin, L. N. See Borzunov, E. E.
Shular, H. E. See Sellors, J., Jr.
Shultz, B. R. See Kaufmann, M.
Shultz, J. I., Bell, R. K., Rains, T. C., and Menis, O. Standard reference materials—methods of analysis of NBS clay standards, (11) 278*d*.
Shulver, W., and Blake, D. L. Tensile members, apparatus and process, P (3) 59*h*.
Shulzhenko, A. A., and Getman, A. F. Method for synthesizing diamond, P (10) 241*e*.
Shumate, P. W., Jr. Anisotropy in the domain-wall mobility of rare-earth orthoferrites, (7) 176*g*.
Shumeiko, R. M. See Yam, V. M.
Shumilin, A. A., Abbakumov, V. G., and Tarakanchikov, G. A. Ratio of zone lengths in high-temp. tunnel kilns, (8) 206*e*.
Shurgan, J. See Koo, R. C.
Shurtz, R. R. See Ahn, B. H.
Shutt, T. C., and Barlow, G. Practical aspects of Ce decolorization of glass, (3) 57*b*.
Shutt, T. C., Campbell, H., and Abrahams, J. H., Jr. New building materials containing waste glass, (10) 243*h*.
Shuvalova, T. A. See Shibryaev, B. F.
Shvab, S. A. See Badyan, A. Kh.
Shwayder, W. M. Method of disintegrating sintered hard carbide masses, P (9) 230*a*. Process for recovering refractory carbide particles from pieces of cemented carbides, P (4) 84*f*.
Shyne, J. J., and Milewski, J. V. Method of growing SiC whiskers, P (3) 61*g*. Three-dimensional crystal whiskers and method for preparation thereof, P (9) 222*h*.
Sibert, F. J. Process for making Al_2O_3, P (10) 257*c*.
Sibilia, J. T. See Feldman, D.
Sibley, W. A. See Chen, Yok; Facey, O. E.
Sibold, J. D. See Grimm, N.
Sicka, R. W. Foamed ceramic comprising fly ash and phosphoric acid, P (3) 60*b*.
Sickbert, A. See Grimm, R.
Sidorko, V. R. See Eremenko, V. N.
Sie, C. H. See Uttecht, R.
Siefert, A. C. Fiber-reinforced ceramics, P (1) 4*b*.
Siegbahn, K., Hammond, D., Fellner-Feldegg, H., and E. F. Barnett. Electron spectroscopy with monochromatized X rays, (8) 204*j*.
Siegel, R., and Howell, J. R. Thermal Radiation Heat Transfer, B (10) 264*e*.
Siegel, V. H. Pressure-transducer with reduced temp. sensitivity, P (10) 252*j*.
Sieger, R. A. See Rabatin, J. G.
Siegfried, E. C., Harwell, C. J., and Murphy, S. L. Apparatus for ram-forming monolithic plastic articles, P (10) 246*a*.
Siegla, D. C. Infrared radiant open coil heating unit with reflective fibrous ceramic heater block, P (2) 34*h*. See Deaton, H. W.
Siegmar, W., and Wissinger, H. Holder for mass-produced miniature electrical compo-

nents, especially semiconductor members, P (7) 168*j*.
Siegwart, E. Flow technique in high output dryers, (2) 45*f*.
Siemssen, E. A. Tower furnace, P (4) 83*i*.
Sierad, T. B. Process of coating glass with durable coatings and resulting products, P (6) 133*e*.
Sierra, R. See Baron, A.
Signorelli, R. A. See Petrasek, D. W.
Sigsbee, R. A. Adatom capture and growth rates of nuclei, (6) 144*i*. Smoothly changing voltage-variable capacitor having an extendible *pn* junction region, P (1) 14*f*.
Siire, Toyokazu, Iizuka, H., and Chino, S. Performance of mortar mixture with addition of waterproofing agent, (4) 79*f*.
Silbiger, J. See Kugler, T.
Sil'chenko, V. A., Pafomov, N. N., Tarasevich, Yu. I., Matyash, I. V., and Suyunova, Z. E. EPR of Cu^{2+} exchange cations in kaolinite, (6) 147*j*.
Silsbee, R. H. See Herendeen, R. A.
Silver, R. S., and Jaklik, J., Jr. Semiconductor diode array vidicon target having selectively insulated defective diodes, P (2) 42*b*.
Silverberg, C. G. All-ceramic glassmaking system, P (9) 215*j*.
Silvernail, W. W., and Goetzinger, N. J. Mechanics of glass polishing (I), (11) 269*a*.
Silvey, G. A. See Regh, J.
Silwanowicz, A. See Phelps, G. W.
Sime, S. J. See Allnatt, A. R.
Simhan, R. See Muschalla, B.
Simhony, M., and Shaulov, A. Pyroelectric voltage response to step signals of ir radiation in triglycine sulfate and Sr-Ba niobate, (5) 123*a*.
Simkovitch, G., Aplan, F. F., and Fensterer, R. A. Point defect effects in the electrostatic separation of NiO, (9) 232*h*.
Simmen, F. G. Mfg. of disposable ceramic dishes from high-alkali pyrophyllite, P (7) 166*c*.
Simmonds, P. G. See Lovelock, J. E.
Simmons, G. A. Glass-ceramic articles having an integral compressive stress surface layer, P (5) 107*f*.
Simmons, J. A., deWit, R., and Bullough, R. (editors). Fundamental Aspects of Dislocation Theory, B (2) 50*h*.
Simmons, J. H. See Haller, W.
Simmons, J. H., Napolitano, A., and Macedo, P. B. Supercritical viscosity anomaly in oxide mixtures, (7) 181*i*.
Simmons, M. I. See Adams, A. L.; King, L. C.
Simo, C., and Holt, S. L. Electronic structure of $LiCrO_2$, (8) 208*j*.
Simoleit, H. See Kemeny, G.
Simon, E. Planar Zener diodes having uniform junction breakdown characteristics, P (2) 42*a*.
Simon, G. Furnace wall [recessed brick] particularly for open-hearth furnaces, P (9) 222*f*.
Simon, L. See Jirkowsky, J.
Simon, P. Method for mfg. a thin-film magnetic head assembly, P (8) 201*f*.
Simonis, H. Glazing bone china, P (8) 198*f*.
Simonyan, K. See Chilton, G. E.
Simonyan, K., and Chilton, G. E. Solid-state temp.-measuring device, P (11) 275*j*.
Simpson, A. W., and Lucas, J. M. Anodic preparation of amorphous films with garnet ferrite and other stoichiometrics, (7) 166*e*.
Simpson, E. A. See Butcher, H. J.
Sims, S. D. See Duffy, J. J.
Simpson, A. W., and Lucas, J. M. Temp. variation of susceptibility of some amorphous antiferromagnetic oxides, (4) 81*c*.
Simpson, J. A. Electron impact spectrometry for gas phase chemical analysis, (2) 44*h*.
Simpson, W. I. See Manasevit, H. M.
Sims, R. E. Lamp filament structure, P (2) 34*i*.
Sinai, P. Correction of optical aberrations by neutron irradiation, (8) 189*j*. Method of making bifocal lenses comprising treating a preselected area of a single focal length lens with ionizing radiation, P (2) 34*e*.
Sinchuk, A. G. See Ischenko, A. Ya.
Sinclair, G. I. See Croll, R. D.
Sinclair, W. See Cole, J. M.
Sinclair, W. R. See Peters, F. G.
Sinfelt, J. H. Serial reforming with Pt catalyst in first stage and Ir, Rh, Ru, or Os catalyst in second stage, P (11) 280*a*.
Singer, H., Kuehr, J., Dellus, H., and Wunderlich, D. Coated abrasive article, P (2) 29*f*.
Singer, K. See Woodcock, L. V.
Singh, A. K., and Balasingh, C. Effect of X-ray diffractometer geometrical factors on the centroid shift of a diffraction line for stress measurement, (7) 173*e*.
Singh, B. N., and Houseman, D. H. Influence of oxide particles on the sintering characteristics of carbonyl Fe, (10) 246*j*.
Singh, L. P. See Kishore, K.
Singh, M. N. See Kesavan, R.
Singh, R. D. See Srivastava, S. P.
Singh, R. S. See Kahan, A.
Singh, S. See Bonner, W. A.; Grodkiewicz, W. H.
Singh, Shobha, and Van Uitert, L. G. GaAs diode with up-converting phosphor coating, P (3) 65*b*. Nonlinear optical devices utilizing substantially hexagonal SiC devices, P (10) 252*f*.
Singhal, L. K. See Subbarao, E. C.
Single, D. Method of reclaiming and coating phosphor, P (6) 139*g*.
Singleton, J. H. Cathode-getter materials for sputter-ion pumps, P (11) 270*d*.
Sinha, B. C., and Roy, S. K. Rapid analysis of chromite, chrome ore, and chrome-bearing materials, (11) 278*i*.
Sinha, B. P., and Hendry, A. W. Further tests on model brick walls and piers, (9) 220*i*.
Sinha, K. P. See Brahmecha, B. G.
Sinkovec, M. G. Low pressure steam for pickling system, (10) 242*g*.
Sioui, R. H., and Cohen, H. M. Resin-bonded metal-coated diamond or cubic BN abrasive tools containing an inorganic crystalline filler and graphite, P (9) 213*f*.
Sirazitdinov, N. S. See Sychev, M. M.
Sircar, A., and Brett, N. H. Phase equilibria in ternary systems containing ZrO_2 and SiO_2 (IV) preliminary study of the system Na_2O-ZrO_2-SiO_2, (1) 23*g*.
Sironi, G. See Colombo, U.; Ferrero, F.
Sironi, G., Sacerdote, R., and Ferrero, F. Process for the purification of $TiCl_4$, P (4) 94*j*.
Sirrine, R. C., and Stein, L. Method of making low-resistance polycrystalline Si contacts to buried collector regions using refractory metal silicides, P (7) 169*j*.
Sirtl, E. Method for epitactic precipitation of Si at low temps., P (8) 201*f*. See Heywang, W.
Sirtl, E., and Seiter, H. Method of producing epitaxic growth layers of semiconductor material for electrical components, P (7) 169*c*.
Sisneros, T. E. Red-emitting material for cathodoluminescent screens, P (4) 90*g*.
Sitek, G. J., and Revesz, R. N. Electrically resistive crucible, P (4) 84*j*.
Sivertsen, D. R., Cecil, O. B., and Haberecht, R. R. Methods of making a composite dielectric body, P (3) 66*i*.
Sivkina, V. A. See Chistyakova, A. A.
Sivokon, V. I. See Papkova, L. P.
Sizova, N. V. See Berul, S. I.
Sjoedin, B., and Jonsson, K. O. Slag attack in the ASEA-SKF [casting] furnace, (8) 195*h*.
Skalny, J. See Odler, I.; Yudenfreund, M.
Skalny, J., and Odler, I. Pore structure of Ca silicate hydrates, (10) 242*b*.
Skaw, E. R. See Degenkolb, R. S.
Skeen, J. W. Experiments on the rain penetration of brickwork (II) effect of mortar type, (1) 5*j*.
Skelly, J. F. Environmental problems in the whitewares industry, (3) 61*i*.
Skelton, R. G. Permanent magnet ferrites, (2) 38*d*.
Skiermont, F. J. See Snedeker, R. H.
Skinner, D. D. See Thompson, J. H.
Skinner, J. G. See Goldrick, M. R.
Skoblo, L. I. Determination of zone length of highest temps. from lining wear, (9) 214*b*.
Skoblo, L. I., Il'ina, N. V., Shadrina, M. N., Shubin, V. I., and Tishkova, K. S. Stability of rotary kiln linings in cement plants, (8) 187*g*.
Skorik, L. I. See Raichenko, A. I.
Skriba, D. A. How a computer and glass communicate, (5) 106*b*.
Skriba, M. C. See Bodman, S. W.
Skudnova, E. V. See Abrikosov, N. Kh.
Skusnov, L. I. See Ksendzovskii, V. R.
Skvorecz, T. See Balint, P.
Slack, G. A. See Scace, R. I.
Slack, G. A., and Austerman, S. B. Thermal conductivity of BeO single crystals, (7) 181*d*.
Slack, G. A., Oliver, D. W., Chrenko, R. M., and Roberts, S. Optical absorption of $Y_3Al_5O_{12}$ from 10- to 55,000-cm^{-1} wave numbers, (5) 122*i*.
Slack, J. R. See Burfoot, J. C.
Slack, L. H. See Eusner, P. R.
Sladek, K. J., and Herron, H. M. TiO_2 coatings [on glass bottles], (7) 160*j*.
Slagle, R. J. See Petermann, J. P.
Slaten, G. G., and Snow, E. H. Surface depletion layer photodevice, P (1) 15*a*.
Slater, T. C., and Hamilton, F. C., Jr. Hydraulic cement and method of producing, P (11) 267*c*.
Slattery, P. W. See Hollox, G. E.
Slattery, W. J. (editor). Index of U.S. Voluntary Engineering Standards, B (2) 51*a*.
Slegten, P. M. A. Automatic grading linings for cylindrical tube or similar mills, P (10) 254*i*. Lining for cylindrical mills, P (4) 92*d*.
Sleight, A. W. See Jeitschko, W.
Sleptsov, V. M. See Petrova, E. M.
Slick, P. I. Heat treatment of Ni-Zn-Co ferrite, P (2) 40*j*.
Sloan, B. J., Jr., Martin, B. M., Clevenger, L. H., and Dunn, R. S. Integrated circuit process utilizing orientation-dependent Si etch, P (8) 200*j*.
Slob, A. See Schmitz, A.
Slobbe, W. W. See Evans, L. W.
Slobodin, B. V. See Fotiev, A. A.
Slobodnik, A. J., Jr. Acoustic surface wave delay line, P (10) 249*d*. Microwave acoustic surface wave amplifier and method of fabrication, P (2) 41*d*.
Slobodnik, A. J., Jr., and Szabo, T. L. New high-coupling low-diffraction cut for acoustic surface waves on $LiNbO_3$, (4) 97*i*.
Slocum, R. A. See Jen, D. P.
Sloka, W. E. Process for producing C fibers, P (7) 164*b*.
Sluse, G., and Joannes, G. Process for the coating of electrodes, P (9) 227*i*.
Small, J. F. See Small, K. R.
Small, K. R., and Small, J. F. Rotary kiln sampling device, P (2) 45*a*.
Small, O. M. Pressurizer nozzle, P (7) 162*f*.
Smart, R. C. See Kuehl, D. K.
Smart, R. St. C. Studies of alkali halide films deposited at low temps. Electron microscopy, electronic spectra from color centers, and ir spectra from the chemisorption of nitric oxide, (1) 25*a*.
Smead, R. G., and Bentsen, L. J. Electrostatic spray gun nozzle and air cap, P (10) 254*j*.
Smedley, S. I. See Cleaver, B.
Smekh, E. V. See Shestakov, A. I.
Smeltzer, W. W. See Moelgaard, J.; Poulton, D. J.
Smethurst, E., and Budworth, D. W. Preparation of transparent MgO bodies (I) by hot-pressing, (11) 282*f*.
Smets, H. J. F. G., and van der Kooi, A. G. Device for producing stimulated ir emission (iraser) by means of an electric discharge in a gas mixture consisting at least partly of carbonic acid gas and discharge tube for such a device, P (2) 40*b*.
Smirnov, V. M. See Menchikov, L. P.
Smith, Arthur M., and Streib, W. C. Method of pelletizing serpentine chrysotile fines and pelleted products thereof, P (3) 61*a*.
Smith, Albert R. Production of α-quartz-cristobalite SiO_2 for pottery, P (8) 198*h*.
Smith, Archibald W. Optical nonlinear devices, P (1) 14*b*.
Smith, Bernard. Glass laser window sealant technique, P (3) 58*j*.
Smith, Bob H., and Reginato, L. L. Si diode protection means, P (1) 14*d*.
Smith, Bradford K. Process for coating flatlike surface [CRT], P (7) 162*h*.
Smith, D. C. See Combe, E. C.
Smith, Douglas. See Boyd, F. R.
Smith, Douglas E. See Gibbons, E. F.
Smith, D. G. W. See O'Nions, R. K.
Smith, David H. See Bobeck, A. H.
Smith, Dennis W. See Riebling, E. F.
Smith, Everett C. See Christensen, R. W.
Smith, Frank T. J. See Gerstenberg, D.
Smith, Gail P. See Beall, G. H.
Smith, G. Pedro. See Braunstein, J.
Smith, G. V. See Ainger, F. W.
Smith, Howard C., and Allan, W. B. Method for making glass tubes, P (1) 4*j*.
Smith, Howard J., and Spencer-Strong, G. H. Preventing scumming in TiO_2-opacified porcelain enamels, (7) 157*h*.
Smith, Harold R. See Herczog, A.
Smith, James C. See Keig, G. A.
Smith, Joseph E. Composite punch for powder compacting press, P (11) 277*g*. Die and punch assembly for compacting powder material, P (9) 229*j*.
Smith, J. F. Educational and public relations aspects of Pb glaze research and surveillance, (1) 9*i*.
Smith, John I. Microwave loaded line ferrite phase shifter, P (6) 139*h*.
Smith, Jonathan S., II. See Mazdiyasni, K. S.
Smith, Luther W. Light modulation in optic fiber, P (6) 133*e*.
Smith, Mark J. See Trask, R. B.
Smith, Morton C. See Wagner, P.
Smith, Peter C., and Moore, Robert E. High-temp. compressive creep apparatus, (1) 17*i*.
Smith, P. J. See Howard, J. K.
Smith, P. K., and Peterson, D. E. High-temp. evaporation and thermodynamic properties of Cm_2O_3, (6) 148*c*.
Smith, R. See Copley, G. J.
Smith, Roy A. See Kizer, D. E.
Smith, Roy E., and Dunn, J. W. Apparatus for processing a plurality of strandlike materials, P (7) 161*g*.
Smith, Robert T. See Hannon, J. J.
Smith, Robert T., and Welsh, F. S. Temp. dependence of the elastic, piezoelectric, and dielectric constants of $LiTaO_3$ and $LiNbO_3$, (4) 99*f*.
Smith, Richard W. Gamma radiation effects in $LiNbO_3$, (1) 11*g*.
Smith, Stanley D. See Seeley, J. S.
Smith, Stephen J. See Spiller, L. L.
Smith, S. R. P. See Davies, J. J.
Smith, S. R. P., Dravnieks, F., and Wertz, J. E. EPR line shape of Ni^{2+} in MgO, (5) 120*i*.
Smith, Sidney T. Thin-film room-temp. electron emitter, P (2) 43*b*.
Smith, Tazzell. See Reade, F. G.
Smith, William N., Jr. Preparation of Li hexafluorophosphate, P (1) 20*g*. Process for preparing Li compounds of the formula $LiMF_6$ where M is As or Sb, P (7) 175*g*.
Smithgall, H. E., and Stone, E. O. Individually hermetically sealed CRTs connected by fiber optics array, P (3) 65*d*.
Smithwick, W. J. Rotary kiln with end and intermediate discharge, P (1) 19*f*.
Smock, G. E. Method for forming an integrated [fibrous] mass, P (10) 245*b*.
Smolker, G. S. See Keister, F. Z.
Smollen, L. E., Larson, R. I., Jr., and Karr, G. H. Composite ir-transmitting stress-free window, P (4) 81*a*.
Smrcek, A. Cast iron for glass molds, (3) 55*c*. Effect of Mo on corrosion of the electrode holder, (8) 190*c*.
Smushkov, I. V. See Livshits, L. I.

Smyly, J. P. Thick-film titanate capacitor composition, P (2) 43*a*.
Snedeker, R. H., Garty, K. T., and Skiermont, F. J. Glass-polycarbonate resin laminates, P (9) 219*d*. Vitreous and organic resin laminates having low-temp. utility, P (3) 60*a*.
Snell, D. S. See Baird, T.
Snelling, E. C. Significance of material properties in ferrite applications, (7) 167*j*.
Snellman, D. L., and Hudson, W. G. Glass fiber cable, P (8) 193*a*.
Snetkov, A. Ya. See Kolomytsev, P. T.
Snitzer, E. Apparatus for controlling the propagation characteristics of coherent light within an optical fiber, P (3) 57*f*. See Landry, R. J.; Robinson, C. C.
Snitzer, E., and Woodcock, R. F. Yb laser device, P (2) 43*c*.
Snodgrass, F. E. See Joo, L. A.
Snow, E. H. See Slaten, G. G.
Snyder, C. A. See Leliaert, R. M.
Snyder, D. G. See Lindberg, J. D.
Snyder, G. E. D., and Bakker, W. T. Permeable refractories, P (3) 61*b*.
Snyder, G. L. Method and apparatus for rotary kiln control, P (2) 45*c*.
Snyder, H. C. See Poole, J. P.
Snyder, M. J. See Niesz, D. E.
Snyder, T. P. See Tarnopol, M. S.
Sobel, J. E. See Hayes, J. C.
Sobel, J. E., and Foley, J. C. Continuous drawing of fibers from a mixture containing an inorganic oxide sol covered by a protective fluid, P (7) 164*b*.
Sobolev, A. S., Kuz'ma, Yu. B., Soboleva, T. E., and Fedorov, T. F. Phase equilibria in Ta, Ti, B and Ta, Mo, B systems, (10) 260*h*.
Sobolev, E. V. See Fedoseeva, T. I.
Sobolev, V. A. See Tertykh, V. A.
Soboleva, T. E. See Sobolev, A. S.
Sobon, L. E. Preparation of rare-earth oxide phosphors of high brightness and cathodoluminescent efficiency, P (11) 275*j*.
Sobon, L. E., Wickersheim, K. A., Buchanan, R. A., and Alves, R. V. Growth and properties of La oxysulfide crystals, (6) 148*j*.
Society of Glass Technology Physical Properties Committee. Survey of bend strength measurements of glass rods, (7) 160*h*.
Soden, R. R. See Greig, W. J.
Soe, Kyaw. See Nvunt, Kan.
Soellner, A. M., Sprouse, J. F., and Raju, T. A. Electron emitter comprising metal oxide-metal contact interface and method for making, P (8) 200*a*.
Soetofte, I. See Larsen, F. K.
Sohn, J. See Honig, J. M.
Sokhatskaya, G. A. See Budnikov, P. P.
Sokolov, O. V. See Lidorenko, N. S.
Sokolov, V. L. See Timofeev, M. M.
Solf, A. See Lehmann, H.
Solmi, F. Process for mfg. glazed ceramic bodies, in particular tiles, with only one firing, P (4) 86*a*.
Solomon, D. H. Surface-modified clays and methods of making, P (3) 72*b*.
Solomon, P. R., Shaw, M. P., and Grubin, H. L. Shaped bulk negative resistance device oscillators and amplifiers, P (1) 14*c*.
Solomon, R. Push-pull structure for solution epitaxial growth of III-V compounds, P (9) 227*b*.
Solovyev, G. I., and Spear, K. E. Phase behavior in the Sm-B system, (10) 260*f*.
Solt, G. See Rokitansky, K.
Solt, P. E. Airlift blending apparatus, P (6) 141*g*.
Soltys, Z. See Szmid, Z.
Somasundaran, P., and Lin, I. J. Effect of the nature of environment on comminution processes, (11) 276*i*.
Sombret, C. See Bonniaud, R.
Somer, T. A. Low energy particle counter with 2-dimensional position sensing, P (10) 251*c*.
Sominskii, E. A. See Gorshkov, V. S.
Somiya, Shigeyuki. See Miyagawa, Saburo; Okikawa, Shinji; Sugai, Mikio.
Somiya, Shigeyuki, Hirano, S., and Anzai, K. Solid solubility of $Ti_2Cr_2O_7$ in the system TiO_2-Cr_2O_3, (6) 151*g*.
Somiya, Shigeyuki, Yamamoto, T., Sanogawa, T., Hiyama, Y., and Amemiya, Y. Present status of steel plant refractories in Japan, (1) 8*c*.
Sommerville, I. D., and Kay, D. A. R. Activity determinations in the CaF_2-CaO-SiO_2 system at 1450°C, (6) 144*j*.
Somodi, Z. Effect of rapid firing on the structure of porcelain, (7) 165*h*.
Somos, I. See De Cecco, A. L.; McIntyre, J. E.
Sonn, M. See Huang, I-Der.
Sonneborn, K. J. See Blumenfeld, M. A.
Sonntag, A. See Borchert, E.
Sopin, A. A. See Menchikov, L. P.
Sorrell, C. A. PbO transformation induced by H_2O, (2) 48*d*. See Ackermann, R. J.
Sosniak, J. Technique for the deposition of GaP resistive films by cathodic sputtering, P (1) 15*b*.
Souchay, P. See Boyer, M.
Souchet, R. See Meunier, G.
Soukup, J. See Kolomaznik, K.
Souri, Hiroshi. Multicolor plasma display panel, P (10) 245*f*.
Southgate, P. D., Hall, D. S., and Dreeben, A. B. Hot-electron distribution in *n*-GaAs derived from photoluminescence measurements with applied electric field, (6) 149*d*.
Sovers, O. J., and Yoshioka, T. Host cation effects on the fluorescence spectrum of Eu^{2+} in oxysulfides, (4) 96*j*.
Sovetov, N. M. See Sovetova, L. V.
Sovetova, L. V., and Sovetov, N. M. Formation of a magnetite film on Fe, (10) 249*c*.
Sowko, J. J., Sr. Method for the low-temp. joining of carbides, P (4) 84*e*.
Sowman, H. G., and Johnson, J. R. Method of making spherules of a crystalline nuclear fuel carbide, P (4) 91*h*.
Spacil, H. S., Hellman, W. R., and Buccilli, P. R. Jacketed alkali metal halide vapor lamp with getter, P (3) 58*e*.
Spain, R. G. C composite structure including a band of helically wound C fibers, P (5) 109*f*.
Spangler, E. G., Moore, M. M., and Topp, R. L. Refractory-ceramic composition and method, P (1) 9*c*.
Spanhoff, G. A. See Nienhuis, W. F.
Spanoudis, L. Method of thermal tempering transparent glass bodies, P (3) 59*g*. Process of making glass lasers of increased heat dissipation capability, P (8) 193*j*. See Jagodzinski, R. F.
Sparks, A. K. See Hayes, C. M.
Sparks, C. R. Reinforcement of structures with coatings of glass fibers and resin, P (3) 59*e*.
Sparks, L. L., and Hust, J. G. Thermoelectric voltage of Ag-28 at.% Au thermocouple wire, SRM 733, vs common thermocouple materials (between liquid He and ice fixed points), (9) 231*a*.
Sparks, L. L., and Powell, R. L. Low temp. thermocouples: KP, "normal" Ag, and Cu versus Au-0.02 at.% Fe and Au-0.07 at.% Fe, (10) 255*f*.
Speakman, K., and Majumdar, A. J. Morphology and microstructure of synthetic kilchoanite, (1) 23*c*.
Spear, K. E. See Leitnaker, J. M.; Solovyev, G. I.
Spear, K. E., and Leitnaker, J. M. Equilibrium investigations of C-rich V(C,N) solutions, (4) 96*d*.
Spear, K. E., Leitnaker, J. M., and Lindemer, T. B. Phase behavior of the U-V-C system and the thermodynamic properties and crystal structure of UVC_2, (8) 203*d*.
Spear, W. E. Drift mobility techniques for the study of electrical transport properties in insulating solids, (3) 72*f*.
Speelman, I. A. Beveled edge microscope slide, P (10) 243*i*.
Speidel, D. See Garcia, D.
Speidel, E. O. See Kizer, D. E.
Speidel, H. See Reichelt, W.
Speigel, K. See Gallaro, A. V.
Speight, M. V. Calculation on the size distribution of intragranular bubbles in irradiated UO_2, (7) 171*a*.
Spenadel, L. See Higgins, J. J.
Spencer, D. R. F., Beamond, T. W., and Coleman, D. S. Solubility of CaO in MgO and its effect on the CaO-MgO-SiO_2 system at 1800°C, (2) 49*c*.
Spencer, E. G. See Bobeck, A. H.
Spencer-Strong, G. H. See Smith, Howard J.
Spengler, A. F., Jr., and Young, W. P. Use of rare earth elements for reducing nozzle deposits in the continuous casting of steel process, P (3) 61*g*.
Spengler, C. J., and Bratton, R. J. Microcharacterization of the reaction zone between UO_2 and Ni-Ti alloy, (7) 171*j*.
Speyer, F. B. In situ carbiding of pyrolyzed composites, P (6) 131*c*.
Spicak, K., and Kunes, K. Examination of the working properties of the porcelain batches, (3) 61*i*.
Spielberg, D. H. See Youtsey, K. J.
Spiller, L. L., and Smith, Stephen J. Electrostatic coating method, P (10) 244*e*.
Spinski, V. Photographs on ceramic or ceramic-like surfaces, P (10) 248*h*.
Spiridonov, F. M., Komissarova, L. N., Kocharov, A. G., and Spitsyn, V. I. System HfO_2-Y_2O_3, (8) 211*f*.
Spit, B. J., and van der Knaap, S. C. Microstructure of cellular concrete, (4) 79*d*.
Spiteri, J. Lamp with support for filament to extend life of filament and envelope filled with Kr and/or Xe, P (7) 162*f*.
Spitsyn, V. I. See Spiridonov, F. M.
Spitsyn, V. I., Murav'eva, I. A., Kovba, L. M., and Korchak, I. I. Reaction of rare earth oxides with Na_2O, (1) 24*e*.
Spitzer, W. G. See Mitchell, I. V.
Splichal, K. See Ondracek, G.
Spooner, P. See Dollimore, D.
Sposobnyi, V. V. See Kruglitskii, N. N.
Sprague, J. W. Method of stabilizing semiconductor devices, P (4) 89*b*.
Spridco, J. P., and Mancewicz, T. A. Method of making multilayer printed circuits, P (1) 13*f*.
Spriggs, R. M. See Penty, R. A.; Steiner, C. J. P.
Springfield, R. L. Thermocouple guide, P (5) 116*h*.
Sprouse, J. F. See Soellner, A. M.
Spruiell, C. E., Jr. See Lamont, W. E.
Squiers, D. J. Electrothermal time proportioning temp. control, P (1) 18*f*.
Srinivasan, G. R. See Aggarwal, I. D.
Srivastava, C. M. See Murthy, N. S. S.
Srivastava, G. P., Mathur, P. C., and Kumar, A. Faraday rotation in artificial dielectrics, (5) 111*j*.
Srivastava, K. K., Wright, G. F., Khanna, S. L., Krishan, I., and Nayar, R. K. Simple and quick method for the dielectric study of solid powders, (7) 173*g*.
Srivastava, R. D. See Farber, M.
Srivastava, R. D., Uy, O. M., and Farber, M. Effusion-mass spectrometric study of the thermodynamic properties of BO^- and BO_2^-, (4) 96*f*.
Srivastava, S. P., and Singh, R. D. Infrared lattice vibrational spectrum of CaO, (3) 73*i*.
Sroubek, Z. See Calvo, R.
Sroussi, R. See Lagrange, A.
Staats, W. R. See Kweller, E. R.
Stacy, D. W. See Manning, W. R.
Stacy, D. W., Johnstone, J. K., and Wilder, D. R. Axial thermal expansion of HfO_2, (10) 258*c*.
Stadler, G., and Vogg, E. Mn-Zn ferrite core, P (10) 251*e*.
Stadler, H. L. See DeLosh, R. G.
Stadlmann, G. See Kuebel, E.
Staerk, K. Some more piezoelectric materials, (2) 39*b*.
Stafeev, V. I. Semiconductor device, P (11) 275*e*.
Staffansson, L. I. Method for solubility measurements in a 2-phase liquid system, (11) 278*a*.
Staffin, R., Ricci, R. J., and Juels, R. J. Particle analyzing apparatus and method, P (10) 256*b*.
Stafsudd, O. M. See Gentile, A. L.
Stafsudd, O. M., Leung, A. F., and Wong, E. Y. Absorption spectrum of NpO_2^{2+} in $Cs_2UO_2Cl_4$, (5) 118*d*.
Stahl, F. T., Steffen, H. M., Schneble, F. W., Jr., and McCormack, J. F. Base material and method for the manufacture of printed circuits, P (3) 64*h*.
Stahr, D. F. Semiconductor devices having low minority carrier lifetime and process for producing, P (8) 202*i*.
Stahr, D. F., and Yandrick, R. M. Method and apparatus for machining articles [wafers], P (1) 13*a*.
Stalego, C. J. Apparatus for producing glass filaments with auxiliary heating means, P (10) 243*g*.
Stalego, C. J., and Wyckoff, R. E. Apparatus for producing curly glass fibers, P (7) 161*h*.
Stalego, J. P. Filamentizing process for glass fibers, P (4) 81*h*. Moldable article of glass fibers and a modified phenolic binder, P (2) 34*h*. Process for producing air-blown glass fiber strand mat, P (10) 245*d*.
Staley, W. W. See Shamash, M. B.
Stalnitz, D. See Becke, H. W.
Stalony-Dobrzanski, J. A. Regenerative thermocouple sensor, P (7) 174*a*.
Stancioff, D. J., and Witt, H. J. TiO_2 suspensions, P (8) 207*i*.
Stanczyk, M. H. See Palumbo, F. J.
Stanczyk, M. H., and Feld, I. L. Ultrafine grinding of several industrial minerals by the attrition grinding process, (11) 277*a*.
Stander, C. M. Co oxide catalysts, P (8) 207*c*.
Standifer, R. L. See Heady, O. E.
Standley, C. L. See Gregor, L. V.
Stanek, J. Dependence of temp. distribution on different electrode types on a completely electric glass tank, (8) 189*f*.
Stankavich, A. J. Process of producing an electrical resistor, P (3) 67*c*.
Stankun, A. V. See Meshengisser, M. Ya.
Stanley, C. C. Production of a line pattern on a glass plate, P (9) 219*f*.
Stanyon, H. E. See Beeson, E. J. G.
Stanyon, H. E., Robinson, K. B., and Beeson, E. J. G. Xe lamp, P (8) 194*a*.
Staples, B. G. Design and operation of corrosion-resistant equipment for high-pressure service, (1) 16*h*.
Stark, D. S. Tritium- and deuterium-impregnated targets for neutron generators, P (11) 276*e*.
Stark, J. P. Thermal diffusion in concentrated solid solutions, (6) 152*c*.
Stark, R. A. See Callahan, J. P.
Starkey, H. C. See Carroll, D.
Starliper, R. L. Method and circuit for measuring effective capacitance of a semiconductive device, P (2) 41*a*.
Starnes, P. E. Apparatus for testing and regulating the flow of powdered material, P (1) 18*d*.
Staron, J. Basic refractories for vacuum containers in steel production, (5) 108*h*.
Starosel'skii, G. L. See Makaruk, A. F.
Starr, C. D., and Wang, Teh Po. Thermocouple for nuclear environment, P (10) 254*b*.
Starr, E. W. See Hawkins, C. T.
Starr, F. C., Jr. See Brushek, D. K.
Stastny, F. See Gaeth, R.
Statz, H. F. See Drangeid, K. E.
Stavropol'skaya, L. E. See Syrkin, Ya. M.
Steadman, R., Tilley, R. J. D., and McColm, I. J. Series of orthorhombic Sn-W bronzes, (10) 260*j*.
Steane, J. M. Firing a medieval kiln, (4) 77*j*.
Stech, H. G. See Brown, Charles E.
Steck, R. E. Friction material [asbestos], P (3) 61*e*.
Steele, B. C. H., and Floyd, J. M. O self-diffusion and electrical transport properties

of nonstoichiometric CeO_2 and CeO_2 solid solutions, (9) 237*i*.
Steele, T. G. See Piazza, J. R.
Steen, A. Method for treating a broken-away refractory lining of a metallurgical furnace, consisting of dolomite bricks, P (8) 196*e*.
Steffen, H. M. See Stahl, F. T.
Steffen, J., and Hofer, A. Method for the fabrication of holes in a workpiece by means of laser beams and apparatus for the performance of the method, P (8) 204*a*.
Steffensen, L. M. See Petermann, J. P.
Stefkova, V. See Novak, J.
Steggewentz, H. Device for epitactic precipitation of semiconductor material, P (9) 225*b*. See Widmann, D.
Steidel, C. A. Thin-film resistors, P (4) 91*c*.
Steimer, A. See Voigt, O.
Stein, B. F. Growth and some magnetic properties of GdIG films, (4) 86*i*; erratum, (7) 167*b*.
Stein, F. P. See Hutchinson, R. W.
Stein, H. N. Thermodynamic considerations on the hydration mechanisms of Ca_3SiO_5 and $Ca_3Al_2O_6$, (7) 157*g*. See Cornelisse, C. W.; van der Wielen, J. C. T. G. M.
Stein, H. N., Cornelisse, C. W., and Stevels, J. M. Rheological behavior of glasses, (3) 57*d*.
Stein, Lawrence. Method of preparing oxidized radon solutions, P (8) 203*d*.
Stein, Leonard. See Sirrine, R. C.
Stein, W. W. See Kinoshita, Joshyo.
Steinberg, D. R., and Sutton, W. T. Means for securing planar member to CRT faceplate, P (8) 193*g*.
Steinbruegge, K. B. See Hopkins, R. H.
Steine, H. T. See Eschnauer, H. R.
Steinemann, S. Implants of Ti or a Ti alloy for the surgical treatment of bones, P (6) 136*b*.
Steiner, C. J. P., Spriggs, R. M., and Hasselman, D. P. H. Synergetic pressure sintering of Al_2O_3, (3) 75*g*.
Steingiser, S. See Cass, R. A.; Ray, J. D.
Steingiser, S., Phillips, R. J., and Cass, R. A. Heat treatment of graphite fibers, P (4) 84*a*.
Steinkamp, R. A. See Insolio, T. A.
Steinmaier, W. See Le Can, C. J. P. F.
Steinmueller, R. E. See Dietert, H. W.
Steitz, W. R., Bradley, R. O., and Waterworth, T. H. Electric glass furnace, P (4) 81*f*.
Stella, A., and Gustinetti, A. Room-temp. electrophotoluminescence in KCl, (6) 151*d*.
Stelmakh, S. I. See Tsimmergakl, V. A.
Stelzer, E. L. See Scott, M. W.
Stepan, E. See Schroll, E.
Stepanov, S. A. See Galimov, D. G.
Stepanov, V. F. See Yam, V. M.
Stephanoff, N. N. Angular impact fluid energy mill, P (10) 254*h*. Constant acceleration fluid energy mill, P (6) 141*d*. Fluid energy drying mill, P (9) 230*c*.
Stephens, A. E., Mackey, H. J., and Sybert, J. R. Effects of contact placement and sample shape in the measurement of electrical resistivity, (5) 116*c*.
Stephens, E. J. Glassware inspection apparatus employing fiber-optic guides, P (5) 107*h*.
Stephens, R. E. Nd_2O_3-BaO catalyst composition, P (10) 257*j*.
Stephenson, A. Spontaneous magnetization curves and Curie points of spinels containing 2 types of magnetic ion, (10) 261*c*.
Stephenson, B. J. Monolithic capacitors, P (3) 66*b*.
Stephenson, M. J. See Anderson, L. W.
Sterling, H. F., Alexander, J. H., and Hazelden, D. W. J. Composite dielectric electrolytic capacitor, P (2) 39*h*.
Sterling, H. F., and Swann, R. C. G. Method of forming Si oxide coatings in an electric discharge, P (7) 169*h*.
Sterlyadkina, Z. K., Alekseeva, L. S., and Mikheeva, V. I. Reaction of Cr trichloride with Na tetrahydroborate, (8) 210*j*.
Stern, D. R., Gundzik, R. M., Jones, Peter M., and Lynskey, P. J. Process for mfg. TiO_2, P (2) 46*c*.
Stern, F. Externally excited [semiconductor] luminescent devices, P (1) 12*c*.
Sternberg, J. C. See Ray, R. A.
Stetka, D. G. See Shaw, E. J.
Stetson, K. A. Method for measurement of surface profile change using a vernier scale in hologram interferometry, P (2) 45*c*.
Steuetz, D. E., Belohlav, L. R., and Reader, A. M. Continuous production of uniform graphite fibers, P (4) 81*i*.
Stevels, J. M. See Cornelisse, C. W.; Stein, H. N.; van der Wielen, J. C. T. G. M.
Stevens, B. Instrument for determining O quantities by measuring O quenching of fluorescent radiation, P (2) 45*a*.
Stevens, C. E. Apparatus for ornamenting glass articles, P (10) 243*f*.
Stevens, D. N., Bisque, R. E., and Bloom, D. N. Process for the recovery of diamond particles from Al_2O_3 or silicate wastes, P (6) 127*h*.
Stevens, G. L. Method of treating cathodoluminescent phosphors, P (5) 113*c*.
Stevens, M. T. See Paksswer, S.
Stevens, R. Neutron irradiation damage in SiC whiskers, (10) 260*c*.
Stevens, R. N. Grain-boundary sliding and diffusion creep in polycrystalline solids, (6) 148*h*.
Stevens, R. P. Application of an empirical correction procedure to electron probe microanalysis of chromites in periclase-chrome brick, (8) 194*j*.
Stevens, T. J., and Holland, A. E. Moisture expansion of fired clay—experiments in controlled environments, (9) 229*i*.
Stevenson, H. See Uttecht, R.
Stevenson, J. F. Glass furnace with triple batch charging and method, P (9) 219*c*.
Steverding, B., and Lehnigk, S. H. Collision of stress pulses with obstacles and dynamics of fracture, (6) 145*a*.
Stewart, C. E. E. Observations on the dislocation etching of $GaAs_{1-x}P_x$ epitaxial layers, (7) 179*i*. Stoichiometric effects in the growth of doped epitaxial layers of $GaAs_{1-x}P_x$, (7) 181*b*.
Stewart, D. A., and Maloney, B. A. Production of Na carbonate, P (7) 176*b*.
Stewart, I. M. Structural analysis, (9) 238*h*.
Stewart, J. E., Evans, D. E., and Larson, G. L. Remote radiation temp. sensor, P (4) 93*g*.
Stewart, J. L., Mazzoni, R. J., and Schutrum, L. F. Method for purging and filling multiple glazed units, P (11) 270*f*.
Stibbs, D. Transition metal boride compositions, P (6) 135*h*.
Stich, H., Ruckensteiner, K., Binder, W., and Huetter, J. Process for mfg. cement clinker of low F content, P (7) 157*e*.
Sticher, H. See Barrer, R. M.
Stickney, W. A. See Elger, G. W.
Stieber, H. C., and Belz, H. M. Asymmetric joint for connecting C electrodes, P (2) 37*d*.
Stiefken, C. E. Method for preparing an asbestos fiber product of improved filtration characteristics, P (6) 144*c*.
Stiehler, R. D. History of measurement and the SI units, (2) 50*g*.
Stiehm, R. W. See Douglas, F. C.
Stiglich, J. J. See Rankin, D. T.
Stiglitz, P. Application of high-Al_2O_3 cement—how to prevent dangers due to its transformations, (7) 155*i*. Method of preparing concretes of stable aluminous cements, P (6) 130*f*.
Stiglitz, P., Sadran, G. H., and de Saint-Chamant, H. Method for stabilizing aluminous cements and cements obtained, P (8) 188*f*.
Stijntjes, T. G. W. See Klerk, J.
Stiles, A. B. See McClellan, W.
Stiles, P. J. See Howard, W. E., Jr.
Still, J. E. See Creer, M. H.
Stilley, G. W., and Eilenfeld, H. W. Method and apparatus for bending glass sheets, P (1) 4*c*.
Stillman, G. E. See Wolfe, C. M.
Stinchcomb, W. W., and Queeney, R. A. High-temp. fatigue fracture initiation in MgO single crystals, (2) 48*e*.
Stirrat, A. Y. [Vacuum] casting apparatus, P (2) 44*d*.
Stober, W. Method of producing monodisperse SiO_2 spheres having a dispersed radioactive tracer, P (4) 9 *i*.
Stockdale, G. F. See Carlson, D. E.
Stocker, H. J. Phenomenology of switching and memory effects in semiconducting chalcogenide glasses, (6) 132*d*.
Stockham, J. D. Composition of glass furnace emissions, (4) 80*d*.
Stockham, J. R. See Hayes, R. R.
Stoddart, D. E. See Crouch, A. G.
Stoebe, T. G. See Fotedar, H. L.
Stoeckmann, H. See Decker, H.
Stoermann, J. See Schaefer, H.
Stoicanescu, C. See Balta, P.
Stojanowski, R. See Szmid, Z.
Stokowski, S. E. See Henderson, B.
Stokowski, S. E., and Schawlow, A. L. Dielectric-related optical line shifts in $SrTiO_3$:Cr^{3+}, (5) 119*j*. Spectroscopic studies of $SrTiO_3$ using impurity-ion probes, (5) 124*c*.
Stoller, A. I., and Opresko, S. T. Method and material for etching semiconductor bodies, P (10) 251*j*.
Stoller, A. I., and Schilp, W. H., Jr. Heat seal of a glass member to another member, P (4) 88*c*. Method for isolating semiconductor devices from a wafer of semiconducting material, P (3) 65*h*.
Stoller, H. M., and Frye, E. R. Processing of C/C composites—an overview, (11) 271*f*.
Stolte, G. See Ruettiger, K.
Stomberg, R. See Svensson, B.
Stone, E. O. See Smithgall, H. E.
Stone, F. S., and Vickerman, J. C. Magnetic properties of Cr ions in oxide matrices (I) Cr_2O_3-Al_2O_3 solid solutions, (1) 23*i*.
Stoneham, A. M. See To, Kin-Ching.
Stong, G. E. Magneto-optical elements and glasses, P (8) 193*f*. See Foster, G. F.
Stookey, G. K. See Muhler, J. C.
Stookey, S. D. See Araujo, R. J.; Garfinkel, H. M.; Rothermel, D. L.
Storhok, V. W. See Chubb, W.; Hilbert, R. F.
Stork, F. Method of producing contacts, P (6) 139*e*. Method of producing a semiconductor device, P (4) 89*f*.
Storm, A. R. See Robbins, M.
Storm, H. F. Interdigitated structures for gate turnoff thyristors and for transistors, P (2) 40*e*.
Storm, J. Spray dried press body, (6) 136*c*.
Stormont, R. W. See Cocks, F. H.
Storms, E. See DePoorter, G. L.
Storms, E., Calkin, B., and Yencha, A. Vaporization behavior of the defect carbides (I) Nb-C system, (4) 99*j*.
Story, H. S. See Rexford, D. G.
Stoute, R. L. See Hastings, I. J.
Straarup, O. See Moeller, A.
Strack, H. A. See Cox, R. H.
Strack, H. A., and Clark, G. D. Junction laser devices having a mode-suppressing region and methods of fabrication, P (3) 65*g*.
Strack, R. R. Leachable bundle of optical fibers, P (7) 162*f*. Method of fabricating illuminated fiber optics, P (10) 245*a*. Method for producing flexible image-transporting fiber-optic conduit, P (9) 214*c*.
Strack, R. R., and Phaneuf, R. A. Flexible fiber-optic conduit, P (3) 58*b*.
Strain, F. See Hoekje, H. H.
Strain, R. J. See Krambeck, R. H.
Strakhov, L. P. See Avetikyan, G. B.
Strakhov, V. I. See Klyucharov, Ya. V.
Strauss, G. See Preisler, E.
Strauss, H. S. Seal structures for electric discharge lamps, P (10) 245*f*.
Straw, R. A. See Kummer, G. L., Jr.
Strazza, N. P. Method of fabricating porous metal bodies, P (7) 171*f*.
Strebkov, D. S. See Lidorenko, N. S.
Streever, R. L. NMR studies of ^{57}Fe in Ba ferrite, (6) 150*c*.
Strehlow, W. H. Method of chemically polishing crystals of IIB-VIA system, P (4) 88*e*.
Streib, W. C. See Smith, Arthur M.
Strekalov, A. V. See Bondarev, K. T.
Strenglein, H. F., and Palka, F. M. Limiter-stabilized oscillator, P (4) 88*a*.
Strickler, D. W., and Roy, R. New family of photoconducting oxide glassy materials, (7) 160*e*.
Striebel, W. K., and Loch, W. H_2O-repellent cement and soils, P (8) 183*g*.
Stringfellow, G. B., and Greene, P. E. Quasi-chemical equilibrium calculation of the Ge-Si-Sn and Ge-Si-Pb ternary phase diagrams, (9) 238*c*.
Strittmatter, D. J. See Anderson, R. C.
Strnad, Z. Determination of the solubility of CO_2 at various partial pressures in Na_2O-SiO_2 melts using gas chromatography, (7) 158*g*.
Strnad, Z., and Dusil, J. Behavior of dissolved H_2O in E-glass and its relation to the secondary bubble formation in the drawing furnace, (3) 54*j*.
Strnat, K. See Ray, A. E.
Strobel, R. F. Series-type electric incandescent lamp with integral automatic cutout means, P (2) 35*b*.
Strohl, R. I. See Hance, P. R.
Strott, D. B. See Trimble, C. H.
Stroud, J. S., and Lell, E. Optical absorption of Pb in glass, (1) 3*g*.
Stroup, R. F., Clingman, W. H., Jr., and Post, R. C. Method for forming adherent TiC coatings on metal or composite substrates, P (11) 272*f*.
Strouse, W. M., and Tobias, I. Method and apparatus for eliminating dominance of laser oscillations at one wavelength over those at another, P (3) 65*c*.
Strubhar, P. D. See Hoelscher, M. W.
Strudwick, P. See Hill, G. J.
Struillou, R. See Baron, A.
Strull, G. Bipolar-unipolar transistor structure, P (8) 200*d*. Process for producing a Cs-coated GaAs photocathode, P (10) 252*b*.
Strumbos, W. P. Multiple heat range spark plug, P (2) 41*h*.
Strunk-Lichtenberg, G. See Beckmann, B.
Stryker, F. J. See Chapman, D. W.
Stuart, G. L. See Thornton, L.
Stuart, J. L. See Woodham, G. W.
Stuart, W. I., Whately, T. L., and Adams, R. B. Adsorption of fluoride on ThO_2 and its effect on hot-pressed density, (9) 233*e*.
Stubican, V. S. See Schultz, A. H.
Stuby, K. P. Hourglass-shaped conductive connection through semiconductor structures, P (6) 138*a*.
Stuetz, D. E. Direct production of graphite fibrous materials from preoxidized acrylic fibrous materials, P (8) 196*h*.
Stuijts, A. L. Renaissance in ceramic technology, (9) 224*d*.
Sturel, B. See Guillet, H.
Sturhahn, H. H. See Hennicke, H. W.
Sturlason, L. V. See Petersen, J. H.
Sturm, B. J. See Butler, C. T.
Sturm, B. J., Quincy, R. B., Jr., and Butler, C. T. Preparation of high-purity MgO powder of high bulk density, (7) 171*c*.
Stuve, J. M. See Pankratz, L. B.
Suarez, C. B., and Grinfeld, R. Contribution to the study of GdO band spectrum, (7) 176*e*.
Subbarao, E. C. See Maiti, H. S.; Ramani, S. V.
Subbarao, E. C., Chakravorty, D., Merriam, M. F., Raghavan, V., and Singhal, L. K. Experiments in Materials Science, B (10) 263*j*.
Subba Rao, G. V. See Rao, G. V. S.
Subbarao, K. V. Kunavaram series—a group of alkaline rocks, Khammam district, Andhra Pradesh, India, (8) 209*c*.
Suchoff, L. A. Method of making Li ferrite powders, P (1) 13*c*.
Suchowski, K. Beneficiation of clays contaminated with naturally occurring foreign substances, (5) 117*c*. Question of hot [plastic] shaping, (9) 229*d*.
Suda, Naoki. See Yoshioka, Tsunehiko.

Sudo, Tsuneta. See Mizushima, Yoshihiko.

Sudoh, Giichi, Asahara, N., and Senda, M. Studies on sample preparation technique and application of mathematical correction method for fluorescent X-ray analysis, (10) 255*d*.

Sudoh, Giichi, and Nakamura, T. Hydration products in the system $C_4A_3(SO_3)$ or CA-$Ca(OH)_2$-$CaSO_4$-R_2SO_4 and the presence of K_2O-bearing Ca monosulfoaluminate hydrate, (9) 214*a*. Influence of curing temp. on the expansion due to hydration of $C_4A_3(SO_3)$, (4) 78*j*.

Suemune, Yasutaka. Hot-pressing of Ni-Zn ferrites, (3) 63*a*.

Suenaga, Masanobu, Machii, T., Sawano, T., Kobayashi, T., Dengo, T., and Nakai, T. Laminated semiconductor structure, P (6) 138*c*.

Suga, Hiroshi. See Onodera, Natsuo.

Sugahara, Yujiro, Maeno, M., Eguchi, S., and Kurosaki, H. Dry acid treatment process for Al_2O_3-SiO_2 type clay, P (3) 71*i*.

Sugai, Mikio, Naito, R., Hirano, S., and Somiya, S. Phase relations in the system ZrO_2-SiO_2-TiO_2, with special reference to the system $ZrSiO_4$-TiO_2, (6) 150*g*.

Sugaike, Suezo, and Imai, A. β-Al_2O_3—characteristics and applications, (6) 143*e*.

Sugano, Izuru. See Akashi, Tsuneo.

Sugano, Izuru, Akashi, T., Matsubara, T., Kenmoku, Y., and Okuda, T. Oxide magnetic materials, P (7) 169*h*.

Sugano, Keiichi, Ohmori, T., and Yuge, Y. Halogen cycle incandescent lamps, P (3) 58*b*.

Sugano, Satoru. See Uesaka, Yasutaro.

Sugano, Satoru, Aoyagi, K., and Tsushima, K. Exciton absorption lines in antiferromagnetic rare-earth orthochromites (with particular reference to $YCrO_3$), (3) 73*g*.

Sugata, Eizi. See Nomura, Setsuo.

Sugawara, Kastuyuki. See Okuda, Kensuke.

Sugihara, Jun. See Tanizake, Mikio.

Sugihara, Kanji. See Sato, Kunio.

Sugimoto, Koichi. Method of nondestructive examination of specimens, P (3) 70*e*.

Sugimura, Takashi. See Maki, Iwao.

Sugita, Kiyoshi. Recent trends in refractories for the iron and steel industry, (6) 134*g*. See Ohba, Hiroshi.

Sugita, Tatsuzo. See Asano, Shunkichi.

Sugiura, Kozo, and Kunimoto, K. Bloating behavior of shale from Uchida mine, (6) 128*a*.

Sugiura, Seiji. See Hasaba, Shigemasa.

Sugiyama, Hiroshi. See Nanamatsu, Satoshi; Yamane, Mikiya.

Sugiyama, Kohzoh. See Takahashi, Takehiko.

Sugiyama, Sachio. See Kito, Masao.

Suire, J. Reactions between glass and HF, (2) 32*h*.

Sujto, Hideaki, and Gaskell, D. R. Thermodynamics of melts in the system VO_2-V_2O_5, (6) 152*e*.

Suits, J. C., and Lee, K. Giant magneto-optical Kerr effect in EuO, (6) 148*h*.

Sukegawa, Tokuzo. See Nishizawa, Jun-ichi.

Sukhareva, G. E. See Markovskii, L. Ya.

Sukharevskii, B. Ya. See Gavrish, A. M.

Sukhikh, L. L. See Marek, B. A.

Suladze, I. Sh. See Kutateladze, K. S.

Sulinski, H. V. Shell mold composition, P (8) 197*c*.

Sullivan, G. A. Diffusion and solubility of Cu in CdS single crystals, (5) 119*e*.

Sullivan, J. C. See McCombs, F. P.

Sullivan, M. V. See Peters, F. G.

Sullivan, P. M. See Palumbo, F. J.

Sultanyan, T. A. See Chaporova, I. N.

Sumi, Kenshiro. See Moriki, Juichi.

Sumikama, Sadao. Heat flowmeter, P (10) 255*j*.

Sumita, Minoru. See Zenbutu, Sakae.

Sumiyoshi, Yoshiro. See Watanabe, Koichi.

Summerling, R. A. See Clark, E.

Summers, J. J. See Tate, G. L.

Summitt, R. See Luxon, J. T.

Sumoto, Takao. See Uekusa, Genzo.

Sumski, S. See Panish, M. B.

Sun, Kuan H. See Goldstein, N. P.

Sunano, Naomasa, and Nishida, S. Memory- and nonmemory-type switching element, P (4) 88*d*.

Sundberg, D. G. See Green, G. W.

Sunnegren, C. E. Method of making calcined minerals with reduced S content, P (4) 94*j*.

Sunners, B. See Greenstein, B.; Hoogendoorn, H. M.

Sununu, J. H. Temp. control with thermal conductance, (1) 18*b*.

Surina, A. V. See Butt, Yu. M.

Surinova, S. I. See Bering, B. P.

Surkov, M. E., Kharitonov, F. Ya., and Maslennikova, G. N. Stabilizing ZrO_2 with Nd_2O_3 and some properties of the resulting ceramics, (8) 195*j*.

Surls, J. P. See Tveter, E. C.

Sury, F. P. Stopper plug valve [C] for hot metal ladles, P (7) 164*g*.

Sussmann, E. Method of purifying a quartz processing vessel for use in the production of semiconductors, P (6) 133*a*.

Sutarno; Bowman, W. S.; and Alexander, G. E. Effect of forming pressure and of sintering time and temp. on the magnetic and ceramic properties of Sr ferrite, (8) 199*d*. Magnetic and ceramic properties of mixed Ba-Sr ferrites, (8) 199*b*.

Sutch, R. D. See Sharp, D. J.

Sutcliffe, J. Temp. baths for electrical standards, (3) 70*f*.

Sutherland, K. S. Introduction to pneumatic drying, (7) 174*f*.

Suto, Ken. See Okuno, Yasuo.

Sutter, D. M. See Boore, E. J.

Sutton, W. T. See Steinberg, D. R.

Suyunova, Z. E. See Sil'chenko, V. A.

Suzukawa, Yuichi, Kono, H., Terai, K., and Saito, M. Process for the production of spherical Al_2O_3/SiO_2-containing solid particles which are predominantly mullite, P (2) 46*e*.

Suziki, Hideaki. See Henmi, Yoshinori.

Suzuki, Hideo, and Yano, N. Numerical analysis of magnetization characteristics of rods, (11) 274*a*.

Suzuki, Hiromitsu. See Kamiyama, Susumu.

Suzuki, Hiroshige. See Hattori, Takeo; Matsuda, Shinichi; Tanaka, Takaho; Yoshida, Hiroshi.

Suzuki, Ichizo, Yasui, H., and Nanba, K. Optical glass, P (9) 219*f*.

Suzuki, Joji, and Kume, M. Phototropic glass, P (3) 59*b*.

Suzuki, Kazuo. See Okushima, Masaichi.

Suzuki, Kazutaka, and Hira, I. Study of the system $2CaO$-SiO_2-$3CaO$-B_2O_3, (3) 75*g*.

Suzuki, Kazutaka, and Huruhashi, I. β-Ca_2SiO_4 in portland cement clinker, (4) 78*f*.

Suzuki, Kazutaka, Huruhashi, I., and Hujii, T. Alite phase in portland cement clinker, (9) 213*i*.

Suzuki, Kazutaka, Huruhashi, I., and Hukui, H. Study on the X-ray characteristics of Ca_2SiO_4 with the single crystals synthesized and isolated from portland cement clinker, (5) 104*d*.

Suzuki, Kenkichi. See Kumada, Akio.

Suzuki, Kunimoto. See Matsushita, Toru.

Suzuki, Makoto. Electric furnaces for ceramic products, (3) 70*i*. See Iwabuchi, Toshitsugu.

Suzuki, Osamu. See Kanda, Mamoru.

Suzuki, Shigeru. Electron microscope specimen stage which maintains specimen position when subjected to thermal fluctuations, P (2) 44*j*.

Suzuki, Shohachi. See Hara, Ei.

Suzuki, Suguru, Sakamura, H., and Imaoka, M. Free vol of glasses in the systems As-S, As-S-I, and As-S-Tl at transition temps., (6) 131*j*.

Suzuki, Takeyuki, Tatsuno, S., and Saito, S. Sintering by electrolytic heating, (11) 276*j*.

Suzuki, Takuya, Ikeda, M., Furuto, Y., Nagata, Y., and Miura, T. Process for producing Nb-Ti superconducting material, P (11) 275*c*.

Suzuki, Toshiichiro. See Nogi, Takaji.

Suzuki, Toshio. See Kawabuchi, Katsuhiro.

Suzuki, Y. See Fujiki, Yoshinori.

Suzuki, Yoshinori. See Kumagai, Yasuji.

Suzuki, Yoshio. ZrO_2. (6) 143*h*.

Suzuki, Yoshiro, Nagahara, S., and Ichimura, N. Solder glass for adhering, sealing, or coating, P (10) 245*g*.

Svec, J. J. Coronation Brick's new $3.8 million plant already on stream, (5) 108*e*. Delta-Macon launches production of large units, (9) 220*e*. Double "C" (Care and Control) for quality brick, (9) 220*f*. Israeli high-Al_2O_3 refractories at home and abroad, (9) 221*f*. Kiln starts Columbus expansion, (11) 271*c*. Round and round it goes, (2) 35*f*. South African panels easy to make—low cost, (5) 108*d*. Ultramodern plant a symbol of South Africa's brick progress, (5) 108*e*. Where our industry stands [South Africa's brick industry], (5) 108*e*.

Svedberg, P. Thyristor circuit, P (5) 114*c*.

Svejda, H. Determination of Mg in silicate materials by atomic absorption spectrometry, (8) 204*e*.

Svensson, B., and Stomberg, R. Peroxovanadates (I) crystal structure of ammonium μ-oxo-bis(oxodiperoxovanadate(V)), $(NH_4)_4[O(VO(O_2)_2)_2]$, (3) 74*e*.

Svintitskikh, V. E. See Timofeeva, N. V.

Svizela, A. See Kristek, L.

Svoronos, J. Method of recovering Al_2O_3 from alunite and aluminosilicate materials, P (6) 144*d*.

Swamy, R. N. Dynamic Poisson's ratio of portland cement paste, mortar, and concrete, (5) 102*j*.

Swann, R. C. G. See Pitzer, D. C.; Sterling, H. F.

Swanson, A. B., and Loher, R. T. Ramming mixes, P (3) 61*d*.

Swanson, G. D. Fracture energies of ceramics, (2) 47*i*.

Swanson, H. E. See McMurdie, H. F.

Swanson, H. E., McMurdie, H. F., Morris, M. C., Evans, E. H., and Paretzkin, B. Standard X-ray diffraction powder patterns, (3) 70*c*.

Swanson, R. M. See Anderson, W. W.

Swart, R. Method for adjusting capacitance values, P (3) 65*c*.

Swartz, G. A. Bulk semiconductor [GaAs] negative resistance loaded slow wave device amplifiers and oscillators, P (2) 39*d*.

Sweet, L. H., and Baker, N. H., Jr. Furnace wall construction, P (9) 222*f*.

Sweitzer, S. E. Methods for selectively coating ferromagnetic articles, P (4) 89*d*.

Swenson, D. O., and Rau, C. A., Jr. Stress distribution around a crack perpendicular to an interface between materials, (10) 261*f*.

Swenson, E. G. See Ciach, T. D.

Swets, D. E. Crystal growth of tetragonal GeO$_2$, (7) 176*g*. Crystal growth of tetragonal GeO_2 from a flux, P (7) 168*c*. See Albers, W. A., Jr.

Swider, R. A. See Brewer, G. E. F.

Swift, D. J. P., Schubel, J. R., and Sheldon, R. W. Size analysis of fine-grained suspended sediments—a review, (8) 205*e*.

Swift, J. See Cooper, A. R.

Swift, P. See Thomas, J. M.

Swiggard, E. M. See Bishop, S. G.

Swillinger, F. L. Atm tweel seal method and apparatus, P (5) 106*j*. Exit sealing drape for float glass bath, P (10) 244*f*. Float glass method and apparatus for controlling temp., P (3) 58*c*. Float glass plenum chamber closures, P (1) 4*d*. Start-up hood in float glass apparatus and method of using, P (11) 270*j*. Water fence support in float glass apparatus, P (7) 163*a*.

Swirsky, D. M. See Burock, R.

Sybert, J. R. See Stephens, A. E.

Sychev, M. M., and Komlev, V. G. Deformation of materials based on phosphate binders during hardening and heating, (8) 186*d*.

Sychev, M. M., Korneev, V. I., Sirazitdinov, N. S., Yugai, A. F., Yanovskaya, M. S., Kas'yanova, G. N., and Balitskii, V. K. Use of Kara-Tau phosphorites as an alloying additive, (8) 188*a*.

Sykes, E. C. See Sawbridge, P. T.

Sykes, M. Apparatus for use in forming pipes, P (8) 194*g*.

Symons, M. C. R. Structure of trapped-hole centers in γ-irradiated borate glasses, (7) 158*j*.

Syono, Yasuhiko. See Akimoto, Syuniti; Ishikawa, Yoshikazu.

Syono, Yasuhiko, Fukai, Y., and Ishikawa, Y. Anomalous elastic properties of Fe_2TiO_4, (3) 72*d*.

Syrkin, Ya. M. See Satarin, V. I.

Syrkin, Ya. M., Fedoryakin, B. F., Shatokhina, L. P., Novosel'skii, L. G., and Stavropol'skaya, L. E. Development and mastery of technology of fast setting slag portland cement, (8) 186*f*.

Syvakari, P. See Landa, T.

Szabo, A., and Petri, L. Contributions to the creating of new refractory materials technologies and assortments, (3) 60*g*.

Szabo, E. Approx determination of crushing energy from grain structure, (2) 45*j*.

Szabo, T. L. See Slobodnik, A. J., Jr.

Szai, A. P. See Gasparac, R. J.

Szalontai, K. Automation in the glass industry, (2) 32*b*.

Szarras, S. See Szmid, Z.

Szatura, L. See Opoczky, L.

Szczygiel, Z., and Oestvold, T. Determination of the thermodynamic functions of LiCl in LiCl-$MgCl_2$ mixtures from concentration cell measurements, (11) 281*b*.

Sze, S. M. See Coleman, D. J., Jr.

Szedon, J. R. See Chu, Ting Li.

Szego, L. L. Methods of comminuting particulate matter, P (3) 69*e*.

Szegvari, A. Fine grinding apparatus, P (1) 16*i*. Method and apparatus for comminuting and reacting solids, P (9) 230*e*.

Szekely, J. (editor). Blast Furnace Technology—Science and Practice, B (8) 212*f*.

Szente, P. A., and Joly, R. Wide band stop band filter including a ferrite region biased by a graded magnetic field, P (9) 228*d*.

Szilj, F. See Revay, M.

Szikszay, G. Problems of concrete mfg. and aggregate classification, (6) 129*j*.

Szklarz, E. G. See Krikorian, N. H.

Szmid, Z., Szarras, S., Stojanowski, R., and Soltys, Z. Detection of strains in Si epitaxial layers by X-ray diffractometry, (10) 258*d*.

Sznajd, J. Landau theory of the 2d-order magnetic phase transitions in uniaxial ferromagnets with external field, (6) 149*i*.

Sztankovics, L. Electrotechnical Al_2O_3 ceramics—TITMALOX, (5) 110*d*.

Szupillo, R. E. Cr-filmed glass articles and method for making, P (6) 132*c*. Microcircuit [Fe_2O_3] mask and method, P (10) 252*e*.

Szydlo, N., and Poirier, R. Internal photoemission measurements in a metal-Al_2O_3-Si system, (7) 178*a*.

Szymanski, H. A. See Alpert, N. L.

Tabata, Hideyo, and Okuda, H. Growth of $MgAl_2O_4$ single crystals by the flux method, (5) 115*e*.

Tabata, Hideyo, Okuda, H., and Ishii, E. Growth of $MgAl_2O_4$ single crystals by the flux method, (3) 73*d*.

Tabata, Hisanobu, Tabata, N., and Nakajima, R. Production of fresh water, brine, and $Mg(OH)_2$, P (10) 257*g*.

Tabata, Katsuhiro. See Nishida, Shinii.

Tabata, Katsuhiro, Fujiwara, T., and Omori, H. Direct-bonded basic brick for mixer lining, (2) 35*j*.

Tabata, Masayuki. See Koh, Yoshiro.

Tabata, Norimasa. See Tabata, Hisanobu.

Tabata, Saburo. See Eguchi, Kivohisa.

Tabata, Yoneho, Oizumi, C., and Otani, S. Production of C fibers, P (10) 248*a*.

Tabikh, A. A., and Miller, F. M. Nature of phosphogypsum impurities and their influence on cement hydration, (5) 104*a*.

Tabikh, A. A., and Weht, R. J. X-ray diffraction analysis of portland cement, (5) 104*f*.

Tabuteau, A., Pages, M., and Freundlich, W. Scheelite structure phases in the systems Pu molybdate-Li or Na molybdate, (10) 260*g*.

Tachibana, Masakiyo. See Inoue, Touru.

Tachikawa, Kyoji, Tanaka, Y., and Fukuda, S.

Superconductor and its mfg. method, P (10) 253*e*.

Tackaberry, R. B. Method of surface interference microscopy, P (3) 70*e*.

Tada, Osamu, Shintani, Y., and Yoshihara, T. Anomaly of resistance in reduced $BaTiO_3$ crystal, (4) 95*d*.

Taeger, J. Device for cleaning magnetic filters, P (4) 92*b*.

Taga, Koji, and Noguchi, M. Mfg. method for high-purity synthetic cryolite from crude wet-process phosphoric acid, P (10) 257*g*. Mfg. method for pure synthetic cryolite, P (10) 257*g*.

Tagai, Hideo. See Iseki, Takayoshi; Moori, Takahiko; Yasuda, Eiichi.

Taggart, W. J. See Helgeland, W.

Tagore, A. K., and Basavara, T. N. Si *pn* junction photodiode characteristics with variable drift field in the diffused region, (4) 86*j*.

Taguchi, Naoyoshi. Gas-detecting element and method of making, P (6) 137*f*, P (10) 250*e*.

Tahirbegovic, T. See Ozretic, V.

Tailby, R. V. Control testing in whiteware mfg., (11) 272*i*.

Tait, W. C. See Weiher, R. L.

Tajima, Iwao. See Yoshimura, Susumu.

Tak, M. G. A. See Wanmaker, W. L.

Takacs, S. See Csetenyi, J.

Takada, Toshio. See Iwauchi, Kozo.

Takagi, Toru. See Mizushima, Yoshihiko.

Takagi, Yutaka. See Ishibashi, Yoshihiro.

Takahashi, Akira. See Kubo, Kazuhiko.

Takahashi, Frank T. See Capek, R. G.

Takahashi, Hisamitsu. See Doi, Kazuo.

Takahashi, I. See Ugajin, M.

Takahashi, K., Morizumi, T., and Nagashima, Y. Memory effect of GaAs thin-film diode, (5) 111*j*.

Takahashi, Katsuaki, and Goto, Y. Optical and ESR spectra of Ni-containing alkaline earth borate glasses, (3) 56*i*.

Takahashi, Katsuaki, and Yoshio, T. Thermochemical investigations of glasses (I) energy relations in the alkali silicates by solution calorimetry, (2) 33*e*; (II) O–R bond energy in alkali silicates (R_2O SiO_2), (4) 81*f*.

Takahashi, Kazusaburo, Sasaki, T., Takeuchi, H., Morita, K., and Toda, T. Semiconductor device, P (7) 170*j*.

Takahashi, Makoto, and Yamazaki, Takeshi. Bending strength of boxed mortar beam, (6) 128*a*. Compressive strength of boxed concrete column, (6) 128*c*.

Takahashi, Masao. Electrical resistivity of Pb zirconate titanate ceramics containing impurities, (3) 62*g*. See Doi, Kikuo; Ohno, Tomeji.

Takahashi, Minoru. See Tamaoki, Osamu.

Takahashi, Susumu, Nakashima, H., and Migitaka, M. Method of diffusing an impurity into a compound semiconductor substrate, P (8) 201*a*.

Takahashi, Takashi. See Ichinose, Noboru.

Takahashi, Takehiko, and Sugiyama, K. Process for production of fibrous carbides, nitrides, or borides of Ti and Zr, P (8) 196*j*.

Takahashi, Takehiko, Sugiyama, K., and Itoh, H. Single-crystal growth of TiC by chemical vapor deposition, (9) 238*i*.

Takahashi, Tatsuo. See Sata, Toshiyuki.

Takahashi, Yoshiichi. See Satou, Sumio.

Takahashi, Yutaka. See Nakamura, Atsushi.

Takai, Kazuo. See Uchida, Shinichi.

Takaishi, Shogo. See Yamamoto, Zensaku.

Takaio, Shigeaki. See Miyahara, Yoshikazu.

Takaku, Tetsuo, and Miyashita, M. Piezoelectric ceramic filter, P (5) 113*i*.

Takakuwa, Juzo. See Hasaba, Shigemasa.

Takami, Akio. See Naruse, Akira.

Takamiya, Saburo. See Fujikawa, Kyoichiro.

Takamizawa, Hideo, Yotsuyanagi, K., and Okada, T. Ca-V series ferrimagnetic garnets, P (5) 112*g*.

Takamori, Takeshi, and Roy, R. Preparation of thin glass films for transmission electron microscopy by splat cooling, (11) 278*h*.

Takamori, Takeshi, Roy, R., and McCarthy, G. J. Observations of surface-nucleated crystallization in memory-switching glasses, (4) 80*g*.

Takaoka, Sumiko. See Aiki, Kunio.

Takashima, Hiroo, and Kato, E. Study of the structure of silicate glazes by the ir reflection method, (5) 111*e*.

Takashima, Hiroo, Kato, E., and Saito, H. Studies on the composition change in silicate glazes by the ir reflection spectrum method, (5) 111*d*.

Takashima, Saburo, and Higaki, K. Dissolution and determination of glass phase in portland cement by the picric acid-methanol method, (4) 78*c*.

Takashio, Haruo. Al_2O_3 ceramic-to-metal seals by the Mo-Mn process, (6) 136*f*. Ceramic-to-metal seals (I) sapphire-to-metal seal by the reactive alloying method, (3) 62*g*.

Takashio, Haruo, and Matsuzawa, T. Cs evaporator, P (6) 137*h*.

Takats, T. See Tamas, F.

Takaya, Yoshitada. See Muguruma, Hiroshi.

Takayanagi, Shigetoshi. See Yoshioka, Satoshi.

Takeda, Yutaka. See Iida, Shinya.

Takei, W. J. See Braginski, A. I.

Takeishi, Yoshiyuki. See Maeda, Hajime; Sato, Tai.

Takeishi, Yoshiyuki, Hara, H., Sato, T., and Sasaki, I. Oxide-coated semiconductor device having [311] planar face, P (4) 89*h*.

Takeishi, Yoshiyuki, Sato, T., Hara, H., Okamoto, Y., and Maeda, H. Semiconductor device, P (2) 42*i*.

Takemoto, Takeo, Miyata, Y., and Kawamura, T. Implosion-proof CRT and method of making, P (6) 133*c*.

Takemura, Makoto, and Tani, K. Thermal conductivity of $SrTiO_3$, $KTaO_3$, and $BaTiO_3$ near the Curie points, (3) 75*j*.

Takeno, Syozo. See Murakami, Yoshio.

Takeshima, Masumi. See Teramoto, Iwao.

Takeuchi, Hisaaze. See Takahashi, Kazusaburo.

Takeya, Kenichi. See Okuyama, Naoki.

Takher, E. A. See Fedoseeva, T. I.

Taki, Hiromitsu, Hayakawa, S., and Nagase, K. Ceramic dielectric comprising Ca titanosilicate, P (10) 249*j*.

Takiguchi, Hirofumi. Apparatus for automatically and successively opening bags of powder, P (9) 229*f*.

Takita, Hajime. Screen for CRT with discrete phosphor layers, P (7) 170*j*.

Takita, Hitoshi. See Araki, Tadashi.

Takizawa, Tsuyoshi. See Kamada, Osamu.

Taksis, G. A. See Khoroshavin, L. B.; Rutman, D. S.

Takusagawa, Nobuo, and Saito, H. Crystallization of glass of the fluor-richterite composition (III) nucleation and crystal growth in the fluor-richterite glass composition; (IV) effect of glassy phase separation on nucleation in the fluor-richterite glass composition, (3) 55*j*; (V) kinetic studies of the crystallization of glass of the fluor-richterite composition, (5) 105*g*; (VI) studies on the heat treatment of glass of the fluor-richterite composition for obtaining polycrystalline material having high mechanical strength, (6) 131*h*.

Talaber, J. Role of automation in the development of the building materials industry, (2) 35*e*.

Talbert, D. V. Lateral transistor structure and method of making, P (7) 169*a*.

Talbert, S. G. See Davis, J. A.

Talerchik, B. A. See Egorova, T. N.

Tallan, N. M. See Graham, H. C.; Tripp, W. C.

Tallman, R. L. See Andrew, K. F.

Tamaka, Tatsuo. See Shinohara, Kunio.

Tamaoki, Osamu, Takahashi, M., Shiolri, T., Toki, T., Fujii, T., Nishimura, H., and Kunihiro, E. Compressive strength and temp. rise tests on concrete containing fly ash, (6) 128*b*.

Tamas, F., Takats, T., and Peter, E. Comparative X-ray diffraction study on the quantitative mineralogical composition of Hungarian brick clays, (6) 141*i*.

Tamas, F. D., and Fabry, M. Solid state diffusion of Ca into kaolinite and illite, (5) 104*b*.

Tamura, Hideo. See Kubo, Kazuhiko.

Tamura, Shozo. See Okabe, Tadao.

Tamura, Takaaki, Kato, T., and Sakamoto, K. Method of preparing an oxidizing catalyst for the exhaust gases of internal combustion engines, P (8) 207*h*.

Tamura, Teizo. See Sakurai, Yo.

Tamura, Toshiyasu. See Satou, Sumio.

Tanabe, Isao. Method of producing MnO_2, P (6) 144*d*.

Tanabe, Motoko. See Aiki, Kunio.

Tanabe, Tadaaki. Fundamental study on joints of precast concrete members, (6) 129*f*.

Tanahashi, Isamu. See Ohgishi, Sakichi.

Tanaka, Eihachiro, Onodera, Y., Fukuda, T., Yamashita, T., Saito, T., and Kumia, S. Method of mfg. superconductive materials, P (9) 226*e*.

Tanaka, Hirobumi. See Hori, Shoichiro.

Tanaka, Hirokichi. See Inomata, Yoshizo.

Tanaka, Kazunobu. See Kohashi, Tadao.

Tanaka, Kazunobu, and Kohashi, T. Semiconductive electroluminescent element, P (6) 140*a*.

Tanaka, Makoto. See Okabe, Tadao.

Tanaka, Masami. See Hattori, Makoto; Minami, Tsutomu.

Tanaka, Sadao, Hirose, K., Atsumi, M., and Osawa, J. Experiments on false set in daily tests, (4) 78*h*.

Tanaka, Shigezo, and Minagawa, K. Process for mfg. facedown-bonded semiconductor device, P (3) 67*c*.

Tanaka, Shunji. See Umeya, Kaoru.

Tanaka, Takaho. See Chiba, Toshinobu.

Tanaka, Takaho, and Suzuki, H. Thermal conductivity of AlN, (3) 75*i*.

Tanaka, Takashi. See Machida, Jitsuro.

Tanaka, Tatsuo. Scale-up theory of jet mills on basis of comminution kinetics, (7) 172*g*. See Furuya, Masaaki.

Tanaka, Teruhisa. See Watanabe, Shigeo.

Tanaka, Tetsuro. See Matsunami, Hiroyuki.

Tanaka, Yoshiaki. See Tachikawa, Kyoji.

Tanaka, Yoshio. See Tomizuka, Isao.

Tananaev, I. V. See Kuznetsov, V. G.

Tananaev, I. V., Kuznetsov, V. G., and Petushkova, S. M. X-ray study of mixed phosphates and mixed H phosphates of Pr, Sm, and Yb, (8) 211*i*.

Tanasoiu, C., Florescu, V., and Rosenberg, M. Crystal growth and bubble domain properties of some Al substituted hexaferrites, (2) 47*f*.

Tanemura, Tadashi, Iwabuchi, T., Okaue, H., and Nakano, S. Some problems and their remedies concerning the closed circuit grinding of cement with liquid grinding aid, (9) 215*g*.

Tang, Chung L. See Giallorenzi, T. G.

Tani, Kensuke. See Takemura, Makoto.

Tani, Tetsuro. Recent technical trends in the refractory industry, (2) 36*d*.

Tani, Zenpei. See Sakurai, Takeshi.

Tanigawa, Yasuo. See Kosaka, Yoshio; Oota, Fukuo.

Taniguchi, Hideo. Semiconductor device with coplanar electrodes also overlying lateral surfaces thereof, P (11) 275*f*.

Taniguchi, Norio. Outline of electron beam working and its application to ceramics, (3) 69*b*.

Tanimura, Shigeru. See Uekusa, Genzo.

Taniuchi, Tsuyoshi. Mechanism of sintering in powder metallurgy, (3) 74*h*.

Tanizake, Mikio, Omori, Y., and Sugihara, J. Ferroelectric ceramic composition, P (5) 112*b*.

Tanji, Mikiharu. Character-indicating electron tube with fluorescent display structure, P (3) 57*i*.

Tannenberger, H. See Schachner, H.

Tannenberger, H., and Lanaspeze, P. Method for depositing on a support a thin layer of a solid ceramic electrolyte for a fuel cell, P (6) 138*a*.

Tanner, T. F. Colored cement, P (9) 215*e*.

Tanno, Yoshikazu. See Ichinose, Noboru.

Tarakanchikov, G. A. See Shumilin, A. A.

Taranukhin, N. A., Fominykh, G. V., and Vasil'ev, A. G. Accelerated determination of Ca and Mg oxides and titer in limestone and slurries, (8) 204*d*.

Tarasevich, Yu. I. See Sil'chenko, V. A.

Tardif, A., Piquard, G., and Wach, J. Eutectoid decomposition of Ta_2C, (6) 148*a*.

Tarnopol, M. S., and Snyder, T. P. Applying electroconductive heating circuits to glass, P (9) 218*d*.

Tartakoff, A. See Audesse, E. G.

Tarumi, Shuii. See Eguchi, Kiyohisa.

Tashiro, Chuichi. Steam curing of cement mortar added with seed crystal, (9) 215*a*.

Tashiro, Chuichi, and Ikeda, K. Effect on strength of cement of the addition of small amounts of mineral powders, (9) 214*g*. Effect on strength of cement paste of addition of cement hydrates, (6) 128*e*.

Tashiro, Megumi. See Kokubo, Tadashi; Yamamoto, Tokuji.

Tatchell, J. J. Manufacture of C filaments, P (8) 196*c*.

Tate, G. L., Summers, J. J., and Kramer, J. O. Means to sense and control speed of movement of glass sheet on gas support bed, P (4) 82*g*.

Tateno, Hideo, and Nemoto, K. Method of fabricating semiconductor devices having alloyed junctions, P (9) 226*g*.

Tates, H. G. K. See Daniels, H. P. C.

Tatsumi, Ryuji. See Miyauchi, Tsuneshige.

Tatsuno, Satoru. See Suzuki, Takevuki.

Tauber, A., Moller, W. M., and Danks, F. Magnetic ordering in $LiCr_{1-x}Fe_xO_2$, (8) 209*e*.

Tauber, A. F. See Fritsch, V.

Tauber, E., Crook, D. N., and Murray, M. J. Self-glazing cordierite, (8) 198*k*.

Tauber, E., and James, R. J. Zircon and its uses, (8) 207*b*.

Tauber, E., and Murray, M. J. Glass-clay mosaics and tiles, (8) 190*j*. Glazing concrete P (5) 104*g*.

Taubner, F. R., and Chenot, C. F. Phosphor coating for arc discharge lamps, P (6) 139*i*.

Tauchi, Makoto. See Ohama, Fumihiko.

Tauchi, Shoji. See Itoh, Yokichi; Koga, Yasushi.

Tavernier, B. H., de Jaeger, N. C., and Vanheertum, J. J. Pb oxide-containing photoconductive recording process utilizing X rays or visible light, P (3) 67*j*.

Taxil, A. M. V. See Boucher, R. C. E.

Taylor, B. Double glazing, P (9) 218*h*.

Taylor, D. W. See Evans, J. D.

Taylor, E. D. News pots, (2) 30*b*.

Taylor, F. M. Vortex tube laser, P (6) 140*e*.

Taylor, H. F. W. See Crennan, J. M.; Dyczek, J. R. L.

Taylor, H. P., Jr., and Forester, R. W. Low-^{18}O igneous rocks from the intrusive complexes of Skye, Mull, and Ardnamurchan, Western Scotland, (8) 209*j*.

Taylor, J. A. G. See Tyler, A. J.

Taylor, J. C. W., and Weichman, F. L. Role of excitons in the luminescence of Cu_2O, (6) 151*d*.

Taylor, L. S. Gem making for the enamelist, (2) 30*g*. Thread making for the enamelist, (2) 30*f*.

Taylor, M. I., Ford, W. F., and White, J. Mechanism of the B_2O_3 effect in magnesite refractories, (1) 7*f*. Phase relations in sections of the system CaO-MgO-B_2O_3-SiO_2 relevant to magnesite refractories containing B_2O_3, (2) 48*e*.

Taylor, M. J. Antiresonance phenomena in the absorption spectra of rare-earth ions in X-irradiated CaF_2, (6) 145*b*.

Taylor, P. C. See Griscom, D. L.

Taylor, P. C., and Bray, P. J. Structural properties of glasses inferred from computer simulations of magnetic resonance spectra, (4) 81*b*.

Taylor, P. R. Process for coating ceramic molds, P (6) 135*c*.

Taylor, R. E. See Layman, H. D.

Taylor, R. L. See Naschke, J. H.

Taylor, W. A., and Holdridge, D. A. Mineralogy of Jamaican clays (I) clays of the Frome area, Westmoreland Parish; (II)

clays of the Holland and Frenchman areas, St. Elizabeth Parish, (1) 20*e*.
Tazaki, Makoto. See Matsunami, Hiroyuki.
Tchalenko, J. S., Burnett, A. D., and Hung, J. J. Correspondence between optical and X-ray measurements of particle orientation in clays, (6) 145*e*.
Teagle, W. T. Portable mixing machines, P (8) 204*c*.
Teague, D. M., Bertrand, W. F., Willson, P. J., and Ammermann, F. E. Extrudable refractory fibrous material, P (9) 222*d*.
Teague, E. D. Manufacture of plaster mold having sprayed metal oxide linings and product, P (10) 254*d*.
Teale, R. W. See Enz, U.
Teboul, A. Device for feeding powdered material, P (7) 172*c*.
Teder, L. I. See Likhoradov, A. P.
Tedmon, C. S., Jr., and Mitoff, S. P. Sintered stabilized ZrO_2 containing discontinuous phase of Co-containing oxide, P (1) 9*e*.
Tedrow, P. M. See Kumbhare, P. R.
Teeg, R. O., and Hallman, R. W. Processes for obtaining V suboxides, P (5) 118*b*, P (7) 175*f*.
Teeter, F. J. High-Al_2O_3 refractory composition, P (2) 37*g*.
Tefft, E. G. Glass-encapsulated semiconductor device fabrication process, P (5) 112*f*.
Tegel, M. J. See Baas, W.
Tegman, R. See Rosen, E.
Teiwes, H. J. See Krauth, A.
Telang, Y. P. See Rao, V. D.
Telegus, V. S. See Kuz'ma, Yu. B.
Telegus, V. S., and Kuz'ma, Yu. B. Phase equilibria in the systems W-Cr-B and W-Mo-B, (10) 260*g*.
Tell, B. Properties of alkalis in CdS, (5) 122*h*.
Teller, A. J. Control of emissions from glass mfg., (9) 216*i*.
Tellgren, R., and Liminga, R. H bond studies (54) a neutron diffraction study of ferroelectric $LiH_3(SeO_3)_2$, (10) 259*b*.
Temple, C. S., and Matthews, J. R. Glass-fiber-reinforced thermoplastic article, P (11) 270*j*.
Tench, A. J. Infrared study of the adsorption of NH_3 on MgO (II) hydrated surface, (11) 281*c*.
Tench, A. J., and Giles, D. Infrared study of the adsorption of NH_3 on MgO (I) dehydrated surface, (11) 281*c*.
Tenebaum, Y. See Gorodetsky, G.
Tenney, D. R. See Carpenter, J. A.
Tennstedt, H. J. See Mikoteit, F.
Teo, T. K. See Rothwell, E.
Teodorovich, O. K. See Marek, B. A.
Terada, Michiko, and Sakata, M. Ferromagnetic resonance in thin films of Mn_3Ge_2 at X-band. (3) 62*i*.
Terada, Yukio. See Kawamata, Tadashi.
Teral, Kenji. See Suzukawa, Yuichi.
Teramoto, Hideo. Mfg. of superhigh early strength portland cement. (9) 214*h*.
Teramoto, Hideo, and Kasakawa, T. Method of production of superhigh early strength cements. P (2) 31*f*.
Teramoto, Iwao. See Yokozawa, Masami.
Teramoto, Iwao. Iwasa, H., Miyai, Y., and Takeshima, M. Varactor-controlled *pn* junction semiconductor microwave oscillation device. P (10) 253*d*.
Teranishi, Haruo. See Ishikawa, Toshikatsu.
Terao, Nobuyo. Some observations on Ni oxide scale, (3) 75*i*.
Terasaki, Osamu, and Watanabe, D. Electron microscopic study on the structure of Ti_nO_{2n-1}($4 \leq n \leq 10$) phases, (3) 73*a*.
Terekhov, V. P. See Lanshov, Yu. K.
Terekhovich, S. V. See Bash, S. M.
Terenyi, G. See Nagy, K.
Terman, L. M. MOSFET memory circuits, (7) 167*j*.
Termin, E. See Keddeinis, H.
Terry, L. E. Soutter etch mask, P (6) 140*h*. Use of Pt thin films as mask in semiconductor processing, P (4) 91*b*.
Tertykh, V. A., Chuiko, A. A., Sobolev, V. A., and Bobrushev, A. I. Spectral study of the structure of H_2O on an SiO_2 surface, (6) 151*h*.
Ter Vrugt, J. W. See Wanmaker, W. L.
Terwilliger, G. R. See Gordon, R. S.
Tesoro, G. C. See Moore, D. R.
Testa, G. See Calza Bini, A.
Testori, M. See Kemeny, G.
Teterin, E. G. See Anoshina, N. P.
Tettenhorst, R. See Lincoln, J.
Tettenhorst, R., and Reynolds, R. C., Jr. Choice of origin and its effect on calculated X-ray spacings for thin montmorillonite crystals, (1) 21*b*.
Teuschler, H. J. IGFET. P (2) 40*d*.
Te Velde, T. S. Electrode system, particularly semiconductor electrode system, and method of producing. P (3) 64*h*.
Te Velde, T. S., and van Heusden, S. Semiconductor devices comprising a heterojunction. P (10) 252*i*.
Tewari, R. P., and Mehta, P. K. Fluorogypsum as a mineralizer in portland cement clinker mfg., (6) 123*d*.
Thakur, R. L. See Chakravarty, N. K.
Tharmalingam, K. Theoretical study of the energies of formation of point defects in CaF_2 and UO_2, (6) 152*a*.
Thayer, A. G. Apparatus for shear and fatigue testing of [shear] pins, P (6) 142*c*.
Thelen, J. See Bade, E.
Theng, B. K. G. Mechanisms of formation of colored clay-organic complexes—a review, (6) 150*g*.
Theobald, P. R. See Davis, M. P.
Theodorou, D. G. See Deradoorian, B.
Thery, J. See Le Cars, Y.
Theuerer, H. C. See Nesbitt, E. A.
Theunissen, M. J. J., and Verkuijlen, W. H. C. G. Mfg. semiconductor devices, P (10) 251*f*.
Thiagarajan, K. See Kulkarni, A. K.
Thiagarajan, S. See Chakravarty, N. K.
Thibault, D. J. See Knerr, R. H.
Thibieroz, J. P. A. See Genisson, R. R.
Thiel, H. D. See Schneider-Arnoldi, A.
Thiemann, H. New work of Gilbert Portanier, (11) 266*d*.
Thimons, A. J. See Junge, A. E.
Thire, J. Method of mfg. a semiconductor device comprising a Zener diode and semiconductor device manufactured by using this method, P (4) 89*f*.
Tholome, R. Electrostatic spray gun, P (9) 230*a*.
Thom, C. L. See Machlan, G. R.
Thom, C. L., and McKinnis, C. L. Apparatus for producing glass filaments, P (1) 3*h*.
Thom, K. F. Process for the preparation of rare-earth fluorides, P (2) 46*d*.
Thomann, H. Piezoelectric structure composed of a ceramic ferroelectric material having a perovskite arrangement of components, P (8) 202*b*.
Thomas, A. Moisture expansion in brickwork, (1) 6*d*.
Thomas, A. G. See Andrews, R. H.
Thomas, D. A. See Gebauer, J.
Thomas, D. M. Wheel formulation in ceramic grinding, (9) 213*e*.
Thomas, F. W., and Tooke, W. R., Jr. Coated incandescent electric lamp, P (3) 57*j*.
Thomas, G., Fulrath, R. M., and Fisher, R. M. (editors). Electron Microscopy and Structure of Materials, B (10) 263*g*.
Thomas, H. J., Alvarez, A. G., and Pereira, E. Quantitative analysis of the SiO_2-Al_2O_3-CaO system by X-ray diffraction, (11) 278*h*.
Thomas, I. L. Method for exchanging counterions in actinide oxide sols, P (4) 91*h*.
Thomas, I. M. Method for the preparation of ultrahigh-purity SiO_2 in a porous bead form, P (9) 232*j*.
Thomas, J. Glassware-forming machine blow-mold station, P (5) 107*h*.
Thomas, J. B., and George, V. J. CRT with serpentine-shaped transmission line deflection means, P (6) 137*h*.
Thomas, J. M., Evans, E. L., Barber, M., and Swift, P. Determination of the occupancy of valence bands in graphite, diamond, and less-ordered carbons by X-ray photoelectron spectroscopy, (6) 146*j*.
Thomas, K. Strength, function, and other properties of wall ties, (9) 221*c*.
Thomas, M. J. B. See Dale, E. A.; Lagos, C. C.
Thomas, M. J. B., Dale, E. A., and Butler, K. H. Process for making improved phosphate phosphors from monetite, P (7) 170*f*.
Thomas, M. J. B., Dale, E. A., and Finch, W. A. Furnace for continuous firing of phosphors, P (1) 12*e*.
Thomas, T. B., Beebe, R. R., and Thompson, N. J. Ore carrier with slurry repulping and unloading system, P (1) 20*e*.
Thomas, W. F. Investigation of the factors affecting the strength of glass fiber strand (I), (2) 32*g*; (II), (9) 217*d*.
Thomasson, G. I. See Levand, V. A., Jr.
Thomasson, G. I., and Parillo, E. V. Quartz-to-metal seal mfg., P (4) 83*a*.
Thompson, A. G. See Wagner, J. W.
Thompson, B. A., and Miller, E. C. Determination of trace elements in ruby laser crystals by neutron activation analysis, (9) 230*h*.
Thompson, D. A., and Mackintosh, W. D. Stopping cross sections for 0.3- to 1.7-MeV He ions in Si and SiO_2, (6) 151*j*.
Thompson, D. F. Integrated circuit package, P (10) 250*j*.
Thompson, I. M. See Mayer, R. P.
Thompson, J. D. See Moore, V. D.
Thompson, J. H., Durgin, C. B., and Skinner, D. D. Device for coupling a transducer to a transmitter and receiver (U), P (2) 40*a*.
Thompson, N. J. See Thomas, T. B.
Thompson, P. See Fryer, G. M.
Thompson, W. A. Superconducting oscillators and method for making, P (4) 91*b*.
Thompson, W. L. See Martin, J. C.
Thomson, G. M., and Davies, W. Stress and strain in furnace life, (1) 19*b*.
Thomson, J., Jr. See Egerton, L.
Thomson, R., Hsieh, C., and Rana, V. Lattice trapping of fracture cracks, (5) 121*h*.
Thoonen, T. J. Process for the preparation of anhydrous AlF_3, P (6) 144*b*.
Thorington, L., and Parascandola, L. J. Electric lamps producing energy in the visible and uv ranges, P (9) 218*h*.
Thorland, R. H. See DuVarney, R. C.
Thorn, R. J. See McCreary, J. R.
Thornton, L., and Stuart, G. L. Apparatus for sensing and ejecting bricks of improper size, P (9) 221*a*.
Thornton, W. A., and Sausville, J. W. Phosphor blend lamps which reduce the proportions of the costlier phosphors, P (1) 5*g*.
Thornton, W. A., and Unglert, M. C. Color-corrected high-pressure Hg-vapor lamp, P (9) 218*f*.
Thorp, J. S. See Casselton, R. E. W.
Thorp, W., and Jones, Charles T. Semiconductor strain transducers, P (8) 202*b*.
Thorsen, A. C., and Manasevit, H. M. Heteroepitaxial GaAs on Al_2O_3—electrical properties of undoped films, (4) 86*j*.
Thuemmler, F. See Politis, C.
Thurman, M. E., Jr. Semiconductor tester having visual display, P (1) 14*a*.
Thurnay, K. See Hoffmann, H.
Thyoux, G. See Collard, R.
Tibol, G. See Christensen, R. W.
Tiede, R. L. Modification of the dipping cylinder method of measuring surface tension, (7) 173*a*. See Brady, W. C.
Tien, Tseng-Ying. See DeLosh, R. G.; Gibbons, E. F.; Kummer, J. T.
Tierman, M. Thin-film capacitor and method of making, P (5) 114*c*.
Tiernan, R. J. Calculation of grain-boundary diffusion parameters and comparison with experiment, (7) 176*j*.
Tilbrook, K. B. Glass fiber cooling means made of Pd, P (6) 132*i*.
Till, H. Process for the production of alkali metal perborates, P (7) 175*i*.
Tilley, R. J. D. See Steadman, R.
Timashev, V. V. See Butt, Yu. M.
Timke, R. F. Method of forming indented decorative patterns on ceramic tile, P (4) 86*c*.
Timmers, H. J. Some physical and chemical changes during the firing of bricks, (4) 83*e*. See van der Plas, L.
Timms, P. L. Reaction products of SiO and aromatic compounds such as benzene, P (8) 198*h*.
Timofeev, M. M., Sokolov, V. L., German, S. I., Levenberg, N. E., and Popov, N. I. Coated electrode for electric arc welding of steel of varying structure, P (6) 131*f*.
Timofeeva, I. I. See Samsonov, G. V.
Timofeeva, N. V., Apollonov, V. N., Vinogradova, G. Z., Svintitskikh, V. E., Feklichev, E. M., Kalashnikov, Ya. A., and Dembovskii, S. A. New polymorphic modification of realgar obtained at high pressure, (5) 122*h*.
Timperley, G. K. We never learn, (2) 35*g*.
Timusk, T., and Ward, R. W. Singular points in defect-induced far-ir spectra of KBr, (6) 151*f*.
Ting, C. H., and Pearson, G. L. Temp. dependence of the effective diffusion coeff. for Zn in GaAs, (4) 99*e*.
Tingquist, S. C. See Trench, W. H.
Tishkevich, Yu. B. See Koren, M. G.
Tishkova, K. S. See Skoblo, L. I.
Tisinger, R. M. See Beattie, W. H.
Tissier, P. Method and apparatus for the production of sheet glass, P (7) 162*j*.
Tite, M. S. Interpretation of thermal-expansion data from clay ceramics, (1) 17*j*.
Title, R. S. See Brodsky, M. H.
Tiwari, A. N., and Das, A. R. Correlation of refractive index and density in oxide glasses of high refractive index, (10) 242*j*.
Tkachenko, Yu. G. See Samsonov, G. V.
Tkachev, V. V., Ginzburg, Yu. N., Oganesov, V. N., Adel'son, L. M., and Orlova, T. M. Grinding of raw material with the use of classifiers, (8) 186*c*.
To, Kin-Ching, Stoneham, A. M., and Henderson, B. ESR from a vacancy-pair center in MgO, (5) 120*a*.
Tobe, Hideharu. Vibrating grinding mill, P (6) 141*h*.
Tober, H. Convection currents in electrically heated tanks—model experiments, (9) 216*j*.
Tobias, I. See Strouse, W. M.
Tobin, J. M. See Fleischer, L. R.
Tobin, M. C., and Baak, T. Raman spectra of vitreous B_2O_3 and of some B_2O_3-Bi_2O_3-Al_2O_3 glasses, (8) 191*e*.
Tod, J. H. Porcelain Insulators—Guide Book for Collectors (Unipart Pin Types), B (6) 154*c*.
Toda, Masumi. See Naito, Kiyoshi.
Toda, Masumi, and Fujiwara, N. Use test results obtained on rotary kiln lining constructed using resin, (7) 174*h*.
Toda, Masumi, Nagaoka, H., and Nishimura, K. Pumping transportation for refractory castable, (2) 36*c*.
Toda, Naoyoshi. See Uchida, Shinichi.
Toda, Seiichi. See Izumitani, Tetsuro.
Toda, Tadatoshi. See Takahashi, Kazusaburo.
Todd, C. F. Long-life [graphite] spout, P (4) 84*c*. Method of preparing pouring spout, P (10) 248*b*.
Todorovic, M. See Gal, I. J.
Togawa, Kazuo. See Araki, Kenichi.
Togawa, Senichi, Inkinen, O., and Manninen, S. Compton profile of MgO, (3) 72*g*.
Toguri, J. M. See Bale, C. W.
Tohi, Atsutomo, Sakai, K., Fukai, M., and Tsujimoto, Y. Method for diffusing an impurity substance into SiC, P (4) 88*g*.
Tokarev, G. I., Kopylev, B. A., and Varshavskii, V. L. $CaSO_4$ solubility and supersaturation of solutions of the system CaO-P_2O_5-$CaSO_4$-H_2O, (7) 176*h*.
Toki, Hisashi. See Yamamoto, Masayuki.
Toki, Takashi. See Tamaoki, Osamu.
Tokonami, Masayasu. See Morimoto, Nobuo.
Tokumitsu, Yoshiharu, Moon, J. K., and Ishikawa, T. Experimental investigation on work-

ability and segregation of crushed stone concrete, (6) 128*h*.

Tokuyama, Takashi. See Morita, Tadahisa; Tsuchimoto, Takashi.

Tokuyama, Takashi, Miyazaki, T., Tsuchimoto, T., Morita, T., Ikeda, T., Nishimatsu, S., Sano, H., and Horiuchi, M. Method of forming a junction by ion implantation, P (1) 13*d*.

Tokuyama, Takashi, and Mori, T. Method for producing a semiconductor device, P (4) 89*a*.

Tol, T., and De Vrijer, B. Electric discharge lamp comprising container of densely sintered Al_2O_3, P (2) 40*c*.

Tolar, N. J. See Leedy, H. M., Jr.

Tolk, N. H., and White, C. W. Method of analyzing a solid surface from photon emissions of sputtered particles, P (6) 142*f*.

Tolksdorf, W. Device for a method of growing monocrystals, P (10) 250*g*.

Tolksdorf, W., and Holst, P. Integrated microwave system having a hybrid structure with a nonmagnetic dielectric ceramic substrate, P (2) 40*d*.

Tolochkova, M. G., and Kolosovskaya, V. M. Use of ash from thermal power plants as a hydraulic cement additive, (8) 188*g*.

Toma, S. Z. See Mathers, J. E.

Toma, S. Z., and Palumbo, D. T. Broad emission and excitation bands in Y_2O_3 and YVO_4, (2) 47*c*.

Tomandl, G. Approx method for a simple calculation of the "true" sphere radius distribution of polished sections from the circle radius, (1) 17*f*. See Frischat, G. H.

Tomas, M. S. See Rao, G. V. S.

Tombrel, F. Process for producing pyrolytic C impregnated thermal insulating carbonized felt, P (1) 9*a*.

Tomii, Kaoru, and Miyama, H. Thin-window CRT, P (3) 59*i*.

Tomii, Kaoru, Miyama, H., Muto, T., and Kaneko, M. Photographic recording tube with a phosphor layer in a thin-window narrow-slit faceplate, P (3) 59*b*.

Tomii, Kaoru, and Miyazaki, E. Fiber optics element, P (3) 58*b*.

Tomiie, Kazuo. See Makishima, Shoji.

Tominaga, Megumi. See Muguruma, Hiroshi.

Tomita, Kinzo, Hayashi, R., and Nagase, T. Relation between modification of clinker mineral such as α-belite and strength of cement, (9) 215*d*.

Tomita, Kinzo, Ogawa, T., Abe, S., and Sagiya, I. Effect of cooling rate of cement clinker on the strength of cement, (4) 78*e*.

Tomita, Kojiro. See Muguruma, Hiroshi.

Tomiwa, Hiroshi. See Matsuo, Masao.

Tomizawa, K., Kawashima, M., and Kataoka, S. New logic functional device using transverse spreading of a high-field domain in *n*-type GaAs, (7) 167*a*.

Tomizuka, Isao. See Watanabe, Osamu.

Tomizuka, Isao, Kurita, T., Tanaka, Y., and Watanabe, O. Voids in C fibers produced by the Kureha process, (5) 109*e*. Voids in C fibers produced from lignin and polyvinyl alcohol, (6) 135*c*.

Tomkinson, F. R. Fe_2O_3 pigments, P (3) 71*b*.

Tomokawa, Hideo. See Doi, Kazuo.

Tomozawa, M. See Fahmy, M.

Tompkins, R. E. See Edgar, R. F.

Toms, G. L. Pigments, P (10) 257*j*.

Tong, H. C. See Gilman, J. J.

Tong, S. Y., and Maradudin, A. A. Normal modes of a semi-infinite ionic crystal, (5) 122*i*.

Tooke, W. R., Jr. See Thomas, F. W.

Toombs, T. N. See Dill, H. G.

Topp, R. L. See Spangler, E. G.

Topping, J. A., and Isard, J. O. Dielectric properties of Na aluminosilicate glasses at microwave frequencies, (7) 158*h*.

Toppler, B., Bauer, F., and Golde, H. J. New receiver feeders for steel jet casting, (2) 36*j*.

Torchio, S. See Pizzini, S.

Tordjman, I. See Bagieu-Beucher, M.

Torok, A. Formation of colloidal suspensions of chrysotile asbestos by treatment with H smectites, P (7) 164*c*.

Torok, A., and Walsh, T. F. Kaolin pigments and methods of producing, P (2) 46*h*.

Toropov, N. A. See Bondar, I. A.; Kolesova, V. A.

Toropov, N. A., and Ismatov, A. A. Solid solutions in the system $Ca_2Al_2SiO_7$-$CaLaAl_3O_7$, (8) 210*d*.

Toropov, N. A., and Khotimchenko, V. S. Catalyzed crystallization of glasses of pyroxene compositions, (9) 216*d*.

Toropov, N. A., Udalov, Yu. P., and Medvedeva, Z. S. Growth of $12CaO{\cdot}7Al_2O_3$ single crystals, (8) 199*i*.

Toropov, Yu. S. See Rutman, D. S.

Torrence, S. L. See Ball, F. J.

Toth, L. S., and Collins, S. A., Jr. Means for holographically recording a 3-dimensional microscopic sample, P (9) 231*h*.

Toth, M. See Kozar, L.

Totta, P. A. See Riseman, J.

Touboul, M. Tl borates, (4) 99*g*.

Touchy, W. Apparatus for producing photolithographic structures, particularly on semiconductor crystal surfaces, P (2) 39*a*.

Tourneur, D. See Ravez, J.

Toussaint, F. See Boffe, M.; Plumat, E.

Toussaint, F., and Boffe, M. Mechanically strengthening articles made of vitreous or ceramic materials, P (3) 58*h*.

Touzain, P. See Natola, F.

Touzain, P., Brisse, F., and Caillet, M. Alkali metal-O systems (III) polymorphism of K_2O, (7) 176*d*.

Touzeau, M. Glazing and decorating tiles and tableware, (4) 92*f*.

Tovaglieri, G. L. Machine for the dimensional control of elements for nuclear fuels, P (3) 68*i*.

Towe, K. M. See Roberson, H. E.

Towell, J. F. See Heady, O. E.

Towner, J. M. See Sarkar, B. K.

Townsend, L. W., Jr., and Wilburn, W. E. Glass-forming apparatus, P (8) 193*a*.

Townsend, P. D. See Arsenovici, L. C.

Toyoda, Minoru. Electron multiplier device using semiconductor ceramic, P (2) 40*e*.

Toyoshima, Isao. Method of mfg. an energy trapped type ceramic filter, P (7) 169*b*.

Toyuki, H., and Akagi, S. EPR and optical spectra of the vanadyl ion in alkali borate glasses, (9) 217*g*.

Tragert, W. E. See Hall, J. W., II.

Traina, F., and Pernicone, N. Mfg. methods and their effects on the properties of solid catalysts, (4) 85*h*.

Trampier, C. R., Jr. See Heywood, K. W.; Olmsted, L. E.

Trampisch, W. See Herrman, R.

Trap, H. J. L. [Electrode] glass, P (8) 192*g*.

Trask, R. B., and Smith, Mark J. Method for producing a graphite article, P (8) 196*e*.

Trattner, H., and Klar, R. Melt-resistant welding electrodes, P (5) 105*d*.

Trease, R. E., and Dietz, R. L. Rheology of pastes in thick-film printing, (11) 274*j*.

Treffner, W. S. See Farrington, G. M.; Marr, R. J.

Tremblay, R. See Angers, R.

Trench, W. H., and Tinguist, S. C. Apparatus for mfg. refractory shell molds, P (1) 8*i*.

Trench de Freitas, C., and Handwerk, J. W. Warm-pressing method of making stacked fuel plates, P (9) 229*b*.

Trent, P. E., and Miner, J. E. Fibrous carbonaceous composites and method for mfg., P (9) 222*e*.

Trent, R. L. Method of mfg. semiconductor devices using refractory dielectrics, P (1) 13*a*.

Tresouthick, S. W. Apparatus for and method of mfg. white portland cement clinker, P (2) 31*d*.

Trethewey, W. C. Method and apparatus for producing fibers with environmental control, P (6) 133*i*.

Tret'yak, Z. A. See Korobka, L. A.

Tret'yakov, Yu. D. See Granik, V. A.; Kosinskaya, I. Ya.; Volkov, V. I.

Tret'yakov, Yu. D., and Kosinskaya, I. Ya. Properties of magnetic ceramics formed during sintering of ferrite powders, (9) 224*b*.

Tret'yakov, Yu. D., Kosinskaya, I. Ya., and Petrova, A. A. Catalytic activity and specific surface of ferrite powders produced by thermal decomposition of solid salt solutions, (9) 223*i*.

Treves, D. See Gorodetsky, G.

Triano, A. See Dalal, V. L.

Triggiani, L. V., and Sanchez, M. G. Process for preparing multicomponent nuclear fuels, P (9) 229*a*.

Trimble, C. H., and Strott, D. B. Y purification process, P (5) 118*c*.

Tripp, T. G. Production of $[SiO_2]$ sols, P (6) 144*e*.

Tripp, W. C. See Davis, Hubert H., Jr.

Tripp, W. C., and Tallan, N. M. Revised wt change in nonstoichiometric ZrO_2, (2) 49*h*.

Trivedi, R. K. See Jones, G. J.

Trivich, D., and Pollack, G. P. Preparation of single crystals of Cu_2O in an arc-image furnace, (9) 224*a*.

Troegel, G. See Schultes, B.

Trofimov, M. G. See Kestner, O. E.

Trojer, F., and Breslmair, G. Method for determining the frost resistance of roofing tile bodies, (1) 17*i*.

Trolle, S. See Jonsson, F. L.

Trontelj, M. See Kolar, D.

Trostanetskii, L. M. See Brumberg, R. M.

Troup, G. J. See Walter, J. A.

Trueb, L. F., and de Wys, E. C. Carbonado—natural polycrystalline diamond, (1) 19*i*.

Trunin, A. S. See Bergman, A. G.

Trunov, G. V. Method of casting from thermoplastic slips, (3) 69*a*.

Trunov, V. K. See Pokrovskii, A. N.; Velikodnyi, Yu. A.

Truppe, M., Schernthaner, M., and Poferl, G. Measuring device for continuously measuring the temp. of metal baths, P (6) 142*e*. Refractory hollow body, P (7) 164*f*.

Trusov, V. V. See Potryasov, V. N.

Trussell, C. W. See Ahn, B. H.

Trutner, D. G. Glass tube forming machine, P (4) 82*d*.

Tsagina, R. F. See Krylov, V. S.

Tsai, J. C. Method for diffusion of acceptor impurities into semiconductors, P (2) 41*b*.

Tsai, Jui-Hsiung. Process for the separation of useful compounds from waste formed from the production of Al_2O_3 by the Bayer process, P (9) 233*b*.

Tsekhomskii, V. A. See Galimov, D. G.; Pavlovskii, V. K.

Tsikin, A. N. See Kunin, V. Ya.

Tsimmergaki, V. A., and Stelmakh, S. I. Installation for DTA of fusible systems, (6) 142*c*.

Tskhai, V. A., and Gel'd, P. V. Evaluation of the thermodynamic characteristics of refractory carbides from their ir absorption spectra, (8) 209*a*.

Tsu, R. See Esaki, L.

Tsu, R., Esaki, L., and Ludeke, R. Photoconductivity in disordered NiO films, (6) 150*h*.

Tsubaki, Takayuki. See Hattori, Makoto.

Tsuboi, Tatsuaki, Ito, T., Hokinoue, Y., and Matsuzaki, Y. Effects of MgO, SO_3, and ZnO on sintering of portland cement clinker, (9) 214*h*.

Tsuboi, Tatsuaki, Okada, M., and Asao, S. Sintering mechanism of portland cement clinker, (4) 79*c*.

Tsubouchi, Norio. See Ohno, Tomeji.

Tsuchihashi, Shoji. See Kawamoto, Yoji; Nakashima, Hiroshi.

Tsuchimoto, Takashi. Method of implanting impurity ions in surface of a semiconductor, P (4) 88*i*. See Morita, Tadahisa; Tokuyama, Takashi.

Tsuchimoto, Takashi, Tokuyama, T., and Komatsubara, K. Method for producing semiconductor device utilizing ion implantation, P (8) 201*i*.

Tsuda, Nobuo. See Chiba, Toshinobu; Mitsuhashi, Takefumi; Noguchi, Masayasu.

Tsuei, Chang Chyi. Metallic resistance thermometer, P (6) 142*f*.

Tsuge, Akihiko. See Komeya, Katsutoshi.

Tsuji, Masaru. See Shirai, Yoshihiro.

Tsuji, Shigeo. See Hori, Hiroo.

Tsuji, Shigeo, and Shirouzu, S. Semiconductor photoelectric converting device having spaced elements for decreasing surface recombination of minority carriers, P (4) 90*f*.

Tsuji, Toshiro. See Akashi, Tsuneo.

Tsujide, Tohru. See Nakanuma, Sho; Wada, Toshio.

Tsujide, Tohru, Nakanuma, S., and Ikushima, Y. Properties of Al_2O_3 obtained by hydrolysis of $AlCl_3$, (9) 238*c*.

Tsujikawa, Ikuji. See Uesaka, Yasutaro.

Tsujimoto, Yoshinobu. See Tohi, Atsutomo.

Tsukagoshi, Tsunehiro. See Ohshita, Masahide.

Tsukayama, Ryuichi, Miyoshi, A., Matsunaka, K., and Miyaji, H. Drying shrinkage and its effect on strength of concrete using various cements, (6) 128*j*.

Tsukioka, Masayuki. See Mitsuhashi, Takefumi.

Tsukiyama, Koichi. See Uchikawa, Hiroshi.

Tsumagari, Akira, and Hita, T. Influence of alkalis and other materials on the adhering of dust and the formation of coating, (9) 214*c*.

Tsunekawa, Munehisa. Anomalous dispersion optical glass having a good weatherproof characteristic, P (7) 161*e*.

Tsuno, Fumio. See Miyaji, Naoki.

Tsunooka, Tsutomu. See Banno, Hisao.

Tsurikova, G. A. See Galimov, D. G.

Tsushima, Kuniro. See Sugano, Satoru; Uesaka, Yasutaro.

Tsutsumi, Tadashi. See Hori, Hiroo; Nakagawa, Takashi.

Tsutsumi, Tadashi, and Matsuo, T. Semiconductor device passivated with rare earth oxide layer, P (8) 202*h*.

Tsuya, Hideki, and Fujino, Y. Determination of the distribution coeffs. of Li_2O into $LiNbO_3$ by phase matching temps., (4) 96*c*.

Tsuyuki, Naomitsu, and Kasai, J. Study of rapid hardening cement, (2) 31*c*.

Tsuzi, Kazuo. See Urata, Toshio.

Tu, Yih-O. Determination of magnetization of micromagnetic wall in bubble domains by direct minimization, (7) 177*b*.

Tucker, T. N. Production of ultrapure semiconductor materials, P (6) 139*i*.

Tuerk, G. See Eisenmenger, E.

Tuft, B. R. Glass passivated double beveled semiconductor device with partially spaced preform, P (5) 112*f*.

Tuinstra, F., and Koenig, J. L. Raman spectrum of graphite, (7) 179*j*.

Tulley, F. T. Composition and process for injection molding thermoplastic material and glass fibers, P (6) 132*d*.

Tulp, T. J., Appels, J. A., and Kooi, E. Deep depletion semiconductor device with surface inversion preventing means, P (10) 250*f*.

Tumanov, S. G. See Morozova, G. P.

Tummala, R. R. See Detweiler, J. R., Jr.

Tung, S. K., and Caffrey, R. E. Deposition and physical properties of aluminosilicate films, (2) 38*d*.

Tungesvik, K. See Rosenqvist, T.

Tunimanova, I. V. See Pavlovskii, V. K.

Turchanin, A. G., and Fesenko, V. V. Enthalpy and thermal capacity of ZrC in the homogeneous range 1300°–2500°K, (10) 259*d*. Thermodynamic characteristics of refractory carbides in their homogeneity regions, (10) 261*c*.

Turchinova, L. N., Savenkov, M. I., Kirichenko, T. P., and Ivanova, G. M. Effect of limestone composition on the quality of milk of lime in the production of seawater MgO, (8) 205*i*.

Turene, F. E. See Revitz, M.

Turk, H. L. See Brede, D. W.; Secrist, D. R.

Turkalo, A. M. See Doremus, R. H.

Turkdogan, E. T. See Kor, G. J. W.

Turkdogan, E. T., and Kor, G. J. W. Sulfides

and oxides in Fe-Mn alloys (I) phase relations in Fe-Mn-S-O system, (6) 152*e*.
Turnbull, A. A. Photocathodes, P (4) 89*j*.
Turnbull, D., and Cohen, M. H. Free-vol model of the liquid-glass transition, (5) 105*h*.
Turnbull, J. A. Distribution of intragranular fission gas bubbles in UO_2 during irradiation, (6) 171*f*.
Turnbull, J. A., and Cornell, R. M. Observations demonstrating the re-solution of gas from bubbles and sintering pores during the irradiation of UO_2 at a high temp., (1) 15*h*.
Turner, G. A. Apparatus for pelletizing powderous materials by vibrational forces, P (7) 172*a*.
Turner, J. A. See Turner, W. H.
Turner, P. A. See English, A. T.
Turner, W. H., and Turner, J. A. Ligand-field spectra and structure of Ni in silicate glasses, (5) 106*d*.
Turner, W. R. Transceiver ultrasonic image system, P (1) 15*b*.
Turowski, G. Color control in the appliance industry, (10) 242*g*.
Turpin, M. [Metal] fibers and fiber composite materials, (8) 195*j*.
Turriziani, R. See Collepardi, M.
Tuttle, J. W. See Bhatt, H. J.
Tveter, E. C., and Suris, J. P. Continuous preparation of TiO_2 seed suspensions, P (4) 94*g*.
Tweed, D. G., and Bomar, R. L. Hybrid element variable resistor, P (1) 12*f*.
Twist, D. See Giddings, D. G.
Tyler, A. J., Taylor, J. A. G., Pethica, B. A., and Hockey, J. A. Heat of immersion studies on characterized silicas, (5) 121*a*.
Tymkewicz, J. Thermocouple connector construction, P (7) 174*a*.
Tynes, A. R. See Kolb, E. D.
Tyrrell, M. E., Feld, I. L., and Barclay, J. A. Fabrication and cost evaluation of experimental building brick from waste glass, (7) 159*h*.
Tyutkalo, L. I. See Dubok, V. A.
Tyutyunnikov, A. I. See Funke, V. F.

Uchida, Naotake. See Shirai, Yoshihiro.
Uchida, Naoya. See Ohmachi, Yoshiro.
Uchida, Naoya, Ohmachi, Y., Nilzeki, N., Miyazawa, S., and Iwasaki, H. Di-lead molybdate ultrasonic light deflector, P (9) 225*c*.
Uchida, Shinichi, Funato, M., Toda, N., and Nagatuka, K. Fluorescence X-ray analysis of cement raw mix, (9) 214*i*.
Uchida, Shinichi, Sakoda, H., Takai, K., and Toda, N. Determination of Na and K by atomic absorption spectrophotometry, (4) 78*b*.
Uchida, Teiji. Converging solid-state laser element for high-power output use, P (3) 64*d*.
Uchida, Teiji, Furukawa, M., Yoshikawa, S., Kitano, I., and Koizumi, K. Faraday-effect element, P (4) 81*g*.
Uchida, Teiji, and Sakaguchi, M. Light beam deflection control device with gradient index light guide, P (1) 4*j*.
Uchida, Yoshihiko. See Fujita, Masayuki; Sata, Toshiyuki.
Uchidate, Mamoru. See Waku, Shigeru.
Uchikawa, Hiroshi, and Kasai, N. Pyrolitic separation and alkalimetric determination of F in fluorspar, cryolite, and other inorganic fluoride compounds, (10) 255*a*.
Uchikawa, Hiroshi, and Tsukiyama, K. Polymorphic transformations of Ca_3SiO_5, (5) 104*c*.
Uchikawa, Hiroshi, Tsukiyama, K., and Yamamoto, M. Polymorphic transformation of Ca_3S, (4) 79*g*.
Uchimura, Ryoji. See Yamaguchi, Goro.
Uchino, Koichi. See Yasuda, Kazuo.
Uchiya, Fumitoshi. System designing of glass and its characteristics, (3) 57*a*.
Ueko, P. J. Authenticity of vessels and figurines in the Hacilar style (IV) stylistic and technological analysis, (5) 101*h*. See Moorey, P. R. S.
Udalov, Yu. P. See Flem, Z. L.; Toropov, N. A.
Ueda, Minoru. See Kijima, Goro.
Ueda, S. See Daimon, M.
Ueda, Tadao, Sato, K., and Nakamura, Y. Process for producing crystalline zeolite A, P (10) 257*f*.
Ueda, Toshimasa. See Inoue, Taiichi.
Ueda, Y. See Roberts, J. T. A.
Uei, Isao. See Hayashi, Kunio.
Ueki, Atsufumi. See Miyauchi, Tsuneshige.
Uekusa, Genzo, Tanimura, S., Higashi, K., and Sumoto, T. Semiconductor having Sn oxide layer and substrate, P (10) 252*i*.
Uekusa, Shinichiro. Photodielectric effect in dispersed ZnS phosphors, (3) 74*f*.
Ueltz, H. F. G., and Rzucidlo, A. G. Process for making cubical sintered aluminous abrasive grains, P (5) 101*f*.
Uematsu, Yutaka, and Fukuda, T. Nonlinear optical properties of $KNbO_3$ single crystals, (3) 74*c*.
Ueno, Kazunari. See Hayakawa, Masashi.
Ueno, Tokihiro, and Odajima, A. Growth of trigonal Se and Te films on glass, (3) 56*i*.
Ueno, Tsutomu. Glass fiber as an optical transmission line, (6) 132*a*.
Ueoka, Hisayoshi, Horii, K., and Umeya, K. Semiconducting ceramic compositions, P (10) 252*g*.
Uesaka, Yasutaro, Tsujikawa, I., Aoyagi, K., Tsushima, K., and Sugano, S. Exciton absorption lines in antiferromagnetic $DyCrO_3$, (4) 96*f*.
Ugajin, M., and Takahashi, I. Phase reaction in the UC-W system, (1) 15*e*.
Uginchus, D. A. See Mchedlov-Petrosyan, O. P.
Uglietti, G. See Colombo, U.
Uninck, R. W. Methods of upgrading Al_2O_3-bearing materials, P (4) 94*c*.
Uhland, K. L. Process for recovering $TiCl_4$ from titaniferous ore, P (4) 95*a*.
Uhlmann, D. R. See Hakim, R. M.; Li, J. H.
Ukai, Masayasu. See Ohgishi, Sakichi.
Ulanova, M. S. See Kochergin, V. P.
Ulion, N. E. See Blecherman, S. S.
Ulmer, G. C. (ed.tor). Research Techniques for High Pressure and Temperature, B (7) 184*i*. See Leonard, R. J.
Ul'yanova, G. G., and Zaionts, R. M. Use of asbestos waste for making chemically resistant articles, (8) 198*a*.
Umeda, Junichi. Light-emitting diode with built-in drift field, P (4) 88*j*. Light-emitting diode with subnanosecond response time, P (4) 88*j*.
Umemoto, Noriyasu. Results of hot repair test on 1500-ton mixer by gunning method, (7) 163*h*.
Umeya, Kaoru. See Nishikawa, Tomozo.
Umeya, Kaoru, Tanaka, S., and Gomi, S. Sintered ceramic body containing residual C and process for preparing it, P (8) 197*a*.
Umeya, Kaoru, Watanabe, A., and Gomi, S. Process for preparing a molded pitch-powder granule system with an improved bonding material and product produced therefrom, P (9) 222*d*.
Umeya, Kazumasa. See Ueoka, Hisayoshi.
Unglert, M. C. See Thornton, W. A.
Unno, Yoichi. See Iida, Seishi.
Uno, Tatujiro, and Mochizuki, M. Extra high early strength portland cement, P (6) 130*d*.
Uno, Yoshihiro. Thin-window image pickup and recording tube, P (10) 253*b*.
Uno, Yoshihiro, and Kawakami, H. Method for producing a device for transmitting an electron beam, P (1) 13*g*.
Uno, Yoshihiro, Maeda, H., and Koike, Y. Recording CRT having an electron penetrative window, P (2) 42*f*.
Upadhyaya, D. D. See Kulkarni, A. K.
Upadkhaya, G. Sh. See Samsonov, G. V.
Upson, L. L. See Macarus, D. P.
Upson, L. L., and Wood, R. T. Zeolite A synthesis, P (8) 207*i*.
Ura, Mitsuru, and Ogawa, T. Zener diode and method of making, P (1) 15*c*.
Urabe, Kazuyori, Ossaka, J., and Yamada, H. Experimental formation of kaolinite from vermiculite, (6) 143*e*.
Urano, Teruo. See Sata, Toshiyuki.
Urata, Toshio, Ozaki, Y., and Tsuzi, K. Filtration of porous concrete pipe and the gradings of aggregate filtrating layers for the pipe, (6) 129*b*.
Urayama, Kiyoshi. See Hosokawa, Masuo.
Urbach, J., and Wiene, H. W. Technique for lathe grinding multifocal contact lenses, P (8) 194*c*.
Urban, P. See El-Assal, K.
Ur'ev, N. B., and Mikhailov, N. V. Mechanism of destruction of reinforcing glass fiber in hardening cement, (8) 191*a*.
Urnes, S. Studies of partial electronic radial distribution curves involving Si and O only in amorphous silicate systems, (2) 32*i*. X-ray diffraction studies of glasses in the system Li_2O-Al_2O_3-SiO_2-GeO_2, (2) 33*h*.
Urushibara, Kotaro. See Motoi, Soichiro.
U.S. Bureau of Mines and IIT Research Institute (cosponsors). Proceedings of the Third Mineral Waste Utilization Symposium, B (9) 240*e*.
Ushakovskii, V. T. Interrelation of the forms of vicinal growth on the faces of quartz crystals, (8) 209*c*.
Ushatinskii, I. N. See Babitsyn, P. K.
Ushio, Masumi. See Saito, Hajime.
Ushio, Masumi, and Saito, H. Hydrothermal experiments on materials corresponding to fluorhydroxyl chrysotile $[Mg_6Si_4O_{10}F_x(OH)_{8-x}]$, (3) 73*f*.
Ustalov, V. E. See Likhoradov, A. P.
Ust'yantsev, V. M. See Budnikov, P. P.; Khoroshavin, L. B.
Usui, Yukihiko. See Koyanagi, Wataru.
Usvitskii, M. B. Dependence of crystallization temp. on the rate of heating and its relation to the energy of activation, (8) 189*e*.
Uto, Yashimitsu, Yamasaki, D., Watanabe, T., and Matsuoka, K. Method for making a mold using $MnCO_3$, P (2) 37*a*.
Utsugi, Mikio, and Ohta, T. Method of making plastic fiber-optical plates, P (9) 219*a*.
Utsumi, Yoshikazu. Microstructure and strength of crystallized glass of the photoceram-type, (5) 106*e*.
Utsunomiya, Taizo, Hoshino, Y., and Sato, M. Crystallization of YAG from PbO-YF_3-Al_2O_3 melts, (11) 280*g*. Phase relations in the system BaF_2-YF_3, (11) 281*j*. Process of the hydrolysis reaction from YF_3 to Y_2O_3 in humid air at high temps., (11) 282*i*.
Uttecht, R., Stevenson, H., Sie, C. H., Griener, J. D., and Raghavan, K. S. Electric field-induced filament formation in As-Te-Ge glass, (6) 131*i*.
Uveges, J. See Kozar, L.
Uy, O. M. See Farber, M.; Srivastava, R. D.

Vadacz, L. L., Chua, H. T., and Grove, A. S. Semiconductor random-access memories, (7) 167*i*.
Vadimsky, R. G. See Keith, H. D.
Vagnard, G. See Zikovsky, L.
Vail, J. W., and de Wet, J. D. Hydrogarnet phase in kaolinite-lime-water slurries, (9) 214*b*.
Vaipolin, A. A. See Borisova, Z. U.
Vainrameev, V. I. See Zorina, M. L.
Valentin, G. See Kiehl, J. P.
Valentino, C. R. See Jen, D. P.
Valenziano, F. P. Pipe joint, P (8) 194*f*.
Valet, J. Y. Anisotropic thin ferromagnetic film magnetometer, P (3) 64*d*.
Val'kovskaya, L. I. See Alekseeva, A. N.
Vallcona, G. See Bonet, C.
Valyashko, V. M. Phase equilibria in binary and ternary systems of the I type including components of different volatility, (8) 210*a*.
Van Amstel, J. J. A. P. Method of coating substrates by vapor deposition, P (1) 13*b*.
Van Asbroeck, P. L. See Aerts, L. J.
Van Bakel, H. A., and Meijer, R. A. J. M. Halogen lamp employing a quartz envelope provided with a colored layer, P (3) 66*b*.
Van Beem, M. J. L. See Kouwenhoven, H. W.
Van Boort, H. J. J. See Groth, R.
Van Buren, N. See Wang, P.
Van Damme, F. M. Glass-tube re-forming apparatus, P (3) 58*a*.
Van den Berg, H., and Levelink, H. G. Process for preparing molding sand, P (9) 222*e*.
Van den Broek, J. See Kwestroo, W.
Van den Heuvel, A. P., Owen, R. B., and Joshi, S. G. Hybrid surface-wave transducer, P (9) 225*d*.
Van den Heuvel, A. P., Richter, R. W., and Joshi, S. G. Composite surface-wave transducer, P (10) 250*c*.
Vanderbilt, B. M., and Fasnacht, J. J. Glass fibers sized with a composition comprising a vinylic aromatic dioolefin copolymer and a hydrolyzable silane, P (10) 244*j*.
Van der Giessen, A. A. Hydrothermal preparation of ceramic powders, (4) 97*a*.
Van der Giessen, A. A., and Huizinga, F. Method of preparing a metal powder consisting at least substantially of Fe for magnetic recording, P (1) 13*e*.
Van der Giessen, A. A., and Klomp, C. J. Method of preparing a magnetically stable metal powder consisting mainly of Fe and meant for magnetic recording, P (4) 89*h*. Method of preparing a metal powder consisting at least substantially of Fe for magnetic recording, P (1) 13*e*.
Van der Klugt, L. J. A. R. Drying times of heavy clay articles, (4) 83*e*.
Van der Knaap, S. C. See Spit, B. J.
Van der Kooi, A. G. See Smets, H. J. F. G.
Van der Maat, A. T. See Haes, E. J.
Van der Meulen, J. See Brants, J. P.
Van der Plas, L. See Henstra, S.
Van der Plas, L., and Timmers, H. J. Physicochemical changes during the firing of bricks (an investigation of the properties of 2 types of clay and of the red and yellow bricks made thereof and relations to the firing process), (6) 134*a*.
Vanderpool, C. D. See Chiola, V.
Van der Tas, J. C., and Meulemans, C. C. E. Flashbulb [ignition], P (4) 81*h*.
Van der Tas, J. C., Meulemans, C. C. E., and Martens, K. P. Photoflash lamp, P (1) 5*g*.
Van der Velden, J. H. Shuttle kiln in the heavy clay industry, (6) 134*a*.
Van der Ven, T. J. See Daniels, H. P. C.
Van der Werf, P. See Goorissen, J.
Van der Wielen, J. C. T. G. M., Stein, H. N., and Stevels, J. M. Glass formation in alkali Mo systems, (3) 56*f*.
Van der Ziel, A. Mode for the SbSI-SnO_2 heterostructure switch, (3) 63*i*.
Van der Ziel, J. P., and Van Uitert, L. G. Cr-Eu pair emission in $EuAlO_3$:Cr^{3+}, (5) 118*f*. Magnon-assisted optical emission in $YCrO_3$ and $LuCrO_3$, (5) 121*f*.
Van de Water, J. T., Van Hout, J. J., and Baelde, A. Heat-sink package for semiconductor integrated circuit, P (6) 137*i*.
Van de Water, P. W. M. Semiconductor device having an improved heat sink arrangement, P (4) 90*c*.
Van Dijk, H. J. A. Method of mfg. a semiconductor device and device manufactured by the method, P (5) 113*i*. Method of mfg. semiconductor devices in which a selective electrolytic etching process is used, P (2) 41*h*.
Van Doorn, C. Z. See Schipper, D. J.
Van Dornick, E. M. Reduction of alkali in cement production, P (3) 54*d*.
Van Duyne, R. E. Ceramic substrate interconnection device, P (10) 250*a*.
Van Es, A. C., and Waller, A. Process for the preparation of phosphoric acid and gypsum from phosphate rock, P (4) 94*h*.
Van Esdonk, J., and Janssen, J. F. M. Electric gas discharge tube having vacuum-tight sealing means for a plurality of supply leads positioned close together, P (9) 218*h*.
Van Heerden, P. J. See Goldberg, P.
Vanheertum, J. J. See Tavernier, B. H.
Van Heusden, S. See Te Velde, T. S.
Van Horn, J. L. Pigments for lasting colors, (11) 279*h*.
Van Hout, J. J. See van de Water, J. T.
Van Impe, J., Chaussonnet, P. E., and Rombaux,

J. P. M. Process for separating the core of a tubular nuclear fuel element, P (10) 254*c*.
Van Keulen, J. Frost resistance, (9) 220*h*.
Van Laer, K. J. B. Method of providing an electric connection to a surface of an electronic device and device obtained, P (3) 66*e*.
Van Laethem, R. Chemical and thermal tempering of vitreous materials, P (7) 161*j*. See Plumat, E.
Van Landuyt, J., Amelinckx, S., and Remeika, J. P. Domain formation accompanying the metal-insulator transition in $V_{2-x}Cr_xO_3$, (11) 281*e*.
Van Landuyt, J., de Ridder, R., Brabers, V. A. M., and Amelinckx, S. Jahn-Teller domains in $Mn_xFe_{3-x}O_4$ as observed by electron microscopy, (7) 178*a*.
Van Lierde, W., Pelsmackers, J., and Lecocq-Robert, A. Phase limits of U_4O_9, (1) 15*j*.
Van Loan, P. R. Conductive ternary oxides of Ru, and their use in thick film resistor glazes, (4) 86*d*. Electrical resistor containing Pb ruthenate, P (11) 274*f*.
Van Nielen, J. A. Semiconductor device comprising an FET having an insulated-gate electrode and circuit arrangement comprising such a device, P (3) 67*a*.
Vannorsdall, J. W. See Evans, J. L.
Van Peer, W. J., and Bannister, M. J. Preparation of dense MnO-MgO solid solutions, (9) 237*h*.
Van Reeuwijk, L. P. High-temp. phases of zeolites of the natrolite group, (9) 236*a*.
Van Tassel, J. H. See Marek, D. A.
Van Tongerloo, E. H. See Hantusch, G. H.
Van Uitert, L. G. See Bobeck, A. H.; Bonner, W. A.; Cohen, E.; Geusic, J. E.; Grodkiewicz, W. H.; Holmes, L.; Pinnow, D. A.; Singh, Shobha; Van der Ziel, J. P.
Van Vucht, J. H. N. See Donkersloot, H. C.
Van Willigen, B. J. Quality control in the heavy clay industry, (4) 83*d*.
Vanyarkho, V. G., Zlomanov, V. P., Novoselova, A. V., and Fokin, V. N. System PbSe-MnSe, (9) 239*f*.
Van Zandt, L. L. See Honig, J. M.
Varaksina, A. V. See Chaporova, I. N.
Vardiman, R. G. Preferred orientation of $NiAl_2O_4$ spinel grown on sapphire, (10) 260*j*.
Varekamp, R. R. P. See Perduijn, D. J.
Varga, J., Kosar, J., and Brand, M. Feeding devices for ceramic ovens, P (2) 45*f*.
Varitimos, T. E. See Weber, M. J.
Varlas, M. High-modulus graphite-fiber-reinforced hybrid laminates, P (6) 135*h*.
Varlow, J. See Harris, B.
Varner, L. P. See Hicks, D. G.
Varnerin, L. J., Jr. See Hackett, W. H., Jr.
Varrati, A. J. Apparatus for vacuum-forming hot top bottom rings, P (6) 135*d*.
Varshavskii, V. I. See Tokarev, G. I.
Varshneya, A. K. See Cooper, A. R.
Varshneya, A. K., and Cooper, A. R. Diffusion in the system K_2O-SrO-SiO_2 (II) cation self-diffusion coeff., (5) 105*j*; (III) interdiffusion coeffs., (7) 158*j*; (IV) mobility model, electrostatic effects, and multicomponent diffusion, (9) 216*h*.
Vasadi, F. Modern dressing and sintering technologies for dolomite and magnesite, (11) 279*f*.
Vasadi, F., and Nyitray, I. Novel-type obturator ring rotary furnace for mfg. of quicklime, (6) 129*f*.
Vaschetti, A. See Colombo, U.
Vasicek, Z. See Forman, I.
Vasil'ev, A. G. See Taranukhin, N. A.
Vasil'eva, A. G. See Nisel'son, L. A.
Vasilevskaya, I. I. See Nisel'son, L. A.
Vasil'kova, I. V., Podzorov, B. N., and Shapkin, P. S. Determination of the thermal capacities of Ti chlorides, (4) 93*a*.
Vasistha, S. R. See Mitra, N. K.
Vasselin, J. F. Method and apparatus for flame working mineral bodies, P (2) 46*i*; P (8) 203*j*.
Vassilevsky, A. N., and Renke, A. Lightweight high-strength cement compositions, P (9) 215*f*.
Vaughan, D. E. W. See Barrer, R. M.
Vautier, R. See Globus, A.
Veazie, F. M. See Brady, W. C.
Vecchi, G. Chemistry and technology of ceramic glazes (II), (7) 165*a*. Determination of the resistance to wear of flooring materials, (7) 165*f*. Moisture stress in unfired ceramic clay bodies, (7) 165*e*. See Emiliani, T.
Ved, E. I., Bludov, B. F., and Satarin, A. V. Method of changing electroconductivity of slurry, (8) 187*f*.
Vedam, K. See Schneider, W. C.
Vedam, K., and Davis, T. A. Pressure dependence of the refractive indices of the hexagonal crystals beryl, α-CdS, α-ZnS, and ZnO, (5) 122*g*.
Vedder, W. Tubular heating elements and MgO insulation therefor and method of production, P (3) 61*f*.
Vedrine, A., Besse, J. P., and Capestan, M. Hexafluorides of mono- and trivalent metals with elpasolite structure—various cation substitutions and solid solutions with compounds of related structure, (6) 148*b*.
Veeneman, D. See Driessens, F. C. M.
Vellex, R. Semiconductor device [GaAs] for producing and amplifying electrical signals of very high frequency, P (6) 140*b*.
Veillard, A. See Gladney, H. M.
Vekshina, N. V. See Markovskii, L. Ya.
Veldkamp, J. D. B., and Knippenberg, W. F. New reinforced materials, (9) 221*g*.
Velednitskii, I. P. See Meshengisser, M. Ya.
Velikanova, T. Ya. See Eremenko, V. N.
Velikodnyi, Yu. A., Kovba, L. M., and Trunov, V. K. Reaction of In tungstate with K tungstate, (2) 49*f*.
Veltri, R. D. See Galasso, F. S.
Venanzetti, M. Vibrating screen with one or more groups of screening elements, P (5) 115*j*.
Vendelin, G. D., and Webster, R. R. Low-capacitance planar varactor diode, P (4) 88*b*.
Venet, P. See Herrmann, F. J.
Venier, D. A. See Lass, J. L.
Venkatu, D. A. Discussion of "Compressive creep of rutile at high temps.," (2) 47*j*. See Hulbert, S. F.
Venkatu, D. A., and Johnson, D. L. Analysis of sintering equations pertaining to constant rates of heating, (1) 21*a*; correction, (3) 72*d*.
Verbeck, G. J. See Greening, N. R.
Verberkt, J. See Albers, W.
Veres, F. Glass sealing compositions containing Al titanate, P (6) 132*j*.
Vergnolle, J. See Glang, R.
Verhaegen, J. P. See Fierens, P.
Verheyden, L., Klein, K., and Kind, H. Direct vitreous SiO_2-metal sealing by soldering with an active metal—present state of the art, (7) 159*a*.
Verin, J. See De Mendez, M. O.
Verjans, H. C. See Perduijn, D. J.
Verkuijlen, W. H. C. G. See Theunissen, M. J. J.
Verma, J. R., and Mushran, S. P. Spectrophotometric determination of tetravalent V with *p*-substituted phenyl-azo-chromotropic acid dyes, (4) 98*h*.
Verma, S. S. See Bharadwaj, S. C.
Vernois, J., and Muxart, R. Hydrated protactinium(V) oxide, (6) 148*d*.
Verspui, G. See Bootsma, G. A.; Knippenberg, W. F.
Verulashvili, R. D. See Kutateladze, K. S.
Vesely, K. D. Mfg. of low bulk density-high strength spherical Cr_2O_3-Al_2O_3 particles, P (10) 257*g*.
Vetelino, J. F., and Mitra, S. S. Lattice dynamics of cubic SiC, (5) 121*h*.
Vezzoli, G. C. Electrical resistance of liquid S to 420°C and of liquid Se to 700°C, (3) 62*g*.
Vicard, P. Electrostatic dust separator, P (9) 230*a*.
Viccaro, P. J. See Barros, F. de S.
Vichy, M. See Picon, M.
Vickerman, J. C. Magnetic properties of Cr ions in oxide matrices (II) $MgCr_2O_4$-$MgAl_2O_4$ solid solutions, (1) 23*a*. See Stone, F. S.
Vickers, V. E. See Shepherd, F. D., Jr.
Vickery, R. C. Castable refractory die and model compositions, P (3) 61*c*. See Brigham, K.
Viehboeck, F. P. See Betz, G.
Vietzke, H. See Ploeger, F.
Vigliani, E. C. Silicosis and powder control in the Italian ceramic industry, (7) 182*f*.
Viglione, J., Jankowsky, E. J., and Ketcham, S. J. Effects of metallic coatings on the fatigue properties of high strength steels, (7) 157*h*.
Viktorov, E. A. Effect of oxide films in the impregnation of TiC with liquid steel, (10) 258*j*.
Vilardi, F. See Mashbane, A.
Vil'f, F. Zh., and Lysenko, A. P. Homogeneous semiconductor with interrelated antibarrier contacts, P (8) 200*i*.
Villard, M. See Combe, C.
Villers, P., Allen, M. A., and Mulvaney, J. M. Enhanced contrast semiconductor wafer alignment target, P (8) 200*b*.
Vincent, B. T., Jr. Semiconductor with improved heat dissipation characteristics, P (2) 42*e*.
Vincent, B. T., Jr., and Earhart, C. E. Method of making miniature hybrid integrated circuits, P (4) 89*b*.
Vincent, D. A. See Hantusch, G. H.
Vincent, J. H. Collecting apparatus for electrostatic precipitators, P (9) 229*h*.
Vincenzini, P. Experimental analysis on the impact strength of ceramic materials, (10) 259*e*.
Vincenzini, P., and Ortelli, G. Examination of Italian brick clays, (2) 46*b*.
Vinogradova, G. Z. See Timofeeva, N. V.
Vinokurov, V. I. See Kestner, O. E.
Viquesnel, A. Hot water tank enameling, (5) 105*c*.
Vishnevskii, V. B. See Beloivan, A. F.
Visser, T. J. M. See Cornelisse, C. W.
Viswanathan, C. R., and Ogura, S. Direct measurement of built-in voltage in MOS structures, (7) 166*e*.
Vitalis, G. Evaluation and comparison of geological and technical prospecting for cement raw materials in North Hungary, (2) 31*a*. See Hegyi-Pako, J.
Vitovsky, J. Measuring specific surface of powders, P (6) 142*f*.
Vitter, G. See Dontsov, G.; Hammou, A.
Viva, O. R. See Joshi, M. L.
Vivers, R. W. J. See Mills, A. L.
Vizir, L. A. See Morozova, G. P.
Vlachos, D. P. See Melillo, M. B.
Vlajic, M. See Abdel-Azim, M. S.
Vlasov, A. D. See Galkin, N. P.
Vlasova, M. T. See Potryasov, V. N.
Vlasyuk, R. Z., and Radomysel'skii, I. D. Behavior of glass in the sintering of metal-glass materials, (10) 242*j*.
Vodenicharov, M. Synthesis and properties of glasses in the quaternary system Na_2O-CaO-MgO-SiO_2 with an equimolar ratio of alkaline earth oxides, (2) 33*a*.
Voevodskaya, T. K. See Markovskii, L. Ya.
Vogel, C. H. See Haas, E.; Longo, H. E.
Vogel, G. J. See Jonke, A. A.
Vogel, H. E. Brick elevator, P (10) 246*b*.
Vogel, R. A. Fine line printing for consumer electronics, (11) 273*g*.
Vogel, S. F. Sputtering process for making ferroelectric films, P (10) 253*d*.
Vogel, W. Structure and Crystallization of Glasses, B (5) 126*b*.
Vogelbruch, W. See Bayer, E.
Vogg, E. See Stadler, G.
Vogl, N. G., Jr. See Chang, J. J.
Vogler, M., Daxer, H., Roeder, M., and Dietz, W. Apparatus for mfg. semiconductor substances from Ge-Si or Mo-Si, P (10) 249*f*.
Vohl, P. Apparatus and method for producing II-VI crystals [ZnSe], P (10) 249*e*.
Vohler, O. See Ernst, H.
Voigt, O., and Steimer, A. Apparatus for heating and controlling kiln atm, P (2) 45*f*.
Voinovitch, I. A. See Baron, A.
Volger, J. See De Vos, W. J.
Volkov, G. M., and Kotova, T. V. Structure of C deposits during the simultaneous pyrolysis of hydrocarbons with refractory-metal halides, (8) 196*b*.
Volkov, N. V. See Pirogov, A. A.
Volkov, O. S. See Budnikov, P. P.
Volkov, V. I., Tret'yakov, Yu. D., and Klimov, V. V. Kinetics of NiO sintering, (9) 236*c*.
Volpe, M. L., and Reddy, J. Cation self-diffusion and semiconductivity in NiO, (7) 176*d*.
Volterra, V. See Higgins, T. J.; Provenzano, V.
Volzhenskii, A. V., Chistov, Yu. D., and Garashin, V. R. Effect of temp. setting on the properties of portland cement, (8) 186*j*.
Von Chiari, B. See Schwiete, H. E.
Von der Decken, C. B. See Rausch, W.
Vondracek, M. Soviet spray dryer plants, (5) 115*j*.
Von Dreele, R. B. See Bless, P. W.
Von Freyhold, H. Process for the promotion of flow of aqueous inorganic solids dispersions, P (2) 38*b*.
Von Freyhold, H., and Wehle, V. Posttreatment of phosphatized metal surfaces with silicates, P (2) 32*a*. Process for the preparation of stabilized alkali metal silicate solutions, P (3) 71*h*.
Von Muench, W. See Drangeid, K. E.
Von Neida, A. R. See Shick, L. K.
Von Ohlsen, L. H., Jr. See Beadle, W. E.
Von Platen, B. C. See Jonsson, F. L.
Von Seebach, H. M. See Locher, F. W.
Von Strasser, R. Diamond-engraved glass service of the early 17th century, (11) 265*g*.
Von Willisen, F. K. See Mottier, F.
Vora, M. B. See Chang, J. J.; Lubart, N. D.
Voris, S. S. See Kim, C. K.
Vorob'ev, A. A. See Budnikov, P. P.
Voronchikhina, T. P., Lovygin, B. A., and Zhuravleva, Z. K. Statistical method for checking grain-size composition of refractory batches, (8) 196*a*.
Voronkova, R. M. See Kruglitskii, N. N.
Voronov, Yu. F. See Borisov, V. G.
Voronovich, L. P., and Cherpak, A. G. Modern slip preparation technology, (8) 198*a*.
Voroshilov, Yu. V., and Kuz'ma, Yu. B. Reaction of Zr with the transition metals and B, (10) 260*e*.
Voskresenskaya, N. K. See Krivovyazov, E. L.
Vosper, R. R. Duct burner for operation with liquid or gaseous fuels, P (11) 279*a*.
Voss, P. See Boer, K. W.
Vossen, J. L., Jr. Method of metalizing semiconductor devices, P (5) 113*j*.
Vossen, J. L., Jr., and Banfield, J. H. Method of making electrical contacts on the surface of a semiconductor device, P (5) 113*h*.
Vossos, P. H. Stabilizing aqueous deionized SiO_2 sols of small particle size against celling, P (6) 144*f*. See Kovarik, J. F.
Vrestalova, M. See Novak, J.
Vuaroqueaux, J. C. Refractory dressing method, P (10) 248*b*.
Vujnovic, V. W emissive properties, (8) 199*i*.
Vuksta, C. E. Standardizing specifications cuts everyone's costs, (2) 29*g*.
Vyse, J. See Astbury, N. F.
Vysokovsky, S. N. Analytical determination of balanced deformation of layered materials, (8) 207*j*.
Wacenske, H. R. See Santry, G. J.
Wach, J. See Tardif, A.
Wacher, P. Phosphor display screen and filter including Pt and Mn chloride derivatives of tetraphenylporphin, P (5) 113*g*.
Wachtel, A. Divalent Eu-activated alkaline-earth metal sulfates and method of preparation, P (9) 225*c*. Divalent rare earth activated 96% SiO_2 glass, (9) 216*h*. Multiple luminescent layer improved lumen maintenance combination, P (1) 5*e*.
Wada, Hiroaki. See Yamaguchi, Shigeto.

Wada, Kingo. See Ise, Yukihiko; Kaname, Yuichi.

Wada, Makoto. See Inoue, Noboru; Kurokawa, Takaaki.

Wada, Toru. Automatic brick setting machine for tunnel kiln car completed by and installed at Harima Refractories, Co., Ltd., (7) 163*f*.

Wada, Toru, and Asahara, G. Basic tests involving furnace design, material selection, block shaping, and conditions of construction for establishment of block system of furnace construction using unshaped refractories, (1) 6*f*.

Wada, Toshio. See Haneta, Yuichi; Matsukura, Yasuo; Nakanuma, Sho.

Wada, Toshio, and Nakanuma, S. Semiconductor integrated circuit device having improved wiring layer structure, P (8) 202*j*.

Wada, Toshio, Onoda, K., Igarashi, R., Nakanuma, S., and Tsujide, T. Electronic memory circuit employing semiconductor memory elements and a method for writing to the memory element. P (6) 137*d*.

Wada, Yasuo. See Okamoto, Fumio.

Waddell, E. P. Multiple-compartment grinding mills, P (3) 69*f*.

Waddell, J. J. See Perav, K.

Waddingham, J. L. See Wilson, J. D.

Wade, R. C. Aqueous coating compositions for glass articles, P (8) 192*a*.

Wadell, J. S. See Royse, C. F., Jr.

Wadsworth, M. E. See Hanson, C. K.

Waffle, A. L., and Barham, D. Direct production of ZrO_2 from zircon, (8) 195*b*.

Wageneder, F. Rotary impact crusher, P (2) 46*g*.

Waggener, H. A. See Lepselter, M. P.

Wagman, D. D. See Parker, V. B.

Wagner, J. B., Jr. See Chang, R. H.; Childs, P. E.; Price, J. B.

Wagner, J. W. Preparation and properties of bulk $In_{1-x}Ga_xAs$ alloys, (9) 237*g*.

Wagner, J. W., and Thompson, A. G. Growth and characterization of PbTe epitaxial layers, (9) 235*i*.

Wagner, J. W., and Willardson, R. K. Growth of $Pb_{1-x}Sn_xTe$ from nonstoichiometric melts, P (2) 40*j*.

Wagner, P., Dickinson, J. M., and Smith, Morton C. Polycrystalline graphite with controlled electrical conductivity, P (6) 139*c*.

Wagner, P., O'Rourke, J. A., and Armstrong, P. E. Porosity effects in polycrystalline graphite, (5) 122*f*.

Wagner, R. S. See Arthur, J. R., Jr.

Wagner, S. R. Cathodic sputtering method, P (4) 87*i*.

Wagner, W., and Hull, C. J. Inorganic Titrimetric Analysis—Contemporary Methods, B (1) 27*f*.

Wagner, W. E. See Donley, H. E.

Wahl, A. C. See Carlson, K. D.

Wahl, E. A. Apparatus for mixing particulate materials. P (1) 16*i*.

Wainer, E., Rose, S. H., and Harkulich, T. M. Channel multiplier of Al_2O_3 produced anodically, P (3) 64*b*.

Waits, R. K. Thin film resistor contact, P (6) 140*b*.

Wajda, E. S. Constrainment of autodoping in epitaxial deposition, P (8) 200*h*. See Joshi, M. L.

Wakabayashi, Hajimu. See Hayami, Ryozo.

Wakabayashi, Takashi. See Sato, Kunio.

Wakao, Yoshiyuki. See Ninomiya, Mitsuo.

Wake, Makoto. See Fujita, Tadao.

Wakefield, G., Boyd, W. W., and Rea, S. N. Refractory laminar films, (5) 112*b*.

Wakefield, G. F. Process for the vapor deposition of metals, P (3) 67*d*. Vapor phase deposition of silicide refractory coatings, P (8) 197*b*.

Wakefield, R. H. See Cunningham, J. A.

Wakefield, S. L. Production of Pb-Sn telluride material for ir detectors. P (10) 252*d*.

Wakely, W. T. See Rogers, B. C.

Wakim, F. G. See Ghosh, A. K.

Waksman, D. Jacketed fibrous duct, P (7) 162*e*.

Waku, Shigeru, Nishimura, A., Murakami, T., Yamali, A., Edahiro, T., and Uchidate, M. Classification and dielectric characteristics of the boundary layer ceramic dielectrics, (3) 62*h*.

Walberer, M. One-dimensional cutting problem in plate glass mfg., (8) 191*g*.

Walberg, A. C. Method of electrostatically coating with highly conductive materials, P (5) 105*e*.

Walchhuter, U. Apparatus for automatic depositing of glazed tiles in magazines arranged for subsequent firing. P (2) 38*a*.

Walczak, D. A. See Ernick, F. G.

Waldman, N. See Brubaker, B. D.

Waldner, M. See Pedinoff, M. E.

Waldron, B. B. See Greener, J. W.

Walker, A. B. See Brown, Robert F.

Walker, D. W. High-strength catalyst pellets, P (9) 239*g*.

Walker, E. G., and Holdridge, D. A. Vitrification and expansile characteristics of feldspathic and feldspathoid fluxes, (1) 26*a*.

Walker, E. S., and Westwood, W. D. Resistivity measurements on Ta microcircuits, (8) 205*c*.

Walker, J. See Clark, C. D.; Lowe, I. R. G.; Moltran, H. J.

Walker, R. E. See Kirchner, H. P.

Walker, R. H. Method and apparatus for mfg. [Al_2O_3] tumbling media, P (11) 265*e*.

Walker, W. C. See Whited, R. C.

Wallace, D. C. Thermodynamics of Crystals, B (11) 284*b*.

Wallace, R. W., Norton, C. L., Jr., Bart, R. K., and Brady, J. G. Precision studies of ASTM thermal conductivity test for refractories, (2) 4*g*.

Wallace, R. W., and Pavlica, S. R. Compaction of particulate matter, P (2) 43*j*.

Wallace, W. E., Jr. See Headley, L. C.

Waller, A. See van Es, A. C.

Wallick, C. R., Jr., Blodgett, W. E., and Lazor, D. K. Powder compacting press, P (9) 223*d*.

Wallington, F. L. Article inspection and reject system, P (8) 192*a*. See Banyas, J. D.; Mallory, J. D.

Wallis, G., Dorsey, J. J., and Beckett, J. Field assisted seals of glass to Fe-Ni-Co alloy, (1) 3*d*.

Wallis, G., Dorsey, J. J., and Phillips, B. L. Hermetic seal, P (6) 137*i*.

Walsh, A. Atomic absorption spectroscopy, P (6) 142*d*.

Walsh, P. J., Hall, J. E., Nicolaides, R., Defeo, S., Calella, P., Kuchmas, J., and Doremus, W. Experimental results in amorphous semiconductor switching behavior, (6) 148*b*.

Walsh, T. F. See Torok, A.

Walsh, W. J., and Pierce, R. D. Mixing and settling separation process for U or Pu, P (10) 254*a*.

Walter, J. A., and Troup, G. J. NMR studies of irradiated BeO (II), (5) 115*a*.

Walter, L. See Kemeny, G.

Waltermire, C. L. Fast warm-up indirectly heated cathode structure, P (9) 225*i*.

Walters, D. S., and Wirtz, G. P. Electron diffraction superlattice lines in Mg ferrite, (2) 47*b*. Kinetics of cation ordering in Mg ferrite, (1) 23*g*.

Walters, E. M. See Bobeck, A. H.

Walters, J. P., and Bruhns, T. V. Current-injection spark source for emission spectroscopy, P (7) 174*b*.

Walters, K. C. Segmented grinding wheel assembly, P (11) 265*f*.

Waltersson, K. See Loefgren, P.; Wilhelmi, K. A.

Walton, F. D. See Shamash, M. B.

Walton, R. R. See Price, T. F.

Walz, D. D. Method of making an inorganic reticulated foam structure, P (3) 61*g*.

Wamser, C. A. See Selman, M.

Wandres, J. Interview with Raymond Gallucci, (2) 30*a*. Porcelains of Kit Snyder, (2) 30*c*.

Wanesky, W. R. Releasable mounting and method of placing an oriented array of devices on the mounting, P (4) 90*h*. See Hance, P. R.

Wang, Chih-Chun. Epitaxial Si on HMg aluminate spinel single crystals, P (8) 200*c*. See Dismukes, J. P.

Wang, C. H. See Schuck, J. F.

Wang, C. L. Alpha production by 28.5-GeV proton incident on BeO. (6) 145*b*.

Wang, Mian-Chang, and Mitchell, J. K. New stress and strain gages for measurements in stabilized soil pavements, (7) 173*a*.

Wang, P., Van Buren, N., and Edraos, P. SEM observation of self-healing breakdown in thermally grown SiO_2 films, (2) 38*h*.

Wang, Rong, and Zielonka, J. M. Synthesis of Na zeolite W-Z, P (6) 144*g*.

Wang, Teh Po. See Starr, C. D.

Wanie, W. Drying and firing in the coarse and fine ceramic industries, (11) 276*i*.

Wanmaker, W. L., and Radielovic, D. Preparation of phosphors, (4) 86*e*.

Wanmaker, W. L., and Tak, M. G. A. Sr pyrophosphate as adhesive in luminescent screens, P (4) 91*a*.

Wanmaker, W. L., ter Vrugt, J. W., and de Bres, J. G. C. M. Luminescent material, P (6) 138*f*.

Warble, C. E. See de Bruin, H. J.

Ward, C. R. Apparatus for separating glass sheets, P (5) 106*j*.

Ward, E. S. See Kruppa, R. W.; Lester, W. C.

Ward, F. R. See McMillan, P. W.

Ward, G. V. See Borland, L. D.

Ward, H. F. Alkaline earth halosilicate phosphors, P (7) 168*h*.

Ward, J. C. See Reid, A. F.

Ward, J. E. Sizing composition and glass fibers treated therewith, P (7) 163*a*.

Ward, M. D. See Baxendale, J. H.

Ward, P. C. See Denes, L. J.

Ward, R. W. See Timusk, T.

Wardle, R., and Brindley, G. W. Dependence of the wavelength of $AlK\alpha$ radiation from aluminosilicates on the Al–O distance, (4) 96*a*.

Wardman, P. See Baxendale, J. H.

Ware, P. G. [Liquid fuel] burners, P (10) 256*i*.

Waren, F. A. O. See Mason, F. P.

Warner, A. W. See Coquin, G. A.

Warner, P. D. See Hirshon, J. M.

Warren, D. See Eastman, C.

Warren, H. D. Radiation detector solid state radiation detection using an insulator between the emitter and collector, P (1) 14*f*.

Wartenberg, E. W. Method of producing toughened glass, P (7) 162*e*. Process for producing prestressed glass, P (7) 162*h*.

Warter, P. J., Jr. See Comizzoli, R. B.

Warthen, J. L., and Cheavens, T. H. Process for producing high avg pore vol SiO_2, P (9) 233*a*.

Warzawski, B., Marioge, J. P., Mahe, C., Demarcq, J., and Mullot, M. Attempts at polishing glasses by electronic bombardment, (7) 166*c*.

Wasa, Kiyotaka. See Hada, Toshio.

Wasa, Kiyotaka, Hayakawa, S., and Hada, T. Electrical and optical properties of sputtered *np* ZnO-Si heterojunctions, (4) 96*i*.

Washburn, M. E. Control of shrinkage and growth of Si oxynitride bodies, P (10) 247*g*. Process for producing Si oxynitride, P (5) 110*b*.

Washio, Shigeaki. See Akazawa, Hakuichi.

Washio, Shigeaki, and Inoue, M. Production of refractory body, P (8) 196*j*.

Wasilewski, Z. See Kalabinski, B.

Watanabe, Akihiro. See Higuchi, Noboru.

Watanabe, Akinori. See Yano, T.

Watanabe, Akira. See Umeya, Kaoru.

Watanabe, Denjiro. See Terasaki, Osamu.

Watanabe, Fumio. See Muguruma, Hiroshi.

Watanabe, Hisashi, and Yamaga, I. Effect of grain size diam. in relation to the ferrite noise produced by audiomagnetic recording heads, (4) 86*f*.

Watanabe, Kinnosuke. See Kajiura, Hiroshi.

Watanabe, Koichi, Sumiyoshi, Y., and Anbo, E. Properties of SiO_2-B_2O_3-Na_2O glass, (3) 57*d*.

Watanabe, Naozo. See Kaneko, Kunio.

Watanabe, Osamu. See Tomizuka, Isao.

Watanabe, Osamu, and Shiota, T. Semiconductor strain gage, P (2) 42*e*.

Watanabe, Osamu, Tomizuka, I., and Ikesawa, H. C fiber coated with pyrolytic graphite, (5) 108*i*.

Watanabe, Satoshi. See Sasaki, Kiyoshi.

Watanabe, Shigeo, Akita, M., and Tanaka, T. Research on some properties of high-strength concrete, (6) 130*b*.

Watanabe, Shigeo, Akita, M., Yoshida, A., and Ichisa, M. 1968 test results of concrete in Tokyo metropolis, (6) 130*h*.

Watanabe, Takashi. See Hara, Ei.

Watanabe, Teisiro. See Uto, Yashimitsu.

Watanabe, Tetsuo. See Iwai, Shinichi.

Watanabe, Tetsuo, Morikawa, H., Saito, S., and Iwai, S. X-ray line profile analysis of rutile powder subjected to impact, (11) 283*c*.

Watanabe, Yoshio, and Sakai, T. Semiconductor device and method of producing, P (5) 114*d*.

Watanabe, Yutaka. See Kitagawa, Yasuo.

Watanarungsun, Ampon. See Hamano, Kenya.

Watano, Yutaka. Sliding thin-film resistor for measuring instruments. P (4) 90*i*.

Watanuki, Teruhiko. See Saito, Turuyoshi.

Waters, W. P. See Portnoy, W. M.

Waters, W. P., and Lovelace, B. K. Planar Schottky barrier, P (7) 170*d*.

Waterworth, T. H. See Gell, P. A. M.; Steitz, W. R.

Watkinson, D. H., and Wyllie, P. J. Experimental study of the composition join $NaAlSiO_4$-$CaCO_3$-H_2O and the genesis of alkalic rock-carbonatite complexes, (1) 22*h*.

Watson, A. N. Capacitor utilizing a glass sleeve as structural and spacing means, P (4) 87*i*. Capacitor with malleable means for providing a hermetic seal and strain relief, P (4) 87*h*.

Watson, D. D. See Brown, Lloyd H.

Watson, D. R. See Davis, J. E.

Watson, J. H. P. Composite superconductive body comprising a matrix of porous glass and a superconductive material, P (7) 168*a*.

Watson, R. C. Dual intensity signal lamp, P (5) 107*e*.

Watson, W. C. See Schweiker, M. A.

Watts, J. M. J. See Keig, G. A.

Watts, R. K. Doped Sr halide phosphor and device for ir to visible light conversion, P (3) 64*g*.

Waxler, R. M., and Cleek, G. W. Refractive indices of fused SiO_2 at low temps., (1) 3*h*.

Waye, B. E. Ceramic ferroelectrics, (1) 10*j*. See Oliver, J.

Waymouth, J. F. High-pressure electric discharge lamp having electrolysis-preventing means, P (3) 58*c*. See Lo, J. M.

Weaver, H., Jr., and Roaper, R. B., II. Cooling of pyrogenic TiO_2 pigment-containing gas streams, P (1) 20*c*.

Webb, J. E. Synthesis of Zn titanate pigment and coatings containing it, P (1) 3*a*.

Webb, J. M. See Loxley, T. A.; Mellen, E. J., Jr.

Webb, J. S. Analytical requirements in geochemistry, (9) 230*e*.

Webb, W. W. See King, C. Y.

Weber, H. Silicones in the ceramic industry, (11) 276*i*.

Weber, J. Filter press, P (3) 69*e*.

Weber, J. N. See White, R. A.

Weber, M. J. See Monchamp, R. R.

Weber, M. J., and Varitimos, T. E. Optical spectra and intensities of Nd^{3+} in $YAlO_3$, (7) 179*i*.

Weber, P. O., and Butschko, G., Jr. Apparatus for heat treatment of fine material, P (2) 45*f*.

Weber, R. A. See Schaefer, H.

Webster, R. Hydraulic control for gyratory crusher, P (1) 20*d*.

Webster, R. R. See Vendelin, G. D.

Wedel, W. v. Insulating structural units for dryers, kilns, etc., (5) 116*j*.

Wedemeyer, H. See Politis, C.

Weeks, G. A. See Crooker, P. P.

Weeks, I. A. See Bloom, H.

Weeks, R. A. See Chatelain, A.

Weeton, J. W. See Petrasek, D. W.

Weger, M. See Nebenzahl, I.

Wehle, V. See Von Freyhold, H.
Wehmeier, F. H. P. Growth of crystalline rare earth Fe garnets and orthoferrites by vapor transport, P (2) 40*j*.
Wehner, A. Screening machine [vibratory], P (4) 92*i*.
Weht, R. J. See Tabikh, A. A.
Weichman, F. L. See Taylor, J. C. W.
Weidman, V. W. See Gerow, S. A.
Weidmann, W. See Zirngibl, H.
Weiher, J. F. See Bouchard, R. J.
Weiher, R. L., and Tait, W. C. Observation of mixed-mode excitons in the photoluminescence of ZnO, (6) 150*c*.
Weijland, B. H. See Frentz, H.
Weimann, K. See Mueller, E.; Sattler, G.
Weiner, J. R. See Adamski, J. A.
Weiner, M. See Haag, A. P.
Weiner, M. E. Method of group III–V semiconductor crystal growth using getter-dried boric oxide encapsulant, P (6) 138*g*.
Weinerth, H. Method for mfg. a solid-state circuit adaptable as hf tuner, P (6) 139*a*.
Weinreich, G. See Henrich, V. E.
Weins, M. J., Gleiter, H., and Chalmers, B. Computer calculations of the structure and energy of high-angle grain boundaries, (5) 118*i*.
Weinstock, H. See Guenther, R. A.
Weintroub, S. See Ahmed, S.
Weinz, E. A. Methods and apparatus for cutting, grinding, and polishing single-crystal workpieces, P (7) 172*e*.
Weir, S. R. Method for concentrating slimed minerals, P (9) 232*i*. See Mercade, V.
Weiser, K. See Keyes, R. W.
Weiss, A. D. See Schroeder, D. A.
Weiss, C. W. See Heald, E. F.
Weiss, K. Diffusion-controlled sintering of binary oxides, (7) 177*c*.
Weiss, S. I. Annular cutting blades, P (5) 101*e*.
Weisselberg, E. B., Worden, G. M., Sr., Lamp, W. F., and Lane, A. M. Nondusting high-temp. dryer, P (11) 279*c*.
Weisshaar, E. Semiconductor element having at least 1 control electrode, P (6) 140*d*.
Weisweiler, W. Catalytic graphitization of glassy C with Fe and ferrosilicon in comparison with Ni, (8) 194*g*.
Weisz, R. S. See Chen, C. P.
Welch, B. J. See Grjotheim, K.
Wells, H., and Colclough, W. J. Treatment of fibrous materials, P (8) 203*f*.
Wells, W. O. See Graffeo, J. V., Jr.
Welsh, F. S. See Smith, R. T.
Welty, A. B., Jr. Sulfate control in NH_3 flue gas desulfurization, P (10) 256*j*.
Welty, J. M., Shiota, P., and Murray, R. W. Flip-chip integrated circuit and method therefor, P (5) 112*d*.
Wemple, S. H., DiDomenico, M., Jr., and Jayaraman, A. Electron scattering in perovskite-oxide ferroelectric semiconductors, (5) 120*j*.
Wen, Cheng P. Gyromagnetic isolator wherein even mode components are converted to odd mode components by biased ferrite, P (6) 137*h*. Transmission line formed by a dielectric body having a metalized nonplanar surface, P (4) 91*a*.
Wenckus, J. F. See Castonguay, R. A.
Wendler, C. F., and Baum, C. S. Heat-resistant high-strength composite structure of hard metal particles in a matrix and methods of making, P (11) 272*c*.
Wendler, F. See Peehs, M.
Wendling, E., Benali-Baitich, O., and Yaker, G. Adsorption spectrophotometric study of the systems Cu^{2+}-Cl^-, Ni^{2+}-Cl^-, and Co^{2+}-Cl^- in concentrated aqueous perchloric acid media, (6) 144*j*.
Wendt, J. A. See Kummer, G. L., Jr.
Wengert, P. R., and Bayard, M. Analysis of crystals in bubbles in glass, (1) 3*c*.
Wenkhous, D. R. See Junge, A. E.
Wenninger, C. E. [Foundry] sand mulling apparatus, P (1) 16*i*.
Wensink, B. L., and Cense, A. Integrated semiconductor device, P (9) 225*e*. Semiconductor device, P (10) 252*g*.
Wentorf, R. H., Jr. Monitoring means for temp. and piston stroke in superpressure apparatus, P (3) 69*e*. Reaction vessel for high-pressure apparatus, P (2) 29*i*.
Wenz, D. A. Pu separation from U, P (1) 16*d*. See Nelson, P. A.
Wenzel, K. Electrical element laminated in structure, P (10) 250*j*.
Wenzig, W. Variable capacitance diode, P (10) 253*e*.
Werner, A. J. Rutile TiO_2 pigment for paper laminates, P (9) 257*i*.
Werner, L. C. See Knochel, W. J.
Werner, L. C., and Kane, R. M. Arc tube centering device, P (3) 57*h*.
Wernick, J. H. See Buehler, E.
Wertheim, G. K. See Robbins, M.
Wertz, J. E. See Davies, J. J.; O'Mara, W. C.; Smith, S. R. P.
Wesch, L. Apparatus for mfg. of fiber-glass-reinforced plastic tubes and similar bodies, P (4) 81*i*. Process and apparatus for mfg. fiber glass reinforced plastic tubes and similar bodies according to the filament winding process, P (3) 59*c*.
Wesseling, G. Adhesion problems in the laying of tiles, (5) 110*d*. Laid tiles, (5) 110*g*.
West, A. R., and Glasser, F. P. Preparation and crystal chemistry of some tetrahedral Li_3PO_4-type compounds, (8) 210*f*.
West, E. D., Case, W. E., Rasmussen, A. L., and Schmidt, L. B. Reference calorimeter for laser energy measurements, (7) 173*c*.
West, H. W. H. Performance of walls built of wirecut bricks with and without perforations (I) basis of experimentation, (9) 220*g*. See Beech, D. G.
West, H. W. H., and Hodgkinson, H. R. Performance of walls built of wirecut bricks with and without perforations (III) tests of rain penetration, (9) 220*i*.
West, H. W. H., Hodgkinson, H. R., Beech, D. G., and Davenport, S. T. E. Performance of walls built of wirecut bricks with and without perforations (II) strength tests, (9) 220*h*.
West, J. E. See Sessler, G. M.
West, K. W. See Eibschuetz, M.
West, R., and Gerow, J. V. Estimation and optimization of glaze properties, (11) 272*j*.
West, R. N., Brook, R. A., Shaw, R. G., Lobb, D. R., and Allnutt, A. J. Method and electrooptical system for inspecting bodies such as tiles, P (10) 248*f*.
Westendorp, F. F. See Luiten, W.
Westendorp, F. F., and Rijnbeek, A. G. Method of making a permanent-magnetizable body of compressed fine particles of a compound of M and R, P (8) 201*c*.
Westerlund-Sundback, M. Crystal structure of $W_2O_3(AsO_4)_2$, (3) 72*i*.
Westman, E. See Landa, T.
Weston, R. F., and Furmidge, K. F. [Fused SiO_2] arc tubes, P (3) 58*d*.
Westwood, A. R. C. See Hollox, G. E.
Westwood, W. D. See Walker, E. S.
Westwood, W. D., and Sadler, A. G. Comparison of methods for the quantitative phase analysis of ceramics—the NiO–α-Fe_2O_3 system, (11) 277*i*.
Wetzenstein, W. Quantitative X-ray determination of the minerals montmorillonite, kaolinite, quartz, and alunite, (6) 142*d*.
Wey, R. See Guth, J. L.
Weyl, W. A. Modification of surface properties of glasses by chemical reactions, (8) 191*c*. See Marboe, E. C.
Weyland, J. A. Another look at the pressure dependence of interstitial-substitutional dissociative diffusion, (7) 176*h*.
Weymouth, J. H. See Petty, M. A.
Whaley, H. L. See Adler, L.
Whaley, H. L., and Adler, L. Determining the size of flaws in materials, (3) 69*i*.
Whang, T. J. See Cunningham, W. P.
Whapham, A. D. Formation of gas bubbles in fissile material during reactor irradiation, (6) 140*j*.
Whately, T. L. See Stuart, W. I.
Whatley, M. E. Method for reprocessing molten fluoride salt reactor fuels, P (10) 253*i*.
Wheat, T. A., and Carruthers, T. G. Hot-pressing behavior of Al_2O_3 gel and boehmite, (1) 22*e*.
Wheatly, C. F., Jr. See Einthoven, W. G.
Wheeler, B. D. Apparatus [press] for preparing spectrographic sample, P (11) 278*g*.
Wheeler, J., and Chatterji, S. Settling of particles in fresh cement pastes, (10) 242*f*.
Wheeler, J. C., and Gordon, R. G. Rigorous bounds for thermodynamic properties of harmonic solids, (4) 98*c*.
Wheeler, P. J. Electrochemical analyzer for measuring the O content of hot gases, P (1) 18*e*.
Wheeler, W. R. See Robertson, D. D.
Wheelock, T. D., and Boylan, D. R. Process for high-temp. gaseous reduction of $CaSO_4$, P (1) 2*g*.
Whippey, P. W. See Schlesinger, M.
Whipps, P. W. Stability regions for the growth of Ba-Sr niobate crystals, (10) 261*d*.
Whitaker, A., and Darby, I. A. Phase equilibria in the high-MgO corner of the system MgO-ThO_2-B_2O_3 at 1200°C, (2) 48*d*.
Whitaker, N. D. Method for making thermosetting resinous abrasive tools, P (8) 185*f*.
White, A. H. See Golding, R. M.
White, C. W. See Tolk, N. H.
White, D. See Sansom, K. G.
White, Donald L., Donaldson, E. B., and Middleton, A. J. Refractory bed for gas machine and process for producing oil gas, P (1) 9*b*.
White, E. W. See White, R. A.
White, G. D. See Dusek, J. T.
White, H. G. See Logan, R. A.
White, I. G., and Grimshaw, R. W. Determination of crystalline quartz by DTA—modification to technique, (1) 17*h*.
White, J. See Hatfield, T.; Taylor, M. I.
White, James C. Apparatus for grinding glass slides or the like, P (9) 218*c*. Apparatus for mfg. assemblies of closed glass tubes each with a pellet therein, P (7) 161*f*. Glass-cutting apparatus and method, P (4) 82*a*.
White, Jerry E. See Rao, V. D.
White, J. L. See Juo, A. S. R.
White, J. M. Method for metalizing BeO at low temps., P (6) 139*c*.
White, P. L. Mechanical relaxations of Li-Cu aluminosilicate glasses, (2) 32*d*.
White, R. A., Weber, J. N., and White, E. W. Replamineform—a new process for preparing porous ceramic, metal, and polymer prosthetic materials, (10) 254*d*.
White, Robert L. See Allen, J. W.
White, Robert M. Magnetic field dependence of indirect transitions in ferromagnetic semiconductors, (9) 236*e*.
White, William B. See O'Horo, M. P.; **Porter, V. R.**
White, William R. See Chemtob, E. M.
Whited, R. C., and Walker, W. C. Exciton and interband spectra of crystalline CaO, (6) 148*b*. Exciton spectra of CaO and MgO, (6) 148*b*.
Whitehead, D. M. See Desty, D. H.
Whitehead, J. See Williams, Frank R.
Whiteheart, C. Electrical contact brushes, P (1) 12*h*.
Whitehouse, R. G. Furnaces, P (9) 215*j*.
Whitehouse, W. E., and Riley, R. R. Refractory construction units with high temp. bonding joint fillers and method of making said units, P (2) 37*e*.
Whiting, G. Quality in glazes, (11) 266*e*.
Whitley, J. B., and Iannicelli, J. Method for producing mineral products, P (9) 233*b*.
Whitmarsh, R. B. Precise sediment density determination by γ-ray attenuation alone, (3) 70*b*.
Whitner, R. A. See Burock, R.
Whitney, A. G. See DeKalb, A.
Whitney, I. Method of mfg. C fibers, P (10) 248*b*.
Whitney, I., and Johnson, J. W. Method of mfg. C fibers, P (2) 37*a*.
Whittaker, M. P., and Wilson, W. F. Method of graphitization, P (2) 37*g*.
Wickersheim, K. A. See Alves, R. V.; **Sobon, L. E.**
Wickham, D. G. Reactions of $LiFeO_2$ and the formation of spinels, (7) 180*c*.
Wicks, B. J. Direct observations of the internal structure of C fibers, (5) 119*f*.
Wickstrom, R. A. See Nathanson, H. C.
Widakowich, M. See Lundquist, D.
Wideman, L. H. Container-handling chuck, P (2) 33*h*.
Widman, H. Sintering of highly refractory oxides, (5) 123*h*.
Widmann, D., Kappelmeyer, R., Schlueter, K., and Steggewentz, H. Contact exposure mask for the selective exposure of photovarnish coatings for semiconductor purposes, P (6) 137*j*.
Widmer, A. E. Zn diffusion into GaP, P (7) 170*i*.
Widmont, J. C. See De Forest, W. S.
Wiedeking, E. Graphite tube spectroscopy sample cell including illumination and observation structure, P (9) 231*g*.
Wieder, H. Mode perturbations and filamentary coupling in GaAs lasers, (5) 111*j*.
Wieder, H., Lavenberg, S. S., Fan, G. J., and Burn, R. A. Study of thermomagnetic remanence writing on EuO, (5) 124*j*.
Wiederhorn, S. M. Chemical interpretation of static fatigue, (3) 72*f*.
Wiederhorn, S. M., and Johnson, H. Effect of pressure on static fatigue of glass, (1) 3*d*.
Wiedmann, S. K. Inverse transistor with high current gain, P (8) 200*j*.
Wiedmann, T. Investigation of the H_2O absorption and frost resistance of glazed grooved tiles (III), (5) 108*f*; (IV), (11) 271*a*.
Wiegmann, W. See Logan, R. A.
Wiehe, A. E., and Mott, L. W. Coated consumable guide tube for electroslag welding, P (3) 54*i*.
Wieker, W. New methods in silicate chemistry, (11) 278*f*.
Wielinga, P. S. Process of mfg. structural elements, P (7) 157*f*.
Wiene, H. W. See Urbach, J.
Wiener, E., Levin, S., and Pelah, I. Antiferroelectric transitions in $NH_4H_2PO_4$ and $NH_4H_2AsO_4$ studied by ir absorption, (5) 118*i*. Proton dynamics in KH_2PO_4-type ferroelectrics studied by ir absorption, (5) 122*j*.
Wierich, H., and Schwiete, H. E. Influence of the furnace atm on the hot crushing strength of various refractories, (1) 7*h*.
Wiesboeck, R. A. Fluorination of boric acid and phosphorous acid, P (4) 94*h*.
Wiesler, M., and Macintyre, J. S. Apparatus for [automatically] bonding semiconductive devices, P (9) 224*h*. [Tape] package for electronic devices and the like, P (2) 42*i*.
Wiesner, K. H. See Dislich, H.
Wiggins, P. F. See Duffey, D.
Wigley, D. A. Mechanical Properties of Materials at Low Temp., B (7) 183*d*.
Wigmore, J. K. See Lewiner, J.
Wiker, F. See Rupprecht, C. F.
Wilburn, W. E. See Townsend, L. W., Jr.
Wilcock, R. J. See Jackson, B. L. J.
Wilcox, D. L. See Young, W. S.
Wilcox, P. D. See Buckner, D. A.
Wilcox, W. R. See Baughman, R. J.
Wilcox, W. R., and Leon, A. Twinning of KBr, (7) 182*a*.
Wilde, D. F. See Passmore, E. M.
Wilder, D. R. See Stacy, D. W.
Wilding, M. D. Coating glass filaments, P (10) 243*j*.
Wiley, R. F. Glass gob delivery, P (7) 161*j*.
Wilhelmi, K. A. See Danielsson, L.
Wilhelmi, K. A., Lagervall, E., and Muller, O. Crystal structure of $Nd_4Re_2O_{11}$, (5) 119*c*.
Wilhelmi, K. A., and Waltersson, K. Crystal structure of V_4O_9, (1) 21*f*.
Wilkalis, J. E. See Selman, M.
Wilke, W. See Donaldson, W. K.
Wilkens, K. See Engel, O.
Wilkes, A., and Pearson, A. W. Project management in research and development, (4) 100*a*.

Wilkins, B. J. S. Static fatigue of graphite, (1) 25*g*.
Wilkins, B. J. S., and Reich, A. R. Resistance of SiC to dynamic fatigue, (6) 134*i*.
Wilkins, C. W. See Hart, P. B.
Wilkins, P. E. Clean air act—implications for industry, (5) 126*a*.
Wilkinson, J. F. G. Petrology of some vitrophyric calc-alkaline volcanics from the Carboniferous of New South Wales, (8) 209*j*.
Wilks, E. M. See Cotty, W. F.
Wilks, J. See Casey, M.
Willardson, R. K. See Wagner, J. W.
Willardson, R. K., Allred, W. P., and Cook, J. E. GaAs, P (4) 88*a*.
Willcox, D. J. Red clay renaissance in Finland, (2) 30*c*.
Willcox, O. B. Coating glass particles with an oxygen-containing compound to prevent sticking during heating, P (8) 192*c*.
Willem, J. See Nienhuis, W. F.
Willemsen, P. J. M. Low-pressure discharge lamp having an envelope encompassing the discharge space and consisting inter alia of a support, P (6) 138*e*.
Willett, C. S. Method and apparatus for obtaining high-resolution X-ray interference patterns, P (4) 93*f*.
Williams, Albert E. Mfg. of nuclear reactor fuel elements, P (9) 228*i*.
Williams, A. W. S. See Collins, A. T.
Williams, A. W. S., Lightowlers, E. C., and Collins, A. T. Ac Hall effect measurements on synthetic semiconducting diamond, (4) 86*c*.
Williams, C. R. See Isaksen, R. A.
Williams, Ferd. See Lauer, R. B.
Williams, Frank R. See Hughes, W.
Williams, Frank R., Whitehead, J., Marshall, J., Conners, A., and Gosden, D. V. Beneficiating Fe-containing titaniferous material, P (6) 143*i*. Process of beneficiating titaniferous beach sand, P (10) 257*c*.
Williams, G. F. Method and apparatus for drawing a devitrifiable glass at a temp. below the liquidus temp., P (1) 4*d*.
Williams, J. C. CaO-Al_2O_3-SiO_2 ceramic substrate material for thin-film circuits, P (2) 39*e*. See DiMarcello, F. V.
Williams, Lyle K. See Evans, L. W.; Faria, S.
Williams, P. D. Process for making oxide cathodes having improved thermal emissivity, P (3) 67*b*.
Williams, R. L. See Osment, H. E.
Williams, Robert M. Material-reducing hammer mill, P (9) 230*d*. O-deficient material-reducing system and apparatus therefor, P (2) 44*b*.
Williams, Robert P. See Cunningham, J. A.
Williams, R. T. See Chen, Yok.
Williams, Ray T. See Yalof, S. A.
Williams, S. B. See Dornfeld, J. E.
Williams, W. S. See Bachmann, K.; Shacklette, L. W.
Williamson, W. O. See Arakawa, Masafumi.
Willson, P. J. See Teague, D. M.
Wilson, E. J. See Kreidler, E. R.
Wilson, G. H. See Jenkins, R. T.
Wilson, H. A. See Greene, L. C.
Wilson, H. E. Dual intensity signal lamp, P (5) 107*e*.
Wilson, H. H. See Hulbert, S. F.
Wilson, J. D., Donoghue, B. R., and Waddingham, J. L. Apparatus for hydraulic crushing, P (1) 20*j*.
Wilson, L. E. Strengthened photosensitive opal glass, P (8) 194*c*.
Wilson, L. K. See Dozier, A. W.; Friebele, E. J.
Wilson, O. W. Photoconductive detector material, P (10) 252*h*.
Wilson, R. C., Jr. Clinoptilolite blends with shape-selective catalyst, P (5) 117*f*.
Wilson, R. H. See Schaefer, D. L.
Wilson, R. W. See Andrysiak, C. D.; Ihrig, A. C.; Petermann, J. P.
Wilson, W. F. See Whittaker, M. P.
Wilson, W. L. See Hoekje, H. H.; Holden, C. B.; Sheppard, R. S.
Wiltshire, A. J. Preform roller, P (10) 245*a*.
Wiltshire, A. J., Ranallo, H. U., and Czumber, F. E. Fiber preform and method and apparatus for making, P (7) 161*e*.
Wilyman, P. See Mahajan, S.
Wincierz, P. See Borgstedt, H. U.
Winer, A. A. Relatively rapid system for measuring the size distribution of variform particulates, (8) 205*b*.
Winfree, J. J. Brick wall construction, P (5) 108*f*.
Winget, J. O., and Linstrom, R. E. Separation of rare earth elements by ion exchange, P (2) 46*h*.
Winkworth, D. A. See Laws, W. R.
Winn, J. B., Jr. Apparatus for dispensing catalyst-coated fibers and cementitious material onto a surface, P (10) 243*f*.
Winnick, J. M. Method of forming a foam cored wall panel having ceramic tile on one face, P (6) 136*c*.
Winnicki, H. S. See Seglin, L.
Winstel, G. See Zschauer, K. H.
Winter, E. See Caimann, V.; Draeger, T.
Winter, G. See Zirngibl, H.
Winyall, M. E. Anhydrous silicic acid organosols, P (8) 196*f*.
Winyall, M. E., and Acker, E. G. Process for preparing microspheroidal desiccant SiO_2 gel, P (1) 20*h*.
Wirkus, C. D. See McGee, T. D.
Wirth, D. G., Jr. See Rettew, R. R.
Wirtz, G. P. See Walters, D. S.
Wirtz, L. H. See Lussow, R. O.
Wise, J. F. Si solar cell array hardened to space nuclear blast radiation, P (3) 67*h*.
Wishnie, F. T. See Broderick, J. P.
Wishon, B. E., and Crosby, D. P. Fireclay refractory articles, P (8) 196*i*.
Wisman, E. C. See Portnoy, W. M.
Wisseman, W. R. Traveling high-gain amplifier [GaAs], P (3) 68*c*.
Wissinger, H. See Siegmar, W.
Withers, J. C. See McCandless, L. C.
Witkin, D. E. Yoke-type isostatic press, P (7) 172*i*.
Witt, H. J. See Stancioff, D. J.
Wittekoek, S., and Bongers, P. F. Magneto-optical investigation of the band edge of $CdCr_2S_4$ and related absorption measurements on Cr-doped $CdIn_2S_4$, (9) 236*f*.
Witteman, W. J., and Zalm, P. Device for producing stimulated ir emission (iraser) by means of an electric discharge in a gas mixture consisting at least partly of carbonic acid gas and discharge tube for such a device, P (2) 40*b*.
Witting, H. L. Electric lamp apparatus having diffusion barrier, P (11) 270*e*.
Wittmann, F. See Englert, G.
Wittmoser, A., Schade, J., and Krzyzanowski, E. Gasifiable casting core, P (7) 164*d*.
Wixted, J. M. See Fleck, H. G.
Wladyslaw, B. See Clayton, C. G.
Woerner, L. M., Kivela, W. C., and Qunal, G. J. SiC-encased graphite articles and their production, P (4) 85*b*.
Wohlfarth, E. See Nitzsche, S.
Wojcik, G. E. Electroconductive sintered glass, P (5) 107*e*. Novel foamable glass compositions comprising Cu, P (3) 59*a*.
Wojnarovits-Hrapka, I. Relations between structural parameters of basalt glasses, (6) 132*f*. See Kocsis, G.
Wold, A. See Schlein, W. S.
Wolf, E. L. See Losee, D. L.
Wolf, J. D. See Little, E. L., Jr.
Wolf, K. See Gender, J. R.
Wolf, W. Apparatus for producing a hollow hammer handle with longitudinally tensioned glass fibers, P (7) 161*g*.
Wolf, W. W. See Brady, W. C.
Wolfe, C. M., Stillman, G. E., and Owens, E. B. Residual impurities in high-purity epitaxial GaAs, (2) 38*h*.
Wolfe, R. Magnetic element using isolated domains in rare-earth orthoferrites, P (6) 138*h*. See Kurtzig, A. J.; Robbins, M.
Wolfe, R. W. See Newnham, R. E.
Wolfersperger, J. J. Two-chamber fuel burner, P (10) 256*j*.
Wolfmeyer, M. W. See Fox, G. T.
Wolfram, T. See DeWames, R. E.
Wollam, J. Equipment for the chemical vapor deposition of ultrauniform SiO_2 films, (10) 249*c*.
Wollast, R., Brennet, P., and Jelli, A. Attack of a soda-lime glass in a strong acid medium, (11) 267*i*.
Wolosin, S. M. See Ettinger, B. L.
Wones, D. R. See Hazen, R. M.
Wong, Eugene Y. See Leung, A. F.; Stafsudd, O. M.
Wong, Philip, and Messier, D. R. Production of single-crystal Al_2O_3, P (8) 202*f*.
Wong, R., and Hill, H. G. Method of producing bonded randomly oriented glass fiber mats and bats, P (9) 219*c*.
Wong, Yeng P. See Merz, J. P.
Woock, H. J. Method of preparing, maintaining, and controlling the supply and consistency of hard facing slurry, P (11) 277*d*.
Wood, B. V. Impact crusher, P (7) 175*c*.
Wood, C. See Schottmiller, J. C.
Wood, C., Schottmiller, J. C., and Roy, R. Electrophotographic devitrified glass binder plate, P (7) 161*d*.
Wood, D. L., Holmes, L. M., and Remeika, J. P. Exchange fields and optical Zeeman effect in $ErFeO_3$, (5) 120*e*.
Wood, J. R., and Wright, J. D. Solder bump metalization system using a Ti-Ni barrier layer, P (8) 202*c*.
Wood, L. Sack casting, (2) 30*d*.
Wood, R. T. See Macarus, D. P.; Upson, L. L.
Wood, S. J., Jr. See Cunningham, J. A.
Woodall, H. C., Jr. See Nisbet, J. L.
Woodall, J. M. Converter of electromagnetic radiation to electrical power, P (10) 250*e*.
Woodcock, L. V., and Singer, K. Thermodynamic and structural properties of liquid ionic salts obtained by Monte Carlo computation (I) KCl, (5) 125*c*.
Woodcock, R. F. See Snitzer, E.
Woodham, G. W., and Stuart, J. L. Method for the continuous production of glass-fiber-reinforced thermoplastics, P (7) 162*b*.
Woodhouse, D. Refractories development for arc furnace steelmaking, (2) 36*d*.
Woodman, B. Teapots, (2) 30*e*.
Woods, K. N., and Doremus, R. H. Measurement of inert gas diffusion in glasses by the powder method, (2) 32*b*.
Woods, L. See Mills, H.
Wooldridge, J. E., and Yamasaki, G. K. As-Sb-Bi hollow cathode lamp, P (6)) 132*b*.
Woolfrey, J. L. Effect of green density on the initial-stage sintering kinetics of UO_2, (9) 228*h*.
Woolfrey, J. L., and Bannister, M. J. Nonisothermal techniques for studying initial-stage sintering, (9) 237*f*.
Wooten, F. T. See Sheng, H. P.
Word, J. C., IV. See Fisher, P. D.
Worden, G. M., Sr. See Weisselberg, E. B.
Worden, R. D. Quartz holder for supporting wafers, P (2) 42*e*.
Worrall, W. E. See Davis, G. A.; Joyce, I. H.
Worrell, W. L. See Belton, G. R.
Worstell, E. M., Jr. See Redwine, D. J.
Worthington, J. V. Continuously operable mixing and kneading device, P (8) 203*g*.
Wortman, D. E. See Morrison, C. A.
Wortman, D. E., and Sanders, D. Ground-term energy levels of triply ionized Ho in Ca tungstate, (7) 177*h*.
Wotke, H. See Betz, G.
Woulbroun, J. M. See Mason, D. W.
Wray, J. H. Refractive index of several glasses as a function of wavelength and temp., (1) 3*h*.
Wright, A. N., and Merrill, R. C. Removal of organic polymeric films from a substrate, P (9) 227*c*.
Wright, D. A. See Casselton, R. E. W.
Wright, E. S. Production of SiO_2 brick, P (11) 272*f*.
Wright, G. F. See Srivastava, K. K.
Wright, J. D. See Wood, J. R.
Wright, J. W. T., and Humphery, T. Incandescent filament lamps, P (4) 82*d*.
Wright, R. E. Acoustic emission of Al titanate, (2) 38*d*.
Wright, T. R. See Roehrig, F. K.
Wu, B. P. F. See Chang, J. J.
Wuhrer, J., Kurczyk, H. G., and Ottenheym, A. Process for the production of synthetic diopside, P (7) 175*j*.
Wulff, C. A. See Heller, K. H.
Wullaert, R. A. See Chubb, W.
Wunderlich, D. See Singer, H.
Wurm, J. G., and Payrissat, M. Method of decanning nuclear fuel elements having a can of stainless steel, P (9) 228*j*.
Wurst, J. C., and Nelson, J. A. Lineal intercept technique for measuring grain size in 2-phase polycrystalline ceramics, (3) 69*h*.
Wyatt, B. S. UO_2 article and method of producing, P (2) 43*e*.
Wyatt, M. E. See Flanagan, T. M.
Wyatt, P. J. Microparticle analyzer employing a spherical detector array, P (3) 70*f*.
Wyckoff, R. E. See Stalego, C. J.
Wyllie, P. J. See Watkinson, D. H.
Wyss, H. Method for the production of electrical resistor bodies and the bodies produced, P (10) 252*c*.

Yada, Keiji. Microstructure of chrysotile asbestos by high-resolution electron microscopy, (9) 236*i*.
Yager, B. P. See Adams, A. L.; King, L. C.
Yagi, Hajime. Field-effect transistor, P (8) 200*e*.
Yagnik, C. M. See Canner, J. P.
Yagodin, P. P. See Meshengisser, M. Ya.
Yahagi, Kichinosuke. See Katsuta, Yukio.
Yajima, Seishi. See Aoki, Koichi.
Yaker, G. See Wendling, E.
Yakerson, V. I. See Shikunov, B. I.
Yakovlev, A. A. See Kestner, O. E.
Yakovleva, M. A. See Aslanova, M. S.
Yakubov, T. S. See Bering, B. P.
Yakunina, G. M., Alekseenko, L. A., and Serebrennikov, V. V. Thermal stability of the iodates of the rare-earth elements and Y, (8) 211*a*.
Yale, R. L. Rare earth oxide phosphors containing alkali metal silicates and germanates, P (7) 170*h*. See Mathers, J. E.
Yalof, S. A., and Williams, Ray T. Cutting tool with B filament composite, P (3) 53*f*.
Yam, V. M. Effect of force factors on density of products during vibroimpact consolidation, (8) 203*i*.
Yam, V. M., Stepanov, V. F., Krasotkina, N. I., Shumeiko, R. M., Evseenko, N. K., and Oleinik, V. T. Vibroimpact molding of large SiC shapes, (8) 196*e*.
Yamada, Eiichi. Method of selective etching, P (2) 41*b*.
Yamada, Eiichi, and Yamamoto, M. Method for mfg. semiconductor device with passivation film, P (2) 41*h*.
Yamada, Eiichi, Arakawa, Y., Yamamoto, M., and Nagatomo, H. Apparatus for [gas] forming films, P (5) 112*e*.
Yamada, Hisao. See Urabe, Kazuyori.
Yamada, Junji. See Kurokawa, Takaaki.
Yamada, Masatoshi, and Okabe, J. Effect of lignosulfonate type H_2O-reducing admixtures on some properties of extremely high-early-strength portland cement (Super-velo Cement), (10) 241*h*.
Yamada, Naoto, and Shionoya, S. Vibronic transitions of Eu^{2+} ions in $CaWO_4$ and other tungstates, (3) 76*a*.
Yamada, Shigehiko. See Hoda, Tokiti.
Yamada, Shigeki, Miyazawa, K., Naka, H., and Yoshida, Y. Process for the preparation of TiO_2 concentrates, P (8) 196*j*.
Yamada, Tadashi. See Yamashita, Akio.
Yamada, Tetsuya. See Inoue, Touru.
Yamada, Tomoaki, and Niizeki, N. New formulation of piezoelectric plate thickness vibration, (3) 63*i*.
Yamada, Toyoaki. See Noguchi, Tetsuo.
Yamada, Yoshito. See Shirane, Gen.
Yamada, Yoshito, Shirane, G., and Linz, A. Study of critical fluctuations in $BaTiO_3$ by neutron scattering, (5) 124*i*.
Yamaga, Isao. See Watanabe, Hisashi.

Yamagami, Teiichi. See Matsushita, Tatsuhiko.
Yamagishi, Takashi. Pulverizer, P (2) 46*g*.
Yamagiwa, Yasuhide. See Asano, Shunkichi; Inoue, Yoshiki.
Yamaguchi, Akira. Corrosion of basic bricks by alkaline vapors, (3) 60*h*. Effect of acid radical components of alkali salts on corrosion of mullite and zircon by alkaline vapors, (5) 103*f*. $K_2O{\cdot}Al_2O_3{\cdot}SiO_2$ and $K_2O{\cdot}Al_2O_3$, (2) 48*j*.
Yamaguchi, Akira, and Sakakura, M. Reactions of vapors of molten mixed alkali salts with refractory materials, (6) 134*f*.
Yamaguchi, Fumio. See Kawamura, Susumu.
Yamaguchi, Goro. See Nakano, Mitsuko.
Yamaguchi, Goro, and Nakano, M. Proposal of a new diffusion equation related to solid state reactions, (3) 74*i*.
Yamaguchi, Goro, Nakano, M., and Uchimura, R. Measurement of the interdiffusion coeff. of Mg^{2+} and Al^{3+} ions in the defective spinel $MgO{\cdot}nAl_2O_3$ and analysis of the reaction rate of spinel formation, (5) 121*g*.
Yamaguchi, Goro, Shirasuka, K., and Morita, T. X-ray study on tricalcium aluminate with Fe^{3+} ion substitution, (3) 76*a*.
Yamaguchi, Goro, Shirasuka, K., and Munekata, M. Solid-state spinel formation in the system $MgO{-}Al_2O_3$, (5) 124*a*.
Yamaguchi, Hisao. See Shiraiwa, Toshio.
Yamaguchi, Isao. Method of making a film resistor, P (8) 201*c*.
Yamaguchi, Kenji. Recent progress in the mixing of solids, (6) 141*f*.
Yamaguchi, Masafumi, and Nagai, O. Surface effects of radiation on MOS diodes. (4) 91*g*.
Yamaguchi, Shigeto, and Wada, H. Hydrothermal synthesis of spinel-type Fe_2S_4, (5) 121*c*.
Yamaguchi, T., and Shiraishi, T. Kinetic studies of eutectoid decomposition of $CuFe_2O_4$, (1) 23*g*.
Yamai, Iwao. See Saito, Hajime.
Yamaji, Akihiko. See Waku, Shigeru.
Yamamoto, Hajime. See Kano, Tsuyoshi.
Yamamoto, Hirohiro. See Shimakura, Keiichi.
Yamamoto, Hirohiko, and Shiraishi, M. Self-sealing facedown-bonded semiconductor device, P (8) 203*g*.
Yamamoto, Hirotaka, and Horiuchi, T. Quality control for materials in electronic ceramics industries, (3) 63*e*.
Yamamoto, Ikuo. See Kanazawa, Takafumi.
Yamamoto, Kazuji. See Nonomura, Takuo.
Yamamoto, Keita. See Kira, Kimihiro.
Yamamoto, Masaharu. See Morinaga, Michio
Yamamoto, Masayoshi. See Uchikawa, Hiroshi.
Yamamoto, Masayuki. See Yamada, Eiichi.
Yamamoto, Masayuki, Toki, H., and Shibuya, H. Semiconductive device and method of mfg., P (9) 227*e*.
Yamamoto, Shigehisa. See Iwauchi, Kozo.
Yamamoto, Tokuji, Saeka, S., and Tashiro, M. Formation of defects in glass under electron bombardment, (10) 243*e*.
Yamamoto, Tsutomu. See Somiya, Shigeyuki.
Yamamoto, Yasuhiko, and Shimada, S. Bending and exhausting machine for mfg. circular fluorescent lamps, (11) 267*j*.
Yamamoto, Yoshio. See Yoshimura, Susumu.
Yamamoto, Zensaku, Sato, S., Ono, S., Horiguchi, H., Ariga, S., Takaishi, S., and Sato, H. Enameling grade steel and method of producing, P (2) 31*j*.
Yamamura, Katsumi, and Kasai, M. Method of hardening sintered cemented carbide compositions by boronizing, P (6) 135*i*.
Yamanaka, Shunichi. See Naoe, Masahiko.
Yamane, Mikiya, Saito, A., Matsumoto, K., Kawasumi, K., Murayama, K., and Sugiyama, H. High-pressure metal vapor discharge lamp, P (5) 112*g*.
Yamane, Sho, Furuoto, T., and Hitotsuya, K. Test report on vacuum concrete mixed with shrinkage-reducing material containing gypsum anhydrite, (6) 130*g*.
Yamaoka, Shinobu. Synthesis of $PbZrS_3$ at high pressures, (3) 63*j*.
Yamasaki, Daizo. See Uto, Yashimitsu.
Yamasaki, G. K. See Wooldridge, J. E.
Yamashita, Akio, and Yamada, T. Semiconductor pressure-electric transducer including a semiconductor element having a deep level impurity and a semiconductor pressure transmitting plate, P (9) 227*h*.
Yamashita, Kazuo. Photovoltaic cell and its method of mfg., P (2) 42*a*.
Yamashita, Sadahiko. Memory device utilizing pulse-generating diode, P (10) 251*g*.
Yamashita, Tadaoki. See Nada, Naohiro.
Yamashita, Toshio, Ohtani, T., Yoshida, M., Kitamura, S., and Murakami, H. Sintered semiconductor film and method of mfg., P (4) 90*h*.
Yamashita, Toshio, Yoshida, M., Hasegawa, N., and Kitamura, S. Light sensor matrix device consisting of [CdS] photoconductive elements, P (9) 225*f*.
Yamashita, Tsutomu. See Keskar, K. S.; Tanaka, Eihachiro.
Yamashita, Yohachi. See Ichinose, Noboru.
Yamazaki, Hisashi. Absorption kinetics of N+Ta system, (3) 77*e*.
Yamazaki, Hisashi, Oguri, T., and Kanomata, I. Calorimetric studies on chemisorption of N on Ta, (3) 77*e*.
Yamazaki, Masaki, and Nozaki, H. Transient phenomena caused by temp. change on capacitance of Ti-TiO_2-metal systems, (4) 99*f*.
Yamazaki, Masato. See Kijima, Goro.
Yamazaki, Shumpei. Process for forming a film on the surface of a substrate by a gas phase, P (7) 170*e*. Study of the interface of the Si-SiO_2 system, (4) 99*c*.
Yamazaki, Shumpei, and Kagawa, I. Study of thermally oxidized SiO_2 films by transmission electron micrographs, (3) 75*g*.
Yamazaki, Takeshi. See Takahashi, Makoto.
Yamazaki, Yasuo, Furuta, M., and Kuramoto, Y. Device for optical focusing using a glass fiber plate as a focusing screen, P (8) 192*f*.
Yamazoe, Hiroshi. See Hiratsuka, Toshio.
Yamskov, N. S. See Funke, V. F.
Yamura, Kiyoshi. See Okada, Kiyoshi.
Yanagawa, Takayuki. Integrated circuit lateral transistor, P (8) 200*j*.
Yanagi, Masamitsu. See Saitou, Masashi.
Yanagida, Hiroaki. Electrical conduction in ceramic materials, (3) 62*e*. System Al_2O_3-Al_4C_3, (3) 75*h*. See Kuwabara, Makoto.
Yanagida, Hiroaki, and Shigehara, H. $Al_{1-x}Cr_xOOH$ solid solutions with boehmite structure, (3) 72*c*.
Yandrick, R. M. See Stahr, D. F.
Yang, A. C. See Shepherd, F. D., Jr.
Yang, E. S. Injected carrier lifetime and aging of GaAs injection lasers, (7) 178*h*.
Yang, J. Method of steam curing hydraulic setting calcareous cement and SiO_2 containing compositions, P (4) 79*h*.
Yanina, R. I. See Chemodanov, D. I.
Yano, Norio. See Suzuki, Hideo.
Yano, T., Fukumoto, A., and Watanabe, A. Tellurite glass—a new acousto-optic material, (5) 106*d*.
Yanovskaya, M. S. See Sychev, M. M.
Yario, W. R. Burnable poison for nuclear reactor, P (8) 203*f*.
Yaroshevskii, A. A. Distribution of components after a zone melting test with varying parameters, (5) 120*a*. See Balashov, Yu. A.
Yarwood, J. C., Flemings, M. C., and Elliott, J. F. Inclusion formation in the Fe-O-S system, (6) 148*f*.
Yas, D. S., Lupanov, A. F., Kostin, N. D., and Golovaya, V. D. Use of cermets in the textile industry, (10) 247*a*.
Yasuda, Eiichi, Ootsuka, M., Kimura, S., and Tagai, H. Compression creep of polycrystalline MgO at high temp., (11) 280*g*.
Yasuda, Kazuo, Uchino, K., and Inomata, H. Optical measuring apparatus for sampling material, making a flame test, and comparing the light from an unknown concentration with that from 2 known concentrations, P (2) 45*c*.
Yasuda, Nobuaki. See Murakami, Yoshio.
Yasui, Hideo. See Suzuki, Ichizo.
Yasunaga, Hitoshi. See Okuyama, Naoki.
Yasuoka, Hiroshi, Ngwe, T., Jaccarino, V., and Guggenheim, H. J. ^{55}Mn NMR in MnF_2—the Suhl-Nakamura interaction, (5) 122*c*.
Yasutake, Yoshito. See Hayakawa, Masashi.
Yates, D. See Beach, H. J.
Yates, E. A. C. See Alves, R. V.
Yates, L. Refractories meet heavy demands, (2) 36*e*.
Yates, P. C. Dense submicron grain AlN-SiC bodies, P (6) 127*e*. Fibrous transition metal phosphates, P (9) 232*g*. High-surface-area stabilized SiO_2 sols and process for preparing same, P (7) 175*b*. Method for making metal oxide sols in polar organic solvents, P (10) 257*h*. Organic amine strong base stabilized high surface area SiO_2 sols and method for preparing, P (4) 84*h*. Positively charged fibrous Ce phosphate, P (2) 46*b*. Refractories bonded with aluminides, nickelides, or titanides, P (10) 248*b*. Soluble complex ion metal silicates, P (5) 118*b*. Trivalent metal phosphate-coated colloidal SiO_2 molding powders, P (7) 164*g*.
Yavorskii, I. A., Elchin, V. I., Gnesin, G. G., and Oleinik, G. S. Behavior of nonporous SiC in various gaseous media at high temps., (10) 246*e*.
Yavorsky, P. J., and Cook, L. S. Al polyoxychloride bonded castable refractory, P (4) 84*f*.
Yazaki, Takehito, Kanatani, K., and Sakamoto, S. Longitudinal electrooptic effect in obliquecut SrBa niobate plates, (3) 74*f*.
Ydren, N. E. See Moren, R. E.
Yeaple, F. D. Electric motor-engine hybrids get nod from engineers and ecologists, (2) 36*a*. Intense cooling absorbs heat of new supersemiconductors, (9) 224*g*.
Yearsley, G. A. See Adams, A. L.; King, L. C.
Yeh, Tsu-Hsing. See Duffy, M. C.; Joshi, M. L.
Yeh, W. C. T. See Fishwick, J. H.
Yen, C. F. See Cooper, A. R.
Yen, C. F., and Coble, R. L. Spheroidization of tubular voids in Al_2O_3 crystals at high temps., (11) 282*f*.
Yencha, A. See Storms, E.
Yendrek, M. R. See Ruddle, R. W.
Yeung, K. F. See Hetrick, R. E.
Yin, Lo I., Ghose, S., and Adler, I. Core binding energy difference between bridging and nonbridging O atoms in a silicate chain, (1) 21*d*.
Yocom, W. H. See Melroy, D. O.
Yokomichi, Hideo, Hayashi, M., Maekawa, S., and Ohta, T. Deterioration of reinforced concrete bridge near seaside, (6) 128*i*.
Yokomichi, Hideo, Kakuta, Y., and Ayuta, K. Critical points in deformation of concrete, (6) 128*g*.
Yokomichi, Hideo, Kakuta, Y., and Ono, K. Crack control in reinforced concrete, (6) 128*f*.
Yokomizo, Yuji. See Ichinose, Noboru.
Yokota, Ryosuke. Formation of Ag^0 and Ag^{2+} centers and the tentatively proposed mechanism of colloidal Ag formation in photosensitive glass, (3) 56*c*.
Yokota, Ryosuke, and Muto, Y. Dosimeter using a fluorescent glass element, P (6) 142*e*.
Yokota, Ryosuke, and Nakajima, S. Glass materials for Ag-activated phosphate glass dosimeter, P (1) 4*h*.
Yokoyama, Katsunori. See Ichinose, Noboru.
Yokoyama, Kiyoshi. See Kasai, Yoshio.
Yokoyama, Tohei. See Hosokawa, Masuo.
Yokozawa, Masami. Method of making semiconductor devices, P (2) 41*g*. See Kano, Gota.
Yokozawa, Masami, and Iwasa, H. Semiconductor device and method of mfg., P (4) 90*d*.
Yokozawa, Masami, Iwasa, H., and Teramoto, I. Process for forming a TiO_2 film, P (4) 90*c*.
Yoldas, B. E. [Impregnated] refractory article and method for producing, P (10) 247*i*.
Yoneda, Shun-ichi. See Okada, Kiyoshi.
Yoneda, Yoshitada. Semiconductor device having a body of semiconductor material joined to a support plate by a layer of malleable metal, P (8) 202*h*.
Yonezu, Hiroo, and Kawaji, A. Injection-type semiconductor laser element, P (1) 12*g*.
Yong, R. N. See McKyes, E.
Yoshida, Akihiko. See Minami, Tsutomu.
Yoshida, Akio. See Watanabe, Shigeo.
Yoshida, Akira. See Shirai, Yoshihiro.
Yoshida, Hideo, and Itai, A. Effects achieved through use of unshaped refractories for heating furnace and soaking pit at Mizushima Works and problems involved, (1) 7*h*.
Yoshida, Hideo, Yoshida, M., and Matsuo, A. Studies on thermal fracture of sleeve brick (III) test results obtained on high-Al_2O_3, zircon, chamotte, and high-siliceous sleeve bricks used in steel refining ladle. (1) 8*e*.
Yoshida, Hiroshi, and Suzuki, H. Effect of detonation shock wave on the monoclinic-tetragonal transformation of ZrO_2, (6) 146*h*.
Yoshida, Kenji, and Ichikawa, O. Method of mfg. semiconductor integrated circuits, P (4) 89*g*.
Yoshida, Kozaburo. See Kondo, Renichi.
Yoshida, Manabu. See Yamashita, Toshio.
Yoshida, Masashi. Mineral composition of the Soma Ohori clay in Fukushima prefecture, (5) 117*i*.
Yoshida, Mitsuo. See Yoshida, Hideo.
Yoshida, Tadaaki. See Okuda, Kensuke.
Yoshida, Tetsuro. See Hirashima, Hiroshi.
Yoshida, Toru. See Fujii, Junnosuke.
Yoshida, Yoshio. See Yamada, Shigeki.
Yoshihara, Takao. See Tada, Osamu.
Yoshikawa, Shogo. See Miyauchi, Tsuneshige; Uchida, Teiji.
Yoshikawa, Takayuki, Maki, H., and Kamiya, T. Process for the manufacture of a grinding stone, P (4) 77*i*.
Yoshikiyo, Haruo. Measurements of the focal lengths of long focal length lenses, (11) 268*j*.
Yoshimatsu, Mitsuru. X-ray diffraction apparatus comprising a curved spectroscopic crystal with a rotatable X-ray slit at the focus thereof, P (2) 45*c*.
Yoshimoto, Jiichiro. See Okai, Bin.
Yoshimoto, Jiichiro, Okai, B., and Nomura, S. Effect of pressure on the transition of $Pb(Zn_{1/3}Nb_{2/3})O_3$, (3) 79*i*.
Yoshimura, Masahiro, and Sata, T. Phase studies on the system ZrO_2-Ce_2O_3 from 1350°–1900°C, (11) 282*c*.
Yoshimura, Susumu, Hasegawa, K., Yamamoto, Y., and Tajima, I. Solid electrolytic capacitor with γ-MnO_2 electrolyte, P (3) 67*h*.
Yoshimura, Takuji, Fukunaga, J., and Ihara, M. Metastable immiscibility region in the system Li_2O-B_2O_3-GeO_2, (6) 150*g*. Properties and structure of glasses in the system Li_2O-B_2O_3-GeO_2, (6) 132*e*.
Yoshio, Tetsuo. See Takahashi, Katsuaki.
Yoshioka, Satoshi, and Takayanagi, S. Method for deposition of SiO_2 films, P (3) 65*e*.
Yoshioka, T. See Sovers, O. J.
Yoshioka, Tsunehiko, Sato, H., and Suda, N. Ceramic dielectric compositions, P (3) 64*a*. Ceramic dielectric compositions comprising Ca, La, and Pb titanates. P (8) 200*f*.
Yoshioka, Yasuhiko, Hiraï, M., and Nieda, T. Nominal shear strength of lightweight concrete, (6) 129*f*.
Yotsuyanagi, Keiichi. See Takamizawa, Hideo.
Youdelis, W. V. See Nemeth, J.
Youmans, A. P. See Mitarai, Hajime; Nelson, C. E.
Young, A. R., II. Mixed valency transition metal perovskites as cathodic reduction catalysts, P (6) 144*f*.
Young, C. G. Clad glass laser rod, P (6) 132*e*. Compensator for a radial refractive-index gradient in a disk laser, P (10) 244*a*. Composite glass laser rod, P (4) 81*a*. Laser with a segmented laser rod, P (1) 12*h*. Laser structures, P (3) 65*i*. Tandem oscillator disk amplifier with trivalent Nd input disk and trivalent Nd plus Yb output disks, P (3) 67*i*. Unitary laser system with oval-shaped rod of laser glass, P (2) 35*c*. See Cooper, A. R.
Young, D. A. Ammoniated zeolite catalysts, P (6) 143*i*.
Young, E. E. See Darr, D. E.

Young, E. H., Jr. See Montgomery, R. M.
Young, J. E. See Blachere, J. R.
Young, J. F. Effect of organic compounds on the interconversions of Ca aluminate hydrates. Hydration of monocalcium aluminate, (4) 78*f*. Review of the mechanisms of set-retardation in portland cement pastes containing organic admixtures, (10) 242*d*.
Young, J. W., and Smit, J. Moessbauer effect in Li-Zn ferrites, (4) 86*d*.
Young, O. W. J. See Arber, S. G.
Young, P. A. Reflectivity of vitreous As_2S_3, (8) 191*f*.
Young, R. G., Larson, D. A., and Marks, L. M., Jr. Method of operating a high-pressure gaseous discharge lamp with improved efficiency, P (3) 59*f*.
Young, W. P. See Spengler, A. F., Jr.
Young, W. S., and Wilcox, D. L. Dynamic camber measurements of glazed ceramic substrates, (10) 240*b*.
Youngblood, D. J. See O'Keefe, W. H.
Youngman, C. A., and Roe, G. D. Automatic sample changer for X-ray fluorescence spectrometer, P (3) 70*g*.
Youssef, S. I. See Murthy, N. S. S.
Youtsey, K. J., Holt, W. C., Jr., Carnahan, R. D., and Spielberg, D. H. Pyropolymeric semiconducting organic-refractory oxide material, P (7) 170*h*.
Yperman, J. M. B. G., and Belhomme, C. Electric ceramic [$BaTiO_3$] resistors having positive temp. coeffs. and method of mfg. same, P (10) 250*i*.
Yu, K. K. See Lin, H. C.
Yudenfreund, M. See Odier, I.
Yudenfreund, M., Odler, I., and Brunauer, S. Hardened portland cement pastes of low porosity (I) materials and experimental methods, (8) 186*d*.
Yudenfreund, M., Skalny, J., Mikhail, R. S., and Brunauer, S. Hardened portland cement pastes of low porosity (II) exploratory studies. Dimensional changes, (8) 186*d*.
Yudin, D. M. See Galimov, D. G.
Yudin, N. M. See Olesov, N. A.
Yudovich, B. E. See Potryasov, V. N.
Yugai, A. F. See Sychev, M. M.
Yuge, Yoji. See Sugano, Keiichi.
Yukami, Noboru, Otani, H., and Kurokawa, H. Stress-sensitive semiconductor element having an n^+pp^+ or p^+nn^+ junction, P (9) 228*c*.
Yumoto, Tetsuo, and Kataoka, K. Experimental studies on flexural strength of artificial lightweight aggregate concrete, (6) 128*i*.
Yunker, R. W. Cooler for vertical glass sheet drawing machine, P (4) 81*c*.
Yust, C. S., and McHargue, C. J. Deformation of hyperstoichiometric UO_2 single crystals, (1) 15*d*.
Yut, R. F. See Ghosh-Tagore, R. N.

Zaborenko, K. B., and Balek, V. Dehydration of $CaSO_4 \cdot 2H_2O$ and $CuSO_4 \cdot 5H_2O$ by the emanation method and by gaseous surface-labeling, (1) 21*f*.
Zaborovskii, V. I., Ivanov, O. A., and Savenkov, A. N. Installation for casting a microwire in glass insulation, P (1) 4*i*.
Zacmanidis, P. J. See DeLosh, R. G.
Zacpal, Z., and Filous, J. Development of the shaft-type countercurrent heat exchanger system Prerov machinery, (8) 186*g*.
Zacpal, Z., and Nemecek, P. Arrangement for preheating of pulverulent material, particularly of raw cement powder, P (3) 54*d*.
Zadde, V. V. See Lidorenko, N. S.
Zadumin, V. I., and Borisov, A. F. Crystallization in glasses in the system Na_2O-GeO_2, (9) 216*d*.
Zagar, L. Electrical conductivity of glasses according to Myller's dissociation theory, (8) 190*e*.
Zagar, L., and Lueneberg, H. Investigations of glassy systems with SrO as a main constituent, (8) 190*i*.
Zagieboylo, W. See Davies, J. M.
Zagorin, H. See De Forest, W. S.
Zahn, D. See Clerc, D.
Zahs, G. See Ruettiger, K.
Zaichenko, G. E. State and development of the raw materials base of the refractories industry, (8) 196*a*.
Zaionts, L. A. See Rogozhin, Yu. V.
Zaionts, R. M. See Ul'yanova, G. G.
Zaitsev, B. E., Zakharikova, E. I., Ivanov-Emin, B. N., and Cherenkova, G. I. Infrared absorption spectra of the binary molybdates and lanthanides of alkali metals and ammonium, (1) 22*g*.
Zaitsev, Yu. V. Deformation and failure of hardened cement paste and concrete subjected to short-term load, (4) 78*i*. Deformation and failure of hardened cement paste and concrete under sustained load, (5) 102*j*. Experimental investigation to determine the behavior of hardened cement paste and plaster under high load, (5) 103*d*.
Zaitseva, A. K. See Lidorenko, N. S.
Zajic, J. E. Water Pollution—Disposal and Reuse (Vols. 1 and 2), B (2) 52*j*.
Zakharchenya, B. P. See Zhilich, A. G.
Zakharikova, E. I. See Zaitsev, B. E.
Zakharov, L. A. Anorthosites—new raw materials for making white cement, (8) 185*g*.
Zakharov, R. G. See Shchepetkin, A. A.
Zakhvalinskii, M. N., and Belykh, P. D. Ternary systems formed by alkali metal carbonates, (5) 124*j*.
Zalm, P. See Witteman, W. J.
Zalyaliev, M. A. See Akhunov, A. M.
Zamantakis, M. S. Vocational ceramic training in Japan, (2) 30*g*.
Zaminer, C. Imaging of ceramics in the range room temp. to 2000°C in the photoemission electron microscope, (8) 205*b*.
Zamorani, E. See Savi, C.
Zamyatin, S. R., Mamykin, P. S., and Knyazeva, T. P. Thermal transformations during reaction of H_3PO_4 with chamotte, (8) 196*e*.
Zankar, A. Nomogram for collection efficiency calculation in electrical dust precipitators, (9) 229*j*.
Zapletal, V. See Kolomaznik, K.
Zapolsky, A. K., Sazhin, V. S., Fedoritenko, I. I., and Kostenko, A. S. DTA of basic Al sulfates, (10) 258*g*.
Zapp, F. Thermal expansion of porcelain bodies as a function of the firing temp., (5) 111*f*.
Zaremba, S. See Kedzior, A.
Zarzycki, J. X-ray diffraction study of alkali titanate glasses, (2) 33*h*. X-ray diffraction study of vitreous BeF_2 and alkali fluorberyllate glasses, (2) 33*j*.
Zarzycki, J., and Naudin, F. Spinodal decomposition in the B_2O_3-PbO-Al_2O_3 system, (3) 75*a*.
Zatko, S. See Mihalik, V.
Zaveta, K. See Sestak, J.
Zavol'skii, V. A. See Krivonosov, L. B.
Zbikowski, T. See Buck, R. H., Jr.
Zbojniewicz, W. P. See Mayer, R. P.
Zdansky, K. Dynamic Jahn-Teller effect of MgO:Cu^{2+} at 4.2°K, (5) 120*b*.
Zdorov, A. I. See Kryzhanovskaya, I. A.
Zecchin, L. Miotti family of Murano, glass manufacturers at the sign of "Al Gesu," (11) 266*c*.
Zednicek, W. See Papst, K.
Zeedijk, H. See Brouwer, H. J.
Zeigarnik, V. A., Peletskii, V. E., and Gnesin, G. G. Thermal conductivity of self-bonded SiC, (10) 261*c*.
Zeigler, R. O. See Schirm, H. T.
Zeldes, H. See Abraham, M. M.
Zelenz, M. L. Method for fabricating multilayer electrical components, P (9) 226*g*. See Buzard, J. B.
Zeleyi, I. T. See Mikol'skii, Yu. N.
Zemon, S. Acoustic buildup in photoconducting CdS subjected to high rf electric fields, (5) 118*d*.
Zemskov, A. L. See Nekrasov, N. N.
Zemskov, G. V. See Shestakov, A. I.
Zenbutu, Sakae, Nakata, R., Sumita, M., and Higuchi, E. EPR study of characteristics of Fe^{3+} ions with cubic symmetry in CaF_2 crystals, (4) 96*c*.
Zenko, M. A. Your acid inhibitor—key to greater pickling profits, (1) 3*a*.
Zephoris, M. Relaxation of stresses by passing ultrasonic waves through glass samples, (11) 269*i*.
Zeppieri, D. J., and Barbuto, A. Solid electrolyte capacitor, P (2) 42*g*.
Zerbes, G. Study of Zn-Mg-Perminvar ferrites, (2) 39*e*.
Zerlaut, G. A. See Gates, D. W.
Zezin, M. A. See Gutop, V. G.
Zhabotinskii, V. A. See Pavlushkin, N. M.
Zhdanovich, G. M. Pressure and density distribution in the single- and double-ended pressing of axially symmetric compacts, (10) 247*c*.
Zhelobaeva, N. P. See Arav, R. I.
Zhigarnovskii, B. M., and Ippolitov, E. G. Condensed-state phase diagram of the system CaF_2-BaF_2, (8) 208*f*.
Zhilich, A. G., Halpern, J., and Zakharchenya, B. P. Magnetoabsorption oscillations and Zeeman effect of excitons for forbidden interband transitions in Cu_2O crystals, (6) 150*d*.
Zhukov, E. G. See Grinberg, Ya. Kh.
Zhuraviev, A. K. See Pavlushkin, N. M.
Zhuraviev, E. F. See Ostrikova, N. V.
Zhuraviev, G. I. See Avgustinik, A. I.
Zhuravleva, Z. K. See Voronchikhina, T. P.
Ziebell, R. J. See Loughridge, F. A.
Ziechmann, W., and Rochus, W. Analytical characterization of sand deposits with special reference to the humic materials, (1) 17*d*.
Ziegenhain, W. C. See Hritz, G. G.
Zielonka, J. M. See Wang, Rong.
Ziemelis, O. J. See Fisher, M. B.
Zievers, J. F. Filtration apparatus, P (6) 141*f*.
Zifferer, L. R. Method of making a composite sand mold including recycling the sand, P (11) 272*g*.
Zijlstra, A. L., and Burggraaf, A. J. Fracture phenomena and strength properties of chemically and physically strengthened glass (I) general survey of strength and fracture behavior of strengthened glass; (II) strength and fracture behavior of chemically strengthened glass in connection with the stress profile, (3) 56*d*.
Zikovsky, L., Vagnard, G., and Daniel, J. S. Kinetics of recrystallization and grain growth in Cu_2O, (4) 97*j*.
Zil'berberg, V. G. See Karpinos, D. M.
Zimmer, W. F., Jr., and Chew, H. L. Abrasive foam laminate, P (7) 155*e*.
Zimmerman, D. D. New Au-Sn alloy composition for hermetic package sealing and attachment of hybrid parts, (11) 273*j*.
Zimmerman, D. W. Thermoluminescent dating using fine grains from pottery, (5) 102*c*.
Zimmerman, D. W., and Huxtable, J. Thermoluminescent dating of upper Paleolithic fired clay from Dolni Vestonice, (5) 102*c*.
Zimmerman, G. O. See Abeshouse, D. J.
Zimmerman, Michael, and Zimmerman, Michi. Kimpei Nakamura, (4) 77*j*.
Zimmerman, Michi. See Zimmerman, Michael.
Zimmermann, H. Modern body preparation plant in the ceramic industry—automatic batching, (5) 110*h*.
Zine, A. R., Jr. Pipe coupling, P (4) 82*g*.
Zink, J. S. See Reed, R. D.
Zink, J. S., Goodnight, H., and Reed, R. D. Noiseless radiant wall burner, P (11) 279*b*.
Zink, J. S., and Reed, R. D. Burner assembly producing radiant heat, P (5) 117*b*.
Zinovik, M. A. See Shchepetkin, A. A.
Zirngibl, H., Jaschiski, K., Brandle, K., Beumer, P., and Weidmann, W. Process and apparatus for recovering metal oxides [TiO_2] from hot gases, P (11) 279*i*.
Zirngibl, H., Winter, G., and Mansmann, M. Process for the production of fibrous refractory oxides of polyvalent elements, P (11) 272*e*.
Zirngiebl, E. See Minz, F. R.
Ziver, G. M. See Domicone, J. J.
Zivi, S. M. Safety apparatus for nuclear reactors, P (4) 92*a*.
Zizelmann, W. Optoelectronic semiconductor device, P (5) 113*f*.
Zlomanov, V. P. See Vanyarkho, V. G.
Zmija, J. Study of the diffusion of chalcogen impurities in semiconductive II-VI compounds, (4) 98*j*.
Zoellner, D. See Reichelt, B.
Zografou, C. See Bleckmann, H.
Zolotarev, P. P. Fluctuations of porosity in monodispersed granulated mixture, (3) 73*j*.
Zook, M. A., Jr. See Louderback, A. W.
Zorina, M. L., and Vakhrameev, V. I. Infrared absorption spectra of Na-Sn-SiO_2 glasses, (9) 217*b*.
Zoshchuk, N. I. Slag portland cement as binder for refractory concretes, (8) 187*f*.
Zounova, F. See Sestak, J.
Zoz, E. I. See Gavrish, A. M.
Zschauer, K. H., and Winstel, G. Carrier for semiconductor components, P (2) 39*e*.
Zubarev, Yu. V., Kostikov, V. I., Mirin, B. S., Nagibin, Yu. A., and Nishcheta, V. V. Some properties of molten Al_2O_3, (8) 210*h*.
Zuber, T. W., Jr. See Pitetti, R. C.
Zubler, E. G. Gettering processes for electric lamps and similar devices, P (10) 244*h*.
Zucchinelli, M. See della Porta, P.
Zudkevitz, A. See Ben-Dor, L.
Zuegel, M. See Gregor, L. V.
Zuidema, G. See Caveney, R. J.
Zwack, R. R. See Christenson, R. M.; Le Bras, L. R.
Zwanzig, R. See Lauritzen, J. I., Jr.
Zysk, E. D., and Osovitz, E. E. Pt-Rh vs Pt thermocouple having base metal compensating leads, P (10) 253*a*.

SUBJECT INDEX TO CERAMIC ABSTRACTS FOR 1972

The number in parentheses refers to the issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the issue number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates position on the page. For more complete indexing of papers published in the *Journal of The American Ceramic Society* and the *American Ceramic Society Bulletin*, see indexes to the *Journal* and the *Bulletin*.

Ablation, coating, elastomeric composition, P (3) 61*c*.
Abrading apparatus. See *Grinding apparatus.*
Abrasion, of $CaSiO_3$, reduction, P (8) 207*g*.
dependence, of friction of ferrites, (3) 62*c*.
effect on $BaTiO_3$, (8) 211*a*.
mechanical, resistance of enamel, (11) 267*e*.
resistance, of concrete, vacuum, (6) 130*a*.
resistance of lightweight concrete, (6) 127*i*.
of Ti and Ti alloys, P (3) 53*g*.
Abrasives. See also *Carbides; Diamonds; Grinding apparatus; Polishing apparatus; Silicon, carbide.*
B (6) 153*c*.
adjustable lap, P (8) 185*e*.
aluminous, brown, (3) 53*e*.
article, coated, P (2) 29*f*.
articles, ceramic-bonded, P (9) 213*f*.
belt, P (8) 185*f*.
coated, (11) 265*d*.
coated overlap joint, P (5) 101*e*.
endless, P (6) 127*f*.
joint, coated, P (9) 213*f*.
brush, P (2) 29*j*.
brushing elements, P (9) 213*e*.
circuit trimming with, (3) 62*e*.
coated, adhesive for, (3) 53*e*.
cloth, friction reduction on, P (5) 101*f*.
products, oversized, P (10) 241*f*.
compositions, P (7) 155*f*.
cones, coated, P (9) 213*g*.
cutting element, P (4) 77*h*.
cutting wheels, bossed, P (4) 77*f*.
diamond bit, P (5) 101*f*.
diamond grinding, (1) 1*f*.
engineering terminology, (9) 213*e*.
and expanders, cushion between, P (6) 128*h*.
finishing, P (1) 1*g*.
metal, media in, (3) 53*h*.
tool, composite, P (3) 53*f*.
foam laminate, P (7) 155*e*.
GeO_2, P (4) 77*h*.
grains, bond with binder in grinding tools, (11) 265*e*.
coated, (3) 53*g*.
cubical sintered aluminous, P (5) 101*f*.
jet machining tools, nozzles, (5) 101*e*.
machining, of glass and ceramics, (3) 53*i*.
pack with anchor assembly, P (10) 241*e*.
plumber's tool, P (5) 101*g*.
standardized identification, (2) 29*g*.
testing single diamond particles, (4) 77*e*.
tool, cutting, P (5) 101*f*.
diamond or BN, P (9) 213*f*.
rotary, P (7) 155*g*.
thermosetting resinous, P (8) 185*f*.
treating apparatus, P (4) 77*i*.
tumbling media, Al_2O_3, P (11) 265*f*.
treating with high dynamic pressure, P (9) 213*e*.
wheels. See *Grinding apparatus.*
Zr oxide and Al_2O_3, P (1) 1*g*.
Absorption, atomic, B_2O_3 determination in glasses by, (10) 243*b*.
in glass analysis, (8) 204*j*.
use in chemical element analysis, P (11) 278*g*.
bands, uv, of Bi^{3+} and Eu^{3+} in oxides, (8) 211*e*.
centers, effect on dispersion of glasses, (9) 216*e*.
coeff., of optical materials, (8) 191*d*.
dielectric, in impure NaCl, (9) 236*i*.
edge, optical, in SnO_2, (3) 75*h*.
edges, higher, in SiC, (6) 148*c*.
fluid, of molds, measuring rate, P (9) 232*j*.
gas, effect on CoO properties, (6) 151*g*.
GR1 line, in diamond, (4) 98*a*.
ir, of antiferroelectric transitions in $NH_4H_2PO_4$ and $NH_4H_2AsO_4$, (5) 118*i*.
of MgO powders, (6) 146*j*.
optical, in CdF_2:Y crystals, (5) 121*c*.
of proton dynamics in ferroelectrics, (5) 122*j*.
kinetics of N+Ta system, (3) 72*c*.
lattice in $SrTiO_3$, (6) 149*b*.
magneto-, oscillations in Cu_2O crystals, (6) 150*d*.
microwave sound, in TiO_2, (6) 150*h*.
optical, in chalcogenide glasses, (3) 56*e*.
of MgF_2, (6) 150*d*.
in SiC, *n*-type cubic, (6) 150*e*.
Absorption *(continued)*
of vanadate glasses, (5) 106*f*.
of $Y_3Al_5O_{12}$, (5) 122*i*.
passive and dynamic, in glass, (1) 3*g*.
red shift, in olivine and spinel, (10) 258*j*.
spectra. See *Spectra.*
uv, of Pb in silicate glass, (1) 3*g*.
H_2O, of aggregate, tests, (6) 130*h*.
H_2O, test methods, (1) 18*c*.
Acenaphthylene, pyrolysis to soft C, (1) 24*g*.
Acetate, penta-, NMR studies, (3) 55*b*.
Acids. See also specific types.
aminobutyric, gelling vermiculite in, (9) 235*f*.
base properties, effect in V systems, (3) 72*f*.
carboxylic, use of catalysts in, P (11) 280*b*.
dry, treatment, of Al_2O_3-SiO_2 clay, P (3) 71*i*.
fluoboric, from fluorspar, and purification, (7) 175*e*.
fluosilicic, for purifying gypsum, P (5) 104*i*.
fluosilicic, from waste gases, P (5) 117*h*.
inhibitor, in pickling, (1) 3*a*.
leaching characteristics of glasses, (11) 267*h*.
picric, -methanol method, dissolution of glass phase in cement by, (4) 78*b*.
reactivity with clay minerals, (5) 123*j*.
resistance of enamels, testing, (6) 130*i*.
resistant tile, asbestos waste for, (8) 198*a*.
salicylic-C_3A reaction, (5) 103*c*.
selenious, neutron diffraction study, (3) 74*b*.
solubility, of SiC, (10) 246*f*.
telluric, crystal structure, (5) 119*d*.
triglycine sulfate, ir radiation in, (5) 123*a*.
H_2O-soluble, in electrodeposition bath, P (8) 192*f*.
Acoustics. See also *Insulation, acoustical; Sound.*
acoustoelectric effect in CdS, (5) 122*j*.
acousto-optic devices using $PbMoO_4$, P (3) 64*a*; (4) 98*f*.
and acousto-optical properties of TeO_2, (11) 273*d*.
buildup in CdS, (5) 118*d*.
emission, in crystalline solids, (7) 180*f*.
loss and velocity, of SiO_2, (5) 125*c*.
surface-wave beam diffraction on substrates, (7) 166*c*.
surface waves, on $LiNbO_3$, (4) 97*i*.
Acrylate, poly-, adsorption on clays, (1) 9*h*.
Actinide, oxide and carbide spherical particles, P (9) 229*a*.
oxide structures, (9) 234*f*.
Activation, analyses and tracer techniques, (4) 92*j*.
Additives, amine, for portland cement, P (3) 54*d*.
autodoping epitaxial deposits, preventing, P (8) 201*d*.
autodoping, minimizing in deposition, P (9) 226*f*.
C-forming, in casting molds, P (9) 222*h*.
cement, P (8) 188*d*.
expansive, P (9) 215*h*.
phosphorites as, (8) 188*a*.
coloration of KCl, (9) 238*e*.
coloration of SrO, (5) 118*e*.
colored, in decorative cements, (8) 186*c*.
for concrete and mortar, P (8) 188*c*.
dependence of hole lifetime in GaAs, (6) 146*f*.
doping, profile, for GaP diode, P (9) 225*d*.
semiconductor layer, P (3) 65*b*.
semiconductor materials, P (2) 41*a*.
special agents, use, (9) 224*d*.
effect, on Ca_2SiO_4 and Ca_3SiO_5 autoclaving, (7) 156*i*.
on cement paste, (4) 78*d*.
on hydration of C_3A, C_3S and with or without gypsum, (5) 103*g*.
on kaolin briquet strength, (8) 195*c*.
on morphology of $Ca(OH)_2$, (5) 103*a*.
on portland cement, (10) 241*h*.
on sintering CaF_2, (1) 21*h*; (7) 177*e*.
on stress buildup in glass, (3) 55*e*.
plasticizer, to photoresist for pinhole reduction, P (2) 42*a*.
plasticizing, for mortars and concretes, P (11) 267*b*.
polyvinyl acetate, effect on mortar, (9) 214*c*.
semiconductor compositions, P (8) 202*i*.
semiconductor, SiO_2-based, P (8) 202*a*.
Adherence. See *Enamels.*
Adhesion, strength, of tile-mortar-concrete, (5) 110*g*.
of tiles, problems, (5) 110*d*.
Adhesives, and cements in ceramic technology, (2) 43*g*.
for coated abrasive, (3) 53*e*.
Sr pyrophosphate, in screens, P (4) 91*a*.
Adsorbates, phase transitions, (2) 48*g*.
Adsorption, NH_3 on MgO, ir study, (11) 281*c*.
NH_3, on rutile surfaces, (1) 22*h*.
dye, on ceramic raw materials, (1) 19*h*.
effect on grinding cement, (7) 156*j*.
of fluoride on ThO_2, (9) 233*d*.
gas, isotherms, for textural parameters, (7) 173*b*.
onto glassy pyrogenic SiO_2 surfaces, (9) 216*g*.
hysteresis, on disordered kaolinite, (2) 46*j*.
Fe^{3+}, on SiO_2 gel, Al_2O_3, and natrolite, (4) 97*g*.
measurements on $CdIn_2S_4$, (9) 236*f*.
O on MgO during γ irradiation, (1) 21*j*.
of polyanions by clays, (1) 9*h*.
with silanized aluminosilicate, P (8) 207*g*.
vapor mixtures, on adsorbents, (3) 69*j*.
H_2O, by clays, (2) 47*a*.
and N, on cement pastes, (10) 242*c*.
on SiO_2, (7) 176*c*.
vapor on E-glass, (9) 216*b*.
vapors on mordenite, (3) 73*j*.
Aeration, de-, and compression of powders, P (4) 92*h*.
system, P (3) 60*c*.
Aerogels. See *Colloids.*
Aerosols. See *Colloids.*
Afterglow. See *Luminescence.*
Agate, impurities and micropores, (5) 117*h*.
study: II, X-ray line broadening in, (3) 75*f*.
Agglomerates, Al_2O_3, of high mechanical strength, P (4) 94*f*.
zeolite, P (4) 95*b*.
Agglomeration, of dispersed systems, measuring, (1) 17*g*.
of glass-batch raw materials, (10) 243*h*.
of kaolin suspensions, (2) 46*a*; (6) 146*a*.
of mica, P (2) 46*i*.
Aggregates, artificial, effect on concrete strength, (10) 241*h*.
binderless molecular sieve, P (7) 175*g*.
bloating, effect of firing atm, (2) 31*d*.
bond with mortar, effect on concrete strength, (10) 241*h*.
classification, problems, (6) 129*j*.
custom, for refractories, (11) 271*g*.
high purity, polymer-bonded, (4) 83*j*.
to improve concrete, P (7) 157*b*.
lightweight, bloating clays for, (5) 108*c*.
in brick, (9) 220*d*.
from fly ash, (9) 220*c*.
sintering, P (11) 277*g*.
sp. gr. and H_2O absorption, (6) 130*h*.
micro-, interaction with clinker minerals, (8) 187*c*.
minerals, standards, (4) 78*g*.
powder, strength, (10) 248*h*.
sintered, P (9) 221*d*.
sintered, for road surface, P (1) 6*d*.
sintering materials for, P (7) 163*d*.
Aggregation, in montmorillonites, (2) 37*i*.
Aging, aluminomagnesia spinel ceramics, (8) 194*g*.
dielectrics, Ti-containing, (8) 199*e*.
in ferroelectric ceramics, (2) 38*j*.
of GaAs injection lasers, (7) 178*h*.
optical, of LiF crystal ceramics, (8) 191*i*.
Air, heating or cooling apparatus, P (8) 206*f*.
increased, effect on separation, (4) 78*j*.
Aircraft ceramics. See *Cermets; Spacecraft.*
Alamine, *a*-, adsorbed on montmorillonites, (11) 281*b*.
Albite, -microcline, solvus determination, (1) 22*e*.
Alcohol, -homoionic montmorillonite interactions, (9) 237*i*.
separation from Al alkoxides, P (6) 144*e*.
voids in C fibers from, P (6) 135*c*.
Alite, in cement, (4) 79*i*.
formation, (7) 177*f*.
hydration in clay-cement mixtures, (10) 241*j*.
pastes, low-porosity, properties, (5) 104*g*.
phase in portland cement clinker, (9) 218*i*.
and solid solution, hydration, (4) 78*h*.
Alkaline, salts, of elements, solid-state synthesis, (6) 150*a*.
ultrabasic dikes, liquid immiscibility in, (8) 209*b*.
vapors, corrosion of basic bricks, (3) 60*h*.

Alkaline earths, See also specific types.
aluminates, and hydrates, (2) 47*b*.
fluoride crystals, dielectric relaxation, (5) 119*j*.
fluoride single crystals, P (6) 139*e*.
fluorides, dielectric constants, (4) 97*a*.
metals, carbonates, reaction with B_2O_3, (2) 48*i*.
chlorides, calcining, P (4) 79*f*.
hexaborides, electrical properties, (10) 259*b*.
hexaborides, electrophysical properties, (10) 259*c*.
oxides, source composition, P (4) 95*b*.
solution in molten halides, (11) 281*c*.
sulfates, P (9) 225*c*.
oxyanions, fluorescence properties, (2) 47*i*.
systems. See *Systems*.

Alkalis. See also specific types.
alkalic rock-carbonatite complexes, in NaAlSiO$_2$-CaCO$_3$-H$_2$O, (1) 22*h*.
alkalimetric determination of F in fluoride compounds, (10) 255*a*.
in CdS, properties, (5) 122*h*.
carbonate, effect on 3CaO·SiO$_2$ hydration, (9) 214*d*.
in cement production, reduction, P (3) 54*d*.
effect on alite and belite formation, (7) 177*f*.
effect on dust adherence in kiln, (9) 214*c*.
fluorides, thermodynamic functions, (6) 152*d*.
halides. See *Halides, alkali*.
metals, carbonates, reaction with B_2O_3, (2) 48*i*.
chlorides, reactions with TeCl$_4$, (8) 210*a*.
chlorides, ReCl$_3$ disproportionation in presence of, (8) 203*c*.
hydrosulfates, reactions with TiO_2, (2) 48*j*.
molybdates and lanthanides, ir adsorption spectra, (1) 22*g*.
orthophosphates, P (2) 46*d*.
oxides, source composition, P (4) 95*b*.
perborates, P (7) 175*i*.
reduction in aluminosilicates, P (4) 95*b*.
silicates solutions, stabilized, P (3) 71*h*.
solubility of Fe oxide in, (1) 25*c*.
tetratitanate, P (6) 144*g*.
mixed, effect in glass, (3) 56*f*; (11) 269*e*.
mobility, and relaxation in silicate glasses, (5) 106*g*.
NdTiO$_3$ perovskites, magnetic susceptibility, (9) 237*g*.
nitrate, reaction between perchlorate and iodide ions in, (8) 211*d*.
reactivity with clay minerals, (5) 123*j*.
resistant tile asbestos waste for, (8) 198*a*.
sulfate, mixtures, enthalpies of mixing, (3) 73*c*.
systems. See *Systems*.

Alkyl, alkenyl, and aryl metal compounds, P (7) 175*h*.
aromatics, transfer with metals on B_2O_3-Al_2O_3, P (1) 20*j*.

Alloys, alloying metals, P (9) 226*c*.
Al, lands, reliability, P (3) 67*f*.
Bi-Ni, graphite impregnated with, P (9) 228*h*.
brazing, for bonding cathode to support, P (9) 218*e*.
C-SiC, codeposited pyrolytic, (1) 25*a*.
C-TiC, properties and microstructure, (10) 260*c*.
cermet, of Re and Y hexaboride, (10) 246*f*.
cermet-type, P (9) 222*c*.
Cr-U, viscosity, (4) 91*j*.
EEM study, (11) 255*d*.
eutectic, coupled growth, (8) 199*b*.
Au-Ge, Ge determination, (11) 277*i*.
Au-ThO$_2$, Au-Al$_2$O$_3$, Cu-ThO$_2$, Pt-ThO$_2$, and Pt-Al$_2$O$_3$, electric and tensile properties, (2) 38*e*.
Au-Sn, for package sealing, (11) 273*j*.
hard, for glass molds and cores, (5) 106*g*.
mixtures, oxidation, (10) 260*a*.
rheological properties, (10) 247*h*.
In$_{1-x}$Ga$_x$As, properties, (9) 237*g*.
Fe-Cr cermet, brightness coeff., (10) 246*j*.
Fe-Cr-S, activity coeff. of S in, (6) 146*h*.
Fe-Mn, sulfides and oxides in, (6) 152*e*.
Fe-Ni-Co, glass seals to, (1) 3*d*.
light, flux for welding, P (4) 80*c*.
Mo-Cr-B, phase composition, (10) 260*f*.
Ni, carbidic phases in, (10) 260*i*.
Ni-base, casting, P (6) 135*b*.
Ni-Cr, strengthening, (10) 247*j*.
Ni-Ti, reaction with UO$_2$, (7) 171*j*.
photoconductive, of Cd, Se, and Hg, P (9) 227*e*.
Pt-Rh-Au, P (10) 245*j*.
porcelain bonding dental Au, P (10) 248*h*.
semiconducting, structure and transport in, (6) 147*d*.
superconductive, P (10) 253*e*.
III-V, for ir detectors, P (4) 90*b*.
Ti, abrading, P (3) 53*g*.
of WB-LaB$_6$ system, (10) 259*e*.
WC-Co hard, deformation, (6) 134*h*.
WC-Co, structure, (3) 60*h*.
U and Pu, crucible coating for preparing, P (8) 203*f*.
use in low temp. thermocouples, (10) 255*f*.
V and Fe or Ni, composite material, P (10) 253*j*.
VC-TiC, slip systems in, (2) 49*b*.
vapor deposition, P (7) 170*h*.
wetting of diamond and graphite by, (10) 259*f*.
Zr, elements, brazing, P (11) 275*b*.

Alum, mud suspensions, settling in H$_2$O, (5) 111*b*.

Alumina. See *Aluminum Oxide*.

Aluminates. See also *Alkaline earths*.
solution, extracting Ga from, P (10) 257*h*.

Aluminocalcium, sinters, physicochemical properties, (7) 156*c*.

Aluminosalicylate, complex, ir spectral identification, (9) 214*e*.

Aluminosilicates, alkali metal content reduced, P (4) 95*b*.
Al$_2$O$_3$ recovery from, P (9) 233*b*.
ceramic, thermal-stress fracture, (5) 125*c*.
containing sodalite and/or salts, P (10) 257*b*.
films, deposition and physical properties, (2) 38*d*.
high-temp. reactions, (9) 236*f*.
melts, solubility of N in, (6) 147*j*.
minerals, thermal transformations, (2) 47*c*.
ores, Al$_2$O$_3$ extraction from, P (7) 175*j*.
recovering Al$_2$O$_3$ from, P (6) 144*d*.
silanized crystalline, adsorption with, P (8) 207*g*.

Aluminum, aluminizing cathode-ray tube screen, P (8) 202*d*.
aluminous ores, acid treatment, P (3) 71*f*.
Al^{3+} in MgO·nAl$_2$O$_3$ spinel, (5) 121*g*.
$Al_2Cl_7^-$, coordinate analysis, (6) 151*i*.
AlKα emission wavelengths, (4) 96*a*.
AlKα peak, shift in Ca aluminates, (6) 151*d*.
and Al alloy lands, reliability, P (3) 67*f*.
in cement, determination, (4) 78*g*.
compounds, extraction from dawsonite, P (5) 117*i*.
damping, (5) 116*f*.
diffusions, P (10) 249*e*.
effect on thermal stability of SiC, (3) 72*g*.
electron microprobe analysis, (4) 93*e*.
enamels for, (2) 31*h*.
fluoride, P (8) 207*d*.
anhydrous, P (6) 144*b*.
Gibbs free energy of formation, (11) 281*a*.
pure, P (8) 207*d*.
-rich NaF-AlF$_3$ mixtures, (11) 283*a*.
hydroxide, dehydration, P (11) 279*i*.
hydroxy-, adsorption by phyllosilicates, (5) 118*f*.
ion, role in structure of glasses, (6) 132*g*.
metallic, in recycled glass, (7) 158*e*.
nitrate solution, converting to α-Al$_2$O$_3$, (6) 144*o*.
nitride, P (1) 9*e*.
from AlCl$_3$·NH$_3$, properties, (9) 238*c*.
crystals, for semiconductors, P (4) 89*d*.
fibers, P (7) 164*g*.
reactions with W and Ta, (2) 49*f*.
-SiC bodies, submicron grain, P (6) 127*e*.
in single crystals, P (1) 9*c*.
thermal conductivity, (3) 75*i*.
-Y$_2$O$_3$, sintered, (6) 152*d*.
-Y$_2$O$_3$, sintered, strength, (2) 48*h*.
oxide. See also *Abrasives; Boehmite; Corundum; Refractories*.
P (10) 257*c*.
abrasive, crystalline, P (2) 29*f*.
active agglomerates, P (4) 94*f*.
alkalized, P (4) 94*i*.
alloyed with V for grinding, (2) 29*f*.
α body, coating, P (3) 62*c*.
α-, bonding Ni, Cr, and Nichrome to, (2) 38*j*.
α-, ceramics, X-ray diffraction, (11) 281*c*.
α-, crystals, abrasive, P (2) 29*g*.
α-, relative enthalpy, (9) 236*f*.
from AlCl$_3$, hydrolysis, (9) 238*c*.
from Al nitrates, P (3) 71*i*.
Bayer process, P (4) 94*g*.
β-, (6) 143*e*.
β and β'' in system Al$_2$O$_3$-Na$_2$O, (11) 282*a*.
β-, electrolytes, P (3) 66*d*; (9) 237*j*.
β-, memoranes, Na transport through, (9) 237*a*.
β-, sintered, P (1) 10*e, g*.
β-, Na ion transport in, (9) 238*b*.
bodies, P (7) 164*b*.
bonding to metal alloy, (1) 11*d*.
-B$_2$O$_3$, alkyl transfer on, P (1) 20*j*.
cakes, compression on permeability, (9) 223*c*.
calcined, predicting properties, (1) 11*g*.
catalyst reduction on SO$_2$ in, (11) 280*d*.
cation transport in, (6) 145*g*.
in cement clinker, (1) 2*c*.
ceramics, electrical properties, (7) 166*e*.
ceramics, electrotechnical, (5) 110*d*.
ceramics, surface finish, (2) 29*h*.
ceramics, ultrapure, P (5) 111*g*.
ceramics, white spots in, (7) 165*j*.
channel multiplier, P (3) 64*b*.
chemically machining, P (4) 86*b*.
Cr^{3+} in, magnetic susceptibility, (5) 121*d*.
compacts, grain growth in, (4) 96*i*.
-cryolite mixtures, viscosity, (7) 182*a*.
crystals, deformation recrystallization, strength, and fracture, (3) 72*e*.
desiccant for drying gaseous compounds, P (3) 71*h*.
diffusion coeff., in cryolite-Al$_2$O$_3$, (7) 176*f*.
elasticity-porosity relationship, (5) 125*b*.
electric strength, (7) 165*j*.
electrofused, thermal expansion, (2) 44*i*.
extraction, P (7) 175*j*.
extraction from bauxite, P (10) 257*e*.
fatigue behavior, (1) 22*i*.
fibers, P (4) 86*b*.
films, pyrolytic, on Si, (5) 112*c*.
films, rf sputtered on Si, (9) 224*e*.
flame spray powders, P (1) 3*b*.
flame spraying, P (2) 31*h*.
foamed, shape or catalyst support, P (1) 20*e*.
fracture energies, (2) 47*j*.
GaAs on, (4) 86*j*.
γ-, particles featuring, P (9) 233*d*.
grain growth during sintering, (3) 73*b*.

Aluminum, oxide *(continued)*
high, ceramic substrates, (10) 249*d*.
high-, frits, P (4) 86*a*.
hot-pressing and properties, (1) 21*h*.
hydrate, P (3) 71*i*; P (6) 144*g*; P (9) 233*a*.
hydrate, continuous precipitation, P (1) 20*b*.
ir transmission, (1) 11*b*.
initial sintering, (3) 72*i*.
:Fe^{2+}, detection by APR, (5) 119*g*.
Fe removal, P (1) 20*f*.
Fe^{3+} adsorption on, (4) 97*g*.
low-soda, P (7) 176*a*.
materials, upgrading, P (4) 94*c*.
melt, reaction with Ta, Mo, and Nb, (7) 163*j*.
melt, single-crystal sapphire from, P (1) 10*f*.
melting point, DTA measurement, (5) 121*g*.
metalizing at room temp., (9) 224*j*.
for MOS applications, (10) 249*i*.
miscibility, (1) 26*d*.
molten, properties, (8) 210*h*.
-MoMn bond strengths, (1) 2*h*.
monohydrate, P (10) 257*j*.
plasma-arc-sprayed, microstructure, (1) 18*g*.
plasma-sprayed, (3) 54*h*.
plating for space use, (2) 38*d*.
polycrystalline, creep, (11) 280*h*.
polycrystalline, fatigue, (5) 124*e*.
polycrystalline, strengthening, (2) 49*h*.
powder, explosive shocking, (1) 22*h*.
powders, milling effects, (5) 125*g*.
powders, by plasma evaporation, (7) 175*e*.
pressure-sintering, (1) 24*d*.
pseudoboehmitic, P (4) 95*a*.
rapid sintering, glow-discharge apparatus for, P (8) 205*a*.
rate controlled sintering, (8) 195*d*.
recovery from aluminosilicates, P (9) 233*b*.
recovery from alunite and aluminosilicate materials, P (6) 144*d*.
residual stresses in, (3) 72*g*.
separating from Al alkoxides, P (6) 144*e*.
separation from K$_3$PO$_4$, P (6) 144*f*.
:SiO$_2$, effect of ratio on sintering, (7) 156*c*.
single-crystal, P (8) 202*f*.
sintered article, heating, P (7) 166*b*.
sintered, effects of impurities, (1) 21*e*.
sintering, (5) 123*h*; (8) 195*c*.
sintering aid, for B$_4$C, P (4) 85*a*.
sintering, effect of impurities, (1) 21*b*.
sintering properties, (5) 123*h*.
sintering and surface diffusion in, (4) 97*g*.
-Na borosilicate glass composite, (1) 3*d*.
solid state bonding to Ni, (2) 38*i*.
spheroidization of tubular voids in, (11) 282*f*.
strength degradation and crack propagation in, (6) 152*a*.
strengthening by quenching, (5) 111*c*.
substrates, high-density, (9) 223*f*.
substrates, orientation in, (11) 274*e*.
substrates, strengthening, P (7) 170*d*.
substrates, topography, (9) 224*g*.
surface energies, (7) 157*h*.
synergetic pressure-sintering, (3) 75*g*.
tensile stress in, (1) 25*i*.
thermal grooving, (8) 211*a*.
thin film, current through, (5) 112*d*.
thin films on Si, (5) 111*h*.
Ti-, V-, and Cr-doped, far-ir spectra, (5) 120*f*.
transparent polycrystalline, (7) 165*f*.
treatment with V$_2$O$_5$, P (3) 62*a*.
tubes, translucent, (2) 36*h*.
tumbling media, P (11) 265*f*.
unfired cast, reconstituting, P (4) 86*a*.
use of waste from production, P (9) 233*b*.
vapor phase deposition on Al, (10) 249*b*.
vapor species from, thermodynamic properties, (11) 281*e*.
wastes, diamond recovery from, P (6) 127*h*.
whiskers, P (8) 196*h*.
whiskers, kinetics of growth, (3) 74*d*.
and Zr oxide abrasive, P (1) 1*g*.
oxides, fine-sized, P (10) 257*c*.
phosphates, condensed, P (7) 175*h*.
reflector, silicate coating on, P (3) 54*h*.
silicate, strength under stresses, (8) 210*j*.
silicates, lime action on, (9) 233*d*.
sulfates, basic, DTA, (10) 258*g*.
systems. See *Systems*.
titanate, acoustic emission, (2) 38*d*.
tobermorite, low-temp. synthesis, (9) 214*h*.
-tungstic oxide films, P (10) 252*f*.

Alunite, effect on concrete, (8) 185*h*.
quantitative X-ray determination, (6) 142*d*.
recovering Al$_2$O$_3$ from, P (6) 144*d*.

Americium, isolation and purification, P (2) 43*e*.

Amethyst, chemistry and color, (11) 280*f*.

Amino acid, vermiculite-, complexes, (6) 153*a*.

Ammonia, adsorption, on MgO, ir study, (11) 281*c*.
adsorption, on rutile, (1) 22*h*.
equipment, refractories for, (2) 36*f*.
flue gas desulfurization, sulfate control in, P (10) 256*j*.
systems. See *Systems*.

Ammonium, (NH$_4$)$_3$AlF$_6$, P (4) 94*j*.
NH$_4$CrF$_3$, (4) 98*g*.
NH$_4$H$_2$PO$_4$ and NH$_4$H$_2$AsO$_4$, antiferroelectric transitions in, (5) 118*i*.
NH$_4$H$_2$PO$_4$, intense light scattering in, (5) 120*c*.
(NH$_4$)$_4$[O(VO(O$_2$)$_2$)$_2$], crystal structure, (3) 74*e*.
carbonatozirconates, crystalline, P (2) 46*b*.
chlorides, reactions with TeCl$_4$, (8) 210*a*.
metavanadate, P (7) 170*g*.

Ammonium *(continued)*
molybdates and lanthanides, ir absorption spectra, (1) 22*g*.
uranous pentafluoride, α-, P (10) 254*c*.
Amplifier, GaAs, P (2) 39*d*.
lock-in, (8) 204*i*.
microwave acoustic surface wave, P (2) 41*d*.
negative resistance device, P (1) 14*c*.
semiconductor, data on, (7) 168*f*.
devices, P (11) 275*d*.
hf bulk, P (1) 12*e*.
novel, P (5) 113*e*.
tandem oscillator disk, P (3) 67*i*.
traveling high-gain, GaAs, P (3) 68*c*.
Analogs. See *Computers*.
Analysis. See also *Chromatography; Colorimetry; Electron diffraction; Microscopy; Particles; Photometry; Quality control; Screens and sieves; Spectrography; Spectrometry; Spectrophotometry; Spectroscopy; Testing; Thermal analysis; Thermodynamics; Thermogravimetry; Titration; X rays*.
of chemical elements, apparatus for, P (11) 278*g*.
chemical, gas phase, (2) 44*h*.
of marly clay, (1) 5*h*.
of refractory compounds, B (10) 262*e*.
use in tonnage ceramic industries, (9) 230*g*.
"wet" methods, (9) 231*c*.
wet, of Na_2O-CaO-SiO_2 glasses, (8) 204*e*.
of chrome and MgO refractories, (9) 221*e*.
gas. See *Gases*.
of glasses and raw materials, plasma torch for, (8) 205*h*.
inorganic, chromatography in, B (7) 183*g*.
method for materials investigation, B (3) 76*d*.
micromechanics, of ceramic composites, (1) 17*j*.
phase chemical, of Al_2O_3 refractory, (8) 195*b*.
quantitative, automatic, P (6) 142*b*.
of gas, P (9) 231*d*.
of mineral phases, (1) 18*e*.
phase, of NiO–α-Fe_2O_3 system, (11) 277*i*.
of SiO_2-Al_2O_3-CaO system, (11) 278*h*.
of sintering equations, (1) 21*a*.
size, of fine grained sediments, (8) 205*e*.
solid surface, from photo emissions, P (6) 142*f*.
spectrochemical, of solution, P (3) 70*d*.
spectrochemical, by X-ray fluorescence, B (9) 240*f*.
thermohygrometric, of clay, (6) 142*f*.
titrimetric, inorganic, methods, B (1) 27*j*.
Analyzers. See also *Gases*.
P (4) 93*h*.
electrochemical, for measuring O_2 in gases, P (1) 18*e*.
gas, P (7) 174*b*.
micro-, ion, use in glassmaking, (8) 205*f*.
microparticle, P (3) 70*f*.
particle, P (10) 256*b*.
aperture vessel for, P (7) 174*a*.
for asbestos fibers, (8) 205*b*.
sample, temp.-controlled discrete, P (2) 45*b*.
wet and dry, for SO_2, (10) 255*h*.
Anatase, /rutile transformation, kinetics, (9) 236*a*.
Andalusite, in rocks in Calif., (1) 19*g*.
Angles, measurements of glasses on Pt, (11) 269*h*.
of repose, of granular solid, (5) 117*e*.
Yafet-Kettel, in Zn-Ni ferrites, (5) 125*i*.
Anhydride, carboxylic, use of catalysts in, P (11) 280*b*.
Anhydrite, solubility in NaCl, (7) 156*g*.
Anions. See *Ions*.
Anisotropy, constants of $Y_3Fe_5O_{12}$, (11) 281*f*.
effect on solid-state reaction of CaO and quartz, (10) 259*c*.
energy and magnetization in Ga Fe oxide, (5) 119*f*.
materials, electrical resistivity, (5) 116*a*.
paramagnetic, in $EuAlO_3$, (5) 122*a*.
plastic, in Fe, effect of Mn and C, (6) 148*j*.
of rare-earth orthoferrites, (7) 176*g*.
zero, in Ni-Zn ferrite, (2) 38*j*.
Annealing, effect, on abraded $BaTiO_3$, (8) 211*a*.
effects, GaAs, (6) 149*b*.
expansion of Ag_2O lattice by, (2) 47*g*.
of glass. See *Glass*.
with MgO separator, P (2) 31*i*.
Anodes. See also *Electrodes*.
alloy capacitor porous, P (9) 224*h*.
anodization, plasma, of metal on semiconductor body, P (8) 201*j*.
array techniques, P (4) 87*e*.
graphite, for cathodic protection, (5) 109*g*.
graphite treatment, P (4) 84*j*.
rotary, for roentgen tubes, P (6) 135*e*.
Anorthite, synthetic, crystallization enthalpy, (1) 22*g*.
Anorthosite, raw materials for white cement, (8) 185*g*.
Antiferromagnetism. See *Ferromagnetism*.
Antimony, SbOF, crystal structures, (3) 74*h*.
oxides, reactions with V_2O_5, (6) 145*b*.
phosphate, P (6) 144*c*.
systems. See *Systems*.
Apatite, halo-, alkaline earth, precipitating, P (9) 227*j*.
halo-, thermally refining, P (5) 113*b*.
hydroxy-, hydrothermally prepared, (1) 26*a*.
ir and laser-Raman spectra, (7) 178*f*.
Apparatus. See *Instruments; Machinery and equipment; Testing;* and specific types.
Aquagels. See *Gels*.
Aquasols. See *Colloids*.
Aragonite, P (9) 232*h*.
Archeology, "Al Gesu" glass workshop of Miotti's, (11) 266*c*.
Archeology *(continued)*
bottles, Netherlands, (11) 266*h*.
ceramics, thermoluminescent testing, (5) 102*b*.
cup plates in 19th century, (11) 265*i*.
decorated Mexican wares, B (1) 27*g*.
Egyptian and Arab glass stamps, (11) 266*c*.
Etruscan paintings on terra cotta, (5) 102*b*.
fine-grain dating technique, (5) 102*c*.
fired clay, upper Paleolithic, thermoluminescent dating, (5) 102*c*.
glasses, ancient, dating, (4) 77*j*.
articles of British Iron Age, (5) 102*a*.
blown vessels, Roman, (11) 266*a*.
Roman, with brands, (11) 266*c*.
Roman and Islamic, (11) 265*h*.
service, diamond-engraved, (11) 265*g*.
vessels from Jerusalem, (11) 265*j*.
Hacilar style vessels and figurines, (5) 101*h*.
Lezoux, Lyon, and Arezzo Samian ware, (5) 101*i*.
Mycenaean IIICI ware, Tel Ashdod, (5) 102*c*.
mortars, with vegetable fibers, Roman, (11) 265*i*.
pottery, (1) 2*a*.
Roman clay lamp, mummy shape, (11) 266*b*.
Siegburg ceramic ware and stoneware, (7) 155*g*.
Siegburg stoneware, Chinese influence, (7) 155*g*.
Arcs, electric. See *Electric arcs*.
Armor, composite, P (9) 218*f*.
composite ceramic, P (11) 273*b*.
lightweight ballistic, P (2) 38*b*.
plate, dense ceramic, P (6) 136*d*.
Arsenates, linear electrooptic effects in, (1) 11*c*.
Arsenic, As_2Se_3, far-ir vibrational spectra, (6) 148*e*.
As_2S_3, As_2Se_3, and As_2Te_3, heats of fusion, (9) 235*i*.
implantations into GaAs, *n*-type, (7) 176*h*.
monosulfide, polymorphic modification, (5) 122*h*.
systems. See *Systems*.
telluride, radial distribution, (2) 49*d*.
triselenide, Hall mobility in, (2) 48*e*.
trisulfide, vitreous, reflectivity, (8) 191*f*.
Art and artware. See also *Archeology; Decoration; Design; Majolica; Pottery; Tile*.
Arikara Indian ceramics, (2) 30*a*.
balloon pots, (2) 30*a*.
bamboo handles, (2) 30*a*.
birds, (2) 30*a*.
ceramic drinking horns, (2) 30*b*.
ceramic museums in Italy, (9) 213*h*.
ceramic necklaces, (2) 30*b*.
ceramic training, in Japan, (2) 30*g*.
ceramics of middle ages, (7) 155*g*.
cloissonne, (2) 30*b*.
enameled Cu and wood, (2) 30*c*.
enameled masks, (2) 30*f*.
enameled stones, (2) 30*f*.
enameling kits, portable kiln for, P (11) 266*e*.
enameling metal, teaching, (1) 2*a*.
enamelist, thread making for, (2) 30*f*.
enamels and plastics, (2) 30*c*.
facade forms, (2) 30*d*.
folding slab constructions, (2) 30*f*.
form and technique, (2) 30*f*.
gem making for enamelist, (2) 30*g*.
glass, bottles, closure methods, (11) 266*d*.
medieval windows, (1) 1*i,j*.
recent acquisitions, (11) 266*b*.
weathered, layered crusts on, (5) 101*j*.
glassmaking, Thaddaeus Haenke, (8) 185*g*.
glaze colors for pottery, (11) 266*e*.
glazing stoneware, (11) 266*a*.
in Hungary in 19th century, (5) 101*j*.
jar, by Tom Shafer, (2) 30*f*.
jewelry, TiN and/or ZrN based, P (9) 222*i*.
medallions, stoneware, (2) 30*e*.
metalwork and enameling, B (7) 183*f*.
mosaics, shard, (2) 30*d*.
objects USA—Johnson collection, (4) 77*j*.
owls, by El Jahr, (2) 30*b*.
Perth Potters' Club, (4) 78*a*.
porcelains, (2) 30*c*.
pots, big, student-thrown, (2) 30*a*.
coiling pot in, (2) 30*c*.
collapsed, forms from, (2) 30*e*.
news, (2) 30*b*.
slab, from block, (2) 30*d*.
wedging board, (2) 30*g*.
weed, (2) 30*e*.
wheel-thrown, (2) 30*b*.
potters, poets, prophets, (4) 78*a*.
pottery, from Crete, (5) 102*c*.
family, (2) 30*f*.
at Italian fair, (2) 30*f*.
red clay, in Finland, (2) 30*c*.
sack casting, (2) 30*d*.
Scottish potters in 19th century, (4) 77*j*.
sculpture, hollow-built, (2) 30*a*.
sculpture, water whistle, (2) 30*g*.
stencils, found objects as, (2) 30*g*.
stoneware, cone 6, (2) 30*d*.
stoneware exhibition in Germany, (5) 101*j*.
sundials, (2) 30*e*.
teapots, (2) 30*e*.
Artists, Crespi, David, weed pots, (2) 30*e*.
Duckworth, Ruth, (2) 30*c*.
Engler, Heinz H., (1) 1*j*.
Gallucci, Raymond, (2) 30*a*.
Haenke, Thaddaeus, glassmaking, (8) 185*g*.
McIntosh, Harrison, (2) 30*g*.
Nakamura, Kimpei, (4) 77*j*.
Portanier, Gilbert, earthenware, (11) 266*d*.
potter, as demiurge, (11) 266*d*.
Rada, Pravoslav, (4) 78*a*.
Scheid, Karl and Ursula, (1) 1*j*.
Artists *(continued)*
Shafer, Tom, (2) 30*f*; (4) 78*a*.
Sharp, Mary, cloisonne, (2) 30*b*; (4) 77*j*.
Snyder, Kit, porcelains, (2) 30*c*.
Spinski, Victor, (4) 78*a*.
Spuler, Erwin, exhibition, (5) 102*a*.
Wagner, Hans Joachim, asymmetry, (11) 265*i*.
Asbestos, -cement, board, for panel, (6) 129*f*.
corrosion of fibers in, (11) 266*h*.
corrugated sheets from, P (11) 267*a*.
effect of chrysotile asbestos, (9) 214*j*.
explosion-proof shapes, P (9) 215*f*.
products, B (6) 153*j*.
sheets, P (2) 37*c*.
ware, A-fiber in, (10) 241*g*.
chrysotile, colloidal suspensions, P (7) 164*c*.
effect on asbestos cement, (9) 214*j*.
microstructure, (9) 236*j*.
dispersions, coherent bodies from, P (2) 37*d*; P (4) 85*a*.
fiber material, P (9) 222*d*.
friction material, P (3) 61*e*; P (8) 196*j*.
ore, Ni recovery from, P (10) 257*d*.
ore, Ni separation from, P (6) 144*f*.
process and products, P (4) 84*f*.
processing apparatus, P (4) 94*f*.
structures, water-insensitive bonded, P (8) 197*b*.
treatment, P (8) 197*a*.
waste, for chemically resistant tile, (8) 198*a*.
Ash, fly, in cements, (2) 30*j*.
ceramic product from, P (10) 246*b*.
effect on cement paste, (4) 78*d*.
effect on cements, (2) 30*h*.
effect on concrete properties, (6) 129*h*.
foamed ceramic comprising, P (3) 60*b*.
lightweight aggregate from, (9) 220*c*.
power plant, data, (2) 30*j*.
sulfopozzolanicly active, P (4) 79*i*.
treatment, P (9) 230*d*.
from thermal power plants as cement additive, (8) 188*g*.
volcanic, Kansas, expansion in, (3) 71*c*.
Atmospheres, effect on softening brick under load, (1) 18*i*.
effects on Na diffusion in glass, (6) 131*h*.
firing, effect on aggregate bloating, (2) 31*d*.
furnace, effect on hot strength of refractories, (1) 7*h*.
gaseous, effect on ZrO_2 and CeO_2 reaction, (8) 195*c*.
gaseous, sampling, P (10) 256*a*.
sampling devices, P (8) 205*j*.
Atomic energy. See *Nuclear energy*.
Atomization, for phosphors, P (10) 249*g*.
Atoms, ad-, capture and nuclei growth, (6) 144*i*.
atomizing devices, liquid fuel, P (11) 279*b*.
displacements in pyrolytic graphite, (4) 95*d*.
particles, energy and atomic number, P (2) 39*d*.
recombination at surfaces, (1) 24*h*.
Attrition. See *Crushing; Grinding*.
Augers. See *Extrusion*.
Autoclaves, glass-lined, for high pressures, (1) 16*h*.
effect on Ca silicate brick, (1) 5*j*.

Balances (scales). See also *Weighing*.
for ceramic industry, (6) 141*c*.
micro-, electronic, in gravimetric thermal analysis, (10) 255*f*.
Ball mills. See *Mills*.
Barite. See *Barium, sulfate*.
Barium, $BaBiO_3$, paramagnetism and semiconductivity in, (4) 98*d*.
Ba_2GeS_4, structural evolution, (4) 95*i*.
$BaMg_2Si_2O_7$, luminescent properties, (9) 224*i*.
$BaMnO_3$, preparation, and magnetic properties of $BaMnO_3(2H)$, (8) 209*h*.
BaO·4TiO_2·Al_2O_3, identification in system BaO-TiO_2-Al_2O_3, (2) 48*f*.
$BaTeO_3$·H_2O, crystal structure, (11) 280*e*.
-Ca and Ba-Sr phosphate compositions, Eu^{2+} luminescence in, (9) 236*d*.
carbonate, decomposition, (3) 74*h*.
reaction with Fe(III) oxide, (1) 24*a*.
solid reaction with TiO_2, (6) 146*g*.
chlorides, reaction with YCl_3, (5) 123*i*.
feldspar. See *Feldspars*.
ferrite, P (4) 90*e*.
^{57}Fe in, NMR, (6) 150*c*.
powders, magnetic properties, (10) 249*b*.
hexaferrite, from Fe_2O_3 and $BaCO_3$, (5) 124*a*.
hydroxide, P (7) 175*d*.
hydroxide monohydrate, P (8) 207*d*.
Mg pyrosilicate, Eu-activated, P (7) 168*e*.
Mg titanate, rutile substructures in, (10) 260*g*.
nitrate, ir and Raman spectra, (7) 178*a*.
oxide, crystal structure, (5) 119*d*.
dissociation energy in CO/N_2O flame, (5) 119*h*.
fluorescence, laser-induced, (5) 121*g*.
oxides, in glass analysis, (8) 205*d*.
Na niobate, crack-free, growth, P (6) 137*h*.
-Sr niobate crystals, growth, (10) 261*d*.
sulfate, resources of Tenn., (1) 19*i*.
sulfide, as admixture to gypsum, (8) 185*i*.
sulfide, electronic spectrum, (5) 120*b*.
systems. See *Systems*.
titanate. See also *Dielectrics*.
ceramics, dc bias effects in, (9) 223*h*.
ceramics, energy storage in, (7) 167*a*.
critical fluctuations in, (5) 124*i*.
crystal, resistance in, (4) 95*d*.
crystal structure and sinterability, (11) 273*i*.
dielectric behavior, (1) 11*c*.
dielectric properties, (1) 11*d*; (11) 273*h*.

Barium, titanate *(continued)*
doped and undoped, (1) 11*d*.
electrical properties, (9) 224*f*.
electrical resistivity, P (5) 113*j*.
electrooptic effects in, (5) 119*h*.
flash-evaporated thin films, (9) 224*d*.
force constants in, (4) 96*h*.
Fe-substituted, for capacitors, P (2) 40*f*.
nonstoichiometry in, (11) 274*a*.
oxidation of CO on, (11) 274*b*.
powders, high-purity, P (6) 139*g*.
PTCR behavior, (3) 63*d*.
resistivity anomaly in, (3) 75*a*.
semiconducting properties, (7) 166*g*.
single crystals, growth, P (10) 253*a*.
surface domain reorientation, (8) 211*a*.
thermal conductivity, (3) 75*j*.
Ti-rich, (1) 12*a*.
Basalt, effect on portland cement properties, (8) 186*a*.
fused, glass-ceramic material from, (8) 191*f*.
Hungarian, quarrying, (5) 117*h*.
melts, viscosity and structure, (6) 151*j*.
use in mineral wool, (11) 271*h*.
Base exchange. See *Ions*.
Batteries, high temp. Li, ceramic separators for, (9) 230*g*.
Bauxite, Al_2O_3 extraction from, P (10) 257*e*.
bedrock, in chemical stoneware, (5) 109*j*.
calcined, (2) 46*a*.
and kaolins for refractories, (11) 271*g*.
Bayer process, extracting Ga from aluminate solution in, P (10) 257*h*.
removing impurities in, P (6) 144*e*.
Bearings, for high-temp. applications, P (10) 247*c*.
Belite, α-, effect on cement strength, (9) 215*d*.
formation, (7) 177*f*.
hydration in clay-cement mixtures, (10) 241*j*.
in portland cement, (4) 78*e*.
Bending. See *Deformation*.
Beneficiation. See also *Classification; Classifiers; Crushing; Grinding; Filters; Flotation; Screens and sieves; Separation; Separators.*
of clays, contaminated, (5) 116*c*.
ilmenite, P (8) 207*b*.
of ilmenite ore, P (10) 257*b*.
of kaolins with magnetic separators, (9) 232*e*.
of potash ores by flotation, (3) 70*j*.
talc, P (11) 280*b*.
of titaniferous beach sand, P (10) 257*e*.
of titaniferous material, P (4) 94*f*; P (6) 143*i*.
Bentonites, deposits in Nevada, (3) 71*e*.
Benzene, sorption by Kenya diatomite, (5) 117*j*.
Beryl, crystals, refractive index, (5) 122*g*.
Beryllia. See *Beryllium, oxide*.
Beryllium, $Be(PO_3)_2$, crystallographic data, (8) 208*c*.
fluoride, X-ray diffraction, (2) 33*j*.
leaching, P (2) 46*i*.
ores, low-grade, refining, P (7) 176*a*.
oxide, and Be_2SiO_4, crystallization from Li_2MoO_4-MoO_3, (7) 176*h*.
bonding to metal alloy, (1) 11*d*.
crystals, F^+ centers in, EPR and NDOR, (6) 147*i*.
crystals, thermal conductivity, (7) 181*d*.
depositing, P (10) 257*b*.
He diffusion and precipitation in, (7) 171*d*.
hot isostatic pressing, (9) 236*c*.
metalizing at low temps., P (6) 139*e*.
NMR studies, (5) 115*a*.
powder, sintering, (6) 150*g*.
proton incident on, (6) 145*b*.
-SiC, strength and elastic modulus, (1) 25*g*.
sintering, (5) 123*h*.
solubility in chloride and fluoride systems, in tetraborate, and $NaPO_4$, (8) 210*e*.
sulfate, thermal decomposition, (6) 149*h*.
sulfates, thermal decomposition, (6) 152*g*.
systems. See *Systems*.
windows, vacuumtight closure of, P (3) 66*h*.
Binders, for abrasives. See *Abrasives*.
aluminophosphate, (8) 194*h*.
aluminophosphate, refractory composition based on, (8) 195*e*.
aluminous cement C_2S, P (6) 130*c*.
in casting, (3) 69*a*.
classification and research, (2) 30*h*.
decorative slag, (8) 186*d*.
organic, in spray dried pressbodies, (4) 92*f*.
polymeric, adhesion to glass fibers, (7) 158*b*.
silicate, organic-inorganic, P (11) 272*d*.
slag portland cement, for refractory concretes, (8) 187*f*.
for WC and TiC materials, P (4) 84*i*.
use in refractories, P (8) 196*h*.
Binding, properties, of systems $Ca(OH)_2$-(Ge, Sn,Pb,Ti,Zr,Mn)O_2-H_2O, (9) 233*h*.
Biotite. See *Mica*.
Birefringence. See *Refraction*.
Bismuth, Bi(III), spectroscopic probe in glass, (5) 100*h*.
Bi^{3+} uv absorption band in oxides, (8) 211*e*.
germanate, synthesis and properties, (6) 146*f*.
ion, effect on CdS radiation damage, (4) 96*j*.
oxide ceramics, (7) 171*a*.
oxide-type compounds, ferroelectricity in, (2) 38*h*.
systems. See *Systems*.
titanate, ferroelasticity in, (2) 39*d*.
trioxide, effect on Sr ferrite, (7) 167*e*.
trioxide, reaction with ZrO_2, (5) 123*e*.
Black coring. See *Structural clay products*.
Bleaching, clay, P (4) 95*a*; P (7) 175*a*; P (10) 257*c*.
clay, gray kaolin, P (3) 71*c*.
minerals, P (9) 233*d*.
Blending. See *Mixing*.
Blending apparatus. See *Mixers*.
Bloating, of aggregate, effect of firing atm, (2) 31*d*.
of ceramic raw materials, (5) 116*b*.
minerals, thermal behavior, (6) 134*f*.
of shale from Uchida mine, (6) 128*a*.
Bodies, ceramic. See also *Dielectrics*.
P (9) 223*c*.
eliminating voids in, P (4) 88*h*.
glass-bonded, for magnetic head, P (2) 40*i*.
glass-free, metalizing, P (5) 113*d*.
high dielectric constant, P (9) 225*b*.
metalizing, P (3) 66*b*.
porcelain-type, P (9) 223*c*.
preparation, Beacedis machine for, (11) 276*g*.
protective coatings on, patents, (5) 110*j*.
rare earth-titanate, P (11) 275*a*.
sintered, containing residual C, P (8) 197*a*.
wollastonite, synthetic, use in, (1) 10*h*.
Boehmite, and Al_2O_3 gel, hot-pressing, (1) 22*e*.
compacted, creep and shrinkage, (11) 280*j*.
powder, for translucent Al_2O_3 tubes, (2) 36*h*.
Bonding. See also *Seals and sealing*.
aggregates, high purity, (4) 83*j*.
apparatus, semiconductor, aiming device for, P (8) 200*a*.
back-, π, in pyrite-, marcasite-, and arsenopyrite-type structures, (3) 75*d*.
ball, P (5) 113*c*.
ceramics to metals, (10) 247*f*.
chip devices to hybrid circuitry, P (10) 252*j*.
dissimilar materials, P (8) 200*e*.
with glass frit coating, P (1) 12*c*.
glass prism to metal, P (2) 34*c*.
glass with thermoplastic sealing composition, P (7) 161*i*.
graphite or C articles, P (2) 37*c*.
leads, and testing bond strength, P (4) 89*d*.
metal pattern to substrate, P (10) 251*a*.
metallic articles with glass, P (11) 270*c*.
metals to ceramics, (1) 11*d*; (8) 199*c*.
metals to ceramics and glasses, (10) 242*f*.
with particulate glass, P (9) 219*j*.
particulate materials, P (5) 110*a*.
phosphate, P (8) 196*c*.
quartz to metal, P (8) 193*b*.
semiconductor chip method, P (9) 227*g*.
semiconductor devices, P (9) 224*h*.
semiconductor elements, P (4) 87*d*.
solid-state, ceramics to metals, (4) 79*i*.
of Ni to Al_2O_3, (2) 38*i*.
Ni, Cr, and Nichrome sheets to α-Al_2O_3, (2) 38*j*.
state of alkali ions in glasses, (2) 32*b*.
strength, of guncrete coatings on refractories, (8) 195*f*.
substrate, bumps for arrays, P (6) 140*h*.
thermionic cathode to support, P (9) 218*e*.
Bonds, capillary, in moist sand, (2) 47*e*.
of reinforcement and concrete under load, (6) 129*e*.
Si—O, bond length variations in, (4) 98*h*.
strength, Al_2O_3-MoMn, (1) 2*h*.
strength, of semiconductor device, P (5) 114*b*.
Bone, prosthesis, porous ceramic, P (8) 198*i*.
Bone china, glazing, P (8) 198*f*.
Borates, tetra-, BeO solubility in, (8) 210*e*.
Borax, P (8) 207*f*.
reagent flotation, P (4) 95*b*.
Boric acid, P (7) 175*a*; P (11) 279*g*.
coulometric titrations, (9) 231*d*.
fluorination, P (4) 94*h*.
Boric oxide, anomaly in NaF-Na_2O-B_2O_3 glasses, (11) 268*d*.
effect on MgO electrical conductivity, (8) 208*h*.
in glass, determination, (8) 204*d*.
granulated, by fluidized bed process, P (3) 71*f*.
in magnesite refractories, (1) 7*f*.
systems. See *Systems*.
treatment, for glass-ceramics, P (7) 161*h*.
Borides, boriding, effect on Ni properties, (10) 259*i*.
boriding of sintered parts, (10) 246*f*.
di-, refractory, engineering materials, (3) 60*i*.
emission coeff., (3) 73*a*.
hexa-, of alkaline- and rare-earth metals, (10) 259*b,c*.
Boron, amorphous, neutralization, P (8) 204*a*.
B_2O_3-Al_2O_3, alkyl transfer on, P (1) 20*j*.
B_2O_3, vitreous, Raman spectra, (8) 191*e*.
BO^- and BO_2^-, thermodynamics, (4) 96*f*.
boronizing carbide compositions, P (6) 135*i*.
carbide, Al_2O_3 or Al_2O_3-SiO_2 sintering aid for, P (4) 85*a*.
carbide, film product, P (9) 222*b*.
-C fibers, P (10) 248*c*.
carbonitride, reaction with refractory metals and compounds, (10) 261*a*.
coordination No. in borosilicate glasses, (5) 106*c*.
data calculation of paleosalinities from, (3) 71*b*.
diffusion in refractory metal powders, (1) 7*d*.
effect on friction of Ni, (10) 258*h*.
filaments, BN-coated, P (4) 84*g*.
low-twist tensioning, P (4) 84*c*.
surface preparation on, P (3) 61*f*.
minerals, solubilization of Ca borate in, P (7) 175*j*.
nitride, P (1) 9*f*.
abrasive tools, P (9) 213*f*.
cubic, refining, P (8) 197*a*.
cubic, synthesis, (2) 36*h*.
as diffusion source, (11) 273*e*.
fiber, P (3) 61*b*; P (4) 85*a*.
Boron, nitride *(continued)*
fibers, high-modulus, P (9) 222*h*.
films, optical properties, (5) 122*j*.
hot-pressed, P (8) 196*j*.
hot-pressed in composite, P (10) 247*f*.
reactions with W and Ta, (2) 49*f*.
oxide, in glasses, determination, (10) 243*b*.
reaction with carbonates of alkali and alkaline earth metals, (2) 48*i*.
vitreous and liquid, structure, (3) 75*c*.
reaction with Zr, (10) 260*e*.
silicide, monofilaments, P (1) 9*a*.
-Si-nitride materials, amorphous, P (10) 247*c*.
suboxide, P (8) 203*c*.
suboxide, B_7O, preparation, (3) 68*e*.
systems. See *Systems*.
trifluoride, removing SO_2 from, P (3) 71*d*.
trioxide, diffusion of gases in, (3) 55*b*.
and VO, air firable, P (3) 64*c*.
vapor phase deposition, P (10) 253*d*.
Brazing. See *Soldering*.
Brick. See also *Masonry; Refractories; Structural materials*.
P (9) 221*d*.
antique, process, (11) 271*a*.
blocks, panels, and slabs, connecting, P (10) 246*a*.
building, from waste glass, (7) 159*h*.
building structures, P (8) 194*f*.
Ca silicate, autoclaving, (1) 5*j*.
clays, composition and properties, (5) 108*b*.
Hungarian, X-ray diffraction, (6) 141*i*.
Italian, (2) 46*b*.
plasticity, (6) 143*h*.
compressive strains in, (9) 220*c*.
efflorescence and firing, (4) 83*f*.
firing, changes during, (4) 83*c*.
micromorphological changes, (9) 220*e*.
physicochemical changes during, (6) 134*a*.
frost resistance. See *Frost resistance*.
green and fired, glazing, (4) 83*g*.
hollow, mold box, P (7) 163*c*.
lightweight aggregate in, (9) 220*d*.
lime bursting in, prevention, (2) 35*d*.
mill lining, with wear indicator, P (3) 62*b*.
from nonclay or low quality clay, (2) 35*f*.
panel, in Calif., (9) 220*d*.
Canadian, (9) 220*c*.
concrete backing, (1) 6*e*.
in hi-rise, (9) 220*d*.
prefabricated in S. Africa, (3) 60*b*.
prefabricating, P (5) 108*g*.
quick set, (2) 35*e*; (9) 220*b*.
pressing, upgrading quality, (9) 221*d*.
products, strong market for, (11) 271*a*.
properties, effect of molding, (4) 83*i*.
shortage in S. Africa, (2) 35*e*.
silos for grain storage, (9) 221*c*.
softening under load, (1) 18*i*.
Soviet high-strength perforated, (10) 246*b*.
standards and building regulations, (2) 35*e*.
textured, P (5) 104*h*.
treatment, P (10) 246*b*.
unstacking and sorting, P (8) 194*f*.
wall, backing for, (2) 35*d*.
comparison with concrete, (9) 220*e*.
construction, P (5) 108*f*.
and piers, model, (9) 220*j*.
white, (2) 35*g*.
wirecut, for walls, performance, (9) 220*g*.
-work, moisture expansion, (1) 6*d*.
-work, rain penetration, (1) 5*j*.
Brick industry. See also *Structural clay products industry*.
Atkinson Co., (9) 220*c*.
automation in, (2) 35*d*.
Columbus, tunnel kiln in, (11) 271*c*.
coronation, in S. Africa, (5) 108*e*.
cost factors and profits, (2) 35*g*.
Delta-Macon Co., (9) 220*e,f*.
in Germany, disposal of wastes, (9) 239*h*.
Hillabee Brick Co. high production, (9) 220*d*.
in Hungary, history, (6) 134*a*.
Kings Mountain Brick, white, (2) 35*g*.
Malyi, reject percentage reduced, (5) 108*c*.
panel, (9) 220*c*.
S. Africa, excellent quality, (5) 108*e*.
S. Africa, ultramodern plant, (5) 108*e*.
in S. Hungary, history, (5) 108*f*.
Southern Brick, de-hacking at, (2) 35*h*.
and tile, Red River in Canada, (9) 221*b*.
Brickmaking apparatus and equipment. See also *Dryers; Kilns; Materials handling; Presses*.
automatic setting of transportable stacks, (5) 108*a*.
cutting and stacking, P (1) 6*c*.
de-hacking, (2) 35*h*; P (9) 221*b*.
elevator, for moving, P (10) 246*b*.
handling, P (3) 60*b*.
handling and stacking, P (8) 194*e*.
for positioning blanks in stacks, P (3) 60*b*.
sensing and ejecting improper size, P (9) 221*a*.
for setting green bricks in rows, P (3) 69*d*.
for stacking, P (2) 35*g*; P (9) 221*c*.
with interleaving layers, P (9) 221*b*.
and setting down, P (11) 271*b*.
unloader blender, P (1) 6*e*.
unloading and blending, P (1) 6*c*.
Brines, electrolysis, P (6) 135*f*.
fresh H_2O, and $Mg(OH)_2$, P (10) 257*g*.
Brittle materials, ceramics, strength loss, (10) 261*e*.
elastic energy and crack propagation in, (11) 281*g*.
films, fracture, (6) 136*j*.
fracture, effect of platen friction, (7) 178*e*.
"packing" texture, (10) 247*e*.
scribed plates, separating, P (2) 39*a*.
Bronze, A_2MoO_3, de Haas-van Alphen effect, (6) 150*f*.

Bronze *(continued)*
$Li_2V_2O_5$, phase structure, (6) 149*i*.
Sn-W, (10) 260*j*.
Brucite, decomposition, (3) 74*h*.
Brushite, phosphate phosphors from, P (7) 170*f*.
Bubbles, domain properties, of hexaferrites, (2) 47*f*.
domains, magnetization, (7) 177*b*.
fission gas, distribution in UO_2, (7) 171*a,f*.
gas, in glasses, (7) 159*j*.
migrating in KCl crystals, (4) 97*h*.
trapping and removing, P (3) 58*a*.
in glass, analysis of, (1) 3*c*.
measurement of surface energy of solids, (5) 119*h*.
micro-, formed during Zr combustion in N_2/O_2 mixture, (8) 210*b*.
migration, in KCl, (4) 99*f*.
Building materials. See also *Aggregates; Brick; Enamels; Insulation, thermal; Structural clay products; Structural materials.*
block, hollow, (2) 35*f*.
interlocking, P (6) 134*c*.
bricks, panels, and slabs, connecting, P (10) 246*a*.
heat-insulating elements from lime and silicate, P (7) 157*d*.
hollow ceramic articles for, P (7) 163*c*.
industry, automation, (2) 35*c*.
masonry, cutting apparatus, P (3) 69*a*.
masonry, efflorescence resistant, P (10) 246*c*.
panels, bulletproof compound transparent, P (8) 198*e*.
composite, P (9) 218*g*.
heat-, moisture-, and impact-proof, (6) 129*f*.
S. African, (5) 108*d*.
wall, with ceramic tile, P (6) 136*c*.
slabs, for walls, partitions, P (9) 221*a*.
standards, (4) 84*b*.
stones, natural, B (6) 153*j*.
structural elements, (7) 157*f*.
wall, preformed, molding apparatus, P (5) 108*g*.
wallboard, fire-resistant, P (2) 31*e*.
wall ties, properties, (9) 221*d*.
from waste glass, (10) 243*h*.
Bulbs. See *Glass.*
Burners. See also *Flames.*
air-gas flow device for, P (8) 206*f*.
for combustible gas and air, P (8) 206*h*.
control apparatus, P (7) 174*j*.
design, effect on glass furnaces, (8) 190*a*.
duct, for liquid or gaseous fuels, P (11) 279*a*.
effect of furnace aerodynamics, (7) 174*e*.
excess air, P (10) 256*e*.
for fluid fuels, P (4) 93*j*.
fuel, feed unit for, P (8) 206*c*.
pressurized, P (11) 279*c*.
safety control circuit, P (3) 70*i*.
two-chamber, P (10) 256*j*.
unit, P (10) 256*f*.
gas, P (7) 174*j*; P (10) 256*g*.
control apparatus, P (10) 256*h*.
ignition tube for, P (7) 174*e*.
pilot for, P (6) 143*b*.
premix, P (4) 93*j*.
for top-heated ovens, P (7) 174*d*.
for gas-fired apparatus, P (11) 279*d*.
glass tank, automatic oil feed for, (8) 206*c*.
grate coating, P (10) 242*h*.
high combustion rate, P (2) 45*h*.
ir, P (4) 93*j*.
ir, and radiant plates, P (11) 272*d*.
liquid fuel, P (10) 256*i*.
microwave plasma, light source for emission spectroscopy, (8) 205*f*.
muffle, control system for, P (6) 143*d*.
multifuel, P (9) 232*e*.
noiseless radiant wall, P (11) 279*b*.
oil atomization, P (7) 174*a*.
oil, atomizing nozzle for, P (9) 232*c*.
postmix gas ring, P (2) 45*h*.
power gas, flame-stabilizing, P (6) 143*a*.
producing radiant heat, P (5) 117*b*.
self-igniting, P (10) 256*i*.
turbulence muffle, P (2) 45*i*.
Burning. See *Calcination; Combustion; Firing; Lime.*
condition, effect in cement clinker, (4) 79*d*.
time and temp., effect on limestones, (11) 266*j*.
Burnishing. See *Polishing.*

Cables, glass fiber, P (8) 193*a*.
H-V, modular pothead for, P (10) 248*i*.
Cadmium, Cd^+, s-character, in glasses, ESR, (3) 55*j*.
Cd^{2+}, ion-exchange equilibria of zeolite with, (1) 23*e*.
Cd_2BaFe_6, (10) 258*g*.
$CdCr_2Se_4$, photomagnetic effects, (9) 237*e*.
$CdCr_2S_4$, magneto-optical study, (9) 236*f*.
$CdIn_2S_4$, adsorption measurements on, (9) 236*f*.
$CdSiP_2$ and $CdSnP_2$, single crystals, (7) 177*j*.
$CdTm_4Mo_3O_{16}$ phase, (4) 98*d*.
Cd_2TiWO_7, (3) 63*c*.
chalcogenide, single crystal growth, (7) 180*c*.
diffusion in MgO at high temps., (6) 145*d*.
fluoride:Y, electrical properties, (5) 120*h*.
fluoride:Y crystals, ir optical absorption in, (5) 121*c*.
fluorides, crystalline miscibility of Ca, Sr, and Pb fluorides in, (10) 258*g*.
implantations into GaAs, *n*-type, (7) 176*h*.
oxide, conduction-electron interaction in, (5) 122*h*.
oxide, diamagnetism in, (9) 237*h*.
selenide, Se and Te diffusion in, (4) 98*j*.
sulfide, acoustic buildup in, (5) 118*d*.
Cadmium, sulfide *(continued)*
alkalis in, properties, (5) 122*h*.
a-, refractive index, (5) 122*g*.
or CdSe powder for electrophotography, P (6) 139*d*.
-chalcogen compound as photoconductive material, P (10) 249*i*.
crystals, donor-acceptor spectra, (6) 146*e*.
crystals, optical probing, (6) 150*f*.
donor-acceptor pair lines in, (5) 120*a*.
edge emission bands in, (5) 120*b*.
films, (6) 146*f*.
hole-trap depletion-layer formation in, (5) 121*b*.
hollow crystals, (7) 177*i*.
increasing photocurrents in, (5) 120*c*.
ion-implanted, hole level in, (7) 180*b*.
photovoltaic cells from, (7) 167*c*.
pulsed ultrasonic studies, (5) 122*j*.
radiation damage in, (4) 96*j*.
radiative recombination in, (5) 123*c*; (6) 147*a*.
radioactive decay in, (5) 123*c*.
Raman effect in, (6) 150*i*.
Raman scattering in, (6) 150*j*.
Raman spectrum, (5) 123*d*.
Se and Te diffusion in, (4) 98*j*.
single crystals, Cu diffusion in, (5) 119*e*.
sublimation, (4) 99*d*.
and telluride, crystals, (7) 182*c*.
thermal conductivity, (5) 125*a*.
vaporization rates, (6) 152*j*.
systems. See *Systems.*
telluride, S and Se diffusion in, (4) 98*j*.
Sn phosphide, in near-ir detector, P (4) 89*f*.
Calcia. See *Calcium, oxide.*
Calcination. See also *Firing.*
of $CaCO_3$-SiO_2 mixtures, (11) 266*h*.
of cement. See *Cement, burning.*
products, $CaCO_3$-silicate in, (8) 185*j*.
Calciner, lime mud, two-stage, P (9) 215*i*.
Calcining, alkaline earth metal chlorides, P (4) 79*f*.
effects on PZT sintering, (4) 86*g*.
gypsum, P (6) 130*g*.
particulate mineral materials, P (6) 143*b*.
tunnel plant, (4) 94*f*.
Calcite, -dolomite, X-ray determination, (1) 26*c*.
lime and MgO in, (3) 69*h*.
quartz, and kaolinite, or dolomite, synthesis, (5) 121*a*.
staining, (8) 204*h*.
structural isotypes, (1) 25*j*.
Calcium, aluminate hydrates, interconversions, (4) 78*f*.
aluminates, Al*Kα* peak shift in, (6) 151*d*.
carbonation, (6) 145*d*.
X-ray diffraction, (7) 173*c*.
borate, solubilization, P (7) 175*j*.
calc-alkaline volcanics, petrology, (8) 209*j*.
$CaCO_3$-SiO_2, calcination and cementing, (11) 266*h*.
Ca_2FeAlO_5, crystal structure, (7) 176*g*.
Ca_2GeS_4, structural evolution, (4) 95*i*.
Ca_2MnO_4, magnetic ordering in, (6) 150*a*.
$CaO·Al_2O_3$ hydration, effect of Fe oxide, (9) 214*f*.
$3CaO·Al_2O_3·6H_2O$ and $3CaO·Al_2O_3·SiO_2·4H_2O$, carbonization, (10) 242*a*.
$4CaO·3Al_2O_3·SO_3$, paste hydration, (7) 157*d*.
$12CaO·7Al_2O_3$ single crystals, growth, (8) 199*i*.
$4CaO(s) + 2P + 5H_2O(g) = 4CaO·P_2O_5(s) + 5H_2(g)$ reaction, equilibrium study, (3) 73*f*.
CaO-SiO_2 and CaO-SiO_2-Al_2O_3 slags, surface tension, (3) 74*f*.
$2CaO·SiO_2$ and analogs, systems, (4) 79*f*.
$3CaO·SiO_2$, hydration, (4) 78*c*; (9) 214*d*.
$5CaO·2SiO_2·H_2O$ single crystals, (9) 239*b*.
$Ca(PO_3)_2$-$NaPO_3$ equilibrium diagram, (8) 209*h*.
Ca_2SiO_4, *β*-, in cement clinker, (4) 78*f*.
boules, stabilization, (6) 132*h*.
·$CaCl_2$, thermal decomposition, (5) 104*e*.
Ca_3SiO_5 and $Ca_3Al_2O_6$, hydration, (7) 157*g*.
Ca_3SiO_5, Cr solid solution in, (5) 104*a*.
$2Ca_2SiO_4·CaCl_2$, crystal growth, (3) 72*h*.
$CaSO_4·2H_2O$, dehydration, (1) 21*f*.
$CaZrO_3$, by solid-state reaction between CaO and ZrO_2, (9) 235*c*.
$C_4A_3(SO_3)$, expansion, (4) 78*j*.
carbonate, precipitated, P (4) 94*e*.
silicate in calcination products, (8) 185*j*.
single crystals, P (8) 207*h*.
in cements, determination, (9) 215*b*.
chromite, behavior during heating, (9) 233*g*.
di-, aluminate, synthesis and properties, (8) 188*c*.
silicate hydrate, *α*-, in Ca silicate, (5) 116*d*.
silicate, X-ray characteristics, (5) 104*d*.
silicate, X-ray diffraction data, (2) 48*g*.
fluoride, active, sintering, (2) 47*g*.
Ce^{3+}-H^- and Ce^{3+}-F^- in, ENDOR, (6) 145*a*.
crystallographic shear relations with UO_3, La_2O_3, and NaCl, (9) 234*f*.
crystals, with Fe^{3+}, EPR, (4) 96*c*.
in dental prosthesis, P (6) 136*a*.
effect on siliceous clinkers, (8) 186*i*.
elastic moduli, (5) 125*d*.
energy levels of Ce^{2+} in, (6) 147*f*.
Gd^{2+} in, line strengths, (6) 149*d*.
Gd^{3+} and Eu^{2+} in, spin-lattice coeff., (5) 124*d*.
as hot-pressing model, (1) 16*h*.
:Ho^{3+}, optical study, (5) 122*a*.
from H_2SiF_6 and/or Na fluorosilicate, P (11) 279*j*.
from phosphate rock, P (11) 279*h*.
photosensitization of Tb fluorescence by Eu in, (9) 237*f*.
Calcium, fluoride *(continued)*
point-defect equilibria, (9) 235*j*.
point defects in, (6) 152*a*.
rare-earth ions in, (6) 145*b*.
recovery from fluorspar ore, P (8) 207*f*.
sintering, (1) 21*h*.
sintering, additives effect, (7) 177*e*.
and SrF_2 photochromic compositions, P (11) 274*e*.
thermal conductivity, (5) 125*b*.
:U^{4+}, electron-nuclear resonance, (6) 152*h*.
fluorides, crystalline miscibility in CdF_2, (10) 258*g*.
fluoroapatite, in laser, P (3) 65*h*.
gallate composition, Mn-activated, P (4) 87*g*.
halophosphate, containing B, P (8) 200*b*.
hydrosilicates, change during hydration hardening, (7) 157*f*.
hydrosilicates, crystals, properties, (9) 139*c*.
hydroxide, carbonation, (6) 145*d*.
effect on clay minerals-cement interaction, (6) 129*j*.
morphology, (5) 103*a*.
role in C_3S paste fracture, (7) 156*b*.
lignosulfonate, effect on Fe corrosion in concrete, (4) 78*h*.
lignosulfonate, interaction with C_3S, hydrated C_3S, and $Ca(OH)_2$, (7) 156*e*.
molybdate, EPR in, (7) 177*a*.
mono-, aluminate hydration, (4) 78*f*.
mono-, silicate, in hot-pressing, (2) 48*h*.
monosulfoaluminate hydrate, K_2O bearing, (9) 214*a*.
monosulfoaluminate hydrates, (1) 2*f*.
monoxide, solid state reaction with *β*-quartz, (10) 259*c*.
montmorillonite, partial molal vol, (9) 237*a*.
nitrate, ir and Raman spectra, (7) 178*a*.
nitrides, reactions, (4) 99*j*.
oxide. See also *Lime.*
and $2CaO·SiO_2$, dissolution in clinker, (3) 53*j*.
crystals, deformation, recrystallization, strength, and fracture, (3) 72*e*.
effect on sintered Al_2O_3, (1) 21*e*.
electronic structure, (6) 147*d*.
exciton and interband spectra, (6) 148*b*.
exciton spectra, (6) 148*b*.
F centers in, luminescence, (5) 121*c*.
ir lattice vibrational spectrum, (3) 73*i*.
MgO, SiO_2, and Fe_2O_3 mixture, phase transformations, (8) 210*b*.
"mirror" spectrum, (3) 74*a*.
solid solubility in MgO, (1) 25*b*.
solubility in MgO, (2) 49*c*.
from ZrO_2 body, by vaporization, (5) 109*d*.
oxides, in limestone and slurries, (8) 204*d*.
phosphates, concentration, (2) 46*b*.
pyrophosphate, use in phosphors, P (5) 113*i*.
silicate, brick, autoclaving, (1) 5*j*.
finely divided, P (8) 207*a*.
hydrate, molding materials of, P (10) 242*e*.
hydrates, microstructure, (4) 79*b*.
hydrates, pore structure, (10) 242*b*.
hydrates, pore structure and specific surface, (9) 213*j*.
insulation, P (7) 164*b*.
products, dust and abrasion reduction, P (8) 207*g*.
silicates, autoclaved, effect of additives, (7) 156*i*.
carbonation, (6) 145*e*.
hydration, (5) 103*h*.
solid state diffusion into kaolinite and illite, (5) 104*b*.
-Sr phosphate compositions, Eu^{2+} luminescence in, (9) 236*d*.
sulfate, anhydrous, P (7) 157*a*.
dihydrate, P (4) 79*g*.
dihydrate and hemihydrate, DTA, (7) 181*c*.
gaseous reduction, P (1) 2*g*.
hemihydrate, hydration, (3) 73*f*.
removing H_2O from, P (3) 54*d*.
solubility in system CaO-P_2O_5-$CaSO_4$-H_2O, (7) 176*h*.
sulfoaluminate and sulfate, in cement, (4) 79*i*.
systems. See *Systems.*
tri-, aluminate, hydration, (5) 103*g*.
in portland cement, (6) 129*h*.
relation to $Na_4CaSi_3O_9$, (3) 72*d*.
-salicylic acid reaction, (5) 103*c*.
structural changes, (6) 152*a*.
X-ray study, (3) 76*a*.
tri-, silicate, adsorbed H_2O in, (8) 187*h*.
hydration, (5) 103*f*.
hydration kinetics, (7) 156*j*.
hydration and strength, (4) 78*h*.
pastes, hydration, (5) 103*j*.
structure and reactivity, (7) 157*g*.
transformation, (4) 79*g*; (5) 104*c*.
tri-, sulfate, C_3A, and gypsum, hydration, (5) 103*h*.
tungstate, crystals, in phototropic glass-ceramics, P (1) 5*a*.
Eu^{3+} vibronic transitions in, (3) 76*a*.
Ho energy levels in, (7) 177*h*.
Calorimeter, for laser energy measurements, (7) 173*c*.
for measuring thermal radiation, (10) 255*a*.
Calorimetry, of chalcogenide alloy glasses, (6) 131*h*.
of chemisorption of N on Ta, (3) 72*e*.
enthalpy of UB_2 by, (4) 91*c*.
micro-, of H_2O adsorption on clay minerals, (9) 236*j*.
of solid-solid interfacial energies, (7) 176*c*.
solution, of alkali silicates, (2) 33*e*.
Cameras. See *Photography.*

Capacitors, $BaTiO_3$ ferroelectric, P (2) 40*f*.
$BiTiO_3$ film, P (2) 39*c*.
ceramic, P (10) 249*j*; P (11) 274*d*.
condenser, P (3) 64*j*.
with counterelectrode, P (1) 12*d*.
high-voltage, P (9) 225*c*.
multilayer, P (2) 41*f*.
terminals, P (9) 224*i*.
composite dielectric electrolytic, P (2) 39*h*.
defects in, charting and curing, P (6) 137*c*.
electrical, P (1) 13*i*.
electrically variable, P (7) 168*g*.
electrolytic, P (3) 64*h*; P (10) 250*a*.
energy storage, P (5) 112*a*.
fusible ceramic, P (5) 112*e*.
glass-ceramic dielectrics for, (11) 273*g*.
with glass-to-metal seal, P (3) 64*j*.
hermetic printed, P (11) 274*i*.
with malleable means, P (4) 87*h*.
metal-insulator-metal, material for, (9) 224*c*.
MIS voltage variable, P (3) 65*b*.
metal-oxide-metal thin-film, P (10) 251*h*.
MOS, capacitance/voltage, (4) 86*g*.
monolithic, P (3) 66*b*.
monolithic components, P (3) 66*a*.
multilayer ceramic, P (11) 275*c*.
printed, (2) 39*g*.
semiconductive ceramic, P (9) 227*c*.
solid, P (1) 13*b*.
solid electrolyte, P (2) 42*g*.
solid electrolytic, P (2) 40*a*, 42*g*; P (3) 67*h*; P (6) 140*f*,*g*.
solid electrolytic, P (2) 40*a*, 42*g*; P (3) 67; solid-state voltage-variable tuning, P (6) 138*a*.
stacked mica, P (7) 170*d*.
thick-film, from glass-ceramics, (2) 39*f*.
thin-film, P (3) 67*j*; P (5) 114*c*.
titanate, thick-film composition, P (2) 43*a*.
using glass sleeve, P (4) 87*i*.
variable, piezoelectric-driven, P (6) 139*c*.
voltage-variable, P (2) 43*b*.
voltage-variable, smoothly changing, P (1) 14*f*.

Carbides. See also specific types.
and actinide oxide spherical particles, P (9) 229*a*.
carbidic phases in Ni alloys, (10) 260*i*.
carbiding pyrolyzed composites, P (6) 131*d*.
cemented composition, WC-Co, P (10) 247*e*.
ceramic, fusion-cast, with free Si, P (9) 222*g*.
compositions, hardening by boronizing, P (6) 135*i*.
defect, vaporization, (4) 99*i*.
effect on properties of cermet Ni, (10) 259*d*.
emission coeff., (3) 73*a*.
-formation kinetics at graphite/metallic melt interface, (10) 259*f*.
joining, low-temp., P (4) 84*e*.
masses, disintegrating, P (9) 230*a*.
microspheres, improved, P (10) 248*e*.
mono-, physical properties, (3) 74*f*.
nuclear fuel, spherules, P (4) 91*h*.
powders, ultrahigh-purity, P (9) 222*f*.
of refractory metals, deposition, (10) 258*d*.
refractory particles, recovery, P (4) 84*j*.
synthesis, by freeze-drying, (2) 47*e*.
transition metal, single crystals, (7) 177*j*.
substructure, (10) 261*a*.
work function, (7) 176*f*.

Carbon. See also *Graphite*.
activated, P (10) 248*b*.
articles, increasing strength and conductivity, P (2) 37*c*.
articles, reinforced, P (10) 248*c*.
in blast furnace, (2) 37*a*.
bodies, brazing to temp.-resistant materials, P (2) 37*e*.
firing behavior, (9) 221*g*.
large molded, P (2) 37*f*.
reinforced, P (8) 197*b*.
unitary porous, P (8) 196*g*.
vitreous, P (3) 61*f*.
carbonado, natural diamond, (1) 19*i*.
carbonization of acrylic fibrous material, P (10) 248*c*.
carbonization, of phases $3CaO{\cdot}Al_2O_3{\cdot}6H_2O$ and $3CaO{\cdot}Al_2O_3{\cdot}SiO_2{\cdot}4H_2O$, (10) 242*a*.
carbonizing, cellulosic fibrous substrates, P (3) 61*c*.
carbonizing, refractory molds, P (11) 272*e*.
cloth, for composite structures, P (5) 110*b*.
coated article, P (10) 247*d*.
in coked magnesite and dolomite, (11) 271*i*.
composite structures, P (4) 84*h*; P (5) 109*f*.
composites and, B (7) 182*g*.
content analysis, P (10) 255*h*.
diffusion, prevention in sintering, P (9) 228*i*.
diffusion in refractory metal powders, (1) 7*d*.
dioxide, ion exchange of glass with, P (10) 244*f*.
dioxide, solubility in Na_2O-SiO_2 melts, (7) 158*g*.
effect on Fe properties, (6) 148*j*.
electrode assembly, with graphite junction nipple, P (8) 196*a*.
excluding from Si body, P (1) 15*c*.
fibers. See *Fibers*.
fibrous structures, P (1) 9*d*.
filamentary, products, P (1) 9*f*.
filaments, P (3) 61*f*.
high strength, P (1) 9*a*.
from low-priced pitches, P (4) 84*j*.
fluoro-, coating, P (3) 54*f*.
foam, strength, P (4) 84*e*.
glass-like, (3) 60*i*.
glassy, catalytic graphitization, (8) 194*g*.
and graphite shapes, P (9) 222*c*.
graphitic, from thermal degradation of aromatics, (1) 22*j*.

Carbon *(continued)*
hydro-, pyrolysis, effect on structure, (8) 196*b*.
inclusion in SiC crystals, (3) 73*g*.
isotopes, in Kansas shales, (3) 71*f*.
materials and articles, P (10) 247*e*.
materials, structural, P (5) 110*a*.
metal-impregnated seal, P (3) 61*h*.
microstructure in BOF refractories, (8) 195*a*.
monoxide, in dehydration, P (4) 94*i*.
ir spectra and spectral shifts, (3) 73*i*.
oxidation on $BaTiO_3$, (11) 274*b*.
no-binder soft, magnetoresistance in, (3) 73*i*.
particles, controlling orientation, P (9) 222*j*; P (10) 247*j*.
porous material, P (6) 135*a*.
products, ASTM standards, B (10) 262*c*.
products, heat-resistant, P (4) 84*f*.
pyrolytic, for coating microspheres, P (5) 115*a*.
coating process, P (11) 276*d*.
deposition below 1600°C, (5) 115*b*.
in insulating felt, P (1) 9*a*.
reactions with refractory oxides, (6) 142*f*.
in refractory compositions, P (6) 135*f*.
sagger for, P (11) 272*f*.
Sc-, phase, superconducting, P (1) 9*g*.
for stack SO_2 recovery as S, (4) 92*b*.
systems. See *Systems*.
thermal diffusion in UC_2-C system, (2) 43*e*.
thermomigration in metals, (6) 152*f*.
thin films, ion beam deposition, (6) 149*b*.
ThO_2 reduction by, (7) 180*d*.
valence bands in, occupancy, (6) 146*j*.
V(C,N) C-rich solutions, equilibrium, (4) 96*d*.

Carbonaceous materials, high-modulus, P (2) 37*c*.
nonwoven fabric, P (11) 272*a*.
refractory products, P (11) 272*a*.
rocks, of Nagyszal Mountain, (6) 143*f*.

Carbonates, of alkali and alkaline earth metals, reaction with B_2O_3, (2) 48*i*.
aragonite-type, phase relations in, (9) 238*j*.
metal, O isotope fractionation in, (4) 98*c*.
for oxide-coated cathodes, (11) 273*e*.

Carbonation, of Ca aluminates, (6) 145*d*.
of $Ca(OH)_2$, (6) 145*d*.
of Ca silicates, (6) 145*e*.
of cement mortar, (4) 78*f*.
of cement pastes, (9) 213*i*.
of $Mg(OH)_2$, effect of temp., (7) 177*j*.

Carburization, of Mo, (6) 145*e*.

Cast iron. See *Enameling metals; Iron*.

Casting. See also *Molding; Molds; Refractories; Slip casting*.
apparatus, vacuum, P (2) 44*d*.
centrifugal, of glass articles, P (7) 161*j*.
continuous, P (9) 229*h*.
die-, apparatus, P (9) 222*d*.
lost wax process, refractories for, (1) 8*a*.
metal, process, P (9) 222*j*.
mold-transferring system, P (6) 141*g*.
Ni-base alloys using calcia cores, P (6) 135*b*.
sack, (2) 30*d*.
slips. See *Slips*.
steel, refractories for, (6) 134*h*.
steel jet, receiver feeders for, (2) 36*j*.
submerged nozzle, P (10) 248*a*.
from thermoplastic slips, (3) 69*a*.

Castings, producing in permanent mold, P (4) 84*g*.
steel, role of SiO_2 in, (9) 221*h*.

Catalysts, P (5) 117*e*.
and activating method, P (5) 117*e*.
active bodies, P (9) 232*i*.
activity of ferrite powders, (9) 223*i*.
Al_2O_3 support, P (10) 257*e*.
aluminosilicate-Al_2O_3, crystalline, P (6) 144*h*.
aluminosilicate, use in dehydration, P (4) 94*i*.
$BiMoO_4$ and phosphomolybdate-on-TiO_2, P (5) 117*f*.
cathodic reduction, perovskites as, P (6) 144*f*.
CrO_2, P (9) 232*f*.
clinoptilolite blends with, P (5) 117*f*.
Co oxide, P (8) 207*c*.
containing V_2O_5 and TiO_2, P (11) 280*a*,*b*.
Cu-Zn shift reaction, low-temp., P (2) 46*i*.
cracking, metal nitrides as, P (4) 94*h*.
cracking, microspherical zeolitic, P (8) 207*i*.
extruded composition, P (8) 207*g*.
fixed bed oxidation, P (3) 71*j*.
hydrocarbon conversion, P (7) 176*b*.
hydrocracking, P (3) 71*j*,*a*.
hydrocracking, with mordenite, P (3) 71*e*.
hydrotreating, P (3) 71*a*.
Ir, Rh, Ru, or Os, in serial reforming, P (11) 280*a*.
microspherical zeolitic molecular sieve composite, P (6) 144*f*.
Nd_2O_3-BaO composition, P (10) 257*j*.
for N oxide reduction, P (10) 257*c*.
oxidation, P (4) 94*d*.
oxidizing, for exhaust gases of internal combustion engines, P (8) 207*h*.
oxyhalogenation, P (4) 94*d*.
pellets, high-strength, P (9) 232*g*.
Pt group metal-α Al_2O_3, regeneration, P (11) 280*b*.
Pt, serial reforming with, P (11) 280*a*.
reduction of SO_2 in Al_2O_3, (11) 280*d*.
SiO_2, Al_2O_3-coated, P (4) 94*i*.
SiO_2 supports, bead-form, P (10) 257*f*.
SiO_2-Al_2O_3 catalytic cracking, P (9) 233*c*.
SiO_2-Al_2O_3 supported Pt group metal, P (11) 279*j*.
SiO_2-Al_2O_3-NiO, P (5) 118*a*.
semiconductor surfaces as, (1) 11*b*.
solid, properties and mfg. methods, (4) 85*h*.
support, of foamed Al_2O_3, P (1) 20*e*.
supports, for stressing, P (5) 117*j*.
UO, P (4) 95*b*.

Catalysts *(continued)*
zeolite, ammoniated, P (6) 144*i*.
reactivation, P (11) 280*b*.
Zn-containing, P (7) 176*b*.
zeolitic, improving activity, P (6) 144*a*.

Cathode-ray tubes. See *Tubes*.

Cathodes, construction, P (8) 192*b*.
dispenser structure, P (10) 244*c*.
display, sealing in glass envelope, P (4) 82*f*.
field emission, P (4) 87*j*.
-getter, for sputter-ion pumps, P (11) 270*d*.
hot, with pink ruby insulator, P (7) 162*d*.
LaB_6, P (4) 80*c*.
oxide, P (3) 67*b*.
oxide-coated, carbonates for, (11) 273*e*.
photo-, P (4) 89*j*.
Cs-activated III-V compound, P (4) 87*c*.
for discharge tubes, P (9) 227*e*.
GaAs, P (10) 252*b*.
masked, P (10) 251*f*.
multialkali, P (8) 193*e*.
rare earth chalcogenide, P (4) 90*f*.
shielded-, mode bulk effect devices, P (2) 42*f*.
structure, indirectly heated, P (9) 225*i*.
target, for rf sputtering apparatus, P (4) 87*i*.
thermionic, P (7) 170*f*.
bonding to support, P (9) 218*e*.
for electron beam, P (4) 91*c*.

Cathodochromic, properties, of sodalites, (6) 151*e*.

Cathodoluminescence. See *Luminescence*.

Cations. See *Ions, cations*.

Cells, conductivity, for particle counting apparatus, P (9) 231*f*.
fuel. See *Fuels, cells*.
graphite tube spectroscopy sample, P (9) 231*g*.
Li-metal selenide organic electrolyte, P (10) 251*b*.
Li-metal vanadate organic electrolyte, P (10) 251*b*.
memory, and $GdMoO_4$, P (2) 40*g*.
photo-, tubular, P (4) 91*a*.
photovoltaic, P (2) 41*j*.
from ceramic CdS, (7) 167*c*.
coating with glass, P (7) 169*f*.
multicolor device, P (5) 113*c*.
Si array, P (3) 67*h*.
simple from multipoles, and hybrid, (5) 124*j*.
solid-state, P (6) 140*f*.
test, for dielectric constants, (3) 70*f*.
unit, of Ti sulfohalides, (2) 47*i*.

Cellulose, fibrous substrates, carbonizing, P (3) 61*c*.

Cement industry, digital computers in, (5) 102*d*.
oval fireproof chains in, (8) 186*b*.
process control machinery in, (11) 266*j*.
raw material grinding in, (6) 128*i*.
research and development, (2) 31*b*.

Cements. See also *Concrete; Plasters; Pozzolans; Refractories*.
P (11) 267*a*.
additive, P (8) 188*d*.
and adhesives in ceramic technology, (2) 43*g*.
Al_2O_3, hardened, strength, (6) 130*e*.
high-, application, (7) 155*i*.
hydration to CAH_{10} and C_2AH_8, (6) 128*f*.
pastes, hydrated to C_2AH_8 and CAH_{10}, (5) 103*b*.
and portland, from clay and limestone, P (5) 118*b*.
aluminous, alum-containing, P (3) 54*c*.
highly refractory, P (3) 54*a*.
hydration, SO_3 effect, (6) 129*i*.
stabilizing, P (8) 188*f*.
stable, concretes of, P (6) 130*f*.
analysis of concrete, P (3) 54*d*.
aqueous hydraulic composition, P (8) 188*d*.
articles, H_2O-containing, coating for, P (10) 242*d*.
ash, effect of fly ash, (2) 30*h*.
Association of Japan, review, B (11) 284*e*.
based on phosphate binders, deformation, (8) 186*d*.
basic, refractory, (2) 31*a*.
Ca and Mg in, determination, (9) 215*b*.
for C electrodes, P (3) 61*c*.
carbonate, Mg distribution in, (8) 186*b*.
carbonate, ultrastructure, (1) 2*c*.
from cement slurry, P (9) 215*g*.
cementation of sandstones, (8) 210*f*.
cementing $CaCO_3$-SiO_2 mixtures, (11) 266*h*.
cementitious compositions, P (8) 188*e*.
cementitious material, lightweight asbestos-containing, P (8) 196*h*.
chemistry, B (10) 263*a*.
clinkers, P (10) 242*e*.
burning, effect of quartz, feldspar, (4) 79*a*.
cooling, P (9) 215*g*.
cooling, effect on strength, (4) 78*e*.
ferrite phase separated from, (9) 215*d*.
firing, automatic control, (8) 185*i*.
formation in rotary kiln, (8) 186*j*.
grindability and bulk weight, (4) 79*d*.
low F content, P (7) 157*e*.
minerals, dissolution in melt, (3) 53*j*.
minerals, interaction with microaggregates, (8) 187*c*.
siliceous, phase compositions, (8) 186*i*.
colored, P (9) 215*e*.
compacts, strength, (5) 103*e*.
compacts, Young's modulus-porosity relation, (10) 241*j*.
composition for lining pipe, P (9) 215*e*.
and concrete properties, interrelations, (7) 156*f*.
columns, square and rectangular, (6) 130*a*.
containing fly ash, (2) 30*j*.
decorative, colored additives in, (8) 186*e*.

Cements *(continued)*
effect on clay minerals-cement interaction, (10) 241*j*.
electrode joint, P (8) 196*i*.
expansive additives, P (9) 215*h*.
firing and properties, effect of SiO_2, (8) 187*b*.
glass fiber reinforcing in, (8) 191*a*.
grinding, closed circuit, (9) 215*g*.
grinding aid, effect on concrete, (6) 128*c*.
grinding aid and pack set inhibitor, P (2) 31*e*.
guns, P (7) 157*c*.
hardened, pore size in, (1) 2*d*.
hardening, effect of temp., (8) 187*e*.
rapid, (2) 31*c*.
with slag electrophosphorus production, (8) 186*f*.
heat of hydration, relation to adiabatic temp. rise of concrete, (9) 215*c*.
hydration, phosphogypsum effect, (5) 104*a*.
hydration, stages, (6) 129*a*.
hydraulic, P (9) 215*h,i*; P (11) 267*c*.
ash as additive for, (8) 188*g*.
compositions, P (2) 31*f*; P (5) 104*h*; P (6) 130*e*.
mixtures, properties, (5) 104*i*.
hydrogel in, microstructure, (2) 31*f*.
hydrophobically activated, (8) 186*h*.
Fe, Ti, and Al in, determination, (4) 78*g*.
joint test, 69–OC, results, (10) 242*b*.
kiln samples, DTA and conductivity, (8) 188*f*.
kilns. See *Kilns*.
lightweight high-strength, P (9) 215*f*.
lightweight, for oil wells, P (9) 215*f*.
MgO and caustic MgO, (5) 102*f*.
mfg., fluorogypsum as mineralizer in, (6) 129*d*.
mechanical properties, (4) 78*b*.
mills. See *Mills*.
minerals, effect on corrosion resistance of portland cement, (8) 186*i*.
minerals, interaction with hydroxycarboxylic-acid retarders, (5) 103*e*; (9) 214*e*.
mix, plastic shrinkage, (9) 214*i*.
mortars. See *Mortars*.
oil-well, P (7) 157*d*.
pastes, carbonation, (9) 213*i*.
chloride ion penetration, (11) 266*i*.
combining of H_2O in, (8) 187*j*.
deformation and failure, (4) 78*i*; (5) 102*j*.
electron optical study, (11) 266*f*.
hardened, frost action in, (2) 48*h*.
high strength, by hot-pressing, (8) 188*a*.
microstructure, (2) 31*b*.
microstructure and drying, (4) 79*e*.
phase composition, (2) 30*i*.
set, fracture studies, (11) 266*h*.
settling of particles in, (10) 242*f*.
short-time creep transition, (7) 157*f*.
strength, effect of hydrates, (6) 128*e*.
thermodynamics of adsorption, (6) 130*a*.
under high load, (5) 103*d*.
using expansive agent, (10) 242*c*.
H_2O and N adsorption on, (10) 242*c*.
plaster, rheology, (9) 215*e*.
plasters, plasticity evaluation, (4) 78*i*.
pore size distribution, apparatus for, (11) 266*f*.
portland, P (1) 2*e*.
additives for, P (3) 54*d*.
belite in, (4) 78*e*.
compositions, P (7) 157*e*; P (8) 188*f*.
containing MgO, P (7) 157*c*.
corrosion resistance, (8) 186*i*.
effect of admixtures, (10) 241*h*.
effect of basalts on, (8) 186*a*.
efflorescence in, P (6) 130*d*.
extra-high early-strength, P (6) 130*d*.
fast-setting slag, (8) 186*c,f*.
flash setting admixture, (9) 215*h*.
glass phase in, (4) 78*b*.
gypsum in, effect on concrete, (6) 129*h*.
high-strength, (8) 187*i*.
hydration, (5) 103*g*.
interaction with clay minerals, (6) 129*j*.
interlayer, H_2O in, (5) 102*g*.
joint test, (6) 129*a*.
major and minor phases in, (5) 104*g*.
mineral grinding aids, P (1) 2*f*.
modified, P (4) 79*h*.
-plastics combinations, (6) 128*j*.
properties, (8) 186*j*.
saccharide set retardation, (5) 104*b*.
sedimentation, (4) 79*c*.
strength-porosity relation, (4) 78*d*.
structure formation, (5) 103*b*.
sulfate-resistant slag, P (11) 267*b*.
superhigh early strength, (9) 214*h*.
white, concrete based on, (10) 242*c*.
X-ray diffraction analysis, (5) 104*f*.
portland clinker, alite phase in, (9) 213*i*.
Al_2O_3 in, (1) 2*c*.
β-Ca_2SiO_4 in, (4) 78*f*.
Ca_2SiO_4 from, X-ray, (5) 104*d*.
effect of P_2O_5, (3) 53*j*.
phase analysis, (6) 129*h*.
prismatic phase in, (9) 215*f*.
reaction in, (2) 31*c*.
sintering, (4) 79*c*; (9) 214*h*.
strength and color, (9) 214*f*; 215*a*.
C_3A in, (6) 129*h*.
white, P (2) 31*d*.
portland mortar, efflorescence prevention, (9) 214*f*.
portland mortar, strength, (4) 79*a*.
portland paste, effect of temp. change, (7) 156*e*.
heated, sintering phenomenon, (7) 157*b*.
He flow into, (6) 129*c*.
Cements, portland paste *(continued)*
hydration, expansion and porosity, (10) 241*i*.
of low porosity, (8) 186*d*.
Poisson's ratio, (5) 102*j*.
pore size distribution, (5) 102*i*.
set-retardation, (10) 242*d*.
portland plaster, physical properties, (4) 79*g*.
portland slag, as binder for refractory concretes, (8) 187*f*.
portland slag, MgO content in, (11) 266*i*.
powder, raw, preheating, P (3) 54*d*.
production, alkali reduction in, P (3) 54*d*.
products, safe usable temp. for, (10) 242*b*.
properties, (1) 2*g*; (4) 79*i*.
properties, diethylene glycol effect, (4) 78*f*.
-quartz cubes, phase compositions, (8) 187*a*.
quick setting and hardening, P (9) 215*i*.
raw materials, computer-controlled for kiln, (4) 79*h*.
grinding, (8) 186*c*.
homogenization, (9) 215*a*.
mine surveys, (8) 207*a*.
in N. Hungary, (2) 31*a*.
optimum fineness for, (8) 187*d*.
work index test, (4) 79*b*.
raw meal, tandem grinding plant for, (8) 188*d*.
raw mix, control, P (1) 2*d*.
homogenization, (8) 187*h*.
X-ray analysis, (9) 214*i*.
refractory high-Al_2O_3, (8) 194*i*.
reinforced with C fibers, (7) 156*d*.
retarder determination, P (2) 31*e*.
set, false, tests, (4) 78*h*.
sheet, textured, P (2) 31*g*.
shrinkage-compensating, P (6) 130*h*.
and SiO_2 compositions, curing, P (4) 79*h*.
slag, decorative binder, (8) 186*d*.
slag, replacement with quartzite, (8) 187*h*.
slurry, electroconductivity, (8) 187*f*.
measuring level, (8) 187*d*.
physicochemical properties, (8) 187*a*.
process of averaging, (8) 187*b*.
and soils, water-repellent, P (8) 188*g*.
sorel. See *Cement, magnesium oxychloride*.
standards, improvement, (8) 186*h*.
standards and testing, (4) 78*f*.
strength, curing temp. effect, (6) 128*e*.
effect of grinding, (4) 78*i*.
effect of mineral powders, (9) 214*g*.
relation to α-belite, (9) 215*d*.
sulfate-slag, (8) 188*b*.
superhigh early strength, P (2) 31*f*; (9) 214*d*.
superhigh early strength, chemistry, (6) 128*b*.
supersulfated, microstructure, (4) 79*e*.
superwhite, P (3) 54*b*.
suspensions, conserving air phase in, (7) 156*e*.
system CaO-MgO-Al_2O_3-SiO_2, dispersions, hardening, (7) 156*h*.
C_3A-$CaSO_4$-H_2O systems, hydration, (5) 103*i*.
C_3S-H_2O system, He flow and density, (5) 103*h*.
ultrafine, apparatus for, P (2) 31*d*.
-H_2O system, relaxation and polarization, (3) 54*b*.
white, anorthosites for, (8) 185*g*.
Ceramals. See *Cermets*.
Ceramet. See *Cermets*.
Ceramic engineering. See *Engineering*.
Ceramic industry, air pollution in, (7) 182*c*.
batch processes, computer control, (11) 276*h*.
charging devices and balances for, (6) 141*c*.
computers, in plant and design, (11) 276*f*.
Italian, silicosis in, (7) 182*f*.
Soviet, new equipment in, (8) 197*e*.
technical, in Australia, (9) 239*h*.
terminology problems in, (7) 182*d*.
tonnage, chemical analysis in, (9) 230*g*.
Ceramic materials. See *Bodies, ceramic; Materials, raw;* and specific types.
Ceramic-metal systems. See also *Enamels*.
coating surfaces, P (10) 242*g*.
bonding metals to ceramics and glasses, (10) 242*f*.
cermet-type coating on metal, P (10) 242*h*.
composition for marking hot metal, P (5) 105*a*.
corrosion-resistant, P (8) 189*b*.
hot-rolled metal body, treating, P (6) 131*e*.
phosphatized surfaces, posttreatment, P (2) 32*a*.
Na‖Cl,SiO_4,PO_3, (8) 189*d*.
solid-state bonding, (4) 79*i*.
strips, P (8) 189*c*.
Ceramics, abrasive machining, (3) 53*i*.
cellular nodule, C-coated, P (8) 198*g*.
cellular nodules, for burning combustible liquid, P (8) 198*g,h*.
classification, (4) 100*a*.
constituents, spectrometry, (9) 230*g*.
early American, B (7) 184*f*.
fluorocarbon coating on, P (3) 54*f*.
industrial processing and testing, B (10) 262*d*.
-to-metal bonding, (10) 247*f*.
metalization, P (1) 12*j*.
metalized and brazed, P (9) 226*b*.
in microelectronics, (2) 39*j*.
precision engineering, B (9) 240*b*.
products in contact with foodstuffs, (7) 165*a*.
products, effects of porosity, (4) 98*g*.
properties, of Ba-Sr ferrites, (8) 199*b*.
properties, of Sr ferrite, (8) 199*d*.
in severe environments, B (8) 212*f*.
special, symposium, B (11) 284*f*.
thin sheets, by calendering, (9) 223*g*.
Ceria. See *Cerium, oxide*.
Cerium, Ce^{3+}, energy levels in CaF_2, (6) 147*f*.
Cerium *(continued)*
Ce^{3+}-H^- and Ce^{3+}-F^- in CaF_2, ENDOR, (6) 145*a*.
Ce^{3+}, transition, in MPO_4 (M=Sc, Y, and Lu), (3) 73*a*.
$CeTi_2O_6$, properties, (1) 25*i*.
-ic oxide, grain growth, TiO_2 effect, (6) 147*a*.
-ic oxide, reaction with ZrO_2, (8) 195*c*.
Mg nitrate, phase transition in, (6) 150*b*.
monosulfide, (6) 143*j*.
oxide, effect on thermal expansion of enamels, (1) 3*a*.
O self-diffusion and electrical transport properties, (9) 237*i*.
use in glass decolorization, (3) 57*b*.
phosphate, positively charged, P (2) 46*b*.
sulfide, thermal expansion coeff., (10) 258*d*.
trimetaphosphate trihydrate, crystal structure, (6) 145*j*.
Cermets, conductivity, (8) 199*a*.
film components, anodizable, P (6) 137*f*.
Au-metal oxide, electron emission from, (7) 167*i*.
hardness and wear, grinding effect, (10) 246*i*.
high-melting-point, testing, (10) 247*i*.
of high static and dynamic strength, P (11) 272*c*.
mfg., infiltration technique, (1) 8*f*.
"molecular," of U-Mo oxide, (1) 15*i*.
Ni, properties, effect of carbides, (10) 259*d*.
in phase diagrams, (5) 108*i*.
powders, external friction, (10) 246*g*.
slip casting, P (10) 248*d*.
TiC base, sintering, (10) 247*j*.
use in textile industry, (10) 247*a*.
Cesium, borates, ^{133}Cs NMR in, (7) 159*d*.
Cs_2CS_2·H_2O, crystal structure, (6) 145*j*.
$CsFeF_4$, ferroelastic effect in, (11) 281*i*.
$CsNiCl_3$, (7) 179*e*.
$Cs_2UO_2Cl_4$ and $CsUO_2(NO_3)_3$, NpO_2^{2+} EPR in, (5) 120*j*.
$Cs_2UO_2Cl_4$, NpO_2^{2+} absorption spectrum in, (5) 118*c*.
$CsUO_2(NO_3)_3$, NpO_2^{2+} in, (6) 144*i*.
chloride, high-pressure equation, (6) 148*b*.
evaporator, P (6) 137*h*.
field desorption, (3) 73*i*.
iodide, interference filter, P (2) 33*g*.
ions, effect on TaC work function, (5) 125*f*.
minerals, thermal expansion, (6) 152*h*.
and K nitrates, separation by zone melting, (3) 71*e*.
salts, films, (3) 73*i*.
silicates, polymorphism, (8) 210*e*.
systems. See *Systems*.
vaporization, (11) 283*b*.
Chalcogenides, alloy films, electrical conductivity, (6) 136*h*.
alloy films, optical properties, (6) 136*i*.
films, glassy, depositing, P (8) 201*e*.
hopping conduction and optical properties, (6) 136*g*.
switching in, thermal effects, (4) 87*a*.
glassy, transformations in, (6) 152*d*.
PdP, P (7) 169*i*.
semiconductors, films, switching in, (6) 145*c*.
thin films, electrical measurements, (6) 137*d*.
thin films, transformations in, (6) 136*h*.
Chalcogens, diffusion in II-VI compounds, (4) 98*j*.
Chamotte. See *Refractories*.
Checker-brick. See *Refractories*.
Chemical analysis. See *Analysis*.
Chemical engineering. See *Engineering*.
Chemical industry, plant, glass for construction, (2) 32*g*.
Chemical properties, of Mg_2Si, (3) 60*g*.
of $MTiO_4$ and MTi_2O_6, (1) 25*i*.
of Nb germanides, (6) 145*a*.
of refractory compounds, B (10) 262*e*.
Chemical reactions, collision dynamics, (4) 95*c*.
rate coefficient, (6) 151*j*.
under high pressure, (4) 95*j*.
Chemisorption, of N on Ta, (3) 72*e*.
Chemistry. See also *Analysis; Electrochemistry; Geochemistry; Thermodynamics*.
of amethyst, (11) 280*f*.
attack of enamel surfaces, (11) 267*d*.
of cement and concrete, B (10) 263*a*.
of cement, super-high early-strength, (6) 128*b*.
chemical attack of enamel surfaces, (4) 79*j*.
of clays and ceramic materials, B (6) 153*c*.
composition, determination, B (5) 126*c*.
cryo-, process, (3) 62*f*.
high temp., B (6) 153*f*.
high temp., advances in, B (8) 212*a*.
methods of silicate analysis, B (7) 182*h*.
molten salt, advances in, B (4) 100*b*.
silicate, (11) 278*f*.
of silicate materials, B (10) 262*j*.
of Si and silicates, B (5) 126*b*.
stereo-, of Pt metals in melts and glasses, (2) 32*f*.
wet-chemical preparation of glass, (9) 218*a*.
Chinaware. See *Art and artware; Dinnerware; Porcelain*.
Chlorides, corrosion in concrete, protection, (4) 78*h*.
effect on alite and belite formation, (7) 177*f*.
ions, penetration into cement pastes and concretes, (11) 266*i*.
Chlorination, selective, of ilmenite, (2) 46*e*.
of Y_2O_3 in presence of C, (9) 232*g*.
Chromates, double, crystallography, (9) 234*h*.
Chromatography, of compounds in systems $NaPO_3$-Fe_2O_3 and $NaPO_3$-Al_2O_3, (1) 21*e*.
extraction, for Am isolation and purification, P (2) 43*e*.

Chromatography *(continued)*
gas, of bubbles in glass, (6) 132*a*.
gas, to determine CO_2 solubility in Na_2O-SiO_2 melts, (7) 158*g*.
in inorganic analysis, B (7) 183*g*.
separation with porous SiO_2, P (10) 255*h*.
sorbent sheet for, P (6) 143*h*.
Chrome. See *Chromium; Refractories.*
Chrome-magnesite brick. See *Refractories.*
Chromia. See *Chromium, oxide.*
Chromite. See *Refractories.*
Chromium, arsenide, magnetic structure, (4) 97*d*.
borides, magnesiothermic production, (3) 60*d*.
carbide, stability, (3) 75*b*.
Cr-C and Cr-Ni-C resistive films, P (2) 39*f*.
Cr(III) ions, absorption in glasses, (11) 267*g*.
Cr^{3+} in Al_2O_3, magnetic susceptibility, (5) 121*d*.
Cr^{3+}, ESR in $LiNbO_3$, (5) 120*a*.
Cr^{3+}, fluorescence in $SrTiO_3$, (5) 125*j*.
$CrSb_2$, neutron diffraction study, (5) 118*i*.
$CrAs_{1-x}Se_x$, magnetic properties, (4) 97*b*.
CrI_3, internal field studies, (5) 121*c*.
$Cr_{1-x}Fe_xSb_2$, phase, (5) 118*i*.
Cr_2O_3-V_2O_3 mixtures, Cr_2O_3 and V_2O_3 in, (9) 239*f*.
dioxide, ferromagnetic, for magnetic tape, (1) 11*f*.
recording compositions, P (4) 87*a*.
synthesis and bond lengths, (5) 117*d*.
double fluorides, (4) 98*g*.
effect on S activity coeff. in Fe-Cr-S alloys, (6) 146*h*.
-Eu pair emission in $EuAlO_3$:Cr^{3+}, (5) 118*f*.
glaze colorant, (2) 30*c*.
-ic oxide, effect on cement clinker, (9) 214*f*.
final sintering, (10) 259*g*.
miscibility, (1) 26*d*.
optical absorption spectrum, (5) 121*d*.
ultrasonic behavior, (6) 152*h*.
vaporization over Al_2O_3-Cr_2O_3 solid solutions, (11) 283*b*.
ion pairs in ruby, energy levels, (5) 120*b*.
ion pairs in ruby, resonance study, (6) 150*c*.
ions, in oxide matrices, magnetic properties, (1) 23*i*.
and Ni-Cr sheets, bonding to α-Al_2O_3, (2) 38*j*.
oxide-Al_2O_3 spherical particles, P (10) 257*g*.
oxide, ferromagnetic, P (4) 94*h*.
solid solution, in Ca_2SiO_3, (5) 104*a*.
systems. See *Systems.*
Te-, dioxides, Fe-modified, P (5) 114*b*.
trichloride, reaction with Na tetrahydroborate, (8) 210*j*.
-W coating on W, P (4) 80*a*.
vanadate, thermal expansion, (7) 181*d*.
Chrysotile, fluorhydroxyl, hydrothermal experiments, (3) 73*f*.
high-surface-area, P (7) 164*f*.
synthesis, (1) 25*c*.
Circuits, applications, of semiconductors, (6) 137*b*.
boards, stacked, P (10) 251*f*.
chip, transistor, P (6) 138*c*.
component, piezoelectric, P (10) 252*f*.
composite crystal filter, P (2) 39*h*.
electric, protector for, P (6) 136*d*.
electrical, assemblies, P (4) 87*c*.
electroconductive heating, for glass, P (9) 218*d*.
electronic memory, P (6) 137*d*.
ferromagneto-piezosemiconductor, P (9) 226*i*.
fuel burner safety control, P (3) 70*i*.
high *Q*, on ceramic substrates, P (10) 250*h*.
hybrid, bonding chip devices to, P (10) 252*j*.
hybrid, mounting components in, P (10) 251*b*.
integrated, P (3) 65*f*; P (5) 112*i*; 113*b*; P (6) 138*b*; P (11) 275*a*.
air-isolated, P (10) 251*j*.
arrays, P (5) 113*c*.
beam-lead devices for, (3) 62*f*.
ceramic package, P (6) 137*j*; P (9) 224*i*.
clamping, P (7) 169*a*.
composite, P (10) 250*b*.
device, multiple lead, P (2) 41*h*.
device, semiconductor, P (8) 202*j*.
dielectrically isolated, P (3) 65*e*.
electronic, wiring, P (4) 89*a*.
flip-chip, P (5) 112*d*.
forming beam leads on, P (7) 169*g*.
heat-sink package for, P (6) 137*i*.
leadless package for, P (5) 113*a*.
Mg-Al spinel crystals for, P (3) 66*e*.
mask, P (9) 226*j*.
miniature hybrid, P (4) 89*b*.
monolithic, P (2) 39*g*; P (4) 89*e*.
monolithic, Si, P (3) 66*b*.
monolithic structure, P (2) 41*e*.
package, P (10) 250*j*.
packages, sealing technique, P (3) 67*i*.
probe header for, P (2) 42*c*.
process, P (8) 200*j*.
resistor for, P (4) 90*j*.
semiconductor, P (1) 12*g*; P (2) 42*c*; P (3) 67*e,f*; P (4) 89*g*; P (5) 112*f*; P (6) 138*d*.
semiconductor devices, P (11) 275*h*.
semiconductor devices in, P (5) 112*h*.
semiconductor, large, P (4) 89*j*.
semiconductor package, P (10) 250*j*.
on semiconductor substrate, P (2) 42*d*.
solid-state, P (2) 41*i*.
structure, P (6) 137*i*.
three-dimensional, P (2) 43*c*.
using bulk resistor, P (3) 64*i*.
interrupters, vacuum-type, P (2) 39*g*.
LSI, P (3) 65*g*.
low-voltage pulser, P (10) 251*d*.
for measuring capacitance of semiconductive device, P (2) 41*a*.
member, composite, P (3) 64*c*.

Circuits *(continued)*
MOS, P (1) 14*a*.
MOSFET memory, (7) 167*j*.
MOSIC, P (1) 14*a*.
MOS integrated, driver system, P (10) 252*e*.
micro-, ceramics for, (9) 223*j*.
modular package, P (11) 275*f*.
Ta, resistivity measurements, (8) 205*c*.
microelectronic, P (3) 66*j*.
microwave, P (4) 89*d*.
monolithic, ac line operation, P (6) 137*e*.
network, crystal ladder, P (2) 39*j*.
oscillator, crystal, P (11) 275*g*.
piezoresistive elements, P (11) 275*j*.
Pt resistance thermometer, P (2) 45*d*.
printed, P (7) 169*c*; P (10) 252*j*.
base material and mfg., P (3) 64*h*.
board, plating Cu layer on, P (4) 89*g*.
boards, P (9) 227*i*.
boards, additive, P (9) 226*a*.
glass masters, P (5) 107*d*.
grid layout for, P (2) 41*f*.
multilayer, P (1) 13*f*.
prototype facility for CerDip packaging, (11) 274*h*.
Schottky barrier, diode, P (10) 252*f*.
semiconductor, P (4) 90*a*.
Si pressure transducer, P (6) 140*f*.
slow wave, P (2) 42*g*.
solid-state, as hf tuner, P (6) 139*a*.
starting, for discharge lamp, P (4) 83*b*.
thermocouple, grounded, (11) 279*c*.
thermocouple input temp. sensing, P (7) 174*b*.
thin-film, P (1) 13*b*; P (2) 39*e*.
elements, P (2) 41*a*.
hybrid, P (9) 226*b*.
thyristor, P (5) 114*c*.
trimming, with abrasives, (3) 62*e*.
for tuning YIG filter, P (9) 224*j*.
Circulators, ferrite, wave-guide, P (8) 203*b*.
stub-tuned, P (10) 253*e*.
Y-junction, with common arm capacitor, P (1) 15*b*.
Classification. See also *Separation; Separators.*
of binders, (2) 30*h*.
of BL ceramic dielectrics, (3) 62*h*.
of ceramics, (4) 100*a*.
of fibers by wet process, P (4) 92*g*.
of liquid suspensions and solid materials, P (3) 71*h*.
of particles, irregularly shaped, (3) 69*h*.
pneumatic system, P (2) 44*c*.
Classifiers. See also *Beneficiation.*
with adjustable fines outlet, P (9) 229*h*.
centrifugal, dry, P (9) 230*e*.
grinding equipment with, (9) 214*i*.
hydraulic, for solids, P (8) 203*j*.
hydrocyclone, underflow outlet for, P (5) 111*b*.
for particles by sphericity, P (10) 254*h*.
powder, P (9) 230*b*.
for slurry, (8) 186*c*.
for suspensions in liquid or solid, P (10) 255*g*.
Clays. See also *Bentonite; Fireclay; Kaolin.*
Al_2O_3-SiO_2, dry acid treatment, P (3) 71*i*.
ball, blue, deflocculation, (1) 9*h*.
bauxite-accompanying, of Halimba area, (2) 46*e*.
beneficiation, (5) 117*c*.
blast furnace slag addition, (1) 6*a*.
bleaching, P (4) 95*a*; P (7) 175*a*; P (10) 257*c*.
bloating for lightweight aggregates, (5) 108*c*.
bodies, for ranges, (2) 30*b*.
testing, (2) 30*e*.
unfired ceramic, moisture stress in, (7) 165*e*.
-cement, hydration of alite and belite in, (10) 241*j*.
ceramic, characterization, (6) 141*h*.
ceramic properties, testing, (6) 142*i*.
ceramics, thermal-expansion data, (1) 17*j*.
chemistry and physics, B (6) 153*c*.
china. See *Kaolin.*
compacted, specimen uniformity, (7) 173*i*.
discolorants separated from, P (8) 207*g*.
drying processes, (3) 70*i*.
Dutch, firing temp. and maturing time, (4) 83*h*.
effect on $BaTiO_3$, (11) 273*i*.
English, of Italy, (4) 94*e*.
fired, moisture expansion, (9) 229*i*.
foamed, process, P (10) 246*c*.
freeze-dried and thawed, (5) 120*j*.
glass mold, (7) 159*c*.
hectorite-type, synthetic, P (9) 233*b*.
industrial, plasticity chart for, (6) 143*h*.
industries, and fuel pollution, (2) 50*g*.
ion exchange in, (1) 19*j*; (4) 85*h*.
Jamaican, mineralogy, (1) 20*e*.
kaolin, gray, bleaching, P (3) 71*c*.
kaolin, for white brick, (2) 35*g*.
kaolinitic, adsorption of polyanions, (1) 9*h*.
kaolinitic, vitrification, (8) 209*g*.
and limestone, cement from, P (5) 118*b*.
lumps, comminution in concrete aggregates, (7) 156*i*.
materials, analysis of standards, (11) 278*d*.
New Mexico, test data, (3) 71*g*.
strain during firing, (2) 35*f*.
microstructure and pore structure, (5) 121*j*.
minerals. See also specific types.
data, calculation of paleosalinities from, (3) 71*b*.
diagenesis in shales and sandstones, (8) 208*d*.
diffuse reflectance spectra, (9) 234*j*.
effect of deflocculants, (5) 110*i*.
interaction with cement, (6) 129*j*.
magnetic separation, (8) 207*a*.
neoformation, (9) 237*c*.

Clays, minerals *(continued)*
reactivity with acids and alkalis, (5) 123*j*.
specific gravity, (11) 282*d*.
H_2O vapor adsorption on, (9) 236*j*.
montmorillonitic, Kansas, DTA, (3) 71*c*.
natural, elimination in bodies and glazes, (1) 10*e*.
-organic complexes, colored, (6) 150*g*.
particle orientation in, measurements, (6) 145*e*.
particle size distribution and surface area, (11) 281*i*.
particles, liquid filter for, P (11) 277*b*.
pellets, thermally bloating, P (3) 60*c*.
permeability, (5) 121*h*.
Ranong, properties, (11) 281*g*.
raw kaolinitic, rheological properties, P (10) 257*d*.
red, in Finland, (2) 30*c*.
refractory flint, of Sydney basin, (8) 206*i*.
satin white-, compositions, P (3) 72*a*.
and shale resources of Ill., (3) 71*b*.
and silt, size analysis, (1) 18*i*.
Soma Ohori, mineral composition, (5) 117*i*.
of southwestern Ala., (3) 71*c*.
spray-drying effects, (4) 94*d*.
structural, Dutch, dilatometer curve, (4) 83*d*.
surface-modified, P (3) 72*b*.
suspensions, particle geometry, (5) 122*b*.
Swiss marly, (1) 5*h*.
systems. See *Systems.*
thermohygrometric analysis, (6) 142*f*.
-ware industry, cost and profits, (2) 35*g*.
-ware shaping machine, P (7) 166*a*.
H_2O adsorption by, (2) 47*a*.
H_2O removal, (1) 20*a*.
web wastes, removal in shaping machine, P (6) 134*c*.
Cleaning, apparatus, filter press with, P (3) 69*f*.
control for precipitator, P (1) 16*g*.
flue gases, apparatus for, P (2) 43*h*.
grinding wheels, P (9) 213*e*.
magnetic filters, P (4) 92*b*.
sanitary ware surfaces, P (10) 242*h*.
Clinker. See also *Cement; Dolomite; Forsterite; Magnesite.*
minerals, quantitative determination, (4) 79*a*.
Coagulation. See *Agglomeration.*
Coal. See *Fuels.*
Coatings. See also *Enamels; Glazes; Resins.*
ablative, elastomeric composition, P (3) 61*c*.
antireflection, P (1) 3*c*.
antisublimation, P (3) 64*d*.
apparatus, vacuum, P (5) 114*e*, P (8) 202*j*.
application. See *Deposition; Electrostatic processes; Spraying.*
aqueous compositons for glass, P (8) 192*a*.
Bi oxide-containing, P (10) 243*e*.
burner grate, P (10) 242*h*.
C, low density pyrolytic process, P (11) 276*d*.
for cathode-ray tubes, P (7) 162*h*.
ceramic molds, P (6) 135*c*.
cermet-type alloy, on metal, P (10) 242*h*.
Cr-W on W, P (4) 80*a*.
chromizing, graphite powders, (10) 246*j*.
colored, for glass sheet, P (11) 270*b*.
composite, electrodeposition, P (10) 250*a*.
composition, P (8) 189*a*.
for porous ceramic insulation, P (9) 219*f*.
spray, P (3) 54*i*.
conductive, on substrate, P (11) 275*a*.
continuous-cleaning, for ovens, (6) 131*d*.
continuous, metal powders in, (6) 131*b*.
crucible, for preparation of U and Pu alloys, P (8) 203*f*.
detonation, (10) 246*i*.
diamond particles with metal, P (7) 155*f*.
diffusion, of ferrous articles, P (3) 54*i*.
diffusion and plasma, for electrodes in Al, (10) 246*i*.
electro-, enamels, (3) 54*e*.
electrodes, P (9) 227*i*.
electrostatic. See *Electrostatic processes.*
epoxy resin, for α-Al_2O_3 body, P (3) 62*c*.
ferromagnetic articles, P (4) 89*d*.
films. See *Films.*
flame spray powder, ceramic clad, P (7) 157*j*.
fluorocarbon, on metals and ceramics, P (3) 54*f*.
fuel-element, containing burnable poison, P (3) 68*h*.
for Ge semiconductor devices, P (3) 64*c*.
glass, B_2O_3-SiO_2, for substrate, P (6) 133*b*.
borosilicate, on solar cell, P (7) 169*f*.
with durable coatings, P (6) 133*e*.
fiber, P (6) 132*h*.
fiber structures, P (10) 245*b*.
fibers and resin, P (3) 59*e*.
filaments, P (10) 243*j*.
in float glass method, P (8) 192*d*.
GeO_2-SiO_2, P (9) 225*j*.
for Au conductor pattern, P (10) 253*g*.
hot, apparatus for, P (7) 161*f*.
lining for flanged tube, P (11) 267*e*.
for lining reactors, (11) 267*d*.
on molten metal bath, P (10) 243*j*.
particles with O compound, P (8) 192*c*.
for radioactive waste, (11) 268*f*.
for steel sheets, P (3) 54*f*.
-ware, P (11) 270*d*.
grain, effects on quartz growth, (1) 22*f*.
guncrete, on refractories, (8) 195*f*.
high-temp., for metals, P (2) 31*i*.
inorganic, composition, P (9) 216*a*.
resists, P (6) 139*g*.
thermal control, P (3) 54*e*.
insulating on Si, P (5) 112*h*.
La boride, for field emission cathode, P (4) 87*j*.

Coatings *(continued)*
lehring-sensitive phosphor on lamp, P (10) 245*c*.
Li silicate glare-reducing, on glass, P (4) 82*f*.
lubricant, removal from extruded products, P (11) 277*e*.
for metal coil, use of pigments, (11) 279*h*.
metal oxide, on flat glass, P (10) 245*a*.
on glass, P (6) 133*f*.
on refractory substrates, P (8) 193*c*.
on substrates, P (6) 138*j*.
metal powder, on molds and plungers, (7) 158*i*.
metal-silicate, electrodepositing, P (4) 80*b*.
metal vapor, apparatus, P (9) 228*j*.
metalizing, Al_2O_3 at room temp., (9) 224*j*.
BeO at low temps., P (6) 139*c*.
ceramic bodies, P (2) 33*f*; P (3) 66*b*; P (5) 113*d*.
ceramic, composition, P (8) 189*b*.
ceramic member, P (3) 66*b*.
ceramic parts, P (9) 226*b*.
ceramics, P (1) 12*j*.
chamber viewing system, P (3) 69*b*.
decal, of substrates, P (2) 39*j*.
dual-etched refractory, P (8) 200*j*.
Au, of refractory metals, P (9) 225*a*.
material, P (2) 40*j*.
Mo, sintering, (1) 11*j*.
Pt thin-film method, P (8) 202*c*.
semiconductor devices, P (5) 113*j*.
semiconductors, P (7) 169*c*.
solder bump system, P (8) 202*c*.
substrates, P (3) 66*c*.
metallic, effect on fatigue of steels, (7) 157*h*.
on glass, P (9) 219*i*.
materials, P (7) 158*a*.
metals or insulating substrates, P (9) 226*d*.
on metals, USSR, B (4) 100*h*.
of Mo sulfide, by plasma jet, P (8) 197*a*.
Ni or Co wear-resistant, P (10) 248*d*.
nonglare, for TV tubes, P (10) 245*g*.
for nonmetallics for space use, (2) 38*d*.
organic, electrodeposition, (4) 79*j*.
oxidation-resistant, for graphite electrodes, P (7) 164*d*.
oxide, flame-deposited, P (5) 105*c*.
particulate materials, P (7) 170*d*.
phosphor, for lamp, P (4) 82*e*.
plating, metal, vapor phase, P (6) 135*i*.
for Pt-group metals, P (2) 31*i*.
plurality, to substrate, P (6) 137*f*.
K silicate-Zn, P (3) 54*g*.
protective, on ceramic bodies, (5) 110*j*.
protective, testing and selection, (1) 18*b*.
reflective, flame spraying Al_2O_3 for, P (2) 31*h*.
refractory, for electrical steels, P (9) 222*c*.
screens, P (5) 105*f*.
Se, amorphous, P (7) 170*e*.
silicate, on Al reflector, P (3) 54*h*.
silicide refractory, vapor phase deposition, P (8) 197*b*.
SiC, stoichiometric, P (3) 61*c*.
Si oxide, in electric discharge, P (7) 169*h*.
for strengthening vitreous bodies, P (4) 85*j*.
substrates, by vapor deposition, P (1) 13*b*.
surface, compositions, P (8) 189*c*.
temp.-resistant, P (8) 189*c*.
thickness, controlling, P (9) 226*a*.
thin films. See *Films, thin*.
TiC hard, P (5) 109*j*.
TiC, on substrates, P (11) 272*f*.
TiO_2 on glass bottles, (7) 160*j*.
W-W oxide, vapor deposition, P (9) 226*i*.
vacuum deposition, P (3) 68*c*.
vapor, means for, P (8) 193*h*.
vitreous, electrodeposition on substrate, P (10) 242*f*.
for H_2O-containing cement articles, P (10) 242*d*.
Cobalt, arsenide, structural and magnetic properties, (11) 282*g*.
Co^{2+}, combined with Ti^{4+} in rutile, (4) 97*j*.
effect on GdIG, (6) 147*b*.
effect on $Y_3Fe_5O_{12}$, (11) 281*f*.
ion-exchange equilibria of zeolite with, (1) 23*e*.
in TiO_2, ESR, (4) 96*b*.
^{57}Co implanted in diamond, (5) 122*c*.
$CoSb_2$-type crystal structure, compounds, (6) 151*f*.
$Co_{1-x}Ni_xSb_2$, phase, (5) 118*i*.
$CoTe_2$, crystal structure, (5) 118*h*.
fine particles, magnetic properties, (11) 274*e*.
monoselenide, epitaxial growth in, (7) 177*c*.
in optical glass, (3) 57*g*.
-ous oxide, crystal, spin flopping in, (4) 98*h*.
crystals, (7) 179*e*.
crystals, cation self-diffusion in, (6) 149*c*.
crystals, electrical conductivity, (6) 146*i*.
magnetic symmetry and antiferromagnetic resonance in, (5) 121*e*.
Néel temp., (5) 120*d*.
properties, (6) 151*g*.
oxides, reaction with kaolinite, (9) 238*d*.
-rare earth intermetallic product, P (11) 274*h*.
systems. See *Systems*.
wear-resistant coatings, P (10) 248*d*.
Coesite, -quartz transition, reexamination, (1) 18*e*.
quartz-, transition, shear effect, (7) 177*i*.
Coke. See also *Fuels*.
effect on $BaCoO_3$ and TiO_2 reaction, (6) 146*g*.
Coke ovens. See *Refractories*.
Colloids, aerosols, SiO_2, fractionation, P (6) 144*a*.
effects on KCl thermal conductivity, (5) 120*e*.
gelling and desiccation, in glass preparation; (1) 3*e*.

Colloids *(continued)*
gelling of vermiculite, (9) 235*f*.
gels, aluminosilicate, mullitization, (8) 195*a*.
Al hydroxide, crystallization in, (2) 47*h*.
Al_2O_3, and boehmite, hot-pressing, (1) 22*e*.
hydro-, in cement, (2) 31*f*.
SiO_2, P (6) 144*d,e*; P (7) 175*d,e*.
SiO_2, formed, P (1) 20*g*.
SiO_2, Fe^{3+} adsorption on, (4) 97*g*.
SiO_2, in MgO insulating composition, P (11) 272*f*.
SiO_2, microspheroidal desiccant, P (1) 20*h*.
hydrogel, alkali aluminosilicate, stability, (11) 282*g*.
sols, actinide oxide, P (4) 91*h*.
crystalline, of UO_2, P (4) 91*j*.
metal oxide, P (10) 257*h*.
organo-, silicic acid, P (8) 196*f*.
organo-, SiO_2, P (8) 196*i*.
oxide gel microspheres from, P (3) 69*d*.
SiO_2 P (1) 20*j*; P (10) 257*i*; P (11) 280*a*.
SiO_2, Al_2O_3 coated, P (3) 71*h*.
SiO_2, by electrolysis, P (7) 176*b*.
SiO_2, high surface area, P (4) 84*h*.
SiO_2, stabilized, P (7) 175*b*.
SiO_2, stabilizing, P (6) 144*f*.
of synthetic silicate, P (7) 175*b*.
Color. See also *Pigments; Stains*.
amber, effect of glass composition, (11) 268*i*.
of amethyst, (11) 280*f*.
centers, in laser glass, (5) 106*f*.
in MgO·Ni, (3) 72*f*.
in rf sputtered SiO_2 films, (4) 86*g*.
and color tolerances in artificial light or sunlight, P (7) 174*c*.
and color tolerances, determination, P (10) 256*b*.
colorant, adding to molten glass, P (4) 82*i*.
control in appliance industry, (19) 242*g*.
difference and tolerance evaluation, (7) 182*d*.
discolorants, separation from clay, P (8) 207*g*.
in glass, change in continuous furnaces, (3) 55*c*.
of high-melting compounds, (10) 258*i*.
matching, apparatus for, P (11) 278*f*.
measurement. See *Colorimetry*.
of portland cement clinker, (9) 214*f*.
tests, on ceramic tiles, (4) 85*d*.
zircon, Pr-doped, (1) 2*j*.
Coloration, additive, of KCl, (9) 238*e*.
additive, of SrO, (5) 118*e*.
nonlinear effects in $SrTiO_3$, (6) 150*c*.
Coloring materials. See *Decoration; Pigments; Stains*.
Columbium. See *Niobium*.
Combustion. See also *Burners; Firing; Flames; Furnaces; Heat; Kilns*.
apparatus, P (10) 256*d*.
combustible impurities, removal from air or gas current, P (7) 174*f*.
fuel, indicator device, P (7) 174*j*.
of gas or vapor mixture, apparatus, P (7) 174*i*.
of gases, P (8) 206*e*.
of liquid fuel, P (7) 174*g*.
method for determination of S, (7) 173*h*.
separation method in glass analysis, (8) 204*i*.
Comminution. See *Crushing*.
Compaction. See also *Pressing*.
apparatus, high-temp., high-pressure, (3) 68*j*.
compactibility of disperse structures, (2) 48*i*.
of concrete by vibration, (6) 128*b*.
of granular material, P (7) 172*b*.
high-pressure apparatus, P (2) 29*i*.
of particulate matter, P (2) 48*j*.
of powder, die and punch assembly for, P (9) 229*j*.
in powder pressing, (10) 254*e*.
properties, of calcined Al_2O_3, (1) 11*g*.
Compacts, Al_2O_3, very porous, grain growth in, (4) 96*i*.
axially symmetric, pressing, (10) 247*c*.
porosity and strength, (10) 247*a*.
Composites, ablative, char depth reduction in, P (7) 164*c*.
in aerospace application, (2) 36*b*.
Al_2O_3, impact strength, (6) 131*b*.
arcuate shaped, of refractory tapes, P (6) 135*c*.
articles, with bonded fibrous glass, P (5) 107*d*.
behavior under intense impact, (7) 179*h*.
bodies, P (7) 164*c*.
bodies, treatment, P (7) 164*g*.
B-reinforced, P (7) 164*b*.
with BN, high-purity hot-pressed, P (10) 247*f*.
B polyimide, (11) 271*f*.
capstan assembly, P (3) 62*a*.
C and, B (7) 182*g*.
C-C, (3) 54*f*.
C/C, processing, (11) 271*f*.
C-fiber filled materials, P (10) 247*e*.
C fiber polyester, strength and fracture, (7) 163*h*.
with C fiber reinforcement, P (10) 247*g*.
C structure, P (5) 109*f*.
ceramic-organic material, P (9) 223*b*.
ceramic package breakaway notch, P (1) 10*c*.
ceramic-rubber, for ball mill lining, P (1) 10*c*.
design, for thermal expansion control, (1) 2*k*.
enamel-metal, thermal conductivity, (11) 267*d*.
fabric-concrete, nylon spun bonded, P (5) 104*i*.
fiber. See also *Glass, reinforced*.
P (7) 164*h*.
properties, B (10) 264*f*.
reinforced, P (1) 4*b*; P (9) 222*i*.
reinforcement, (4) 83*j*.
fibrous carbonaceous, P (9) 222*c*.
of glass, P (10) 244*b*.

Composites *(continued)*
glass-ceramic, metal part sealed in, P (9) 226*g*.
glass-fiber-reinforced, P (9) 219*c*.
graphite-metal, anisotropic, P (9) 222*e*.
hard metal product, P (5) 109*f*.
heat-resistant high-strength, P (11) 272*c*.
insulating layer, P (6) 138*e*.
Fe-Cr carbide, sintering, (10) 259*f*.
with layer of HfO_2, ZrO_2, and TiO_2, P (8) 202*d*.
layered, Si_3N_4 and SiO_2, etching, P (1) 14*e*.
lightweight transparent, P (4) 86*b*.
material, P (8) 196*g,h*.
Al-Mg-Al_2O_3-MgO, P (3) 68*i*.
elastic moduli, (6) 148*j*.
with flake reinforcement, P (8) 196*g*.
metal/carbide-oxide, P (10) 247*j*.
metal-ceramic, forming, P (1) 12*b*.
metal-matrix, low cost, (3) 54*g*.
multiple-layer structures, P (6) 138*f*.
particulate, mechanical properties, (8) 187*e*.
polyimide, glass cloth in, P (1) 5*d*.
polymer-cement and polymer-mortar, (5) 104*e*.
polyurethane, C-fiber-reinforced, P (9) 222*b*.
porous and filled, micromechanics analysis, (1) 17*j*.
pyrolyzed, carbiding, P (6) 131*d*.
refractory heat-insulating products, P (7) 164*f*.
resin-ceramic, organic, P (1) 10*f*.
shell with ceramic base, P (5) 111*c*.
siliceous fiber corrosion-inhibiting, P (8) 193*f*.
Na borosilicate glass-Al_2O_3, fracture energy and strength, (1) 3*d*.
structural, reinforcements for, (10) 246*h*.
structure of ZnO on sapphire, P (9) 225*a*.
structures, C cloth for, P (5) 110*b*.
thin films, deposition, P (8) 200*f*.
Sn-C fiber, P (3) 61*f*.
TiO_2-ZrO_2 and TiO_2-Al_2O_3, densification, (11) 282*i*.
transition metal-Au thin-film, P (10) 253*g*.
of IIB-VIA compounds, P (9) 225*a*.
of IIB-VIA binary film compounds, P (8) 200*g*.
UO_2-W, microscopy and diffraction, (1) 16*d*.
use, care in, (2) 31*h*.
use of heat-resisting fibers in, (10) 246*g*.
of V alloys and Fe or Ni alloys, P (10) 253*j*.
wear-resistant material, P (10) 242*i*.
Compounds, (ABX_3)-$(AX)_n$, high-pressure synthesis, (8) 209*f*.
with $CoSb_2$-type crystal structure, (6) 151*f*.
high-melting, electrical resistance and color, (10) 258*i*.
high-melting, emission coeff., (3) 73*a*.
nonstoichiometric, diffusion coeff., (9) 233*d*.
with pyrite-, marcasite-, and arsenopyrite-type structures, back-bonding in, (3) 75*d*.
IIB-VIA, growth on substrates, P (9) 225*a*.
III-V semiconducting, properties, B (1) 27*f*.
III-V, solution epitaxial growth, P (9) 227*b*.
Compressibility, diamond and graphite, (6) 149*a*.
in Hf and Zr titanates, (9) 239*c*.
of halloysite, hectorite, and illite clays, (8) 210*f*.
Compression, and deaeration of powders, P (4) 92*h*.
Computers, control of batch processes, (11) 276*h*.
controlled growth of crystals, (3) 62*f*.
for determining thermal shock resistance of refractories, (8) 204*d*.
digital, use in cement factories, (5) 102*d*.
in glass processing, (5) 106*b*.
in plant and design depts., (11) 276*f*.
in preparing raw materials for cement kiln, (4) 79*h*.
simulation of NMR spectra of glasses, (4) 81*b*.
techniques in physical metallurgy, B (2) 50*h*.
use in porcelain industry, (11) 276*j*.
Concretes. See also *Cement; Masonry; Mortars; Pozzolans*.
P (7) 157*d*.
additive for, P (8) 188*c*.
adiabatic temp. rise, relation to heat of hydration of cement, (9) 215*c*.
adjuvant composition for, P (8) 188*c*.
admixture, impact-resistant, P (6) 130*f*.
aggregate, comminution of clay lumps in, (7) 156*i*.
Al_2O_3 cement, effect of fly ash, (6) 129*h*.
Al_2O_3 cement, use in hot season, (6) 128*g*.
aluminosilicate, properties, (8) 187*j*.
artificial lightweight aggregate, (6) 130*b*; (10) 242*b*.
beams, bar arrangement in, (6) 129*f*.
composite prestressed, (6) 127*j*.
crack width control in, (6) 129*b*.
effects of reinforcements, (6) 128*f*.
reinforced, deformation, (6) 128*h*.
shear strength, (10) 241*h*.
2-span, deflections, (6) 128*g*.
block, P (8) 194*e*.
boxed column, compressive strength, (6) 128*c*.
bridge, seaside, deterioration, (6) 128*i*.
cellular, P (3) 54*e*.
microstructure, (4) 79*d*.
porosity-strength, (5) 104*d*.
cement analysis, instrument for, P (3) 54*d*.
chemistry, B (10) 263*a*.
chloride ion penetration, (11) 266*i*.
compaction by vibration, (6) 128*b*.
compressive strength, (6) 128*b*.
creep rupture, (6) 128*f*.
crushed stone, properties, (6) 130*f*.
crushed stone, workability, (6) 128*h*.
deformation, critical points, (6) 128*g*.
deformation and failure, (4) 78*i*; (5) 102*j*.

Concretes *(continued)*
dry mix, strength and mix proportion, (6) 129*e*.
end condition, effect on stress distribution, (6) 128*b*.
fiber reinforced, fracture, (10) 241*g*.
fibrous glass fabric reinforcement, (9) 213*j*.
with fly ash, compressive strength, (6) 128*b*.
fresh, H_2O content and unit weight, (7) 157*d*.
frost resistance, (6) 130*f*.
glazing, P (5) 104*g*.
green, frost damage, (6) 129*j*.
hardened for 40 years, structure, (8) 187*h*.
hardening, accelerated with ir lamps, (6) 127*j*.
high-Al_2O_3 cement, strength, (10) 242*a*.
high-strength, P (10) 242*e*.
properties, (6) 130*b*.
shrinkage and creep, (6) 130*c*.
impregnated, radiation, (4) 79*b*.
industry, (2) 31*b*.
inherent stresses in, evaluation, (6) 128*h*.
lightweight, abrasion resistance, (6) 127*i*.
aggregate, durability, (6) 128*a*.
flexural strength, (6) 128*i*.
frost resistance, (6) 129*d*.
hot water pretreatment, (6) 130*c*.
material, P (8) 188*e*.
shear strength, (6) 129*f*.
low-density, P (10) 242*d*.
mfg., problems, (6) 129*j*.
mechanical properties, (6) 129*c*.
microcracks, (6) 129*d*.
piles, jointed, deformation, (6) 128*g*.
plasticizing additive for, P (11) 267*b*.
Poisson's ratio, (5) 102*j*.
portland cement, bond strength, (10) 241*g*.
precast members, joints, (6) 129*f*.
properties, (1) 2*g*; (6) 128*i*.
effect of cement grinding aid, (6) 128*e*.
effect of gypsum, (6) 129*h*.
effect of H_2O-reducing admixture, (6) 129*i*.
improved with aggregate, P (7) 157*b*.
ready mixed, based on white cement, (10) 242*c*.
refractory, properties, (8) 195*g*.
refractory, slag portland cement as binder for, (8) 187*f*.
reinforced, columns, ductility, (6) 128*a*.
crack control in, (6) 128*f*.
cracking moment, (6) 128*c*.
flexural member, (6) 129*e*.
Fe corrosion in, (4) 78*h*.
slabs, strengthening, (6) 130*e*.
and reinforcement, bond under load, (6) 129*e*.
seat, with tile covering, P (5) 111*g*.
setting and hardening, (6) 128*d*.
shielding, neutron attenuation in, (5) 114*j*.
shrinkage, determination, (5) 102*e*.
splitting strength, (10) 241*h*.
of stable aluminous cements, P (6) 130*f*.
standards and testing, (4) 78*g*.
steam-cured, effect of admixtures, (6) 128*d*.
and steel studs, deformation, (6) 128*a*.
strength, drying shrinkage effect, (6) 128*j*.
and elastic modulus, (5) 103*a*.
fundamentals, (4) 78*c*.
increased with alunite, (8) 185*h*.
variation, (6) 130*b*.
stress and strength law for, (8) 187*g*.
structural expanded clay, strength, (9) 215*b*.
structures, inelastic behavior, (6) 129*g*.
superdry mix, (6) 130*f*.
from super-high early-strength cement, properties, (9) 214*d*.
tests in Tokyo, 1968, (6) 130*h*.
thermodynamics of adsorption, (6) 130*a*.
using expansive agent, (10) 242*c*.
vacuum, properties, (6) 130*a*.
vacuum, test, (6) 130*g*.
wall, comparison with brick, (9) 220*e*.
H_2O diffusion in at 30°C, (5) 102*h*.
white portland cement, properties, (10) 241*i*.
zero slump, study, (6) 127*j*.
Condensers. See *Capacitors*.
Conductance, surface, of Ge with O, (6) 149*j*.
Conductivity, electrical, and(or) **Conduction, electric,** of Al_2O_3-Cr_2O_3 system, (5) 125*e*.
in amorphous solids, (6) 148*f*.
of $CaCl_2$-NaCl and $ZnCl_2$-NaCl melts, (5) 120*g*.
of cement kiln samples, (8) 188*f*.
in ceramic materials, (3) 62*e*; P (11) 275*b*.
of cermets and multiphase materials, (8) 199*a*.
of chalcogenide alloy films, (6) 136*h*.
of CoO and NiO crystals, O effect, (6) 146*i*.
of Cu_2O, pure and impure, (4) 96*h*.
of dielectrics, during aging, (8) 199*e*.
dc, in hematite at high temps., (5) 119*e*.
electro-, of alkali glasses, (7) 160*i*.
electro-, of slurry, changing, (8) 187*f*.
-electron interaction in CdO, NMR, (5) 122*h*.
of EuO, (9) 239*a*.
in GeTe films, (6) 136*g*.
of glasses, (3) 57*c*; B (6) 153*i*.
alkali silicate, (3) 55*e*.
chalcogenide, measurements, (3) 56*e*.
at high fields, (11) 268*c*.
Myller's theory, (8) 190*e*.
in system Sb-Ge-Se, (9) 217*e*.
W-V-phosphate, (8) 190*d*.
V- and Fe-containing, (3) 55*f*.
glaze, P (1) 12*j*.
of graphite or C articles, P (2) 37*c*.
heatable rail and support assembly, P (8) 106*c*.
high, materials, P (8) 201*g*.
hopping, of chalcogenide films, (6) 136*g*.
in insulators, Poole-Frenkel effect, (5) 122*e*.
of I_2+Te solutions, (6) 147*e*.
of PbO, (5) 119*a*.
Conductivity, electrical *(continued)*
of liquids in system CaF_2+CaO+Al_2O_3, (6) 147*f*.
of MCl+$ZnCl_2$ systems, (6) 147*d*.
of MgO, effect of B_2O_3, (8) 208*h*.
for $HgCl_2$, $HgBr_2$, and HgI_2, (5) 122*g*.
in metal oxides, B (10) 263*j*.
negative differential, in thin films, (7) 160*c*.
in noncrystalline systems, (6) 145*c*.
in olivine and spinel, (10) 258*j*.
in oxide systems $M'O_2$-M''_2O_3, (11) 281*g*.
phenomena in Fe oxide, (5) 118*j*.
photo-, material, CdS-chalcogen compound, P (10) 249*i*.
in NiO films, (6) 150*h*.
radiation in ovonic switches, (6) 137*a*.
polaron, in disordered 3*d* oxides, (6) 151*d*.
polaronic hopping, in V phosphate glasses, (5) 106*g*.
Poole-Frenkel, in solids, (6) 151*d*.
premelting, of crystalline NaCl, (5) 122*f*.
refractory bodies, P (1) 12*j*.
semi-, in $BaBiO_3$, (4) 98*d*.
in semiconductors, disordered, (6) 147*e*.
in semiconductors in system As-Se-Te, (3) 62*e*.
sheathed, hermetic seal for, P (2) 35*a*.
of system PbO-B_2O_3-Fe_2O_3, (6) 147*f*.
tensor, in magnetic semiconductors, (6) 145*c*.
of ThO_2, effect of frequency, (7) 177*i*.
of $(ThO_2)_{0.75}$-$(CeO_2)_{0.25}$ at high temp., (1) 11*c*.
of ThO_2-YO_2 solid solutions, (9) 236*h*.
of SnO_2 crystals, (3) 72*i*.
in ZrO_2, (9) 235*a*.
of ZrO_2-CeO_2, hot-pressed, (3) 72*e*.
Conductivity, electronic and(or) **ionic,** in fluorite oxides, statistics, (9) 238*e*.
in semiconductors, (6) 147*c*.
in NaCl, impure, (9) 236*i*.
in solids, noncrystalline, (6) 147*c*.
Conductivity, thermal. See also *Heat*.
across metal-diamond interfaces, (4) 77*g*.
of alkali halide crystals, (6) 152*b*.
of aluminosilicate refractories, (8) 196*e*.
of AlN, (3) 75*i*.
of BeO single crystals, (7) 181*d*.
of CdS, pure and doped, (5) 125*a*.
of CaF_2 in magnetic fields, (5) 125*b*.
of ceramic fuels, (7) 171*b*.
computing from experimental data, (3) 69*h*.
of crystalline hard bodies, P (2) 45*a*.
of enamel-metal composites, (11) 267*d*.
of magnetite and hematite, (5) 125*b*.
of KCl, effects of colloids, (5) 120*e*.
of refractories, (1) 8*j*.
laboratory tests, (7) 172*j*.
rapid determination, (1) 8*e*.
of SiC, (10) 261*c*.
of $SrTiO_3$, $KTaO_3$, and $BaTiO_3$, (3) 75*j*.
temp. control with, (1) 18*b*.
test for refractories, (2) 44*g*.
under vacuum at high temps., measuring, (5) 109*b*.
of $(U,Pu)O_2$ solid solutions, (7) 171*g*.
of U_3Si, swelling effect, (6) 140*j*.
Conductors, electrical. See also *Semiconductors; Superconductors*.
P (4) 90*c*.
elements, P (10) 250*d*.
light-wave, exciting, P (2) 42*d*.
metal, connecting metal contact to, P (9) 226*e*.
multilevel, insulating, P (8) 201*c*.
pattern, glass-covered Au, P (10) 253*g*.
pinhole shorts in, eliminating, P (6) 138*a*.
sputter etch removal rates, (10) 249*a*.
super ionic, ionic transport in, (10) 259*g*.
super-, TaS_2 and NbS_2, (4) 97*h*.
thick-film pastes, (11) 273*f*.
thin-film circuit, testing, (3) 62*c*.
Conferences, glass, 9th international, B (7) 184*c*.
Contacts, P (6) 139*e*.
arc and spark extinguishing, P (3) 64*f*.
bonding to SiC, P (7) 169*d*.
electrical, formation on diamonds, (4) 86*h*.
material, P (3) 64*g*.
materials, Ag-CdO, P (9) 228*a*.
metal-ceramic reinforced, (10) 249*e*.
on semiconductor device, P (5) 113*h*.
for SiC members, P (8) 200*j*.
structure, P (9) 225*e*.
joining to semiconductor material, P (9) 226*j*.
lead, for semiconductor, P (3) 64*e*.
low current electrical, P (10) 251*c*.
metal, connecting to metal conductors, P (9) 226*e*.
metal, to high-speed transistors, P (10) 252*a*.
ohmic, P (10) 251*c*.
for GaAs, P (6) 139*i*.
to high-resistivity Si, P (5) 113*d*.
to *n*-type SiC, P (2) 41*h*.
for semiconductor devices, P (5) 113*e*; P (7) 169*g*; P (9) 227*c*.
in semiconductor layer, P (9) 226*h*.
to semiconductors, P (1) 13*g*; P (11) 275*g*.
system, P (6) 139*i*.
to ZnS devices, P (2) 41*i*.
polycrystalline Si, P (7) 169*j*.
sealed applications, reed material for, P (9) 227*b*.
semiconductor, P (5) 113*f*.
to semiconductor body, P (4) 90*e*.
to semiconductor devices, P (4) 89*a*.
strip, 3-layer metallic, P (4) 91*d*.
system, for ceramic-like material, P (10) 250*e*.
system for semiconductor devices, P (4) 87*b*.
thin film resistor, P (6) 140*b*.
Ti-W-Au, for semiconductors, P (1) 15*b*.
Y electrical, to SiC, P (4) 91*c*.
Containers. See *Glass*.
Controls. See also *Instrumentation; Temperature*.
for feeding apparatus. *See Feeding apparatus.*
process, chemical composition determination applied to, B (5) 126*c*.
production, in small or medium industry, (7) 172*f*.
system, for muffle burners, P (6) 143*d*.
systems, for electric furnace, P (4) 81*c*.
Conveyors. See also *Materials handling*.
P (4) 83*h*.
for free-flowing and lump materials, P (3) 69*c*.
furnace, P (2) 44*j*.
for magnetic powder, P (4) 92*e*.
for roofing tiles, P (1) 6*c*.
vibratory, P (11) 277*h*.
counterflow, P (1) 16*g*.
or reciprocatory, P (4) 92*i*.
Coolers, fluidized-bed, P (10) 256*f*.
for glass sheet drawing machine, P (4) 81*c*.
for rotary kiln, P (6) 143*d*.
Cooling, air, apparatus, P (8) 206*f*.
artificial, of kiln shell, (8) 185*h*.
cement clinker, P (9) 215*g*.
clinker, effect on cement strength, (4) 78*e*.
container mold, (8) 190*c*.
device for glassware molds, P (7) 162*c*.
falling film, of molten glass, P (8) 192*h*.
fired or sintered material, P (9) 232*d*.
gas streams, containing TiO_2, P (1) 20*c*.
glass, (3) 57*c*.
bulb blow molding apparatus, P (4) 82*a*.
fiber, means made of Pd, P (6) 132*i*.
granular materials in beds, (7) 175*a*.
grinding wheels, P (9) 213*e*.
and holding specimen in electron microscope, P (10) 255*h*.
hot gas mixtures of TiO_2, P (11) 279*i*.
hot sinter, (9) 215*g*.
intense, absorbs heat of supersemiconductors, (9) 224*g*.
particulate solid material, P (10) 256*f*.
pre-, apparatus for ultrasonic inspection, P (8) 206*a*.
product of rotary furnaces, P (4) 93*j*.
reactor core fragments in reactor, P (10) 253*j*.
splat, preparation of thin glass films, (11) 278*h*.
H_2O treatment, (9) 229*e*.
Copper, chloride, crystal, flux growth of, (2) 47*i*.
Cu^+, diffusing into glass, (3) 56*j*.
Cu^{2+} in kaolinite, EPR, (6) 147*j*.
$CuFe_2O_4$, eutectoid decomposition, (1) 23*g*.
CuS, conversion to $Cu_{1.8}S$, kinetics, (6) 149*d*.
$CuSO_4$·$5H_2O$, dehydration, (1) 21*f*.
$CuTeO_3$ and $CuTe_2O_5$, crystal structures, (1) 21*f*.
diffusion and solubility in CdS crystals, (5) 119*e*.
fluoride, high-purity, P (1) 20*f*.
layer, plating on circuit board, P (4) 89*g*.
liquid, TaC wetting by, (4) 80*a*.
metaniobate and metatantalate, (8) 209*f*.
in optical glass, (3) 57*g*.
-ous oxide, crystals, transitions in, (6) 150*d*.
electrical conductivity, (4) 96*h*.
luminescence, (6) 151*d*.
recrystallization and grain growth, (4) 97*j*.
single crystals, (7) 177*i*; (9) 224*a*.
oxide, P (6) 144*d*.
plating mirrors, (8) 190*e*.
powder, sintering electrolytically, (11) 276*j*.
sulfate and oxysulfate, enthalpies and entropies, (7) 177*b*.
sulfide, black stones, in green glass, (3) 56*j*.
sulfide, oxidation, kinetics, (6) 149*e*.
surface energy, bubble measurement, (5) 119*h*.
systems. See *Systems*.
Cordierite, formation in ceramics, (2) 47*j*.
formation from clinochlore and kaolinite, (8) 197*i*.
self-glazing, (8) 198*h*.
Cores, accurate, P (10) 248*a*.
blocks for nuclear reactors, P (10) 254*b*.
bonded structure, with glass-coated steel sheets, P (9) 215*j*.
casting, gasifiable, P (7) 164*d*.
curing by induction heating, P (5) 109*h*.
ferrite, plug-in devices, P (7) 169*d*.
ferrite memory, strength, (7) 167*g*.
ferromagnetic storage, P (5) 112*c*.
glass, hard alloys used in, (5) 106*g*.
magnet, from Mn-Zn-ferrous ferrite, P (6) 138*f*.
magnetic particle, P (1) 14*e*; P (9) 225*j*.
Mn-Zn ferrite, P (10) 251*e*.
memory, ferrite, strength, (7) 168*d*.
and mold materials, ceramic, P (3) 61*b*.
plug for nuclear reactor, P (9) 228*g*.
reactor, for nuclear reactor, P (11) 276*e*.
in shell mold, supporting, P (8) 196*d*.
for SiC furnace, P (6) 135*f*.
of tubular nuclear fuel element, separating, P (10) 254*c*.
Corrosion, acid, by kiln exhaust gases, (1) 19*a*.
of asbestos fibers, (6) 128*e*.
of basic bricks by alkaline vapors, (3) 60*h*.
of cement-lined water mains, (7) 156*e*.
chemical and mechanical, of enamel, (11) 267*c*.
of electrode holder, effect of Mo, (8) 190*c*.
of electrodes and refractories in glass tanks, (8) 191*g*.
of enameled surfaces, (6) 130*i*.
of fibers in asbestos cement, (11) 266*h*.
in glass tank furnaces, (2) 33*f*.
of glass windows by demineralized H_2O, (11) 268*f*.
of Fe in reinforced concrete, (4) 78*h*.

Corrosion *(continued)*
of mold surface in slip-casting, (7) 165*c*.
of mullite and zircon, (5) 109*f*.
of refractories, bauxite-based, (1) 6*j*.
relation to glass composition, (10) 243*i*.
resistance. of mullite crucibles, (5) 109*b*.
of polymer-cement composites, (5) 104*e*.
of portland cements, (8) 186*i*.
of refractories, (8) 195*a*.
-resistant materials, (2) 35*i*.
of SiO_2 by Na_2CO_3 and carbonate-rich melts, (7) 158*j*; (11) 268*g*.
by slag of MgO-CaO refractories, (7) 163*h*.
stress, in E glass filaments, (9) 217*h*.
Corundum. See also *Aluminum, oxide; Refractories.*
ceramics, thermal stability, (9) 221*j*.
effect on phase composition in system Al_2O_3-P_2O_5-H_2O, (9) 234*g*.
electric field gradient in, (5) 120*d*.
gemstones, asteriated synthetic, P (7) 175*j*.
rate of Ti^{3+} exolution from, (3) 74*j*.
structural changes during production, (1) 8*b*.
structural isotypes, (1) 25*j*.
Coulometry, device, P (1) 12*e*.
Coupling, coupler, directional, strip-type, P (8) 202*f*.
filamentary, in GaAs lasers, (5) 111*j*.
transducer to transmitter and receiver (U), P (2) 40*a*.
Cracking, of concrete, effect of reinforcement, (6) 128*c*.
dunting, vitreous china refire, (4) 85*f*.
surface, of opacified glasses, (7) 160*h*.
Cracks, analysis, fracture surface energies from, (10) 259*h*.
on chalcogenide glass surfaces, (3) 55*i*.
control in concrete, reinforced, (6) 128*f*.
control in concrete beams, (6) 129*b*.
-dislocation effects during cleavage, (4) 95*d*.
fracture, lattice trapping, (5) 121*h*.
in glass-metal seals, (10) 243*a*.
micro-, of concrete, (6) 129*d*.
propagation, in Al_2O_3, (6) 152*a*.
propagation in brittle materials, (11) 281*g*.
Crazing. See *Glazes.*
Creep, of compacts of colloidal boehmite, (11) 280*j*.
compressive, high-temp. apparatus, (1) 17*i*.
of polycrystalline Al_2O_3, (11) 280*h*.
of polycrystalline MgO, (11) 280*g*.
of rutile at high temps., (2) 47*j*.
of concrete, high-strength, (6) 130*c*.
of concrete, superdry mix, (6) 130*g*.
diffusion, in polycrystalline solids, (6) 148*h*.
of Ge and LiF single crystals, (6) 147*e*.
high-temp., of basic refractories, (11) 271*i*.
in LiF single crystals, (6) 148*c*.
of magnesite bricks, (1) 7*f*.
measurements, UO_2 helices for, (3) 68*d*.
of Ni-Zn ferrites, (5) 111*j*; (6) 146*d*.
-resistant, substructure, in rutile, (2) 49*g*.
rupture, of concrete and mortar, (6) 128*f*.
of SiO_2 dispersions in ice, (6) 145*f*.
of $SrZrO_3$, high-temp., (4) 96*j*.
transient, in MgO, (10) 261*e*.
transition, for cement paste, (7) 157*f*.
in UO_2, stoichiometric, (5) 114*g*.
of ZrO_2 storage heater refractories, (3) 60*d*.
Cristobalite. See *Silicon, oxide.*
Crucibles. See *Refractories.*
Crushing. See also *Crushing apparatus; Mills.*
clay lumps in concrete aggregates, (7) 156*i*.
energy, determining from grain structure, (2) 45*j*.
molten slag, P (2) 35*b*.
Crushing apparatus. See also *Mills.*
P (2) 44*d*. 46*g*.
cone, feed distributor, P (1) 20*a*.
design and application, (9) 232*h*.
dry fine, P (2) 44*b*.
for fine-grained solid substances, P (11) 277*c*.
gyratory, P (2) 46*g*.
crusher tool for, P (1) 20*c*.
hydraulic control for, P (1) 20*d*.
hammer, P (3) 71*j*.
impact, P (7) 175*c*.
nonclogging, P (2) 46*a*.
rotary, P (2) 46*g*.
for rocks, using sonic wave action, P (11) 279*f*.
roll, rotor for, P (6) 144*e*.
upper liner for, P (6) 144*h*.
vibratory jaw, P (8) 207*i*.
Cryogenics, insulating materials, standards, (4) 84*b*.
sensing device, P (6) 140*j*.
Cryolite, P (3) 71*i*.
-Al_2O_3, Al_2O_3 diffusion coeff., (7) 176*f*.
-Al_2O_3 mixtures, viscosity, (7) 182*a*.
-based mixtures, density, (6) 146*h*.
high purity, P (9) 232*i*.
pure synthetic, P (10) 257*g*.
synthetic, high-quality, P (8) 207*e*.
from H_3PO_4, P (10) 257*g*.
improving quality, P (2) 46*a*.
Cryoscopy, of germanates of trivalent elements, (6) 145*g*.
of V_2O_5 reactions with Sb_2O_3 and Sb_2O_4, (6) 145*b*.
Crystal chemistry, and crystallography, introduction, B (1) 26*j*.
of Eu_2TiO_4 and $Eu_2Ti_2O_7$, (9) 234*e*.
of Li_3PO_4-type compounds, (8) 210*f*.
of O compounds of transition metals, (5) 119*a*.
of phases in systems V-W-O and Li-V-W-O, (6) 145*h*.
of system Mg-Ti-Fe-O, (5) 119*b*.
of titanian and zirconian garnet, (4) 95*e*.
Crystalline materials, bodies, growing, P (7) 168*h*.
ceramics, precipitation in, (7) 179*e*.
compound, P (4) 89*d*.
compounds, Cs borate, NMR, (7) 160*g*.
fragmented, P (6) 127*f*.
hard bodies, thermal conductivity, P (2) 45*a*.
ion channeling in, prevention, P (7) 169*c*.
mass, solution, P (11) 277*g*.
mono-, precision engineering, B (9) 240*b*.
mono-, rod, crucible-free zone melting, P (3) 66*d*.
producing, P (2) 44*a*.
rod, crucible-free zone melting, P (3) 64*b*; P (4) 92*b*; P (6) 138*a*; P (11) 274*e*.
device for melting, P (1) 12*g*.
zone melting, P (8) 200*b*; 201*e*,*j*; P (9) 225*b*.
rod-shaped members, P (3) 64*f*.
solids, acoustic emission and dislocation kinetics in, (7) 180*f*.
solids, anelastic relaxation in, B (10) 262*h*.
vitro-, modifying, P (7) 162*h*.
properties, improving, P (4) 81*e*.
strengthening by coating, P (4) 85*j*.
Crystallinity, face, dependence of band bending in GaAs, (7) 177*a*.
phases, in degradation of aromatics yielding C, (1) 22*j*.
surface layers, strengthen Al_2O_3, (2) 49*h*.
Crystallite, size and shape in MgO-$Mg(OH)_2$, (6) 146*d*.
Crystallization, in Al hydroxide gels, (2) 47*h*.
of BeO, Be_2SiO_4, and SiO_2 from Li_2MoO_4-MoO_3, (7) 176*h*.
effect on fused SiO_2 refractories, (1) 7*b*.
effect on Li_2O-SiO_2 glass-ceramics, (3) 55*d*.
enthalpy, of diopside and anorthite, (1) 22*g*.
equilibria in fluoride systems, (6) 146*e*.
of glass. See *Glass.*
of gypsum, high-temp. effect, (7) 156*c*.
on phyllosilicates, (10) 259*f*.
plant, continuous, P (11) 279*f*.
polymer, two-dimensional, model, (5) 120*c*.
pre-, heat treatment, effect on glass crystallization, (8) 190*g*.
re-, of ceramic crystals, (3) 72*e*.
of Cu_2O, kinetics, (4) 97*j*.
of luminescent material, P (6) 137*e*.
during sintering of Nb and TiC powders, (10) 260*e*.
of MgO-Al_2O_3 spinel, (8) 210*c*.
of transition metal carbide, (7) 177*j*.
of semiconductor binary compound, P (4) 88*f*.
of Si thermal oxide film, (3) 63*e*.
in Na_2O-BaO-SiO_2 system, (3) 56*h*.
spherulitic, in 3BaO-5SiO_2 glass, (8) 189*f*.
temp., dependence on rate of heating, (8) 189*e*.
thermal, of memory glasses, (8) 192*c*.
of vitreous Se, strain effects, (11) 268*j*.
of YAG from PbO-YF_3-Al_2O_3 melts, (11) 280*g*.
Crystallochemistry, factors, effect on separation of rare earths, (1) 21*i*.
Crystallography, of Cd Zn sulfide solid solutions, (2) 49*a*.
and crystal chemistry, B (1) 26*j*.
data for $Be(PO_3)_2$, (8) 208*c*.
data for $CaNa_4(PO_3)_6$ and $CaNa(PO_3)_3$ (8) 209*h*.
introduction, B (8) 212*b*.
order in systems Ta_2VO_8-VO_2 and WV_2O_8-VO_2, (7) 177*f*.
orientations of CdS films, (6) 146*f*.
parameters of sulfofluorides of rare-earth metals, (10) 258*i*.
point groups and systems, (1) 8*h*.
of sulfates and chromates, double, (9) 234*h*.
Crystals. See also specific kinds.
anisotropic, optical constants, (1) 17*h*.
binary ionic, ionic diffusion in, (1) 26*a*.
birefringent, Faraday rotation in, (5) 120*f*.
coupling and molecular vibrations in, (4) 96*d*.
crystallizer, verneuil, P (1) 15*a*.
cubic, <110> dislocation in, (5) 119*h*.
defect reactions in, (7) 181*h*.
diamond-structure, lattice vibrations, (6) 146*c*.
diamond-type, strain effects in, (5) 124*g*.
disclination loops, strain energies, (5) 124*h*.
dislocations. See *Dislocations.*
epitaxial, forming in substrates, P (4) 88*h*.
field, magnetic moment for d^4 ions in, (6) 152*a*.
-field splittings in $EuAlO_3$, (5) 122*a*.
formation. See *Crystallization.*
grower with expandable chamber, P (10) 250*f*.
growing, P (8) 200*i*.
apparatus, P (5) 117*a*.
method and structure, P (3) 66*h*.
power control for, P (3) 66*i*.
growth, apparatus, P (10) 250*f*.
at constant rate, P (4) 88*c*.
with electron beam heating, P (4) 88*b*.
of ferroelectric phase of $PbZrO_3$, (8) 199*b*.
in fluor-richterite glass, (3) 55*j*.
of Gd Al garnet (2) 47*f*.
of hexaferrites, (2) 47*f*.
liquid phase, apparatus, P (9) 225*d*.
of Mn_2PO_4Cl, (2) 47*g*.
in opal glasses, (7) 160*e*.
promotion, P (8) 200*g*.
in solid state materials, B (2) 52*i*.
by vapor deposition, P (4) 88*f*.
by vapor-phase transport, (8) 199*g*.
hydrothermal synthesis, B (1) 27*a*.
imperfect, thermodynamics, (11) 283*c*.
inclusions in glass, microscopy, (11) 267*i*.
intercrystalline links in, (7) 178*j*.
ionic, dynamics, B (3) 76*j*.
electric field theory, (5) 124*j*.
Crystals, ionic *(continued)*
interactions in, (7) 178*a*.
normal modes, (5) 122*i*.
large, Czochralski growth, P (9) 226*c*.
large, flux growth, (7) 172*f*.
lattice, absorption in $SrTiO_3$, (6) 149*b*.
diamond, impurity diffusion in, (5) 119*a*.
diamond-type, channeling in, (5) 118*f*.
distortion in V_2O_3, (5) 118*i*.
dynamics of cubic SiC, (5) 121*h*.
dynamics of $SrTiO_3$, phase transition, (5) 121*h*.
of fluoroperovskites, (1) 24*e*.
magnifying devices for, P (1) 18*g*.
parameter of U(C,N), (4) 91*g*.
parameter, of wustite, (4) 97*f*.
Ag_2O, expansion, (2) 47*g*.
spin-, coeff. of Gd^{3+} and Eu^{2+} in CaF_2 and Gd^{3+} in CaO, (5) 124*d*.
strain in 3CaO·SiO_2 solid solution, (9) 214*f*.
super-, based on V_8C_7, (10) 261*b*.
of Ti-Nb oxide, (7) 178*b*.
trapping of fracture cracks, (5) 121*h*.
vibrations, damping in solids, (8) 208*d*.
-melt interface, (8) 199*c*.
and melt, transportation, P (4) 89*c*.
microstructure, measuring by X-ray, P (4) 93*d*.
mixed, growth, P (4) 88*i*.
molecular, semiempirical theories, (1) 49*e*.
mono-. See *Crystals, single.*
nonmetallic, B (10) 263*h*.
optically active, from racemic mixture, P (7) 162*b*.
orbital theory of conduction in diamond and graphite, (1) 21*g*.
perovskite-type, phase transition in, (6) 152*b*.
polishing chemically, P (4) 88*e*.
precipitated, from glasses, (3) 57*i*.
pulling, from molten melts, P (1) 12*f*.
purifying, P (9) 230*c*.
ribbons, horizontal growth, P (10) 250*h*.
seed, P (2) 39*j*.
seed, pulling means, P (1) 12*a*.
separation and purification from suspension, P (7) 170*g*.
single, P (4) 92*e*.
crystallographic directions, P (6) 142*d*.
filamentary, P (1) 13*g*.
growing, P (10) 250*g*.
rod, from polycrystal bar, P (1) 13*d*.
solution growing, P (9) 230*a*.
structure, determinative methods, (8) 205*j*.
of $FeVO_4$, (8) 208*i*.
of Mg-Mn ferrites, (8) 208*h*.
of $SmAlO_3$ and $NdAlO_3$, (8) 208*a*.
of solid electrolyte $(C_5H_5NH)Ag_3I_4$, (10) 258*g*.
of solid solutions in systems Mg-Ti-Fe-O and Mn-Ti-Fe-O, (1) 25*g*.
of $Sr_2V_2O_7$, β-, (8) 208*j*.
and thermal expansion, (2) 47*h*.
surface, intrinsic disclinations in, (5) 121*d*.
systems, and point groups, (1) 8*h*.
thermodynamics, B (11) 284*b*.
twinned, group III-V semiconductor, P (5) 112*f*.
twinning, of KBr, (7) 182*a*.
twins and stacking faults in MoC, (4) 98*i*.
vapor-liquid-solid, growth, P (4) 88*c*.
void, in thin films, (7) 168*f*.
whiskers, P (4) 92*i*.
whiskers, 3-dimensional, P (9) 222*h*.
wurtzite-type, Γ_7 band, spin-orbit effects, (5) 124*d*.
wurtzite-type, Raman effect in, (5) 120*i*.
(Zn,Cd)S and (Zn,Cd)Te, vapor growth, (7) 182*c*.
Curie points, of spinels with magnetic ions, (10) 261*c*.
Curing, foundry molds and cores, P (5) 109*h*.
steam, of cement mortar, (9) 215*a*.
steam, cement and SiO_2 compositions, P (4) 79*h*.
temp., effect on cement strength, (6) 128*e*.
temp., effect on cement structure, (5) 103*b*.
Curium, Cm_2O_3, evaporation and thermodynamic properties, (6) 148*c*.
Currents, controlling device, with VO_2 film, P (6) 138*h*.
high, density path, on glass, (3) 56*d*.
photo-, in CdS, increasing, (5) 120*c*.
in Si radiation detectors, (6) 137*b*.
in SiO films, (6) 150*h*.
thermally released, in Ce glass, (3) 55*e*.
thermo-, ionic, in impure NaCl, (9) 236*i*.
tunnel, through thin Al_2O_3 film, (5) 112*d*.
-voltage, of chalcogenide glass films, (6) 131*h*.
Cutting, complex shapes, P (1) 16*j*.
in plate glass mfg., (8) 191*g*.
processes using laser, P (11) 277*h*.
Cutting tools. See *Tools.*
Cyclones. See *Classifiers; Separators.*

Damping, Al, glass, and glass-ceramic mica, (5) 116*f*.
lattice vibrations in solids, (8) 208*d*.
Dealkalization, of glass surfaces, P (7) 161*b*.
Debye-Waller, *B* values of NaCl-type structures, (10) 258*b*.
Decals. See *Decoration.*
Decay, radioactive, in CdS, (5) 123*c*.
Decomposition, eutectoid, of $CuFe_2O_4$, (1) 23*g*.
eutectoid, of Ta_2C, (6) 148*a*.
hydrochemical, of nepheline, (7) 179*b*.
of kaolinite, brucite, and $BaCO_3$, (3) 74*h*.
of mullite, (3) 72*d*.
of solid solutions, ZrO_2-based, (8) 211*g*.
spinodal, in B_2O_3-PbO-Al_2O_3 system, (3) 75*a*.

Decomposition *(continued)*
spinodal, in systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3, (2) 47*e*.
temp. of $Th(WO_4)_2$, (3) 72*d*.
thermal, of acenaphthylene to soft C, (1) 24*g*.
of Be sulfates, (6) 152*g*.
of $BeSO_4$, kinetics, (6) 149*h*.
of Ca_2SiO_4-$CaCl_2$, (5) 104*e*.
of colloidal boehmite, (11) 280*j*.
of goethite, (5) 120*d*.
inhomogeneous, of talc, (4) 97*g*.
of nitrate mixtures for synthesis of $MgAl_2O_4$ and $Y_3Al_5O_{12}$, (10) 249*a*.
of polyphenylene and oxides, (1) 24*i*.
of K and Na hydroaluminates, (8) 211*i*.
Decoration. See also *Art and artware; Color; Engobes; Glazes.*
American Indian design and, B (3) 76*b*.
with coils, (2) 30*c*.
decal on pottery, P (5) 111*c*.
decal with pyrolyzable film base, P (4) 81*d*.
of fiber glass articles, P (8) 193*b*.
glass, intaglio plate, P (4) 82*h*.
surface, P (8) 193*j*.
water slide-off decals, (3) 57*c*.
of glass-ceramic articles, P (7) 161*b*.
of glass-ceramic body P (2) 33*h*.
of glazed article with beam of corpuscular energy, P (8) 204*a*.
high temp. curing thermosetting composition, P (9) 219*e*.
patterns on ceramic glaze surfaces, P (9) 223*c*.
photographs on ceramic surfaces, P (10) 248*h*.
porcelain, spraying machine for, (8) 198*i*.
printing ceramic articles via offset, P (11) 277*d*.
printing on glassware and earthenware, P (4) 82*e*; P (9) 219*c*.
screen printing, apparatus for, P (11) 277*e*.
screen printing, glass articles, P (8) 194*a*.
silk screening, (4) 85*i*.
on glass substrate, P (5) 107*c*.
of pottery, (8) 197*f*.
on tile, P (4) 86*c*.
of tiles and tableware, (4) 92*f*.
De-enameling. See *Enameling.*
Defects. See also *Crystals; Enameling; Enamels; Glass.*
in alkali halides by electron irradiation, (10) 261*c*.
in capacitors, charting and curing, P (6) 137*c*.
cluster centers in MgO, (5) 119*d*.
distribution in transistor structures, (9) 233*f*.
Griffith, size in glass containers, (7) 158*d*.
inclusions, in laser materials, (1) 11*i*.
inclusions, nonmagnetic, effect on YIG, (6) 147*i*.
interstitial, in LiF, ENDOR, (6) 147*e*.
in materials, determining size, (3) 69*i*.
point, in CaF_2 and UO_2, (6) 152*a*.
effects in NiO separation, (9) 232*h*.
equilibria in CaF_2, EPR, (9) 235*j*.
in Y_2O_3, (7) 182*a*.
revealed by acoustical holograms, (5) 116*a*.
role in mass transport, (9) 235*b*.
Schottky, in ionic crystals, (9) 234*c*.
in SiO_2 and GeO_2, (2) 47*c*.
size indication in materials testing, P (6) 142*g*.
structure, of $BaTiO_3$, (1) 12*a*.
in transparent material, laser detection, P (7) 161*c*.
ultrasonic determination, P (8) 206*a*.
Wadsley, in rutile, aggregation, (6) 145*a*.
white spots in Al_2O_3 ceramics, (7) 165*j*.
Deflector, light, di-$PbMoO_4$ ultrasonic, P (9) 225*c*.
Deformation, balanced, of layered materials, (8) 207*j*.
of cement paste and concrete, (4) 78*i*; (5) 102*j*.
of cement paste and plaster of paris, (5) 103*d*.
of cements based on phosphate binders, (8) 186*d*.
of ceramic crystals, press-forged, (3) 72*e*.
compressive, of UO_2 crystals, P (1) 15*d*.
of concrete, beams, reinforced, (6) 128*h*.
critical points, (6) 128*g*.
jointed piles, (6) 128*g*.
and steel studs, (6) 128*a*.
of fireclay at high temps., (11) 271*g*.
micro-, and strength of diamond, (4) 77*g*.
plastic, chemical kinetics, (4) 95*h*.
effects on WC-Co alloys, (3) 60*h*.
in pure NaCl, (10) 260*j*.
of ZrB_2 crystals, (1) 24*d*.
properties, of Al_2O_3 refractories, (8) 195*g*.
of WC-Co hard alloys, (6) 134*h*.
of UO_2, effect of porosity, (4) 91*g*.
de Haas-van Alphen effect, in Mo bronzes, A_xMoO_3, (6) 150*f*.
Dehumidifiers. See *Dryers.*
Dehydration, of Al hydroxide, P (11) 279*i*.
of $CaSO_4$·$2H_2O$ and $CuSO_4$·$5H_2O$, (1) 21*f*.
of gypsum, by autoclave, (5) 102*f*.
of porcelain slip, (8) 197*d*.
thermal, of Fe(III) hydroxide, (8) 211*j*.
using CO and aluminosilicate catalyst, P (4) 94*i*.
Dehydroxylation. See *Decomposition, thermal.*
Delay line, acoustic surface wave, P (10) 249*d*.
ultrasonic, glass for, P (10) 244*a*.
Densification, in Al_2O_3, grain growth during, (11) 280*h*.
during hot-pressing, (5) 121*h*.
in kaolin bodies, (11) 280*j*.
macroscopic, in hot-pressing, (1) 16*h*.
of MgO during sintering, (2) 49*j*.
of powders, magnetically anisotropic, P (2) 41*b*.
in TiO_2-ZrO_2 and TiO_2-Al_2O_3 composites, (11) 282*i*.
of W layers, P (3) 68*d*.
of U_3Si, swelling effects, (6) 140*j*.
of ZrO_2-CeO_2, hot-pressed, (3) 72*c*.
Density, of alkali metal Cl+ZnCl melts, (6) 146*g*.
bulk, of granular solid, (5) 117*e*.
bulk, high of MgO powder, (7) 171*c*.
of $CaCl_2$-NaCl and $ZnCl_2$-NaCl melts, (5) 120*g*.
charge distribution in kernite, (8) 208*b*.
compacted, statistical study, (7) 173*i*.
correlation with grain size, (6) 151*c*.
of cryolite-based mixtures, (6) 146*h*.
distribution in pressing compacts, (10) 247*c*.
of ferrites after sintering powders, (9) 223*h*.
of fluoroperovskites, (1) 24*e*.
green, effect on UO_2 sintering kinetics, (9) 228*h*.
of halloysite, hectorite, and illite clays, (8) 210*f*.
of $MgCl_2$-$CaCl_2$-alkali metal chloride melts, (5) 119*f*.
of melts in systems Ba-$BaCl_2$, Ba-$BaBr_2$, and Sr-$SrCl_2$, (11) 282*c*.
orthobaric, on fusion of $NbCl_5$, (8) 208*h*.
in oxide glasses, (10) 242*j*.
pinhole, decrease, (11) 273*g*.
of products during vibro-impact consolidation, (8) 203*i*.
of sediments, precise determination, (3) 70*b*.
of ThO_2, effect of fluoride adsorption, (9) 233*d*.
of C_3S-H_2O system, (5) 103*h*.
of ZrC compacts, (10) 247*b*.
firing ovens, P (7) 174*j*.
furnace for, vacuum electrical, P (5) 117*b*.
Dental ceramics, firing ovens, P (7) 174*j*.
Au alloy, porcelain bonding, P (10) 248*h*.
polishing, amalgam composition, P (2) 29*f*.
porcelain teeth, semibaked, P (3) 62*a*.
prosthesis model base composition, P (6) 136*a*.
replamineform, new process, (10) 254*d*.
Deposition, of aluminosilicate films, (2) 38*d*.
anodic, of frit with cationic coating, P (4) 80*b*.
anodic, of frit in dual envelope, P (3) 64*d*.
apparatus, P (7) 168*c*.
of BeO, P (10) 257*b*.
of carbides of refractory metals, (10) 258*d*.
chemical vapor, of garnet films, (10) 248*j*.
growth of TiC crystals, (9) 238*i*.
of rutile films, P (7) 168*j*.
of silicate glasses, (9) 216*i*.
of SiO_2 films, (10) 249*c*.
of YIG films, (11) 274*i*.
electrochemical, of W oxide bronzes, (8) 208*i*.
electro-, bath, acid control in, P (8) 192*f*.
bath, electrodialysis and ultrafiltration, P (8) 192*e*.
bath, treatment, P (8) 194*d*.
of ceramic coatings, (4) 79*j*.
of composite coatings, P (10) 250*a*.
compositions, P (8) 192*f*.
compositions, pretreating, P (8) 193*i*.
compositions, ultrafiltration, P (8) 194*d*.
of PbO_2, P (4) 87*d*.
of metal-silicate coatings, P (4) 90*b*.
of metals in glass, (9) 217*g*.
vitreous coatings on substrate, P (10) 242*f*.
electrophoretic, of clay slip, (4) 85*h*.
electrophoretic, of color phosphors, P (10) 244*e*.
epitaxial, autodoping in, P (8) 200*h*.
for making semiconductor device, P (1) 13*a*.
method, P (4) 87*g*.
minimizing autodoping in, P (9) 226*f*.
flame, of oxide coating, P (5) 105*c*.
heterogeneous, of thin film rutile, (9) 224*i*.
homoepitaxial, Si, (3) 63*b*.
ion-beam apparatus, (5) 116*a*.
ion-beam, of C thin films, (6) 149*b*.
pre-, on semiconductive wafer, P (1) 13*d*.
pyrolytic, of Si_3N_4 films, P (5) 114*a*.
of semiconductor material, P (4) 88*f*.
of SiO_2 films, P (3) 65*e*; (11) 273*g*.
of Si nitride, P (3) 65*d*.
sputter, of EuO thin films, (7) 168*b*.
surface, with twist grain boundaries, (10) 261*e*.
thin-film, mechanism, P (3) 65*a*.
of thin lines, apparatus for, P (8) 200*c*.
vacuum, of coatings, P (3) 68*c*.
vacuum, of epitaxial layer, P (6) 140*d*.
vapor, of alloys, P (7) 170*h*.
apparatus, P (1) 15*d,a*; P (5) 114*e*; P (8) 203*a*.
coating substrates by, P (1) 13*b*.
for crystal growth, P (4) 88*f*.
of films, P (5) 112*f*.
metallic, arrangement, P (7) 169*d*.
of metals, P (3) 67*d*.
Si_3N_4 layer on Si, P (7) 169*e*.
of thin insulating films, P (4) 89*c*.
of W for Si devices, P (10) 249*b*.
of W-W oxide coating, P (9) 226*i*.
vapor phase, of Al_2O_3 on Al, (10) 249*b*.
of B, P (10) 253*d*.
Deposition, vapor phase *(continued)*
of silicide refractory coatings, P (8) 197*b*.
for SiO_2 articles, P (6) 140*c*.
Design. See also *Art and artware; Decoration.*
American Indian, and decoration, B (3) 76*b*.
Detectors. See also *Tubes, electron.*
dew point condensate, (9) 231*a*.
diamond nuclear radiation, P (9) 228*h*.
for failed nuclear fuel elements, P (9) 228*g*.
gas, P (6) 137*f*.
gas leak, P (7) 174*c*.
Ge, Li-drifted, B (7) 183*c*.
Ge (Li), large volume planar pair, P (2) 40*f*.
ir, Pb-SnTe material for, P (10) 252*d*.
ir, III-V alloys for, P (4) 90*b*.
MOSFET ir, P (9) 227*a*.
of movement between two bodies, P (10) 251*i*.
multijunction photodiode, P (3) 66*d*.
near-ir, using Cd Sn phosphide, P (4) 89*f*.
nuclear radiation, P (9) 229*a*.
nuclear, thin, β-particle detection in, P (3) 68*h*.
phase difference, P (11) 275*h*.
photoconductive material, P (10) 252*h*.
piezoelectric sorption, P (10) 251*j*.
radiation, P (1) 14*f*; P (3) 67*e*; P (6) 139*j*.
for minerals, P (5) 116*g*.
polygonal-shaped, P (3) 66*i*.
semiconductor-type, P (10) 253*b*.
Si, photocurrents in, (6) 137*b*.
thermal change, P (6) 140*b*.
Devitrification, of glasses in CaO-MgO-P_2O_5 system, (5) 105*h*.
Dewatering. See *Water, removal.*
Dewaxing, using aluminosilicate zeolites, P (11) 279*g*.
Dewetting. See *Wetting.*
Dialysis, electro-, for demineralization, P (8) 203*j*.
of silicate for colloidal SiO_2, P (9) 233*a*.
and ultrafiltration of electrodeposition bath, P (8) 192*e*.
Diamonds, abrasive tools, P (9) 213*f*.
in abrasive wheels. See *Grinding apparatus.*
apparatus for making, P (4) 77*i*.
bits, design, P (1) 1*g*.
^{57}Co implanted in, Moessbauer study, (5) 122*c*.
compressibility data, (6) 149*a*.
converting graphite to, P (4) 77*f*.
crystals, P (1) 1*f*; P (7) 155*f*.
crystals, catalytic growth, P (8) 207*c*.
edge, for ultrathin sectioning, P (6) 127*g*.
electrical contacts on, (4) 86*h*.
from different sources, (4) 77*f*.
friction of diamond sliding on, (6) 127*f*.
GR1 center in, optical measurements, (4) 98*a*.
growth process, P (4) 77*f*.
as heat sink for solid state devices, (4) 87*b*.
as heat sinks, (4) 86*e*.
indentation hardness, (4) 77*g*.
implosion apparatus, P (8) 185*e*.
improves productivity, finish, (2) 29*j*.
impurity levels in, (6) 151*j*.
impurity platelet in, X-ray topography, (10) 261*h*.
kimberlite, genesis, (4) 77*f*.
lattice, impurity diffusion in, (5) 119*a*.
mfg. in H-free environment, P (10) 241*f*.
metal-, interfaces, thermal conduction, (4) 77*g*.
microdeformation and strength, (4) 77*g*.
natural, carbonado, (1) 19*i*.
N in, properties, (4) 98*g*.
particles, coating with metal, P (7) 155*f*.
particles, recovery from wastes, P (6) 127*h*.
photoconductivity spectrum, (5) 123*f*.
powder dispersions, process, P (8) 185*e*.
powder, Si-coated, P (3) 67*d*.
securing by brazing, P (10) 241*f*.
semiconducting, acceptor center in, (4) 86*e*.
single particles, testing, (4) 77*e*.
synthesis, high-pressure device in, P (5) 115*g*.
synthesizing, P (10) 241*e*.
synthetic, P (1) 1*h*; P (4) 77*g*; P (7) 155*f*.
synthetic, Hall effect measurements, (4) 86*c*.
theory of conduction in, (1) 21*g*.
tool, P (8) 185*e*.
turning tools, wear, (6) 127*e*.
valence bands in, occupancy, (6) 146*j*.
wetting by molten metals and alloys, (10) 259*f*.
Diatomaceous earth, or **Diatomite.** See *Kieselguhr.*
Dicalcium silicate. See *Calcium.*
Dielectrics. See also *Ferrites; Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials; Glass; Porcelain, electrical; Spark plug insulators; Steatite; Titanates; Whiteware.*
artificial, Faraday rotation in, (5) 111*j*.
body, composite, P (3) 66*i*.
body, transmission line formed by, P (4) 91*a*.
ceramic, body, P (3) 65*j*.
of Ca titanosilicate, P (10) 249*j*.
compositions, P (3) 64*a*; P (8) 200*f*.
compositions with Pb-Ba borosilicate glass, P (10) 245*g*.
constants, of alkaline earth fluorides, (4) 97*a*.
of bulk GaAs, (7) 178*a*.
of $LiTaO_3$ and $LiNbO_3$, (4) 99*f*.
test cell for, (3) 70*f*.
enclosures, ion implanted, P (8) 201*d*.
film thickness monitoring and control system, P (2) 40*c*.
glass-ceramics, for capacitors, (11) 273*g*.
loss curves, asymmetrical, (1) 23*b*.
lossy structure, P (9) 225*g*.
materials, P (9) 225*c*.

Dielectrics, materials *(continued)*
electret charges in, P (6) 139*f*.
high *K*, P (10) 250*g*.
Si oxynitride, for capacitors, (9) 224*c*.
thermal radiation, (6) 134*j*.
measurements of H_2O adsorption on clay minerals, (9) 236*j*.
pastes, (8) 199*j*.
photo-, effect in ZnS phosphors, (3) 74*f*.
properties, of Al_2O_3, sintered, (1) 21*e*.
of $BaTiO_3$, (1) 11*c*; (11) 273*h*.
of $BaTiO_3$, polycrystalline, (1) 11*d*.
of BL ceramic dielectrics, (3) 62*h*.
of CoO and NiO crystals, (6) 146*i*.
of electrical porcelain, (1) 11*b*.
of glasses in M_2O-GeO_2 and M_2O-B_2O_3-GeO_2 systems, (8) 189*j*.
of Fe_3O_4 particles and ferrites, (3) 62*d*.
of α-Fe_2O_3, TiO_2, and Fe_2TiO_5 mixtures, (3) 62*d*.
of $Pb(Cd_{1/3}Nb_{2/3})/O_3$, (4) 95*g*.
of K Bi Zn niobate, (4) 98*b*.
of Na aluminosilicate glasses, (7) 158*h*.
of system $PbNb_2O_6$-$BaNb_2O_6$, (11) 281*b*.
of Y_2O_3, sintered, (1) 11*b*.
refractory, in mfg. semiconductors, P (1) 13*a*.
screening model for lattice vibrations, (6) 146*c*.
siphons, (4) 93*a*.
structure, for semiconductor device, P (6) 137*a*.
study of solid powders, (7) 173*g*.
substrates, electrical resistivity, P (5) 113*j*.
Ti-containing, aging, (8) 199*e*.

Dies. See also *Extrusion*.
castable-refractory composition, P (6) 136*d*.
ceramic, P (2) 38*b*.
ceramic, assembly, P (2) 38*b*.
extrusion, design, (3) 69*a*.
graphite, for ceramic TiO_2 with low dielectric loss, (1) 11*h*.
and model compositions, P (3) 61*c*.
powder press, filling of, P (1) 17*a*.
and punch assembly for compacting powders, P (9) 229*j*.

Differential thermal analysis. See *Thermal analysis*.

Diffraction. See also *Electron diffraction; Neutrons; X rays*.
glancing incidence, of TiC crystals, (10) 259*i*.
light, in fused quartz, (5) 121*j*.
powder, sample preparation for, (4) 93*h*.
surface-wave, in $LiNbO_3$, (4) 99*g*.

Diffractometers. See also *Electron diffraction; X rays*.
for determination of clinker minerals, (4) 79*a*.

Diffusion, of acceptor impurities into semiconductors, P (2) 41*b*.
along grain boundaries and dislocations, (5) 119*a*.
Al, P (10) 249*e*.
Al_2O_3 coeff., in cryolite-Al_2O_3, (7) 176*f*.
barriers for generator elements, P (7) 168*d*.
Cd, in MgO at high temps., (6) 145*d*.
cation, in UO_2 solid solutions, (9) 228*f*.
of chalcogen in II-VI compounds, (4) 98*j*.
chemical, in compounds, (9) 233*d*.
chromizing, graphite powders, (10) 246*j*.
coatings, for electrodes in Al, (10) 246*i*.
coeff., in glass, (1) 3*i*.
coeff., for nonstoichiometric compounds, (9) 233*d*.
of Cu in CdS single crystals, (5) 119*e*.
dissociative, pressure dependence, (7) 176*h*.
of dopants into semiconductor, P (11) 275*a*.
equation, related to solid state reactions, (3) 74*i*.
gas, inert, in glasses, (2) 32*b*.
of gases, in vitreous B_2O_3, (3) 55*b*.
gaseous, technique, P (8) 200*f*.
heat, in laser materials, (1) 11*h*.
He, in BeO, (7) 171*d*.
for improving glass properties, P (4) 81*e*.
impurity, in diamond lattice, (5) 119*a*.
impurity, into SiC, P (4) 88*g*; P (11) 272*f*.
ion, in system alkali metal salt-V_2O_5, (5) 121*e*.
ionic, in stress gradient, (1) 26*a*.
Fe tracer, in hematite at high temps., (5) 119*e*.
length in GaAs, (4) 96*e*.
of Mn in single crystalline MnO, (2) 47*j*.
mask, Si_3N_4, P (2) 41*e*.
in metal oxides, B (10) 263*j*.
in orthosilicates, (9) 234*b*.
O, in TiO_2, (9) 238*i*.
O, in ZrO_2, (9) 237*i*.
of rare gases, in silicates, (2) 50*e*.
of refractory metal powders with C and B, (1) 7*d*.
self-, cation, in CoO crystals, (6) 149*c*.
cation, in MgO, (6) 145*f*.
cation, in NiO, (7) 176*d*.
cation, in UN_{1+x}, (7) 171*b*.
O, of CeO_2 and CeO_2 solid solutions, (9) 237*i*.
in spinels, (10) 260*h*.
single-step, for FETs, P (2) 41*f*.
Na, in glass, atm. effects, (6) 131*h*.
solid state, of Ca into kaolinite and illite, (5) 104*b*.
source, BN, (11) 273*e*.
in space-charge theory, (7) 178*d*.
of sulfide ion in ZnS crystals, (7) 180*h*.
surface, and sintering in Al_2O_3, (4) 97*g*.
in system Al_2O_3-SiO_2, (11) 281*e*.
in system MgO-Fe_2O_3, (5) 119*c*.
in system K_2O-SrO-SiO_2, (5) 105*j*; (7) 158*j*; (9) 216*h*.
thermal, C, in UC_2-C system, (2) 43*e*.

Diffusion, thermal *(continued)*
of O in UO_2, (7) 171*c*.
in solid solutions, (6) 152*c*.
tracer, in glassy and crystalline SiO_2, (5) 106*d*.
treatments, of glass by electric arc, P (6) 132*e*.
H_2O, in concrete at 30°C, (5) 102*h*.
Zn, into GaP, P (7) 170*i*.
zones, composition and substructure, (5) 116*h*.

Diffusivity, of glasses at high temps., (7) 158*j*.
thermal, of TiB_2, ZrB_2, and HfB_2, (4) 97*e*.

Dilatometers. See also *Expansion*.
curve of Dutch structural clays, (4) 83*d*.

Dilatometry, of chalcogenide alloy glasses, (6) 131*h*.
data of majolica wall tiles, (7) 165*g*.
of firing behavior of C bodies, (9) 221*g*.

Dinnerware. See also *Art and artware; Pottery; Whiteware*.
automatic production lines, (11) 272*j*.
china, vitreous, refire dunting, (4) 85*f*.
cups, bone china, production machine, (4) 85*c*.
disposable, from pyrophyllite, P (7) 166*c*.
glazing and decorating, (4) 92*f*.
kiln loader, P (1) 10*i*.
Pb glaze research on, (1) 9*i,j*.
plate, automatic mfg. in Germany, (5) 110*c*.
saucer, P (4) 78*a*.

Diodes. See also *Tubes, electron; Rectifiers*.
alloy, characteristics control, P (8) 200*a*.
array radiation-responsive device, P (8) 200*j*.
array target, P (10) 250*h*.
camera tube, P (9) 226*h*.
vidicon, semiconductor, P (2) 42*b*.
bond-type, using Sn-doped GaAs, P (8) 200*c*.
directed emission light emitting, P (10) 250*h*.
electroluminescent, configuration, P (9) 225*c*.
electroluminescent, efficiency improved, (2) 38*i*.
GaAs, light-emitting, P (6) 139*j*.
with phosphor coating, P (3) 65*b*.
thin-film, memory effect, (5) 111*j*.
tunnel, partial recovery, (5) 112*a*.
GaP, doping profile for, (9) 225*d*.
GaP electroluminescent, P (3) 66*a*.
gate protection, P (9) 224*j*.
hot carrier *pn*, P (9) 225*d*.
hyperabrupt junction Si, P (4) 89*c*.
injection-luminescent, P (3) 65*c*.
IMPATT, P (11) 274*j*.
junction, treatment, P (3) 66*h*.
light-emitting, P (4) 88*j*.
multiple color, P (2) 41*g*.
semiconductor, P (4) 90*c*.
MOS, surface effects of radiation on, (4) 99*g*.
microwave tunnel, P (9) 227*a*.
photo-, avalanche, P (3) 64*h*.
Schottky barrier, P (1) 14*h*.
Si *pn* junction, (4) 86*j*.
planar varactor, low-capacitance, P (4) 88*b*.
pn junction, electroluminescent, P (6) 137*c*.
Schottky barrier, P (3) 67*h*; P (6) 137*j*; P (10) 250*f*.
Schottky-emission thin-film, P (4) 90*a*.
semiconductive, P (8) 201*h*.
semiconductor, P (9) 227*f*.
and arrays of, P (5) 113*f*.
avalanche, P (8) 202*g*.
laser, P (2) 42*d*.
Schottky type, P (5) 114*a*.
Si, array target, P (9) 225*h*.
detecting surface ions on, P (9) 226*d*.
protection means, P (1) 14*d*.
SiC junction, P (6) 139*f*; P (8) 201*e*.
surface barrier junction, P (6) 140*i*.
uninsulated in-core thermionic, P (10) 253*d*.
varactor, P (2) 43*b*.
variable capacitance, P (5) 113*i*; P (10) 253*e*.
with voltage variable capacitance, P (4) 87*b*.
Zener, P (1) 13*j*, 15*c*; P (9) 226*f*; P (10) 251*i*.
planar, P (2) 42*a*.
semiconductor device with, P (4) 89*f*.
of ZnO doped with Ga oxide, P (2) 40*c*.
ZnO thin film, bistable switching, (3) 62*g*.
ZnSe-GaAs, light emission from, (5) 111*h*.

Diopside, synthetic, P (7) 175*j*.
synthetic, crystallization enthalpy, (1) 22*g*.

Disintegrators. See *Crushing apparatus*.

Dislocations, basal, in sapphire, (10) 261*h*.
cells, theory, (5) 124*j*.
crack, effects during cleavage, (4) 95*d*.
depinning and repinning, (6) 145*d*.
elastic properties, (11) 281*g*.
geometry, (11) 281*j*.
glide in UO_2 single crystals, (6) 140*i*.
and grain boundaries, diffusion along, (5) 119*a*.
kinetics, in crystalline solids, (7) 180*f*.
motion, effect of viscous drag, (7) 179*c*.
motion in pure NaCl, (10) 258*h*.
<110> in cubic crystals, (5) 119*h*.
relation with disclinations, (5) 123*c*.
in Si_3N_4, β-, (6) 146*d*.
sources in surface crystals, (5) 121*d*.
theory, fundamental aspects, B (2) 50*h*.

Dispersion, aqueous inorganic solids, flow, P (2) 38*b*.
of ball clay, blue, (1) 9*h*.
forces between fused SiO_2 objects, (2) 47*a*.
of glasses, changes in, (9) 216*e*.
of kaolinite suspensions, rheology, (2) 49*h*.
laponite, rheological properties, (9) 238*g*.
in montmorillonites, (2) 37*i*.
of SiC, β-, (1) 25*a*.

Display devices. See also *Electronic equipment*.
based on ZnO excitation in gas plasma, (4) 86*e*.
image, P (5) 112*h*.

Display devices *(continued)*
optoelectronic panel, P (8) 201*j*.
panel, multicolor plasma, P (10) 245*f*.
SiC, single-crystal, P (4) 90*h*.

Dissociation, thermal, and reassociation of zircon, (7) 179*j*.

Dissolution. See *Solutions*.

Dolomite. See also *Refractories*.
or calcite, quartz, and kaolinite, synthesis, (5) 121*a*.
calcite-, X-ray determination, (1) 26*c*.
coked tarred, residual C in, (11) 271*i*.
dressing and sintering, (11) 279*f*.
effect on $BaTiO_3$, (11) 273*i*.
lime and MgO in, (3) 69*h*.
and magnesite, hydrates, purifying, P (10) 257*j*.
Ontario, TGA of, (7) 181*e*.
plaster. See *Plaster*.
undeformed, orientation, (1) 23*b*.

Domains. See *Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials*.

Doping. See *Additives*.

Dosimeter, neutron, including step wedge, P (2) 16*c*.
phosphate glass, materials for, P (1) 4*h*.
radiation, phosphor for, P (5) 113*h*.
using fluorescent glass element, P (6) 142*e*.

Drilling, diamond bits, design, P (1) 1*g*.
by laser pulses, P (1) 17*b*.

Drills, tubular shank, solves dust problems, (3) 69*b*.

Dry pressing. See *Pressing*.

Dryers. See also *Drying*.
air, /filtration unit, P (7) 172*i*.
gas, P (10) 256*h*.
for granular or particulate material, P (8) 206*g*.
high output, flow technique in, (2) 45*f*.
hyperfrequency, in ceramic industry, (2) 45*g*.
insulating structural units for, (5) 116*j*.
nondusting high-temp., P (11) 279*c*.
rotary, P (9) 232*e*.
rotary, for granular materials, P (7) 174*h*.
spray, plants, Soviet, (5) 115*j*.
spray, types, (4) 92*g*.
for structural ceramics, (7) 174*f*.
tumbler, P (7) 174*i*.

Drying. See also *Dryers*.
cement paste, (4) 79*e*.
ceramic moldings, P (11) 279*d*.
chamber apparatus for fiber, P (10) 244*f*.
clay product, updating processes, (3) 70*i*.
clay structural articles, (4) 83*e*.
coarse and fine ceramics, (11) 276*i*.
cylinder, steam-heated, P (8) 206*h*.
device for, P (2) 44*a*.
freeze, P (10) 254*e*.
freeze-, carbide synthesis by, (2) 47*e*.
gas, adsorbent selection for, (9) 232*b*.
glass fiber forming packages, P (2) 34*c*.
methods in Russia for ceramics, (3) 70*i*.
pneumatic, (7) 174*f*.
pulverant materials, P (2) 43*i*.
racks, P (11) 279*a*.
rapid conveyor and automatic, P (3) 70*i*.
rapid, in existing dryers, (3) 70*i*.
refractory concrete linings, (4) 84*b*.
slurries or sludges, P (1) 16*g*.
spray, binders in, (4) 92*f*.
effects on clays, (4) 94*d*.
for phosphors, P (10) 249*g*.
in preparing porcelain body, (9) 223*b*.
steam, filter cake, P (10) 254*f*.

Ductility, of concrete reinforced columns, (6) 128*a*.
in Fe, effect of Mn and C, (6) 148*j*.

Dunite, changes during heating, (7) 181*e*.

Durability, of concrete, lightweight aggregate, (6) 128*a*.

Dust. See also *Air, pollution; Particles; Powders*.
adherence in kiln, alkali effect, (9) 214*c*.
analysis of free SiO_2 in, (1) 17*d*.
collectors, P (6) 141*e*.
electrostatic separator, P (9) 230*a*.
elimination with tubular drill shank, (3) 69*b*.
extraction, cloth filters for, (5) 115*d*.
extraction from gases with filter, P (5) 115*g*.
industrial, centralized removal, (8) 203*h*.
particles, charged, electrodynamics, (6) 141*e*.
properties, effect of soap substitute, (8) 203*g*.
removal from gaseous stream, P (10) 254*c*.
separation from cement kilns, P (5) 104*j*.
separation from gas, P (3) 69*c*.
and silicosis problem, Dutch, (5) 126*a*.
in waste gases, purifying, P (10) 254*i*.

Dysprosium, chloride, vapor pressure, (8) 210*b*.
Dy^{3+}, effect on efficiency of phosphor, (3) 72*g*.
effect on luminescence of Y_3OCl_7:Yb^{3+}-Er^{3+}, (3) 72*h*.
fluorescence in Na borate glass, (7) 159*b*.
$DyCrO_3$, exciton absorption lines in, (4) 96*f*.
hydroxide, magnetic properties, (8) 209*j*.

Earthenware, articles, printing on, P (9) 219*c*.
bone china, reaction with glazes, (1) 10*a*.
green bodies for, thermal expansion, (5) 111*e*.
industry, Pb glazes in, (9) 223*d*.
printing on, P (4) 82*e*.
production, Pb solubility and, (7) 165*d*.

Efflorescence, in bricks, and firing conditions, (4) 83*f*.
in portland cement products, P (6) 130*d*.
prevention in portland cement mortar, (9) 214*f*.

Elasticity, aftereffect in cold-pressing metal-carbide, (10) 246*f*.

Elasticity *(continued)*
constants, of graphite, (10) 258*j*.
of $LiTaO_3$ and $LiNbO_3$, (4) 99*f*.
of $SrTiO_3$, pressure effects, (4) 98*b*.
of disclinations in nonhomogeneous media, (7) 177*a*.
energy, in brittle materials, (11) 281*g*.
inelastic behavior of concrete, (6) 129*g*.
ferro-, (2) 38*g*.
ferro-, in $BiTiO_3$, (2) 39*d*.
and magnetoelastic effects in magnetite, (6) 147*c*.
moduli, of ceramic materials, (9) 239*b*.
of composite materials, (6) 148*j*.
of concrete, (5) 103*a*.
of polycrystalline ferrites, (11) 281*f*.
relation to strength in BeO-SiC, (1) 25*g*.
of SiC, (4) 96*g*.
of Na_2O-TiO_2-SiO_2 glasses, (8) 191*d*.
third-order, of CaF_2, (5) 125*d*.
of UC, UO_2, and UN, (1) 15*d*.
photo-, constants of α-quartz, (1) 24*d*.
plasticity, and structure of matter, B (3) 76*h*.
-porosity relationship in Al_2O_3, (5) 125*b*.
properties, anomalous, of Fe_2TiO_4, (3) 72*d*.
of cast stone, (8) 195*c*.
of dislocations, (11) 281*g*.
of PLZT ceramics, (11) 273*i*.
Young's modulus, of polycrystalline mullite, (4) 99*j*.
Young's modulus, of portland cement, (10) 241*j*.

Elastomers. See *Elastic materials.*

Electric resistors. See *Resistors, electrical.*

Electrical ceramics. See *Electronics.*

Electrical conductivity. See *Conductivity, electrical.*

Electrical properties, of Al_2O_3 ceramics, effect of Fe_2O_3, (7) 166*e*.
of $BaTiO_3$, doped and undoped, (1) 11*d*.
effect of sintering, (9) 224*f*.
thin films, (9) 224*d*.
of CdF_2:Y, (5) 120*h*.
of chalcogenide glasses, (9) 218*g*.
of Cu-ThO_2, Au-ThO_2, Pt-ThO_2, and Au-Al_2O_3, Pt-Al_2O_3 alloys, (2) 38*e*.
field gradient, in corundum, (5) 120*d*.
fields, effect on radiative recombination in CdS, (6) 147*a*.
in ionic crystals, theory, (5) 124*j*.
spin-orbit effects in, (5) 124*d*.
of $Gd_2(MoO_4)_3$, (3) 73*h*.
of GaAs/Al_2O_3 films, (4) 86*j*.
glass, effect of uv irradiation, (3) 55*c*.
of hexaborides of alkaline- and rare-earth metals, (10) 259*b*.
of FeO-P_2O_5 glasses, (9) 218*i*.
of 55FeO-45P_2O_5 glass, (8) 189*d*.
of MnO_2 and Mn_2O_3, (9) 235*c*.
of *np* ZnO-Si heterojunctions, (4) 96*i*.
pyro-, of $PbNb_2O_6$-$BaNb_2O_6$ system, (11) 281*b*.
of RuO_2 thick films, (8) 199*g*.
of rutile thin film, (3) 62*f*.
of silicates and germanates, (7) 181*c*.
of solid solutions in system $LaAlO_3$-$CaTiO_3$, (9) 235*d*.
of solids, B (10) 263*e*.
strength, of Al_2O_3, (7) 165*j*.
in system $BaCeO_3$-$Ba_3(CeTa)O_8$, (11) 282*g*.
of SnO_2 crystals, (6) 147*g*.
of SnO_2 single crystals, reduced, (3) 72*j*.
of Ti oxides, (6) 147*h*.
transport, of CeO_3 and CeO_2 solid solutions, (9) 237*i*.
transport, in insulating solids, (3) 72*f*.
of V_nO_{2n-1} crystals, (1) 11*a*.
of wustite, (9) 233*g*.
of ZrO_2, effect of oxide defect structure, (10) 258*i*.

Electrical resistance. See *Resistance, electrical.*

Electricity, in As-Te glass, (2) 33*f*.
bushing, P (6) 136*b*.
corona, fossilization from Si_3N_4 crystals in electron microscope, (10) 255*d*.
diced single-crystal impurity source, P (9) 226*c*.
dipole moment, of SiO and GeO, (5) 120*g*.
dc bias effects in $BaTiO_3$ ceramics, (9) 223*h*.
direct generation, apparatus for, P (4) 81*h*.
electromagnetic radiation to, P (10) 250*e*.
elements, compositions for, P (10) 250*c*.
field-velocity, of GaAs, (6) 150*h*.
fields, effect on aluminosilicates, (9) 236*f*.
glow-discharge apparatus for rapid sintering of Al_2O_3, (8) 205*a*.
measurements of chalcogenide thin films, (6) 137*d*.
parts, thermal insulation for, P (6) 135*g*.
refractories, breakdown strength, (7) 164*j*.
standards, temp. baths for, (3) 70*f*.

Electroanalysis. See *Analysis.*

Electroceramics. See *Electronics.*

Electrochemistry. See also *Corrosion.*
apparatus, measuring glaze-body reactions, (1) 10*a*.
charging of SiO_2 films, (7) 166*i*.
energy conversion, (4) 86*f*.
in measurement of formation energies of Nb oxides, (1) 21*i*.
of Ag vapor incorporated into Ag_2S, (6) 147*i*.
of sulfides, (5) 120*h*.

Electrochromatography. See *Chromatography.*

Electrodes. See also *Heating elements.*
activated, P (10) 252*c*.
Al welding wire, P (10) 242*h*.
amorphous, or surface, P (2) 39*j*.
arc-welding, tubular composite, P (5) 105*e*.
B_4C, in energy storage device, P (1) 12*i*.

Electrodes *(continued)*
C, connecting joint for, P (2) 37*d*.
joinable, for gouging metal, P (4) 85*a*.
junctions, cement for, P (3) 61*c*.
coated, for electric arc welding, P (6) 131*f*.
coating, P (9) 227*i*.
conductive C membrane, P (10) 250*d*.
corrosion in glass tanks, (8) 191*g*.
for electric arc furnaces, P (8) 206*b*.
etching, P (9) 225*h*.
fuel cell, P (1) 12*d*.
glass, P (8) 192*g*.
K ion sensitive, P (2) 34*d*.
solid-state, P (6) 133*h*.
graphite, P (7) 164*d*.
graphite, for light arc furnaces, P (11) 272*g*.
holder, corrosion, effect of Mo, (8) 190*c*.
joint cement, P (8) 196*i*.
laminated, for semiconductor device, P (8) 201*a*.
loading in glass tank furnaces, (8) 192*b*.
measuring combined, P (9) 231*h*.
in molten Al, increasing durability, (10) 246*i*.
"polarization" in glasses, (8) 190*h*.
semiconductor, doped, P (10) 250*h*.
of semiconductor device, P (10) 251*d*.
SiC, in energy storage device, P (1) 12*i*.
system of electric arc furnace, P (8) 206*h*.
system, semiconductor, P (3) 64*h*.
thermo-, electric insulation for, (8) 199*e*.
WC, for fuel elements, P (11) 272*b*.
type, effect on glass tank, (8) 189*f*.
welding, P (4) 80*c*; P (6) 131*b*.
covered, P (6) 131*a*.
melt-resistant, P (5) 105*d*.
Zn, sintered, P (3) 67*a*.

Electrodialysis. See *Dialysis.*

Electroluminescence. See *Luminescence.*

Electroluminescent materials. See *Luminescent materials.*

Electrolysis, of brine, P (6) 135*f*.
extracting O from silicate rocks by, (7) 175*a*.
for separation of rare earths, P (2) 46*i*.
for SiO_2 sols production, P (7) 176*b*.

Electrolytes, Al_2O_3, β-, P (3) 66*d*; (9) 238*b*.
effect on clay minerals, (5) 110*i*.
effect on glass polishing, (7) 159*d*.
heating, sintering by, (11) 276*j*.
solid $(C_5H_5NH)Ag_3I_4$, crystal structure, (10) 258*g*.
treatment of hollow glass, P (11) 270*e*.

Electromagnets. See *Magnets.*

Electromechanical properties. See *Mechanical properties.*

Electron diffraction, of montmorillonite crystals, (10) 260*b*.
from NiO antiferromagnetic crystal, (4) 96*e*.
of superconducting complexes, (4) 96*j*.
superlattice lines in Mg ferrite, (2) 47*b*.

Electron probes, micro-, (4) 93*c*.
of alkali silicate glasses, (3) 55*e*.
of lunar glass, (6) 132*h*.
of Mg in cements, (8) 186*b*.
of Si, Mg, Al, and S, (4) 93*e*.
microanalysis, B (11) 283*f*.
of chromites in periclase-chrome brick, (8) 194*j*.
of grinding tools, (11) 265*e*.
of inorganic materials, (2) 44*h*.

Electron tubes. See *Tubes.*

Electronic equipment, adjustable capacitor and printed circuit, P (7) 168*i*.
from air firable VO and B, P (3) 64*c*.
arithmetic unit, P (2) 41*f*.
barrier layer, modifying, P (9) 226*j*.
bolometer, thermistor, P (11) 274*j*.
for breaking semiconductor material, P (1) 12*g*.
ceramic bender, high reliability, P (3) 65*c*.
ceramic chip components, P (3) 64*j*.
ceramic member, metalizing, P (3) 66*b*.
ceramic package, P (4) 87*j*.
ceramic substrate interconnection, P (10) 250*a*.
channel multiplier, Al_2O_3, P (3) 64*b*.
channel multipliers, array, P (10) 245*a*.
components, chip-shaped passive, P (3) 65*j*.
encapsulating, P (1) 14*d*.
thin-film, P (8) 202*h*.
condenser, electric, P (10) 250*j*.
for connecting to Nesa layer, P (10) 251*h*.
connector, 0-insertion force, P (9) 228*e*.
to convert ir to visible light, P (3) 64*g*.
convertors, X-ray image, P (3) 68*b*.
counter, low energy particle, P (10) 251*c*.
counter, proportional, high-temp., P (2) 40*b*.
electric connection to, P (3) 66*e*.
electrical, brush structure, P (9) 225*d*.
components, support for, P (10) 253*f*.
contact brushes, P (1) 12*h*.
device, vacuum-type, P (3) 62*b*.
element laminated in structure, P (10) 250*j*.
electrolytic, P (4) 87*e*.
energy storage device, with SiC or B_4C electrode, P (1) 12*i*.
high-power, high-frequency, P (8) 200*h*.
high-voltage source, P (4) 88*f*.
housings, oxide ceramic, (11) 274*b*.
image device, P (2) 40*e*.
image intensifier with emission multiplier, P (1) 12*f*.
inductors, variable, P (8) 203*a*.
integrated-circuit high-frequency, P (4) 88*e*.
$FeBO_3$, P (3) 65*g*.
isolation device, entrance-exit atm, P (6) 137*d*.
isolator, gyromagnetic, P (6) 137*h*.
laser frequency selector, P (1) 14*b*.
for light emission or reception, P (4) 87*e*.

Electronic equipment *(continued)*
light, nonvoltage sensitive indicator, P (9) 227*b*.
lightning arrester, P (4) 91*b*.
logic functional, new, (7) 167*a*.
made by double epitaxial solution regrowth, P (6) 137*b*.
micro-, heat transfer in, B (9) 240*d*.
micro-, hybrid packages, (3) 63*b*.
multilayer electrical components, P (9) 226*g*.
multiple-layer structures with magnetic domains, P (6) 138*f*.
multistation vacuum, P (9) 227*b*.
phase shifter, P (1) 14*f*.
ferrite, P (6) 139*h*; P (10) 252*d*.
ferrite wave guide, P (10) 250*c*.
photoarray package, face-bonded, P (3) 65*a*.
photoconductive recording member, P (8) 202*a*.
photoemitter, P (6) 139*a*.
photomasks, metal-coated glass, P (9) 226*j*.
photoreceptor, trilayered Se-doped, P (7) 170*g*.
photosensitive, P (9) 227*e*.
RC, thin film distributed, P (9) 228*a*.
recording head, P (11) 274*c*.
releasable mounting for, P (4) 90*h*.
resistance capacitance structure, P (1) 13*c*.
resistance elements, P (11) 274*f*.
Schottky barrier, planar, P (7) 170*d*.
with Se semiconductor heterojunction, P (3) 64*f*.
shielded-cathode mode bulk effect, P (2) 42*f*.
signal, audible, P (2) 39*b*.
spark gap devices, protective, P (11) 275*d*.
storage tube, P (4) 87*f*.
tape package for, P (2) 42*i*.
temp.-stabilized devices, P (2) 42*j*.
tetrode, stable *n*-channel, P (4) 90*j*.
thermal actuators, P (11) 276*a*.
vacuum process, P (7) 168*b*.
vibratory treatment, P (4) 91*c*.
vidicon structure, solid-state, P (9) 228*b*.

Electronics. See also *Electronic equipment.*
array, separating articles from, P (4) 89*b*.
capacitance values, adjusting, P (3) 65*c*.
ceramics, physics, B (2) 51*c*; B (7) 183*g*.
quality control in, (3) 63*e*.
raw powders for, (3) 62*h*.
small scale mfg., (2) 38*g*.
coaxial connector, glass insulated, P (3) 40*a*.
connection, W barrier, P (2) 43*a*.
leads, bonding, and bond strength, P (4) 89*d*.
materials, dissimilar, bonding, P (8) 200*c*.
handbook, semiconducting compounds, B (1) 27*f*.
semiconducting, B (6) 154*c*.
Si_3N_4, pyrolytic, (9) 224*c*.
micro-, ceramics in, (2) 39*j*.
electron and ion beams in, (11) 273*e*.
system, encapsulating, P (8) 201*a*.
modules, multilayer ceramic, (11) 273*f*.
multilayer structures, pressure-fusible tapes for, (6) 136*j*.
optoelectronic materials, physics, B (2) 51*j*.
ovonic research, (6) 136*g*.
package sealing, Au-Sn alloy for, (11) 273*j*.
photo-, processes in rutile, (5) 122*d*.
pinhole density, decrease in, (11) 273*g*.
printing, fine line, (11) 273*g*.
printing, rheology of pastes in, (11) 274*j*.
properties, of chalcogenide glasses, (6) 131*j*.
properties, of VO_2, (6) 147*d*, 148*e*.
prototype assembly for CerDip packaging, (11) 274*h*.
resists, inorganic, P (6) 139*g*.
state, in $Na_2Si_2O_5$ glass, (3) 57*b*.
states, of Mn^{2+}-activated phosphors, (9) 235*f*.
structure, of EuO, EuS, EuSe, and GdS, (6) 150*h*.
structure, of $LiCrO_2$, (8) 208*j*.
system for providing pump pulses, P (9) 228*d*.
tamping material, P (9) 228*d*.
trimming, of resistors, P (3) 64*i*.

Electrons, beam, P (10) 250*b*.
analysis of Na and F, (8) 205*a*.
apparatus, cathode for, P (4) 91*c*.
device for transmitting, P (1) 13*g*.
effect on transformations in glass, (11) 269*h*.
insulating material, P (3) 64*i*.
in microelectronics, (11) 273*e*.
use in crystal growth, P (4) 88*b*.
working, (3) 69*b*.
bombardment, glass defects formed under, (10) 243*e*.
bombardment, for polishing glass, (7) 158*c*.
discharge devices, P (2) 34*b*; P (8) 200*e*.
emissions. See *Emissions.*
hot-, distribution in *n*-GaAs, (6) 148*d*.
I_8 donor, in ZnO, (7) 181*a*.
irradiation, defects in alkali halides by, (10) 261*c*.
micrography, of SiO_2 films, (3) 75*g*.
multiplier device, P (2) 40*e*.
multipliers, glass (6) 132*c*.
scattering in V carbide, (7) 180*j*.
-spin exchange interaction, in semiconductors, (6) 148*g*.
state of O^{2-} atom in MgO, (4) 96*b*.
transport, in *n*-GaAs, (7) 180*f*.
trap in rutile, properties, (5) 122*h*.
tunneling in Al-Al oxide-metal systems, (6) 148*g*.
tunneling in Cd-Al_2O_3-Al junctions, (5) 120*b*.

Electrooptic, ceramic device, P (8) 202*e*.
dipoles, P (6) 138*h*.
effect, in Sr Ba NbO_3, plates, (3) 74*f*.
effects in $BaTiO_3$, dispersion, (5) 119*h*.
light modulation in $LiNbO_3$, (1) 11*e*.

Electrooptic *(continued)*
linear effects in phosphates and arsenates, (1) 11*c*.
system for inspecting tiles, P (10) 248*f*.
Electrophoresis, testing apparatus, P (10) 255*i*.
Electrophotography. See *Photography.*
Electrophysical properties. See *Physical properties.*
Electrostatic processes, coating, with conductive materials, P (5) 105*c*.
objects with atomized solids particles, P (2) 43*i*.
phosphor to TV tube, P (10) 244*e*.
dust separator, P (9) 230*a*.
effects in system K_2O-SrO-SiO_2, (9) 216*h*.
for enameled panels of appliances, (8) 189*c*.
fiber deposition, for C-C composites, (3) 54*f*.
glaze application, (4) 85*e*.
glaze to porcelain and ceramic, (11) 272*i*.
power spray systems, automatic, (7) 172*a*.
precipitation, at 1700°F, (4) 92*c*.
precipitator, P (9) 230*a*.
precipitators, collecting apparatus for, P (9) 229*h*.
separation, P (3) 69*e*.
of NiO, (9) 232*h*.
with photoelectric charging, (9) 229*e*.
spray gun, P (9) 230*a*.
spray gun nozzle and air cap, P (1) 254*j*.
spraying devices, P (7) 172*c*.
Elements, chemical, analysis, apparatus for, P (11) 278*g*.
heating. See *Heating elements.*
properties, (8) 207*j*.
trace, in limestone, (9) 232*j*.
trace, migration in kaolin deposit, (1) 20*b*.
tracer, in ruby laser crystals, (9) 230*h*.
Elutriation. See *Beneficiation.*
Emission, acoustic, of Al titanate, (2) 38*d*.
broad bands in Y_2O_3 and YVO_4, (2) 47*c*.
coeff., of high-melting compounds, (3) 73*a*.
edge bands, in CdS, (5) 120*b*.
electron, and Einstein photoelectric law, (4) 97*g*.
from Au-metal oxide cermets, (7) 167*i*.
thermal, of Y_2O_3, (7) 182*a*.
field, study of oxide layers on W, (11) 281*j*.
flame, in glass analysis, (8) 204*j*.
from glass mfg., control, (9) 216*j*.
ir, stimulated, device for producing, P (2) 40*b*.
optical, in $YCrO_3$ and $LuCrO_3$, (5) 121*f*.
photoelectron, from MOS, (5) 120*h*.
photo-, measurements in metal-Al_2O_3-Si system, (7) 178*a*.
photo-, studies of electronic structure, (6) 150*h*.
photon, for analyzing solid surface, P (6) 142*f*.
properties, of Y and Gd borides, (10) 260*j*.
radioactive, effect on electrical porcelain, (9) 224*a*.
stack, lasers to monitor, (11) 277*c*.
X-ray. See *X rays.*
Emissivity, properties, of W, (8) 199*i*.
of TiC at high temps., (8) 199*f*.
Emitters, electron, P (8) 200*a*.
electron, thin-film, room-temp., P (2) 43*b*.
photo-, group III-V compound, P (10) 251*e*.
semiconductor electron, P (9) 227*g*.
semiconductor electron, activating, P (9) 226*b*.
Emulsions, for binding pigments to glass fabrics, P (4) 81*g*.
Enameled ware, sink, self-rimming, P (2) 32*a*.
panels. See *Building materials.*
Enameling, appliances, color control in, (10) 242*g*.
electrolytic pretreatment before, (8) 188*i*.
equipment. See *Spraying.*
furnaces. See *Furnaces.*
grade steel, P (1) 31*j*.
hot water tank, (4) 79*j*; (5) 105*c*.
industry, German and American, (5) 105*e*.
institute, Australasian, B (2) 52*a*.
relation to lacquering, (1) 2*i*.
two-layer, by single stoving, P (11) 267*f*.
Enameling apparatus. See *Electrostatic processes; Furnaces; Spraying.*
Enameling metals, B (7) 183*f*.
alloy steel, treating, P (9) 216*a*.
art, teaching, (1) 2*a*.
drawing compounds for, (5) 105*a*.
effect of chemical methods on quality, (8) 188*h*.
pickling. See *Pickling.*
steel, new, (8) 189*b*.
sheet, gas reactions during, (8) 188*h*.
3-year inspection, (7) 157*h*.
substrates, P (5) 105*b*.
Enamels. See also *Coatings.*
for Al, (2) 31*h*.
application with electronic robot, (5) 105*b*.
CeO_2-containing, thermal expansion, (1) 8*a*.
chemical and mechanical corrosion, (11) 267*c*.
colored, applying to ferrous stock, P (6) 131*d*.
cover coat milling, P (3) 54*g*.
electrocoating, (3) 54*e*.
expansion coeff., (8) 188*j*.
frits. See *Frits.*
ground-coat, suppresses gas reactions, (8) 188*j*.
importance, (6) 131*a*.
$PbTiO_3$, for glass-ceramics, P (8) 193*d*.
microscopy, (1) 17*j*.
for self-cleaning cooking oven, P (9) 216*a*.
sheet steel, fracture radius, (11) 267*f*.
slips. See *Slips.*
on steel, 30-year exposure test, (1) 2*i*.
surfaces, chemical attack, (4) 79*j*; (11) 267*d*.
Enamels *(continued)*
surfaces, mechanical attack, (11) 267*e*.
systems. See *Systems.*
TiO_2-opacified, Fe-containing, P (9) 216*a*.
microstructure, (1) 2*i*.
scum prevention, (7) 157*h*.
Energy, activation, in glass, calculation, (4) 80*e*.
activation, relation to crystallization temp., (8) 189*e*.
barriers in creep of Ge and LiF crystals, (5) 147*e*.
bond, in alkali silicates, (4) 81*f*.
consumption, relation to kiln output, (2) 45*e*.
dissociation, of BaO in CO/N_2O flame, (5) 119*h*.
dissociation, of $MnCl_2$, (4) 96*c*.
domain-wall, in orthoferrites, (7) 177*e*.
electrical microwave, dielectric structure for dissipating, P (9) 225*g*.
electrochemical, conversion, (4) 86*f*.
of formation, of Nb oxides, (1) 21*i*.
of formation, of point defects in CaF_2 and UO_2, (6) 152*a*.
fracture, of ceramics, (2) 47*j*.
fracture surface, from cleavage analysis, (10) 259*h*.
fracture surface, of SiC, (10) 260*a*.
free, of formation, of $VNO_{0.465}$, (6) 147*h*.
free, of formation, of $VN_{0.465}$, (6) 147*h*.
fuel, and environment, (10) 256*e*.
Gibbs free, of formation of AlF_3, (11) 281*a*.
in glass industry, (5) 105*i*.
of grain boundaries, with computer, (5) 118*i*.
kV electron, dissipation vs penetration distance in solids, (7) 177*a*.
levels of Ce^{3+} in CaF_2, (6) 147*f*.
levels of Cr ion pairs in ruby, (5) 120*b*.
loss analysis, and electron microscopy of glass, (6) 131*h*.
materials for, development, (6) 136*f*.
MHD power generation, refractories for, (3) 63*e*.
solid-solid interfacial, calorimetry, (7) 176*c*.
storage in $BaTiO_3$-based ceramics, (7) 167*a*.
storage device, electrical, P (1) 12*i*.
storage device, solid state, P (1) 14*h*.
surface, of Al_2O_3 and graphite, (7) 157*h*.
of metals and refractories, (10) 259*e*.
of solids, bubble measurement, (5) 119*h*.
transfer in oxides (1) 21*j*.
in $SrZnP_2O_7$: UO_2^{2+}, (2) 47*h*.
in systems Mn-Nd, Mn-Ho, and Mn-Er in glasses, (3) 57*e*.
Engineering, fundamentals on fracture of materials, B (3) 76*e*.
precision, of nonmetals, B (9) 240*b*.
standards, U.S., index, B (2) 51*a*.
Enthalpy. See *Heat, content.*
Entropy, of Cu sulfate and Cu oxysulfate, (7) 177*b*.
during thermal transformations of aluminosilicate minerals, (2) 47*c*.
of sublimation of $MnCl_2$, (4) 96*c*.
Epitaxy. See *Crystallization.*
Equations, for grinding wheel, (2) 29*f*.
high-pressure, of state for NaCl, KCl, and CsCl, (6) 148*b*.
parameters, of tunnel diode, method for determining, P (8) 201*d*.
sintering, analysis, correction, (3) 72*d*.
of state for UC and PuC, (5) 114*j*.
Equilibrium studies. See also *Systems.*
computation for growth of α-SiC, (3) 73*e*.
concentration of vacancies in TiO, (3) 73*e*.
diagram, $Ca(PO_3)_2$-$NaPO_3$, (8) 209*h*.
high-temp., thermodnamics, (11) 283*a*.
phase, in glass system Na_2O-CaO-MgO-SiO_2, (11) 269*c*.
phase, of $NaAlSiO_4$-$CaCO_3$-H_2O, (1) 22*h*.
phase diagrams, cermets in, (5) 108*i*.
Ga-GaP-GaAs, (9) 235*f*.
Ge-Si-Sn and Ge-Si-Pb, (9) 238*c*.
lever rule for, (6) 147*g*.
Nb-C, modification, (6) 150*i*.
K_2O and K-K_2O, (7) 179*c*.
of $TeCl_4$-$TiCl_4$ and $TeCl_4$-$SbCl_3$, (8) 209*j*.
on reaction $4CaO(s) + 2P + 5H_2O(g) = 4CaO \cdot P_2O_5(s) + 5H_2(g)$, (3) 73*f*.
of V(C, N) C-rich solutions, (4) 96*d*.
Equipment. See *Machinery and equipment* and specific types.
Erbium, diorthogermanates, single crystals, (8) 211*c*.
$ErFeO_3$, exchange fields and Zeeman effect in, (5) 120*c*.
hydroxide, magnetic properties, (8) 209*j*.
orthochromite, Moessbauer effect of ^{166}Er in, (5) 122*c*.
orthotantalate, synthesis, (2) 50*a*.
sensitizing luminescence, (10) 245*g*.
systems. See *Systems.*
Esters, zeolite, P (11) 280*c*.
Etch, mask, sputter, P (6) 140*h*.
pits, on Ag surfaces, (7) 182*a*.
Si, low-temp., P (9) 225*h*.
thermal, patterns, on SiC crystals, (3) 76*a*.
Etchants, for etching patterns in SiO_2 layers, P (9) 225*g*.
for treatment of semiconductor wafers, P (1) 12*b*; P (2) 43*a*.
Etching, acid, of glass, (4) 80*d*.
completion indication, P (5) 112*a*.
composite layered structures, P (1) 14*e*.
dislocation, of $GaAs_{1-x}P_x$ layers, (7) 179*i*.
electrochemical, of capacitor defects, P (6) 137*c*.
electrodes, P (9) 225*h*.
etched patterns, P (5) 114*a*.
Etching *(continued)*
gas plasma vapor process, P (2) 40*i*.
gaseous nonpreferential, of Si, P (10) 250*f*.
glass plate face, P (2) 33*b*.
of insulating layers, for semiconductor devices, P (2) 40*g*.
PbS whiskers, (7) 177*h*.
mask, oxide films as, P (2) 40*f*.
method for semiconductor device, P (8) 201*c*.
photo-, of metal oxide layers, P (2) 41*j*.
on KBr single crystals, (7) 182*b*.
selective, P (2) 41*b*.
selective electrolytic, semiconductor devices by, P (2) 41*h*.
semiconductor bodies, P (10) 249*f*, 251*j*.
semiconductor body surfaces, P (6) 139*g*.
shadow mask, P (9) 227*j*.
sputter, P (3) 64*e*; P (10) 253*d*.
sputter, end-point detection, P (9) 225*g*.
of Te single crystals, (7) 176*d*.
thin-film materials, P (8) 201*f*.
Sn oxide, P (9) 228*b*.
variable depth, of film layers, P (6) 140*d*.
of ZrO_2 crystals, (5) 121*b*.
Ethylene, di-, glycol, effect on cement properties, (4) 78*f*.
Ettringite, stability on heating, (2) 31*c*.
Europium, aluminate, anisotropy and crystal-field splittings in, (5) 122*a*.
Cr-Eu pair emission in, (5) 118*f*.
photoluminescence, (9) 237*e*.
chalcogenides, optical properties, (9) 237*f*.
Eu^{2+}, in CaF_2, spin-lattice coeff., (5) 124*d*.
luminescence in phosphate compositions, (9) 236*d*.
in ThO_2, ESR spectrum, (6) 147*c*.
Eu^{3+}, fluorescence in Na borate glass, (7) 159*b*.
in oxysulfides, fluorescence, (4) 96*j*.
spectra in Gd_2O_3, (5) 124*b*.
uv absorption band in oxides, (8) 211*e*.
vibronic transitions in $CaWO_4$, (3) 76*a*.
Eu_2TiO_4 and $Eu_3Ti_2O_7$, crystal chemistry and magnetic properties, (9) 234*e*.
monoxide, conductivity, (9) 239*a*.
EuS, EuSe, and EuTe single crystals, (7) 177*i*.
thin films, deposition, (7) 168*b*.
oxide, EuS, and EuSe, electronic structure, (6) 150*h*.
EuS, EuSe, and EuTe, magnetic ordering effects in, (9) 237*g*.
films, P (5) 114*d*.
films, with magnetic exchange, P (10) 250*b*.
magneto-optical Kerr effect, (6) 148*h*.
reflectance, splittings in, (6) 151*j*.
sound propagation in, (6) 151*h*.
thermomagnetic writing on, (5) 124*j*.
sensitizes Tb fluorescence in CaF_2, (9) 237*f*.
sulfide, photoconductivity and magnetoresistance, (3) 76*a*.
systems. See *Systems.*
Evaporation, evaporator, Cs, P (6) 137*h*.
high-temp., of Cm_2O_3, (6) 148*c*.
plasma, for Al_2O_3 ultrafine powders, (7) 175*e*.
of NaCl melts, (7) 177*e*.
vacuum-arc, of ferrites (3) 64*a*.
Exciton, absorption lines in $DyCrO_3$, (4) 96*f*.
mixed-mode, in ZnO photoluminescence, (6) 150*c*.
role in Cu_2O luminescence, (6) 151*d*.
Expansion. See also *Dilatometers.*
coeff. of optical index in solids, P (3) 70*a*.
of feldspathic and feldspathoid fluxes, (1) 26*a*.
of glass. See *Glass.*
incipient, in Kansas volcanic ash, (3) 71*c*.
moisture, in brickwork, (1) 6*d*.
moisture, of fired clay, (9) 229*i*.
of portland cement pastes, (10) 241*i*.
of Ag_2O lattice by annealing, (2) 47*g*.
thermal, of As-S glasses, (3) 57*b*.
of As-S-Te glasses, (3) 57*c*.
axial, of HfO_2, (10) 258*c*.
calculation for $Na_2Si_2O_5$ glass, (3) 57*b*.
of CeO_2-containing enamels, (1) 8*a*.
of Cs minerals, (6) 152*h*.
of $CrVO_4$, (7) 181*d*.
of clay ceramics, (1) 17*j*.
coeff., of alloyed Ce_2S_3, (10) 258*d*.
control, (1) 2*h*.
and crystal structures, (2) 47*h*.
of earthenware green bodies, (5) 111*c*.
of electrofused Al_2O_3, (2) 44*i*.
of enamels, relation to properties, (8) 188*j*.
of graphite-bromine compounds, (2) 49*c*.
in Hf and Zr titanates, (9) 239*c*.
linear, of ZrV_2O_7, (11) 283*d*.
of Nb_2O_5, (8) 211*a*.
of optical materials, (10) 243*a*.
of porcelain bodies, (5) 111*f*.
of silicate glasses, (9) 216*g*.
$(Na_{0.88}\ Li_{0.12})NbO_3$+6 mol% Li_2O ceramic, (1) 26*d*.
of WO_3 phase, (8) 211*j*.
X-ray diffraction measurement, (7) 173*g*.
Extraction, conversion/, efficiencies, for particles, (6) 141*d*.
Extruders, P (8) 203*i*.
disk, P (8) 203*i*.
Extrusion. See also *Dies.*
apparatus, P (9) 230*b*.
continuous mfg., P (11) 277*g*.
of expandable materials, P (11) 277*d*.
of hard shale, (1) 6*b*.
hydrostatic apparatus, P (7) 172*d*.
hydrostatic, of compound material, P (11) 277*b*.
of parisons and tubes, P (9) 230*b*.
of very long hollow products, P (9) 221*b*.

Faraday, effect in $CdCr_2Se_4$, (9) 236*h*.
-effect element, P (4) 81*g*.
rotation, in artificial dielectrics, (5) 111*j*.
in birefringent crystals, (5) 120*f*.
in $FeBO_3$ at 77°K, (3) 73*h*.
studies of MgO, (5) 120*h*.
Fatigue, behavior of Al_2O_3, polycrystalline, (5) 124*e*.
behavior of high-Al_2O_3 ceramics, (1) 22*i*.
properties of enameled Armco Fe, (5) 105*b*.
properties of steels, (7) 157*h*.
of silicate glasses, (1) 3*c*.
SiC resistance to, (6) 134*i*.
static, chemical interpretation, (3) 72*f*.
of glass, (1) 3*d*.
of graphite, (1) 25*g*.
testing on shear pins, P (6) 142*c*.
Faujasite, high-SiO_2, P (5) 117*h*.
high-SiO_2 synthetic, P (9) 233*d*.
Na, synthesis P (5) 118*b*.
synthetic, P (5) 118*a*.
Feeding apparatus, and batchers, of loose materials, control, (8) 203*i*.
for ceramic ovens, P (2) 45*f*.
for grinding media to mill, P (10) 254*j*.
for liquid and solid material, P (9) 229*g*.
Feldspars, albite, superheating, (4) 94*f*.
effect on cement clinker burning, (4) 79*a*.
sintering, (11) 282*b*.
source, Mississippi river sand, (3) 71*d*.
Ferric, Ferrous, etc. See *Iron*.
Ferric oxide. See *Iron, oxide, ferric*.
Ferrimagnetic, films, single-crystal, P (1) 14*c*.
semiconducting material and devices, P (5) 112*b*.
Ferrites, P (4) 87*h*.
Ba, P (4) 90*e*.
Ba, powders, magnetic properties, (10) 249*b*.
Ba-Sr, magnetic and ceramic properties, (8) 199*b*.
body, anisotropic spinel, P (3) 65*i*.
Ca, for making steels, P (6) 135*d*.
composite, P (6) 138*h*; P (8) 201*c*.
density and structure, (9) 223*h*.
dicalcium, sinter, P (9) 222*a*.
dielectric properties, (3) 62*d*.
evaporation, vacuum-arc, (3) 64*a*.
extracted phase, (4) 79*c*.
head, P (3) 65*i*.
head, mounting, P (5) 113*a*.
heat-transfer apparatus for making, P (4) 88*d*.
hexa-, crystal growth and bubble domain properties, (2) 47*f*.
hexagonal, coprecipitating, P (4) 88*e*.
Li, composition, P (5) 113*a*.
-Cr, Moessbauer measurements in, (7) 178*j*.
for magnetic memory elements, P (2) 40*g*.
for microwave latching, (5) 111*h*.
powders, P (1) 13*e*.
Ti Bi, P (4) 88*a*.
-Ti-Zn, P (6) 138*d*.
-Zn composition, P (5) 113*b*.
-Zn, Moessbauer effect in, (4) 86*d*.
Mg, cation ordering in, (1) 23*g*.
electron diffraction superlattice lines in, (2) 47*b*.
-Mn, crystal structure and properties, (8) 208*h*.
magnet, permanent, (2) 38*d*.
magnetization precession in, (7) 167*g*.
Mn, heat treatment, (9) 234*i*.
Mn-Zn, from Fe oxides, (10) 249*d*.
ferrous, magnet core from, P (6) 138*f*.
relation of Fe_2O_3 particle size to properties, (1) 11*i*.
sintered, heat-treating, P (7) 168*j*.
mfg., (6) 136*g*.
material properties in, (7) 167*j*.
materials, P (8) 200*d*.
Ni, Sc-containing, (10) 249*g*.
Ni-Zn, creep behavior, (5) 111*i*; (6) 146*d*.
hot-pressing, (3) 63*a*.
internal friction, (6) 152*j*.
permeability and temp. coeff. changes in, (7) 167*b*.
0 anisotropy in, (2) 38*j*.
Ni-Zn-Co, heat treatment, P (2) 40*j*.
noise, in audiomagnetic recording head, (4) 86*f*.
ortho-, crystalline rare earth Fe, P (2) 40*i*.
domain-wall energies in, (7) 177*e*.
in magnetic element, P (6) 138*h*.
rare earth, anisotropy, (7) 176*g*.
rare earth, magnetic properties, (2) 38*i*.
rare earth, preparation, (6) 136*j*.
Yb and Sm-Tb, single crystals, (2) 48*b*.
uv magneto-optical properties, (6) 152*i*.
particles, light polarization in, (6) 151*b*.
phase, separated from cement clinkers, (9) 215*d*.
physicochemical transformations in, (8) 199*f*.
polycrystalline, elastic moduli, (11) 281*f*.
polycrystalline, internal friction, (3) 62*c*.
powder, P (4) 87*i*.
properties, (9) 223*i*.
sintering, magnetic ceramics formed during, (9) 224*b*.
by powder metallurgy, (2) 38*d*.
preintering, rotary kiln for, (10) 249*f*, 256*g*.
radar-absorbing material, P (8) 200*d*.
recording heads, with glass, P (10) 245*c*.
residue arithmetic unit, multiaperture, P (2) 41*f*.
Sr, magnetic and ceramic properties, (8) 199*d*.
Sr, sintering and magnetic properties, (7) 167*e*.
Ferrites *(continued)*
surfaces, plane, plane waves through, (4) 86*i*.
Zn-Mg-Perminvar-, (2) 39*e*.
Zn-Ni, Yafet-Kettel angles in, (5) 125*i*.
Ferroelastic, effect in $RbFeF_4$ and $CsFeF_4$, (11) 281*i*.
Ferroelectric materials. See also *Barium, titanate; Ferroelectricity*.
ceramic, P (9) 225*j*.
colemanite, bias fields in, (2) 50*b*.
composition, P (9) 225*a*.
fine-grain, for optical memory, P (2) 41*g*.
$LiH_3(SeO_3)_2$, neutron diffraction study, (10) 259*b*.
new, P (5) 113*d*.
oxyfluorides, phases, (8) 210*i*.
physicochemistry of systems for, (5) 122*d*.
Ferroelectricity. See also *Barium, titanate; Ferroelectric materials*.
activity, and glass-forming tendency, (8) 190*i*.
anti-, transitions in $NH_4H_2PO_4$ and $NH_4H_2AsO_4$, (5) 118*i*.
applications and properties, (7) 167*d*.
$BaTiO_3$ compositions, Fe-substituted, P (2) 40*f*.
in Bi oxide-type layer structure compounds, (2) 38*h*.
ceramics, aging in, (2) 38*j*.
composition, P (5) 112*b*.
devices, P (8) 202*e*.
in energy conversion, (1) 10*j*.
optical shutter, P (2) 40*h*.
compositions in system $Pb(Zn_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$, (8) 209*c*.
displacement, statistical theory, (5) 124*f*.
displacive, powder Raman spectra, (2) 38*d*.
domains, enhanced ordering in PLZT, (6) 136*i*.
domains, reorientation by abrasion and annealing of $BaTiO_3$, (8) 211*a*.
films, by sputtering process, P (10) 253*d*.
H-bonded, (5) 125*j*.
in $Pb_5Ge_3O_{11}$, (3) 73*h*.
$PbTi_{0.2}Zr_{0.8}O_3$ and antiferroelectric $PbZrO_3$, (7) 178*i*.
phase of $PbZrO_3$, (8) 199*b*.
and piezoelectric composition, P (4) 87*i*.
polarizable ceramic compositions, P (4) 90*a*.
KH_2PO_4, proton dynamics in, (5) 122*j*.
storage device using $GdMoO_4$, P (3) 65*a*.
transition, in RbH_2AsO_4, (5) 123*d*.
with W bronze structure, (7) 167*g*.
Ferromagnetic materials. See also *Ferromagnetism*.
P (7) 168*i*.
anti-, oxides, susceptibility, (4) 81*c*.
Cr oxide, P (4) 94*h*.
metal powders, P (8) 202*e*.
sintered oxidic body, P (9) 226*e*.
Ferromagnetism. See also *Ferromagnetic materials; Magnetic materials*.
articles, coating, P (4) 89*d*.
domain, formation in $V_{2-x}Cr_xO_3$, (11) 281*f*.
domains, observation by SEM, (7) 179*g*.
magnetic phase transitions in, (6) 149*i*.
relaxation of magnons in, (6) 151*c*.
storage cores, P (5) 112*c*.
thermodynamics, (6) 148*i*.
uniaxial, phase transitions, (4) 96*g*.
Wallace's statistical perturbation method, (6) 148*f*.
$YFeO_3$, susceptibility tensor, (5) 124*h*.
Fibers, acrylic, carbonization, P (10) 248*e*.
acrylic polymer stabilizing, P (9) 222*b*.
-aligning apparatus, P (3) 61*e*.
AlN, (7) 164*g*.
Al_2O_3, P (4) 86*b*.
Al_2O_3-SiO_2, for furnace lining, (8) 194*j*.
A, in asbestos-cement ware, (10) 241*g*.
in asbestos cement, corrosion, (11) 266*h*.
asbestos, corrosion, (6) 128*e*.
length and diam. measurement, (8) 205*b*.
material, P (9) 222*d*.
product, P (6) 144*c*.
B-C, P (10) 248*c*.
BN, high-modulus, P (9) 222*h*.
in insulating sheet, P (10) 247*h*.
mfg., P (3) 61*b*.
carbides, nitrides, or borides of Ti and Zr, P (8) 196*j*.
C, P (2) 37*a*; P (5) 109*j*; P (7) 164*b*; P (8) 196*g*; P (9) 222*e*; P (10) 248*a,b*.
coated with pyrolytic graphite, (5) 108*i*.
in composite materials, P (10) 247*e*.
embedded in glass matrix, P (10) 247*d*.
and glass, apparatus for coating, P (6) 131*f*.
or graphite, use in composites, P (9) 222*i*.
internal structure, (5) 119*f*.
by Kureha process, voids in, (5) 109*e*.
NRDC study, (4) 100*a*.
oxidative heat treatment, P (5) 110*a*.
reinforcement of cement, (7) 156*d*.
reinforcement for composite, P (10) 247*g*.
strength, (2) 49*f*.
tapes, continuous, P (9) 222*c*.
treatment, P (8) 197*b*.
voids in, (6) 135*c*.
carbonaceous induction furnace for, P (8) 196*b*.
carbonized products, P (8) 196*i*.
catalyst-coated, dispensing, P (10) 243*f*.
cellulose, carbonized, P (5) 110*b*.
ceramic, in annealing furnace, (2) 37*b*.
ceramic, preparation and properties, (9) 221*g*.
Ce phosphate, positively charged, P (2) 46*b*.
clad, refractive index in, (8) 190*d*.
classifying, by wet process, P (4) 92*g*.
Fibers *(continued)*
composites, P (7) 164*h*.
-containing plaster products, P (11) 267*c*.
cross-sectioning techniques for SEM, (2) 44*f*.
diameter, device for measuring, P (3) 70*h*.
drawing, continuous, P (7) 164*b*.
electrostatic deposition, for C-C composites, (3) 54*f*.
fiberizing molten mineral materials, P (9) 219*i*.
and filaments from melts, P (8) 193*j*.
and filaments, multicomponent, P (10) 254*h*.
glass. See also *Glassmaking apparatus; Mineral wool*.
P (3) 59*c*; P (7) 162*i*.
adhesion of polymeric binders, (7) 158*b*.
apparatus for, P (3) 57*g*.
apparatus for advancing, P (9) 218*c*.
articles, P (10) 243*g*.
articles, applying transfers, P (8) 193*b*.
base, for plates or shaped sheets, P (2) 34*a*.
binding pigments to, P (4) 81*g*.
bonded with terpolymer, P (2) 34*d*.
bundles, for reinforcement, P (3) 59*h*.
cables, P (8) 193*a*.
chemical treatment, P (3) 59*f*.
clad, (1) 3*c*.
coated, P (9) 220*a*.
coated strand, P (10) 245*d*.
coated with vinyl polymers, P (7) 162*i*.
coating, P (10) 244*j*.
coating method, P (6) 132*h*.
composite articles with, P (5) 107*d*.
composition for, P (3) 58*f*.
container, P (10) 244*i*.
continuous bundle, P (7) 162*d*.
continuous, in mat, P (2) 33*c*.
controlling diameter, P (7) 162*h*.
conveying and forming, P (11) 270*e*.
cooling means of Pd, P (6) 132*i*.
creased blanket, P (2) 34*d*.
curly, P (7) 161*h*.
with dissimiar densities, P (7) 162*c*.
drawing mechanism, DTA, (7) 159*d*.
drying chamber, P (10) 244*f*.
duct, jacketed, P (7) 162*e*.
elastomer-coated, P (3) 58*g*.
with environmental control, P (6) 133*i*.
expanded strand, P (1) 4*a*.
fabric for drapery, P (2) 34*d*.
fabric, reinforcement for concrete, (9) 213*j*.
filamentizing process for, P (4) 81*h*.
finished materials, P (7) 161*e*.
finishing composition, P (8) 193*a*.
first stage filter, P (11) 270*f*.
forming apparatus, P (1) 4*f*.
forming packages, drying, P (2) 34*c*.
forming and supply package, P (10) 244*i*.
furnace for, P (10) 244*h*.
hollow hammer handle with, P (7) 161*g*.
impregnated with polymers, P (7) 161*i*.
injection molding, P (6) 132*d*.
integrated mass, P (10) 245*b*.
laminated structure, P (5) 107*c*.
laminates, P (3) 58*h*; P (10) 244*f*.
light-transmitting, P (1) 4*a*.
making, measuring tension in, P (7) 161*g*.
mat, P (3) 59*b*, P (11) 270*j*.
mats and bats, P (9) 219*c*.
from melt by centrifugation, (4) 80*i*.
microporous, P (7) 162*c*.
molded surfacing unit, P (2) 34*h*.
molten material into, P (4) 82*a*.
NRDC study, (4) 100*a*.
as optical transmission line, (6) 132*a*.
pads or mats, P (2) 34*g*.
and phenolic binder, moldable article, P (2) 34*h*.
pipe winder, fiber band regulator for, P (1) 4*a*.
plastic tubes, P (3) 59*c*.
plate, for optical focusing, P (8) 192*f*.
plurality, P (7) 161*g*.
in polyimide composites, P (1) 5*d*.
preform, P (7) 161*e*.
pretreating, P (11) 270*h*.
process and apparatus, P (7) 162*g*.
products, standards, (4) 81*f*.
-reinforced composite, P (9) 219*c*.
-reinforced elastomers, P (10) 244*j*.
-reinforced plastic tubes, P (4) 81*i*.
-reinforced thermoplastics, P (7) 162*b*; P (11) 270*j*.
reinforcing, in cement, (8) 191*a*.
and resin coatings, P (3) 59*e*.
rods, attachments to, P (8) 193*i*.
size, P (7) 161*h*.
sized, P (10) 244*j*.
with soil release chemicals, P (3) 59*g*.
starch-coated, P (2) 35*c*.
strength, (2) 32*g*; (8) 191*h*; (9) 217*d*.
S-, strength, (11) 269*j*.
staple body, P (11) 270*b*.
strand mat, air blown, P (10) 245*d*.
structure and strength, (3) 57*i*.
structures, P (10) 245*b*.
tape, semiconducting, P (5) 107*d*.
from thermoplastic materials, P (6) 133*j*.
from thermoplastics, P (4) 82*b*.
treated with sizing composition, P (7) 163*a*.
treating, P (11) 270*g*.
webs, P (3) 58*i*.
graphite, P (4) 84*i*; P (8) 196*h*.
heat treatment, P (4) 84*a*.
for plastic reinforcement, P (4) 84*d*.
-reinforced laminates, P (6) 135*h*.
uniform, P (4) 84*i*.
heat-resisting, use in composites, (10) 246*g*.
insulating materials, P (6) 135*h*.

Fibers *(continued)*
Fe, C-containing, properties, (10) 247*d*.
light-conducting, fused bundles of, P (3) 59*e*.
metal, and composite materials, (8) 195*j*.
metal oxide, flexible and strong, P (8) 196*d*.
optic, bundle fusion, P (3) 58*a*.
bundle, termination for, P (10) 244*e*.
conduit, P (9) 219*c*.
core glass P (7) 161*d*.
devices, P (10) 244*g*.
element, P (3) 58*b*.
flexible conduit, P (3) 58*b*.
glass, La borate, P (2) 34*j*.
guides, in glass inspection apparatus, P (5) 107*h*.
illuminated, P (10) 245*a*.
Indian glasses for, (7) 161*a*.
light modulation in, P (6) 133*e*.
light, for X-ray collimator, P (4) 83*b*.
output faceplate assembly, P (4) 87*j*.
ribbons, monofilament, P (1) 3*f*.
stacks, P (1) 4*b*.
and vacuum tube devices, P (10) 244*c*.
optical bundles, P (1) 3*g*.
controlling light propagation in, P (3) 57*f*.
for image-transfer devices, P (2) 34*f*.
leachable bundle, P (7) 162*f*.
photochromic glass for, P (4) 82*g*.
plate, coupling in TV tube, P (5) 112*c*.
plates, plastic, P (9) 219*a*.
polymeric, P (10) 257*h*.
refractory BN, P (4) 85*a*.
extrudable, P (9) 222*d*.
for strengthening metals, (11) 271*h*.
-reinforced ceramics, P (1) 4*b*.
reinforcement of materials, (4) 83*j*.
siliceous, for reinforcement, P (3) 59*g*.
Si compound, P (5) 107*c*.
sorting, P (10) 254*j*.
spinning, nonisothermal, (9) 218*d,e*.
staple, web or mat, P (11) 277*b*.
treatment, P (8) 203*f*.

Filaments. See also *Fibers, glass.*
assembly, evaporation, P (2) 40*f*.
borocarbon-coated, P (3) 61*b*.
B, BN-coated P (4) 84*g*.
low-twist tensioning, P (4) 84*c*.
surface preparation on, P (3) 61*f*.
C, P (3) 61*f*; P (8) 196*c*.
high strength, P (1) 9*a*.
from low-priced pitches, P (4) 84*j*.
warp sheet with, P (8) 196*f*.
by centrifugal forces, P (6) 133*j*.
coated. high-strength high-modulus, P (9) 222*e*.
and fibers, multicomponent, P (10) 254*h*.
filamentizing, of glass fibers, P (4) 81*h*.
formation in As-Te-Ge glass, (6) 131*i*.
glass, P (1) 3*h*; P (2) 33*c*.
coating, P (10) 243*j*.
E, stress corrosion in, (9) 217*h*.
inorganic, and ribbons, growth from melt, P (7) 172*d*.
mono-, BSi, P (1) 9*a*.
-protecting device, P (3) 58*b*.
SiC, P (8) 196*j*.
SiC, stoichiometric, P (3) 61*c*.
structure, with B filaments, P (10) 247*h*.
from vitreous material, P (3) 59*a*; P (11) 270*d*.

Films. See also specific types.
alkali halide, deposited at low temps., (1) 25*a*.
amorphous, (6) 136*i*.
amorphous, anodic preparation, (7) 166*e*.
applying to substrate surface, P (9) 226*c*.
ceramic or glass, on substrate, P (3) 65*e*.
dielectric, thickness monitoring and control, P (2) 40*c*.
electrically conducting, (2) 38*e*.
forming, apparatus for, P (5) 112*e*.
growing, apparatus for, P (5) 112*f*.
insulating, by rf sputtering, P (3) 67*g*.
layers, variable depth etching, P (6) 140*d*.
metallic oxide, on substrate, P (9) 226*d*.
organic, removal from substrate, P (9) 227*c*.
photoresist, removal, (3) 63*a*.
properties, of silicate glasses, (9) 216*j*.
refractory laminar, (5) 112*b*.
resistive, P (1) 13*f*.
on substrate surface, P (7) 170*e*.
thick, consistent results with, (3) 62*d*.
thickness, measuring, P (1) 18*d*.
thin, and applications, B (10) 264*i*.
chalcogenide, electrical measurements, (6) 137*d*.
deposition, mechanism for, P (3) 65*a*.
deposition on substrates, P (7) 169*f*.
electromigration in, (7) 168*f*.
electromigration damage in, (5) 111*j*.
electrothermal instability in, (7) 160*c*.
etching, P (8) 201*f*.
EuO, sputter deposition, (7) 168*b*.
insulating, for transducer, P (4) 89*c*; P (7) 169*h*.
memory, thermal crystallization, (8) 192*a*.
metal, by electroless process, P (9) 218*j*.
oxide, on Ta, (7) 179*i*.
patterns, P (3) 66*i*.
Sn-C, composites, P (3) 61*f*.
ZnO, sputtered, *c*-axis orientation, (7) 166*g*.

Filters, acousto-optic light, P (7) 170*i*.
adjustable knife blade for, P (6) 141*g*.
air, with increased surface area, P (1) 16*i*.
asbestos fiber P (6) 144*c*.
broad-band high-frequency, P (2) 39*d*.
cake, retaining and dislodging, P (7) 172*e*.
cake, steam drying, P (10) 254*f*.
CsI interference, P (2) 33*g*.
cloth, for dust extraction, (5) 115*d*.

Filters *(continued)*
continuous rotary, for slurries, P (2) 44*d*.
for dust-laden gases, P (5) 115*g*.
electromechanical, P (2) 40*d*.
element for upright filter press, P (7) 172*c*.
energy trapped type ceramic, P (7) 169*b*.
fiber glass first stage, P (11) 270*f*.
gas or liquid, P (7) 172*d*.
glass, antidazzle, P (7) 162*i*.
glass-plastic laminated, (8) 191*c*.
leaf core, P (3) 69*e*.
liquid, for fine clay particles, P (11) 277*b*.
magnetic, device for cleaning, P (4) 92*b*.
microminiaturized microwave, P (10) 253*c*.
monolithic crystal, P (10) 262*e*.
piezoelectric ceramic, P (5) 113*i*.
band-pass, P (3) 66*g*.
elements, P (3) 66*c*.
for radioactive materials, P (6) 141*f*.
rotary, drum, P (10) 254*i*.
and operation, P (3) 69*g*.
vacuum drum, P (4) 92*h*.
vacuum, noncellular, P (5) 115*h*.
for suspended solids and filter cake removal, P (1) 16*i*.
temp.-indicating dispersion, P (10) 245*h*.
tobacco smoke, microporous glass for, P (4) 82*i*.
wide band stop band, P (9) 228*d*.
YIG, temp.-independent, P (6) 140*a*.
YIG, tuning with circuit, P (9) 224*j*.

Filtration, of concrete pipe, (6) 129*b*.
pressure or centrifugal, (4) 92*f*.
ultra-, of electrodepositable compositions, P (8) 194*d*.
and electrodialysis of electrodeposition bath, P (8) 192*e*.
ion exchange, P (8) 193*e*.
treatment by reverse osmosis, P (8) 194*c*.

Fine ceramics. See *Whiteware.*

Firebrick. See *Refractories.*

Fireclay. See *Refractories.*

Firing. See also *Burners; Calcination; Combustion; Flames; Furnaces; Kilns; Sintering.*
atm, effect on diffusion in ZnS, (7) 180*h*.
behavior of C bodies, (9) 221*g*.
brick, changes during, (4) 83*e*.
cement clinker, automatic control, (8) 185*i*.
ceramic, recent developments, (2) 43*j*.
coarse and fine ceramics, (11) 276*i*.
effect on efflorescence in bricks, (4) 83*f*.
gas, structura. clay products, B (10) 263*e*.
open, of sanitary ware, (7) 165*h*.
porcelain, by natural gas or propane, (2) 45*f*.
in pottery industry in India, (11) 272*j*.
pottery, supporting structures for, P (11) 272*g*.
rapid, (2) 43*g*.
effect on porcelain structure, (7) 165*h*.
in France, (2) 43*h*.
in Germany, (2) 43*h*.
in walking-beam kiln, (2) 45*e*.
temp., effect on Dutch clay product, (4) 83*h*.

Fission products, in fuel particle coatings, (5) 114*h*.
gaseous, in UO_2, simulation, (8) 203*e*.
inclusions in U-Pu carbide, (7) 171*h*.
noble metals, extraction from nuclear fuels, P (10) 253*j*.

Flame photometry. See *Photometry.*

Flames. See also *Burners; Firing.*
emission, B (1) 26*j*.
spectroscopy, spectral lines, B (1) 27*e*.
working, mineral bodies, P (2) 46*i*; P (8) 203*j*.

Flaws. See *Defects.*

Flocculation, of kaolin suspensions, (2) 46*a*.
of kaolinite by polyacrylamide, (2) 37*h*.

Flotation. See also *Beneficiation.*
of fluorite, P (3) 71*g*.
reagent, of borax, P (4) 95*b*.
and sedimentation apparatus, P (10) 254*i*.
studies of Tenn. phosphates, (7) 175*c*.

Flow, fluid, measurement systems, P (10) 255*j*.
measuring devices for cement mortars, (4) 78*i*.
of particles, measurement, P (5) 116*f*.
study of glass in model tank, (7) 159*j*.
technique, in high output dryers, (2) 45*f*.

Flue gases. See *Gases.*

Fluidization, apparatus, P (6) 141*h*.
of particulate material, P (11) 277*g*.
of pulverant materials, P (2) 43*i*.

Fluids. See also *Liquids.*
flow machines, rotary elastic, P (10) 254*c*.
flow measurement systems, P (10) 255*j*.
fluidics, using to control blending, (10) 254*g*.
separating particles from, P (11) 277*c*.

Fluorapatite. See *Apatite,* fluor-.

Fluorescence, of BaO, laser-induced, (5) 121*g*.
of Dy^{3+}, Eu^{3+}, Sm^{3+}, and UO_2^{2+} in Na borate glasses, (7) 159*b*.
Eu SrCl₂ phosphate composition, P (4) 87*g*.
macroscopic fluorescing material, ruby as, (1) 11*j*.
properties, of alkaline earth oxyanions, (2) 47*i*.
spectrum, of Eu^{3+} in oxysulfides, (4) 96*j*.
of $SrTiO_3$, domain structure effect, (7) 177*g*.
in $SrZnP_2O_7:UO_2^{2+}$, (2) 47*h*.
Tb, in CaF_2, photosensitization by Eu, (9) 237*f*.

Fluorides. See also *Glass.*
adsorption on ThO_2, (9) 233*d*.
double, synthesis and crystallization, (6) 146*e*.
hexa-, of metals with elpasolite structure, (6) 148*b*.
mineralizers, effect on Al_2O_3 sintering, (8) 195*c*.
oxy-, ferroelectric, phases, (8) 210*i*.

Fluorides *(continued)*
rare earth, P (2) 46*d*.
rare earth, flux growth, P (9) 232*g*.
sulfo-, of rare-earth metals, crystallochemistry, (10) 255*i*.

Fluorination, of H_3BO_3 and $H_3(HPO_3)$, P (4) 94*h*.

Fluorine, effect on glass crystallization, (6) 131*h*.
electron beam analysis, (8) 205*a*.
in fluorspar, cryolite, and fluorine compounds, (10) 255*a*.
in glass, rapid analysis, (11) 278*a*.
recovery from phosphatic solutions, P (3) 72*b*.
or volatile F compounds, P (11) 280*b*.

Fluorite, flotation, P (3) 71*g*.
oxides, ionic conductivity and nonstoichiometry in, (9) 238*e*.
phase in system CeO_2-ZrO_2-CoO, (11) 282*j*.

Fluorosilicic acid, concentrating, P (6) 143*j*.

Fluorspar, fluoboric acid from, (7) 175*e*.

Fluxes, feldspathic and feldspathoid, vitrification and expansion, (1) 26*a*.
heat, glass-mold, (2) 32*c*.
low-temp., for cast tiles, (8) 197*f*.
welding. See *Welding.*

Fly ash. See *Ash.*

Forsterite. See also *Refractories.*
dark, ceramic composition, P (6) 137*j*.
monticellite solubility in, (1) 25*e*.

Fracture, of brittle epitaxial films, (6) 136*j*.
of brittle materials, (7) 178*e*.
of ceramic crystals, press-forged, (3) 72*e*.
of C fiber polyester composites, (7) 163*h*.
of cement mortar, (6) 128*d*.
energies, of ceramics, (2) 47*j*.
energy, of Na borosilicate glass-Al_2O_3 composite, (1) 3*d*.
engineering fundamentals and environmental effects, B (3) 76*e*.
fatigue, in MgO single crystals, (2) 48*e*.
of fiber-reinforced concrete, (10) 241*g*.
of glazed porcelain, (1) 10*a*.
and healing effects in mica crystals, (10) 259*h*.
impact, in glass-reinforced plastics, (5) 105*i*.
internal, of glass, (4) 80*e*.
obstacles and dynamics, (6) 145*a*.
process, quantum tunneling as, (5) 123*a*.
radius of sheet steel enamels, (11) 267*f*.
of strengthened glass, (3) 56*d*.
studies of set cement paste, (11) 266*h*.
thermal, of sleeve bricks, (1) 8*e*.
thermal-stress of aluminosilicate ceramic, (5) 125*c*.
of CaS, role of $Ca(OH)_2$ in, (7) 156*b*.
of UO_2, effect of porosity, (4) 91*g*.

Freeze-drying. See *Drying.*

Freezing, point of H_2O in porous glass, (7) 159*c*.

Freezing and thawing. See *Frost resistance.*

Frequency, effect on measuring electrical conductivity of ThO_2, (7) 177*i*.
ir, calculations for ideal mullite, (3) 73*h*.
radio, external probes, determination of plasma conductivity, by, (3) 69*i*.
resonance, for oscillating piezoceramic, (2) 44*j*.

Friction, anti-, of Fe-graphite materials, (10) 246*e*.
anti-, materials, sintered, (10) 247*i*.
on coated abrasive cloth, reducing, P (5) 101*f*.
of diamond sliding on diamond, (6) 127*f*.
external, of cermet powders, (10) 246*g*.
external, of Nb and Ta carbides, (10) 259*d*.
internal, of ferrites, (3) 62*c*.
in impure NaCl, (9) 236*i*.
of $Li_2O{\cdot}Al_2O_3{\cdot}2SiO_2$ glass, (6) 132*b*; (7) 159*d*.
of Ni-Zn ferrite, (6) 152*j*.
of UC, UO_2, and UN, (1) 15*d*.
material, asbestos, P (3) 61*e*; P (8) 196*j*.
material, Fe_3O_4, P (8) 196*i*.
of Ni, effect of B, (10) 258*h*.
platen, effect on fracture of brittle materials, (7) 178*e*.

Frits, anodic deposition in dual envelope, P (3) 64*d*.
with cationic coating, anodic deposition, P (4) 80*b*.
anodic deposition in dual envelope, P (3) 64*d*.
high-Al_2O_3, P (4) 86*a*.

Frost resistance, (9) 220*h*.
of cement and concrete, (7) 156*f*.
in cement paste, (2) 48*g*.
of concrete, (6) 130*f*.
autoclaved lightweight, (6) 129*d*.
vacuum, (6) 130*a*.
of glazed tiles, (1) 6*b*.
of green concrete, (6) 129*j*.
of portland cement paste, (7) 156*e*.
of roofing tile bodies, (1) 17*i*.
of roofing tiles, (4) 83*e*.
of tiles. (11) 271*a*.
of tiles, glazed grooved, (5) 108*f*.

Fuel cells, P (6) 138*a*.
with electrodes, P (11) 274*h*.

Fuel elements, P (4) 91*f*.
articulated housing, P (9) 228*j*.
bundle for nuclear reactors, P (8) 203*b*.
canned irradiated, decanning, P (6) 141*a*.
charging and discharging, P (10) 253*i*.
coating, containing burnable poison, P (3) 68*h*.
and fertile, for nuclear reactors, P (9) 228*j*.
internally pressurized, P (10) 253*i*.
nuclear, P (3) 68*e*; P (7) 171*g*; P (9) 228*i*, 229*c*.
decanning, P (9) 228*j*.
failed, detection, P (9) 228*g*.
irradiated, P (10) 254*a*.
separating core of, P (10) 254*e*.

Fluorides *(continued)*
rare earth, P (2) 46*d*.
rare earth, flux growth, P (9) 232*g*.
sulfo-, of rare-earth metals, crystallochemistry, (10) 255*i*.

Fluorination, of H_3BO_3 and $H_3(HPO_3)$, P (4) 94*h*.

Fluorine, effect on glass crystallization, (6) 131*h*.
electron beam analysis, (8) 205*a*.
in fluorspar, cryolite, and fluorine compounds, (10) 255*a*.
in glass, rapid analysis, (11) 278*a*.
recovery from phosphatic solutions, P (3) 72*b*.
or volatile F compounds, P (11) 280*b*.

Fluorite, flotation, P (3) 71*g*.
oxides, ionic conductivity and nonstoichiometry in, (9) 238*e*.
phase in system CeO_2-ZrO_2-CoO, (11) 282*j*.

Fluorosilicic acid, concentrating, P (6) 143*j*.

Fluorspar, fluoboric acid from, (7) 175*e*.

Fluxes, feldspathic and feldspathoid, vitrification and expansion, (1) 26*a*.
heat, glass-mold, (2) 32*c*.
low-temp., for cast tiles, (8) 197*f*.
welding. See *Welding.*

Fly ash. See *Ash.*

Forsterite. See also *Refractories.*
dark, ceramic composition, P (6) 137*j*.
monticellite solubility in, (1) 25*e*.

Fracture, of brittle epitaxial films, (6) 136*j*.
of brittle materials, (7) 178*e*.
of ceramic crystals, press-forged, (3) 72*e*.
of C fiber polyester composites, (7) 163*h*.
of cement mortar, (6) 128*d*.
energies, of ceramics, (2) 47*j*.
energy, of Na borosilicate glass-Al_2O_3 composite, (1) 3*d*.
engineering fundamentals and environmental effects, B (3) 76*e*.
fatigue, in MgO single crystals, (2) 48*e*.
of fiber-reinforced concrete, (10) 241*g*.
of glazed porcelain, (1) 10*a*.
and healing effects in mica crystals, (10) 259*h*.
impact, in glass-reinforced plastics, (5) 105*i*.
internal, of glass, (4) 80*e*.
obstacles and dynamics, (6) 145*a*.
process, quantum tunneling as, (5) 123*a*.
radius of sheet steel enamels, (11) 267*f*.
of strengthened glass, (3) 56*d*.
studies of set cement paste, (11) 266*h*.
thermal, of sleeve bricks, (1) 8*e*.
thermal-stress of aluminosilicate ceramic, (5) 125*c*.
of CaS, role of $Ca(OH)_2$ in, (7) 156*b*.
of UO_2, effect of porosity, (4) 91*g*.

Freeze-drying. See *Drying.*

Freezing, point of H_2O in porous glass, (7) 159*c*.

Freezing and thawing. See *Frost resistance.*

Frequency, effect on measuring electrical conductivity of ThO_2, (7) 177*i*.
ir, calculations for ideal mullite, (3) 73*h*.
radio, external probes, determination of plasma conductivity, by, (3) 69*i*.
resonance, for oscillating piezoceramic, (2) 44*j*.

Friction, anti-, of Fe-graphite materials, (10) 246*e*.
anti-, materials, sintered, (10) 247*i*.
on coated abrasive cloth, reducing, P (5) 101*f*.
of diamond sliding on diamond, (6) 127*f*.
external, of cermet powders, (10) 246*g*.
external, of Nb and Ta carbides, (10) 259*d*.
internal, of ferrites, (3) 62*c*.
in impure NaCl, (9) 236*i*.
of $Li_2O{\cdot}Al_2O_3{\cdot}2SiO_2$ glass, (6) 132*b*; (7) 159*d*.
of Ni-Zn ferrite, (6) 152*j*.
of UC, UO_2, and UN, (1) 15*d*.
material, asbestos, P (3) 61*e*; P (8) 196*j*.
material, Fe_3O_4, P (8) 196*i*.
of Ni, effect of B, (10) 258*h*.
platen, effect on fracture of brittle materials, (7) 178*e*.

Frits, anodic deposition in dual envelope, P (3) 64*d*.
with cationic coating, anodic deposition, P (4) 80*b*.
anodic deposition in dual envelope, P (3) 64*d*.
high-Al_2O_3, P (4) 86*a*.

Frost resistance, (9) 220*h*.
of cement and concrete, (7) 156*f*.
in cement paste, (2) 48*g*.
of concrete, (6) 130*f*.
autoclaved lightweight, (6) 129*d*.
vacuum, (6) 130*a*.
of glazed tiles, (1) 6*b*.
of green concrete, (6) 129*j*.
of portland cement paste, (7) 156*e*.
of roofing tile bodies, (1) 17*i*.
of roofing tiles, (4) 83*e*.
of tiles. (11) 271*a*.
of tiles, glazed grooved, (5) 108*f*.

Fuel cells, P (6) 138*a*.
with electrodes, P (11) 274*h*.

Fuel elements, P (4) 91*f*.
articulated housing, P (9) 228*j*.
bundle for nuclear reactors, P (8) 203*b*.
canned irradiated, decanning, P (6) 141*a*.
charging and discharging, P (10) 253*i*.
coating, containing burnable poison, P (3) 68*h*.
and fertile, for nuclear reactors, P (9) 228*j*.
internally pressurized, P (10) 253*i*.
nuclear, P (3) 68*e*; P (7) 171*g*; P (9) 228*i*, 229*c*.
decanning, P (9) 228*j*.
failed, detection, P (9) 228*g*.
irradiated, P (10) 254*a*.
separating core of, P (10) 254*e*.

Fuel elements, nuclear *(continued)*
spent, processing, P (10) 253*h*.
of UN, P (8) 203*d*.
vibratory loading, P (11) 276*d*.
nuclear reactor, P (3) 68*g*; P (9) 228*j*.
for high-temp., P (11) 276*c*.
spacer, P (7) 171*j*.
WC electrode for, P (11) 272*b*.
U_3Si, irradiated, (1) 16*f*.
Fuels. See also *Ash, fly; Combustion; Gases; Oil.*
body, nuclear, P (6) 140*j*.
butane, use at Rockware Glass, (4) 80*i*.
ceramic, thermal conductivity, (7) 171*b*.
coal dust, mixed with atomized H_2O for burning, P (8) 206*e*.
combustion indicator device, P (7) 174*j*.
energy, and environment, (10) 256*e*.
liquid, atomizing devices, P (7) 174*e*; P (11) 279*b*.
liquid, burner for, P (2) 45*h*.
microstructure variations, P (3) 68*d*.
nuclear, P (9) 229*a*.
carbide, spherules, P (4) 91*h*.
control of elements for, P (3) 68*i*.
extraction of noble metals, P (10) 253*j*.
multicomponent, P (9) 229*a*.
particles, P (7) 171*i*.
particles, coated, P (6) 141*a*.
powdered, mixer for, P (10) 254*a*.
pyrolytic C coated, P (3) 68*h*.
rod, P (3) 68*f*; P (10) 254*b*.
with UO_2, P (8) 203*e*.
nuclear reactor, assembly, hold-down for, P (9) 228*i*.
composition, P (10) 254*b*.
high-temp., (11) 276*b*.
temp. gradient, P (10) 253*i*.
oil, effect on refractory strength, (1) 7*e*.
oil, in refractories corrosion, (1) 6*j*.
particle coatings, fission products in, (5) 114*h*.
^{240}Pu, use in neutronic reactor, P (9) 228*h*.
PuO_2-Mo, reprocessing, P (6) 141*a*.
porous, from U_3O_8 or UC_2 spheres, P (5) 115*b*.
reactor, molten fluoride salt, reprocessing, P (10) 253*i*.
reactor, spent molten salt, reprocessing, P (10) 253*j*.
stacked plates, warm-pressing method, P (9) 229*b*.
U_3N_4, nonswelling, P (8) 203*e*.
Fuller's earth, deposits in Nevada, (3) 71*e*.
Furnaces. See also *Burners; Fuels; Glassmaking apparatus and equipment; Kilns; Ovens; Refractories.*
aerodynamics, effect on burner, (7) 174*e*.
annealing, P (10) 256*d*.
annealing, ceramic fiber in, (2) 37*b*.
ASEA-SKF casting, slag attack in, (8) 195*h*.
atmospheres. See *Atmospheres.*
bell, for enameled components, P (2) 45*g*.
blast, C in, (2) 37*a*.
nondrying-blow-in, (1) 8*b*.
refractories and design, (2) 37*a*.
technology, B (8) 212*f*.
for ceramic whiskers, P (10) 256*f*.
construction and repair, P (8) 206*c*.
for continuous firing phosphors, P (1) 12*e*.
conveyor system, P (2) 44*j*.
design, with unshaped refractories, (1) 6*f*.
die, P (10) 256*e*.
electric, for ceramic products, (3) 70*i*.
for refractory compounds, (10) 256*e*.
at Wheaton Glass, (5) 106*h*.
electric arc, electrode system, P (8) 206*h*.
electric arc, electrodes for, P (8) 206*b*.
endless, for dry process enameling, P (6) 131*b*.
with feeding structure, P (9) 232*e*.
forehearth, monitoring temp., (8) 191*c*.
for fused quartz hollow slugs, P (7) 161*g*; P (10) 244*h*.
gas-fired and electrical, opal glass melting in, (11) 268*e*.
glass, P (9) 219*c*.
with chamfered walls, P (11) 270*a*.
composition of emissions from, (4) 80*d*.
effect of design on flow, (7) 159*a*.
electric, P (4) 81*f*.
electric, control systems, P (4) 81*c*.
end-fired, model study, (7) 160*a*.
foam pipe, P (7) 162*a*.
forehearth, glass removal from, P (4) 81*j*.
gas combustion and heat exchange, (8) 190*a*.
with heat pipe melting, P (1) 4*g*.
heating, P (11) 270*h*.
lower cost, (4) 80*g*.
MgO to $MgSO_4$ in, (3) 55*h*.
tunnel, P (5) 107*e*.
for glass fibers, P (10) 244*h*.
glassmelting, P (4) 82*d*; P (8) 193*b*; P (10) 244*b*; P (11) 270*a*.
electrical, P (8) 192*g*.
electrical resistance, (9) 217*f*.
floor insulation, P (7) 161*j*.
low cost operation, (9) 218*a*.
opal, (9) 217*j*.
tank, for containers, (5) 106*e*.
tanks, booster for, (11) 268*b*.
glass tank, P (2) 34*g*; P (4) 82*c*.
convection currents in, (9) 216*j*.
corrosion, (2) 33*f*; (8) 191*g*.
effect of electrode type, (8) 189*f*.
electrical resistance, (8) 190*f*.
for float process, P (7) 163*b*.
loading of electrodes in, (8) 192*b*.
NRDC study, (4) 100*a*.
patching, (11) 271*e*.
zircons for pavers, (5) 106*j*.

Furnaces *(continued)*
heat losses, structural, estimation, (2) 45*e*.
heat-treating under high pressure, P (4) 93*i*.
heating, P (3) 70*a*.
high temp., to study ThO_2-SrO and ThO_2-BaO systems, (7) λ72*j*.
ignition, refractories for, (1) 8*d*.
induction, P (11) 279*b*.
for carbonaceous fibrous materials, P (8) 196*b*.
crucible, P (7) 174*e*.
industrial, high-temp., roof for, P (3) 59*h*.
laboratory, temp. control, (2) 44*e*.
life, stress and strain in, (1) 19*b*.
light arc, graphite electrodes for, P (11) 272*g*.
linings. See *Refractories.*
melting, P (9) 232*d*.
for melting vitreous materials, P (4) 93*j*.
modular units, P (9) 232*e*.
movable hearth, P (4) 94*a*.
muffle, replacement, P (9) 215*j*.
multiburner, flame quality, P (2) 45*g*.
pilot, of Hungarian glass works, (6) 143*b*.
preassembled insulating panels, P (1) 9*d*.
push-through, P (2) 45*i*.
radiant, with atm. regulation, P (7) 174*g*.
refractories for. See *Refractories.*
reverberatory, P (8) 206*g*.
with reversible blower for treating goods with heated gas, P (8) 206*g*.
roller hearth, with oscillation controller, P (1) 19*e*.
roofs. See *Refractories.*
rotary, product, cooling, P (4) 93*j*.
for quicklime, (6) 129*f*.
support for, P (6) 143*d*.
shaft, P (1) 19*f*; P (11) 279*c*.
bulk material movement in, (8) 187*b*.
or stack, P (10) 248*d*.
SiC, core for, P (6) 135*f*.
solar, for liquidus curve measurements, (3) 74*d,e*.
for thermal analysis, P (4) 93*e*.
tower, P (4) 83*i*.
tube, P (5) 117*b*.
tunnel, pusher-type, P (7) 174*g*.
tunnel, Steiner, (2) 44*g*.
using gaseous fuel, P (2) 45*g*.
vacuum, electric, for dental ceramics, P (5) 117*b*.
vacuum, for gas sampling, P (11) 278*h*.

Gadolinium, aqueous and silicate phases, (1) 22*a*.
borides, emissive properties, (10) 260*j*.
chloride, vapor pressure, (8) 210*b*.
chlorides, reaction with YCl_3, (5) 123*i*.
diorthogermanates, single crystals, (8) 211*c*.
Gd^{3+}, in CaF_2 and CaO, spin-lattice coeff., (5) 124*d*.
in CaF_2, line strengths, (6) 149*d*.
EPR, in YVO_4, YPO_4, and $YAsO_4$, (5) 120*i*.
in La_2O_2S single crystal, ESR, (4) 96*e*.
$Gd_2(MoO_4)_3$, ferroelectric-ferroelastic, properties, (3) 73*h*.
molybdate, ferroelectric, memory cell, P (1) 12*c*.
molybdate, in storage device, P (3) 65*a*.
monoxide, band spectrum, (7) 176*e*.
oxide, transparent ceramics and phosphors, (10) 249*a*.
sesquioxide, Eu^{3+} spectra in, (5) 124*b*.
sulfide, electronic structure, (6) 150*h*.
Gages, capacitance, for dimensional measurements, (11) 277*i*.
capacitor microstrain for strain measurement, (10) 255*b*.
semiconductor strain, P (2) 42*e*.
semiconductor strain, thin-film, P (3) 68*a*.
strain, rosette and shaped polyester, (7) 173*j*.
stress and strain, for soil pavements, (7) 173*a*.
thickness, ultrasonic nondestructive, P (3) 70*g*.
Gallium, arsenide, P (4) 88*a*.
on Al_2O_3, (4) 86*j*.
annealing effects, (6) 149*b*.
band bending in, (7) 177*a*.
bulk, permittivity, (7) 178*a*.
Cd and As implantations in, (7) 176*h*.
devices, double-injection, (6) 151*g*.
diffusion length in, (4) 96*e*.
as electronic material, B (1) 27*f*.
emission diode characteristics, (6) 149*a*.
epitaxial kinetic studies, (9) 235*i*.
epitaxy, *pn* junction formed during, (6) 151*a*.
far-ir mixing in, (6) 148*e*.
flash evaporating, P (1) 12*d*.
and GaP, Czochralski growth, (11) 273*i*.
and GaP substrates, $InAs_xP_{(1-x)}$ on, (9) 234*i*.
growth and decay rate of high-field domain in, (1) 11*h*.
highly pure, P (8) 201*h*.
hot-electron distribution in, (6) 148*d*.
layers, growth properties, (5) 111*j*.
n-, electron transport in, (7) 180*f*.
n-, epitaxial Sn-doped, P (1) 13*e*.
n-, hole lifetime in, (6) 146*f*.
n-, layers in, P (6) 138*i*.
n-, Schottky barriers, (7) 179*i*.
ohmic contacts for, P (6) 139*i*.
optical constants, (8) 209*i*.
p-, hole velocity in, (5) 124*g*.
residual impurities in, (2) 38*h*.
from trimethyl Ga and arsine, (2) 38*g*.
vapor growth, P (8) 203*a*; (9) 239*c*.
vapor phase etching, (9) 239*d*.
velocity-electric field, (6) 150*h*.

Gallium, arsenide *(continued)*
Zn diffusion in, (4) 99*e*.
compounds with reduced Si contamination, P (3) 65*b*.
electrochemically extracting from aluminate solution, P (10) 257*h*.
Ga-GaP-GaAs phase diagram, (9) 235*f*.
$GaAs_xP_{1-x}$, epitaxial growth, (9) 235*i*.
$GaAs_{1-x}P_x$, epitaxial layers, growth, (7) 181*b*.
$GaAs_{1-x}P_x$, layers, dislocation etching, (7) 179*i*.
$Ga_xFe_{3-x}O_4$ and $GaNiFeO_4$, NMR in, (3) 74*e*.
$Ga_xFe_{3-x}O_4$, spin waves in, (5) 124*e*.
Ga_2O_3 crystals, by floating zone, (7) 179*e*.
Fe oxide, anisotropy energy and magnetization in, (5) 119*f*.
phosphide, bulk, from Ga solutions, (2) 39*f*.
devices, light-emitting, P (6) 138*d*.
films, deposition, P (1) 15*b*.
layers, impurities in, (9) 234*e*.
polishing, P (10) 251*j*.
Zn diffusion into, P (7) 170*i*.
systems. See *Systems.*
-V compounds, in semiconductor materials, (2) 39*i*.
Garnets, compositions, for magnetic devices, P (2) 40*h*; P (6) 138*g*.
crystals, Ce-activated, optical properties, (1) 11*g*.
ferrimagnetic, Ca-V series, P (5) 112*g*.
ferrimagnetic Fe, P (7) 168*h*.
films, chemical vapor deposition, (10) 248*j*.
films, epitaxial, P (1) 12*a*.
Gd Al, crystal growth and optical properties, (2) 47*f*.
GdIG films, magnetic properties, (4) 86*i*; erratum, (7) 167*b*.
GdIG, magneto-optical properties, (6) 147*b*.
hydro-, phase, in kaolinite-CaO-H_2O slurries, (9) 214*b*.
hydro-, resistance to sulfates, (4) 79*b*.
magnetic, P (8) 201*c*.
magnetic anisotropy induced, (1) 21*d*.
magnetic bubble domain, topography, (8) 199*j*.
rare-earth, Al, Ga, and Fe, ir spectra, (1) 22*h*.
films, single crystal, growth, (8) 199*h*.
Fe, crystalline, P (2) 40*i*.
preparation, (6) 136*j*.
-Y Fe-Ga, epitaxial films, (2) 38*g*.
titanian and zirconian, (4) 95*e*.
uv magneto-optical properties, (6) 152*i*.
Y and Gd ferrite, in amorphous films, (7) 166*e*.
YAG, crystallization, (11) 280*g*.
YAG, Lu-Nd-doped, P (4) 88*c*.
YIG, films, composition, (10) 248*j*.
films, on substrates by CVD, (11) 274*i*.
grain growth in, (8) 209*d*.
photomagnetic effects in, (9) 237*e*.
(Si), magnetic effects in, (9) 237*d*.
spin-wave linewidth, (6) 146*i*.
Gases, absorption, effect on CoO properties, (6) 151*g*.
adsorption isotherms, for textural parameters, (7) 173*b*.
bubbles, in fissile material, (6) 140*j*.
in glass, analysis, (8) 204*f*.
in glasses, (7) 159*j*.
combustion, P (8) 206*e*.
combustive quality, P (10) 256*e*.
conveying and measuring, for gas analysis, P (8) 206*a*.
diffusion in vitreous B_2O_3, (3) 55*b*.
discharge device, glass, P (7) 162*d*.
electronegative, concentration determination, P (11) 278*i*.
flow, in porous media, (6) 142*b*.
flowing through fixed beds, pressure decrease, (2) 44*f*.
flue, cleansing apparatus for, P (2) 43*h*.
flue, soap added to, (8) 203*g*.
heating, for TiO_2 pigment, P (4) 94*i*.
hot, electrochemical analyzer for O_2 in, P (1) 18*e*.
mixtures of TiO_2, cooling, P (11) 279*i*.
recovering TiO_2 from, P (11) 279*i*.
kiln exhaust, corrosion and smut emission by, (1) 19*a*.
leak detectors, P (7) 174*c*.
machine, refractory bed for, P (1) 9*b*.
natural, in W Germany, (8) 206*e*.
paramagnetic, removal, P (11) 280*b*.
phase chemical analysis, (2) 44*h*.
quantitative analysis, apparatus, P (9) 231*d*.
rare, trapping and diffusion in silicates, (2) 50*e*.
reactions during enameling, (8) 188*h,j*.
release in UO_2, (5) 114*g*.
re-solution, in irradiation of UO_2, (1) 15*h*.
samples, analyzing, P (3) 70*b*.
sampling tube, P (11) 278*h*.
sampling, vacuum furnace for, P (11) 278*h*.
separating dust from, P (3) 69*c*.
stack, removing pollutants, (1) 19*a*.
stack, removing SO_2 from, P (10) 256*d*.
stream, average temp., P (3) 70*g*.
streams, containing TiO_2, cooling, P (1) 20*c*.
-treating apparatus, P (1) 19*d*.
waste, fluosilicic acid from, P (5) 117*h*.
waste, SO_2 reduced by CO in, (10) 256*c*.
Gels. See *Colloids.*
Generators, coherent far ir, P (2) 39*g*.
hot gas, P (10) 256*i*.
$LiNbO_3$ harmonic, P (5) 113*b*.
NAND gate square wave, P (2) 39*i*.
neutron, targets for, P (11) 276*e*.
piezoelectric high-voltage, P (10) 252*i*.
semiconductive thermoelectric, P (7) 168*d*; (11) 274*a*.

Generators *(continued)*
semiconductor diode hf signal, P (6) 140*d*.
semiconductor photoelectric, P (7) 170*c*.
thermoelectric PbTe, P (10) 253*b*.
Geochemistry, analytical requirements, (9) 230*f*.
Germanates, new "benitoite" type, (10) 260*c*.
single-crystal, synthesis, P (10) 245*d*.
structure, solid solutions, and electrical properties, (7) 181*c*.
of trivalent elements, (6) 145*g*.
Germania. See *Germanium, dioxide.*
Germanium, crystals, resistivity measurements, (3) 63*f*.
dioxide, abrading with, P (4) 77*h*.
crystal growth, P (7) 168*c*, 176*g*.
defects in, (2) 47*c*.
inert gas diffusion in, (2) 32*b*.
reflection spectra, (6) 151*c*.
tetragonal, P (9) 227*j*.
ESR in, (6) 147*b*.
Ge-Si-Sn and Ge-Si-Pb phase diagrams, (9) 238*c*.
in Au-Ge alloys, determination, (11) 277*i*.
monoxide, Ge_2O_2, Ge_2O_3, and Ge_4O_4, ir spectra, (7) 178*c*.
nitrides, reactions, (4) 99*j*.
oxide, electric dipole moment, (5) 120*g*.
with O, surface reaction, (6) 149*j*.
removal of acceptor impurities from, P (9) 227*c*.
single crystals, creep, (6) 147*e*.
single crystals, pulling, P (5) 113*j*.
sulfides, synthesis, (8) 211*d*.
systems. See *Systems.*
telluride films, electrical conduction, (6) 136*g*.
Getters, device, P (3) 58*d*.
pump, P (2) 34*d*.
Gettering, P (9) 219*b*.
for electric lamps, P (10) 244*h*.
Gibbsite, calcination, production of corundum by, (1) 8*b*.
Glass. See also *Art and artware; Furnaces; Glass industry; Glassmaking apparatus and equipment.*
P (9) 219*b*; P (11) 270*h,i*.
abrasive machining, (3) 53*i*.
acetate material, P (6) 133*a*.
acid etching, (4) 80*d*.
acid polishing, P (1) 3*c*.
alkali, and alkaline earth oxide-SiO_2, Cr(III) ions in, (11) 267*g*.
aluminosilicate, articles, P (2) 34*d*.
borate, Newtonian rheology, (3) 55*a*.
borate, vanadyl ion in, (9) 217*g*.
borophosphate, effect of N, (4) 80*g*.
-containing, electrode "polarization" in, (8) 190*h*.
electroconductivity, (7) 160*i*.
fluorberyllate, X-ray diffraction, (2) 33*j*.
silicate, electrical conductivity, (3) 55*e*.
silicate, phase separation, (3) 55*e*.
silicates, electron microprobe, (3) 55*e*.
titanate, ESR, (7) 159*e*.
titanate, X-ray diffraction, (2) 33*h*.
alkaline earth aluminoborate, structure, (6) 132*g*.
alkaline earth borate, optical and ESR spectra, (3) 56*i*.
Al_2O_3, high-, X-ray diffractometry, (3) 57*d*; (5) 105*j*.
aluminosilicate, brazable, P (2) 33*f*.
aluminosilicate, relaxation times in, (2) 33*c*.
amber, composition, (8) 189*f*.
amber, dark, P (4) 81*d*.
analysis, combustion separation in, (8) 204*i*.
by flame emission and atomic absorption, (8) 204*j*.
Pb and Ba oxides in, (8) 205*d*.
plasma torch for, (8) 205*h*.
annealing process for FET devices, P (8) 200*g*.
Sb borate, compositions, P (7) 161*e*.
armor, P (11) 270*i*.
As-chalcogen-halogen, to improve diode efficiencies, (2) 38*i*.
As-S, thermal expansion, (3) 57*b*.
As-S-Te, thermal expansion, (3) 57*c*.
As-Te, electrical effects in, (2) 33*f*.
As-Te-Ge, filament formation in, (6) 131*i*.
As_2O_3 compositions, P (2) 33*c*.
articles, P (11) 270*e*.
aqueous coating for, P (8) 192*a*.
chemical strengthening, P (2) 33*g*.
chemically tempered, P (5) 107*c*.
Cr-filmed, P (6) 132*c*.
with heat-reflecting film, P (9) 219*b*.
with light-dispersing layer, P (6) 133*a*.
mechanically strengthening, P (3) 58*h*.
strengthened by ion exchange, P (2) 35*c*.
strengthening, P (9) 219*i*.
ASTM standards, B (10) 262*c*.
$3BaO\text{-}5SiO_2$, spherulitic crystallization in, (8) 189*f*.
Ba silicate, for cathode-ray tubes, P (4) 81*a*.
bars, profiled, P (8) 194*i*.
basalt, structural parameters, (6) 132*f*.
batch, material for vitreous mfg., P (11) 270*b*.
particulate, melting, P (1) 4*b*.
preheating, P (5) 107*g*.
raw materials, agglomeration, (10) 243*h*.
and batch material, control, (8) 192*c*.
and batch materials, analysis by thermometry, (8) 204*g*.
and batch sample preparation for spectrometry, (8) 205*h*.
beads for electrostatographic developers, P (3) 193*a*.
beads, flotation treatment, P (3) 59*d*.
behavior in sintering metal-glass, (10) 242*j*.

Glass *(continued)*
binder plate, electrophotographic devitrified, P (7) 161*d*.
black enamel, for cathode-ray tube, P (7) 161*i*.
-blowing, B (7) 183*j*.
bodies, chemically strengthened curved, P (4) 82*j*.
body, electric arc diffusion treatment, P (6) 132*e*.
for bonding metallic articles, P (11) 270*c*.
bonding metals to, (10) 242*f*.
bonding with thermoplastic sealing composition, P (7) 161*i*.
borate, compositions, F-containing, P (2) 34*c*.
luminescence of ions in, (9) 216*i*.
structure of trapped-hole centers in, (7) 158*j*.
Ti centers induced in, (4) 81*g*.
B-Mo, formation and properties, (6) 132*b*.
B- and P- containing, removal from Si, P (9) 227*b*.
$B_2O_3\text{-}BaO\text{-}Fe_2O_3$, magnetic properties and structure, (11) 268*h*.
$\text{-}Bi_2O_3\text{-}Al_2O_3$, Raman spectra, (8) 191*e*.
Raman spectrum, (11) 269*g*.
$\text{-}SiO_2$, for coating substrate, P (6) 133*b*.
stress relaxation, (6) 132*j*.
borosilicate, P (7) 161*j*.
acid leaching characteristics, (11) 267*h*.
acid-leaching in, (3) 55*d*.
B coordination no. in, (5) 106*c*.
composition, P (5) 107*a*.
damping, (5) 116*f*.
demixing, (7) 159*e*.
opalizable, P (6) 133*d*.
sintered, (6) 133*g*.
uv-transmitting, P (9) 220*b*.
bottles. See also *Glass, containers.*
and jars, packaging, P (7) 162*f*.
plastic coated, P (8) 193*h*.
TiO_2 coatings on, (7) 160*j*.
treating, P (5) 107*f*.
vacuum, P (5) 107*i*.
brazing method, P (1) 4*f*.
breaks. See *Glass, fractures.*
bubbles in, analysis of (1) 3*c*.
bubbles in, gas chromatography, (6) 132*a*.
bulb, flash, ignition, P (4) 81*h*.
for high-temp. lamps, P (10) 244*h*.
miniature light, P (3) 59*i*.
$CaO\text{-}Al_2O_3\text{-}SiO_2$, leaching in (2) 32*e*.
Ca silicophosphate and Mg silicophospate, (3) 57*h*.
capsules, in chloride matrix, P (4) 82*j*.
capsules, in themoplastic matrix, P (4) 82*j*.
cellular, tower packing element, P (8) 193*d*.
cellular, in USSR, (2) 32*i*.
cellulated bodies, from rock, P (9) 218*e*.
-ceramics, P (2) 33*i*; B (4) 100*g*; P (6) 132*h*; P (7) 161*g*; P (10) 244*i*.
articles, P (5) 107*f*; P (10) 245*c*.
articles, decoration, P (7) 161*b*.
articles, niobate-titanate, P (2) 34*h*.
articles, phototropic, P (1) 6*a*.
body, decorating, P (2) 33*h*.
B_2O_3 treatment, P (7) 161*h*.
cements comprising SiC, P (4) 82*a*.
chemical stability, (9) 216*f*.
Pb ferrite, P (4) 82*e*.
$PbTiO_3$ enamel for, P (8) 193*d*.
$Li_2O\text{-}SiO_2$, mechanical properties, (3) 55*d*.
machinable, (7) 159*e*; (10) 243*g*.
from $MgO\text{-}Al_2O_3\text{-}SiO_2\text{-}TiO_2$, (11) 268*g*.
$MgO\text{-}Li_2O\text{-}Al_2O_3\text{-}SiO_2\text{-}TiO_2$, microstructure and indentation hardness, (7) 160*a*.
material, from basalt, (8) 191*f*.
materials, (4) 80*h*.
mica, damping, (5) 116*f*.
nepheline-feldspar, P (7) 162*e*.
precursor compositions, bismuthate, P (11) 274*d*.
precursors, P (8) 192*j*.
range top, P (2) 33*j*.
semiconducting, (6) 132*h*.
sheets, green, vessels from, P (10) 244*g*.
$SiO_2\text{-}Al_2O_3\text{-}Li_2O$, P (2) 35*c*.
SiO_2-free $CaAl_2O_4$, P (4) 83*c*.
slag, Soviet building with, (5) 106*a*.
in Soviet building, (10) 243*j*.
surface conditioner for, P (10) 246*h*.
surface heating unit, P (2) 34*a*.
surface treatment, P (9) 220*b*.
from system $Al_2O_3\text{-}MgO\text{-}SiO_2$, (4) 81*a*.
of system $Li_2O\text{-}Al_2O_3\text{-}GeO_2\text{-}TiO_2$, (8) 191*j*.
thick-film capacitors, (2) 39*f*.
transparent articles, P (10) 245*i*.
transparent batches for, P (3) 58*e*.
transparent Zn silicate, P (9) 220*a*.
treating process, P (2) 34*e*.
use in optical elements, P (5) 107*a*.
Zn petalite–β-quartz, P (10) 244*g*.
Ce, charge distribution and current in, (3) 55*e*.
Cs borate, structure, NMR, (7) 160*g*.
chalcogenide, in acousto-optic and ultrasonic devices, P (7) 168*g*.
alloy, studies, (6) 131*h*.
electrical conductivity and optical absorption in, (3) 56*e*.
electrical properties, (9) 218*g*.
electronic properties, (6) 131*j*.
filamentary paths on, (3) 55*f*.
films, current-voltage, (6) 131*h*.
glass transition in, (4) 80*d*.
high current density path on, (3) 56*d*.
optical properties, (6) 132*c*.
surfaces, cracks on, (3) 55*i*.
switching and bulk properties, (6) 132*a*.

Glass, chalcogenide *(continued)*
switching and memory effects in, (6) 132*d*.
channel intensifier compositions, P (5) 107*b*.
chemical tempering by spraying, P (10) 243*j*.
-clay mosaics and tiles, (8) 190*j*.
cloth, in polyimide composites, P (1) 5*d*.
cloth, treatment, P (8) 194*d*.
coating, P (9) 219*a*.
collet, applying to cathode-ray tube, P (1) 4*c*.
color change in continuous furnaces, (3) 55*c*.
colorant composition, P (3) 58*f*.
colorless heat-absorbing, P (6) 132*d*.
commercial, B_2O_3 in, determination, (8) 204*d*.
commercial silicate, amber color in, (8) 189*d*.
composition, effect on amber color, (11) 268*i*.
foam, with Cu, P (3) 59*a*.
relation to corrosion, (10) 243*i*.
concentrate capsules, P (9) 219*b*.
conductivity and temp. probe, P (8) 192*j*.
as construction material, (2) 32*g*; (4) 80*i*.
containers, P (3) 60*a*; P (8) 193*g*.
applying oxide coating, P (2) 34*h*.
high-speed fillers for, (3) 56*a*.
lighter, (8) 189*h*.
packing, palletizers for, (8) 192*d*.
sealed, for Na, P (8) 193*d*.
strength and size of Griffith flaws, (7) 158*d*.
wall thickness detection, P (11) 270*d*.
containing Ag halides, (8) 190*c*.
convertible to glass-ceramics, P (5) 107*g*.
cracks in, effect of H_2O on growth, (3) 72*f*.
crystalline. See *Glass-Ceramics.*
crystallization. See also *Crystallization.*
(4) 80*e*; B (5) 126*b*.
advances in, B (10) 261*i*.
fluor-richterite, (3) 55*j*; (5) 105*g*.
$Li_2O\text{-}MgO\text{-}Al_2O_3\text{-}SiO_2$, (6) 131*h*.
$Li_2O\text{-}MgO\text{-}Al_2O_3\text{-}SiO_2\text{-}F$, (6) 131*j*.
memory-switching, (4) 80*g*.
photosensitive, (9) 217*c*.
pyroxene, (9) 216*d*.
in $SiO_2\text{-}Al_2O_3\text{-}CaO\text{-}MgO$ system, (4) 80*j*.
of system $Li_2O\text{-}MgO\text{-}CaO\text{-}Al_2O_3\text{-}SiO_2\text{-}F$, (5) 106*b*.
in system $Na_2O\text{-}GeO_2$, (9) 216*d*.
crystallized, microstructure and strength, (5) 106*e*.
curved, P (11) 270*c*.
decolorization. CeO_2 used in, (3) 57*b*.
decoration. See *Decoration.*
defect detection system, P (8) 192*j*.
defects, under electron bombardment, (10) 243*e*.
delay line, P (9) 218*g*.
devitrifiable, P (2) 33*i*.
devitrifiable, for ferrite recording heads, P (10) 245*c*.
devitrified. See *Glass-ceramics.*
diffusion coeffs. in, (1) 3*i*.
diffusivity at high temps., (7) 158*j*.
dispersed, heating, melting, or softening, P (1) 4*j*.
dispersion, changes in, (9) 216*e*.
drawn sheet, mfg., (5) 105*i*.
durable coatings for, P (6) 133*e*.
dynode electron multipliers, (6) 132*c*.
E-, dissolved H_2O in, (3) 54*j*.
E, H_2O vapor adsorption on, (9) 216*b*.
electrical conduction in, (11) 268*c*.
electrical conductivity, B (6) 153*i*; (8) 190*e*.
electrical properties, (3) 55*c*.
electrical translating device, P (9) 218*i*.
electroconductive sintered, P (5) 107*e*.
electrodes. See *Electrodes.*
electron microscopy and energy loss, (6) 131*h*.
electronic color sorting from waste, (7) 159*f*.
element, sound-insulating, P (8) 194*b*.
fatigue, effect of pressure, (1) 3*d*.
fibers. See *Fibers, glass.*
-filament-wound pressure vessels, (5) 106*f*.
filamentary material, severing, P (5) 107*e*.
films, P (3) 58*j*.
fused on semiconductor devices, (2) 39*c*.
leaching for filter making, P (2) 34*a*.
leaching, for SiO, rigid membranes, P (4) 83*b*.
semiconducting, switching in, (6) 132*j*.
on substrate, P (3) 65*e*.
filters. See *Filters.*
finding, P (3) 59*d*.
flashbulb, P (9) 218*j*.
flat. See also *Glass: plate, sheet, window.*
P (7) 162*h*; P (8) 193*g*; P (11) 270*c*.
charge transfer effects in, (9) 216*h*.
floating, P (6) 133*f*.
layers in, (7) 160*b*.
metal oxide coating on, P (10) 245*a*.
on molten metal bath, P (6) 133*f*.
shipping case, P (7) 161*f*.
float, P (2) 34*b*; P (4) 81*i*; P (6) 133*h,i*; P (9) 219*a*.
bath, exit sealing drape for, P (10) 244*f*.
with even edges, P (4) 82*j*.
low-pressure measurements in, (3) 56*c*.
mfg. and sizing, P (5) 107*g*.
modifying surface, P (1) 5*c*.
with oxidized surface, P (10) 245*e*.
stresses and ionic transport, (8) 191*i*.
strip, with rough surface, P (10) 245*e*.
flow in model tank, (7) 159*j*.
flow patterns in Fourcault process, (7) 158*d*.
of fluor-richterite composition, (6) 131*j*.
fluor-richterite, crystallization, (3) 55*j*.
fluoride, containing xenon, P (7) 161*f*.
fluoride opal, reversible opacity, P (9) 220*b*.
F in, rapid analysis, (11) 278*a*.
fluorine opal, P (3) 58*c*.
fluoroberyllate, effect of radiation, (9) 216*j*.
formation in alkali molybdate systems, (3) 56*f*.

Glass *(continued)*
formation in M_mSe_n-$Ge_{1.5}As_{0.5}Se_2$ systems, (8) 190*a*.
-forming process, factors affecting, (8) 190*j*.
frit coating, bonding with, P (1) 12*e*.
fulminating material application, P (9) 219*a*.
fused energy-conducting structure, P (9) 219*d*.
gas bubbles in, (7) 159*j*.
gas bubbles in, analysis, (8) 204*f*.
gas discharge device, P (7) 162*d*.
Ge borate, ^{11}B NMR in, (11) 267*j*.
GeO_2-SiO_2, coating, P (9) 225*j*.
for glass-coated microwire, P (2) 34*g*.
glassy materials, melting, P (11) 270*d*.
glazed units, purging and filling, P (11) 270*f*.
gradient-index, ray tracing in, (8) 205*b*.
graphite-, compositions, P (3) 58*a*.
green, dark, black stones in, (3) 56*j*.
grenade, frangible, P (11) 270*g*.
grinding. See *Grinding*.
heat-reflecting, P (8) 193*c*.
heating circuits applied to, P (9) 218*d*.
heating cycles for, during hardening, (8) 189*g*.
Hertzian fracture mechanics in, (7) 160*d*.
high pressure effects on, (3) 56*j*.
hollow and bottomed articles, molding, P (8) 193*a*.
hollow, electrolytic treatment, P (11) 270*e*.
honeycomb structure, P (10) 245*a*.
inclusions in, microscopy, (11) 267*i*.
Indian, for fiber optics, (7) 161*a*.
ir-reflecting, P (3) 58*e*.
ir spectroscopy, (9) 217*c*.
inorganic, structure and mechanical properties, B (2) 52*e*.
inorganic, viscosity measurements, (3) 56*g*.
insulation, casting microwire in, P (1) 4*i*; P (7) 162*e*.
internal fracture, (4) 80*e*.
International Congress, 9th, B (11) 283*e*.
ion exchange with CO_2, P (10) 244*f*.
ionic-covalent interaction in, (5) 106*h*.
ionically modified, P (10) 244*g*.
ionizing radiation effect, (8) 190*c*.
FeO-P_2O_5, structure and properties, (9) 218*i*.
$55FeO$-$45P_2O_5$, structure and electrical properties, (8) 189*d*.
laminated, P (9) 219*g*.
bodies, P (10) 244*a*.
bodies, strengthened, P (6) 133*h*.
safety, P (10) 244*g*.
safety and bulletproof, P (8) 193*f*.
stem, P (5) 107*i*.
structures, P (11) 270*b*.
thermally insulating, P (5) 107*h*.
transparent bullet-resisting, P (3) 58*e*.
laminates, and organic resin, P (3) 60*a*.
laminates, -polycarbonate resin, P (9) 219*d*.
laser. See *Laser, glass*.
Pb, -Ba borosilicate, in dielectric composition, P (10) 245*g*.
birefringence in, (2) 32*f*.
borate, phase separation in, (9) 218*c*.
borate, H_2O in, (2) 32*e*.
glazing Au-Cr films with, (9) 217*i*.
microchannel plates, activating, P (4) 82*h*.
silicate, luminescence centers in, (3) 56*d*.
volatilization, (2) 32*j*.
lenses. See *Glass, optical*.
light-conducting structure, P (7) 162*f*.
light-guide elements, surface refractive index, P (6) 133*g*.
liquid-, transition, free-vol model, (5) 105*h*.
liquid-state, properties, discontinuity, (7) 159*c*.
with Li vapor, ion exchange strengthening, P (2) 34*i*.
Li-Cu aluminosilicate, (2) 32*d*.
Li_2O-Al_2O_3-$2SiO_2$, internal friction, (6) 132*b*; (7) 159*d*.
Li_2O-MgO-Al_2O_3-SiO_2, crystallization, (6) 131*h*.
Li_2O-MgO-Al_2O_3-SiO_2-F, crystallized product, (6) 131*j*.
Li silicate, crystallization of Li disilicate in, (9) 216*e*.
low-temp., fabrication, (1) 3*g*.
with low ultrasonic propagation time-temp. coeff., P (2) 34*f*.
lunar, thermal history, (6) 132*h*.
-making problems, ion microanalyzer and electron spectrometer in, (8) 205*f*.
mfg., control of emissions from, (9) 216*j*.
mfg. using Na_2SO_3, P (2) 34*f*.
materials, multilayer, P (7) 162*a*.
materials, for phosphate glass dosimeter, P (1) 4*h*.
melilitic, devitrification, (10) 243*b*.
melting, P (1) 5*d*.
electric, (6) 131*i*.
Ag losses during, (8) 192*d*.
memory, thin films, crystallization, (8) 192*a*.
memory-switching, crystallization in, (4) 80*g*.
-to-metal sealing. See *Seals and sealing*.
metal-, materials, cold pressing, (10) 243*c*.
metal oxide coatings on, P (6) 133*f*.
metallic coatings on, P (9) 219*i*.
microhardness impressions in, (7) 159*i*.
microhardness, tests, (4) 81*d*.
microhole on, oscillation in, (3) 55*g*.
microporous, for tobacco smoke filters, P (4) 82*i*.
microspheres, evacuated, P (1) 5*b*.
mirrors. See *Mirrors*.
mixed-alkali effect in, (11) 269*c*.
modifying, P (7) 162*h*.
molar vol., partial, (6) 131*i*.
in molding compositions, P (1) 5*d*.
molds. See *Molds*.
molten, adding colorant to, P (4) 82*i*.

Glass, molten *(continued)*
controlling rate of flow, P (3) 59*b*.
falling film cooling, P (8) 192*h*.
measuring temp. in, (3) 56*j*.
modifiers incorporated, P (8) 193*i*.
radiation target to cool, P (6) 133*f*.
multicomponent, without fusion, (7) 160*a*.
multiple glazed unit, P (9) 219*a*.
nucleated. See *Glass-ceramics*.
ns^1 centers in, ESR studies, (3) 55*h*,*j*.
nuclear radiation absorbing, P (3) 59*a*.
nucleation and crystallization in, B (10) 261*i*.
opacified, surface cracking, (7) 160*h*.
opal, articles, P (6) 133*b*.
with CaF_2, P (10) 245*h*.
compositions, P (8) 193*h*.
melting in Poland, (9) 217*j*.
melting in tank furnaces, (11) 268*e*.
nucleation and crystal growth in, (7) 160*e*.
photosensitive, strengthened, P (8) 194*c*.
optical, P (8) 193*h*; P (9) 219*f*,*g*; P (10) 245*h*.
aberrations, correction of, (8) 189*j*.
compositions, P (9) 219*g*.
contact lenses, grinding, P (8) 194*c*.
Co, Cu, and Mn in, (3) 57*g*.
fluorophosphate, P (8) 194*b*; P (9) 219*f*.
homogeneity, (10) 243*g*.
La borate, Th-free, P (2) 35*b*.
La borosilicate, P (2) 34*j*.
lens, multifocal, P (3) 59*j*.
lens, multifocal molds, P (6) 133*f*.
lens, spherical, P (9) 220*a*.
lens, unitary composite, P (3) 59*g*.
lenses, bifocal, P (2) 34*e*.
lenses, focal lengths, (11) 268*j*.
materials, refractive index and absorption coeff., (8) 191*d*.
materials, thermal expansion, (10) 243*a*.
mirror, telescopic, P (6) 133*d*.
polishing mechanism, (3) 57*a*.
properties. See *Optical properties*.
surfaces, ion polished, (8) 191*j*.
thermal coeff. of refractive index, (1) 3*j*.
tubular, P (10) 244*i*.
wave guide, fused SiO_2, P (8) 192*i*.
weatherproof, P (7) 161*e*.
windows [GaSb] for lasers, P (2) 41*i*.
optoelectronic structure, P (8) 193*j*.
orifice plates, P (3) 59*c*.
oxide, photoconducting, new, (7) 160*e*.
proton behavior in, (9) 216*b*.
refractive index and density in, (10) 242*j*.
panels, large, package for, P (1) 5*f*.
parisons, extrusion, P (9) 230*b*.
parisons, programing, P (4) 82*e*.
particles, coating with O compound, P (8) 192*c*.
particulate, bonding with, P (9) 219*j*.
passive and dynamic absorption in, (1) 3*g*.
phase, in cement, (4) 78*c*.
phase separation in, (11) 269*d*.
phosphate bodies, P (5) 107*f*.
electron and NMR, (5) 105*j*.
irradiated, structure, (5) 106*h*.
photochromic, P (2) 34*j*; P (9) 219*g*.
articles, strengthening, P (8) 193*a*.
γ-irradiation of, (8) 190*h*.
for optical fiber, P (4) 82*g*.
polarizing, P (7) 162*c*.
photoluminescent, P (5) 107*f*.
photosensitive, crystallization, (9) 217*c*.
photosensitive, Ag formation in, (3) 56*c*.
phototropic, P (3) 59*b*.
pipe. See *Pipe*.
-plastic laminated filters, (8) 191*c*.
plate. See also *Glass: flat, sheet, window*.
cutting problem in, (8) 191*g*.
flexural strength test, (1) 3*f*.
layered structure, (7) 159*j*.
line pattern on, P (9) 219*j*.
or shaped sheets with glass fiber base, P (2) 34*a*.
plating for space use, (2) 38*d*.
plug, floating, for stopcock, P (8) 192*h*.
polished, light scattering measurements, (8) 205*d*.
polishing. See *Polishing*.
porous, ceramic insulation, coating for, P (9) 219*f*.
electrodeposition of metals in, (9) 217*g*.
freezing point of H_2O in, (7) 159*c*.
K V phosphate, polaronic effects, (6) 132*d*.
pots. See *Glassmaking apparatus and equipment; Refractories*.
precision engineering, B (9) 240*b*.
preparation for electron microscopy, (7) 173*b*.
preparation, gelling and desiccation in, (1) 3*e*.
press shaping, by rotary molding, P (2) 34*b*.
pressing, (3) 56*a*.
prestressed, P (7) 162*h*.
printing on, with epoxy resin ink, P (1) 5*b*.
prism, bonding to metal, P (2) 34*c*.
processing, computers in, (5) 106*b*.
processing, diffusional network, (4) 90*j*.
product, electrically heatable, P (3) 58*a*.
production, P (7) 162*a*; B (11) 283*i*.
properties, diffusion for improving, P (4) 81*e*.
discussion, (3) 57*c*.
effect of melt processes, (11) 267*h*.
effect of mixed alkali, (3) 56*f*.
pyroxene, catalyzed crystallization, (9) 216*d*.
quartz, high-purity, P (3) 59*d*.
radiation damage in, EPR studies, (11) 268*d*.
raw material, from solid wastes, (4) 92*b*.
and raw materials, analysis, (8) 189*e*.
razor blades, P (1) 4*j*.
reaction with HF, (2) 32*h*.

Glass *(continued)*
reactive, sintering Ag-Pd in presence of, (7) 160*e*.
reboil, study with hot-stage microscope, (3) 56*a*.
recycled, metallic Al in, (7) 158*e*.
recycling, increase in, (7) 159*c*.
refractive index, (1) 3*h*.
refractive index and optical path length, (10) 243*d*.
refractory, B (4) 100*g*.
-reinforced polyester sheets, P (1) 5*a*.
reinforcement for tires, P (4) 82*d*.
removal from forehearth, P (4) 81*j*.
research, electron spectroscopy in, (8) 204*i*.
reshaping and ion-exchanging, P (5) 107*e*.
review, (10) 243*d*.
rheological behavior, (3) 57*d*.
ribbon, float bath, removing O in, P (3) 59*f*.
regulating, P (9) 219*e*.
surface temp. measurement, (8) 190*d*.
of rigid molecules, relaxations in, (7) 161*d*.
rods, bend strength measurements, (7) 160*h*.
rods, SiO_2, redrawing, P (7) 162*i*.
Ru behavior in, (10) 242*j*.
Ru oxidation in, (2) 32*e*.
safety. See also *Glass, laminated*.
armor unit, P (9) 219*f*.
glazing in hazardous areas, (5) 106*j*.
sand. See *Sands*.
science and technology, frontiers in, B (3) 76*i*.
scientific and technical communications, B (7) 184*c*.
sealing. See *Seals and sealing*.
Se-containing, P (4) 82*h*.
Se and Fe trigonal films on, (3) 56*i*.
semiconducting, electrothermal instabilities in, (7) 160*c*.
semiconducting, memory and switching, (6) 132*c*.
semicrystalline. See *Glass-ceramics*.
sheet. See also *Glass: flat, plate, window*.
bending, P (10) 244*j*.
bending and tempering, P (11) 270*b*.
coated, P (8) 192*c*.
with colored coating, P (11) 270*b*.
controlling thickness, P (11) 270*d*.
dazzle-preventing and heat-blocking, P (7) 161*a*.
downdrawing method, P (4) 81*f*.
drawing process, temp. distribution, (9) 216*c*.
electric welding, P (4) 81*g*.
forming in mold, (11) 268*d*.
ion exchange in, (3) 55*c*.
scoring, P (11) 270*i*.
vertical drawing process, (8) 190*a*.
vertical suspension method, P (10) 245*e*.
silicate, alkali mobility and relaxation in, (5) 106*g*.
cation self-diffusion in, (7) 158*h*.
chemical vapor deposition, (9) 216*i*.
crystallization, (11) 268*h*.
fatigue, (1) 3*c*.
ir absorption spectra, (9) 217*a*.
Ni spectra and structure in, (5) 106*d*.
and phosphate, Moessbauer spectra, (7) 160*c*.
radioluminescent, P (7) 163*c*.
standard ir spectra, (9) 218*f*.
thermal expansion, (9) 216*g*.
transport phenomena in, (9) 217*a*.
uv absorption of Pb in, (1) 3*g*.
SiO_2, determination, (8) 204*g*.
rare earth activated, (9) 216*h*.
-Al_2O_3-CaO-Na_2O, crystallization, (8) 190*g*.
-Al_2O_3-Li_2O, P (2) 35*c*.
-Bi_2O_3-Na_2O, properties, (3) 57*d*.
-CdO batches for expansion glasses, P (7) 162*j*.
Ag^+ and Cu^+ ions diffusing into, (3) 56*j*.
sitalls. See *Glass-ceramics*.
slab facing materials, sealing system for, P (10) 244*d*.
slag, sulfide S in, (8) 190*h*.
Na and K silicate, angle measurements on Pt, (11) 269*h*.
Na aluminosilicate, dielectric properties, (7) 158*h*.
Na borate, fluorescence of Dy^{3+}, Eu^{3+}, Sm^{3+}, and UO_2^{2+} in, (7) 159*b*.
Na borosilicate, -Al_2O_3 composite, (1) 3*d*.
Na borosilicate, opalescent, (7) 160*e*.
Na diffusion in, atm. effects, (6) 131*h*.
NaF-Na_2O-B_2O_3, B_2O_3 anomaly in, (11) 268*d*.
Na_2O in, determination, (8) 204*g*.
Na_2O-B_2O_3-SiO_2, inert gas diffusion in, (2) 32*b*.
Na_2O-CaO, attack in strong acid, (11) 267*i*.
Na_2O-CaO, softening and working temp., P (3) 59*b*.
Na_2O-CaO-SiO_2, analysis, correction for matrix effect in, (8) 205*e*.
batch analysis, (8) 205*c*.
blue, P (7) 162*b*.
damping, (5) 116*f*.
wet chemical analysis, (8) 204*e*.
X-ray fluorescence analysis, (2) 32*j*.
Na_2O-MgO-SiO_2, H_2O attack on, (11) 269*i*.
Na_2O-$3SiO_2$, electrical relaxation in, (11) 268*c*.
Na_2O-$3SiO_2$, relaxation in, (11) 269*a*.
Na_2O-TiO_2-SiO_2, elastic moduli, (8) 191*d*.
Na oxide-containing, (2) 32*b*.
Na oxide-containing, alkali ions in, (2) 32*b*.
Na silicate, phase separation, (3) 57*c*.
properties, (10) 243*j*.
thermal properties, (9) 218*j*.

Glass *(continued)*
$Na_2Si_2O_5$, glass transition, (3) 57*b*.
Na-Sn-SiO_2, ir absorption spectra, (9) 217*b*.
solder, P (6) 132*j*; P (10) 245*g*.
spheres, from quartz particles, (9) 218*c*.
stained, simulated leaded, P (7) 163*a*.
stemware, tempered, P (2) 35*b*.
strengthened, fracture and strength, (3) 56*d*.
strengthening, P (1) 5*f*; P (7) 162*h*.
strengthening chemically, P (4) 82*b*.
stress buildup in, by uv radiation, (3) 55*e*.
stresses, effect of ultrasonic waves, (11) 269*i*.
Sr borate, ^{11}B NMR spectra, (11) 268*a*.
SrO, for storing fission products, (8) 190*j*.
$SrSiO_3$-$ZnSiO_3$, liquation in, (9) 217*g*.
structural relaxation, (1) 3*f*.
structure, and crystallization, B (5) 126*b*.
from NMR spectra simulations, (4) 81*b*.
imaging in electron microscope, (8) 205*b*.
sulfate, oxidation states of Pt metals in, (2) 32*f*.
sulfide, properties and structure, (6) 132*e*.
superficial layers on, thickness, (7) 159*g*.
surface, auger spectroscopy, (2) 32*c*.
composition, (2) 32*c*.
dealkalization, P (7) 161*b*.
glare-reducing, P (2) 34*g*.
ion-exchanged, blocking effect, (7) 158*f*.
Li silicate coating on, P (4) 82*f*.
properties, modification, (8) 191*c*.
tension, measurement by dipping cylinder method, (7) 173*a*.
synthesis, P (10) 245*d*.
synthetic melilite, hydration, (4) 79*e*.
system, Sb-Ge-Se, conductivity, (9) 217*e*.
As-S, As-S-I, and As-S-Tl, (6) 131*j*.
As_2S_3-Sb_2S_3-S, (6) 132*e*.
$BaO·2SiO_2$-$2BaO·3SiO_2$, (8) 189*f*.
B_2O_3-PbO and B_2O_3-SiO_2-Na_2O, (5) 105*g*.
CaO-MgO-P_2O_5, devitrification, (5) 105*h*.
Cs_2O-Al_2O_3-SiO_2, (10) 243*e*.
designing, (3) 57*a*.
Ge-Se, magnetic susceptibility, (9) 217*f*.
$Ge_xAs_{40-x}S_{60}$, heat capacities, (5) 106*b*.
PbO-B_2O_3, viscosity, (8) 192*e*.
PbO-TiO_2-Bi_2O_3-MgO-SiO_2 and PbO-TiO_2-SiO_2, ferroelectric activity, (8) 190*i*.
Li_2O-Al_2O_3-SiO_2, (2) 32*i*.
Li_2O-Al_2O_3-SiO_2-GeO_2, (2) 33*h*.
Li_2O-B_2O_3-GeO_2, (6) 132*e*.
Li_2O-MgO-CaO-Al_2O_3-SiO_2-F, crystallization, (3) 57*i*; (5) 106*b*.
Li_2O-SiO_2, Na_2O-SiO_2, K_2O-SiO_2, and Rb_2O-SiO_2 (2) 33*e*.
M_2O-GeO_2 and M_2O-B_2O_3-GeO_2, (8) 189*j*.
Mn-Nd, Mn-Ho, and Mn-Er, (3) 57*e*.
MnO-Fe_2O_3-B_2O_3, magnetic properties, (11) 269*f*.
K_2O-SrO-SiO_2, cation self-diffusion coeff., (5) 105*j*.
K_2O-SrO-SiO_2, diffusion in, (7) 158*j*; (9) 216*h*.
SiO_2-Al_2O_3-CaO-MgO, crystallization, (4) 80*j*.
Na_2O-BaO-SiO_2, (3) 56*h*.
Na_2O-CaO-MgO-SiO_2, (2) 33*a*.
Na_2O-CaO-MgO-SiO_2, phase equilibria in, (11) 269*c*.
Na_2O-GeO_2, crystallization, (9) 216*d*.
Na_2O-K_2O-SiO_2 and Li_2O-K_2O-SiO_2, viscosity, (7) 161*c*.
wet-chemical preparation, (9) 218*a*.
technology, society, chemical analysis committee, (8) 192*g*.
television tubes. See *Tubes*.
tellurite, acousto-optic material, (5) 106*d*.
temp. measurement, (10) 243*f*.
tempering, P (7) 162*h*.
chemical, P (4) 82*i*; P (7) 161*j*.
chemical, temp. control, P (4) 83*a*.
chemical and thermal, P (7) 161*j*.
by ion exchange, P (10) 245*b*.
tensile members, P (3) 59*h*.
thermally crystallizable, P (3) 59*j*.
thermochemical investigations, (4) 81*f*.
thermoluminescence in, (5) 106*c*.
thickness, nondestructive measuring, P (6) 133*c*.
thin films, for electron microscopy, (11) 278*h*.
thin, strengthening, P (8) 193*g*.
TiO_2-SiO_2, He migration in, (5) 106*b*.
toughened, P (7) 162*e*.
toughening, P (10) 245*h*.
toughening in oil bath, P (5) 107*e*.
transformations in, (11) 270*h*.
transition in amorphous precipitates, (3) 56*h*.
transition, and viscous liquids, (7) 161*d*.
transparent, crystallized, P (10) 245*i*.
or opaque, P (9) 219*d*.
thermal tempering, P (3) 59*h*.
treating process, P (2) 34*e*.
tubes. See *Tubes*.
W-V-phosphate, electrical conductivities, (8) 190*d*.
for ultrasonic delay line, P (10) 244*a*.
ultrasonic transmission medium, P (7) 163*b*.
uv ray cutting, for photography, P (9) 220*b*.
use as garden mulch, (5) 106*a*.
valve, explosively activated, P (9) 218*j*.
vanadate, optical absorption, (5) 106*f*.
V- and Fe-containing, conduction in, (3) 55*f*.
V_2O_5-Na phosphate, V structure in, (6) 131*j*.
V phosphate, conductivity, (5) 106*g*.
magnetic behavior and micro-structure, (4) 80*g*.
polaronic hopping conduction in, (5) 106*g*.
verneuil boules, of Ca_2SiO_4, stabilization, (6) 132*h*.
viscosity-temp. curve for, (11) 269*f*.

Glass *(continued)*
wall, effect on plasma conductivity determination, (3) 59*i*.
mounting disks in, P (10) 245*d*.
securing metal member to, P (3) 59*g*.
-ware, coating, P (11) 270*d*.
colored, P (9) 219*i*.
phase-separated, surface layers in, (11) 269*b*.
printing on, P (4) 82*e*; P (9) 219*c*.
protector, P (1) 5*c*.
waste, building brick from, (7) 159*h*.
waste, for building materials, (10) 243*h*.
H_2O content, effect of melting conditions, (9) 217*j*.
window. See also *Glass: flat, sheet, plate*.
corrosion by demineralized H_2O, (11) 268*f*.
fractures in, (9) 218*b*.
installation (1) 3*e*.
ir-transmitting stress-free, P (4) 81*a*.
medieval, (1) 1*j*.
medieval stained, (1) 1*i*.
multiple glazing units, P (8) 193*d*.
spaced conductive element, P (7) 161*g*.
vehicle, glazing, P (7) 162*a*.
windshields, laminated safety, P (1) 5*e*.
wool. See *Fibers, glass*.
yarns. *See Fibers, glass*.
X-ray fluorescence analysis, (8) 191*c*.
$ZnCl_2$, (5) 106*b*.
Zn-La borate composition, P (10) 245*j*.
Zn phosphovanadate compositions, P (7) 162*g*.
Glass industry, cooperation with laboratories, (8) 189*i*.
energy supplies in, (5) 106*i*.
flat, increase in imports, (3) 56*b*.
marketing and selling in 70's, (10) 243*e*.
recycling in, (5) 105*j*.
Rockware, conversion to butane, (4) 80*i*.
Sajoszentpeter, N. Hungary, (2) 32*b*.
Wheaton Glass uses electric furnaces, (5) 106*h*.
Glassmaking apparatus and equipment. See also *Burners*.
for applying oxide coating, P (2) 34*h*.
article inspection and reject, P (8) 192*a*.
atm. tweel seal, P (5) 106*j*.
blow mold station, P (5) 107*h*.
for blow molding, P (7) 162*e*; P (11) 270*b*, *c*.
for blow molding bulbs, P (4) 81*j*; P (9) 218*c*; cooling, P (4) 82*a*.
blowhead-operating, P (4) 81*a*.
for bottles, P (6) 133*e*.
loading, P (3) 57*i*.
plunger for, P (9) 219*h*.
sorting, P (4) 81*j*.
bulb blowing, P (6) 132*g*.
bulb, light, traying machine, P (7) 163*a*.
for bulb-shaped containers, P (4) 82*i*.
chuck, container-handling, P (2) 33*h*.
for closed tubes with pellet in, P (7) 161*f*.
for coated flat, P (3) 59*a*.
for coating in float glass method, P (8) 192*d*.
for coating hot glass, P (7) 161*f*.
for collecting tubes, P (9) 218*c*.
for comminuting ware, recycle, P (7) 162*h*.
for containers, P (3) 58*g*.
crown ring inspection, P (4) 81*b*.
handling, P (5) 107*d*.
containers for molten, P (7) 161*a*.
control, automatic, for drawing, P (3) 57*h*.
to control speed of sheet on gas support bed, P (4) 82*a*.
for controlling light propagation in optical fiber, P (3) 57*f*.
for conveying in forehearth, P (1) 3*d*.
conveyor, for bottles, P (2) 33*d*.
conveyor for sheets, P (10) 244*b*.
for conveyor flow control, P (1) 3*i*.
for cooling and shaping sheet, P (9) 218*d*.
crack-off, for articles, P (7) 161*a*.
for cutting, P (2) 33*a*; P (4) 82*a*; P (11) 270*i*, *j*.
and grinding, P (10) 243*e*.
tube, P (4) 82*d*.
dead plate assembly, P (1) 3*j*.
designs and systems, continuous, (3) 55*g*.
for detecting defects in container, P (3) 58*g*.
deviation controller, for forehearth temp., (8) 191*c*.
for dissipating foam on molten, P (6) 132*a*.
for drawing, continuous sheets, P (8) 192*a*.
devitrifiable glass, P (1) 4*d*.
sheet, P (1) 4*e*; P (2) 33*b*; P (4) 82*c*.
sheet, cooler for, P (4) 81*c*.
for etching plate, P (2) 33*b*.
feed, for vials and bottles, P (7) 161*d*.
feeder, of Pt-Rh-Ho alloy, P (3) 58*h*.
for feeding, P (3) 57*f*.
for feeding molten, P (3) 58*j*.
for fibers, P (3) 57*g*; P (4) 82*a*.
articles, P (10) 243*g*.
optical, P (1) 3*g*.
with rotating bushing, P (4) 81*j*.
from thermoplastics, P (4) 82*b*.
for filaments, P (1) 3*k*; P (2) 33*c*; P (10) 243*g*.
for firing graduations, symbols, and lettering into articles, P (6) 133*g*.
for flat, P (9) 218*d*; P (10) 244*i*; P (11) 270*a*.
floating on liquid, P (7) 161*h*.
on molten metal, P (4) 82*e*.
on molten metal bath, P (4) 82*j*.
for float, P (1) 4*g*; P (2) 34*a*, *b*; P (6) 132*f*; P (6) 133*i*; P (8) 192*h*, *i*; P (8) 193*h*.
bath temp. control in, P (5) 106*j*.
controlling temp., P (3) 58*c*.
with flow control dams, P (1) 4*c*.

Glassmaking, for float *(continued)*
with lateral guides, P (3) 58*c*.
with longitudinal dams and metal flow control means, P (1) 4*c*.
movable restrictor tiles in, P (9) 219*e*.
plenum chamber closures, P (1) 4*d*.
for sheet crystalline material, P (11) 270*f*.
start-up hood in, P (11) 270*j*.
water fence support in, P (7) 163*a*.
for foam, continuous manufacture, P (1) 4*d*.
for foamed panels, P (4) 81*i*.
forehearth color concentrate, P (8) 192*i*.
-forming, P (3) 58*i*; P (8) 193*a*; P (11) 270*a*.
with article support, P (2) 34*e*.
blanks in optical-quality homogeneous, P (7) 162*i*.
and drawing SiO_2 tubes, P (3) 58*j*.
fluid flow control means, P (4) 82*a*.
hollow articles from sheet, P (1) 4*f*.
lip on container, P (11) 269*j*.
with position sensor, P (1) 4*g*.
for fracturing hot gobs, P (1) 3*e*.
furnaces. See *Furnaces*.
gas hearth with gas-supply channels, P (11) 270*h*.
gob delivery, P (7) 161*j*.
gob shaping and delivering, P (10) 244*a*.
for grinding. See *Grinding apparatus*.
gripping tongs, P (1) 4*g*.
for handling and cutting, P (9) 219*c*.
handling and transferring for sheets, P (9) 219*e*.
for handworking, P (1) 3*h*.
heat load, (3) 55*d*.
for heat-treating sheets, P (1) 4*f*; P (6) 133*h*.
for heat-treating tubular material, P (1) 3*f*.
Heye forming, for lighter containers, (8) 189*h*.
for hollow articles, P (9) 219*g*.
for homogenizing, P (3) 57*e*.
for inspecting, bottle by radiant energy, P (1) 4*i*.
hollow articles, P (11) 270*d*.
surface, P (9) 219*i*.
with fiber-optic guides, P (5) 107*h*.
IS, 8-section, (8) 189*g*; 191*g*.
IS, solid blank process on, (8) 191*f*.
for joining parts or articles, P (8) 193*i*.
laminating procedure, P (7) 161*j*.
lehrs, annealing, P (1) 4*e*.
lens edging, P (10) 244*b*.
for loading articles into cases, P (10) 243*h*.
loading and unloading, P (1) 4*a*.
M-16 for thin-walled ware, (8) 191*h*.
marking, portable means, P (11) 270*g*.
for mechanical operations on sheet, P (11) 270*a*.
-melting, electrically heated, P (9) 218*j*.
melting pot P (3) 58*j*; P (8) 193*b*.
for melting to make laser rods, P (8) 192*h*.
for mixing batch materials, P (1) 5*d*.
for modifying, P (7) 162*g*; P (9) 219*h*.
float glass, surface, P (4) 81*i*.
surface in float process, P (4) 82*a*.
molds. See *Molds, glass*.
for moving article on conveyor, P (1) 3*j*.
optical, lens blocking, P (9) 219*g*.
for orienting cords in downdraw bowl, P (8) 192*i*.
for ornamenting articles, P (10) 243*f*.
packaging protector, P (2) 34*j*.
for placing refractory pins in TV tube face plate, P (4) 82*g*.
for polishing. See *Polishing apparatus*.
preform roller, P (10) 245*a*.
for preheating batch, P (1) 4*g*.
for press bending sheets, P (2) 33*c*.
pressurizer nozzle for, P (7) 162*f*.
to produce metallic surface finish, P (4) 82*a*.
for profile and plate in band form, P (8) 192*j*.
for profiled bars, P (8) 194*i*.
pultrusion, P (11) 270*h*.
for removing, bubbles from sheet overflow forming surfaces, P (1) 4*h*.
excess coating from filaments, P (10) 243*e*.
gas bubbles from, P (3) 58*a*.
for ribbon, P (10) 243*f*.
blow head mechanism, P (6) 132*i*.
by float process, P (8) 192*j*.
on molten metal bath, P (11) 270*h*.
Roirant S-10, (8) 191*h*.
for scoring sheet, P (1) 3*j*.
for separating foam from molten body, P (9) 219*h*.
for severing linear material, P (6) 132*b*.
shears, for molten, P (1) 5*e*; P (10) 245*f*.
for sheet, P (7) 162*f*, *j*.
for bending, P (1) 4*c*; P (4) 82*i*.
for bending and tempering, P (4) 82*j*; P (10) 244*c*.
for conveying through adjacent stations, P (1) 3*e*.
cutting, P (10) 244*c*.
for grinding edges, P (5) 106*i*.
handling, P (7) 162*j*; P (10) 244*i*; P (11) 270*a*.
press bending, P (3) 58*a*; P (11) 270*a*.
for reshaping, P (1) 4*i*.
for separating, P (5) 106*j*.
stacker, automatic, P (4) 81*j*.
tempering, or plates, P (10) 243*h*.
treating, P (5) 107*b*.
for silk-screening on substrate, P (5) 107*c*.
for skimming surface of molten metal baths, P (7) 161*h*.
for spray marking, P (3) 58*h*.

Glassmaking *(continued)*
for supporting flexible ribbons and sheets, P (1) 3*g*.
for surface modification, P (1) 5*b*; control system for float, P (1) 5*c*.
for tempered articles of channel or U cross-section, P (1) 4*h*.
for testing ware, P (3) 59*i*.
tool, heat control in, P (6) 132*j*.
for transferring articles, P (10) 243*h*.
treating tunnel, P (8) 193*c*.
triple gob mold holder arm, P (1) 5*e*.
tube forming, P (4) 82*d*.
for tubular optical, P (10) 244*i*.
turnover and packing, P (10) 244*d*.
for uniting edges of double pane, P (7) 161*c*.
for uniting glass parts, P (13) 58*g*.
for vapor coating, P (8) 193*h*.
-ware, burn-off, controlling fuel supply to, P (2) 35*a*.
cooling and transfer, P (7) 162*a*.
-forming, parison-forming unit for, P (1) 5*f*.
for welding tubular rods, P (3) 57*g*.
for windshields, P (5) 107*b*.
Glazes. See also *Decoration.*
ash, for cone 6, (2) 30*a*.
-body, reactions, (1) 10*a*.
ceramic, chemistry and technology, (7) 165*a*.
for ceramic parts and articles, P (2) 38*c*.
ceramic pigments in, (1) 9*j*.
colorant, Cr as, (2) 30*c*.
colors in pottery studio, (11) 266*c*.
for concrete, P (5) 104*g*.
conducting, based on Fe oxide, (11) 272*h*.
crackle, (2) 30*d*.
crawling, (1) 10*a*.
for dry-press glazing process, (8) 194*e*.
earthenware, reaction with body, (8) 197*j*.
electroconductive, P (1) 12*j*.
electrostatic application, (4) 85*e*.
frits. See *Frits.*
for hard porcelain, (2) 37*j*.
Pb in, benefits and precautions, (1) 10*c*.
microquantity determination, (10) 255*h*.
research on, (1) 9*j*.
research by ILZRO, (1) 10*c*.
seminar introduction, (1) 10*c*.
leadless, B (2) 50*j*.
properties, (11) 272*j*.
raku, (2) 30*c*.
for ranges, (2) 30*b*.
reduction, compositions for, (8) 198*b*.
research and technology, (1) 10*c*.
resistor, Ru-based oxides in, (4) 86*d*.
semiconducting compositions for insulators, P (8) 198*f*.
silicate, structure study, (5) 111*e*.
surfaces, making patterns on, P (9) 223*c*.
Zn crystalline, (3) 61*i*.
Glazing, bone china, P (8) 198*f*.
brick, green and fired, comparison, (4) 83*g*.
ceramic ware, P (10) 248*i*.
double, P (9) 218*h*.
Au-Cr films with Pb-containing glass, (9) 217*i*.
sealing materials for, (7) 160*d*.
stoneware, (11) 266*a*.
strip, P (7) 162*a*.
tiles and tableware, (4) 92*f*.
unit, P (8) 193*c*.
units, welded multiple, P (8) 193*d*.
vehicle windows, P (7) 162*a*.
Glossaries. See *Nomenclature.*
Glucose, α-D, NMR studies, (3) 55*b*.
Glycine, adsorbed on montmorillonites, ir spectra, (11) 281*b*.
Goethite, thermal decomposition, (5) 120*d*.
Gold, atom, in photosensitive glass, ESR, (3) 55*h*.
-Cr films, glazing with Pb glass, (9) 217*i*.
film, deposition on substrate, P (7) 169*g*.
films on $LiNbO_3$, surface acoustic waves, (5) 123*b*.
patterns, conductive, P (11) 277*f*.
removal process, electrolytic, P (8) 200*a*.
-SiO films, semiconductor behavior, (6) 137*a*.
Grain boundaries, diffusion parameters, calculation, (7) 176*j*.
dislocations, (6) 148*h*.
and dislocations, diffusion along, (5) 119*a*.
grooving, causes electromigration damage in thin films, (5) 111*j*.
at Pt/Al_2O_3 interface, (2) 50*c*.
of UC, (7) 171*i*.
role in O self-diffusion in MgO, (3) 75*c*.
sliding in ceramics, (9) 235*h*.
sliding, in polycrystalline solids, (6) 148*h*.
structure and energy, with computer, (5) 118*i*.
twist, in alkali halides, (10) 261*e*.
twist-disclination loops, slip propagation by, (6) 151*f*.
Grain growth, in Al_2O_3, compacts, very porous, (4) 96*i*.
during densification, (11) 280*h*.
effects of MgO, ZnO, and NiO, (1) 21*c*.
in Al_2O_3-Cr_2O_3 system, (5) 125*h*.
of CeO_2, effect of TiO_2, (6) 147*a*.
in Cu_2O, kinetics, (4) 97*j*.
during sintering of Al_2O_3, (3) 73*b*.
in hematite, (3) 75*e*.
in MgO and MgO-Fe_2O_3 solid solutions, (2) 48*b*.
of MgO during sintering, (2) 49*j*.
in YIG, (8) 209*d*.
Grains. See *Particles.*
Grading machines. See *Machinery and equipment.*
Granular materials. See also *Powders.*
compaction, P (7) 172*b*.
cooling in beds, (7) 175*a*.
dry separation, P (9) 229*g*.
fine, heat treatment, P (2) 45*f*.
fine, preheating apparatus for, P (8) 206*g*.
fluid characteristics, measuring, P (9) 231*f*.
gravity separation, P (10) 254*j*.
impact flowmeter for, P (2) 45*a*.
mixture, porosity fluctuations in, (3) 73*j*.
permeability, measuring, P (2) 45*b*.
stabilizers for, P (1) 17*a*.
supplying apparatus, P (9) 229*g*.
Granulation. See *Crushing; Grinding.*
Granulometry. See *Particle size.*
Graphite. See also *Carbon.*
anode treatment, P (4) 84*j*.
anodes, for cathodic protection, (5) 109*g*.
article, P (8) 196*e*.
increasing strength and conductivity, P (2) 37*c*.
reinforced, P (10) 248*c*.
SiC-encased, P (4) 85*b*.
bodies, reinforced, P (8) 197*b*.
brazing, P (10) 248*a*.
-bromine, residual compounds, (2) 49*c*.
C, from degradation of aromatics, (1) 22*j*.
and C shapes, oxidation-resistant, P (9) 222*c*.
compressibility data, (6) 149*a*.
conversion to diamonds, P (4) 77*f*.
fibers, P (4) 84*i*.
field ion microscopy, (5) 116*d*.
heat treatment, P (4) 84*a*.
for plastic reinforcement, P (4) 84*d*.
uniform, P (4) 84*i*.
filaments, P (7) 164*c*.
fracture energies (2) 47*j*.
glass-bonded compositions, P (4) 84*j*.
-glass compositions, P (3) 58*a*.
graphitization, P (2) 37*g*.
of acrylic polymer fibers, P (9) 222*b*.
catalytic, of glassy C, (8) 194*g*.
process, P (8) 196*j*.
impregnated with Bi-Ni alloy, P (9) 228*h*.
impregnation, by pulsed method, P (9) 229*a*.
interaction with O disilicides, (10) 259*c*.
moderators, for nuclear reactors, P (1) 16*c*.
pallet and mask for substrates, P (10) 250*f*.
polycrystalline, P (6) 139*c*.
polycrystalline, porosity effects in, (5) 122*f*.
powders, diffusion chromizing, (10) 246*j*.
products, ASTM standards, B (10) 262*c*.
pyrolytic, P (10) 248*a*.
atomic displacements in, (4) 95*d*.
C fiber coated with, (5) 108*i*.
curved bodies, P (6) 135*b*.
elastic constants and Grueneisen parameters, (10) 258*j*.
reaction with Ti and Zr nitrides, (3) 60*h*.
shaped articles, P (4) 85*b*.
Raman spectrum, (7) 179*j*.
reactivity to O_2, (1) 16*b*.
resistance, pressure-dependent, (4) 96*a*.
static fatigue, (1) 25*g*.
structures, dense, P (4) 84*e*.
surface energies, (7) 157*h*.
theory of conduction in, (1) 21*g*.
use as hot-pressing mold, P (4) 85*b*.
valence bands in, occupancy, (6) 146*j*.
welding and soldering metal wire to, (10) 249*a*.
wetting by molten metals and alloys, (10) 259*f*.
whiskers, P (9) 222*a*.
Gravity, specific, of aggregate, tests, (6) 130*h*.
specific, of clay minerals, (11) 282*d*.
Greases. See *Lubricants.*
Grinding *(Comminution).* See also *Crushing apparatus; Mills.*
cement, effect of adsorption, (7) 156*j*.
effect on strength, (4) 78*i*.
raw material, (6) 128*i*; (8) 186*c*.
closed-circuit, (2) 43*j*.
closed circuit, of cement, (9) 215*g*.
conditions, effect on cermet, (10) 246*i*.
cylindrical surfaces, P (11) 265*f*.
effect of environment, (11) 276*i*.
fine, fluid, P (10) 254*e*.
of granular or lumpy materials, P (11) 277*g*.
grindability of cement clinker, (4) 79*d*.
of industrial minerals, (11) 277*a*.
kinetic processes in, (5) 115*i*.
minerals, P (3) 69*g*.
oxygen-deficient system, P (2) 44*b*.
particulate matter, P (3) 69*e*.
particulate solid materials, P (2) 44*d*.
plates, P (11) 275*d*.
portland cement, mineral aids, P (1) 2*f*.
powder, conditions, effect on $MoSi_2$ heating elements, (10) 246*j*.
precision wide-belt, (2) 29*g*.
shaft, time reduced, (7) 155*e*.
solids, P (9) 230*e*.
tandem plant for cement raw meal, (8) 188*d*.
Grinding *(Material removal).* See also *Abrasives; Diamonds; Polishing.*
ceramic machining and surface finishing, B (10) 264*j*.
diamond, (1) 1*f*.
hard-steel, with Al_2O_3, (2) 29*f*.
lathe, of contact lenses, P (8) 194*c*.
lens surface, P (1) 4*j*.
Grinding apparatus. See also *Abrasives.*
P (7) 155*f*; P (11) 265*e*.
abrasive, resin-bound, P (4) 77*i*.
bond between abrasive grains and binder, (11) 265*e*.
with classifiers, (9) 214*i*.
Grinding apparatus *(continued)*
cutting, and polishing single-crystal workpieces, P (7) 172*f*.
cylindrical, P (8) 203*h*.
disk, P (2) 29*f*; P (11) 265*e*, 277*a*.
drill point, P (11) 265*e*.
glass, edge, P (3) 58*g*.
edges of articles, P (5) 107*j*.
fine, (8) 191*d*.
slides, P (9) 218*c*.
slides, corners, P (4) 81*b*.
with tools with diamonds, (3) 56*h*.
for mineral materials, P (4) 92*h*.
and polishing, sphere, P (2) 44*d*.
pneumatic drive means for, P (2) 46*a*.
precision surface, (2) 29*i*.
stone, P (4) 77*i*.
for tile edge, P (4) 86*b*.
wheels, P (1) 1*g*.
abrasive cutoff, P (11) 265*e*.
abrasive cutting, P (4) 77*f*.
abrasive disk, bonded, P (3) 53*i*.
cleaning and cooling, P (9) 213*e*.
diamond, (9) 213*e*.
diamond abrasive, P (3) 53*h*.
diamond, wear, (3) 53*e*.
dressing apparatus, P (10) 241*e*.
fiber-reinforced, P (2) 29*g*.
lubrication, P (1) 1*h*.
package, P (4) 77*g*.
performance equation, (2) 29*f*.
phosphate-bonded, P (3) 53*i*.
resinoid, with BN, P (6) 127*h*.
and resinoid pocketed cutoff, P (8) 185*e*.
rotary, P (9) 213*f*.
segmented, P (5) 101*g*; P (11) 265*f*.
unbalance, sensing, P (1) 1*h*.
vitreous, P (2) 29*j*.
Grooving, thermal, of MgO and Al_2O_3, (8) 211*a*.
Grueneisen, parameters, of graphite, (10) 258*j*.
Gunite, aged, properties, (6) 129*j*.
Gunn effect, device, controlled, P (3) 64*d*.
Guns. See *Spraying.*
Gypsum. See also *Plaster.*
articles, dried, P (9) 215*g*.
BaS as admixture to, (8) 185*i*.
calcined, P (8) 207*b*.
calcining, P (6) 130*g*.
in cement, determination, (5) 104*i*.
dehydration by autoclave, (5) 102*f*.
effect on concrete properties, (6) 129*h*.
effect on plaster strength, (3) 53*j*.
fluoro-, mineralizer in cement mfg., (6) 129*d*.
hemihydrate, P (2) 31*f*.
hydration kinetics and crystallization, (7) 156*c*.
lime and MgO in, (3) 69*h*.
pastes, hardened, microstructure, (5) 103*d*.
from phosphate rock, P (4) 94*h*.
phospho-, effect on cement hydration, (5) 104*a*.
plaster, cast articles, P (9) 223*b*.
plaster, retarded, P (7) 157*g*.
production, P (6) 130*g*.
purifying, with fluosilicic acid, P (5) 104*i*.
solubility in NaCl, (7) 156*g*.
standards, (4) 78*f*.
thermochemistry, (5) 104*e*.
C_3S, and C_3A, hydration, (5) 103*i*.

Hafnia. See *Hafnium, oxide.*
Hafnium, boride, thermal diffusion, (4) 97*e*.
carbide, stability, (3) 75*b*.
dioxide, and ZrO_2 compositions, P (4) 85*b*.
oxide, axial thermal expansion, (10) 258*c*.
oxide, -rare earth ceramics, P (5) 111*f*.
systems. See *Systems.*
tetrachloride, P (9) 232*j*.
titanate, properties, (1) 25*i*.
titanates, thermal expansion, compressibility, and polymorphism in, (9) 239*c*.
Halides, alkali, crystals, B (10) 263*h*.
crystals, thermal conductivity, (6) 152*b*.
defects in, by electron irradiation, (10) 261*c*.
filamentary crystals, (7) 176*d*.
films, deposited at low temps., (1) 25*a*.
twist grain boundaries in, (10) 261*e*.
of metals and Tl, melts of salts, (5) 125*i*.
Hall effect, coeff., in relaxation-case semiconductor, (7) 180*d*.
device, integrated, P (9) 225*e*.
in magnetic semiconductors, (6) 145*c*.
measurements on synthetic diamond, (4) 86*c*.
mobility in vitreous As_2Se_3, (2) 48*c*.
of WC, (6) 149*j*.
Halloysite, clays, compressibility and density, (8) 210*f*.
with organic compounds, complexes, (9) 233*h*.
Halogens, effect on luminescence of ions in glasses, (9) 216*i*.
Hardening, carbide compositions by boronizing, P (6) 135*i*.
cement, effect of temp., (8) 187*e*.
cement, with slag electrophosphorus production, (8) 186*f*.
of dispersions of system CaO-MgO-Al_2O_3-SiO_2, (7) 156*h*.
of dolomite lime mortars, (5) 103*f*.
strain, in pure NaCl, (10) 260*j*.
Hardness, indentation, of MgO-Li_2O-Al_2O_3-SiO_2-TiO_2 glass-ceramic, (7) 160*a*.
micro-, of glass, (4) 81*d*.
impressions in glass, (7) 159*i*.
measurements in grinding tools, (11) 265*e*.
of porcelain bodies, measurement, (9) 231*c*.
Health. See also *Air, pollution; Dusts; Safety; Silicosis.*
analysis of free SiO_2 in dust, (1) 17*d*.
ceramics in contact with foodstuffs, (7) 165*a*.
Pb, in ceramic containers, (7) 165*d*.

Health, Pb *(continued)*
in dinnerware glazes, (1) 9*j,i*; 10*c,e*.
poisoning, avoidance in earthenware, (9) 223*d*.
poisoning, control in earthenware, (7) 165*d*.
silicosis, in Dutch ceramic mfg., (5) 126*a*.
silicosis in Italian ceramic industry, (7) 182*f*.
Heat. See also *Conductivity, thermal; Temperature*.
of adsorption of H_2O vapor on X-zeolites, (1) 22*b*.
capacities, of glasses and liquids in system $Ge_2As_{6-x}Se_6$, (5) 106*b*.
capacities, of Ti chlorides, (4) 93*a*.
carrier, granular ceramic, P (9) 222*g*.
coeff. of optical index in solids, P (3) 70*a*.
content, of α-Al_2O_3, measurement, (9) 236*f*.
and capacity of ZrC, (10) 259*d*.
of Cu sulfate and oxysulfate, (7) 177*b*.
crystallization, of diopside and anorthite, (1) 22*g*.
of formation of $ZnSiP_2$ and $CdSiP_2$, (7) 177*j*.
high-temp., of rare-earth trifluorides, (8) 211*c*.
of $MnCl_2$, (4) 96*c*.
of mixing, in alkali sulfate mixtures, (3) 73*c*.
of mixing in systems $CaCl_2$-MCl-MBr-$CaBr_2$ (M is Na, K, and Rb), (11) 182*i*.
of UB_2, (4) 91*f*.
of $VN_{0.46}$, (6) 147*h*.
economy in tunnel kilns, (2) 45*g*.
effect on ettringite stability, (2) 31*c*.
emittance study of MgO films, (3) 75*j*.
exchange, during firing, (2) 45*c*.
exchanger system, (8) 186*g*.
exchangers, tubular, P (7) 174*i*.
flowmeter, P (10) 255*j*.
of fusion, of As and Sb compounds, (9) 235*i*.
of fusion, of fluoroperovskites, (1) 24*e*.
of hydration of cement, relation to temp. rise of concrete, (9) 215*c*.
of immersion studies on silicas, (5) 121*a*.
of ionization, of HO_2 and OH, (3) 73*f*.
load, of glassmakers, (3) 55*d*.
losses, furnace structural, estimation, (2) 45*e*.
nonisothermal techniques for studying sintering, (9) 237*f*.
probes, ZrO_2 conductive properties applied to, (7) 172*i*.
processing, minerals, P (9) 230*c*.
pump, semiconductor element for, P (2) 42*c*.
radiation absorbent picture, thermographic duplication, P (7) 172*b*.
resistance, high, materials, P (8) 201*g*.
sinks, diamonds as, (4) 86*e*, 87*b*.
package for integrated circuit, P (6) 137*i*.
semiconductor subassembly for, P (7) 170*h*.
source, radioactive, P (10) 254*b*.
specific, of ferroelectrics, (5) 124*f*.
specific, of rutile, (5) 124*b*.
stabilization of faujasite-type zeolite, P (1) 20*a*.
-storage devices, P (5) 206*d*.
thermal gradient, in tensile test, P (2) 44*h*.
transfer, P (8) 206*f*.
between air and falling particles, (7) 174*d*.
in microelectronic equipment, B (9) 240*d*.
in rotary cement kilns, (8) 186*a*.
and spacecraft thermal control, B (1) 27*j*.
thermal radiation, B (10) 264*e*.
in tunnel kilns, (10) 256*f*.
treating, Mn-Zn ferrites, P (7) 168*j*.
treatment, of CaO-Al_2O_3-SiO_2 glasses, (2) 32*e*.
effect on Ba ferrite powders, (10) 249*b*.
effect on glass crystallization, (9) 217*c*.
effect on Fe-Cr cermet alloys, (10) 246*j*.
effect on Mg-Mn ferrites, (8) 208*h*.
effect on stresses in SiO_2 films, (2) 39*d*.
of fine material, P (2) 45*f*.
of free-flowing materials, P (11) 277*f*.
of glass, fluor-richterite, (6) 131*j*.
of graphite fibers, P (4) 84*a*.
of lunar glass, (6) 132*h*.
of Mn ferrite, (9) 234*i*.
of Ni-Zn-Co ferrite, P (2) 40*j*.
oxidative, of C fibers, P (5) 110*a*.
of powder, P (4) 95*a*.
of semiconductor material, P (2) 42*d*.
and separator for fine material, P (1) 19*d*.
of TiC base materials, (10) 246*h*.
Heat conductivity. See *Conductivity, thermal.*
Heaters. See also *Thermoelectricity.*
clay area, P (10) 247*f*.
gas-fired ir, P (10) 256*i*.
resistance, P (4) 90*i*.
for testing high-melting-point cermets, (10) 247*i*.
Heating. See also *Thermoelectricity.*
air, apparatus, P (8) 206*f*.
constant rates, sintering equations for, (1) 21*a*; correction (3) 72*d*.
cycles, for glass during hardening, (8) 189*g*.
gases for TiO_2 pigment, P (4) 94*i*.
hf, cracks in glass-metal seals by, (10) 243*a*.
at high rates, thermal-shock resistance during, (10) 255*j*.
pre-, apparatus, regenerative blast, P (7) 174*h*.
pre-, fine granular material, P (8) 206*g*.
rate, effect on crystallization temp., (8) 189*f*.
reactor reaction space, P (8) 206*f*.
roasting solids, P (3) 72*b*.
rods, P (7) 174*e*.
super-, of albite feldspar, (4) 94*f*.
Heating elements. See also *Electrodes; Thermoelectricity.*
ceramic-coated, P (10) 242*g*.
electrical, P (3) 61*d*.
Heating elements *(continued)*
electrical, insulator for, P (9) 223*e*.
ir radiant open coil, P (2) 34*h*.
integral, P (5) 105*c*.
integrated, array and drive matrix, P (4) 88*h*.
$MoSi_2$, properties, (10) 246*j*.
oxide resistor, P (2) 41*j*.
resistance, P (8) 206*g*.
SiC, oxidation kinetics, (8) 195*a*.
surface, glass-ceramic, P (2) 34*a*.
transparent, P (7) 174*n*.
tubular, MgO insulation for, P (3) 61*f*.
Heavy clay industry. See *Structural clay products industry.*
Hectorite, clays, compressibility and density, (8) 210*f*.
electron microscope studies, (9) 235*d*.
Helium, diffusion, in glasses, (2) 32*b*.
diffusion and precipitation in BeO, (7) 171*d*.
flow into portland cement paste, (6) 129*c*.
flow of C_3S-H_2O system, (5) 103*h*.
ions, in Si and SiO_2, (6) 151*j*.
migration in SiO_2, (3) 56*j*.
migration in TiO_2-SiO_2 glasses, (5) 106*b*.
Hematite. See also *Iron, oxide, ferric.*
conductivity and Fe tracer diffusion in, (5) 119*e*.
domain wall and resonances in, (4) 96*e*.
magnon interactions in, (6) 150*e*.
sintering kinetics, microstructure and grain growth in, (3) 75*e*.
structural isotypes, (1) 25*j*.
thermal conductivity, (5) 125*b*.
ultrasonic behavior, (5) 125*a*.
Hertzian, fracture mechanics in glass, (7) 160*d*.
Holes, preformed, in substrates, positional deviations, (7) 167*d*.
Holmium, in $CaWO_4$, energy levels, (7) 177*h*.
hydroxide, magnetic properties, (8) 209*j*.
Holography, acoustical, to reveal defects, (5) 116*a*.
recording microscopic sample, P (9) 231*h*.
Homogeneity, in hot-pressing, (1) 16*h*.
of optical glasses, (10) 243*g*.
Homogenization, of cement raw materials, (9) 215*a*.
of raw mix, (8) 187*h*.
Hot tops. See *Refractories.*
Humidity. See also *Moisture; Water.*
effect, on Ca monosulfoaluminate hydrates, (1) 2*f*.
on mixing particulate solids, (7) 172*b*.
on stresses in SiO_2 films, (2) 39*d*.
Hydration, of Al_2O_3 cement, to CAH_{10} and C_2AH_8, (6) 128*f*.
of alite and belite in clay-cement, (10) 241*j*.
CaO-Al_2O_3, effect of Fe oxide, (9) 214*f*.
of 3CaO·SiO_2 in alkali presence, (4) 78*c*.
of 3CaO·SiO_2, effect of alkali carbonate, (9) 214*d*.
of $CaSO_4$ hemihydrate, (3) 73*f*.
cement, aluminous, SO_3 effect, (6) 129*i*.
phosphogypsum effect, (5) 104*a*.
stages, (6) 129*a*.
degree, of portland cement pastes, (10) 241*i*.
of glass, synthetic melilite, (4) 79*e*.
of gypsum, high-temp. effect, (7) 156*c*.
hardening, of Ca hydrosilicates, changes during, (7) 157*f*.
heat of. See *Heat.*
of MgO, electrically fused, (3) 60*d*.
of monocalcium aluminate, (4) 78*f*.
paste, of 4CaO·3Al_2O_3·SO_3, (7) 157*d*.
of portland cement, thermokinetics, (8) 188*f*.
products in calcium systems, (9) 214*a*.
resistance, of MgO, dead-burned, P (10) 248*d*.
of rutile surfaces, (3) 73*j*.
of C_3A-$CaSO_4$-H_2O systems, (5) 103*i*.
of C_3S, alite and solid solutions, (4) 78*h*.
kinetics, (7) 156*j*.
morphological study, (5) 103*f*.
Hydrocyclones. See *Separators.*
Hydrofluoric acid, reaction with glass, (2) 32*h*.
Hydrogels. See *Colloids.*
Hydrogen, bond studies, (10) 259*b*.
fluoride, gaseous, P (6) 144*d*.
HO_2, heats of ionization, (3) 73*f*.
production, P (11) 280*a*.
Hydrogen ion concentration, phosphor, controlling, P (2) 41*a*.
Hydrolysis, reaction from YF_3 to Y_2O_3, (11) 282*i*.
of SiF_4, P (8) 207*e*.
Hydrothermal process, on fluorhydroxyl chrysotile, (3) 73*f*.
Hydroxides, heats of ionization, (3) 73*f*.
in MgO, determination, P (1) 18*h*.
Hydroxyl, groups, in biotite, (1) 23*e*.
Hydroxylation, of rutile surfaces, (3) 73*j*.
Hygrometry. See *Humidity, measurement.*
Hysteresis, loop, of (Pb,Sr)TiO_3, time effects in, (3) 63*j*.

Ice, -brine interfaces, kinetics, (10) 258*g*.
Ignition, piezoelectric system, burner control, P (10) 256*h*.
Illite. See also *Clays.*
clays, compressibility and density, (8) 210*f*.
and kaolinite floccules, fabric of, (6) 148*c*.
specific gravity, (11) 282*d*.
Ilmenite, beneficiating, P (8) 207*b*.
chlorination, selective, kinetics, (2) 46*e*.
concentrate, production of rutile from, (1) 20*h*.
ore, beneficiating, P (10) 257*b*.
Image devices, -converting, solid-state, P (6) 140*g*.
intensifier with phosphor, P (10) 250*h*.
Immiscibility, in glasses containing Ag halides, (8) 190*c*.
liquid, in alkaline ultrabasic dikes, (8) 209*b*.
region in Li_2O-B_2O_3-GeO_2 system, (6) 150*h*.
Impact, resistance of ZrO_2 ceramics, (8) 195*h*.
Impurities, acceptor, diffusion into semiconductors, P (2) 41*b*.
acceptor, removal from Ge, P (9) 227*c*.
C, excluding from Si body, P (1) 15*c*.
combustible, removal from air or gas current, P (7) 174*f*.
concentration in semiconductors, determination, P (1) 13*a*.
diffusing into compound semiconductor substrate, P (8) 201*a*.
diffusing into SiC, P (4) 88*g*; P (11) 272*f*.
distribution in GaP layers, (9) 234*c*.
effect, on deformation properties of Al_2O_3 refractories, (8) 195*g*.
on $Mg(OH)_2$ powder, (1) 21*i*.
on reactivity of graphite, (1) 16*b*.
on sintered Al_2O_3, (1) 21*e*.
on sintering Al_2O_3, (1) 21*b*.
on work-hardening of LiF crystals, (6) 147*a*.
ions, implanting in semiconductor, P (4) 88*i*.
levels in diamond, (6) 151*j*.
platelet in diamond, (10) 261*h*.
predeposition, on semiconductive wafer, P (1) 13*d*.
profile, of semiconductor body, P (8) 201*j*.
removing in Bayer process, P (6) 144*e*.
residual, in GaAs, (2) 38*h*.
Index of refraction. See *Refractive index.*
Indium, Al phosphide, P (6) 138*b*.
ferrocyanides, with K, Rb, and Cs, (8) 211*j*.
$InAs_xP_{(1-x)}$, deposition on substrates, (9) 234*i*.
$In_{1-x}Ga_xP$ crystals, growth, (3) 73*d*.
oxide, free energy of formation, (2) 48*a*.
systems. See *Systems.*
thiospinels, magnetic properties, (10) 258*d*.
thiospinels, properties, (10) 260*a*.
tungstate, reaction with K tungstate, (2) 49*f*.
Infrared, absorption. See *Absorption.*
detecting materials, P (4) 88*f*.
drying. See *Drying.*
energy, for sealing reed switches, P (8) 193*f*.
far-, mixing in GaAs, (6) 148*e*.
optical scanning system, P (1) 18*g*.
radiation. See *Radiation.*
reflection, study of silicate glaze, (5) 111*e*.
spectra. See *Spectra.*
study, of NH_3 adsorption on MgO, (11) 281*c*.
of NH_3 adsorption on rutile, (1) 22*h*.
of rutile surfaces, (3) 73*j*.
of Si, Ti, and $SnCl_4$ reactions with rutile, (11) 281*c*.
transmission, in Al_2O_3, (1) 11*b*.
Inhomogeneity. See *Heterogeneity.*
Inorganic materials, industrial, vibration testing, (9) 230*h*.
nonmetallic raw, electron probe microanalysis, (2) 44*h*.
oxide, modern, B (9) 240*h*.
oxides, by cryochemical process, (3) 62*f*.
H_2O-repellent shaped articles from, P (9) 230*c*.
Inspection. See *Quality control.*
Instrumentation. See *Controls.*
Instruments. See also specific types.
in air pollution control, (9) 231*e*.
bolometer, immersed, P (4) 93*f*.
for checking radiation monitors, P (10) 255*i*.
chemical, (4) 93*d*; (8) 204*i*.
for contact angle measurements, (1) 17*f*.
for counting particles, P (2) 45*d*.
counting, sample holder, P (2) 45*b*.
to determine moisture content and/or temp., P (3) 70*d*.
for determining O quantities, P (2) 45*a*.
flowmeter, heat, P (10) 255*j*.
flowmeter, impact, for powders, P (2) 45*a*.
for holding crystal in X-ray, P (4) 93*d*.
magnifying, for observing crystal lattice, P (1) 18*g*.
for measuring, fluid characteristics of powders, P (9) 231*f*.
friability of particles, P (5) 116*e*.
permittivity, P (9) 231*f*.
states of surface, P (8) 206*a*.
permeameter, pocket, (5) 205*i*.
radiowave, for measuring slurry level, (8) 187*d*.
sensing, grinding wheel unbalance, P (1) 1*h*.
in spectrochemical analysis of solution, P (3) 70*d*.
for S determination, (7) 173*h*.
for S determination by combustion, (4) 93*c*.
thermoelectric couple, mounting for, P (9) 231*i*.
thermometric, improved, (11) 277*i*.
ultrasonic pulse-echo, for flaw size, P (6) 142*g*.
Instability. See *Stability.*
Insulation, acoustical, aggregates of mineral fibers for, P (8) 192*h*.
material, standards, (4) 84*b*.
Insulation, electrical. See also *Dielectrics; Glass; Porcelain.*
P (7) 168*f*.
ceramics for, at high frequencies, (7) 166*h*.
coating on Si, P (5) 112*h*.
compositions, P (7) 168*f*.
electrical transport properties in, (3) 72*f*.
electron beam evaporated quartz, P (3) 64*i*.
housing filled with SiC, P (4) 85*j*.
ion-free layers, P (9) 225*e*.
layers, on carrier body, P (6) 139*f*.
molded epoxy resin body, P (6) 136*c*.

Insulation, electrical *(continued)*
precipitating layers of, P (8) 201*f*.
for thermoelectrodes, (8) 199*e*.
Insulation, thermal. See also *Fibers, glass; Mineral wool; Refractories, insulating.*
P (4) 84*i*.
board, mineral aggregate, P (3) 61*a*.
$CaSiO_3$, P (7) 164*b*.
for dryers, kilns, (5) 116*j*.
fibers, P (6) 135*h*.
flexible sheet with BN fibers, P (10) 247*h*.
inorganic, P (4) 84*f*.
MgO, SiO_2 gel-containing, P (11) 272*f*.
materials for electric parts, P (6) 135*g*.
materials, structured, P (4) 85*c*.
solids, switching to conductive state, (4) 99*h*.
standards, (4) 84*b*.
for steel, stainless, P (5) 109*g*.
Insulators, electrical, P (11) 273*b*.
Al_2O_3, high-, P (2) 38*a*.
bore, machine for profiling, (11) 272*h*.
for conductor rail, P (7) 166*b*.
electric conduction in, (5) 122*e*.
for electrical heating elements, P (9) 223*e*.
high-temp., (7) 165*b*.
porcelain, B (6) 154*c*.
porcelain for, P (10) 248*g*.
for proportional counter, P (2) 40*b*.
quality test, (2) 37*i*.
semiconducting glaze compositions for, P (8) 198*f*.
sputter etch removal rates, (10) 249*a*.
Interferometry, fringe patterns, laser measurement, P (6) 142*g*.
Iodine, I_2+Te solutions, electrical conductivity, (6) 147*e*.
^{129}I, Moessbauer effect, in CrI_3, (5) 121*c*.
^{131}I, trapping, (1) 16*b*.
systems. See *Systems.*
Ionization, heats of, of HO_2 and OH, (3) 73*f*.
Ions. See also specific kinds.
alkali, bonding state, in glasses, (2) 32*b*.
anion and cation defect structure in Mg fluorogermanate, (10) 258*b*.
anions, poly-, adsorption by clays, (1) 9*h*.
beam implantation, for *pn* junctions, P (3) 66*d*.
beams, in microelectronics, (11) 273*e*.
binding by macrocyclic compounds, (4) 97*j*.
cation, diffusion in UO_2 solid solutions, (9) 228*f*.
distribution in spinels, (9) 235*b*.
effect on thermal properties of phosphates, (5) 120*c*.
exchange capacity, in K fixation, (9) 236*d*.
migration into clays, (5) 118*d*.
ordering in Mg ferrite, (1) 23*g*.
self-diffusion coeff., (5) 105*j*.
self-diffusion in MgO, (6) 145*f*.
self-diffusion in silicate glasses, (7) 158*h*.
self-diffusion in $UN_{1.8}$, (7) 171*b*.
stabilization of zeolite, P (1) 20*a*.
substitutions, effect on micas, (9) 234*e*.
transport in Al_2O_3, (6) 145*g*.
channeling in crystalline materials, P (7) 169*c*.
crystal, normal modes, (5) 122*i*.
crystals, Schottky defects in, (9) 234*c*.
exchange, in actinide oxide sols, P (4) 91*h*.
in clays, (1) 19*j*; (4) 85*h*.
effects in TiO_2:Fe^{3+}, (6) 151*i*.
equilibria, of zeolite, (1) 23*e*.
fields in $ErFeO_3$, (5) 120*e*.
of glass with CO_2, P (10) 244*f*.
K-Na, effect on silicate glasses, (9) 217*a*.
for separation of rare earths, P (2) 46*h*.
in sheet glass, (3) 56*c*.
strengthening glass article, P (2) 35*c*.
strengthening of glasses, P (2) 34*i*.
for tempering glass, P (10) 245*b*.
of ultrafiltrate, P (8) 193*e*.
of zeolites, P (10) 257*f*.
implantation, beam, *pn* junctions by, P (2) 41*a*.
for forming junction, P (1) 13*d*.
PbS mask, P (1) 12*h*.
for making ohmic contacts to semiconductors, P (1) 13*g*.
modifying *pn* junction by, P (7) 169*j*.
in semiconductor devices, P (2) 41*c*; (3) 63*d*.
impurity, implant in semiconductor, P (4) 88*i*.
lens, for microprobe apparatus, P (3) 70*b*.
magnetic, spin configuration in spinels, (3) 75*j*.
motion, effect on ^{133}Cs NMR in Cs borates, (7) 159*d*.
perchlorate and iodide, reaction between in alkali nitrate, (8) 211*d*.
rare-earth, luminescence in glasses, (9) 216*i*.
relaxation in Na_2O·$3SiO_2$ glass, (11) 269*a*.
surface, detecting on Si diodes and transistors, P (9) 226*d*.
transport in super ionic conductors, (10) 259*g*.
vanadyl, in alkali borate glasses, (9) 217*g*.
Iridium, dioxide, magnetic susceptibility, (6) 150*c*.
Iron. See also *Enameling metals; Steel.*
Armco, enameled, fatigue properties, (5) 105*b*.
borate devices, P (3) 65*g*.
carbides, from C-rich matrix, (1) 7*a*.
carbonyl, sintering, (10) 246*j*.
cast, ceramic tools for machining, (10) 246*e*.
cast, for glass molds, (3) 55*c*.
in cement, determination, (4) 78*g*.
corrosion in reinforced concrete, (4) 78*h*.
ferrous articles, diffusion coating, P (3) 54*i*.

Iron *(continued)*
ferrous, in calcite staining, (8) 204*h*.
fibers, C-containing, properties, (10) 247*d*.
-graphite, strength and antifriction, (10) 246*e*.
-ic oxide, Ba hexaferrite from, (5) 124*a*.
catalyst in anatase/rutile transformation, (9) 236*a*.
compounds, magneto-optical properties, (6) 152*i*.
Co-doped γ, P (9) 224*j*.
effect on Al_2O_3 ceramics, (7) 166*e*.
effect on sintered Al_2O_3, (1) 21*e*.
MgO, SiO_2, and CaO mixture, phase transformations, (8) 210*b*.
reaction with MgO in powder compacts, (1) 23*h*.
stoichiometry limits in, (5) 124*g*.
TiO_2, and Fe_2TiO_5 mixtures, dielectric properties, (3) 62*d*.
ions, effect on chrysotile formation, (1) 25*f*.
Fe^{2+}-bearing materials, absorption spectra, (11) 278*b*.
Fe^{2+}, effect on GdIG, (6) 147*b*.
Fe^{3+}, in CaF_2 crystals, EPR, (4) 96*c*.
in rutile, spectroscopy on, (5) 120*e*.
on SiO_2 gel, Al_2O_3, and natrolite, (4) 97*g*.
Fe(II) oxide, magnetic properties, (4) 97*c*.
Fe(III) oxide, reaction with $BaCO_3$, (1) 24*a*.
Fe(III) oxide, thermal dehydration, (8) 211*j*.
^{57}Fe in Ba ferrite, NMR, (6) 150*c*.
$FeSb_2$, neutron diffraction study, (5) 118*i*.
$FeBO_3$, Faraday rotation in, (3) 73*h*.
$FeCl_2$·$2AlCl_3$, structure, (6) 152*c*.
$Fe_{1-x}Co_xSb_2$, phase, (5) 118*i*.
Fe_3O_4 friction material, P (8) 196*i*.
Fe_3O_4 particles, dielectric properties, (3) 62*d*.
$FeSi_2$-FeSi mixtures, sintering, (7) 168*a*.
FeS_2, and $FeTe_2$, crystal structure, (5) 118*h*.
FeS_4, hydrothermal synthesis, (5) 121*c*.
Fe_2TiO_5, crystal, neutron and magnetic studies, (3) 74*c*.
Fe_2TiO_4, elastic properties, (3) 72*d*.
Fe_2TiO_4, magnetostriction and magnetic anisotropy, (3) 73*b*.
$FeVO_4$, crystal structure, (8) 208*i*.
in MgO, charge states, interactions, and relaxation, (5) 122*g*.
magnetite film on, (10) 249*c*.
nitride, for magnetic recording, P (10) 250*j*.
-ous oxide, crystals, (7) 179*e*.
oxide, conduction phenomena in, (5) 118*j*.
effect on CaO·Al_2O_3 hydration, (9) 214*f*.
films, by cathodic sputtering, P (7) 170*e*.
films, by sputtering, P (9) 228*e*.
solubility in alkali metals, (1) 25*c*.
oxides, Mn-Zn ferrite from, (10) 249*d*.
oxides, reaction with kaolinite, (9) 238*d*.
particles, stable magnetic, P (3) 67*a*.
plastic anistropy, grain size, and ductility, (6) 148*j*.
removal, from Al_2O_3, P (1) 20*f*.
and steel industry, refractories for, (6) 134*g*.
sulfides, synthesis, (8) 211*d*.
systems. See *Systems.*
X-ray emission spectra, electron microprobe study, (1) 23*d*.
Irradiation. See also *Radiation;* specific types.
electron, effect in flat glass, (9) 216*h*.
γ-, of photochromic glasses, (8) 190*h*.
induced Ti centers in borate glasses, (4) 81*g*.
neutron, for correction of optical aberrations, (8) 189*j*.
of phosphate glasses, (5) 106*h*.
in triglycine sulfate and Sr-$BaNbO_3$, (5) 123*a*.
uv, effect on glass electrical properties, (3) 55*c*.
of UO_2, high temp., (1) 15*h*.
Isotherms, liquidus, in Ga-In-As system, (9) 236*d*.
H_2O adsorption for Ca silicate hydrates, (9) 213*j*.
Isotopes. See also *Radioactive tracers.*
radioactive, for cement plant control, (5) 104*c*.
radioactive, in determining Ag losses during glassmelting, (8) 192*d*.
radio-, instrument for cement analysis, P (3) 54*d*.
radio-, ^{40}K, for determining K_2O in feldspars, (8) 205*g*.

Jahn-Teller effect, domains in $Mn_xFe_{3-x}O_4$, (7) 178*a*.
in Γ exciton of LiBr, (6) 149*c*.
of MgO:Cu^{2+} at 4.2°K, (5) 120*b*.
in MgO:Fe^{2+} spectra, (5) 121*f*.
in system Ta_2CrO_6-$TaCrO_4$, (10) 259*h*.
Jewelry. See *Art and artware.*
Joints. See also *Seals and sealing.*
for connecting C electrodes, P (2) 37*d*.
of concrete precast members, (6) 129*f*.
dielectric-to-metal, P (3) 65*i*.
Junctions, Cd-Al_2O_3-Al, electron tunneling in, (5) 120*b*.
CdS Schottky-barrier, spectroscopy, (6) 152*g*.
forming by ion implantation, P (1) 13*d*.
hetero-, *np* ZnO-Si, properties, (4) 96*i*.
hetero-, Se semiconductor, device with, P (3) 64*f*.
metal-to-ceramic, P (10) 252*b*.
planar *pn*, P (10) 252*i*.
pn, device, P (10) 251*h*.
formation during epitaxy of GaAs, (6) 151*a*.
modifying by ion implantation, P (7) 169*j*.
observation by SEM, (11) 274*b*.
passivated, P (2) 41*a*; P (3) 66*d*.
in ZnSe, ZnS, or ZnS/ZnSe, P (9) 227*h*.

Junctions *(continued)*
semiconductor, P (10) 251*c*.
devices, P (7) 168*e*.
glass passivating Si, P (4) 90*d*.
thermocouple, nonwelded, P (1) 18*h*.
Ti-Si rectifying, P (3) 68*b*.
using Y as solvent, P (9) 228*b*.
Zr-ZrO_2-Au, switching in, (6) 145*c*.

Kaolin, and bauxite for refractories, (11) 271*g*.
beneficiation, with magnetic separators, (9) 232*e*.
bodies, densification in, (11) 280*j*.
computer control, (4) 94*e*.
clay, brightening, P (8) 207*f*.
clay, gray, improving brightness, P (7) 175*d*.
deposit, migration of trace elements in, (1) 20*b*.
Karlsbad deposits, zones in, (5) 117*d*.
product, P (4) 94*h*.
shear distortion, (5) 117*c*.
suspensions, coagulation, (6) 146*a*.
coagulation and dispersion, (7) 178*f*.
coagulation and flocculation, (2) 46*a*.
rheology, (11) 273*c*.
systems. See *Systems.*
thermal transformations, (7) 181*i*.
Kaolinite, bodies, clinochlore-, SEM, (9) 223*e*.
calcite, and quartz, or dolomite, synthesis, (5) 121*a*.
clinochlore-, body, cordierite from, (8) 197*i*.
Cu^{2+} in, EPR, (6) 147*j*.
decomposition, (3) 74*h*.
disorder in, (6) 146*d*.
disordered, adsorption hysteresis on, (2) 46*j*.
floc sizes, (2) 37*h*.
and illite floccules, fabric of, (6) 148*c*.
microcrystals, electron-optical study, (9) 235*d*.
quantitative X-ray determination, (6) 142*d*.
reaction with Fe, Co, and Ni oxides, (9) 238*d*.
specific gravity, (11) 282*d*.
suspensions, dispersion, (2) 49*h*.
systems. See *Systems.*
from vermiculite, (6) 143*e*.
Kernite, charge distribution in, (8) 208*b*.
Kieselguhr, Kenya, benzene sorption by, (5) 117*j*.
Kilchoanite, synthetic, morphology and microstructure, (1) 23*c*.
Kiln furniture, for rapid firing, (2) 36*d*.
and refractories, (1) 10*d*.
sagger, for C, P (11) 272*f*.
setters for tiles, P (8) 196*g*.
in small potteries, (10) 246*f*.
Kilns. See also *Burners; Furnaces; Ovens.*
P (11) 279*b*.
air-cushion, fast firing, (1) 19*b*.
Al_2O_3, modeling and simulation, (9) 232*d*.
atm., heating and controlling, P (2) 45*f*.
batch-type and continuous ceramic, (10) 256*i*.
brickwork, harmful substances from, (10) 246*a*.
car, deck stool, P (3) 70*c*.
cement, computer control of composition for, (4) 79*h*.
control, P (1) 2*e*.
dust separation from, P (5) 104*j*.
feed rate control in, P (4) 79*g*.
ceramic, burners for, (10) 256*c*.
exhaust, corrosion and smut emission by, (1) 19*a*.
firing, in craft pottery, (1) 10*d*.
Hover-, development and use, (2) 45*e*.
inclined, P (8) 206*d*.
insulating structural units for, (5) 116*j*.
linings. See *Refractories.*
long, P (7) 174*f*.
medieval, firing, (4) 77*j*.
muffle, for firing glazed tiles, P (5) 117*a*.
"one-high" for brick, (9) 220*f*.
portable electric, for enameling kits, P (11) 266*e*.
quickfire, BCRA, (9) 232*b*; (11) 279*a*.
rapid firing, in porcelain industry, (9) 223*e*.
rotary, additional feeding, (8) 185*h*.
adjusting heat-generating process, P (8) 206*f*.
cement, B (6) 154*e*.
cement, heat transfer in, (8) 186*a*.
coatings, $CaCO_3$-silicate in, (8) 185*j*.
control apparatus, P (2) 45*c*; P (4) 94*a*.
control by isotopes, (5) 104*c*.
control system for firing material, (8) 206*b*.
controlling operation, P (6) 143*c*.
cooler for, P (6) 143*d*.
dusting in, moisture-dependent, (8) 186*f*.
with end and intermediate discharge, P (1) 19*f*.
gas delivery manifold for, P (8) 206*c*.
melting glassy materials by, P (11) 270*d*.
nose ring, P (11) 279*c*.
preheat and drying section, P (1) 19*e*.
for presintering ferrites, (10) 249*f*, 256*g*.
sampling device, P (2) 45*a*.
seals for, (8) 187*d*.
welded shell, (8) 187*g*.
rotation, rectilinearity of axis, (8) 185*g*.
shaft, MgO production in, P (5) 110*b*.
shell, artificial cooling, (8) 185*h*.
shuttle, in heavy clay industry, (6) 134*a*.
tunnel, changes in, (1) 19*e*.
at Columbus Brick, (11) 271*c*.
coal-fired, (2) 45*e*.
energy consumption and output, (11) 279*c*.
experimental, (1) 19*c*.
heat economy in, (2) 45*g*.
heating cycle control, (8) 206*c*.
heating zone and problems, (4) 93*i*.
package, and Permak system, (2) 45*i*.

Kilns, tunnel *(continued)*
pressure losses and heat transfer in, (10) 256*f*.
ratio of zone lengths in, (8) 206*e*.
walking-beam, rapid firing in, (2) 45*e*.
Kinetics, of anatase/rutile transformation, (9) 236*a*.
of boriding and effect on Ni, (10) 259*i*.
carbide-formation at graphite/metallic melt interface, (10) 259*f*.
of carbothermal reduction of quartz, (9) 236*e*.
of cation ordering in Mg ferrite, (1) 23*g*.
chemical, of plastic deformation, (4) 95*h*.
of CuS conversion to $Cu_{1.8}S$, (6) 149*d*.
of crystallization of glass, (5) 105*g*.
data, plotting, use of reduced time in, (3) 53*j*.
of dissolution of system $CdGe(As_2P_{1-x})_2$, (7) 178*b*.
of eutectoid decomposition of $CuFe_2O_4$, (1) 23*g*.
of growth of Al_2O_3 whiskers, (3) 74*d*.
heterogeneous, at high temps., B (6) 154*g*.
of hydration, of Al_2O_3 cement, (6) 128*f*.
of gypsum, (7) 156*c*.
of CaS, (7) 156*j*.
of ice-brine interfaces, (10) 258*g*.
of ilmenite chlorination, (2) 46*e*.
of lime dissolution, in slags, (1) 2*c*.
of MgO-Fe_2O_3 reaction in powder compacts, (1) 23*h*.
oxidation, of Cu_2S, (6) 149*e*.
oxidation, of SiC heating elements, (8) 195*a*.
of O dissolution in molten Pb, (6) 149*g*.
of recrystallization and grain growth in Cu_2O, (4) 97*j*.
of sintering, at constant rate, (6) 149*g*.
in hematite, (3) 75*e*.
NiO, (9) 236*c*.
of UO_2, (9) 228*h*.
of solid state reactions, (10) 259*j*.
of spalling of aluminosilicate refractories, (11) 271*j*.
studies, of epitaxial GaAs, (9) 235*i*.
of thermal decomposition of $BeSO_4$, (6) 149*h*.
thermo-, of portland cement hydration, (8) 188*f*.
of TiO_2 reactions with hydrosulfates of alkali metals, (2) 48*j*.
of ZnO reduction with CO, (6) 149*h*.
in ZrO_2 transformation, (7) 178*b*.
Kyanites, in rocks in Calif., (1) 19*g*.

Laboratories. See also *Research and research laboratories.*
equipment, for classification of fine particles, (3) 69*h*.
Lacquering, relation to enameling, (1) 2*i*.
Ladles. See *Refractories.*
Laminates, graphite-fiber-reinforced, P (6) 135*h*.
Lamps. See also *Glass; Glassmaking apparatus.*
alkali metal halide vapor, P (3) 58*e*.
Al_2O_3-metal sealed, P (8) 200*b*.
arc, depressurization, P (3) 57*j*.
envelope structure for, P (8) 200*b*.
high-pressure compact, P (3) 58*b*.
arc discharge, P (3) 57*h*; P (10) 243*i*.
arc discharge, phosphor coating for, P (6) 139*i*.
As-Sb-Bi hollow cathode, P (6) 132*b*.
bromine-filled bipost, P (6) 132*b*.
coating phosphor on, P (10) 245*c*.
discharge, P (4) 81*e*.
high-pressure, P (1) 4*h*.
low-pressure, P (6) 138*e*.
Hg vapor iodide, P (5) 107*i*.
metal halide, P (2) 34*a*; P (4) 82*h*.
resistively ballasted, P (10) 244*f*.
seasoning, P (11) 270*f*.
Na or metal halide vapor, P (8) 193*e*.
starting circuit for, P (4) 83*b*.
electric, P (9) 218*h*; P (10) 244*d*.
apparatus, P (11) 270*e*.
gettering process for, P (10) 244*h*.
halogens into, P (3) 59*d*.
holder for, P (10) 244*e*.
pinch-base, P (3) 59*c*.
structure, P (2) 33*j*.
subminiature, P (4) 83*a*.
electric discharge, P (2) 33*j*, 40*c*; P (3) 58*c*; P (10) 245*f*.
electric discharge, metal halide, P (3) 58*c*.
electric incandescent, P (2) 35*b*; P (6) 132*f*; P (10) 244*d*.
to eliminate single frame curtain, P (5) 107*i*.
envelope, P (3) 58*f*.
filament structure, P (2) 34*i*.
with filament support, P (7) 162*f*.
flash, P (4) 81*i*.
flash, indicating, P (10) 244*f*.
flashing electric, P (10) 244*g*.
fluorescent, P (10) 245*c*.
circular, machine for, (11) 267*j*.
highly loaded, P (3) 58*d*.
Hg-vapor gas-discharge, P (11) 270*c*.
panel, P (6) 132*g*.
polyspectral, P (10) 245*a*.
U-shaped, P (1) 5*f*.
fog, P (3) 58*d*.
gas and/or vapor discharge, P (9) 219*a*.
gaseous discharge, high-pressure, P (3) 59*f*.
halogen, P (3) 58*b*.
H-halogen filament, P (6) 133*b*.
halogen filament for headlights, P (6) 133*b*.
illuminating, P (7) 162*d*.
with improved press seal, P (9) 219*g*.
incandescent, halogen cycle, P (3) 58*b*.
reflector-type, P (8) 193*j*.
tubular, P (10) 245*i*.
incandescent electric, coated, P (3) 57*j*.

Lamps *(continued)*
incandescent filament, P (4) 82*d*.
ir, for concrete hardening, (6) 127*j*.
Hg vapor, P (9) 219*h*.
color-corrected, P (9) 218*f*.
high-pressure, restarter for, P (2) 42*f*.
Hg vapor discharge, P (3) 58*i*; 59*g*.
high-pressure, P (7) 162*c*.
low-pressure, P (3) 58*f*; P (4) 82*f*.
metal vapor discharge, P (5) 112*g*; P (9) 219*h*.
miniature, P (1) 5*d*.
phosphor blend, P (1) 5*g*.
photoflash, P (1) 5*g*; P (2) 35*a*; P (3) 59*a*; P (6) 133*d*; P (10) 245*f*.
quartz-halogen, explosion-proof, P (1) 4*a*.
seal arrangements for, P (10) 245*f*.
sealed beam arc, housing for, P (6) 133*b*.
with separate phosphor coatings, P (4) 82*e*.
shock-resistant, P (3) 58*b*.
signal, dual intensity, P (5) 107*e*.
Na vapor discharge, low-pressure, P (6) 133*e*.
solid state assembly, P (10) 253*c*.
of Sr Ba chloroaluminate phosphor, P (6) 138*e*.
W-halogen, P (3) 59*j*; P (4) 83*b*; P (5) 107*i*.
incandescible projection, P (6) 133*c*.
with Mo aluminide seal, P (9) 220*a*.
vapor discharge, P (4) 82*d*.
xenon, P (8) 194*a*.
xenon, high-intensity, P (11) 270*i*.
Lanthanides, of alkali metals and ammonium, ir absorption spectra, (1) 22*g*.
oxytungstates, X-ray study, (8) 211*j*.
separating Y from, P (2) 46*f*.
trivalent, spectral intensities, (11) 282*e*.
Lanthanons. See *Rare earths.*
Lanthanum, aluminate, phonon instability in, (5) 125*j*.
chromate, vaporization, (6) 152*i*.
$La_{0.002}Ba_{0.098}TiO_3$-$Bi_2O_3$ composite ceramics, resistance in, (3) 76*b*.
$(La_{1-x}Ca_x)CrO_3$, x=0.01–0.15, P (4) 89*g*.
La_2O_2S single crystal, Gd^{3+} in, ESR, (4) 96*e*.
$La_xSr_{1-x}RuO_3$, (8) 209*d*.
oxide, crystallographic shear relations with UO_2, CaF_2, and NaCl, (9) 234*f*.
oxide, nature of H_2O in, (1) 23*d*.
oxysulfide, crystals, growth, (6) 148*j*.
oxysulfide, laser material, (5) 112*a*.
Laponite, dispersions, rheological properties, (9) 238*g*.
Lapping, chemical, of Y Al, P (4) 87*j*.
Lasers. See also *Masers.*
beams, for holes in workpiece, P (8) 204*a*.
improving homogeneity, P (8) 200*i*.
ir, visual displayer for, P (10) 253*e*.
inspecting hollow glass articles, P (11) 270*d*.
for working material, P (3) 69*c*.
CdP, P (5) 112*f*.
with Ca fluoroapatite crystal, P (3) 65*h*.
cavity, high-efficiency, P (11) 270*b*.
crystals, ruby, tracer elements in, (9) 230*h*.
for detecting faults in transparent material, P (7) 161*c*.
devices, P (5) 112*j*.
curved junction, P (1) 12*f*.
face-pumped, P (10) 250*c*.
junction, P (3) 65*g*.
semiconductor, P (2) 42*d*.
diode-pumped, P (8) 193*d*.
disk, compensator for refractive-index gradient in, P (10) 244*a*.
dispersion compensation in, P (10) 244*c*.
electron beam excited, P (8) 200*a*.
element, solid-state, P (3) 64*d*.
energy measurements, calorimeter for, (7) 173*c*.
flashtube triggering, P (10) 251*a*.
fluorescent solid, P (1) 12*e*.
frequency selector, multicolor, P (1) 14*b*.
GaAs, filamentary coupling in, (5) 111*j*.
injection, aging, (7) 178*h*.
wavelength tuning and lasing threshold in, (7) 167*f*.
gas, with adjustable mirror, P (2) 34*c*.
gas, for machining oxides, (2) 44*j*.
gas ion, action, P (9) 226*i*.
glass, P (4) 81*j*; (7) 161*a*; P (8) 193*j*.
clad rod, P (6) 132*c*.
color centers in, (5) 106*f*.
coupling reflector, P (3) 65*c*.
damage in, (5) 105*h*.
Er_2O_3/Yb_2O_3-doped, P (8) 192*g*.
Li_2O and SiO_2, P (5) 107*j*.
materials, P (10) 244*b*.
Nd-doped, P (9) 225*j*.
rod, composite, P (4) 81*a*.
rods, end fusion, P (2) 34*a*.
rods, melting glass for, P (8) 192*h*.
self-focusing damage tracks in, (11) 267*j*.
system, P (9) 215*j*.
thermoluminescence in, (5) 106*c*.
unitary system, P (3) 59*j*.
window sealant technique, P (3) 58*j*.
guide construction, P (9) 225*f*.
high-power, P (2) 40*b*.
ir diode-pumped visible, P (3) 65*d*.
light scattering, for determining agglomeration in dispersed systems, (1) 17*g*.
liquid, active medium for, P (3) 64*b*.
machining, (3) 63*e*.
material, P (8) 201*a*.
ARPA-NBS research, (3) 70*j*.
Ca Y silicate oxyapatite, P (4) 87*g*.
damage in, (5) 105*h*.
fluorapatite, P (4) 88*a*.

Lasers, material *(continued)*
heat diffusion near absorbing centers, (1) 11*h*.
inclusions in, (1) 11*i*.
La oxysulfide, Nd-activated, (5) 112*a*.
oxyapatite, P (4) 89*h*.
ruby as, (1) 11*j*.
silicate oxyapatite, with Ca, P (10) 249*h*.
for measuring fringe patterns, P (6) 142*g*.
mirror, polarizing, P (3) 59*c*.
mode-locked, P (2) 41*e*.
modulation, optical shutter for, P (9) 219*g*.
to monitor stack emissions, (11) 277*c*.
Nd:YAG, pulse shape, (6) 151*h*.
nuclear charged self-sustaining, P (9) 227*b*.
optical windows [GaSb] for, P (2) 41*i*.
oscillations, P (3) 65*c*.
pinch effect, P (3) 66*h*.
pulses, boring workpieces by, P (1) 17*b*.
Q-switched frequency doubling, P (2) 42*c*.
rods, athermalization, P (8) 200*d*.
header for, P (2) 34*g*.
sealing, P (9) 226*f*.
solid state, P (11) 274*i*.
with segmented laser rod, P (2) 34*j*.
semiconductive, broad-band, P (10) 249*h*.
semiconductor, P (3) 66*f*; P (4) 88*d*; P (7) 170*b*; P (8) 202*a*.
injection-type, P (1) 12*g*.
modulating, P (2) 41*i*.
pumped, YAG, P (3) 67*g*.
self-pulsing, P (10) 250*i*.
slab, symmetrically pumped, P (6) 133*i*.
solid-state, P (3) 67*i*.
solid-state ring, P (8) 202*c*.
stacked composite plate, P (4) 91*a*.
structure with segmented laser rod, P (1) 12*h*.
structures, P (3) 65*i*; P (6) 133*d*.
substrate parting, P (4) 88*i*.
system, two-slab, P (4) 91*b*.
systems, birefringence in, (8) 193*i*.
unitary system with laser glass rod, P (2) 35*c*.
used in cutting processes, P (11) 277*h*.
vortex tube, P (6) 140*e*.
Yb device, P (2) 43*c*.
with $YAlO_3$:Nd^{3+} active medium, P (2) 40*g*.
YAG:Nd, matched with ir phosphor, (3) 63*d*.
ZnO, CdS, CdSe, and $CdS_{0.6}Se_{0.4}$, (5) 111*i*.
Lattice constants. See *Crystals.*
Lattice defects. See *Crystals.*
Lattices. See *Crystals.*
Leaching, acid-, in borosilicate glass, (3) 55*d*.
Be, P (2) 46*i*.
in CaO-Al_2O_3-SiO_2 glasses, (2) 32*e*.
glass films for filter making, P (2) 34*a*.
for recovery of phosphate, Y, and rare earth, P (6) 144*g*.
Lead. See also *Glass; Glazes.*
chalcogenides and halides, interaction, (8) 209*b*.
in dinnerware glazes, research on, (1) 9*j*.
dioxide, active, P (6) 144*d*.
dioxide, electrodeposition, P (4) 87*d*.
ferrite glass-ceramic articles, P (4) 82*e*.
fluorides, crystalline miscibility in CdF_2, (10) 258*g*.
in glazes, benefits and precautions, (1) 10*e*.
in earthenware industry, (9) 223*d*.
research by ILZRO, (1) 10*c*.
research and surveillance, (1) 9*i*.
seminar introduction, (1) 10*e*.
Pb(II), spectroscopic probe in glass, (5) 106*h*.
$Pb(Cd_{1/3}Nb_{2/3})O_3$, crystal growth, (4) 95*g*.
$Pb_5Ge_3O_{11}$, ferroelectricity in, (3) 73*h*.
PLZT, *A*- and *B*-site vacancies in, (6) 136*g*.
ceramics, ferroelectric domains in, (6) 136*i*.
elastic and piezoelectric properties, (11) 273*i*.
ferroelectric phase transitions in, (11) 273*e*.
Pb_2MoO_5, single-crystal growth, (7) 180*f*.
$(Pb,Sr)TiO_3$, hysteresis loop, (3) 63*j*.
$Pb_{1-x}Sn_xTe$, growth of, P (2) 40*j*.
$Pb_{2-x}(Ti,Ta)_2O_{7-\beta}$, structure, (4) 98*i*.
$Pb(Zn_{1/3}Nb_{2/3})O_3$, (2) 50*a*.
single crystals, growth, (3) 73*d*.
transition, (3) 72*i*.
$PbZrO_3$ antiferroelectric and $PbTi_{0.2}Zr_{0.8}O_3$ ferroelectric, (7) 178*i*.
$PbZrS_3$, synthesis at high pressures, (3) 63*j*.
$Pb(Zr_{0.5}Ti_{0.5})O_3$, nonstoichiometry in, (5) 121*e*.
PZT, ceramic, domain configurations in, (9) 223*i*.
electrical resistivity, (3) 62*g*.
in electromechanical resonator, P (9) 225*f*.
sintering, (4) 86*g*.
microquantities in glazes, (10) 255*h*.
molybdate, acousto-optic devices using, P (3) 64*a*; (4) 98*f*.
molybdate, single-crystal, P (7) 170*c*.
monoxide, crystals, in photoconductive layer, P (2) 34*j*.
monoxide, transformation induced by H_2O, (2) 48*d*.
nitrate, ir and Raman spectra, (7) 178*a*.
oxide, conductivity, (5) 119*a*.
oxides, P (3) 72*a*.
oxides, in glass analysis, (8) 205*d*.
sulfates, new data, (9) 237*c*.
sulfide, thermodynamic properties, (8) 211*c*.
sulfide, whiskers, growth and etching, (7) 177*h*.
systems. See *Systems.*
telluride, epitaxial layers, (9) 235*i*.
telluride, *n*-type, P (7) 169*h*.
Sn tellurides, vacuum deposition, P (6) 140*d*.

Lead *(continued)*
-SnTe material for ir detectors, P (10) 252*d*.
tungstate, EPR, (6) 147*j*.
uv absorption in silicate glass, (1) 3*g*.
zirconate ferroelectric phase, (8) 199*b*.
Lehrs. See *Furnaces; Glassmaking apparatus and equipment.*
Lenses. See *Glass, optical.*
Lepidolite. See *Mica.*
Light, beam deflection control device, P (1) 4*j*.
emission from ZnSe-GaAs diodes, (5) 111*h*.
fluorescent, source, P (2) 34*b*.
polarized, for determining particle concentration, P (2) 45*b*.
scattering, in $LiNbO_3$ and $NH_4H_2PO_4$, (5) 120*c*.
scattering measurements on glass surfaces, (8) 205*d*.
short wavelength, effect on ZnO vaporization, (2) 47*b*.
source, P (4) 88*j*.
temp. indicator, for ceramic-top range, P (2) 35*a*.
Lime. See also *Calcium, oxide; Glass.*
P (3) 54*c*.
action on Al silicates, (9) 233*d*.
bursting in bricks, prevention, (2) 35*d*.
degree of burning, (5) 102*e*.
dissolution in slags, kinetics, (1) 2*c*.
dolomitic, MgO in, (11) 278*e*.
hydrothermal reaction with zeolite, (9) 214*b*.
quick-, quality, (6) 128*c*.
quick-, rotary furnace for, (6) 129*f*.
and silicate in thermal insulation, P (7) 157*d*.
standards, (4) 78*f*.
in structural elements, P (7) 157*f*.
Limestone, burning, time and temp., (11) 266*j*.
Ca and Mg oxides and titer in, (8) 204*d*.
and clay, cement from, P (5) 118*b*.
effect on quality of milk of lime in seawater MgO production, (8) 206*i*.
Ontario, TGA of, (7) 181*e*.
preheating, P (1) 2*g*.
trace elements in, (9) 232*j*.
Linings. See *Refractories.*
Liquids. See also *Fluids.*
combustible, burning using nodules, P (8) 198*g,h*.
-crystalline phases, in degradation of aromatics yielding C, (1) 22*j*.
environments, effect on ferrite memory cores, (7) 167*g*.
-glass transition, free-vol model, (5) 105*h*.
liquation, in $SrSiO_3$-$ZnSiO_3$, (9) 217*g*.
liquefying agent, Kerkortan, (10) 248*g*.
mixing with liquid or solid, P (11) 277*c*.
movement in single capillary, (5) 122*d*.
scintillation counting apparatus, P (2) 45*b*.
-solid interfaces, structure relaxation at, (7) 181*f*.
in system CaF_2+CaO+Al_2O_3, electrical conductivity, (6) 147*f*.
system, solubility measurements in, (11) 278*a*.
thickened with SiC fiber, P (7) 164*f*.
Liquidus, isotherms, in Ga-As-Zn and Ga-P-Zn systems, (6) 149*g*.
Lithia. See *Lithium, oxide.*
Lithium, aluminosilicates, synthesis, (8) 211*b*.
Al silicates, structure and properties, (11) 282*b*.
battery, high temp., separators for, (9) 230*g*.
borogermanate, crystal structure, (5) 119*b*.
bromide, Jahn-Teller effect in, (6) 149*c*.
in ceramics, review, (11) 279*f*.
chloride, thermodynamics in LiCl-$MgCl_2$, (11) 281*b*.
compounds, $LiMF_6$ (M=As or Sb), P (7) 175*g*.
ferrite powders, P (1) 13*e*.
fluoride, crystal ceramics, optical aging, (8) 191*i*.
crystals, work-hardening, (6) 147*a*.
defect in, ENDOR, (6) 147*e*.
single crystals, creep, (6) 147*e*, 148*c*.
formate nonlinear devices, P (10) 251*b*.
hexafluorophosphate, P (1) 20*g*.
iodate, Raman and polariton scattering in, (5) 124*f*.
$LiAl_5O_8$, hot-pressing, (4) 97*a*.
$LiBiO_2$, crystal structure, (6) 146*a*.
$LiCr_{1-x}Fe_xO_2$, magnetic ordering in, (8) 209*e*.
$LiFeO_2$, reactions, (7) 180*c*.
Li_2MoO_4-MoO_3, crystallization of BeO, Be_2SiO_4, and SiO_2 from, (7) 176*h*.
$LiNb_3O_8$, crystal structure, (11) 280*e*.
Li_3PO_4-type compounds, crystal chemistry, (8) 210*f*.
$Li_xV_2O_5$ bronzes, phase structure, (6) 149*i*.
metachromite, electronic structure, (8) 208*j*.
metagallate, hydrothermal growth, (7) 178*c*.
niobate, acoustic surface waves on, (4) 97*i*.
composition, and devices, P (9) 226*j*.
Cr^{3+} ESR in, (5) 120*a*.
elastic surface waves on, (7) 178*h*.
γ radiation in, (1) 11*g*.
intense light scattering in, (5) 120*c*.
and $LiTaO_3$, stoichiometry variations in, (6) 146*i*.
melt composition, (6) 146*h*.
modulation of light in, (1) 11*e*.
monocrystals, culture, P (1) 14*d*.
^{93}Nb NQR, (7) 179*e*.
single-crystal films, P (6) 139*d*.
surface-wave diffraction in, (4) 99*g*.
Y-plate, switch using, (3) 62*i*.
oxide and niobate, distribution coeff., (4) 95*c*.
silicate coating on glass surface, P (4) 82*f*.
systems. See *Systems.*
Lithium *(continued)*
tantalate, experiment and ferroelectric theory, (5) 124*f*.
tantalate and niobate, temp. dependence of constants, (4) 99*f*.
Lubricants, coatings, removing from extruded products, P (11) 277*e*.
Luminescence, centers in Pb silicate glasses, (3) 56*d*.
of Cu_2O, role of excitons in, (6) 151*d*.
devices, externally excited, P (1) 12*c*.
electro-, device, GaAlAs, P (10) 251*a*.
device, using In Al phosphide, P (6) 138*b*.
diode configuration, P (9) 225*e*.
element, P (6) 139*e*.
element, semiconductive, P (6) 140*a*.
of GaP diode, P (9) 225*d*.
semiconductor display apparatus, P (9) 225*e*.
electrophoto-, in KCl, (6) 151*d*.
of Eu^{2+} in phosphate compositions, (9) 236*d*.
from *F* centers in CaO, (5) 121*c*.
of F^+ center in MgO, (6) 150*b*.
laser-excited, in ZnO, (7) 181*a*.
of MgF_2, (6) 150*d*.
photo-, of $EuAlO_3$, (9) 237*e*.
photo-, in $SrTiO_3$, (5) 122*d*.
properties, of $BaMg_2Si_2O_7$, (9) 224*i*.
ruby sharp-line, for pressure measurement, (8) 205*j*.
sensitizing, of Er, P (10) 245*g*.
thermo-, determination of minerals, (8) 205*f*.
in laser glass, (5) 106*c*.
testing of ancient art, (5) 101*h*, 102*b,c*.
transitions, of ZnO, (6) 150*c*.
of Y_3OCl_7:Yb^{3+}-Er^{3+}, effect of Dy^{3+}, (3) 72*h*.
Luminescent materials, P (6) 138*f*.
alkaline earth, AlF_3, P (4) 87*c*.
halocapatites, P (9) 227*j*.
pyrosilicate, P (10) 253*a*.
Ca gallate, Mn-activated, P (4) 87*g*.
cathodo-, CaS, P (10) 249*i*.
of Ce phosphates, Tb-activated, P (4) 88*b*.
lanthanide oxysulfide, recrystallization, P (6) 137*c*.
multiple layer, P (1) 5*c*.
rare earth metal phosphate-vanadate, P (8) 201*g*.
rare-earth oxide, treating, P (11) 275*c*.
SiO_2 glass, device with, P (4) 88*c*.
thermo-, P (11) 276*a*.
Luminophors. See *Phosphors.*
Lutecium, chromate, optical emission in, (5) 121*f*.
phosphate, Tb^{3+} and Ce^{3+} transition in, (3) 73*a*.

Machinery and equipment. See also *Materials handling* and specific types.
for bag stacking, P (10) 254*j*.
Beacedis, for body preparation, (11) 276*g*.
for breaking hard material, P (7) 175*c*.
for breaking rock, P (11) 277*a*.
clayware shaping, P (7) 166*a*.
deburring, ceramic ware, P (5) 115*f*.
for drawing and/or reducing, and trimming hollow bodies, P (9) 229*i*.
electric, for heating, welding, and cutting workpiece, P (11) 277*a*.
electromechanical weighing, conveyor-type, (1) 16*g*.
electronic color sorting, of waste glass, (7) 159*f*.
high-pressure, piston construction for, P (2) 44*b*.
for mixing, kneading, or drying, P (2) 44*a*.
for opening bags of powder, P (9) 229*f*.
phase-synchronized rotating systems, P (11) 277*f*.
powder processing, (6) 141*f*.
for profiling bore of insulator, (11) 272*h*.
for reproducing pictures stereoscopically, P (11) 277*f*.
rock-boring, roller for, P (7) 172*f*.
rotary drums, lifting members in wear lining for, P (5) 115*h*.
rotary followup, P (7) 172*f*.
scraper to recover bulk material from storage, P (8) 204*b*.
for sorting fibrous material, P (10) 254*j*.
for splitting double tiles, P (11) 277*f*.
for stabilizing granular materials, P (1) 17*a*.
for treating clusters of particles, P (9) 230*b*.
using sonic vibrations to move particles, P (5) 115*e*.
vibratory, for particulate solids, P (3) 69*g*.
wet scrubber system, P (6) 141*h*.
Magnesia. See *Magnesium, oxide.*
Magnesiothermic, production of metal borides, (3) 60*d*.
Magnesite. See also *Refractories.*
coked tarred, residual C in, (11) 271*i*.
and dolomite, hydrates, purifying, P (10) 257*j*.
dressing and sintering, (11) 279*f*.
seawater, high-temp. constitution, (1) 19*j*.
sintered, from SO_2 in flue gases, (11) 279*i*.
H_2O in, (10) 255*c*.
Magnesium, aluminate, bodies, P (7) 164*b*.
fracture energies, (2) 47*j*.
single crystals, growth, (3) 73*d*; (5) 115*e*.
synthesis, (10) 249*a*.
-Al spinel crystals, P (7) 175*c*.
-Al spinel crystals, for circuits, P (3) 66*e*.
Al spinel monocrystal, P (3) 68*b*.
in cements, determination, (9) 215*b*.
chloride, anhydrous, P (1) 9*d*; P (6) 144*b*.
brines, removing sulfate from, P (10) 257*g*.
Magnesium, chloride *(continued)*
solutions, purification, P (10) 257*h*.
distribution in carbonate cements, (8) 186*b*.
electron microprobe analysis, (4) 93*c*.
ferrite, cation ordering in, (1) 23*g*.
ferrite, electron diffraction superlattice lines in, (2) 47*b*.
fluoride, optical absorption and luminescence, (6) 150*d*.
fluorogermanate, anion and cation defect structure in, (10) 258*b*.
hydroxide, P (8) 207*f*.
carbonation, (7) 177*j*.
effect of impurities, (1) 21*i*.
fresh water, and brine, P (10) 257*g*.
Mg^{2+} in MgO·nAl_2O_3 spinel, (5) 121*g*.
$Mg_2(Al_{4-x}Ga_xSi_2O_{18})$, synthesis, (4) 99*h*.
$MgAl_2O_4$ spinel, chemical preparation, (10) 258*c*.
$MgFe_2O_4$, for strengthening MgO, (2) 49*a*.
Mg_2Pb, semiconductor properties, (9) 238*h*.
Mg_2SiO_4, crystals, Czochralski growth, (7) 176*j*.
Mg_2SiO_4, Mn^{2+} in, EPR study, (6) 147*a*.
oxide. See also *Refractories.*
P (2) 46*d*.
Cd diffusion in, (6) 145*d*.
in calcite, dolomite, and gypsum, (3) 69*h*.
CaO solubility in, (1) 49*c*.
cation self-diffusion in, (6) 145*f*.
and caustic MgO, for cement, (5) 102*f*.
charge states, interactions and relaxation of Fe in, (5) 122*g*.
Compton profile, (3) 72*g*.
:Cu^{2+}, Jahn-Teller effect, (5) 120*b*.
crystals, compressive strength, (10) 258*e*.
crystals, deformation, recrystallization, strength, and fracture, (3) 72*e*.
crystals, fracture in, (2) 48*c*.
dead-burned, hydration resistance, P (10) 248*d*.
defect cluster centers in, (5) 119*d*.
diamagnetism in, (9) 237*h*.
in dolomitic limes, (11) 278*e*.
effect on cement mortar strength, (4) 79*a*.
effect on grain growth in Al_2O_3, (1) 21*c*.
effect on sintered Al_2O_3, (1) 21*e*.
effect on sintering cement clinker, (9) 214*h*.
electrical conductivity, (8) 208*h*.
electrically fused, hydration, (3) 60*d*.
ESR from vacancy-pair center in, (5) 120*a*.
exciton spectra, (6) 148*b*.
Faraday rotation studies, (5) 120*h*.
F band, magnetooptical structure, (5) 121*e*.
films, thermal emittance study, (3) 75*j*.
grain distributions and growth in, (2) 48*b*.
high-density dead-burned, P (5) 110*b*.
hot strength, (2) 35*j*.
or hydroxide, P (10) 248*d*.
OH in, determination, P (1) 18*h*.
ir optical-index values for, (8) 209*a*.
insulating composition, P (11) 272*f*.
insulation in heating element, P (3) 61*d*.
:Fe^{2+}, far-ir, EPR, and Moessbauer spectra, (5) 121*f*.
luminescence of F^+ center in, (6) 150*b*.
-Mg chromite spinel bodies, P (1) 9*c*.
-Mg(OH)$_2$, crystallite size and shape, (6) 146*d*.
to $MgSO_4$ in glass furnace, (3) 55*h*.
Mn^{4+} EPR in, (5) 120*j*.
moldable hydrated, P (7) 164*h*.
:Ni, color centers in, (3) 72*f*.
Ni^{2+} EPR line shape in, (5) 120*i*.
O adsorption during irradiation, (1) 21*j*.
O^{2-} atom in, electron state, (4) 96*b*.
polycrystalline, creep, (11) 280*g*.
polycrystalline, O self-diffusion in, (3) 75*c*.
in portland slag cement, (11) 266*i*.
powder, high purity, of high bulk density, (7) 171*c*.
powders, ir absorption, (6) 146*j*.
precipitation strengthening, (2) 49*a*.
reaction with Fe_2O_3 in powder compacts, (1) 23*h*.
seawater, limestone composition effect, (8) 206*i*.
separator, annealing with, P (2) 31*i*.
SiO_2, CaO, and Fe_2O_3 mixture, phase transformations, (8) 210*b*.
sintering, (2) 49*j*; (5) 123*h*.
structure of center in, (5) 124*i*.
thermal grooving, (8) 211*a*.
transient creep in, (10) 261*e*.
transparent bodies, (11) 282*f*.
whiskers, P (4) 84*d*.
oxides, in limestone and slurries, (8) 204*d*.
phosphates, phase transformations, (8) 210*c*.
in silicate materials, determination, (8) 204*e*.
silicide, chemical properties, (3) 60*g*.
sulfate, salts, K_2SO_4 from, P (4) 94*b*.
sulfite, conversion to MgO, P (10) 257*i*.
systems. See *Systems.*
values, solutions of, P (2) 37*d*.
Magnetic materials. See also *Ferrites; Ferromagnetic materials; Ferromagnetism.*
P (7) 169*b*.
Co ferrite powder for tape recording, P (7) 168*a*.
compositions, P (10) 251*d*.
garnets, P (8) 201*c*.
oxide, P (7) 169*h*; P (11) 275*b*.
films, heteroepitaxial, (2) 49*i*.
platelets, surface coercivity in, (5) 125*d*.
polishing, P (8) 201*g*.
permanent, intermetallic compound, P (11) 275*d*.
powders, permanent, P (9) 227*d*.

Magnetic materials *(continued)*
powders, permanent, stabilizing, P (2) 41*b*.
single domain, contacts using, P (3) 64*f*.
stress-induced uniaxial anisotropy in, (1) 21*d*.
submicroscopic metal particles, P (10) 252*b*.
Magnetic properties. See also *Anisotropy; Resonance.*
of Ba ferrite powders, (10) 249*b*.
of Ba-Sr ferrites, (8) 199*b*.
of $BaMnO_3(2H)$, (8) 209*h*.
of B_2O_3-BaO-Fe_2O_3 glass, (11) 268*h*.
of Cr ions in oxide matrices, (1) 23*j*.
of CrAs, (4) 97*d*.
of $CrAs_{1-x}Se_x$, (4) 97*b*.
of Co fine particles, (11) 274*e*.
of CoAs, (11) 282*g*.
domain, effect on $SrTiO_3$ fluorescence, (7) 177*g*.
effects of wall inertia, (5) 120*f*.
high-field in CdS crystals, (6) 150*f*.
high-field, growth and decay rate in GaAs, (1) 11*h*.
propagation in $Sm_{0.55}TbO_{0.45}FeO_3$ platelets, (7) 176*i*.
wall in hematite, (4) 96*c*.
of Eu_2TiO_4 and $Eu_2Ti_2O_7$, (9) 234*e*.
field, dependence of EuO conductivity, (9) 239*a*.
dependence of transitions in ferromagnetic semiconductors, (9) 236*e*.
effect on CoO properties, (6) 151*g*.
effect on Sm^{3+} ion, (3) 72*h*.
spin flopping in CoO crystal in, (4) 98*h*.
spin-orbit effects in, (5) 124*d*.
of GdIG films, (4) 86*i*; erratum, (7) 167*b*.
of glassy system MnO-Fe_2O_3-B_2O_3, (11) 269*f*.
of In thiospinels, (10) 258*d*.
of Fe(II) oxide and solid solutions, (4) 97*c*.
of Mn Zn Fe_2O_4, relation to particle size, (1) 11*i*.
permeability, of fluoroperovskites, (1) 24*e*.
of rare earth orthoferrites, (2) 38*i*.
of Sr ferrite, (8) 199*d*.
of Sr ferrite, effect of Bi_2O_3, (7) 167*e*.
of xSrRuO$_3$·$(1-x)$LaRhO$_3$ system, (3) 74*f*.
studies, on Ti-O system, (11) 281*e*.
susceptibility, of alkali $NdTiO_3$ perovskites, (9) 237*g*.
of Cr^{3+} in Al_2O_3, (5) 121*d*.
of glasses of system Ge-Se, (9) 217*f*.
of IrO_2 and RuO_2, (6) 150*c*.
of rutile, (5) 124*b*.
in (SrLa)(FeTa)O_3 perovskite, (3) 74*b*.
in system $BaCeO_3$-Ba_2(CeTa)O_6, (11) 282*g*.
of TbOOH, DyOOH, HOOOH, ErOOH, and YbOOH, (8) 209*j*.
of V phosphate glasses, (4) 80*g*.
Magnetism, articles, ceramic, P (4) 92*e*.
ceramics, properties, (9) 224*b*.
compositions, of Cr oxide, P (6) 138*g*.
devices, multilayer, P (10) 251*c*.
semiconductor, P (11) 275*h*.
using garnet compositions, P (2) 40*h*; P (6) 138*g*; P (9) 225*i*.
dia-, in MgO and CdO, (9) 237*h*.
domain-wall mobility of rare-earth orthoferrites, (7) 176*g*.
effects in YIG(Si), (9) 237*d*.
and electric fields, spin-orbit effects in, (5) 124*d*.
electro-, waves, reciprocity, (7) 180*c*.
element, using isolated domains, P (6) 138*h*.
film array, P (2) 40*i*.
films, sputtered, P (2) 42*h*.
head, P (8) 202*e*.
air bearing, P (9) 224*h*; P (10) 249*e*.
assembly, multiple track, P (7) 170*d*.
ceramic body for, P (2) 40*i*.
long-wearing, P (9) 225*g*.
thin-film assembly, P (8) 201*f*.
latch and switch, P (9) 225*i*.
magnetochemistry, in SI units, (7) 182*e*.
magnetoconductivity, of K halides, (6) 151*h*.
MHD power generation, refractories for, (3) 63*e*.
magnetostriction, and anisotropy of Fe_2TiO_4, (3) 73*b*.
constants of $Y_3Fe_5O_{12}$, (11) 281*f*.
of Mn ferrites, (6) 150*d*.
magnetothermal, oscillations and Fermi surface of ReO_3, (6) 150*e*.
memory member, P (11) 275*a*.
model of matter, (1) 15*h*.
moment for d^4 ions in crystal field, (6) 152*a*.
nuclear transition, in ruby, (6) 150*b*.
ordering, in Ca_2MnO_4, (6) 150*a*.
effect in EuO, EuS, EuSe, and EuTe, (9) 237*g*.
effect on Faraday effect in $CdCr_2Se_4$, (9) 236*h*.
in $LiCr_{1-x}Fe_xO_2$, (8) 209*e*.
para-, in $BaBiO_3$, (4) 98*d*.
para-, -response line shapes in ruby, (5) 150*h*.
permanent-magnetizable body, P (8) 201*c*.
photo-, effects in YIG and $CdCr_2Se_4$, (9) 237*e*.
recording, head, P (5) 113*c*.
Fe_4N for, P (10) 250*j*.
media, P (6) 138*g*.
metal powder for, P (1) 13*e*; P (4) 89*h*.
study, of Fe_2TiO_4 single crystal, (3) 74*c*.
symmetry in CoO, (5) 121*e*.
tape, ferromagnetic CrO_2 for, (1) 11*f*.
tapes, interactions in, (5) 123*d*.
thermomagnetic writing on EuO, (5) 124*i*.
thin-film element, P (9) 226*c*.
thin films, substrates of, treating, P (9) 227*a*.
Magnetite, elastic and magnetoelastic effects in, (6) 147*c*.
film on Fe, (10) 249*c*.
Magnetite *(continued)*
films, continuous, P (3) 67*b*.
Indian, physicochemical properties, (11) 282*f*.
metal-nonmetal transition in, (5) 120*a*.
Néel temp., effect of pressure, (6) 146*j*.
thermal conductivity, (5) 125*b*.
Magnetization, in bubble domains, (7) 177*b*.
characteristics of rods, (11) 274*a*.
curves, of spinels with magnetic ions, (10) 261*c*.
precession in ferrites, (7) 167*g*.
in spinel Fe_2MoO_4, (3) 72*f*.
Magnetoelastic, effects in thin film memory elements, (10) 249*d*.
properties, of $RbMnF_3$, (6) 152*h*.
Magneto-optical, devices, controllable, P (9) 218*g*.
elements, P (5) 113*c*.
elements and glasses, P (8) 193*f*.
Kerr effect in EuO, (6) 148*h*.
properties, of GdIG, (6) 147*b*.
properties, of orthoferrites, garnets, and Fe_2O_3 compounds, (6) 152*i*.
structure of MgO F band, (5) 121*e*.
study of band edge of $CdCr_2S_4$, (9) 236*f*.
Magnetoresistance. See *Resistivity, electrical.*
Magnets, bubble domain applications, garnet films for, (2) 38*g*.
ferrite-cored kicker, (9) 224*c*.
magnetometer, ferromagnetic film, P (3) 64*d*.
material powders, permanent, P (7) 169*j*.
oxide, P (5) 113*g*.
permanent, P (8) 201*e*; P (10) 252*h*.
basic powder for, P (10) 251*j*.
from Sm and Pr, Sm and La, Sm and Ce, Sm and Ce misch metal, P (11) 275*i*.
radially oriented, P (1) 13*c*.
Magnons, interactions in hematite, (6) 150*e*.
relaxation in ferromagnets, (6) 151*c*.
Manganese, carbonate, mold using, P (2) 37*a*.
dichloride, enthalpy and entropy, (4) 96*c*.
diffusion in single crystalline MnO, (2) 47*j*.
difluoride, ^{55}Mn NMR in, (5) 122*c*.
dioxide, P (6) 144*d*.
battery-grade, P (10) 257*e*.
β-, exchange integrals in, (3) 72*e*.
electrolytic production, P (4) 94*g*.
with less K, P (9) 233*a*.
and Mn_2O_3, electrical properties, (9) 235*c*.
disulfate, (4) 96*c*.
effect on properties of Fe, (6) 148*j*.
ferrites, magnetostriction, (6) 150*d*.
Mn^{2+} in Mg_2SiO_4, EPR study, (6) 147*a*.
Mn^{2+}, effect on $Y_3Fe_5O_{12}$, (11) 281*f*.
Mn^{4+} in MgO, EPR, (5) 120*j*.
Mn_2-GeO_4 polymorphs, crystal structures, (9) 234*e*.
Mn_5Ge_3 thin films, ferromagnetic resonance, (3) 62*i*.
$Mn_xFe_{3-x}O_4$, Jahn-Teller domains in, (7) 178*a*.
Mn_2PO_4Cl, crystal growth and properties, (2) 47*g*.
$MnSiO_3$, high-pressure transformation, (9) 235*j*.
in optical glass, (3) 57*g*.
oxide, crystals, (7) 179*e*.
silicate-containing minerals, nodules, P (10) 257*f*.
silicides, defect, structure, (2) 50*a*.
silicides, thermodynamic properties, (10) 261*d*.
systems. See *Systems.*
Zn Fe_2O_4, relation of Fe_2O_3 particle size to properties, (1) 11*i*.
Marcasite, -type structure, back-bonding in, (8) 75*d*.
Masers. See also *Lasers.*
modulation, optical shutter for, P (9) 219*g*.
optical, P (2) 34*i*; P (5) 113*e*.
semiconductor, wide-band dc-pumped, P (3) 68*b*.
$^2S_{1/2}$ impurity, P (10) 252*e*.
Masks and masking, AsS, P (3) 66*j*.
back etching for color TV tubes, P (10) 245*b*.
contact exposure, P (6) 137*j*.
diffusion, in semiconductor preparation, P (5) 112*i*.
PbS ion implantation, P (1) 12*h*.
microcircuit Fe_2O_3, P (10) 252*e*.
optical, P (10) 252*g*.
photo-, P (10) 251*d*.
laminar, P (10) 251*a*.
technology, (3) 63*a*.
photovarnish, for semiconductors, P (1) 13*h*.
semiconductor regions, P (10) 251*i*.
shadow, with focusing function, P (9) 219*j*.
Si_3N_4 during H_3PO_4 etching, P (8) 202*g*.
transparent, P (3) 59*i*; P (8) 202*i*.
Materials, Bingham, slow plastic flow, (4) 98*d*.
ceramic, chemistry and physics, B (6) 153*c*.
elastic moduli, (9) 239*b*.
electrical conduction in, (3) 62*e*.
flooring, wear resistance, (7) 165*g*.
grain-boundary sliding in, (9) 235*h*.
impact strength, (10) 259*e*.
processing and testing, B (10) 262*d*.
testing, (7) 173*i*.
texture, (7) 182*e*.
elasticity, plasticity, and structure, B (3) 76*h*.
fusible, melting, P (8) 206*d*.
hard, breaking, P (7) 175*c*.
hard, heterogeneous, sampling, (1) 18*f*.
with high strength, high electrical conductivity, and high heat resistance, P (8) 201*g*.
humic, separation from sand deposits, (1) 17*d*.
investigation, analytical methods, B (3) 76*d*.
kaolin-quartz-feldspar, for porcelain, (8) 198*c*.
layered, balanced deformation, (8) 207*j*.
mechanical properties at low temps., B (7) 183*d*.
Materials *(continued)*
nonmetallic, chemical-resistant, B (6) 153*j*.
porous. See *Porous materials.*
raw, analysis, plasma torch for, (8) 206*h*.
bloating properties, (5) 116*b*.
ceramic, free SiO_2 in, (7) 173*a*.
ceramic, geoelectrical prospecting for, (1) 20*h*.
for ceramic industry, fine grinding, (9) 229*g*.
dye adsorption, (1) 19*h*.
processing changes, (11) 276*h*.
research, pressure variable in, (10) 260*c*.
science, annual review, B (2) 50*h*.
experiments in, B (10) 263*j*.
introduction, B (2) 51*c*.
optical microscopy for, B (5) 126*d*.
research, B (8) 212*f*.
strong, B (11) 284*a*.
systematization and quantitation in, (4) 100*a*.
variations in, and compacted densities, (7) 173*i*.
working, using laser beams, P (3) 69*c*.
Materials handling. See also *Conveyors; Feeding apparatus; Machinery and equipment.*
bulk, bins and bunkers for, B (3) 76*h*.
bulk, scraper to recover from storage, P (8) 204*b*.
container for holding fine material, P (5) 115*f*.
dinnerware, P (1) 10*i*.
in dust and powder form, P (11) 277*f*.
for filling sacks, P (8) 20*g*.
free-flowing and lump, conveying, P (3) 69*c*.
ore carrier, with slurry system, P (1) 20*e*.
pallets, advancing, for making tiles, P (10) 248*i*.
for particulate dry product, P (8) 203*i*.
shipping mineral solids, P (1) 20*d*.
stacking molded articles in groups, P (9) 221*c*.
storage systems, P (3) 69*a*.
transfer apparatus, P (10) 254*i*.
transporting bulk solids, P (3) 69*d*.
of UO_2, P (10) 253*j*.
Measurement, contact angle, P (1) 17*f*.
continuous, of moisture in high-temp. chamber, P (1) 18*c*.
dimensional, capacitance gage for, (11) 277*i*.
of film thickness, P (1) 18*d*.
interferometric, of two lengths, P (2) 44*h*.
of length by optical interferometry, P (11) 278*i*.
moisture content of loose material, P (11) 278*g*.
nondestructive, of glass thickness, P (6) 133*c*.
nuclear physical behavior, (7) 171*i*.
of semiconductor materials and devices, (10) 249*f*.
for semiconductors, (1) 11*c*.
and SI units, history, (2) 50*g*.
surface profile change, P (2) 45*c*.
Mechanical properties, of Al_2O_3, hot-pressed, (1) 21*h*.
of basic bricks, (1) 7*b*; (2) 36*d*.
of C deposited below 1600°C, (5) 115*b*.
of C-SiC alloys, (1) 25*a*.
of cast stone, (8) 195*c*.
of cements, (4) 78*b*.
of ceramic tile bodies, (6) 135*j*.
of ceramics, (1) 17*h*.
electro-, of PLZT ceramics, (6) 136*g*.
of $Gd_2(MoO_4)_3$, (3) 73*h*.
of glasses, inorganic, B (2) 52*e*.
of Li_2O-SiO_2 glass-ceramics, (3) 55*d*.
of materials at low temps., B (7) 183*d*.
micro-, of ceramic composites, (1) 17*j*.
of particulate composites, (8) 187*e*.
of porcelain bodies, (11) 273*c*.
of refractories, high-Al_2O_3, (2) 36*g*.
of TaC, polycrystalline, (2) 48*a*.
Mechano-optical, study of kaolin suspensions, (7) 178*f*.
Meetings. See *Conferences.*
Melting, behavior, of mullite, (1) 24*g*.
conditions, effect on H_2O content of glass, (9) 217*j*.
crystalline rod (semiconductor), P (1) 12*g*.
electric, of glasses, (5) 131*i*.
electroslag, fluxes for, (4) 95*c*.
fusible materials, P (8) 206*d*.
glass batch, particulate, P (1) 4*b*.
glassy materials, by rotary kiln, P (11) 270*d*.
point, of Al_2O_3, DTA measurement, (5) 121*g*.
of system SiO_2-Al_2O_3-CaO-MgO, (9) 233*j*.
of SnF_2, (4) 97*f*.
solid, P (8) 206*f*.
vapor free, UC or PuC, P (9) 228*j*.
with variable-diam. coil, P (1) 13*b*.
Melts, alkali metal Cl+ZnCl, densities, (6) 146*g*.
of alkali metals, solubility of Fe oxide in, (1) 25*c*.
of $CaCl_2$-NaCl and $ZnCl_2$-NaCl, (5) 120*g*.
carbonate-rich, corrosion of SiO_2 by, (7) 158*j*.
crystal seed path in, P (2) 39*j*.
and crystals, transportation, P (4) 89*c*.
densities in systems Ba-$BaCl_2$, Ba-$BaBr_2$, and Sr-$SrCl_2$, (11) 282*c*.
halide-phosphate, TiO_2 solubility in, (8) 210*f*.
ionic, solution model for, (11) 281*i*.
$MgCl_2$-$CaCl_2$-alkali metal chloride, (5) 119*f*.
metallic, wettability of SiC crystals by, (9) 239*e*.
of salts of halides of metals and Tl, (5) 125*i*.
NaCl+$ZnCl_2$, viscosities, (6) 153*c*.
NaF-LiF, reaction of UO_2 and MoO_3 in, (1) 24*f*.
Na_2O-SiO_2, solubility of CO_2 in, (7) 158*g*.
sulfate and bisulfate, (2) 32*f*.

Melts *(continued)*
in system VO_2-V_2O_5, thermodynamics, (6) 152*e*.
temp., detecting, P (7) 174*c*.
vitreous, processing, P (5) 117*a*.
Memory, bipolar semiconductor random access, P (4) 87*f*.
cell, ferroelectric $GdMoO_4$, P (1) 12*c*.
integrated-circuit bipolar, P (4) 88*g*.
mini-, P (3) 66*j*.
nonvolatile, P (7) 169*g*.
effect in chalcogenide glasses, (6) 132*d*.
effect of GaAs thin-film diode, (5) 111*j*.
element, three-terminal active glass, P (2) 43*c*.
ferroelectric, P (3) 65*a*.
magnetic matrix, P (10) 251*c*.
magnetic thin-film, flat, P (7) 168*i*.
matrix using MIS semiconductor, P (9) 226*a*.
member, magnetic coating, P (1) 12*j*.
MOS array chip, P (11) 274*f*.
monolithic, Si monocrystals for, (9) 224*e*.
multilayer core, process, P (4) 89*f*.
optical, P (2) 41*g*.
planar segmented unit, P (2) 41*g*.
in semiconducting glasses, (6) 132*c*.
storage with semiconductor crystal, P (11) 274*j*.
strip array, P (9) 226*f*.
thin film, magnetoelastic effects, (10) 249*d*.
Memory cores. See *Cores; Electronic equipment.*
Memory devices, ferroelectric/photoconductor, P (10) 250*d*.
magnetic, encapsulated, P (5) 112*j*.
magnetic, Li ferrite, P (2) 40*g*.
matrix planes, P (8) 201*b*.
MIS device, P (3) 66*a*.
MIS-type semiconductor read-only, P (8) 201*h*.
semiconductor, P (1) 14*a*.
-ferroelectric, P (3) 67*d*.
random-access, (7) 167*i*.
signal, P (1) 14*c*.
using pulse-generating diode, P (10) 251*g*.
Mercury, detection by hyperfine spectrometer, (4) 93*d*.
-ic chloride, $HgBr_2$, and HgI_2, electrical conductivity, (5) 122*g*.
porosimetry, of pore size distributions in cement pastes, (5) 102*i*.
systems. See *Systems.*
Metalizing. See *Coatings.*
Metalloceramic compositions. See *Cermets.*
Metallography, techniques and applications, B (8) 212*c*.
Metallurgy, gas-, refractories requirements of, (2) 36*f*.
physical, computational techniques in, B (2) 50*h*.
powder, for ferrite development, (2) 38*d*.
research in, B (10) 264*j*.
sintering mechanism in, (3) 74*h*.
of superconductors, B (2) 51*i*.
Metals. See also *Enameling metals; Rare earths.*
alloying, P (9) 226*c*.
and alloys, EEM study, (10) 255*d*.
articles, elongated powdered, P (9) 230*a*.
bivalent, chlorides, reactions with TaCl5 and $NbCl_5$, (5) 123*i*.
bonding to ceramic, (8) 199*c*.
bonding glass prism to, P (2) 34*c*.
brazing to ceramics, P (4) 85*j*.
-carbide mixtures, cold-pressing, (10) 246*f*.
-ceramic materials. See *Cermets.*
coating, P (9) 226*d*.
compounds, alkyl, alkenyl, and aryl, P (7) 175*i*.
crystal-melt interface, (8) 199*c*.
-diamond interfaces, thermal conduction, (4) 77*g*.
electrodeposition in porous glass, (9) 217*g*.
finishing, various media in, (3) 53*h*.
fluoride, in single crystals, P (1) 9*c*.
fluorocarbon coating on, P (3) 54*f*.
group VIII, in alkyl transfer on B_2O_3-Al_2O_3, P (1) 20*j*.
hexafluorides, with elpasolite structure, (6) 148*b*.
interaction with $MoSi_2$, (10) 242*g*.
melts of salts of halides of, (5) 125*i*.
metallic materials, coating, P (7) 158*a*.
-organics, in semiconductor materials, (2) 39*i*.
oxides. See *Oxides.*
paint for, high-temp., P (2) 31*i*.
powders, coating on molds and plungers, (7) 158*i*.
protective coatings on, USSR, B (4) 100*h*.
refractory, Au metalizing, P (9) 225*a*.
sealing, in vitreous enclosure, P (1) 5*c*.
-semiconductor transition device, P (6) 137*g*.
-SiC, high-strength article, P (7) 164*f*.
strengthening, by refractory fibers, (11) 271*h*.
structures, on semiconductor surfaces, P (1) 13*h*.
surface energy, (10) 259*e*.
systems. See *Systems.*
trace, in sediments, spectroscopy, (9) 230*g*.
transition, boride compositions, P (6) 135*h*.
carbide, single crystals, (7) 177*j*.
carbides, substructure, (10) 261*a*.
carbides, work function, (7) 176*f*.
monocarbides, physical properties, (3) 74*f*.
O compounds, (5) 119*a*.
perovskites, as catalysts, P (6) 144*f*.
phosphates, fibrous, P (9) 232*g*.
reaction with Zr, (10) 260*e*.
vapor deposition, P (3) 67*d*.
Metals *(continued)*
wetting of diamond and graphite by, (10) 259*f*.
Metaphosphates. See *Phosphates.*
Mica. See also *Refractories; Vermiculite.*
ceramics, properties, (10) 260*d*.
crystals, fracture and healing effects in, (10) 259*h*.
dipole moments of OH groups in, (1) 23*e*.
ditrigonal distortions in, (4) 98*a*.
foil, stretchable creped, P (8) 202*f*.
hydrothermal stability relations, (4) 97*c*.
physical properties, (9) 234*e*.
stability in system SiO_2-$NaAlSi_3O_8$-Al_2O_3-H_2O, (5) 124*e*.
ultradisintegration and agglomeration, P (2) 46*i*.
Microhardness. See *Hardness.*
Microscopes, electron, fossilization of electrical corona streamers from Si_3N_4 in, (10) 255*d*.
holding and cooling specimen in, P (10) 255*h*.
specimen stage, P (2) 44*j*.
hot-stage, for studying reboil, (3) 56*a*.
Leitz heating, use in ceramics, (1) 17*e*.
photoemission electron, imaging of ceramics in, (8) 205*b*.
rapid method for quantitative determination of fine sands, (10) 255*c*.
sample, holographically recording, P (9) 231*h*.
scanning electron, of ferromagnetic domains, (7) 179*g*.
in observation of SiO_2 films breakdown, (2) 38*h*.
study of *pn* junction, (11) 274*b*.
use in inorganic material, (9) 231*f*.
slide, beveled edge, P (10) 243*i*.
stereoscopic, P (7) 163*a*.
X-ray TV, P (2) 45*c*.
Microscopy, electron, of alkali halide films, (1) 25*a*.
of Al_2O_3 cement pastes, (5) 103*b*.
of chrysotile asbestos, (9) 236*j*.
of demixing of glasses, (7) 159*e*.
of dolomitized rocks, (5) 117*g*.
and energy loss analysis of glass, (6) 131*h*.
of kinetics of cement hydration, (6) 128*f*.
of $Mn_xFe_{3-x}O_4$, (7) 178*a*.
of melilitic glass, (10) 243*b*.
of milling Al_2O_3 powder, (5) 125*g*.
of mineral grain mounting, (4) 93*f*.
preparation of glasses and nonconductors for, (7) 173*b*.
of radiation damage in CdS, (4) 96*j*.
of shear structures based on MoO_3, (10) 259*c*.
of Na borosilicate opalescence, (7) 160*e*.
and structure of materials, B (10) 263*g*.
to study sintering, (4) 93*f*.
of superconducting complex, (4) 96*j*.
of synthetic hectorite, (9) 235*d*.
of system Al_2O_3-Na_2O, (11) 282*a*.
thin glass films for, (11) 278*h*.
of Ti-Nb oxide crystal lattice, (7) 178*b*.
on Ti_nO_{2n-1} ($4 \leq n \leq 10$) phases, (3) 73*a*.
of transformations in chalcogenide films, (6) 136*a*.
of UO_2 particles, (11) 278*a*.
emission electron, of metals and alloys, (11) 255*d*.
of enamels, (1) 17*j*.
field ion, of graphite fibers, (5) 116*d*.
of opaque minerals, B (11) 284*c*.
optical, for materials sciences, B (5) 126*d*.
reflection, of inclusions in glass, (11) 267*i*.
reflection, of strain effects on Se, (11) 268*j*.
scanning electron, of clinochlore-kaolinite bodies, (9) 223*e*.
cross-sectioning, (2) 44*f*.
of plasma-arc-sprayed Al_2O_3, (1) 18*g*.
of UO_2-W composite, (1) 16*d*.
surface interference, P (3) 70*e*.
Microstructure. See *Structure, micro-.*
Microwaves. See *Waves, micro-.*
Migration, electro-, damage in thin films, (5) 111*j*.
thermo-, of C in metals, (6) 152*f*.
Milling. See also *Crushing; Grinding.*
chemical, of SiC, P (1) 8*j*.
effects on Al_2O_3 powders, (5) 125*g*.
Mills. See also *Crushing apparatus; Grinding apparatus.*
P (7) 172*f*.
angular impact fluid energy, P (10) 254*h*.
automatic grading linings for, P (1) 25*4i*.
ball, agitator, P (11) 277*e*.
ceramic-rubber lining, P (1) 10*c*.
productivity, nomograph for, (5) 115*f*.
cylindrical, lining for, P (4) 92*d*.
disk, P (3) 69*d*.
drying, fluid energy, P (9) 230*c*.
feeding grinding media to, P (10) 254*j*.
fluid energy, constant acceleration, P (6) 141*d*.
fluid energy steam, collection system, P (3) 69*g*.
grinding, filler material for, P (1) 16*h*.
powders, P (10) 254*g*.
multiple-compartment, P (3) 69*f*.
regulating material to, P (4) 92*h*.
vibrating, P (6) 141*h*.
hammer, P (9) 230*d*.
hammer, two-stage, P (6) 144*h*.
impact, P (11) 277*g*.
jet, scale-up theory, (7) 172*g*.
pin or hammer, and air sifting, (9) 229*g*.
plant control by isotopes, (5) 104*c*.
pneumatic, for fine powder, P (1) 17*c*.
Mills *(continued)*
rebound pug, P (10) 254*h*.
residence time distributions in, (5) 104*j*.
rotary, conical, P (2) 44*a*.
end liner assembly, P (1) 20*c*.
trunnion liner assembly for, P (1) 20*j*.
stirring, P (5) 115*j*; P (7) 172*h*.
wet-pan and roller, (9) 229*c*.
Mineral fibers. See *Mineral wool.*
Mineral wool. See also *Fibers, glass.*
adhesion to walls of chamber, prevention, P (5) 107*a*.
aggregates, for acoustic insulation, P (8) 192*h*.
basalt use in, (11) 271*h*.
mineral fiberboards with, P (11) 272*b*.
from silicate glass, P (10) 245*f*.
Mineralization, de-, by electrodialysis, P (8) 203*j*.
Mineralizers. See also *Fluxes.*
effect on clinker formation, (8) 186*j*.
effect on porcelain and oxide bodies, (10) 248*f*.
Mineralogy, analysis, of argillaceous soils, B (1) 28*j*.
of Jamaican clays, (1) 20*c*.
in K fixation, (9) 236*d*.
X-ray powder diffractometry in, (4) 92*j*.
Minerals. See also *Materials, raw; Rocks;* and specific types.
argillaceous, neutron irradiation, (7) 179*g*.
bleaching, P (9) 233*d*.
bloating, thermal behavior, (6) 134*f*.
bodies, flame working, P (2) 46*i*; P (8) 203*j*.
calcined, with reduced S, P (4) 94*j*.
clay. See *Clays.*
crushed, particle size and distribution, (7) 172*c*.
deposits, with U, Th, P (2) 43*f*.
-detection apparatus, P (5) 116*g*.
determination by thermoluminescence, (8) 205*f*.
grains, mounting methods, (4) 93*f*.
grinding, P (3) 69*g*.
grinding apparatus for, P (4) 92*h*.
heat processing, P (9) 230*c*.
industrial, ultrafine grinding, (11) 277*a*.
Mn silicate-containing, nodules, P (10) 257*f*.
opaque, microscopy, B (11) 284*c*.
phases, quantitative analysis, (1) 18*e*.
powders, effect on cement strength, (9) 214*g*.
products, P (9) 233*b*.
pyrophyllite diaspore, thermal studies, (11) 283*a*.
separation, P (8) 207*i*; P (9) 233*c*.
slimed, concentrating, P (9) 232*i*.
solids, shipping, P (1) 20*d*.
synthetic claylike, smectite-type, P (9) 233*c*.
in system $CaAl_2Si_2O_8$-SiO_2-H_2O, *P-T* stabilities, (1) 24*f*.
ultradisintegration and agglomeration, P (2) 46*i*.
waste, utilization, symposium, B (9) 240*e*.
Mines and mining, quarry machinery, (2) 46*f*.
Mirrors, glass, blank core, P (8) 193*g*.
glass, Cu plating, (8) 190*c*.
spray finishing, automated, (7) 158*d*.
Miscibility. See also *Solubility.*
of Al_2O_3 and Cr_2O_3, (1) 26*d*.
crystalline, of Ca, Sr, and Pb fluorides in CdF_2, (10) 258*g*.
Missiles. See *Spacecraft.*
Mixers, P (2) 44*a*; P (6) 141*d*; P (8) 204*b*; P (10) 254*f*.
airlift, P (6) 141*g*.
based on continuous and batch systems, (7) 172*f*.
continuous, P (9) 229*i*.
device for attachment to, P (9) 229*i*.
1500-ton, hot repair test on, (7) 163*h*.
for foundry sand, P (1) 16*i*.
and kneader, continuously operable, P (8) 203*g*.
lining, direct-bonded basic, (2) 35*i*.
for one or more substances, P (8) 203*h*.
pan-type, modular plow system for, P (4) 92*f*.
for particulate materials, P (1) 16*j*.
portable, P (8) 204*c*.
for powdered materials, P (10) 254*h*.
for powdered nuclear fuel, P (10) 254*a*.
rotary drum, P (11) 267*c*.
screw, P (1) 17*b*.
solids-liquids, dispersion head for, P (4) 92*c*.
for stirring material, P (1) 16*g*.
Mixing, batch, with weighing machine, (1) 16*g*.
continuous intensive, (9) 229*d*.
de-, of borosilicate glasses, (7) 159*e*.
enthalpies, in alkali sulfate mixtures, (3) 73*c*.
glass batch materials, P (1) 5*d*.
intensive, (9) 229*i*.
liquid with liquid or solid, P (11) 277*c*.
particulate solids, humidity effect, (7) 172*b*.
problems, solutions to, (9) 229*e*.
sand, or conditioning apparatus, P (9) 230*d*.
screw, lower bearing assembly for, P (2) 44*c*.
and settling process for U and Pu, P (10) 254*a*.
solids, (6) 141*f*.
system, (10) 254*d*.
using fluidics to control, (10) 254*g*.
Mobility, model, for system K_2O-SrO-SiO_2, (9) 216*h*.
Models, for material movement in shaft furnace, (8) 187*b*.
for sheet glass drawing process, (8) 190*a*.
solution, for phases and melts, (11) 281*i*.

Modulators, electrooptic, wide aperture, P (2) 43*c*.
electrooptical, P (3) 64*i*.
light, P (8) 201*a*.
Modulus of elasticity. See *Elasticity*.
Modulus of rupture. See *Rupture*.
Moessbauer, effect, on $PbZrO_3$ and $PbTi_{0.2}Zr_{0.8}O_3$, (7) 178*i*.
of ^{166}Er in Er orthochromite, (5) 122*c*.
in ^{129}I, CrI_3 internal field studies by, (5) 121*c*.
in Li-Zn ferrites, (4) 86*d*.
in (SrLa)(FeTa)O_3 ordered perovskite, (3) 74*b*.
study of $FeVO_4$, (8) 208*i*.
measurements in Li-Cr ferrites, (7) 178*j*.
study, of ^{57}Co implanted in diamond, (5) 122*c*.
of Fe^{3+} adsorption and thermal treatment, (4) 97*g*.
of silicate and phosphate glasses, (7) 160*c*.
Moisture. See also *Humidity; Steam; Water*.
continuous measuring in high-temp. chamber, P (1) 18*c*.
dependence of dusting in kiln on, (8) 186*f*.
expansion, in brickwork, (1) 6*d*.
of loose material, measuring, P (11) 278*g*.
measuring system, P (6) 141*f*.
of moving material, P (3) 70*d*.
steam, low pressure, for pickling, (10) 242*g*.
sorptive, of clays, (6) 142*i*.
stress, in ceramic clay bodies, (7) 165*c*.
surface, effect on dielectric behavior of $BaTiO_3$, (1) 11*c*.
Molding, ceramic, drying, P (11) 279*d*.
compositions, with high wt% glass, P (1) 5*d*.
effect on brick and tile properties, (4) 83*i*.
forms on various substrates, P (10) 251*i*.
glass articles, hollow and bottomed, P (8) 193*a*.
injection, glass fibers, P (6) 132*d*.
materials of Ca silicate hydrate, P (10) 242*c*.
materials, thermoplastic, P (8) 207*h*.
press, glassware, P (1) 5*b*.
press-, rotary apparatus, P (8) 204*a*.
refractory, P (9) 222*g*.
rotary, for press-shaping glass, P (2) 35*b*.
vibroimpact, of SiC shapes, (8) 196*c*.
Molds. See also *Slip casting; Slips*.
apparatus for removing shapes, P (9) 223*f*.
casting, P (7) 166*a*.
casting, substitute for coal dust in, P (9) 222*h*.
ceramic, coating, P (6) 135*c*.
shell, support for, P (1) 9*f*.
support means for, P (9) 223*e*.
coated graphite, P (11) 272*c*.
composite, P (6) 135*c*.
composite sand, P (11) 272*g*.
conductive, P (6) 132*e*.
container, cooling, (8) 190*c*.
for continuous casting plant, P (7) 166*a*.
and core materials, ceramic, P (3) 61*b*.
cores for. See *Cores*.
fluid sand, using water glass and slag, (3) 60*i*.
forming glass sheets in, (11) 268*d*.
foundry, P (2) 37*a*.
curing, P (5) 109*h*.
dosing molding sand into, P (8) 196*d*.
process and pattern, P (7) 164*d*.
glass, blow, P (2) 33*e*.
cast iron for, (3) 55*c*.
cleaning, (7) 159*c*.
coating of metal powders on, (7) 158*i*.
controlling temp., P (2) 33*d*.
coolant, air to, P (3) 59*f*.
hard alloys used in, (5) 106*g*.
heat fluxes, (2) 32*c*.
sheet press bending, P (4) 82*b*.
temp. control, P (4) 83*a*.
-ware, holding and cooling device for, P (7) 162*c*.
heat transfer between glass and, (8) 190*b*.
hot-pressing, graphite as, P (4) 85*b*.
ingot, bottom brick for, P (11) 272*b*.
coating, P (9) 222*j*.
and foundry, linings for, P (8) 196*c*.
investment, inoculating, P (1) 9*b*.
isostatic, high production, P (10) 254*d*.
linings, by slurry supply method, P (7) 164*c*.
molded articles, P (9) 230*d*.
for orienting abrasive particles, P (2) 29*h*.
pattern, P (10) 248*c*.
permeable ceramic, P (5) 111*d*.
plaster, in ceramic slip casting, (4) 85*j*.
fluid absorption rate, P (9) 231*j*.
with metal oxide linings, P (10) 254*d*.
pores in, (9) 223*d*.
testing in German laboratory, (5) 116*c*.
plastic pottery, (8) 197*h*.
plates for complex shapes, blade for cutting, P (1) 16*j*.
preformed wall section, P (5) 108*g*.
press, plates, improving resistance, (8) 203*j*.
refractory, P (1) 9*g*.
carbonizing, P (11) 272*e*.
shell, P (1) 8*i*.
sand core elements, P (5) 109*g*.
shell, composition, P (8) 197*c*.
multilayer, P (3) 61*h*.
porcupine, P (7) 164*b*.
supporting core in, P (8) 196*d*.
solid press, P (10) 255*j*.
spray apparatus, P (3) 59*j*.
surface, corrosion in slip-casting, (7) 165*c*.
thermostatically controlled, holder with, P (9) 219*e*.
using $MnCO_3$, P (2) 37*a*.
Molecules, macrocyclic compounds, ion binding by, (4) 97*j*.
Molybdates, of alkali metals and ammonium, ir absorption spectra, (1) 22*g*.
Molybdenum, borides, magnesiothermic production, (3) 60*d*.
bronzes A_xMoO_3, de Haas-van Alphen effect, (6) 150*f*.
carbide, stability, (3) 75*b*.
carbide, stacking faults and twins in, (4) 98*i*.
disilicide heating elements, (10) 246*j*.
interaction with metals, (10) 242*g*.
resistance elements, P (1) 13*j*.
disilicides, interaction with graphite, (10) 259*c*.
effect on corrosion of electrode holder, (8) 190*c*.
Mn, -Al_2O_3, bond strengths, (1) 2*h*.
metalizing, sintering, (1) 11*j*.
Mo_3O_{14} and $Mo_{17}O_{47}$, in Mo-W-O system, (4) 96*i*.
oxides, optical spectra, (10) 260*d*.
reaction with Al_2O_3 melt, (7) 163*j*.
reaction with SiO_2 melt, (7) 163*g*.
sulfide coatings, by plasma jet, P (8) 197*a*.
systems. See *Systems*.
trioxide, reaction with $ReCl_5$, (5) 123*h*.
reaction with UO_2, in NaF-LiF melt, (1) 24*f*.
shear structures, (10) 259*c*.
Monetite, phosphate phosphors from, P (7) 170*f*.
Monticellite, solubility in forsterite, (1) 25*e*.
Montmorillonite, aggregation and dispersion in, (2) 37*i*.
alcohol-homoionic, interactions, (9) 237*i*.
cation migration into, (5) 118*d*.
Cu, ir spectra of alamine adsorbed on, (11) 281*b*.
crystals, effect of origin on X-ray spacings, (1) 21*b*.
deposits in Nevada, (3) 71*e*.
glycine adsorbed on, ir spectra, (11) 281*b*.
quantitative X-ray determination, (6) 142*d*.
single crystals, electron diffraction, (10) 260*b*.
specific gravity, (11) 282*d*.
systems. See *Systems*.
Mordenite, P (2) 46*c*.
H_2 form, formation and properties, (3) 73*j*.
low-Al_2O_3, bonded, P (5) 117*e*.
Morphology, of $Ca(OH)_2$, (5) 103*a*.
of kilchoanite, synthetic, (1) 23*c*.
micro-, changes during brick firing, (9) 220*e*.
of portland cement, hydrating, (5) 103*g*.
of SiC single crystals, (11) 281*a*.
stability, aspects, (8) 207*j*.
of C_2S hydration, (5) 103*f*.
of C_2S pastes, hydrated, (5) 103*j*.
Mortars, P (7) 157*d*.
additive for, P (8) 188*c*.
adjuvant composition for, P (8) 188*c*.
beam, boxed, bending strength, (6) 128*a*.
bedding, specifications, (9) 221*c*.
in brickwork, effect of rain, (1) 5*j*.
cement, flow measuring devices, (4) 78*i*.
fracture, (6) 128*d*.
high Al_2O_3, carbonation, (4) 78*f*.
properties, (9) 214*c*.
steam curing, (9) 215*a*.
strength, effect of slag, (4) 78*e*.
with waterproofing agent, (4) 79*f*.
creep rupture, (6) 128*f*.
dolomite lime, hardening and weathering, (5) 103*f*.
grouting, with high flowability, (6) 127*j*.
high-strength, P (10) 242*c*.
hydraulic, composition, P (6) 130*e*.
long-set, gypsum plaster for, P (7) 157*g*.
masonry, and units, B (6) 153*j*.
mechanical properties, (6) 129*c,d*.
plasticizing additive for, P (11) 267*b*.
Poisson's ratio, (5) 102*j*.
resistance to sulfate attack, (6) 129*d*.
Muirite, cyclosilicate rings in, (1) 21*g*.
Mullite. See also *Refractories*.
corrosion, by alkaline vapors, (5) 109*f*.
crystal structure, (6) 135*j*.
decomposition, (3) 72*d*.
fiber, SiO_2-deficient, P (1) 9*d*.
formation, P (11) 272*c*.
ideal, ir frequency calculations, (3) 73*h*.
melting behavior, (1) 24*g*.
mullitization of aluminosilicate gels, (8) 195*a*.
polycrystalline, Young's modulus, (4) 99*j*.
solid particles, P (2) 46*e*.
Muscovite. See *Mica*.

Natrolite, Fe^{3+} adsorption and thermal treatment, (4) 97*g*.
Neodymium, chlorides, reaction with YCl_3, (5) 123*i*.
hydroxide, by vapor-phase reaction, (8) 210*i*.
Nd^{3+} in $YAlO_3$, optical spectra, (7) 179*i*.
$NdAlO_3$, crystal structures, (8) 208*a*.
$Nd_4Re_2O_{11}$, crystal structure, (5) 119*c*.
oxide, for stabilizing ZrO_2, (8) 195*j*.
systems. See *Systems*.
Neon, diffusion in glasses, (2) 32*b*.
Nepheline, decomposition, hydrochemical, (7) 179*b*.
structural element of porcelain, (5) 110*j*.
syenite, in fast-fire tile, P (7) 166*b*.
Neptunium, NpO_2^{2+}, absorption spectrum in $Cs_2UO_2Cl_4$, (5) 118*c*.
in $CsUO_2(NO_3)_3$, (6) 144*i*.
EPR in $Cs_2UO_2Cl_4$ and $CsUO_2(NO_3)_3$, (5) 120*j*.
separation from UF_6, P (2) 43*f*.
Neutrons, activation analysis, of ruby laser crystals, (9) 230*h*.
activation, thermal, determination of Co, Cu, and Mn in optical glass by, (3) 57*g*.
attenuation in concrete shielding, (5) 114*j*.
californium-252, P (4) 91*i*.
californium-252 source, P (5) 115*b*.
diffraction, of $CrSb_2$ and $FeSb_2$, (5) 118*i*.
of magnetic ordering in Ca_2MnO_4, (6) 150*a*.
study of ferroelectric $LiH_3(SeO_3)_2$, (10) 259*b*.
study, of H_2SeO_3, (3) 74*b*.
U_4O_9 superstructure analysis by, (10) 253*h*.
irradiation, of argillaceous minerals, (7) 179*g*.
damage in SiC whiskers, (10) 260*c*.
effect on high-melting compounds, (10) 258*i*.
source tube, with coated target, P (5) 115*c*.
study of Fe_2TiO_4 single crystal, (3) 74*c*.
Nickel, -base materials, sintered, properties, (10) 260*c*.
disulfate, (4) 96*e*.
fluoride, P (1) 20*i*.
mechanical properties, boriding effect, (10) 259*i*.
Ni^{2+}, EPR line shape in MgO, (5) 120*i*.
Ni^{2+}, ion-exchange equilibria of zeolite with, (1) 23*e*.
Ni^{3+}, in MgO-NiO-Li_2O solid solutions, (1) 22*c*.
and Ni-Cr sheets, bonding to α-Al_2O_3, (2) 38*j*.
$NiAl_2O_4$ spinel, grown on sapphire, (10) 260*j*.
NiF_6^{4-}, Hartree-Fock theory, (5) 121*a*.
$Ni_{1-x}Fe_xSb_2$, (5) 118*i*.
$Ni_{1-x}Se$, crystal structure, (11) 280*g*.
oxide, P (6) 144*d*.
cation self-diffusion and semiconductivity in, (7) 176*d*.
crystal, antiferromagnetic, (4) 96*e*.
crystals, (7) 179*e*.
crystals, electrical conductivity, (6) 146*i*.
effect on grain growth in Al_2O_3, (1) 21*c*.
effect of ThO_2 and ThO_2-Y_2O_3 sintering, (11) 280*d*.
electroreflectance study, (6) 147*e*.
electrostatic separation, (9) 232*h*.
films, photoconductivity in, (6) 150*h*.
scale, observations, (3) 75*i*.
sintering, (9) 238*j*.
sintering kinetics, (9) 236*c*.
stoichiometry limits in, (5) 124*g*.
surface spin waves in, (6) 152*f*.
oxides, reaction with kaolinite, (9) 238*d*.
-O vacancy pair in $SrTiO_3$, (6) 150*d*.
plating, on nonconductive substrates, P (5) 112*j*.
porous, friction, effect of B, (10) 258*h*.
recovery from asbestos ore, P (10) 257*d*.
separation from asbestos ore, P (6) 144*f*.
in silicate glasses, spectra, (5) 106*d*.
solid state bonding to Al_2O_3, (2) 38*i*.
systems. See *Systems*.
wear-resistant coatings, P (10) 248*d*.
Niobium, borides, magnesiothermic production, (3) 60*d*.
carbides, external friction, (10) 259*d*.
Nb *L*-spectra in, (4) 95*g*.
stability, (3) 75*b*.
-C phase diagram, modification, (6) 150*i*.
compounds of W-bronze type, (3) 75*i*.
disilicides, interaction with graphite, (10) 259*c*.
fluoride, separation from UF_6, P (3) 68*i*.
germanides, chemical properties, (6) 145*a*.
^{93}Nb NMR study of $LiNbO_3$-$LiTaO_3$ system, (7) 179*d*.
^{93}Nb NQR study of $LiNbO_3$, (7) 179*e*.
Nb_4As_3, crystal structure, (4) 95*h*.
NbC_{1-x}, physical properties, (3) 74*f*.
Nb_2O_5, thermal expansion, (8) 211*a*.
$Nb_{29}O_{141}F$ and $Nb_{48}O_{124}F_8$, crystal structures, (6) 146*d*.
Nb_2P_3 crystal structure, (6) 146*b*.
Nb_3Sn, conductor material, P (4) 90*f*.
nitride, ac losses, (7) 166*d*.
films, superconducting temps., (3) 63*j*.
and Nb_4N_3 films, (3) 74*h*.
oxides, energies of formation, (1) 21*i*.
pentachloride, fusion, (8) 208*h*.
reaction with chlorides of bivalent metals, (5) 123*i*.
vapor pressure, (8) 211*f*.
pentoxide, aluminothermic reduction, (6) 143*f*.
pentoxide flux, brazing with, P (4) 90*h*.
powder, P (10) 257*g*.
reaction with Al_2O_3 melt, (7) 163*j*.
recovery, P (5) 115*b*.
sulfide, new superconductor, (4) 97*h*.
systems. See *Systems*.
-Ti superconducting material, P (11) 275*c*.
and TiC powders, sintering, (10) 260*e*.
X-ray *K*-absorption edge, (6) 153*b*.
Nitrides, emission coeff., (3) 73*a*.
metal, as cracking catalysts, P (4) 94*h*.
nitriding of Mo, (6) 145*e*.
passivation, of mesa transistors, P (4) 89*f*.
reactions with refractory metals, (2) 49*f*.
Nitrogen, adsorption on cement pastes, (10) 242*c*.
adsorption, in study of gel texture, (2) 47*h*.
atoms, recombination at surfaces, (1) 24*h*.
chemisorption on Ta, (3) 72*e*.
desorption, for measurement of specific surface areas of powders, (9) 230*f*.
in diamond, properties, (4) 98*g*.
effects on alkali borophosphate glass, (4) 80*g*.

Nitrogen *(continued)*
films, effect on P impurity profiles in Si, (9) 223*j*.
gas, in melt to improve refractories, P (9) 222*i*.
oxide reduction, catalyst for, P (10) 257*c*.
role in microbubble formation during Zr combustion in N_2/O_2 mixture, (8) 210*b*.
solubility in aluminosilicate melts, (6) 147*j*.
systems. See *Systems*.
V(C,N)C-rich solutions, equilibrium, (4) 96*d*.
Noise, ferrite, in recording heads, (4) 86*f*.
in X-ray films, (9) 231*h*.
Nomenclature, for abrasive engineering, (9) 213*e*.
problems in ceramic industry, (7) 172*d*.
Nomographs, to compare mill productivity, (5) 115*f*.
use in electrical dust precipitators, (9) 229*j*.
Nose cones. See *Spacecraft*.
Nozzles. See *Refractories; Spacecraft*.
Nuclear materials, rotary elastic fluid flow machines, P (10) 254*c*.
particles, structure, (1) 15*h*.
physical behavior of bodies, P (7) 171*i*.
Nucleation, in fluor-richterite glass, (3) 55*j*.
in glasses, advances in, B (10) 261*i*.
heterogeneous, on substrate, (8) 199*j*.
homogeneous, theory, (5) 118*f*.
in opal glasses, (7) 160*c*.
in Na_2O-BaO-SiO_2 system, (3) 56*h*.

Olivine, electrical conductivity and absorption in, (10) 258*j*.
Opacification. See *Enamels; Glass; Glazes*.
Optical. See also *Glass, optical*.
absorption edge, in SnO_2, (3) 75*h*.
density of clay suspensions, (5) 122*b*.
focusing, using glass fiber plate, P (8) 192*f*.
ir scanning system, P (1) 18*g*.
interferometry, for measuring length, P (11) 278*i*.
line shifts in $SrTiO_3$:Cr^{3+}, (5) 119*j*.
measurements, on GR1 center in diamond, (4) 98*a*.
of particle orientation in clays, (6) 145*c*.
sample holder for, P (3) 70*g*.
of temp. in hot glass, (3) 56*j*.
of wear of tiles, (8) 198*c*.
phonons in $KCl_{1-x}Br_x$ and $K_{1-x}Rb_xI$ crystals, (5) 122*j*.
photo-, particle analysis, P (8) 206*a*.
probing, of CdS crystals, (6) 150*f*.
ray tracing in gradient-index glasses, (8) 205*b*.
shutter, ferroelectric ceramic, P (2) 40*h*.
study, of CaF_2:Ho^{3+}, (5) 122*a*.
of Cr^{3+} in Al_2O_3, (5) 121*d*.
electron, of cement pastes, (11) 266*f*.
electron, of kaolinite microcrystals, (9) 235*d*.
of Ag^+ and Cu^+ ions diffusing into glass, (3) 56*j*.
Optical devices, acousto-, with chalcogenide glasses, P (7) 168*g*.
$PbMoO_4$ for, P (3) 64*a*; (4) 98*f*.
tellurite glass in, (5) 106*d*.
coherent, using Zn Ge phosphide, P (10) 244*a*.
elements, using glass-ceramics, P (5) 107*a*.
nonlinear, P (1) 14*b*; P (10) 252*f*.
for sampling material, P (2) 45*c*.
Optical materials, optoelectronic, physics, B (2) 51*j*.
Optical properties, of BN thin films, (5) 122*j*.
of chalcogenide alloy films, (6) 136*i*.
of chalcogenide films, (6) 136*g*.
of chalcogenide glasses, (6) 132*c*.
constants, of anisotropic crystals, (1) 17*h*.
constants, of GaAs, (8) 209*i*.
of Eu chalcogenides, (9) 237*f*.
of Gd Al garnet, (2) 47*f*.
of $Gd_2(MoO_4)_3$, (3) 73*h*.
of garnet crystals, Ce-activated, (1) 11*g*.
-index values, ir, for MgO, (8) 209*a*.
nonlinear, of $KNbO_3$ single crystals, (3) 74*c*.
of *np* ZnO-Si heterojunctions, (4) 96*i*.
second-harmonic-generation coeff., of $LiNbO_3$, (6) 146*h*.
of SiO_2, fused, (8) 191*j*.
in system $BaCeO_3$-$Ba_2(CeTa)O_6$, (11) 283*g*.
of SnO_2 single crystals, reduced, (3) 72*j*.
Optics, electrooptic modulation of light in $LiNbO_3$, (1) 11*d*.
Ores, deposits, composition, size, and location, P (8) 207*d*.
Organic materials, effect on Ca aluminate hydrates, (4) 78*f*.
gaseous compounds, Al_2O_3 desiccant for drying, P (3) 71*h*.
liquefying agent, Kerkortan, (10) 248*g*.
liquid, cement sedimentation in, (4) 79*c*.
-refractory oxide, semiconducting, P (7) 170*h*.
Orientation, in Al_2O_3 substrates, (11) 274*e*.
Orthopyroxenes. See *Pyroxenes, ortho-*.
Orthosilicates. See *Silicates, ortho-*.
Oscillations, elastic spin, in circuits, P (9) 226*i*.
electrical, in microhole on glass, (3) 55*g*.
Gunn effect-type, in semiconductors, P (8) 202*d*.
Oscillators, crystal, temp.-compensated, P (8) 202*g*.
GaAs, P (2) 39*d*.
limiter-stabilized, P (4) 88*a*.
negative resistance device, P (1) 14*c*.
pn junction semiconductor microwave, P (10) 253*d*.
semiconductor, bulk, P (3) 67*j*.
data on, (7) 168*f*.
Oscillators, semiconductor *(continued)*
hf bulk, P (1) 12*e*.
n-type GaAs, P (3) 68*c*.
Si avalanche L-band, compact, P (5) 112*g*.
solid-state microwave, P (9) 228*a*.
superconducting, P (4) 91*a*.
temp.-compensated, P (11) 275*j*.
transistor crystal, P (2) 43*d*.
for treating particulate solids, P (6) 141*g*.
ZnO crystal bulk effect, P (9) 233*d*.
Ovens. See also *Furnaces; Kilns*.
ceramic, feeding devices for, P (2) 45*f*.
continuous-cleaning coatings, (6) 131*d*.
for continuous firing, (4) 93*j*.
firing, dental ceramic, P (7) 174*j*.
liners, P (7) 164*a*.
self-cleaning cooking, enamels for, P (9) 216*a*.
top-heated, gas burners for, P (7) 174*d*.
use in mfg. enameled wires, P (1) 17*c*.
Oxidation, of CO on La_2O_3-doped $BaTiO_3$, (11) 274*b*.
of Cu_2S, kinetics, (6) 149*e*.
high temp., vapor phase during, (11) 277*c*.
kinetics. See *Kinetics*.
low-temp., of hard-alloy mixtures, (10) 260*a*.
in mfg. semiconductor device, P (1) 13*a*.
plasma, to remove photoresist films, (3) 63*a*.
of Pt metals in melts and glasses, (2) 32*f*.
reduction, in $PbTiO_3$-$La_{2/3}TiO_3$ system, (3) 63*a*.
potentials in O compounds of transition metals, (5) 119*a*.
reactions in BOF refractories, (2) 36*g*.
resistance, of Ni-base materials, (10) 260*c*.
resistance, of SiC, (10) 246*f*.
-resistant, graphite and C shapes, P (9) 222*c*.
-resistant shaped bodies, P (5) 110*c*.
of Ru in glasses, (2) 32*e*.
of Si, SiO_2 thin layers formed by, (9) 239*d*.
temp., of magnesite and dolomite, (11) 272*i*.
of UO_2 fuel pellets, (11) 276*c*.
for white metal oxides, P (3) 71*b*.
Oxides. See also *Rare earths* and specific types.
antiferromagnetic, susceptibility, (4) 81*c*.
binary, sintering, (7) 177*c*.
bodies, structure and strength, (10) 248*f*.
charge distributions in, (6) 150*i*.
crystals, solution growth, (2) 39*h*.
defect structure, effect on ZrO_2, (10) 258*i*.
disordered 3*d*, polaron conduction in, (6) 151*d*.
effect on glaze/body reactions, (8) 197*j*.
effect on sulfide S in slag glass, (8) 190*h*.
electrowinning from silicate rocks, (7) 175*a*.
energy transfer in, (1) 21*j*.
films, effect in TiC impregnation with liquid steel, (10) 258*j*.
as etching mask, P (2) 40*f*.
heteroepitaxial magnetic, (2) 49*i*.
sputtering, P (4) 90*j*.
group IV, matrix isolation studies, (7) 178*e*.
high-temp., B (4) 100*g*.
inorganic, by cryochemical process, (3) 62*f*.
in Fe-Mn alloys, (6) 152*e*.
layers, formation and desorption on W, (11) 281*j*.
machining, with gas lasers, (2) 44*j*.
materials, modern, B (9) 240*h*.
metal, P (5) 118*c*.
coating, on substrates, P (6) 138*j*.
coatings for refractories, P (8) 193*c*.
continuous forming, P (5) 112*i*.
film structure, P (10) 251*h*.
films, sputtered, P (7) 170*d*.
finely divided, P (8) 207*b*.
layers, photoetching, P (2) 41*j*.
negative resistance and modulation in, (6) 150*j*.
nonstoichiometry, diffusion and electrical conductivity in, B (10) 263*j*.
single crystal films, P (3) 65*f*.
white, oxidation for, P (3) 71*b*.
metallic, layers on glass, (7) 159*i*.
mixtures, viscosity anomaly in, (7) 181*i*.
oxidizing method and apparatus, P (7) 169*i*.
oxidizing, Si wafer, controllably, P (6) 138*j*.
particles, effect on sintering carbonyl Fe, (10) 246*j*.
piezoelectric materials, P (11) 275*j*.
positrons in, life times, (4) 95*d*.
powders, hydrothermal preparation, (4) 97*a*.
in Si_3N_4, solid solubility, (4) 98*d*.
single crystals, growth, (2) 48*c*.
structural formula $(La_{1-x}Ca_x)CrO_3$, P (4) 89*g*.
systems. See *Systems*.
ternary, Ru, use in resistor glazes, (4) 86*d*.
transition metal, electronic transport in, (9) 235*h*.
O_2 content of, (3) 74*i*.
and SmB_6, transition model, (6) 151*e*.
Oxygen, activity, effect on sintering Cr_2O_3, (10) 259*g*.
adsorption on MgO during irradiation, (1) 21*j*.
atoms, recombination at surfaces, (1) 24*j*.
atoms, in silicate chain, core binding energy in, (1) 21*d*.
compounds of transition metals, (5) 119*a*.
content of transition metal oxides, (3) 74*i*.
diffusion in TiO_2, (9) 238*i*.
diffusion in ZrO_2, (9) 237*i*.
dissolution, in molten Pb, kinetics, (6) 149*g*.
-18, analysis in solid oxides, (5) 118*h*.
in gases, electrochemical analyzer for, P (1) 18*e*.
impurity, effect on CoO and NiO crystals, (6) 146*i*.
Oxygen *(continued)*
ions, activity in Na phosphate, (5) 123*c*.
isotope fractionation in carbonates, (4) 98*c*.
melt activity, effect on amber glass, (8) 189*f*.
octupoles, effect on electric field gradient in corundum, (5) 120*d*.
O^{2-} atom, in MgO, electron state, (4) 96*b*.
quantities, instrument for determining, P (2) 45*a*.
removing from glass ribbon float bath, P (3) 59*f*.
role in spinel formation from MgO and Al_2O_3, (5) 123*c*.
self-diffusion, of CeO_2 and CeO_2 solid solutions, (9) 237*i*.
self-diffusion, in MgO, (3) 75*c*.
systems. See *Systems*.
thermal diffusion in UO_2, (7) 171*c*.
Packaging. See also *Shipping*.
bottles and jars, P (7) 162*f*.
piece goods on base frame, P (3) 69*d*.
shipping case for flat glass, P (7) 161*f*.
Paleosalinities, calculation from B and clay mineral data, (3) 71*b*.
Palladium, $Pd_3P_2S_8$ compound, P (7) 168*b*.
phosphide chalcogenides, P (7) 169*i*.
Pallets. See *Materials handling*.
Panels. See *Building materials; Glass*.
Paraffin, *n*-, conversion in hydrocarbon oils, P (11) 279*g*.
Paragonite. See *Mica*.
Paramagnetic materials. See *Magnetic materials*.
Particles. See also *Colloids*.
analysis, photo-optical, P (8) 206*a*.
analyzing apparatus, P (10) 256*b*.
atomic, energy and atomic number, P (2) 39*d*.
clusters, treating material containing, P (9) 230*b*.
coating by slurry process, P (7) 170*d*.
compaction, P (2) 43*j*.
conversion/extraction efficiencies, (6) 141*d*.
counting apparatus, P (2) 45*d*.
counting apparatus, conductivity cell for, P (9) 231*f*.
dispersed, effect on elastic behavior of composite materials, (6) 148*j*.
fine, container for holding, P (5) 115*f*.
fine, thermically treating, P (6) 143*b*.
flow measurement, P (5) 116*f*.
fluidization, P (11) 277*g*.
geometry, of refractory-compound powders, (10) 259*j*.
grading according to sphericity, P (10) 254*h*.
granules, spherical, P (3) 69*b*.
mean size in fluid, determination, P (10) 256*a*.
mineral, calcining, P (6) 143*b*.
mixing, apparatus for, P (1) 16*j*.
movement in bin by sonic vibrations, P (5) 115*c*.
polycrystalline, 2-dimensional shape, (6) 152*g*.
pumping apparatus, P (10) 254*f*.
separation, apparatus for, P (4) 92*h*.
from effluent stream, P (6) 141*f*.
from fluid, P (11) 277*c*.
size, analysis, using settling tubes, (8) 204*c*.
control, P (3) 71*e*.
correlation with density, (6) 151*e*.
determination, (11) 278*a*.
diameter, relation to ferrite noise, (4) 86*f*.
and distribution of crushed minerals, (7) 172*c*.
in Fe, effect of Mn and C, (6) 148*j*.
Fe_2O_3 and spinel, relation to magnetic properties of Mn Zn Fe_2O_4, (1) 11*i*.
in MgO and MgO-Fe_2O_3 solid solutions, (2) 48*b*.
measurement, P (10) 256*a*.
measurements, industrial, (11) 277*j*.
nonclay, role in whiteware casting, (8) 198*g*.
in polycrystalline ceramics, (3) 69*h*.
in predicting properties of calcined Al_2O_3, (1) 11*g*.
of rare earth oxide, P (4) 90*g*.
reduction by explosive shocking, (1) 22*h*.
of refractory batches, (8) 196*a*.
segregation in storage, (11) 276*g*.
and shape, effect on MgO ir absorption, (6) 146*j*.
-vs-strength, for ceramics, (6) 151*j*.
size distribution, of ceramic clays, (11) 281*i*.
in clay suspensions, (5) 122*b*.
determination, P (9) 231*i*.
in ground material, P (4) 93*f*.
measurement, P (7) 174*a*.
solid, angles of repose and bulk densities, (5) 117*e*.
concentration measurement, P (5) 116*f*.
measuring friability, P (5) 116*e*.
mixing, humidity effect, (7) 172*b*.
treatment by oscillation, P (6) 141*g*.
sorting by shape, (1) 17*i*.
spherical, Al_2O_3-SiO_2-containing, P (2) 46*e*.
spherical, calculation of radius distribution, (1) 17*f*.
submicroscopic magnetizable metal, P (10) 252*b*.
suspended, concentration, P (2) 45*b*.
very fine, irregularly shaped, classification, (3) 69*h*.
Pelletization, powders by vibration, P (7) 172*a*.
serpentine chrysotile fines, P (3) 61*a*.
Pellets, compression resistance testing, P (2) 44*i*.
Periclase, grains, crystalline plasticity, detecting in basic bricks, (1) 18*h*.
microstructure in BOF refractories, (8) 195*a*.

Peridotite, alpine-type, structure and petrology, (1) 20*i*.
Perlite, fine raw, treatment, (10) 257*a*.
from Shirasu, (6) 143*g*.
structures, water-insensitive bonded, P (8) 197*b*.
Permeability. See also *Porosity*.
of clays, (5) 121*h*.
compression, of Al_2O_3 cakes, (9) 223*c*.
of granular material, measuring, P (2) 45*b*.
measurement with pocket permeameter, (8) 105*i*.
of Ni-Zn ferrites, (7) 167*b*.
of sandstone, increase in, (7) 175*g*.
H_2O, of concrete, vacuum, (6) 130*a*.
Permittivity. See *Dielectrics, constant*.
of materials, measuring device for, P (9) 231*f*.
Perovskites, fluoro-, properties, (1) 24*e*.
Moessbauer effect and magnetic susceptibility in, (3) 74*b*.
transition metal, as catalysts, P (6) 144*f*.
Petrology, of calc-alkaline volcanics, (8) 209*j*.
of peridotite, alpine-type, (1) 20*i*.
pH. See *Hydrogen ion concentration*.
Phase, analysis, of mixtures of solids, (3) 69*j*.
analysis, of portland cement clinkers, (6) 129*h*.
boundaries, UC-UC_2, (4) 91*h*.
composition, of binding materials, (2) 30*i*.
of cement-quartz cubes, (8) 187*a*.
of magnesite-chromite refractories, (8) 195*b*.
of Mo-Cr-B alloys, (10) 260*f*.
of siliceous clinkers, (8) 186*i*.
of sitalls, (8) 191*j*.
high-temp., of zeolites, (9) 236*a*.
$MLn_4Mo_3O_{16}$ and $M'Ln_6Mo_4O_{22}$, (4) 98*d*.
in portland cement, (5) 104*g*.
relations in carbonates, (9) 238*j*.
separation, of alkali silicate glasses, (3) 55*c*.
of glass, (3) 57*c*; (11) 269*d*.
in Pb borate glasses, (9) 218*c*.
of Na_2O-SiO_2 glasses, (3) 57*c*.
in systems Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3, (2) 47*e*.
solid and liquid, effects on cement clinker, (4) 79*d*.
stoichiometric, solution model for, (11) 281*i*.
transformations, lateral growth in, (6) 149*a*.
of MgO, SiO_2, CaO, and Fe_2O_3 mixture, (8) 210*b*.
of Mg phosphates, (8) 210*c*.
in milled ZrO_2, (11) 282*d*.
in SiC, (7) 179*a*.
transitions, of adsorbates, (2) 48*g*.
in Ce Mg nitrate, (6) 150*b*.
during nepheline decomposition, (7) 179*b*.
ferroelectric in PLZT, (11) 273*d*.
of ferromagnets, (4) 96*g*.
in $PbZrO_3$ and $PbTi_{0.2}Zr_{0.8}O_3$, (7) 178*i*.
magnetic, in EuO, (6) 151*h*.
magnetic, in ferromagnets, (6) 149*i*.
110°K, in $SrTiO_3$, (5) 121*g*.
in perovskite-type crystals, (6) 152*b*.
in $PrAlO_3$, (6) 152*b*.
vapor. See *Vapor, phase*.
Phase diagrams. See *Equilibrium studies*.
Phillipsite, rare gases in, (2) 50*c*.
Phlogopite. See *Mica*.
Phonons, instability in $LaAlO_3$, (5) 125*j*.
optical, hypersonic attentuation in $SrTiO_3$, (6) 148*e*.
role in photoconductivity spectrum of diamond, (5) 123*f*.
Phosphates. See also *Glass* and specific types.
bonding, (8) 196*c*.
-coated rare-earth oxides, P (1) 14*c*.
linear electrooptic effects in, (1) 11*c*.
ortho- and pyro- compositions, Eu^{2+} luminescence in, (9) 236*d*.
and phosphors from, P (4) 89*i*.
poly-, adsorption on clays, (1) 9*h*.
recovery by leaching, P (6) 144*g*.
and silicates, mixtures, P (3) 71*g*.
soluble, from phosphate rock, P (11) 279*h*.
solutions, recovery of F_2 and P_2O_5 from, P (3) 72*b*.
systems. See *Systems*.
Tenn., flotation studies, (7) 175*c*.
thermal properties, cation effect, (5) 120*c*.
transition metal, fibrous, P (9) 232*g*.
Phosphoric acid, clarification, P (6) 143*j*.
compounds from phosphate rock, P (4) 94*b*.
cryolite from, P (10) 257*g*.
fluorination, P (4) 94*h*.
foamed ceramic comprising, P (3) 60*b*.
at high concentration, P (7) 175*i*.
ortho-, effect on concretes, (8) 187*j*.
ortho-, reaction with chamotte, (8) 196*e*.
from phosphate rock, P (4) 94*h*.
production, recovering Na_2SiF_6 in, P (1) 20*i*.
Phosphors, P (5) 113*j*; P (6) 139*a*; P (7) 169*j*.
alkaline earth, halosilicate, P (7) 168*h*.
metal fluoro-chloro-phosphate, P (8) 202*c*.
metal sulfide, P (3) 66*g*.
sulfate, compositions, P (7) 169*e*.
thiogallate, P (5) 112*e*.
atomizing, spray-drying, and flame process for, P (10) 249*g*.
Ca Al_2O_3, Ce-activated, P (8) 203*a*.
Ca halophosphate, P (7) 170*g*.
cathode luminescent, reclamation, P (6) 137*g*.
cathode-ray, efficiency, (9) 224*c*.
cathodoluminescent, treating, P (5) 113*c*.
cathodoluminescent, ZnS:CdS, P (7) 168*j*.
coating, for arc discharge lamps, P (6) 139*i*.
color, electrophoretic deposition, P (10) 244*e*.
compositions, P (6) 139*j*.
Phosphors *(continued)*
display screen and filter, P (5) 113*g*.
electron, for cathode-ray tubes, P (9) 225*f*.
fast decay, (9) 224*c*.
firing, continuous, P (1) 12*e*.
GaAs junction, P (8) 200*f*.
halophosphate, P (5) 113*i*.
halophosphate, particle size increase, P (8) 200*i*.
pH, controlling in processing, P (2) 41*a*.
improved conversion efficiency, (3) 73*g*.
ir matched with YAG:Nd laser, (3) 63*d*.
lehring-sensitive, coating on lamp, P (10) 245*c*.
luminescent decay-time, P (3) 68*a*.
luminophor, ZnS ir-sensitive, P (1) 12*g*.
Mg aluminate gallate, P (9) 227*j*.
Mg gallate, P (9) 225*a*.
Mn^{2+}-activated, electronic states, (9) 235*f*.
particles, coating to TV tube, P (10) 244*e*.
from phosphate, P (4) 89*i*.
phosphate, from monetite, P (7) 170*f*.
by precipitation from solution, P (9) 227*h*.
preparation, (4) 86*e*.
for radiation dosimeter, P (5) 113*h*.
rare-earth, P (7) 169*e*.
metal orthovanadate, P (4) 89*h*.
oxide, P (7) 170*h*; P (11) 275*j*.
oxide, stabilizing, P (10) 252*d*.
oxyhalide, P (9) 228*e*.
trifluoride up-conversion, (6) 136*i*.
reclaiming and coating, P (6) 139*g*.
reclamation from slurry, P (3) 66*f*.
screen, P (3) 66*f*.
spheroidal, in translating device, P (9) 218*i*.
Sr, Ba chloroaluminate, luminescent, P (6) 138*e*.
fluoroborate, P (8) 200*c*.
halide, doped, P (3) 64*g*.
phosphate, Yb-activated, P (2) 43*c*.
thiogallate, P (3) 67*i*.
Zn pyrophosphate, P (9) 228*c*.
transparent Gd_2O_3 ceramics and, (10) 249*a*.
Y, Ga oxide, solid solution, P (8) 200*g*.
orthophosphate, P (10) 253*f*.
orthovanadate, reclaiming, P (9) 227*a*.
orthovanadate, upgrading, P (6) 139*j*.
Y_3OCl_7:Yb^{3+}-Er^{3+}, efficiency, (3) 72*g*.
YOF:YB, Er, (3) 63*d*.
$YSnO_3$, for warm-white blends, P (5) 113*f*.
YVO_3, Eu-activated, P (4) 90*d*.
Zn and CdS, P (1) 14*g*.
Zn-Mg silicogermanate, composition, P (6) 140*e*.
ZnO, display devices based on, (4) 86*e*.
ZnS, P (8) 203*a*.
blue, P (9) 227*i*.
Cu-resistant Ag-activated, P (11) 275*b*.
effect of firing atm, (7) 180*h*.
photodielectric effect in, (3) 74*f*.
Phosphorus, pentoxide, effect on cement clinker, (3) 53*j*; (9) 214*f*.
pentoxide, recovery from phosphatic solutions, P (3) 72*b*.
phosphorites, as cement additive, (8) 188*a*.
PCl_3-$FeCl_3$, spectroscopy, (6) 151*i*.
selenides, ^{31}P NMR, (9) 233*g*.
systems. See *Systems*.
Photoconductive effect, and(or) **Photoconductivity,** layer, of PbO and SnO crystals, P (2) 34*j*.
layers, preparing on substrates, P (1) 13*e*.
of pyrite, (4) 98*e*.
recording process, P (3) 65*j*.
target, Se-S, P (2) 42*h*.
transient, of EuS, (3) 76*a*.
Photoconductors. See *Conductors, electrical, photo-*.
Photoelectric cells. See *Cells*.
Photoelectricity, Einstein law, and electron emission, (4) 97*g*.
device, P (1) 14*c*.
Photography, color, pink glass for, P (9) 220*b*.
electro-, CdS or CdSe powder for, P (6) 139*d*.
electro-, plates, with additives, P (6) 137*g*.
flashbulb, P (4) 81*i*.
flashbulb, ignition, P (4) 81*h*.
for reproducing stereoscopically, P (11) 277*f*.
Photometers. See also *Spectrophotometers*.
hydro-, size analysis of silt and clay by, (1) 18*i*.
Photometry, determination of Zr in refractories, (8) 195*a*.
micro-, of undeformed dolomites, (1) 23*b*.
Phototropy, articles of thallous halide, P (2) 35*a*.
in glasses containing Ag halides, (8) 190*c*.
Physical chemistry. See *Chemistry*.
Physical properties, of alloys of WB-LaB_6 system, (10) 259*e*.
of aluminosilicate films, (2) 38*d*.
of ceramic tile bodies, (6) 135*j*.
electro-, of hexaborides, (10) 259*c*.
of micas, cation substitution effect, (9) 234*e*.
of portland cement plaster, (4) 79*g*.
of TiC_{1-x} and NbC_{1-x}, (3) 74*f*.
of TiO, (5) 118*j*.
Physicochemical properties, changes during firing of bricks, (6) 134*a*.
of Indian magnetites, (11) 282*f*.
of slurries, effect on kiln operation, (8) 187*a*.
of systems for ferroelectric and piezoelectric materials, (5) 122*d*.
transformations in ferrites, (8) 199*f*.
Physicomechanical properties, of aluminocalcium sinters, (7) 156*c*.
Physics, of clays and ceramic materials, B (6) 153*c*.
of electronic ceramics, B (2) 51*c*; B (7) 183*g*.
Physics *(continued)*
of optoelectronic materials, B (2) 51*j*.
of superconductors, B (2) 51*i*.
Pickling, acid inhibitor, (1) 3*a*.
low pressure steam for, (10) 242*g*.
Piezoceramic, oscillating, measuring frequency, (2) 44*j*.
Piezoelectricity, accelerometer, P (4) 89*j*.
bender bilayer, P (4) 89*j*.
ceramics, P (4) 90*a*; B (7) 184*a*; P (9) 227*g*; P (11) 275*i*.
CeO_2 and Cu additives, P (7) 170*b*.
compositions, P (5) 113*i*; P (6) 139*a,b*; P (7) 170*a*; P (9) 227*f*.
filter, P (5) 113*i*.
filter elements, P (3) 66*c*.
material, P (11) 275*i*.
constants, of $LiTaO_3$ and $LiNbO_3$, (4) 99*f*.
crystal, assembly, P (3) 66*h*.
device, P (11) 275*i*.
units, P (8) 201*e*.
device, P (6) 138*c*; P (7) 170*c*.
device using Li germanate, P (9) 227*g*.
effect in quartz, (5) 124*h*.
and ferroelectric composition, P (4) 87*i*.
ignition devices, P (7) 170*c*.
lighter, P (7) 170*c*.
materials, (2) 39*b*.
oxide, P (8) 202*a*; P (11) 275*j*.
physicochemistry of systems for, (5) 122*d*.
piezo-optic properties, of Se, amorphous, (8) 191*a*.
plate, thickness vibrations, (3) 63*i*.
power supply, negatively charging, P (3) 66*e*.
properties, of PLZT ceramics, (11) 273*i*.
properties, of $PbNb_2O_6$-$BaNb_2O_6$ system, (11) 281*b*.
structure of ferroelectric material, P (8) 202*b*.
switching device for demodulator, P (7) 170*c*.
Pigments. See also *Color; Stains*.
P (7) 176*a*; P (9) 233*d*; P (10) 257*j*.
binding to glass fabrics, P (4) 81*g*.
ceramic, in glazes, (1) 9*j*.
Dulevo (USSR) Color Factory, (8) 197*f*.
Fe-MnO black, temp.-stable, P (2) 46*g*.
Fe oxide, P (3) 72*b*.
Fe_2O_3, P (3) 71*b*.
kaolin, P (2) 46*h*.
for metal coil coatings, (11) 279*h*.
metal oxide, P (5) 117*i*.
SiO_2, modified, P (11) 279*h*.
stanniferous ceramic, P (11) 279*h*.
TiO_2, P (5) 117*h*, 118*c*; P (7) 175*h*; P (8) 207*h*; P (10) 257*c*.
anatase, P (2) 46*b*; P (3) 71*f*.
with anatase crystal structure, P (3) 71*f*.
coated, P (8) 207*c*.
heating gases for, P (4) 94*i*.
rutile, for paper laminates, P (10) 257*i*.
white, inorganic, P (9) 232*h*.
$ZnTiO_4$, for coatings, P (1) 3*a*.
Pipe. See also *Tile*.
apparatus for forming, P (8) 194*g*.
cement-lined water, corrosion, (7) 156*e*.
cement composition for lining, P (9) 215*e*.
clay, and concrete, B (6) 153*j*.
epoxy branching, (9) 220*g*.
industry, (2) 35*f*.
large, machine for, (9) 220*d*.
vitrified, (2) 35*f*.
concrete, filtration, (6) 129*b*.
coupling, P (4) 82*g*.
fiber glass, with joint thread, P (8) 193*c*.
glass, coupling for, P (10) 244*c*.
glass, seam-free foam, P (7) 162*a*.
from glass metal, device for, P (4) 81*d*.
joint, P (8) 194*f*.
-lines, testing, P (10) 246*d*.
plastic, for aeration system, P (3) 60*c*.
stoneware, black cores in, (11) 271*d*.
connecting with rubber rings, (10) 246*a*.
factory, (7) 163*c*.
stopper, for bell and spigot tile, P (10) 246*c*.
Pitch. See *Resin*.
Plasma, coatings, for electrodes in molten Al, (10) 246*i*.
conductivity, determination, (3) 69*j*.
torch, for analysis of glasses and raw materials, (8) 205*h*.
Plaster of Paris. See *Gypsum; Plasters*.
Plasters, admixtures, (4) 79*g*.
alpha, P (8) 188*g*.
gypsum, assessment by weight loss, (11) 266*j*.
interior, coating composition, P (3) 54*b*.
molds. See *Molds*.
of Paris, under high load, (5) 103*d*.
products, fiber-containing, P (11) 267*e*.
strength, influence of gypsum, (3) 53*j*.
Plasticity, of brick clays, (6) 143*h*.
of cement, measurement, (9) 215*e*.
of cement plasters, (4) 78*i*.
chart for industrial clays, (6) 143*h*.
crystalline, of periclase grains in basic bricks, (1) 18*h*.
elasticity, and structure of matter, B (3) 76*h*.
Plastics. See also *Resins*.
articles, ram-forming, P (10) 246*a*.
flow of Bingham material, (4) 98*d*.
glass-reinforced, impact fracture in, (5) 105*i*.
plating for space use, (2) 38*d*.
portland cement-, combination, (6) 128*j*.
precision engineering, B (9) 240*b*.
reinforcement with graphite fibers, P (4) 84*d*.
thermo-, glass-fiber-reinforced, P (7) 162*b*; P (11) 270*j*.
thermo-, molding materials, P (8) 207*h*.
Plating. See *Coatings*.
Platinum, /Al_2O_3 interface, grain-boundary grooving, (2) 50*c*.

Platinum *(continued)*
contact angle measurements of glasses on, (11) 269*h*.
-Au, films, electrically conducting, (2) 38*e*.
-group metals, coatings for, P (2) 31*i*.
-metal oxides, type Pt_3MO_4, P (8) 207*a*.
metal thermocouples, (10) 255*i*.
metals, in melts and glasses, (2) 32*f*.
-Rh vs Pt thermocouple, P (10) 256*a*.
systems. See *Systems*.
thin-film metallization method, P (8) 202*e*.
thin films, use as mask, P (4) 91*b*.
Plutonium, carbide, equations of state for, (5) 114*j*.
carbide, vapor free melting, P (9) 228*j*.
dioxide, reducing to Pu, P (3) 68*h*.
effect on thermal conductivity of $(U,Pu)O_2$ solid solutions, (7) 171*g*.
formate and dioxide, P (8) 203*f*.
hexafluoride, reduction, P (9) 229*b*.
mixing and settling process for, P (10) 254*a*.
separation from U oxides and PuO_2, P (1) 16*d*.
systems. See *Systems*.
Poisson's ratio, of cement paste, mortar, and concrete, (5) 102*j*.
Polarization, of light in magnetic field, (6) 151*b*.
of H_2O-cement system, (3) 54*b*.
Polishing. See also *Abrasives; Diamonds; Lapping*.
acid, of glass, P (1) 3*c*.
calendering for forming ceramic sheets, (9) 223*g*.
chemically, crystals, P (4) 88*e*.
GaP, P (10) 251*j*.
glass, P (10) 245*d*.
according to DIN 3140, (7) 158*c*.
electrolytes effect, (7) 159*d*.
by electronic bombardment, (7) 158*c*.
machinery, P (10) 244*c*.
mechanics, (11) 269*a*.
optical, (3) 57*a*.
ion beam, of glass, (9) 217*e*.
magnetic oxide materials, P (8) 201*g*.
semiconductor materials, P (11) 275*a*.
Si surface, P (2) 41*j*.
Polishing apparatus. See also *Abrasives; Diamonds*.
brush track for brush transformer, P (3) 53*h*.
cutting, and grinding, for single-crystal workpieces, P (7) 172*f*.
vibratory, slide holder for, (4) 93*a*.
Pollution, air, analysis, B (8) 212*e*.
from brickwork kilns, (10) 246*a*.
C for stack SO_2 recovery as S, (2) 92*b*.
in ceramic industries, (7) 182*c*.
control in Germany, (9) 239*h*.
from fuel combustion, reducing, (1) 19*a*.
instrumentation in, (9) 231*e*.
from kiln exhaust gases, (1) 19*a*.
regulations, (5) 126*a*.
solid sorbents for SO_2, (6) 143*a*.
spraying equipment related to, (10) 254*e*.
in structural clay industry, (9) 220*g*.
S problem in fuels, (5) 117*a*.
anti-, chamber, P (9) 229*f*.
fuel, and clay industries, (2) 50*g*.
H_2O, disposal and reuse, B (2) 52*j*.
new standards, (5) 115*g*.
and noise, in whitewares industry, (3) 61*i*.
Polyacrylamide, flocculation of kaolinite, (2) 37*h*.
Polyamide, -polyimide as semiconductor surface passivator and coating, P (2) 42*b*.
Polycrystalline materials, ceramics, grain-boundary sliding in, (9) 235*h*.
ceramics, grain size in, (3) 69*h*.
fracture energies, (2) 47*j*.
grains, 2-dimensional shape, (6) 152*g*.
solids, grain-boundary sliding and creep in, (6) 148*h*.
Polyelectrolytes. See *Electrolytes*.
Polyester, sheets, glass-reinforced, P (1) 5*a*.
Polymers, characterization, B (2) 52*d*.
crystallization, model, (5) 120*c*.
impregnated concrete, (5) 103*a*.
impregnation, effect on tile bodies, (6) 135*j*.
intercrystalline links in, (7) 178*j*.
Polymorphism, in Hf and Zr titanates, (9) 239*c*.
modifications of Pm_2O_3, (9) 228*i*.
of K_2O, (7) 176*e*.
of silicates of Rb and Cs, (8) 210*e*.
Polymorphs, of Mn_2-GeO_4, crystal structures, (9) 234*e*.
Polyphenylene, and oxides, pyrolysis chemistry, (1) 24*i*.
Polyphosphates. See *Phosphates*.
Poole-Frenkel effect, on electric conduction in insulators, (5) 122*e*.
Porcelain, art. See *Art and artware*.
batches, working properties, (3) 61*i*.
bodies, green, hardness measurement, (9) 231*c*.
mechanical properties, (11) 273*c*.
preparation methods, (9) 223*b*.
structure and strength, (10) 248*f*.
thermal expansion, (5) 111*f*.
ultrasonic treatment, (8) 198*j*.
bonding dental Au alloy, P (10) 248*h*.
collector's handbook, B (7) 184*f*.
dental. See *Dental ceramics*.
for electric insulators, P (10) 248*g*.
electrical. See also *Insulators, electrical*.
dielectric strength, (1) 11*b*.
properties, (9) 224*a*.
electrostatic application of glaze, (11) 272*i*.
firing, effect of quartz genesis, (8) 197*g*.
firing by natural gas or propane, (2) 45*f*.
hard, glaze for, (2) 37*j*.
hard, mfg. and composition, (2) 37*j*.
Porcelain *(continued)*
for high-voltage applications, (7) 165*f*.
industry, rapid firing kiln in, (9) 223*e*.
Royal Worcester, description, (1) 9*i*.
use of computer in, (11) 276*j*.
low-thermal-expansion, P (7) 166*a*.
rods, fracture, (1) 10*a*.
semivitreous, nepheline structure in, (5) 110*j*.
slip, dehydrating, (8) 197*d*.
structure, rapid firing effect, (7) 165*h*.
whiteness, measuring, (8) 197*i*.
Pores, closure, during sintering, (1) 26*b*.
-forming, in perlite-chamotte products, (8) 195*c*.
in paste, effect on C_3S and alite, (4) 78*h*.
in plaster molds, (9) 223*d*.
size, measurements, industrial, (11) 277*j*.
size, and porosity, measurement, P (11) 278*i*.
size distribution, (1) 18*a,c*.
of cement, (11) 266*f*.
of cement pastes, (5) 102*i*.
in hardened cement, (1) 2*d*.
studying, (11) 278*d*.
spheroidization in Al_2O_3, (11) 282*f*.
structure, of Ca silicate hydrates, (9) 213*j*; (10) 242*b*.
structure, of clays, (5) 121*j*.
Porosity. See also *Permeability; Pores*.
of compacts, effect of sintering, (10) 247*a*.
correction factor for ceramic fuel conductivity, (7) 171*b*.
effects, on ceramic products, (4) 98*g*.
on electric strength of Al_2O_3, (7) 165*j*.
in polycrystalline graphite, (5) 122*f*.
on polymer-impregnated concrete, (5) 103*a*.
on UO_2 deformation, (4) 91*g*.
-elasticity relationship in Al_2O_3, (5) 125*b*.
fluctuations, in granulated mixture, (3) 73*j*.
of Fe-graphite materials, (10) 246*e*.
measurement, (6) 130*d*.
micro-, in carbonate rocks, (3) 71*d*.
of mordenite, H_2 forms, (3) 73*a*.
of Ontario limestones and dolomites, (7) 181*e*.
and pore size, measurement, P (11) 278*i*.
of portland cement paste, (4) 78*d*; (10) 241*i*.
-strength, of cellular concrete, (5) 104*d*.
of zircon ceramics, relation to electrical resistance, (8) 200*i*.
Porous materials. See also *Cements; Concretes; Insulation, thermal*.
bodies, surface treatment, P (1) 10*h*.
gas flow in, (6) 142*b*.
impregnating with noncolloidal solids, P (9) 230*d*.
polymer-impregnated, strength, (4) 85*e*.
solids, shock-wave structure in, (7) 180*c*.
solids, specific area, (2) 44*g*.
strength, (5) 104*c*.
Portland cement. See *Cement, portland*.
Positrons, in oxides, life times, (4) 95*d*.
Potash, ores, beneficiation by flotation, (3) 70*j*.
Potash feldspar. See *Feldspar*.
Potassium. See also *Alkalis*.
Bi Zn niobate, dielectric properties, (4) 98*b*.
bromide, crystals, whiskers and etching on, (7) 182*b*.
far-ir spectra, (6) 151*f*.
twinning, (7) 182*a*.
/Ca cation exchange selectivity of phyllosilicates, (5) 118*f*.
carbonatozirconates, crystalline, P (2) 46*b*.
chloride, additive coloration, (9) 238*c*.
-$AlCl_3$ melts, Raman spectra, (6) 151*i*.
bubble migration in, (4) 99*f*.
crystals, migrating bubbles in, (4) 97*h*.
electrophotoluminescence in, (6) 151*d*.
high-pressure equation, (6) 148*b*.
:Li^+, paraelectric resonance, (6) 150*f*.
properties, (5) 125*c*.
:NaCl crystals, *F* centers in, (5) 120*e*.
thermal conductivity, (5) 120*e*.
determination by spectrophotometry, (4) 78*b*.
fixation by soil clays, (9) 236*d*.
halides, magnetoconductivity, (6) 151*h*.
hydroaluminates, thermal decomposition, (8) 211*i*.
monoxide, effect on cement strength, (4) 79*a*.
in feldspars, determination, (8) 205*g*.
polymorphism, (7) 176*e*.
niobate, crystals, optical properties, (3) 74*c*.
nitrates, separation by zone melting, (3) 71*e*.
oxide and K-K_2O phase diagram, (7) 179*c*.
perrhenate, purification and crystal growth, (7) 179*i*.
phosphate, separation from Al_2O_3, P (6) 144*f*.
$KCl_{1-x}Br_x$ and $K_{1-x}Rb_xI$ crystals, optical phonons in, (5) 122*j*.
$KCrF_3$, (4) 98*g*.
$KH_2(PO_4)_3$, crystal structure, (6) 145*j*.
K_2O-Al_2O_3-SiO_2 and K_2O-Al_2O_3, (2) 48*j*.
silicate-Zn coatings, P (3) 54*g*.
and Ag sulfates and tungstates, reaction, (5) 123*h*.
-Na niobate, hot-pressing, (9) 223*g*.
solubility in melts of Na systems, (7) 177*c*.
sulfate, P (8) 207*f*.
from $MgSO_4$ salts, P (4) 94*b*.
ores, Al_2O_3 extraction from, P (7) 175*j*.
systems. See *Systems*.
tantalate, ultrasonic attentuation in, (5) 125*a*.
thermal conductivity, (3) 75*j*.
tri-, phosphate, for strengthening glass, P (1) 5*f*.
tungstate, reaction with In tungstate, (2) 49*f*.
in zeolite, decreasing, P (5) 117*g*.
Potters. See *Artists*.
Pottery. See also *Archeology; Art and artware; Bodies, ceramic; Design; Dinnerware; Earthenware; Stoneware; Whiteware*.
Pottery *(continued)*
α-quartz-cristobalite SiO_2 for, P (8) 198*h*.
collector's handbook, B (7) 184*f*.
decoration. See *Decoration*.
early American folk, B (11) 283*i*.
firing in medieval kiln, (4) 77*j*.
firing, supports for, P (11) 272*g*.
Gien, in France, (9) 213*h*.
Gladstone, restoration, (9) 213*h*.
historic, (1) 2*b*.
kiln firing, (1) 10*d*.
teaching, B (1) 28*c*.
ware, dispensing from extruder, P (1) 10*d*.
Pottery industry, Indian, firing problems, (11) 272*j*.
production methods, (1) 10*h*.
in Soviet Union, (8) 198*f*.
Potterymaking apparatus and equipment. See also *Dryers; Kiln furniture; Kilns; Materials handling; Molds*.
wheel, with variable speed drive, P (1) 17*a*.
wheels, P (8) 198*g*.
Powder metallurgy, metallurgy, B (10) 264*j*.
Powders. See also *Granular materials;* and specific types.
bags, apparatus for opening, P (9) 229*f*.
bodies, isostatic compression, P (2) 44*c*.
classifier, P (9) 230*b*.
compacts of uniform porosity, P (7) 172*i*.
compression and deaeration, P (4) 92*h*.
extra-fine, pneumatic mill for, P (1) 17*c*.
feeding to die of press, P (7) 172*c*.
flame spray, with Al_2O_3, P (1) 3*b*.
flow, testing and regulating, P (1) 18*d*.
fluidizing and drying, P (2) 43*i*.
gravimetric separation, P (8) 207*e*.
impact flowmeter for, P (2) 45*a*.
Li ferrite, P (1) 13*e*.
magnetic, conveyance for, P (4) 92*e*.
magnetically anisotropic, densifying, P (2) 41*b*.
making rods or tubes from, P (1) 17*b*.
mass, solution, P (11) 277*g*.
metal, for magnetic recording, P (1) 13*e*.
magnetically stable, P (4) 89*h*.
use in continuous cleaning coatings, (6) 131*b*.
and mill for grinding, P (10) 254*g*.
oxide, hydrothermal preparation, (4) 97*a*.
packing process, (6) 141*f*.
pelletizing by vibration, P (7) 172*a*.
permanent magnetic, stabilizing, P (2) 41*b*.
plasma spray, P (6) 131*c*.
preheating, P (3) 54*d*.
pressing, compaction in, (10) 254*e*.
processing equipment, (6) 141*f*.
properties, of $Mg(OH)_2$, (1) 21*i*.
solid, dielectric study, (7) 174*g*.
specific mass, (3) 70*a*.
specific surface, measuring, P (6) 142*f*; (9) 230*f*.
technology, research, (6) 141*g*.
thermal treatment, P (4) 95*a*.
ultrafine mixed metallic-oxide, P (10) 257*b*.
Power. See also *Energy*.
consumption in solid-liquid slurries, (2) 43*i*.
control, for crystal growing, P (3) 66*i*.
piezoelectric supply, P (3) 66*e*.
Pozzolans. See *Cements; Mortars*.
Praseodymium, chloride, vapor pressure, (8) 210*b*.
phosphates and hydrogen phosphates, (8) 211*i*.
phosphates, X-ray study, (8) 211*i*.
$PrAlO_3$, phase transitions in, (6) 152*b*.
Precipitates, amorphous, glass transition in, (3) 56*h*.
Ti-containing, in abrasives, (3) 53*e*.
Precipitation, continuous, of Al_2O_3 hydrate, P (1) 20*b*.
cryo-c[illegible], preparation of metallic-oxide powders, P (10) 257*b*.
in crystalline ceramics, (7) 179*e*.
electro-, P (1) 16*h*.
epitactic, of semiconductor material, P (9) 225*b*.
epitactic, of Si, P (8) 201*f*.
He, in BeO, (7) 171*d*.
of solid sulfides and liquid oxysulfides, (6) 152*e*.
Precipitators, automatic SCR control, P (6) 141*d*.
electrical dust, nomogram for, (9) 229*j*.
electrostatic, cleaning control, P (1) 16*g*.
electrostatic, pneumatic rapper for, P (1) 17*a*.
Presses, band filter, P (1) 16*j*.
components, charging systems, (7) 171*a*.
extrusion, P (9) 230*b*.
feeding powdered material to, P (7) 172*c*.
filter, P (2) 44*b*; P (3) 69*e*; P (4) 92*d*; P (6) 141*e*; P (9) 230*c*.
cavity, sealing, P (4) 92*c*.
with cleaning apparatus, P (3) 69*f*.
element for, P (7) 172*c*.
plate shifter and scraper for, P (5) 115*i*.
plates, P (8) 198*e*; P (9) 230*b*.
releasing filter cake in, P (9) 229*j*.
shaking filter cake in, P (3) 69*c*.
high-pressure torsion, P (4) 77*f*.
HP 350, running, (7) 172*g*.
impact spindle, pressure measurement, (5) 115*h*.
isostatic, P (3) 69*a*.
isostatic, yoke-type, P (7) 172*i*.
multiarticle, P (2) 44*a*.
platen locking device in, P (4) 92*f*.

Presses *(continued)*
powder, compacting, P (9) 223*d*; P (11) 277*a*.
compacting, punch for, P (11) 277*g*.
compacts of uniform porosity, P (7) 172*i*.
filling die, P (1) 17*a*.
hole-forming attachment for, P (3) 62*b*.
material forming, device in, P (9) 229*h*.
rotary, P (10) 254*i*.
for spectrographic sample, P (11) 278*g*.
Pressing, axially symmetric compacts, (10) 247*c*.
cold-, metal-carbide mixtures, (10) 246*f*.
cold, of metal-glass materials, (10) 243*c*.
dry-, ceramic tile, P (9) 223*c*.
glass, (3) 56*a*.
glass articles, (8) 190*b*.
hot-, of Al_2O_3 gel and boehmite, (1) 22*e*.
Al_2O_3 with Mo-dispersed phase, (1) 21*h*.
apparatus for, P (1) 16*j*.
densification during, (5) 121*h*.
densification and homogeneity in, (1) 16*h*.
in graphite dies, ceramic TiO_2, (1) 11*h*.
laboratory installation, (10) 255*e*.
for high strength cement pastes, (8) 188*a*.
$LiAl_5O_8$, (4) 97*a*.
monocalcium silicate, in, (2) 48*h*.
Ni-Zn ferrites, (3) 63*a*.
of K-Na niobate, (9) 223*g*.
preparation of MgO transparent bodies, (11) 282*f*.
problems, solutions to, (9) 229*d*.
for producing TiO, composition, P (5) 114*d*.
ZrB_2-$MoSi_2$ mixtures, (2) 48*f*.
hydrostatic, of washbasins, (8) 197*j*.
isostatic, hot, P (3) 69*a*.
hot, of BeO, (9) 236*c*.
of powder bodies, P (2) 44*c*.
by Quintus process, (5) 115*e*.
of refractories, (6) 135*a*.
for sanitary ware, (4) 85*g*.
roof tile, mechanical methods, (4) 83*i*.
stiff-mud vs wet, (5) 115*j*.
warm-, method for stacked fuel plates, P (9) 229*b*.
workpieces from finely divided materials, P (9) 221*c*.
Pressure, calcintering, P (10) 254*g*.
chamber for treating material, P (2) 44*c*.
decrease, in gases in fixed beds, (2) 44*f*.
dependence of dissociative diffusion, (7) 176*h*.
dependence of elastic moduli of glasses, (8) 191*d*.
effect, on elastic constants of $SrTiO_3$, (4) 98*b*.
on glass fatigue, (1) 3*d*.
on Néel temp. of CoO, (5) 120*d*.
on Néel temp. of magnetite, (6) 146*j*.
on slip casting, (6) 134*f*.
on transition of $Pb(Zn_{1/3}Nb_{2/3})O_3$, (3) 72*i*.
forming, effect on Sr ferrite, (8) 199*d*.
high, apparatus, P (2) 44*b*; P (10) 254*d*.
device, for diamond synthesis, P (5) 115*g*.
dynamic, treating solids with, P (9) 213*e*.
effect on chemical reactions, (4) 95*j*.
effects on glass, (3) 56*j*.
high-temp. techniques, B (7) 184*i*.
$PbZrS_3$ synthesis at, (3) 63*j*.
in materials research, (10) 260*c*.
hydrostatic, dependence of electronic properties of VO_2, (6) 148*e*.
hydrostatic, measurement of specific mass, (3) 70*a*.
losses in tunnel kilns, (10) 256*f*.
low, measurement in float glass, (3) 56*c*.
measurements by ruby luminescence, (8) 205*j*.
for metal-semiconductor transition in V_2O_3, (6) 145*g*.
meter, grout expansion, P (10) 255*j*.
on presses, measurement, (5) 115*h*.
in pressing symmetric compacts, (10) 247*c*.
-sintering, of Al_2O_3, (1) 24*d*.
super-, apparatus, temp. and piston stroke in, P (3) 69*e*.
-temp. apparatus, ultrahigh, P (6) 141*h*.
vacuum or fluid, forming sheet material, P (8) 204*c*.
vapor. See *Vapor pressure.*
vessels, glass-filament-wound, (5) 106*f*.
Printing, on glass using epoxy resin ink, P (1) 5*b*.
Promethium, Pm_2O_3, polymorphic modifications, (9) 228*i*.
Protactinium, (V) oxide, hydrated, (6) 148*d*.
Protons, behavior in oxide glasses, (9) 216*b*.
dynamics in KH_2PO_4 ferroelectrics, (5) 122*j*.
incident, 28.5-GeV, on BeO, (6) 145*b*.
radiation, effects on MOS capacitors, (4) 86*g*.
Pug mills. See *Mills.*
Pulverizers. See *Crushing and grinding apparatus.*
Pulverizing. See *Crushing and grinding.*
Pulverulent materials. See *Powders.*
Pumps, gettering, high-vacuum, P (9) 219*f*.
liquid-ring, for gas compression, P (8) 203*j*.
particulate material, P (10) 254*f*.
sputter-ion, cathode-getter for, P (11) 270*d*.
Purification, of crystals, P (9) 230*c*.
of crystals from suspension, P (7) 170*g*.
of dolomite and magnesite hydrates, P (10) 257*j*.
of fluoboric acid by ion exchange, (7) 175*e*.
of $MgCl_2$ solutions, P (10) 257*h*.
of $KReO_4$, (7) 179*i*.
of sand, P (4) 95*a*; P (8) 207*e*.
of $TiCl_4$, P (2) 46*e*; P (4) 94*j*.
of waste gases, dust-loaded, P (10) 254*i*.
of Y, P (5) 118*c*.
Pyristor. See *Temperature, measurement.*
Pyrite, and arsenopyrite-type structures, back-bonding in, (3) 75*d*.
photoconductivity, (4) 98*e*.
Pyrolysis, of hydrocarbons, effect on C structure, (8) 196*b*.
Pyrometers; Pyrometry. See *Temperature measuring instruments.*
Pyrophyllite, for disposable ceramic dishes, P (7) 166*b*.
effect on tobermorite synthesis, (5) 117*i*.
shear strength up to 80 kbars, (3) 75*d*.
Pyroxenes, from lunar rock 12021, zoning in, (8) 108*e*.
PZT. See *Lead, zirconate titanate.*

Quality control, of ceramic stains, (3) 61*j*.
in electronic ceramics, (3) 63*e*.
in structural clay industry, (4) 83*d*.
Quarrying, basalt, Hungarian, (5) 117*h*.
Quartz. See also *Glass; Refractories; Silicon, dioxide.*
acoustic attentuation in, (6) 145*c*.
α-, photoelastic constants, (1) 24*d*.
α-, Raman spectrum, (6) 149*d*.
β, solid state reaction with CaO, (10) 259*c*.
bonding to metal, P (8) 193*b*.
calcite, and kaolinite, or dolomite, synthesis, (5) 121*a*.
carbothermal reduction, kinetics, (9) 236*c*.
in Ca silicate autoclaved materials, (5) 116*d*.
-coesite transition, reexamination, (1) 18*e*.
-coesite transition, shear effect, (7) 177*i*.
crystalline, DTA determination, (1) 17*h*.
crystals, growth pyramid on, (8) 210*d*.
structure and thermal expansion, (2) 47*h*.
vicinal growth on faces, (8) 209*c*.
effect on cement clinker burning, (4) 79*a*.
fused, light diffraction in, (5) 121*j*.
genesis, effect in porcelain firing, (8) 197*g*.
graphite crucibles in production, P (7) 162*b*.
growth, effects of grain coatings, (1) 22*f*.
holder, for wafers, P (2) 42*e*.
hydrothermal synthesis, P (1) 14*i*; P (3) 67*i*.
optical harmonic generation in, (3) 75*i*.
particles, glassy spheres from, (9) 218*c*.
piezoelectric effect in, (5) 124*h*.
processing vessel, purifying, P (6) 133*a*.
quantitative X-ray determination, (6) 142*d*.
rf sputtering, P (2) 42*c*.
structural isotypes, (1) 25*j*.
synthesis, (1) 24*j*.
synthetic, low optical loss, (8) 190*j*.
systems. See *Systems.*
transmissivity and absorption, (10) 243*b*.
Quartzite, deposit, in Quebec, (11) 279*e*.
Quenching, for strengthening Al_2O_3, (5) 111*c*.
Quicklime. See *Lime.*

Radiation, of concrete, impregnated, (4) 79*b*.
damage in CdS, (4) 96*j*.
damage in glass, EPR studies, (11) 268*d*.
-detection device, P (1) 18*f*.
detector, P (1) 14*f*.
effect on fluoroberyllate glasses, (9) 216*j*.
electromagnetic, to electrical power, P (10) 250*e*.
gamma, effects in $LiNbO_3$, (1) 11*g*.
ionizing, effect on glasses, (8) 190*c*.
on MOS diodes, surface effects, (4) 99*g*.
monitors, remote checking of, P (10) 255*i*.
nuclear, detection device, P (9) 229*a*.
radioactive, protective brick against, P (2) 37*e*.
radiometric assay of U ores, (3) 68*f*.
recombination in CdS, (5) 123*c*.
safety standards, (10) 255*b*.
-sensing device, P (1) 14*f*.
shield, applying to anode button, P (9) 219*j*.
target structure, for cooling glass, P (6) 133*f*.
thermal, of dielectric materials, (6) 134*j*.
thermal, measurement by calorimeter, (10) 255*a*.
ultrasonic, of kaolin suspensions, (6) 146*a*.
Radioactive materials. See *Isotopes; Wastes.*
Radioactive tracers. See also *Isotopes.*
to investigate semiconductor surface, (11) 274*a*.
Radioactivity. See also *Isotopes.*
heat source, P (10) 254*b*.
materials, filtration, P (6) 141*f*.
Radiography, of rock slabs, voltage and film choice in, (8) 204*i*.
Radioisotopes. See *Isotopes.*
Radomes, P (3) 59*e*.
Radons, oxidized solutions, P (8) 203*d*.
Raman effect, in CdS, (6) 150*i*.
in wurtzite-type crystals, (5) 120*i*.
Rare earths (lanthanons). See also specific types.
ceramics, ZrO_2-, HfO_2-, ThO_2-, P (5) 111*f*.
elements, for reducing nozzle deposits, P (3) 61*g*.
fluorides, P (2) 46*d*.
flux growth, P (9) 232*g*.
single crystals, P (6) 139*d*.
fluorocarbonate, ores, P (3) 71*d*.
intermetallic compounds, P (3) 67*f*.
iodates, thermal stability, (8) 211*a*.
ions, in CaF_2, absorption spectra, (6) 145*c*.
lanthanide, separating Y from, P (2) 46*f*.
metals, hexaborides, electrical properties, (10) 259*b*.
hexaborides, properties, (10) 259*c*.
orthovanadates, P (9) 233*b*.
sulfofluorides, crystallochemistry, (10) 258*i*.
orthochromites, absorption spectra, (3) 73*g*.
oxides, effect on stress buildup in glass, (3) 55*e*.
with inert layer on, P (3) 67*f*.
Rare earths (lanthanons), oxides *(continued)*
particle size, increasing, P (4) 90*g*.
phosphate-coated, P (1) 14*c*.
reaction with Na oxide, (1) 24*e*.
oxychlorides, reaction with chlorides, (5) 123*g*.
recovery by leaching, P (6) 144*g*.
separation, effect of crystallochemical factors, (1) 21*i*.
by electrolysis, P (2) 46*i*.
by ion exchange, P (2) 46*h*.
systems. See *Systems.*
trifluorides, high temp. enthalpy, (8) 211*c*.
tungstate ceramics, refractory, (7) 180*e*.
tungstates, normal, P (7) 170*f*.
Ray materials. See *Cement; Materials; Sands; Rocks.*
Reactors, breeder, measurements in, P (11) 276*c*.
continuous hydrothermal, for slurries, P (1) 20*b*.
epitaxial deposition, P (3) 64*j*.
fast breeder, P (8) 203*f*.
cooling core fragments in, P (10) 253*j*.
fuel assembly for, P (10) 253*h*.
glass-lined, for corrosive service, (11) 267*d*.
neutronic, using ^{240}Pu fuel, P (9) 228*h*.
nuclear, burnable poison for, P (8) 203*f*.
core blocks for, P (10) 254*b*.
core plug for, P (9) 228*g*.
core structures for, P (4) 92*a*.
fuel element for, P (11) 276*c*.
fuel subassembly for, P (3) 68*i*; P (8) 203*c*.
graphite moderators for, P (1) 16*c*.
high-temp., fuels for, (11) 276*b*.
operation, P (11) 276*d*.
porous metal bodies for, P (7) 171*f*.
safety apparatus for, P (4) 92*a*.
shroud for fuel assembly in, P (8) 203*f*.
spring ferrule spacer grid, P (9) 229*b*.
thermionic, core for, P (11) 276*e*.
use of Bi_2O_3 in, (7) 171*a*.
vapor suppressing means for, P (9) 229*b*.
reaction space, heating, P (8) 206*f*.
Reagents. See specific types.
Recrystallization. See *Crystallization.*
Rectifiers, controlled, and triac, P (10) 250*e*.
Schottky barrier power, P (7) 170*i*.
semiconductor, P (10) 252*j*.
assemblies, P (11) 275*h*.
controlled, P (6) 140*b*; P (9) 227*d*.
Recuperators. See *Furnaces; Kilns; Refractories.*
Reduction, -fusion process for rare earth compounds, P (3) 67*f*.
Reflectance. See *Reflection.*
Reflection, anti-, coatings, P (1) 3*c*.
of As_2S_3, vitreous, (8) 191*f*.
electro-, study of NiO, (6) 147*e*.
of EuO, splittings in, (6) 151*j*.
optical, study of magnetic ordering effects in Eu compounds, (9) 237*g*.
Reflectivity. See *Reflection.*
Reflectors, AGA and laser, (7) 158*b*.
durable first surface, P (1) 3*j*.
glass laser coupling, P (3) 65*c*.
Refraction, birefringence, in Pb glasses, (2) 32*f*.
Refractive index, in clad fibers, (8) 190*d*.
of crystals beryl, CdS, ZnS, and ZnO, (5) 122*g*.
differential dispersion measurement, (9) 231*a*.
in glass light-guide element, P (6) 133*g*.
of glasses, (1) 3*h*.
effect of temp., (10) 243*d*.
optical, thermal coeff., (1) 3*j*.
oxide, (10) 242*j*.
of optical materials, (8) 191*d*.
of SiC, *β*-, (1) 25*a*.
of SiO_2, fused, (1) 3*h*.
Refractivity. See *Refraction.*
Refractories. See also *Aircraft ceramics; Insulation, thermal; Kiln furniture; Silicon, carbide.*
(2) 36*d*.
acid-resistant and wall-lining, from bauxite, (5) 109*j*.
Al_2O_3, P (7) 164*a*.
in arc-furnace roofs, (1) 6*i*.
deformation properties, (8) 195*g*.
effect of fuel oil on strength, (1) 7*e*.
high-, P (5) 109*h*.
high-, composition, P (2) 37*g*.
high-, Israeli, (9) 221*f*.
high-, mechanical properties, (2) 36*g*.
high-, performance, (2) 36*c*.
phase chemical analysis, (8) 195*b*.
aluminosilica, slag attack, (1) 6*j*.
aluminosilicate, glass resistance, (8) 195*d*.
spalling, kinetics, (1) 271*j*.
thermal conductivity, (8) 196*e*.
aluminous, fast firing, (2) 36*h*.
Al polyoxychloride bonded castable, P (4) 84*f*.
for NH_3 equipment, (2) 36*f*.
anorthite insulating, (8) 194*j*.
for arc furnace steelmaking, (2) 36*d*.
asbestos panels, P (9) 222*j*.
ASTM standards, B (10) 262*c*.
attack by oxides of Na, S, and V, (1) 8*a*.
baddeleyite-corundum, surface changes, (8) 196*d*.
Bakor, for high-temp. glassmelting, (8) 195*e*.
basic. See also *Refractories, chrome-magnesite;* specific kinds.
P (5) 109*f*; P (9) 222*b*.
ceramically bonded, P (4) 84*h*.
fused cast, P (3) 61*f*.
high-temp. creep, (11) 271*i*.
material, P (11) 272*e*.
for mixer lining, (2) 35*i*.
performance, (2) 36*c*.

Refractories, basic *(continued)*
phase equilibria of performance, (1) 8*b*.
in regenerators, V_2O_5 attack, (10) 247*a*.
shapes, P (4) 84*g*.
use in steel production, P (5) 108*h*.
basic bricks, corrosion, (3) 60*h*.
in degassing furnaces, (5) 108*g*.
detecting crystalline plasticity of periclase grains in, (1) 18*h*.
mechanical properties, (1) 7*b*; (2) 36*d*.
unburned, P (2) 37*f*.
BOF, oxidation-reduction reactions in, (2) 36*g*.
BOF, periclase and C microstructure in, (8) 195*a*.
batch, P (2) 37*b*.
batches, grain-size composition, (8) 196*a*.
bauxite, corrosion, (1) 6*j*.
bed, for gas machine, P (1) 9*b*.
behavior at high temps., in vacuum, (5) 108*j*.
binders for use in, P (8) 196*h*.
blast-furnace, linings. See *Refractories, linings*.
blast furnace, trends in, (2) 37*a*.
bloating type, (11) 271*e*.
block furnace wall, P (7) 162*j*.
bodies, electrically conductive, P (1) 12*j*.
body, P (8) 196*j*.
bonded with aluminides, nickelides, or titanides, P (10) 248*b*.
brick. See also *acid*, *basic* and specific types under *Refractories*.
Al_2O_3, high-, MURAL series, (2) 36*i*.
bottom, for ingot molds, P (11) 272*b*.
from calcined dolomite, P (11) 272*a*.
hanging, P (7) 164*e*.
molded flue, P (11) 272*c*.
with oblique surface, P (4) 85*a*.
protective against radioactive radiations, P (2) 37*e*.
sand-lime, P (10) 248*c*.
setting machine for kiln car, (7) 163*f*.
or slag, accretion or removal, (6) 134*e*.
tar-bonded, tempering, P (10) 248*c*.
in vacuum metallurgy, (5) 109*f*.
briquet, kaolin, strength, (8) 195*c*.
carbide particles, recovery, P (4) 84*j*.
carbides, thermodynamic properties, (8) 209*a*.
carbides, thermodynamics, (10) 261*c*.
carbonaceous products, P (11) 272*a*.
cast, in Europe and U.S., comparison, (5) 109*e*.
products, upgraded, P (9) 222*j*.
stone, properties, (8) 195*c*.
castable, pumping transportation for, (2) 36*c*.
cement. See also *Refractories, blast-furnace*.
composition, P (8) 197*b*.
new, (3) 60*f*.
-ceramic composition, P (1) 9*c*.
Ceranox materials, (9) 221*e*.
chamotte, cordierite, (1) 8*f*.
dinas, and siliceous, resistance to open hearth slags, (8) 195*g*.
reaction with $H_2(HPO_3)$, (8) 196*c*.
chemical behavior with molten steels, (5) 109*a*.
chimney, metal, with ceramic lining, P (4) 84*c*.
chrome-MgO, mechanical properties, (1) 7*d*.
chrome and MgO, analysis, (9) 221*c*.
chrome-magnesite. See also *Refractories, magnesite-chromite*.
chrome-magnesite, microstructure, (11) 271*d*.
chrome materials, analysis, (11) 278*i*.
chrome ore, sampling technique, (1) 18*f*.
chromite, ores, solid-state reduction, (6) 151*g*.
in periclase-chrome brick, (8) 194*j*.
quality, effect of dressing ores, (9) 221*j*.
recovery from molding sands, (1) 8*f*.
clays. See *Clays*.
closure, for bottom-pour vessels, P (3) 61*d*.
coatings. See *Coatings*.
compositions, based on aluminophosphate binder, (8) 195*c*.
compositions containing C, P (6) 135*f*.
compounds, chemical properties and analysis, B (10) 262*e*.
powders, grain geometry and strength, (10) 259*j*.
surface energy, (10) 259*e*.
concrete. See *Concrete*.
construction units, P (2) 37*e*.
converter, with "hard" tars, (8) 194*j*.
corrosion resistance, (8) 195*a*.
corundum, properties, (8) 195*d*.
crucible, electrically resistive, P (4) 84*j*.
graphite, in quartz production, P (7) 162*b*.
by isostatic compaction, (11) 271*g*.
of mullite, corrosion resistance, (5) 109*b*.
in degassing steel, large scale, (2) 36*e*.
in DH vacuum vessels, (5) 108*h*.
diborides, engineering materials, (3) 60*i*.
die and model compositions, P (3) 61*c*.
dimensions, testing after-variations, (2) 36*j*.
dressing method, P (10) 248*b*.
in electric arc furnaces, (2) 36*a*.
electrical, breakdown strength, (7) 164*j*.
electrocast. See *Refractories, fused cast*.
electrofused, Al_2O_3-ZrO_2-SiO_2, (4) 84*c*.
elements for glass float furnace wall, P (9) 222*f*.
feeders, for steel jet casting, (2) 35*j*.
fibrous material, extrudable, P (9) 222*d*.
firebrick, Al_2O_3, after-variations in, (2) 36*j*.
mechanical strength, (2) 36*c*.
template for marking, P (8) 197*a*.
fireclay, articles, P (8) 196*i*.
masses, structure, (2) 50*b*.

Refractories, fireclay *(continued)*
performance, (2) 36*c*.
service at high temps., (5) 109*g*.
structure and deformation, (11) 271*g*.
foam structure, P (3) 61*g*.
fused-cast, corrosion in glass tanks, (8) 191*g*.
fused-cast, improving with N gas, P (9) 222*i*.
for gas-metallurgy and Gazal process, (2) 36*f*.
in glass furnaces, effect of fuel, (1) 6*f*.
grid, P (3) 61*e*.
guncrete coatings on, (8) 195*f*.
hanging bosh construction, P (11) 272*c*.
hearth, in float glass furnace, P (8) 196*f*.
heat accumulating ceramic materials, (6) 134*i*.
heat-insulating composite products, P (7) 164*f*.
hollow body, P (7) 164*f*.
hot strength, effect of furnace atm, (1) 7*h*.
hot tops, P (10) 247*i*.
bottom rings, P (6) 135*d*.
exothermic, P (3) 61*d*.
liner and ring in metal casing, P (8) 196*b*.
surface, retaining heat, P (2) 37*c*.
hydraulic setting composition, P (10) 248*c*.
for ignition furnace of sintering plant, (1) 8*d*.
imaging in electron microscope, (8) 205*b*.
impregnated article, P (10) 247*i*.
insulating. See also *Refractories, firebrick*.
carbonized felt, P (1) 9*a*.
low-density, P (6) 135*a*.
panels, preassembled, P (1) 9*d*.
insulation block, high-temp., P (11) 272*d*.
for iron and steel industry, (6) 134*g*.
for kiln furniture. See *Kiln furniture*.
ladle, bottom pour, closure for, P (10) 247*f*.
brick, new plant production, (2) 36*j*.
brick, testing in USSR, (8) 196*d*.
bricks, P (11) 272*e*.
lining, P (1) 9*a*; P (5) 109*i*.
valve, Mitsubishi-Metacon, (2) 36*f*.
lining, for blast furnaces, P (9) 222*i*.
brick, P (7) 164*d*.
burner, for steam boiler, (8) 194*g*.
concrete, installation, (3) 60*j*.
concrete, installing and drying, (4) 84*b*.
converter, (2) 36*g*.
cryolitic, for Al smelting, P (9) 222*c*.
for hot-blast stoves, P (7) 164*f*.
hot-face, Al_2O_3-SiO_2 fiber for, (8) 194*j*.
induction furnace, (10) 246*i*.
for ingot and foundry molds, P (8) 196*c*.
of Kaldo vessels, (1) 7*i*.
of metallurgical furnace, treating, P (8) 196*e*.
oven, P (7) 164*a*.
of O converters, (8) 195*f*.
reinforcing metals for, (7) 163*g*.
review, (10) 247*g*.
in rotary cement kiln, (8) 187*g*.
rotary kiln, of resin, (7) 174*h*.
for shaft or stack furnace, P (10) 248*d*.
skull removal from, P (10) 248*e*.
of steelmaking vessel, temp., P (9) 231*h*.
wear, increased, (9) 214*b*.
wear in vacuum vessels, (5) 109*c*.
magnesia, brick, fired, P (7) 164*e*; P (10) 248*b*.
-CaO, corrosion by slag, (7) 163*h*.
-chrome, mechanical properties, (1) 7*b*.
clinker, bricks of, (1) 6*i*.
-containing products, P (3) 61*e*.
high-density, P (9) 222*c*.
insulation for heating elements, P (3) 61*f*.
magnesite. See also *Refractories, chrome-magnesite*.
B_2O_3 effect, (1) 7*f*.
creep properties, (1) 7*f*.
-chrome brick, P (2) 37*b*.
-chromite, phase composition, (8) 195*b*.
effect of fuel oil on strength, (1) 7*e*.
furnace hearth, P (4) 84*i*.
materials, P (10) 247*j*.
periclase and silicate phases, (1) 6*g*.
phase relations in, (2) 48*e*.
thermal cycling resistance, (1) 6*g*.
masses, P (11) 272*g*.
materials, P (6) 143*c*.
brazing, P (10) 248*a*.
heat resisting metallic, (3) 60*j*.
highly gas-permeable, P (3) 61*a*.
for MHD power generation, (3) 63*e*.
new, (3) 60*g*.
nonshaped, use, (4) 84*d*.
projecting against BOF lining, P (8) 196*e*.
recommendations, (7) 163*h*.
SiO_2, P (3) 61*e*.
testing, (7) 173*f*.
meet heavy demands, (2) 36*e*.
metals, iodides, anhydrous, P (3) 67*b*.
carbides, deposition, (10) 258*d*.
compatibility with Sc_2O_3, (10) 246*i*.
and compounds, reaction with B carbonitride, (10) 261*a*.
powders, diffusion with C and B, (1) 7*d*.
reaction with nitrides, (2) 49*f*.
reaction with SiO_2 melt, (7) 163*g*.
/refractory metal nitride resistor films, P (7) 164*f*.
in microwave furnace, for use in lost wax process, (1) 8*a*.
molded shapes, semimechanized process, (4) 84*a*.
molds. See *Molds*.
mortar, P (6) 135*g*.
mullite-bonded, P (2) 37*d*.
mullite grain, P (4) 109*i*.
nitride bodies, securing to steel, P (9) 222*a*.

Refractories *(continued)*
nitride-oxide, P (7) 164*i*.
nozzle, atomizing, for oil burners, P (9) 232*c*.
deposits, reduction, P (3) 61*g*.
for pouring ladle, P (7) 164*a*.
repairing, P (2) 31*j*.
sliding, (1) 8*e*.
submerged, casting, P (10) 248*a*.
oxide, crystals, by floating zone, (7) 179*e*.
fibrous, P (11) 272*e*.
with granular structure, (8) 195*c*.
organic-, material, P (7) 170*h*.
reactions with C, (6) 142*f*.
sintering, (5) 123*h*.
periclase-spinelide, microstructure, (7) 163*g*.
perlite-chamotte products, (8) 195*c*.
permeable, P (3) 61*b*.
plastic, conditions for using, (1) 6*h*.
soaking pit of, (1) 8*a*.
for soaking pit walls, (1) 8*d*.
plug, gas-permeable, P (2) 37*f*.
plugs and nozzles for ladles, (8) 195*c*.
polymer-bonded, testing data, (4) 83*j*.
porous cellular bodies, P (9) 222*g*.
pouring spout, P (10) 248*b*.
problems, solving in refineries, (10) 247*j*.
processes, silicate binder for, P (11) 272*d*.
protective member, P (6) 135*e*.
ramming bodies for soaking pits, (8) 195*d*.
ramming mixes, P (3) 61*d*.
rare-earth tungstate ceramics, (7) 180*e*.
raw materials, X-ray fluorescence analysis, (8) 205*i*.
reactions with alkali salts, (6) 134*f*.
recuperators, ceramic, P (2) 37*e*.
refractometric properties of silicates, (9) 238*f*.
refractoriness under load, effect of shape and size, (6) 134*j*.
refractoriness-under-load test, (1) 8*h*.
for regenerators, blast furnace, (6) 134*g*.
gas turbine, P (1) 8*j*; (2) 36*a*.
gas turbine ceramic, P (10) 247*h*.
thermal, P (10) 248*e*.
V_2O_5 attack, (4) 84*e*; (10) 247*a*.
roof, for high-temp. furnaces, P (11) 279*d*.
roof, modular panel, prefabricated, P (9) 232*b*.
shape, impregnated fired, P (9) 222*h*.
shaped bodies cast in molten state, P (7) 164*g*.
shaping by isostatic pressing, (6) 135*a*.
shapes, high-density, P (7) 164*e*.
SiO_2 brick, P (9) 222*g*; P (11) 272*f*.
SiO_2, fused, changes during heating, (1) 7*b*.
silicide coatings, vapor phase deposition, P (8) 197*b*.
sillimanite, service at high temps., (5) 109*g*.
sintered articles, P (3) 61*e*.
slabs, heat-insulating, P (7) 164*e*.
slag. See *Slags*.
sleeve brick, spalling tests, (1) 7*a*,*b*; 8*b*.
sleeve brick, thermal fracture, (1) 8*e*.
for Na silicate melting furnace, (7) 163*j*.
spout, graphite, P (4) 84*c*.
for steel casting, (6) 134*h*.
steel plant, in Japan, (1) 8*c*.
steel plant, in seventies, (8) 196*b*.
stopper plug valve for ladles, P (7) 164*g*.
stopper rod, removing and reinserting, P (4) 84*b*.
structure for combustion shaft, P (8) 197*b*.
tar-dolomite bricks, behavior, (6) 134*i*.
tar-dolomite plant in Romania, (2) 36*a*.
technology, physicochemical systems, (8) 194*g*.
thermal conductivity, (1) 8*j*.
laboratory tests, (7) 172*j*.
rapid determination, (1) 8*e*.
test, (2) 44*g*.
thermal shock resistance, (8) 204*d*.
W boride-containing articles, P (9) 222*j*.
tuyere block, radial interlocking, P (5) 110*c*.
unshaped, for furnace construction, (1) 6*f*.
unshaped, for furnace and soaking pit, (1) 7*h*.
wall, P (1) 9*d*.
in glass tank, P (7) 164*e*.
for open-hearth furnaces, P (9) 222*f*.
wear by molten metals, testing, (7) 173*e*.
Zr in, photometric determination, (8) 195*a*.
ZrO_2, P (3) 61*b*.
-Al_2O_3-SiO_2 fusion-cast, P (4) 85*b*.
storage heater, creep, (3) 60*d*.
Refractories industry, A. P. Green, planning center, (2) 36*b*.
J. Gimson & Co., production techniques, (1) 10*d*.
Kaiser, research in new lab, (9) 221*g*.
mechanization and automation, (8) 195*j*.
raw materials base, (8) 196*a*.
technical trends in, (2) 36*d*.
Regenerators. See *Refractories*.
Relaxation, anelastic, in crystalline solids, B (10) 262*h*.
anelastic and dielectric, study of defect reactions in crystals by, (7) 181*h*.
dielectric, in alkaline-earth fluoride crystals, (5) 119*j*.
electrical, in Na_2O·$3SiO_2$ glass, (11) 268*c*.
in glasses of rigid molecules, (7) 161*d*.
of Fe in MgO, (5) 122*g*.
of magnons in ferromagnets, (6) 151*c*.
mechanical, and alkali mobility in silicate glasses, (5) 106*g*.
of glasses, (2) 32*d*.
and ionic, in Na_2O·$3SiO_2$ glass, (11) 269*a*.
phenomena, of glass, (3) 57*c*.
process in ESR of VO_2, (3) 74*j*.
proton, in $UO_{2+x}H_2O$, (6) 151*h*.

Relaxation *(continued)*
step perturbation, techniques, (4) 93*d*.
structural, in glass, (1) 3*f*.
times, in aluminosilicate glasses, (2) 33*c*.
of H_2O-cement system, (3) 54*b*.
Replica method. See *Microscopy.*
Research, ARPA-NBS, on high temp. and laser materials, (3) 70*j*.
ceramic, 5 years in Europe, (7) 182*e*.
materials, pressure variable in, (10) 260*c*.
NRDC projects for 1970-71, (4) 100*a*.
ovonic, (6) 136*g*.
on powder technology, (6) 141*g*.
project management in, (4) 100*a*.
Resins, cationic, for coating frit, P (4) 80*b*.
epoxy, as filler for grinding mills, P (1) 16*h*.
epoxy, impregnating rock with, (3) 70*e*.
and glass fiber coatings, P (3) 59*e*.
organic, and vitreous laminates, P (3) 60*a*.
pitch-powder granule system, molded, P (9) 222*d*.
for rotary kiln lining, (7) 174*h*.
Resistance, electrical. See also *Conductivity, electrical; Electrical properties.*
capacitance structure, discrete, P (1) 13*c*.
composition, P (5) 112*i*.
electro-, of high-melting compounds, (10) 261*b*.
elements, P (5) 110*c;* P (7) 168*f*.
elements, $MoSi_2$, P (1) 13*j*.
of glassmelting furnaces, (9) 217*f*.
of glass tank furnaces, (8) 190*f*.
of high-melting compounds, (10) 258*i*.
in $La_{0.002}Ba_{0.998}TiO_3$-$Bi_2O_3$ composite ceramics, (3) 76*b*.
of PZT ceramics with impurities, (3) 62*g*.
of liquid S and liquid Se, (3) 62*g*.
magneto-, of EuS, (3) 76*a*.
negative, effects in Ti_2O_3, (5) 122*g*.
in soft carbons, (3) 73*i*.
material, P (4) 87*d*.
and elements from, P (3) 67*g*.
of SiC particles and binder, P (1) 14*g*.
measurements on Ta microcircuits, (8) 205*c*.
nonohmic properties of ZnO ceramics, (3) 74*c*.
photo-, plasticizer additive for, P (2) 42*a*.
positive temp. coeff., of $BaTiO_3$, (3) 63*d*.
of TiC at high temps., (8) 199*f*.
of zircon ceramics, relation to porosity, (8) 199*i*.
Resistivity, of anisotropic materials, (5) 116*a*.
anomaly in semiconducting $BaTiO_3$ (3) 75*a*.
constant, graphite with, P (6) 139*c*.
of dielectric substrates, modifying, P (5) 113*j*.
as function of concentration and stereometry, (8) 199*a*.
low-temp., size effect, (5) 116*f*.
measurement, (5) 116*c*.
measurements on Ge crystals, (3) 63*f*.
of resistors, adjusting, P (8) 201*i*.
in semiconductors, determination, P (4) 87*d*.
of WC, (6) 149*j*.
of $YBaZrTiO_3$, (3) 63*e*.
Resistors, electrical, P (3) 67*e;* P (6) 138*j*.
bodies, P (10) 252*c*.
bulk, and circuit using, P (3) 64*i*.
cermet, vapor-plated, P (9) 228*c*.
Cr-SiO film, P (7) 168*j*.
composition, P (5) 114*b*.
with oxides and Pt, P (4) 90*j*.
and pastes, P (10) 252*d*.
electric ceramic $BaTiO_3$, P (10) 250*i*.
electroconductive coating, P (2) 41*d*.
enamel, P (6) 131*f*.
of Eu_2O_3, EuS, and EuSe, P (7) 168*i*.
film, P (8) 201*c*.
film, specifications, (1) 11*a*.
fused-substrate, P (3) 65*a*.
glazes, Ru-based oxides in, (4) 86*d*.
HfN, P (6) 140*a*.
with heat-dissipating means, P (4) 86*b*.
hermetically sealed, P (5) 112*g*.
hybrid element variable, P (1) 12*f*.
ignition circuit radiation suppression, P (10) 250*h*.
for integrated circuit, P (4) 90*j*.
integrated diffused emitter ballast, P (3) 66*f*.
with Pb ruthenate, P (11) 274*f*.
metal oxide film, P (4) 89*b*.
metallic film, P (1) 12*j*.
microelectronic, electronic trimming, P (3) 64*i*.
microelectronic, trimming, P (10) 250*b*.
molded C composition, P (10) 251*f*.
negative, P (10) 252*f*.
negative-temp.-coeff., P (3) 66*d*.
nonlinear, bulk type, P (8) 201*j*.
nonlinear, and composition, P (8) 201*j*.
oxide materials, P (10) 252*g*.
planar, thin-film, P (6) 133*i*.
with Pt Co oxides, P (4) 87*d*.
refractory metal carbide thin-film, P (9) 226*b*.
SCR, with amplified gate, P (3) 67*h*.
SCR, peripheral gate, P (3) 66*e*.
semiconductor, P (4) 90*f*.
semiconductor, with impurities, P (11) 275*j*.
with semiconductor overlay, P (10) 250*j*.
Si, P (4) 90*g*.
sintered cold-conductor, P (5) 114*a*.
sliding thin-film, P (4) 90*i*.
TaN film, P (8) 201*h*.
TaN film, by sputtering, P (9) 226*i*.
thermistor composition, P (7) 170*f*.
compositions, P (10) 253*b*.
material for, P (9) 226*a*.
thick-film, adjusting resistivity, P (8) 201*i*.
Resistors, electrical *(continued)*
thick-film, trimmed, (3) 63*g*.
thin-film, P (4) 91*c*.
elements, P (1) 13*c*.
high resistance, P (1) 13*f*.
thyristor, P (4) 91*e*.
circuit, P (5) 114*c*.
with control device, P (9) 228*a*.
mounting devices for, P (8) 201*i*.
vertical, P (10) 253*f*.
voltage-dependent, P (9) 228*c*.
voltage-dependent, bulk type, P (11) 276*a*.
voltage variable, P (5) 114*e;* P (9) 228*d*.
ZnO_2, P (4) 90*j*.
ZnO voltage variable, P (4) 88*i*.
Resonance, acoustic paramagnetic, for detection of Al_2O_3:Fe^{2+}, (5) 119*g*.
antiferromagnetic, in CoO, (5) 121*e*.
electron-nuclear double, of defect in LiF, (6) 147*e*.
electron and nuclear magnetic, in glasses, (5) 105*j*.
EPR, in $CaMoO_4$, (7) 177*a*.
of Cu^{2+} in kaolinite, (6) 147*j*.
of Gd^{3+} in YVO_4, YPO_4, and $YAsO_4$, (5) 120*i*.
of Fe^{3+} in CaF_2, (4) 96*c*.
of irradiation of glass, (8) 190*h*.
of $PbWO_4$, (6) 147*j*.
of Mn^{2+} in Mg_2SiO_4, (6) 147*a*.
of Mn^{4+} in MgO, (5) 120*j*.
of NpO_2^{2+} in $Cs_2UO_2Cl_4$ and $CsUO_2(NO_3)_3$, (5) 120*j*.
of Ni^{2+} in MgO, (5) 120*i*.
and NDOR, of F^+ centers in BeO crystals, (6) 147*i*.
of point-defect equilibria in CaF_2, (9) 235*j*.
of radiation damage in glass, (11) 268*d*.
of vanadyl ion in glasses, (9) 217*g*.
ESR, of alkali titanate glasses, (7) 159*e*.
of Cr^{3+} in $LiNbO_3$, (5) 120*a*.
of Co^{2+} in TiO_2, (4) 96*b*.
of Gd^{3+} in La_2O_2S, (4) 96*e*.
in MgO, (5) 120*a*.
of Ni^{3+} in MgO-NiO-Li_2O (*ss*), (1) 22*c*.
of ns^1 centers in glass, (3) 55*h,j*.
in Si, Ge, and SiC, (6) 147*b*.
of Ag^+ and Cu^+ ions diffusing into glass, (3) 56*j*.
of V structure in glasses, (6) 131*j*.
of VO_2, relaxation in, (3) 74*j*.
ferromagnetic, of Mn_5Ge_3 thin films, (3) 62*i*.
magnetoelastic, in hematite, (4) 96*e*.
^{93}Nb nuclear quadrupole, of $LiNbO_3$, (7) 179*e*.
NMR, of BeO, (5) 115*a*.
^{11}B, in Ge borate glasses, (11) 267*j*.
^{11}B, of Sr borate glasses, (11) 268*a*.
of ^{133}Cs in Cs borates, (7) 159*d*.
of Cs borate glasses and crystalline compounds, (7) 160*g*.
of conduction-electron interaction in CdO, (5) 122*h*.
in $Ga_{2x}Fe_{3-2x}O_4$ and $GaNiFeO_4$, (3) 74*e*.
of ^{57}Fe in Ba ferrite, (6) 150*c*.
of glucose and penta-acetate, (3) 55*b*.
of ^{55}Mn, in MnF_2, (5) 122*c*.
of motions in fluosilicates, (4) 97*j*.
of ^{31}P in P selenides, (9) 233*g*.
optical and electron-spin, of Cr ion in ruby, (6) 150*e*.
paraelectric, of KCl:Li^+, (6) 150*f*.
paramagnetic, observation of $SrTiO_3$, (6) 150*d*.
ultrasonic electron-nuclear, of CaF_2:U^{4+}, (6) 152*h*.
ultrasonic paramagnetic, of U^{4+} in CaF_2, (5) 125*a*.
Resonators, ceramic, P (10) 250*a*.
electromechanical, P (9) 225*f*.
$LiTaO_3$, low-temp.-coeff., P (1) 12*i*.
piezoelectric, P (8) 202*b*.
ceramic, P (3) 66*g*.
ceramic ring, P (2) 42*a*.
monolithic, P (2) 41*f*.
in switching device, P (2) 42*h*.
Retardant, hydroxycarboxylic acid, interaction with cement minerals, (9) 214*e*.
Rhenium, $ReCl_5$, reaction with MoO_3, (5) 123*h*.
ReO_3, band structure and Fermi surface, (5) 118*i*.
Fermi surface, (6) 150*e*.
position life time in, (3) 74*g*.
heptoxide, properties, (1) 25*f*.
oxide, new, structure, (10) 260*f*.
trichloride, disproportionation, (8) 209*e*.
Rheology, behavior of glasses, (3) 57*d*.
of cement plaster, (9) 215*e*.
of china clay suspensions, (11) 273*c*.
of clay concrete, (9) 215*b*.
of disperse systems during vibration, (7) 180*g*.
of dispersed kaolinite suspensions, (2) 49*h*.
of hard alloy mixtures, (10) 247*h*.
of kaolinitic clay, P (10) 257*d*.
of laponite dispersions, (9) 238*g*.
Newtonian, in alkali borate glass, (3) 55*a*.
of raw-material slurries, (8) 204*h*.
Rock wool. See *Mineral wool.*
Rockets. See *Spacecraft.*
Rocks. See also *Phosphates; Silicates.*
alkaline, Kunavaram series, India, (8) 209*c*.
breaking, devices for, P (11) 277*a*.
carbonate, microporosity in, (3) 71*d*.
crushed, industry, automation in, (2) 46*a*.
dolomitized, electron microscopy, (5) 117*g*.
low-^{18}O igneous, of Scotland, (8) 206*j*.
natural, strength testing, (6) 142*h*.
natural, thermal behavior, (11) 283*a*.
porous, impregnating with resin, (3) 70*e*.
Rocks *(continued)*
sampling, P (1) 17*b;* P (2) 44*c*.
slabs, radiography, (8) 204*i*.
ultramafic, of Calif., (8) 206*j*.
Roughness. See *Surface.*
Rubidium, chlorides, reaction with YCl_3, (5) 123*i*.
dichromate, crystal structure, (6) 146*b,c*.
molybdates, double, and $RbLn(MoO_4)_2$ compounds, (8) 208*f*.
nitrates, separation by zone melting, (3) 71*e*.
$RbCrF_3$, (4) 98*g*.
RbH_2AsO_4, ^{87}Rb quadrupole coupling in, (5) 123*d*.
$RbFeF_4$, ferroelastic effect in, (11) 281*i*.
$RbMnF_3$, magnetoelastic properties, (6) 152*h*.
$RbNiCl_3$, (7) 179*e*.
silicates, polymorphism, (8) 210*e*.
systems. See *Systems.*
Ruby. See also *Garnets; Lasers; Masers.*
Cr ion pairs in, energy levels, (5) 120*b*.
Cr ion pairs in, resonance studies, (6) 150*e*.
crystals, deformation, recrystallization, strength, and fracture, (3) 72*e*.
as fluorescing and laser material, (1) 11*j*.
magnetic nuclear transition in, (6) 150*b*.
paramagnetic-response line shapes in, (6) 150*g*.
Rupture, modulus, of ceramics, factors in, (1) 17*h*.
Ruthenium, dioxide, films, (8) 200*g*.
dioxide, magnetic susceptibility, (6) 150*c*.
in glass, (10) 242*j*.
oxidation, in glasses, (2) 32*e*.
Rutile. See also *Pigments; Titanium, dioxide.*
NH_3 adsorption on, (1) 22*h*.
Co^{2+} combined with Ti^{4+} in, (4) 97*j*.
with Co^{2+} ions, ESR, (4) 96*b*.
creep at high temps., (2) 47*j*.
electron trap in, properties, (5) 122*h*.
Fe^{3+} in, spectroscopy on, (5) 120*e*.
photoelectronic processes in, (5) 122*d*.
pigments. See *Pigments.*
recovery of substructure in, (2) 49*g*.
specific heat and paramagnetic susceptibility, (5) 124*b*.
surfaces, ir studies, (3) 73*j*.
synthetic, production from ilmenite, (1) 20*h*.
thin films, dielectric, deposition, P (7) 168*j*.
electrical properties, (3) 62*f*.
heterogeneous deposition, (9) 224*i*.
Wadsley defects in, aggregation, (6) 145*a*.
X-ray line profile analysis, (11) 283*c*.

Saggers. See *Kiln furniture.*
Safety, glazing in hazardous locations, (5) 106*j*.
standards for radiation protection, (10) 255*b*.
Salts, alkali, effect on mullite and zircon corrosion, (5) 109*f*.
alkali, reactions with refractories, (6) 134*f*.
of hydroxy carbonic acid, water-reducing admixture, (6) 130*b*.
molten, capillary viscometer for, (7) 173*c*.
chemistry, advances in, B (4) 100*b*.
in systems $CdCl_2$-MCl, vapor pressure over, (8) 211*f*.
treating with H_2O vapor, P (8) 193*b*.
nitrate, Ag nitrate in, (6) 144*i*.
NaCl. See *Sodium, chloride.*
Samarium, phosphates and hydrogen phosphates, (8) 211*i*.
phosphates, X-ray study, (8) 211*i*.
Sm^{2+} fluorescence in Na borate glass, (7) 159*b*.
Sm^{2+}, in $TbPO_4$ and YPO_4, (3) 72*h*.
$SmAlO_3$, crystal structure, (8) 208*a*.
SmB_6 and metal oxides, transmission model, (6) 151*e*.
$Sm_{0.2}TbO_{0.8}FeO_3$, platelets, domain propagation in, (7) 176*i*.
systems. See *Systems.*
Samples, holder, for optical measurements, P (3) 70*g*.
nondestructive examination, P (3) 70*e*.
preparation for powder diffraction, (4) 93*h*.
Sampling, device, rotary kiln, P (2) 45*a*.
devices, atm, P (8) 206*j*.
gaseous atm, P (10) 256*a*.
hard heterogeneous materials, (1) 18*f*.
optical measuring apparatus for, P (2) 45*c*.
product, method and apparatus, P (9) 231*j*.
rock, P (2) 44*c*.
slurry flow, P (9) 231*i*.
Sandblasting. See *Blasting.*
Sands, deposits, analysis of, (1) 17*d*.
fine, quantitative determination, (10) 255*c*.
foundry, article forming machine, P (2) 37*f*.
compositions, P (6) 135*g;* P (9) 222*f*.
hardening agents for, P (9) 222*g*.
live clay content, P (1) 9*b*.
testing, P (5) 110*a*.
grains, coated, effect on quartz growth, (1) 22*f*.
Mississippi river, feldspar source, (3) 71*d*.
moist, capillary bonds in, (2) 47*e*.
mold and core, used, recovering, P (11) 272*b*.
molding, P (9) 222*e*.
dosing into box of foundry mold, P (8) 196*d*.
liquid self-hardening, P (11) 272*e*.
recovery of chromite and SiO_2 from, (1) 8*f*.
mulling or conditioning apparatus, P (9) 230*d*.
purification, P (4) 95*a;* P (8) 207*e*.
resources, of Indiana, (3) 71*f*.
SiO_2, role in steel castings, (9) 221*h*.
silicate-bonded mixtures, hardened, P (5) 110*a*.
titaniferous beach, beneficiating, P (10) 257*c*.
Sandstones, cementation and lithification, (8) 210*f*.
clay-mineral diagenesis within, (8) 208*d*.

Sandstones *(continued)*
permeability increase, (7) 175*g*.
thermal formation factor, (3) 71*g*.
Sanidine. See *Feldspar*.
Sanitary ware, cast, setting acceleration, (2) 37*h*.
firing, open, problems in, (7) 165*h*.
isostatic pressing, (4) 85*g*.
resembling natural stone or marble, P (4) 85*i*.
surfaces, cleaning, P (10) 242*h*.
toilet bowl structure, P (7) 166*b*.
washbasins, hydrostatic pressing, (8) 197*j*.
washstands, P (8) 198*d*.
Sapphire, basal dislocations in, (10) 261*h*.
prismatic slip in, (3) 74*h*.
single-crystal, from Al_2O_3 melt, P (1) 10*f*.
ZnO deposited epitaxially on, P (9) 225*a*.
Scandium, -C phase, superconducting, P (1) 9*g*.
molybdate and tungstate, properties, (8) 210*h*.
oxide, compatibility with refractory metals, (10) 246*i*.
phosphate, Tb^{3+} and Ce^{3+} transition in, (3) 73*a*.
Sc_4C_3, crystal structure, (4) 98*a*.
Scattering, Brillouin, study of attenuation in quartz, (6) 145*c*.
of elastic waves from cavities, (7) 177*f*.
electron, by vacancies in V carbide, (7) 180*j*.
electron, in ferroelectric semiconductors, (5) 120*j*.
laser light, for determining agglomeration in dispersed systems, (1) 17*g*.
light, and particle-scattering in ellipsoids of revolution, (1) 17*g*.
light, spin-flip, in semiconductors, P (8) 202*d*.
neutron, study of fluctuations in $BaTiO_3$, (5) 124*i*.
Raman, in CdS, (6) 150*j*.
Raman, and polariton, in $LiIO_3$, (5) 124*f*.
Raman, by $Sr_xBa_{1-x}Nb_2O_6$, (5) 123*d*.
space-charge, in *n*-GaAs, (7) 180*f*.
Scheelite, structure phases in $PuMoO_3$—Li or Na molybdate systems, (10) 260*g*.
Schools. See *Education*.
Science, of ceramic machining and surface finishing, B (10) 264*j*.
Screen process printing. See *Decoration*.
Screening and sieving, cathode-ray tubes, P (10) 245*d*.
color cathode-ray tube, P (1) 14*h*; P (4) 89*a*; P (10) 252*f*.
of color picture tubes, P (7) 170*j*.
shadow mask color tube, P (9) 227*a*.
vibratory apparatus, P (4) 92*i*.
Screens and sieves, cathode ray tube, P (1) 12*c*; P (7) 170*j*.
aluminizing, P (8) 202*d*.
structure, P (3) 66*f*.
cathodoluminescent, P (4) 90*g*.
coated, P (5) 105*f*.
color CRT, P (5) 113*d*; P (8) 200*d*.
color CRT, windowed web in, P (9) 227*c,d*.
color picture tube, P (2) 33*h*.
display, P (6) 137*b*.
elastic bottom, P (9) 229*j*.
fluorescent, P (6) 138*f*.
fluorescent, for electron discharge devices, P (8) 200*e*.
image, for cathode ray tube, photodepositing, P (8) 201*g*.
luminescent, P (5) 113*b*; P (6) 139*g*.
adhesive in, P (4) 91*a*.
by electrophoresis, P (10) 245*e*.
with separation medium, P (1) 12*i*.
molecular ultrastable 3 A, P (10) 257*j*.
phosphor, P (3) 63*f*; P (10) 245*b*.
phosphor, for cathode-ray tube, P (10) 251*g*.
projection, composite back, P (10) 245*b*.
self-supporting, for stone and ore, P (2) 46*h*.
for shadow-mask tubes, P (10) 245*c*.
slurry, P (9) 230*e*.
straining, and grading, machines for, (2) 43*j*.
vibrating, P (5) 115*j*.
increasing throughput, P (8) 204*b*.
for liquids, P (9) 230*e*.
Zn-CdS cathodoluminescent, P (7) 170*h*.
Sculpture. See *Art and artware*.
Seals and sealing. See also *Bonding; Soldering*.
Al_2O_3 ceramic-to-metal, (6) 136*f*.
arrangements for lamps, P (10) 245*f*.
building joint, standards, (4) 84*b*.
C, metal-impregnated, P (3) 61*h*.
ceramic, P (3) 62*a*.
crossarm for regenerators, P (1) 8*j*.
-to-metal, (3) 62*g*; P (10) 244*b*.
display cathodes in glass, P (4) 82*f*.
filter press cavity, P (4) 92*e*.
glass, P (9) 219*j*.
or ceramic-to-composite metal, P (3) 59*e*.
compositions, with Al titanate, P (6) 132*j*.
with high absorption for ir radiation, P (10) 245*f*.
to Fe-Ni-Co alloy, (1) 3*d*.
glass-to-metal, P (4) 82*f,g*.
for capacitor, P (3) 64*h*.
cracks in, (10) 243*a*.
and elastomeric, for capacitor, P (3) 64*j*.
thermal stresses in, (7) 160*j*.
and gripping system for slab facing materials, P (10) 244*d*.
heat, of glass member to another, P (4) 88*c*.
hermetic, P (6) 137*i*.
hermetic, for electrical conductors, P (2) 35*a*.
high-temp., P (9) 222*h*.
high-temp. composite, P (4) 84*a*.
In alloy, for cathode-ray tube, P (4) 82*e*.
Seals and sealing *(continued)*
on integrated circuit packages, P (3) 67*i*.
laser rods, P (9) 226*f*.
materials for glazing, (7) 160*d*.
metal, in vitreous enclosure, P (1) 5*c*.
metal-to-glass-to-ceramic, P (5) 107*a*.
metal-glass–metal-metal, P (2) 34*f*.
Mo aluminide, for W halogen lamp, P (9) 220*a*.
Ni-base metalloceramic material, P (11) 272*c*.
quartz-to-metal, P (4) 83*a*.
reed switches with ir energy, P (8) 193*f*.
regenerator, ceramic, P (6) 136*e*.
for rotary kilns, (8) 187*d*.
sapphire-to-metal, by alloying, (3) 62*g*.
semiconductor element, P (2) 41*b*.
SiC, for earth-boring bit, P (1) 20*j*.
SiO_2-metal, by soldering with metal, (7) 159*a*.
solder-glass, controlling behavior, (11) 274*c*.
structure, ribbon conductor press, P (10) 245*e*.
Sedimentation, and flotation apparatus, P (10) 254*i*.
Sediments, central tendency and dispersion in, analysis, (8) 204*g*.
cores, thermoluminescence, (8) 205*f*.
density, precise determination, (3) 70*b*.
fine grained, size analysis, (8) 205*e*.
particle-size analyses using settling tubes, (8) 204*c*.
silt and clay, size analysis, (1) 18*i*.
Selenium, amorphous, coating, P (7) 170*c*.
amorphous, piezo-optic properties, (8) 191*a*.
diffusion in CdS, CdSe, and CdTe, (4) 98*j*.
films, trigonal, growth on glass, (3) 56*i*.
liquid, electrical resistance, (3) 62*g*.
$SeCl_4$-2TlCl, structure, (6) 152*c*.
systems. See *Systems*.
vitreous, crystallization, strain effects, (11) 268*j*.
Semiconduction, in NiO, (7) 176*d*.
Semiconductors, P (9) 226*g*; P (11) 275*b*.
alloyed device, P (1) 13*c*.
alloys, homogeneous bodies from, P (10) 251*h*.
amorphous, B (10) 262*c*.
short-range order in, (3) 63*h*.
structure, (6) 152*c*.
switching in, (6) 152*g*.
assembly, P (6) 140*a*.
beam leads, P (3) 64*i*.
behavior, of Au-SiO thin films, (6) 137*a*.
body, apparatus for cleaning, P (4) 91*c*.
contacts on, P (4) 90*e*.
diffusion regions in, P (9) 226*g*.
etching, P (10) 249*f*, 251*j*.
impurity profile, P (8) 201*j*.
plasma anodization of metal on, P (8) 201*j*.
solder for contacting, P (1) 14*g*.
surfaces, etching, P (6) 139*g*.
bonding apparatus, aiming device for, P (8) 200*a*.
buried-layer device, P (2) 39*d*.
ceramic, compositions, P (10) 252*g*.
in electron multiplier device, P (2) 40*e*.
use, (9) 224*f*.
chip, attachment method, P (5) 114*b*.
bonder, P (3) 67*a*.
bonding method, P (9) 227*g*.
devices, bonding to hybrid circuitry, P (10) 252*j*.
embedding in dielectric layer, P (2) 41*c*.
monolithic, P (7) 168*b*.
rigidly mounted, P (1) 14*j*.
separation from substrate, P (9) 226*i*.
torque testing, P (2) 39*f*.
circuit applications, (6) 137*b*.
circuit device, P (4) 90*e*.
components, P (4) 89*e*.
carrier for, P (2) 39*e*.
elements, P (11) 275*d*.
on magnetic substrate, P (10) 252*c*.
press electrode, encasing process for, P (2) 40*f*.
composition, P (4) 87*a*.
compounds, P (6) 139*a*.
binary, crystallizing, P (4) 88*f*.
growing, P (6) 138*g*.
contaminated surfaces, detecting, P (10) 252*d*.
crystals, Ga diffused regions in, P (5) 113*a*.
growth, P (3) 67*e*.
growth, group III-V, P (6) 138*g*.
insulating layer on, P (8) 201*h*.
luminescent, (2) 39*f*.
twinned, group III-V, P (5) 112*f*.
vapor growth, P (11) 275*e*.
device, P (1) 13*a*, 13*i*, 14*i*; P (2) 40*g*, 41*g*, 42*a,b,h,j*; P (3) 64*g*, 66*j*, 67*b*; P (4) 87*h*, 89*f,j,a*, 90*b,e,d*, 91*b*; P (5) 113*i*, 114*c,d*; P (6) 137*e*, 138*d,i,j*, 139*b,c*; P (7) 169*e,d*, 170*j,a,b*; P (8) 201*f*, 202*h,i*; P (9) 225*e*, 226*g*, 227*e*; P (10) 251*f*, 252*c,g,h*; P (11) 275*b,d,e*.
with alloyed junctions, P (9) 226*g*.
AlN crystals for, P (4) 89*d*.
assembling, P (2) 40*j*.
assembly, P (9) 225*h*; P (10) 249*g*.
with bistable circuit, P (3) 67*a*.
bonding, P (9) 224*h*.
with breakdown voltage, P (9) 226*d*.
buried layer, P (3) 65*h*.
components, P (7) 169*a*.
composite stripe for, P (3) 64*d*.
comprising heterojunction, P (10) 252*i*.
comprising IGFET, P (10) 252*h*.
connecting parts, P (7) 169*i*.
connection to terminals, P (9) 226*e*.
contact system for, P (4) 87*b*.
with cup-shaped regions, P (9) 225*i*.
deep depletion, P (10) 250*f*.
with dielectric barrier, P (2) 42*a*.
Semiconductors, device *(continued)*
dielectric structure for, P (6) 137*a*.
diffractive image-forming means in, P (6) 137*b*.
with diffused Pt, P (5) 114*e*.
with diffusion pathways, P (3) 66*j*.
effective capacitance, P (2) 41*a*.
etching, P (8) 201*c*; P (10) 251*j*.
facedown-bonded, P (3) 67*c*.
with field-effect transistor, P (3) 67*a*.
film-deposited, P (10) 250*d*.
forming beam leads on, P (7) 169*g*.
fused glass films on, (2) 39*c*.
glass-encapsulated, P (5) 112*f*; P (9) 226*a*.
glass passivated, P (5) 112*f*.
with heat sink, P (1) 14*j*.
hermetically sealed, P (8) 200*g*.
high performance, P (10) 252*b*.
high-power, P (6) 137*j*.
with high switching speed, P (3) 67*b*.
with improved compatibility, P (4) 90*d*.
with improved heat sink, P (4) 90*c*.
increasing stability, P (4) 88*j*.
in integrated circuits, P (5) 112*h*.
inversion prevention for, P (2) 40*e*.
by ion implantation, P (2) 41*c*; (3) 63*d*; P (8) 201*i*.
isolating, P (3) 65*h*.
with junction passivation, P (2) 42*j*.
with lateral transistor, P (9) 227*e*.
lead contact for, P (3) 64*e*.
with lines and electrodes, P (2) 42*a*.
made with metal conductor, P (1) 14*j*.
magnetically operated, P (9) 225*j*.
making contact to, P (4) 89*a*.
mfg. using refractory dielectrics, P (1) 13*a*.
and materials, measurement, (7) 167*i*.
with metalization, P (3) 67*d*.
metalizing, P (5) 113*j*.
monitoring, P (7) 169*b*.
with multilevel metalization, P (9) 227*f*.
NOT circuit, P (1) 14*j*.
ohmic contact for, P (5) 113*e*; P (9) 227*c*.
package for, P (3) 64*f*.
passivated, P (8) 202*h*.
passivated surfaces and coatings for, P (11) 275*h*.
with passivation film, P (2) 41*h*.
planar, P (6) 140*c*.
with polycrystalline diode, P (7) 170*a*.
for producing oscillations, P (9) 227*f*.
for producing radiation, P (6) 140*c*.
by selective electrolytic etching, P (2) 41*h*.
self-sealing, P (8) 202*g*.
with small area contacts, P (7) 170*a*.
of small dimensions, P (9) 227*i*.
stabilizing, P (4) 89*b*.
with superlattice region, P (3) 67*d*.
surface controlled avalanche, P (10) 253*f*.
with Ta-Au composite conductor, P (5) 114*c*.
testing bond strength, P (5) 114*b*.
3-layer, P (3) 67*c*.
with [311] planar face, P (4) 89*g*.
Ti-W-Au contacts for, P (1) 15*b*.
with TiO_2-SiO_2 layer, P (2) 42*i*.
with transistors, P (3) 67*c*.
using two-metal contact, P (9) 227*e*.
Zener diode, P (1) 13*j*; P (4) 89*f*.
dicing, P (4) 87*b*.
diffusion, of acceptor impurities into, P (2) 41*b*.
of dopants into, P (11) 275*a*.
of impurities into, P (10) 251*b*.
treatment, P (7) 169*f*.
disks, packaging, P (10) 252*h*.
display apparatus, electroluminescent, P (9) 225*e*.
doping compositions, P (8) 202*i*.
electrical conduction mechanism in, (6) 147*e*.
electrical devices, P (11) 274*g*.
electrode system, P (3) 64*h*.
electroluminescent, device, of GaN, P (11) 274*g*.
junction, P (1) 12*j*.
pn junction, P (4) 87*e*.
elements, P (3) 65*j*; P (6) 140*d*; P (9) 227*d*; P (11) 275*g*.
beveled cavity in, P (4) 90*d*.
bonding, P (4) 87*d*.
for heat pump, P (2) 42*c*.
isolating, P (2) 42*c*.
laminated structure for, P (3) 65*i*.
with n^+pp^+ or p^+nn^+ junction, P (9) 228*c*.
sealing [metal cap], P (2) 41*b*.
series connected, P (3) 64*g*.
for switching, P (5) 114*e*.
treating, P (1) 13*j*.
epitaxial device, P (4) 87*g*.
exclusive OR gate, metal oxide, P (9) 224*j*.
exclusive NOR gate, metal oxide, P (11) 274*e*.
ferroelectric, electron scattering in, (5) 120*j*.
ferromagnetic, charge carriers in, (6) 148*g*.
ferromagnetic, transitions in, (9) 236*e*.
field-effect device, P (1) 12*d*; P (3) 65*j*; P (6) 137*f*.
films, epitaxial compound, P (2) 42*j*.
growing on substrate, P (9) 226*i*.
sintered, P (4) 90*h*.
flip-chip soldering method, P (9) 227*g*.
forming epitaxial layer on, P (3) 41*d*.
GaAs device, P (2) 40*h*; P (6) 140*b*.
Ge devices, coatings for, P (3) 64*c*.
glass-coated, P (4) 88*a*.
growth layer on MgAl spinel, P (3) 68*b*.
with heat sink and connector bodies, P (5) 114*b*.
heterojunction device, P (5) 114*f*.
hf device, P (10) 252*a*.

Semiconductors *(continued)*
high-power devices, P (3) 66*c*.
high-purity III-V compositions, P (2) 41*c*.
high-temp., P (2) 40*c*.
homogeneous, P (8) 200*i*.
housing, P (8) 201*b*.
for image sensing and storage, P (10) 252*g*.
with improved heat dissipation, P (2) 42*e*.
improved power and hf response, P (4) 90*g*.
impurity concentration, determination, P (1) 13*a*.
impurity regions in, P (5) 112*e*.
indirect-gap, radiation from, P (4) 88*d*.
InSb thin-film element, P (10) 251*e*.
IGFETS, P (7) 169*a*.
integrated-circuit device, P (2) 41*d*, 42*c*; P (7) 169*g*.
integrated devices, P (8) 200*c*.
interconnecting system, P (8) 202*j*.
ion implantation in, P (7) 169*d*.
island thickness, P (3) 65*d*.
isolation structure, P (3) 67*g*.
joining to contact, P (9) 226*j*.
junction-type devices, P (4) 89*b*.
layers, epitaxic growth, P (7) 169*c*.
layers, on foreign substrates, P (7) 169*d*.
leads, P (10) 251*d*.
logic device, P (7) 170*c*.
luminescent devices, externally excited, P (1) 12*c*.
magnetic, conductivity tensor and Hall effect in, (5) 145*c*.
mfg., photoresists in, (3) 63*d*.
material, P (3) 66*a*; P (6) 139*h*; P (10) 252*j*.
breaking scribed slices, P (1) 12*g*.
carrier concentration, P (3) 65*a*; P (6) 142*b*.
continuous doping, P (2) 41*a*.
depositing, P (4) 88*f*.
epitactic precipitation, P (9) 225*b*.
group III-V compound, P (8) 201*d*.
group IV, B (6) 154*c*.
layer, accurately doping, P (3) 65*b*.
measurement for, (1) 11*c*.
metal-organics in, (2) 39*i*.
polishing surface, P (11) 275*a*.
precipitating layers of, P (8) 201*f*.
process control, and devices, (10) 249*f*.
progress report, (9) 224*j*.
single-crystal, P (6) 139*h*.
slices of, P (5) 113*a*.
in system Ga-As-Te-Ge, (6) 145*j*.
thermal treatment, P (2) 42*d*.
ultrapure, P (6) 139*i*.
members, holder for, P (7) 168*j*.
memory apparatus, P (1) 14*a*.
mesa-type device, P (3) 65*b*.
MIS, array, P (8) 201*h*.
device, P (3) 66*a*.
memory matrix using, P (9) 226*a*.
structures, P (10) 251*g*.
-type variable capacitance device, P (2) 41*d*.
MOS, bipolar-to-, interface stage, P (3) 64*i*.
device, P (3) 66*b*; P (4) 89*e*.
devices, gate protection in, P (6) 139*j*.
devices, openings in, P (10) 250*e*.
integrated circuit device, P (9) 227*a*.
photoelectron emission from, (5) 120*h*.
photosensitivity, P (4) 88*j*.
pyrohydrolytic Al_2O_3 for, (10) 249*i*.
structures, built-in voltage in, (7) 166*e*.
MOSFETS, P (10) 252*b*.
-metal transition, device, gated, P (6) 137*g*.
model for, (6) 151*e*.
in V_2O_3 and V_2O_4, (8) 57*j*.
metalization, P (7) 169*c*.
microcomponents by planar technique, P (10) 252*j*.
microwave devices, (7) 168*f*.
monocrystalline body, P (9) 226*j*.
monocrystalline rod, P (1) 12*e*.
monolithic apparatus, P (8) 201*i*.
monolithic, for charge transfer, P (7) 169*f*.
multiple pellet device, P (3) 66*d*.
multivalley, light scattering and oscillations in, (8) 202*c*.
ohmic contacts to, P (1) 13*g*.
optoelectronic device, P (5) 113*f*; P (11) 275*h*.
p-type, inversion, prevention during rf sputtering of quartz, P (2) 42*c*.
p-type, ohmic contact for, P (11) 275*g*.
package, P (8) 202*a*.
packages, beam-lead wiring for, P (11) 275*g*.
passivated device, P (4) 89*h*; P (8) 202*a*.
passivated wire bonded device, P (4) 89*i*.
passivating process, P (5) 114*f*.
passivating process and product, P (6) 140*d*.
pellet, fitted on metal body, P (10) 252*j*.
pellet, fitting on metal body, P (5) 113*g*.
phenomena in, (6) 145*j*.
phonon- and impurity-scattering in, (7) 167*c*.
photodevice, with surface depletion layer, P (1) 15*a*.
photoelectric converting device, P (4) 90*f*.
photosensitive device, P (9) 226*d*, 227*f*,*h*.
photovarnish masks for, P (1) 13*h*.
point contact device, P (8) 202*c*.
power devices, P (3) 65*g*.
preparation, crystal growth, properties, B (10) 264*b*.
preparation, diffusion masking in, P (5) 112*i*.
pressure-biased component, P (4) 90*b*.
pressure-sensitive device, P (4) 89*e*.
production, purifying quartz vessel for, P (6) 133*a*.
properties of Mg_3Pb, (9) 238*h*.

Semiconductors *(continued)*
radiation-sensitive devices, P (7) 169*b*.
recombination radiation device, P (2) 42*e*.
rectifying arrangement, P (10) 253*a*.
regions, masking, P (10) 251*i*.
relaxation-case, Hall coeff. in, (7) 180*d*.
replacements for electron tube devices, P (6) 140*e*.
rod, device for melting, P (1) 12*g*.
rods, growing from pedestal, P (4) 88*i*.
Schottky barrier device, P (4) 90*j*.
shallow junction devices, P (1) 13*d*.
SiC device, P (1) 14*d*.
SiO_2-based doping compositions, P (8) 202*a*.
single crystals, P (2) 42*a*.
film devices, P (3) 64*j*.
groups III-V, P (2) 41*j*.
spreading resistance in, P (4) 87*d*.
sputter etch removal rates, (10) 249*a*.
structures, P (6) 138*e*; P (8) 202*b*.
conductive connection through, P (6) 138*a*.
laminated, P (6) 138*c*.
pinched resistor, P (11) 275*c*.
reducing carrier lifetime, P (3) 66*g*.
subassembly, for heat sink, P (7) 170*h*.
substances from Ge-Si or Mo-Si, P (10) 249*f*.
substrate impurity diffusion into, P (8) 201*a*.
substrate, integrated circuits on, P (2) 42*d*.
super-, intense cooling absorbs heat, (9) 224*g*.
surfaces, as catalysts, (1) 11*b*.
contamination investigation, (11) 274*a*.
implanting impurity ions, P (4) 88*i*.
passivator and protective coating, P (2) 42*b*.
photolithographic structures on, P (2) 39*a*.
producing metal structures on, P (1) 13*h*.
properties, B (3) 76*j*.
SiO_2 films on, P (2) 40*a*.
switch structure, coplanar, P (3) 64*e*.
switching behavior, (6) 148*b*.
switching device, (6) 136*g*.
switching device, barrier-free, P (2) 39*e*.
switching element, P (4) 87*f*.
in system As-Se-Te, conduction in, (3) 62*e*.
system, Au Ge GaAs metal, transport, (5) 112*d*.
target structure for image converting device, P (10) 253*b*.
temp.-sensitive means, P (9) 227*i*.
tester, with visual display, P (1) 14*a*.
testing, device for, P (8) 200*i*.
thin layer, ohmic contact in, P (9) 226*h*.
with Sn oxide layer and substrate, P (10) 252*i*.
wafer, P (1) 13*g*.
air slide, P (1) 14*b*.
alignment target, P (8) 200*b*.
dividing, P (4) 88*g*; P (10) 251*b*.
elements, P (2) 41*e*.
etchants for, P (1) 12*b*; P (2) 43*a*.
forming in substrates, P (4) 88*h*.
Au solder preforms on, P (1) 14*g*.
grooving, P (10) 251*f*.
heat dispersion from, P (10) 250*g*.
impurity predeposition on, P (1) 13*d*.
machining, P (1) 13*a*.
positioning, P (6) 142*i*.
positioning system, P (2) 39*b*.
processing, P (1) 14*b*.
quartz holder for, P (2) 42*e*.
severing, P (11) 275*e*.
SiO_2 layer on, P (10) 252*b*.
slice, P (9) 224*i*.
subdivided separator, P (1) 14*j*.
supporting device for, P (10) 250*i*.
weldable surface on, P (6) 139*d*.
Zr mask for, P (10) 253*f*.
Sensors, composite thermistor temp., P (10) 250*c*.
light, matrix device, P (9) 225*f*.
microwave ferrite acceleration, P (5) 113*c*.
Ni temp., thin-film, P (8) 202*h*.
quartz pressure, P (6) 139*i*.
for resistance temp. probes, P (5) 116*g*.
resonant cavity photon, P (2) 42*f*.
temp., thin-film, P (10) 256*b*.
Separation. See also *Beneficiation; Classification; Flotation.*
of crystals from suspension, P (7) 170*g*.
electrostatic. See *Electrostatic processes.*
gravity, of granular materials, P (10) 254*j*.
liquid-solid systems, (11) 276*h*.
MgO, annealing with, P (2) 31*i*.
magnetic, P (10) 254*g*.
mineral, P (8) 207*i*.
minerals, process, P (9) 233*c*.
of Ni from asbestos ore, P (6) 144*f*.
of particulate material from stream, P (6) 141*f*.
of K_3PO_4 and Al_2O_3, P (6) 144*f*.
pyrolitic, of F in fluoride compounds, (10) 255*a*.
size, of particles in storage, (11) 276*g*.
solute, in solids, vacancy effect, (9) 234*i*.
of U from aqueous solution, P (10) 253*i*.
Separators, ceramic, for high temp. Li battery, (9) 238*g*.
for coarse and/or heavy particles, P (4) 92*g*.
cyclone, advantage, (8) 185*j*.
dry, for granular materials, P (9) 229*g*.
electrode, P (10) 250*a*.
gravimetric, of granular materials, P (8) 207*e*.
magnetic, for beneficiation of kaolins, (9) 232*e*.
magnetic, for clay minerals, (8) 207*a*.
for metallic and nonmetallic matter, P (7) 172*g*.
particle, P (4) 92*h*.

Separators *(continued)*
preheating, P (3) 64*d*.
semiconductor wafer, subdivided, P (1) 14*j*.
for solid articles, P (10) 254*h*.
Sturtevant, increased air through, (4) 78*j*.
vibratory, screen support for, P (3) 69*g*.
Serpentine, chrysotile fines, pelletizing, P (3) 61*a*.
serpentinization, chemical study, (1) 19*j*.
Setting. See *Binders.*
Settling. See *Sedimentation.*
Sewer pipes. See *Pipe.*
Shales, bloating, from Uchida mine, (6) 128*a*.
clay-mineral diagenesis within, (8) 208*d*.
and clay resources of Ill., (3) 71*b*.
dawsonitic oil, Al compounds from, P (5) 117*i*.
hard, extrusion, (1) 6*b*.
Kansas, studies of C isotopes in, (3) 71*f*.
Shear, crystallographic, in WO_3, Nb_2O_5-doped, (10) 258*j*.
distortion of clay, (5) 117*c*.
effect on quartz-coesite transition, (7) 177*i*.
rate, and stress, calculation, (5) 116*a*.
structure compounds, Cr-Fe titanates, (10) 260*j*.
testing, of shear pins, P (6) 142*c*.
Shock, explosive, of Al_2O_3 powder, (1) 22*h*.
thermal, of brittle ceramics, (10) 261*e*.
thermal, glass fracture induced by, (4) 80*e*.
wave, behavior of solids, (5) 123*f*.
effect on ZrO_2 transformation, (6) 146*h*.
structure in porous solids, (7) 180*c*.
Shock resistance, thermal, during heating at high rates, (10) 255*j*.
of refractories, (8) 204*d*.
of ZrO_2 ceramics, (8) 195*h*.
Shrinkage, of artificial stone, reducing, P (8) 188*e*.
of compacts of colloidal boehmite, (11) 280*j*.
of concrete, high-strength, (6) 130*c*.
superdry mix, (6) 130*f*.
vacuum, (6) 130*a*.
drying, effect on concrete strength, (6) 128*j*.
plastic, of cement mix, (9) 214*i*.
Sieves. See *Screens and sieves.*
Silica. See *Silicon, dioxide.*
Silicates, alkali, O-R bond energy in, (4) 81*f*.
analysis, chemical methods, B (7) 182*h*.
analysis, X-ray fluorescence in, (9) 230*i*.
bodies, with coprecipitated oxides, P (10) 245*g*.
chemistry, (11) 278*f*.
coating, on Al reflector, P (3) 54*h*.
crystallization differentiation, (1) 21*i*.
cyclo-, rings, in muirite, (1) 21*g*.
dicalcium. See *Calcium, dicalcium silicate.*
electrodialysis, for colloidal SiO_2, P (9) 233*a*.
fluo-, internal motions in, NMR, (4) 97*j*.
foams, silane-stabilized, P (8) 194*a*.
industries, (2) 50*g*.
ir absorption spectra, (8) 190*h*.
layer, interlayer complexes in, (3) 74*b*.
and lime in thermal insulation, P (7) 157*d*.
mass spectrographic analysis, (9) 230*j*.
materials, chemistry and technology, B (10) 262*j*.
materials, Mg in, determination, (8) 204*e*.
metal, soluble complex ion, P (5) 118*b*.
modified, P (11) 280*a*.
molten, properties, B (2) 51*j*.
new "benitoite" type, (10) 260*c*.
with octrahedra chains, structure, (1) 25*j*.
organically modified, P (1) 20*h*.
ortho-, diffusion in, (9) 234*b*.
phases, effect on basic bricks, (2) 36*d*.
phases, effect on MgO hot strength, (2) 35*j*.
and phosphates, mixtures, P (3) 71*g*.
phyllo-, crystallizations on, (10) 259*f*.
phyllo-, hydroxy-Al adsorption by, (5) 118*f*.
physical chemistry, B (5) 126*b*.
for posttreatment of phosphatized metal, P (2) 32*a*.
rare gases in, (2) 50*e*.
rocks, electrowinning of O from, (7) 175*a*.
elements in, X-ray fluorescence, (9) 231*i*.
lime and MgO in, (3) 69*h*.
science and technology, B (5) 126*f*; B (8) 212*g*.
skeletons, structure, in glasses, (2) 32*b*.
structure, solid solutions, and electrical properties, (7) 181*c*.
systems. See *Systems.*
thermodynamic and refractometric properties, (9) 238*f*.
vibrational spectra and structure, B (11) 284*g*.
wastes, diamond recovery from, P (6) 127*h*.
Silicic acid, organically modified, P (1) 20*b*.
sorbent chromatographic sheet, P (6) 143*h*.
Silicides, emission coeff., (3) 73*a*.
Silicon, Al_2O_3 films on, stoichiometry, (5) 111*h*.
Al_2O_3 films rf sputtered on, (9) 224*e*.
body, excluding C from, P (1) 15*c*.
carbide. See also *Refractories.*
P (11) 272*d*,*e*.
acid solubility and oxidation resistance, (10) 246*f*.
α, growth, (3) 73*c*.
behavior in gaseous media, (10) 246*e*.
β-, formation, (5) 120*i*.
bonding contacts to and forming alloy sites on, P (7) 169*d*.
chemical milling, P (1) 8*j*.
coatings and filaments, P (3) 61*c*.
crystals, P (2) 41*i*.
crystals, C inclusion in, (3) 73*g*.
crystals, etch patterns on, (3) 76*a*.

Silicon, carbide *(continued)*
crystals, traveling solvent growth, P (9) 228*b*.
crystals, wettability, (9) 239*c*.
cubic, lattice dynamics, (5) 121*h*.
diffusing impurity into, P (4) 88*g*; P (11) 272*f*.
elastic modulus, (4) 96*g*.
fiber, liquids thickened with, P (7) 164*f*.
fracture energies, (2) 47*j*.
fracture surface energy, (10) 260*a*.
glass-ceramic cements with, P (4) 82*a*.
higher absorption edges in, (6) 148*c*.
laminated article, P (10) 247*j*.
members, contact for, P (8) 200*j*.
metal-, high-strength article, P (7) 164*f*.
from methylchlorosilanes, (10) 247*c*.
n-type, ohmic contact to, P (2) 41*h*.
nonlinear optical devices, P (10) 252*f*.
optical absorption in, (6) 150*c*.
phase transformations and crystal growth, (7) 179*a*.
resistance to dynamic fatigue, (6) 134*i*.
seal, for earth-boring bit, P (1) 20*j*.
semiconductor device, P (1) 14*d*.
shapes, vibroimpact molding, (8) 196*e*.
single crystals, growth, (6) 148*a*, 150*j*.
single crystals, morphology, (11) 281*a*.
thermal conductivity, (10) 261*c*.
thermal stability, (3) 72*g*.
use in ablative coating, P (3) 61*c*.
whiskers, (3) 61*a*; P (11) 275*b*.
whiskers, growing, P (3) 61*g*.
whiskers, neutron irradiation damage in, (10) 260*c*.
Y electrical contact to, P (4) 91*c*.
carrier concentration measurement, (6) 142*b*.
chalcogenides, P (2) 42*f*.
chemistry, B (5) 126*b*.
crystals, computer controlled growth, (3) 62*i*.
ordered structure, (3) 74*c*.
p-doped zones in, P (11) 275*c*.
device, with Pb silicate on, P (9) 227*j*.
devices, vapor-deposited W for, (10) 249*b*.
diffusion sources, deposited, P (9) 225*b*.
dioxide. See also *Coesite; Cristobalite; Glass; Quartz; Quartzite; Refractories; Sands.*
P (8) 207*d*.
acoustic loss and velocity, (5) 125*c*.
agglomerated bodies, P (7) 175*i*.
a-quartz–cristobalite, for pottery, P (8) 198*h*.
-Al_2O_3, as sintering aid for B_4C, P (4) 85*a*.
analysis in dust, (1) 17*d*.
articles, P (2) 43*i*.
articles, vapor phase deposition, P (6) 140*c*.
bead particles, P (8) 207*g*.
beads, ultrahigh-purity, P (9) 232*j*.
charge distribution in, (6) 150*i*.
chromatographic separation with, P (10) 255*h*.
-clay tooling, for welding, P (4) 80*b*.
colloidal, P (9) 233*a*.
corrosion by Na_2CO_3 and carbonate-rich melts, (7) 158*j*; (11) 268*g*.
crystallization, from Li_2MoO_4-MoO_3, (7) 176*h*.
defects in, (2) 47*c*.
depositing, from silane and O, P (1) 15*a*.
dispersions, creep in ice, (6) 145*f*.
effect on $BaTiO_3$, (7) 166*g*.
effect on firing and properties of cement, (8) 187*b*.
effect on sintered Al_2O_3, (1) 21*c*.
films, breakdown in, (2) 38*h*.
films, chemical vapor deposition, (10) 249*c*.
films, color centers in, (4) 86*g*.
films, deposition, P (3) 65*c*; (11) 273*g*.
films, electrochemical charging, (7) 166*i*.
films, electron micrography, (3) 75*g*.
films, on semiconductors, P (2) 40*a*.
films, stresses in, (2) 39*d*.
finely divided, P (5) 118*a*; P (8) 207*e*.
free, in ceramic raw materials, (7) 173*a*.
fused. See *Silicon, dioxide, vitreous.*
in glass, determination, (8) 204*g*.
glassy and crystalline, diffusion in, (5) 106*d*.
glassy pyrogenic, adsorption on, (9) 216*g*.
heat of immersion studies, (5) 121*a*.
He migration in, (3) 56*j*.
high average pore vol, P (9) 233*a*.
from H_2SiF_6 and/or Na fluorosilicate, P (11) 279*j*.
hydrophobic, P (10) 257*i*.
inert gas diffusion in, (2) 32*b*.
layer on semiconductor wafer, P (10) 252*b*.
MgO, CaO, and Fe_2O_3 mixture, phase transformations, (8) 210*b*.
melt, reaction with Ta, Mo, and W, (7) 163*g*.
modified, P (11) 280*a*.
molding powders, P (7) 164*g*.
monodisperse spheres, P (4) 91*i*.
noncrystalline, fabrication, (1) 3*g*.
pigmentary, P (8) 207*e*.
platelet, and uses, P (10) 257*a*.
recovery from molding sands, (1) 8*f*.
refractory material, P (3) 61*e*.
rigid membranes, P (4) 83*b*.
sand, use in steel castings, (9) 221*h*.
Si–O stretching band, (9) 238*c*.
and Si_3N_4 film, P (1) 14*i*.
solid solubility in MgO, (1) 25*b*.
surface hydroxyl groups on, (7) 176*c*.
surface, H_2O structure on, (6) 151*h*.
thin layers, etchant for, P (9) 225*g*.
thin tunnelable layers, (9) 239*d*.
transparent or opaque, P (9) 219*d*.

Silicon, dioxide *(continued)*
vitreous, extrudates, P (8) 193*f*.
vitreous objects, dispersion forces between, (2) 47*a*.
vitreous, optical properties, (8) 191*j*.
vitreous, refractive indices, (1) 3*h*.
disks, heat treatment, P (1) 12*h*.
electron microprobe analysis, (4) 93*c*.
epitaxial, on H $MgAl_2O_4$ spinel crystals, P (8) 200*c*.
etch, low-temp., P (9) 225*h*.
film, thermal oxide, crystallization, (3) 63*c*.
gaseous nonpreferential etching, P (10) 250*f*.
growth, using SiN films as mask, (4) 86*j*.
halides, P (10) 257*i*.
high-resistivity, ohmic contact to, P (5) 113*d*.
homoepitaxial, depositing, (3) 63*b*.
insulating coating on, P (5) 112*h*.
layers, strains in, detection, (10) 258*d*.
monocrystalline, high-purity, P (10) 251*j*.
monocrystalline ribbons, P (3) 64*e*.
monoxide, reaction products with organic compounds, acetylenes, organic halides, and aromatic compounds, P (8) 198*h*.
monoxide, structure, (2) 50*b*.
nitride, corrosion-resistant, (2) 35*i*.
diffusion mask, P (2) 41*e*.
dislocations in, (6) 146*d*.
films, properties, (2) 39*c*.
films, pyrolytic deposition, P (5) 114*a*.
improves transistors, (11) 274*a*.
layer, application, P (3) 65*d*.
layers, P (9) 225*j*.
masking during etching, P (8) 202*g*.
NRDC study, (4) 100*a*.
pyrolytic, (9) 224*c*.
reactions with W and Ta, (2) 49*f*.
and SiO_2 composite, etching, P (1) 14*e*.
solid solubility of oxides in, (4) 98*d*.
vapor deposition on Si, P (7) 169*e*.
oxide, coatings, in electric discharge, P (7) 169*h*.
electric dipole moment, (5) 120*g*.
films, contamination, (3) 72*h*.
films, deposition, P (9) 226*f*.
films, photocurrents in, (6) 150*h*.
oxides, finely particulate, P (6) 144*h*.
and O compound, thin deposit, P (10) 257*h*.
oxynitride, P (5) 110*b*.
bodies, shrinkage and growth, P (10) 247*g*.
as dielectric material, (9) 224*c*.
sputtering deposition, P (4) 90*j*.
synthesis, (8) 207*b*.
P-impurity profiles in, (9) 223*j*.
powder structures, joining, P (11) 275*f*.
powder structures, spray deposition, P (9) 222*h*.
powders, reaction with ZrC, (11) 260*d*.
precipitation, epitactic, P (8) 201*f*.
reactions with rutile, ir study, (11) 281*c*.
siliceous minerals, carbothermal reduction, (8) 206*i*.
and SiC, ESR in, (6) 147*b*.
-(SiO_2)-Al_2O_3 structures, interface, (9) 236*i*.
and SiO_2, He ions in, (6) 151*j*.
Si_2N_2O, preparation, (6) 151*c*.
single crystal, growth, diam. control, P (1) 14*f*.
for monolithic memory, (9) 224*c*.
rod-shaped, P (7) 169*i*.
sulfides, thermodynamics, (4) 99*h*.
surface, polishing, P (2) 41*j*.
surfaces, removal of glasses from, P (9) 227*b*.
systems. See *Systems.*
tetrafluoride, generation, P (10) 257*c*.
tetrafluoride, hydrolysis, P (8) 207*c*.
thin, fragile slices, scrubbing, P (9) 226*h*.
Vidicon target, experimental, (3) 73*g*.
wafer, controllably oxidizing, P (6) 138*j*.
wafers, frame for supporting, P (5) 107*i*.
willemite films on, (7) 168*d*.
Silicone, in ceramic industry, (11) 276*i*.
Sillimanite. See also *Refractories.*
natural, compositions, (4) 94*b*.
in rocks in Calif., (1) 19*g*.
Silver, -arsenide deposits of Ontario, (9) 232*i*.
atom in alkali silicate glass, ESR, (3) 55*h*.
-CdO electrical contact materials, P (9) 228*a*.
formation in photosensitive glass, (3) 56*c*.
liquid, TaC wetting by, (4) 80*a*.
nitrate, in nitrate salts, activity, (6) 144*i*.
oxide, lattice, expansion, (2) 47*g*.
-Pd, sintering in presence of reactive glass, (7) 160*e*.
and K sulfates and tungstates, reaction, (5) 123*h*.
Ag^+, diffusing into glass, (3) 56*j*.
Ag β-Al_2O_3, structure and stoichiometry, (8) 210*i*.
surfaces, etch pits on, (7) 182*a*.
systems. See *Systems.*
vapor, incorporation into Ag_2S, (6) 147*i*.
Silvering. See *Glass.*
Single crystals. See *Crystals,* and specific types.
Sintering, Al_2O_3, effect of fluoride mineralizers, (8) 195*c*.
BeO powder, (6) 150*g*.
of binary oxides, (7) 177*c*.
CaF_2, effect of additives, (1) 21*h*; (7) 177*e*.
carbonyl Fe, effect of oxide particles, (10) 246*j*.
conditions, effect on compacts, (10) 247*a*.
dolomite and magnesite, (11) 279*f*.
during hot pressing of MgO-Al_2O_3 spinel, (8) 210*c*.
effect on Al_2O_3-MoMn bond strengths, (1) 2*h*.
electric discharge, preventing C diffusion in, P (9) 228*i*.
by electrolytic heating, (11) 276*j*.

Sintering *(continued)*
equations, analysis, (1) 21*a*.
equations, analysis, correction, (3) 72*d*.
feldspar, (11) 282*b*.
final, of Cr_2O_3, (10) 259*g*.
final-stage, of active CaF_2, (2) 47*g*.
H, of UO_2 fuel pellets, (11) 276*c*.
initial, of Al_2O_3, effect of TiO_2, (3) 72*i*.
initial-stage, studying, (9) 237*f*.
initial-stage, of UO_2, kinetics, (9) 228*h*.
Fe-Cr carbide composite materials, (10) 259*f*.
kinetics, in Al_2O_3-Cr_2O_3 system, (5) 125*h*.
at constant rate, (6) 149*g*.
in hematite, (3) 75*e*.
PZ-PT, effects of calcining, (4) 86*g*.
lightweight aggregates, P (11) 277*g*.
liquid-phase, B (1) 28*h*.
MgO, densification and grain growth, (2) 49*j*.
materials for aggregates, P (7) 163*d*.
mechanism in powder metallurgy, (3) 74*h*.
metal-glass, glass behavior in, (10) 242*j*.
Mo metalizing, (1) 11*j*.
Ni-O, kinetics, (9) 236*c*.
Nb and TiC powders, (10) 260*c*.
parameters, effect on $BaTiO_3$ properties, (9) 224*f*.
phenomenon in portland cement pastes, (7) 157*b*.
pore closure during, (1) 26*b*.
portland cement clinker, (9) 214*h*.
preparation of MgO transparent bodies, (11) 282*f*.
pressure-, of Al_2O_3, (1) 24*d*.
Al_2O_3, effect of impurities, (1) 21*b*.
synergetic, of Al_2O_3, (3) 75*g*.
properties, of calcined Al_2O_3, predicting from particle size, (1) 11*g*.
rapid, of Al_2O_3, glow-discharge apparatus for, (8) 205*a*.
rate controlled, of Al_2O_3, (8) 195*d*.
refractory oxides, (5) 123*h*.
Ag-Pd in presence of reactive glass, (7) 160*e*.
interability of $BaTiO_3$, (11) 273*i*.
Sr ferrite, effect of Bi_2O_3, (7) 167*e*.
studies on Zn oxide, (3) 75*e*.
study by electron microscopy, (4) 93*f*.
and surface diffusion in Al_2O_3, (4) 97*g*.
thermoelectric devices, (7) 168*a*.
ThO_2 and ThO_2-Y_2O_3 with NiO, (11) 280*d*.
time and temp., effect on Sr ferrite, (8) 199*d*.
TiC, (10) 261*a*.
TiC base cermets, (10) 247*j*.
Sinters, sintered materials, cooling, (9) 215*g*.
Size reduction. See *Crushing; Grinding.*
Slags, attack in casting furnace, (8) 195*h*.
blast furnace, in ceramics, (1) 6*a*.
blast-furnace, effect on cement mortar, (4) 78*e*.
or brick, accretion or removal, (6) 134*e*.
CaO-FeO-SiO_2, lime dissolution in, (1) 2*c*.
corrosion of MgO-CaO refractories, (7) 163*h*.
MnO-SiO_2-base, absorption spectra, (6) 149*b*.
molten, granulation, P (2) 35*b*.
open hearth, refractories resistance to, (8) 195*g*.
resistance, of aluminosilica refractories, (1) 6*j*.
slagging in steelmaking process, P (6) 135*g*.
steel, handling, P (1) 3*a*.
wool. See *Mineral wool.*
Slaking. See *Lime, hydration of.*
Slate, articles from, P (9) 230*c*.
Slip casting, acceleration, (2) 37*h*.
cermets, P (10) 248*d*.
corrosion of mold surface in, (7) 165*c*.
creative, (2) 30*e*.
plaster molds in, (4) 85*j*.
pressure, to form Al_2O_3 cakes, (9) 223*c*.
pressure, mechanics, (6) 134*f*.
whiteware, nonclay particle size in, (8) 198*g*.
Slips. See also *Suspensions.*
clay, electrophoretic deposition, (4) 85*h*.
method for production of floor tile, (8) 197*d*.
preparation technology, (8) 198*a*.
prismatic, in sapphire, (3) 74*h*.
propagation, across twist boundary, (6) 151*f*.
systems in VC-TiC alloys, (2) 49*b*.
Slurries. See also *Cement.*
Ca and Mg oxides and titer in, (8) 204*d*.
distribution, deflocculation, and dispersion, P (11) 277*e*.
filtration, P (2) 44*d*.
flow, continuous sampling, P (9) 231*i*.
forming apparatus, P (10) 254*i*.
forming member from, P (1) 8*i*.
kaolinite-CaO-H_2O, hydrogarnet phase in, (9) 214*b*.
preparing, maintaining, and controlling, P (11) 277*d*.
process, for coating particles, P (7) 170*d*.
processing for transportation by sonics, P (11) 277*g*.
-pumping means, P (5) 115*i*.
raw-material, rheological properties, (8) 204*h*.
reactor for processing, P (1) 20*b*.
repulping and unloading system, for ore carrier, P (1) 20*e*.
solid-liquid, power consumption in, (2) 43*i*.
thermal treatment, apparatus for, P (11) 277*f*.
Smectites, H, for forming asbestos suspensions, P (7) 164*c*.
Smelting. See *Metallurgy.*
Smoke, stack clarifier, P (8) 204*b*.
Soapstone. See *Talc.*
Soda or Soda ash. See *Sodium, carbonate.*
Sodalites, cathodochromic, (6) 151*e*.

Sodium. See also *Alkalis.*
aluminate solutions, P (8) 207*h*.
aluminosilicate, crystalline zeolitic, P (10) 257*e*.
atoms, contamination of SiO films with, (3) 72*h*.
borates, thermodynamic properties, (2) 50*c*.
carbonate, P (6) 144*a*; P (7) 176*a,b*; P (8) 207*i*; P (9) 232*h*.
carbonate, corrosion of SiO_2 by, (7) 158*j*; (11) 268*g*.
chloride, crystallographic shear relations with UO_2, CaF_2, and La_2O_3, (9) 234*f*.
deformation and hardening in, (10) 260*j*.
dislocation motion in, (10) 258*h*.
electrical conductivity, (5) 122*f*.
high-pressure equation, (6) 148*b*.
impurity diffusion techniques, (9) 236*i*.
melts, evaporation, (7) 177*e*.
superstructure, new, (10) 258*c*.
-type structures, *B* values, (10) 258*b*.
determination by spectrophotometry, (4) 78*b*.
diffusion in glass, atm effects, (6) 131*h*.
electron beam analysis, (8) 205*a*.
fluoride-AlF_3, under pressure, (11) 283*a*.
fluoride-LiF melt, reaction of UO_2 and MoO_3 in, (1) 24*f*.
fluoroaluminates, ir absorption spectra, (11) 281*a*.
fluosilicate, recovery in production of H_3PO_4, P (1) 20*i*.
hydroaluminates, thermal decomposition, (8) 211*f*.
ion transport in β-Al_2O_3, (9) 238*b*.
metaniobate, nonstoichiometric, (8) 209*h*.
monoxide, effect on cement strength, (4) 79*a*.
niobate(T_2), structure, (10) 261*f*.
oxide, in glass, determination, (8) 204*g*.
oxide, reaction with rare earths, (1) 24*e*.
oxides, attack on refractories, (1) 8*a*.
phosphate, activity of O ions in, (5) 123*c*.
phosphate, BeO solubility in, (8) 210*e*.
silicate, foam, insolubilizing, P (8) 207*f*.
melting furnace, refractories for, (7) 163*j*.
and oxalate, deflocculation of ball clay by, (1) 9*h*.
$NaAlSiO_4$-$CaCO_3$-H_2O, composition join, (1) 22*h*.
$Na_4CaSi_3O_9$, relation to $Ca_3Al_2O_6$, (3) 72*d*.
$Na_2Ca_3(SO_4)_3$, solubility in NaCl, (7) 156*g*.
$Na_4Ge_4S_{10}$, crystal structure, (6) 146*a*.
$NaHSO_4$·H_2O, crystal structure, (11) 280*g*.
solubility in melts of Na systems, (7) 177*c*.
sulfides, X-ray powder diffraction, (11) 282*i*.
sulfite, in glass mfg., P (2) 34*f*.
systems. See *Systems.*
tetrahydroborate, reaction with $CrCl_3$, (8) 210*j*.
transport through β-Al_2O_3 membranes, (9) 237*a*.
Softening, of brick under load, effect of atm, (1) 18*i*.
Soils, argillaceous, mineralogical analysis, B (1) 28*j*.
and cement, water-repellent, P (8) 188*g*.
Solar batteries or **Solar cells.** See *Cells, photovoltaic.*
Solar furnaces. See *Furnaces.*
Solder, for contacting semiconductor, P (1) 14*g*.
glass, P (6) 133*j*.
preforms, Au, P (1) 14*g*.
Soldering. See also *Seals and sealing.*
brazable compositions, P (2) 33*f*.
brazing, C bodies to temp.-resistant materials, P (2) 37*e*.
ceramic parts, P (9) 226*b*.
metals to ceramics, P (4) 85*j*.
refractory metal, with Nb_2O_5, P (4) 90*h*.
for securing diamond, P (10) 241*f*.
SiO_2-clay tooling for, P (4) 80*b*.
diffusion, metal wire to graphite, (10) 249*a*.
glass, method, P (1) 4*f*.
graphite and refractory materials, P (10) 248*a*.
low-temp., of carbides, P (4) 84*e*.
semiconductor flip-chip method, P (9) 227*g*.
for vitreous SiO_2-metal sealing, (7) 159*a*.
Zr alloy elements, P (11) 275*c*.
Solid solutions. See *Solutions, solid.*
Solid state, chemistry, B (10) 264*e*.
devices, P (5) 113*g*.
diamond as heat sink for, (4) 87*b*.
electronic, P (10) 253*c*.
energy storage, P (1) 14*h*.
Gunn-type, P (9) 225*b*.
image-converting, P (6) 140*g*.
three-terminal, P (10) 253*c*.
high-frequency source, P (4) 90*i*.
integrated optical-electronic, P (4) 88*h*.
kinetic data, application to decomposition of kaolinite, brucite, and $BaCO_3$, (3) 74*h*.
materials, crystal growth, B (2) 52*i*.
photoresist technology, (3) 63*j*.
reaction, of CaO and β-quartz, (10) 259*c*.
of CaO and ZrO_2 forms $CaZrO_3$, (9) 235*c*.
diffusion equation related to, (3) 74*i*.
of particles, optimum size ratio, (5) 118*d*.
plotting kinetic data, (3) 53*j*.
kinetics, (10) 259*j*.
reduction, of chromite ores by H, (6) 151*g*.
scanning, P (8) 202*d*.
synthesis of alkaline salts of elements, (6) 150*a*.
vidicon structure, P (9) 228*b*.
Solidification, products in system Al_2O_3-P_2O_5-H_2O, (9) 238*c*.
of radioactive waste, (10) 242*a*.
Solids, amorphous, conductivity in, (6) 148*f*.
amorphous, sputtered, (2) 47*d*.
Solids *(continued)*
bulk, transporting, P (3) 69*d*.
comminuting and reacting, P (9) 230*e*.
crystalline, anelastic relaxation in, B (10) 262*h*.
damping lattice vibrations in, (8) 208*d*.
electrical properties, B (10) 263*e*.
in electrodepositable compositions, P (8) 192*f*.
floated, treating, P (4) 94*c*.
harmonic, thermodynamic properties, (4) 98*c*.
hydraulic classification, P (8) 203*j*.
kV electron energy dissipation vs penetration distance in, (7) 177*a*.
liquid-, interfaces, structure relaxation at (7) 181*f*.
materials, classifying, P (3) 71*h*.
melting, P (8) 206*f*.
mixing, (6) 141*f*.
mixtures, ingredients in, (3) 69*i*.
mixtures, phase analysis, (3) 69*j*.
noncrystalline, electronic conduction, (6) 147*c*.
optical index in, furnace for measurement, P (3) 70*a*.
particulate material, cooling, P (10) 256*f*.
Poole-Frenkel conduction in, (6) 151*d*.
roasting, P (3) 72*b*.
secondary emission and structural properties, B (6) 154*f*.
shock-wave behavior and properties, (5) 123*f*.
-solid reactions to form thin layers of mixed titanates, (6) 136*i*.
solute segregation in, (9) 234*i*.
sound speed measurements in, (4) 93*a*.
switching to conductive state, (4) 99*h*.
Sols. See *Colloids.*
Solubility, BeO, in chloride and fluoride systems, in tetraborate, and $NaPO_4$, (8) 210*e*.
$CaSO_4$, in system CaO-P_2O_5-$CaSO_4$-H_2O, (7) 176*h*.
of CO_2 in Na_2O-SiO_2 melts, (7) 158*g*.
of compounds in H_2O, (5) 124*a*.
of Fe oxide in melts of alkali metals, (1) 25*c*.
measurements in liquid system, (11) 278*a*.
of monticellite in forsterite, (1) 25*e*.
of N in aluminosilicate melts, (6) 147*j*.
in K and Rb systems, (3) 75*h*.
of Na and K in melts of Na systems, (7) 177*c*.
solid, of CaO and SiO_2 in MgO, (1) 25*b*.
of oxides in Si_3N_4, (4) 98*d*.
of $Ti_2Cr_2O_7$ in TiO_2-Cr_2O_3 system, (6) 151*h*.
of TiO_2 in halide-phosphate melts, (8) 210*f*.
Solutions, dis-, of clinker minerals in melt, (3) 53*j*.
kinetics of system $CdGe(As_xP_{1-x})_2$, (7) 178*b*.
lime, in slags, (1) 2*c*.
O in molten Pb, kinetics, (6) 149*g*.
of W oxide bronzes, (8) 208*i*.
Solutions, solid. See also *Equilibrium studies.*
$Al_{1-x}Cr_xOOH$, (3) 72*c*.
Al_2O_3-Cr_2O_3, vaporization of Cr_2O_3 over, (11) 283*b*.
Cd Zn sulfide, (2) 49*a*.
3CaO·SiO_2, lattice strain in, (9) 214*f*.
CeO_2, O self-diffusion and electrical transport properties, (9) 237*i*.
Cr, in Ca_3SiO_5, (5) 104*a*.
Cr_2O_3-Al_2O_3, magnetic properties of Cr ions in, (1) 23*i*.
growth, review, (8) 209*e*.
Fe(II) oxide, magnetic properties, (4) 97*c*.
in $FeTi_2O_5$-TiO_2 system, (3) 75*h*.
$MgCr_2O_4$-$MgAl_2O_4$, magnetic properties of Cr ions in, (1) 23*a*.
MgO-Fe_2O_3, grain distributions and growth in, (2) 48*b*.
MgO-NiO-Li_2O, Ni^{2+} in, (1) 22*c*.
MnO-MgO, dense, (9) 237*h*.
a-Nb, system Nb-N-O near, (6) 152*j*.
of silicates and germanates, (7) 181*c*.
Ag_2S-Cu_2S, activity-composition, (4) 95*c*.
in system, $Ca_3Al_2SiO_7$-$CaLaAlO_4$, (8) 210*d*.
$LaAlO_3$-$CaTiO_3$, (9) 235*d*.
Mg-Ti-Fe-O and Mn-Ti-Fe-O, synthesis and crystal structure, (1) 25*g*.
thermal diffusion in, (6) 152*c*.
$(ThO_2)_{0.75}$-$(CeO_2)_{0.25}$, electrical conductivity at high temp., (1) 11*c*.
ThO_2-$YO_{1.5}$, ac conductivity, (9) 236*h*.
of CaS and alite, hydration and strength, (4) 78*h*.
UC-UN, (4) 91*g*.
UO_2-based, cation diffusion in, (9) 228*f*.
$(U,Pu)O_2$, thermal conductivity, (7) 171*g*.
ZrO_2-based, decomposition, (8) 211*g*.
Sonics, method and apparatus for processing slurries, P (11) 277*g*.
ultra-. See *Ultrasonics.*
wave action, use in crushing rock, P (11) 279*f*.
Sorel cement. See *Cement, magnesium oxychloride.*
Sorption. See also *Absorption; Adsorption.*
apparatus, disconnecting from vacuum source, (7) 173*e*.
of benzene by Kenya diatomite, (5) 117*j*.
de-, field, of Cs, (3) 73*i*.
Sound, attenuation, in $SrTiO_3$, (6) 145*f*.
propagation in EuO, (6) 151*h*.
speed measurements in solids, (4) 93*a*.
Spacecraft, high efficiency materials, (2) 35*b*.
high-temp. materials, (2) 35*c*.
plating nonmetallics for, P (2) 38*d*.
thermal control, B (1) 27*j*.
thermal-shock resistance at high heating rates, (10) 255*j*.
Spalling. See *Refractories.*
Spark plugs, P (10) 242*h*.
with internal resistor, P (1) 14*h*.
low-voltage, P (8) 201*b*.
multiple heat range, P (2) 41*h*.
seat, P (9) 228*b*.
self-cleaning, P (10) 248*h*.
with single-piece ceramic insulator, P (1) 14*i*.
Specific gravity. See *Density.*
Specific heat. See *Heat, capacity.*
Specific surface. See *Surface.*
Spectra, absorption, and fluorescence of Eu^{3+} in Gd_2O_3, (5) 124*b*.
of Fe^{2+}-bearing materials, (11) 278*b*.
of MnO-SiO_2-base slags, (6) 149*b*.
of NpO_2^{2+} in $Cs_2UO_2Cl_4$, (5) 118*c*.
of NpO_2^{2+} in $CsUO_2(NO_3)_3$, (6) 144*i*.
of rare-earth ions in CaF_2, (6) 145*b*.
in rare-earth orthochromites, (3) 73*g*.
of ZnS, Zeeman effect, (5) 125*j*.
analysis, for flaw determination, P (8) 206*a*.
band, of GdO, (7) 176*e*.
diffuse reflectance, of clay minerals, (9) 234*j*.
donor-acceptor recombination, in CdS, (6) 146*e*.
ENDOR, of Ce^{3+}-H^- and Ce^{3+}-F^- in CaF_2, (6) 145*a*.
ESR, of Eu^{2+} in ThO_2, (6) 147*c*.
electronic, of gaseous BaS, (5) 120*b*.
electronic, and ir, of alkali halide films, (1) 25*a*.
exciton, of CaO and MgO, (6) 148*b*.
exciton and interband, of CaO, (6) 148*b*.
far-ir, of Al_2O_3, Ti-, V, and Cr-doped, (5) 120*f*.
EPR, and Moessbauer, of MgO:Fe^{2+}, (5) 121*f*.
of KBr, (6) 151*f*.
vibrational, of As_2Se_3, (6) 148*e*.
ir, of alanine adsorbed on montmorillonites, (11) 281*b*.
of aluminosalicylate complex, (9) 214*e*.
of Ge oxides, (7) 178*e*.
of glycine adsorbed on montmorillonites, (11) 281*b*.
and laser-Raman, of apatites, (7) 178*f*.
lattice vibrational, of CaO, (3) 73*i*.
and Raman, of $Ca(NO_3)_2$, $Sr(NO_3)_2$, $Ba(NO_3)_2$, and $Pb(NO_3)_2$, (7) 178*a*.
of rare-earth Al, Ga, and Fe garnets, (1) 22*h*.
of simplest silicates, (9) 218*f*.
and spectral shifts of CO, (3) 73*i*.
of Sn oxides, (7) 178*e*.
of zeolites, (6) 149*a*.
ir absorption, of molybdates and lanthanides, (1) 22*g*.
of refractory carbides, (8) 209*a*.
of silicate glasses, (9) 217*a*.
of silicates, (8) 190*h*.
of Na fluoroaluminates, (11) 281*a*.
of Na-Sn-SiO_2 glasses, (9) 217*b*.
intensities of trivalent lanthanides, (11) 282*e*.
"mirror," of CaO, (3) 74*a*.
of Ni in silicate glasses, (5) 106*d*.
Nb *L*-, in Nb carbides, (4) 95*g*.
NMR, of glasses, computer simulation, (4) 81*b*.
optical, and ESR, of glasses, (3) 56*i*.
of Nd^{3+} in $YAlO_3$, (7) 179*i*.
of Sm^{3+} ion, (3) 72*h*.
of Ti, V, Mo, and W oxides, (10) 260*d*.
of vanadyl ion in glasses, (9) 217*g*.
optical absorption, of Cr_2O_3, (5) 121*d*.
optical absorption, of W-V-phosphate glass, (8) 190*d*.
photoconductivity, of diamond, (5) 123*f*.
photoconductivity, of TiO_2, (3) 74*f*.
polarized reflectivity, of GeO_2, (6) 151*c*.
Raman, of *a*-quartz, (6) 149*d*.
of B_2O_3 glass, (11) 269*g*.
of B_2O_3 and glasses, (8) 191*e*.
powder, (2) 38*d*.
of SnO_2, (7) 179*j*.
of ZnS, (5) 123*d*.
vibrational, of hydroxyapatites, (1) 26*a*.
vibrational, of silicates, B (11) 284*g*.
X-ray emission, of Fe, electron microprobe study, (1) 23*d*.
Spectrochemical analysis. See *Analysis.*
Spectrography, applications, (9) 230*i*.
ir, of portland cement clinkers, (6) 129*h*.
mass, of silicate materials, (9) 230*j*.
sample, press for preparing, P (11) 278*g*.
Spectrometer, electron, use in glassmaking, (8) 205*f*.
mass, source and deflector for, P (1) 18*i*.
optical, P (9) 232*a*.
X-ray, double-crystal, P (5) 116*e*.
X-ray fluorescence, sample changer for, P (3) 70*g*.
Zeeman effect atomic absorption, (4) 93*d*.
Spectrometry, atomic absorption, B (1) 26*j*.
atomic absorption, for determining Mg in silicate materials, (3) 204*e*.
direct-reading, applications, (9) 230*g*.
effusion-mass, of BO^- and BO_2^-, (4) 96*f*.
electron impact, for gas phase chemical analysis, (2) 44*h*.
mass, of GaAs system, (5) 121*f*.
of O-18 in solid oxides, (5) 118*h*.
of vapor species from Al_2O_3, (11) 281*e*.
of volatilization in Pu-C system, (8) 203*b*.
Spectrophotometers, automatic line adjustment, P (6) 142*d*.
Spectrophotometry. See also *Photometry.*
absorption, of systems Cu^{2+}-Cl^-, Ni^{2+}-Cl^-, and Co^{2+}-Cl^-, (6) 144*j*.

Spectrophotometry *(continued)*
atomic absorption, of Ge in Au-Ge alloys, (11) 277*i*.
atomic absorption, Na and K determination, (4) 78*b*.
test apparatus, P (4) 93*h*.
of V, tetravalent, (4) 98*h*.
Spectroscopy, atomic absorption, B (2) 50*h*; P (6) 142*c*; (9) 230*j*.
auger, of glass surfaces, (2) 32*c*.
with electrodeless discharge tube, P (6) 142*c*.
electron, in glass research, (8) 204*i*.
electron, with monochromatized X rays, (8) 204*j*.
emission, microwave plasma burner as light source for, (8) 205*f*.
emission, spark source for, P (7) 174*b*.
F- and X-band, on Fe^{3+} in rutile, (5) 120*e*.
flame, spectral lines, B (1) 27*e*.
fluorescence, total reflection, P (1) 18*j*.
ir, B (4) 100*c*.
of glasses with trace impurities, (9) 217*c*.
of $Th(CO_3)_2$, (8) 211*a*.
ir absortion, B coordination No. in glasses by, (5) 106*c*.
of PCl_3·$FeCl_3$, (6) 151*i*.
photoelectron, (4) 93*g*.
Raman powder, for detecting stoichiometric variations in $LiNbO_3$ and $LiTaO_3$, (6) 146*i*.
of $SrTiO_3$, (5) 124*c*.
tunneling, of CdS junctions, (6) 152*g*.
of H_2O structure on SiO_2 surface, (6) 151*h*.
X-ray photoelectron, determination of valence band occupancy, (6) 146*j*.
Sphalerite, structure, thermal stability, (3) 76*a*.
Spheres, micro-, coating with pyrolytic C, P (5) 115*a*.
glass, evacuated, P (1) 5*b*.
oxide gel, from sols, P (3) 69*d*.
uniform, P (2) 69*f*.
radius distribution, calculation from circle radius, (1) 17*f*.
spherical particles, P (9) 229*a*.
Spheroidization, of tubular voids in Al_2O_3 crystals, (11) 282*f*.
Spinel. See also *Refractories*.
aluminomagnesia ceramics, aging, (8) 194*g*.
crystalline chalcogenide, growth, P (4) 88*b*.
crystals, fracture-resistant, P (11) 275*c*.
dense ceramics, in $MgAl_2O_4$-Al_2O_3 system, (1) 10*g*.
electrical conductivity and absorption in, (10) 258*j*.
formation from $LiFeO_2$ reactions, (7) 180*c*.
H $MgAl_2O_4$ crystals, Si on, P (8) 200*c*.
Fe_2MoO_4, magnetization in, (3) 72*f*.
layers, thickness ratio, (5) 125*d*.
Mg-Al crystals for circuits, P (3) 66*e*.
$MgAl_2O_4$, chemical preparation, (10) 258*c*.
from MgO and Al_2O_3, role of O, (5) 123*e*.
MgO-Al_2O_3, hot pressing, (8) 210*c*.
MgO-nAl_2O_3, Mg^{2+} and Al^{3+} ions in, (5) 121*g*.
MgO-Mg chromite bodies, P (1) 9*c*.
magnetic anisotropy induced, (1) 21*d*.
with magnetic ions, Curie points, (10) 261*c*.
$NiAl_2O_4$, $CuAl_2O_4$, and $ZnAl_2O_4$, cation distribution in, (9) 235*b*.
$NiAl_2O_4$ grown on sapphire, (10) 260*j*.
recombination of O atoms on, (1) 24*j*.
self-diffusion in, (10) 260*h*.
solid-state, in system MgO-Al_2O_3, (5) 124*a*.
spin configuration of magnetic ions in, (3) 75*j*.
thio-, In, magnetic properties, (10) 258*d*.
thio-, In, properties, (10) 260*a*.
Spraying. See also *Atomization*.
apparatus, mold, P (3) 59*j*.
atomizer wheel, P (5) 115*e*.
booth, P (1) 17*c*.
coating compositions, P (3) 54*i*.
deposition of Si powder structures, P (9) 222*h*.
with electronically controlled robot, (5) 105*a*.
electrostatic. See *Electrostatic processes*.
equipment, related to air pollution, (10) 254*e*.
finishing, in mirror production, (7) 158*d*.
flame, Al_2O_3, P (2) 31*h*.
powder and process, P (3) 69*f*.
powders, with Al_2O_3, P (1) 3*b*.
torch, P (3) 69*f*.
gun, nozzle for, P (8) 204*c*.
machine for porcelain decoration, (8) 198*i*.
marking glass, P (3) 58*h*.
nozzle, ceramic-lined, repairing, P (7) 158*a*.
plasma, of Al_2O_3, (3) 54*h*.
plasma arc, P (6) 131*c*.
powder, flame, ceramic clad, P (7) 157*j*.
spray dried press body, (6) 136*c*.
Sputtering, P (7) 172*g*.
amorphous solids, (2) 47*d*.
apparatus, P (6) 140*h*; P (9) 228*b*.
apparatus, cathode, P (8) 200*f*.
cathodic, for depositing GaP films, P (1) 15*b*.
for Fe oxide films, P (7) 170*e*; P (9) 228*e*.
method, P (4) 87*j*.
deposition of Si oxynitride, P (4) 90*j*.
diode, for applying film to substrate, P (9) 226*c*.
direct cathodic back, for etching, P (8) 201*f*.
for ferroelectric films, P (10) 253*d*.
for fission product distribution determination, (5) 114*h*.
of oxide films, P (4) 90*j*.
process, for SiO_2 and Si_3N_4 film, P (1) 14*i*.
rf, for insulating films, P (3) 67*g*.
$LiNbO_3$ films by, P (6) 139*d*.
method, P (10) 252*e*.
of quartz, P (2) 42*c*.
system, P (8) 202*f*.

Sputtering *(continued)*
rf apparatus, P (8) 202*f*; P (10) 252*e*.
cathode target for, P (4) 87*i*.
targets for, P (3) 67*j*.
system, P (9) 228*c*.
system, continuous, P (2) 39*i*.
TaN film resistors, P (9) 226*i*.
Stability, chemical, of sitalls, (9) 216*f*.
of ettringite on heating, (2) 31*c*.
of fiber spinning, (9) 218*d,e*.
morphological, aspects, (8) 207*j*.
of paragonite in system SiO_2-$NaAlSi_3O_8$-Al_2O_3-H_2O, (5) 124*e*.
relations, hydrothermal, of lepidolite, (4) 97*c*.
of semiconductor devices, P (4) 88*j*.
thermal, of corundum ceramics, (9) 221*j*.
of iodates of rare-earth elements and Y, (8) 211*a*.
of SiC, (3) 72*g*.
of SiC, basic polytypes, (3) 61*a*.
of wurtzite and sphalerite structures, (3) 76*a*.
of TiO, (5) 118*j*.
of transition metal carbides, (3) 75*b*.
of transition metal-Au composites, P (10) 253*g*.
of ZrO_2, cubic, (7) 180*h*.
Stabilization, of aluminous cements, P (8) 188*f*.
of verneuil boules of Ca_2SiO_4, (6) 132*h*.
Stains. See also *Color; Pigments*.
ceramic, quality control, (3) 61*j*.
Standards, ASTM, for chemical-resistant nonmetallics, B (6) 153*j*.
for glass textile products, (4) 81*f*.
on refractories, glass, and ceramic materials, B (10) 262*c*.
for cements, improvement, (8) 186*h*.
of clay materials, (11) 278*d*.
redox, comparison, (11) 278*b*.
SI units, magnetochemistry in, (7) 182*e*.
U.S. Voluntary Engineering, index, B (2) 51*a*.
Stannic oxide. See *Tin, oxide*.
Statistics, for checking grain-size of refractory batches, (8) 196*a*.
technology and, (7) 182*d*.
theories, of chemical reactions, (4) 95*c*.
Steatite. See *Talc*.
Steam. See *Moisture; Water*.
Steels. See also *Enameling metals; Iron*.
Ca ferrite for making, P (6) 135*d*.
casting, refractories for, (6) 134*h*.
electrical, refractory coatings for, P (9) 222*c*.
degassing, refractories in, (2) 36*e*.
enamels on, 3-year inspection, (7) 157*h*.
fatigue properties, (7) 157*h*.
grade, enameling, P (2) 31*j*.
and iron industry, refractories for, (6) 134*g*.
machining, ceramic cutting tools in, (10) 246*e*.
-making process, slagging in, P (6) 135*g*.
securing refractory nitride bodies to, P (9) 222*a*.
sheets, electrical, bonded core structure with, P (9) 215*j*.
sheets, glass coating for, P (3) 54*f*.
slag, handling, P (1) 3*a*.
stainless, thermal insulation for, P (5) 109*g*.
Stoichiometry, of Al_2O_3 thin films on Si, (5) 111*h*.
effects in growth of $GaAs_{1-x}P_x$ layers, (7) 181*b*.
limits in NiO and Fe_2O_3, (5) 124*g*.
non-, B (1) 28*b*.
in $BaTiO_3$, (11) 274*a*.
in fluorite oxides, (9) 238*e*.
intrinsic, in $Pb(Zr_{0.8}Ti_{0.8})O_3$, (5) 121*e*.
in metal oxides, B (10) 263*j*.
of Ag β-Al_2O_3, (8) 210*i*.
variations in $LiNbO_3$ and $LiTaO_3$, (6) 146*i*.
Stones. See also *Rocks*.
artificial, reducing shrinkage, P (8) 188*f*.
gem-, asteriated synthetic corundum, P (7) 175*j*.
materials, diffusion for improving, P (4) 81*e*.
Stoneware, bodies, microstructure, (6) 135*j*.
Strains, in ceramic materials, gages for measurement, (7) 173*j*.
of clay materials during firing, (2) 35*f*.
compressive, in bricks, (9) 220*e*.
effect on crystallization of vitreous Se, (11) 268*j*.
effects in diamond-type crystals, (5) 124*g*.
energies of disclination loops, (5) 124*h*.
rate, effect on work-hardening of LiF crystals, (6) 147*a*.
in Si epitaxial layers, detection, (10) 258*d*.
uniaxial, measurement by microstrain gage, (10) 255*b*.
Strength, of AlN-Y_2O_3, sintered, (2) 48*h*.
behavior of thermally shocked ZnO, (9) 238*g*.
bend, of glass rods, measurements, (7) 160*h*.
bending, of boxed mortar beam, (6) 128*a*.
bond, of portland cement concrete, (10) 241*g*.
bond, testing, P (4) 89*d*.
breakdown, of electrical refractories, (7) 164*j*.
of brick walls, (9) 220*h*.
of C fiber polyester composites, (7) 163*h*.
of C fibers, (2) 49*f*.
of C foam, P (4) 84*e*.
of cement, columns, (6) 130*a*.
compacts, (5) 103*e*.
effect of clinker cooling, (4) 78*e*.
effect of curing temp., (6) 128*e*.
effect of grinding, (4) 78*i*.
effect of mineral powders, (9) 214*g*.
hardened Al_2O_3, (6) 130*e*.
mortar, effect of slag, (4) 78*e*.
paste, effect of hydrates, (6) 128*e*.

Strength *(continued)*
of clay concrete, (9) 215*b*.
of ceramic crystals, press-forged, (3) 72*e*.
of compacts, effect of sintering, (10) 247*a*.
compressive, of concrete, (5) 103*a*, (6) 128*b*.
of concrete column, (6) 128*c*.
of concrete with fly ash, (6) 128*b*.
of MgO crystals, (10) 258*e*.
of concretes, dry mix, (6) 129*e*.
drying shrinkage effect, (6) 128*j*.
fundamentals, (4) 78*c*.
superdry mix, (6) 130*g*.
vacuum, (6) 130*a*.
variation, (6) 130*b*.
degradation, in Al_2O_3, (6) 152*a*.
of ferrite memory cores, (7) 167*g*, 168*d*.
flexural, of lightweight concrete, (6) 128*i*.
of glass container sections, (7) 158*d*.
of glass, crystallized, (5) 106*e*.
of glass fiber, (2) 32*g*; (3) 57*i*; (8) 191*h*; (9) 217*d*.
of graphite or C articles, P (2) 37*c*.
of high-Al_2O_3 cement concrete, (10) 242*a*.
high materials, P (8) 201*g*.
hot, of MgO, (2) 35*j*.
impact, of Al_2O_3 composites, (6) 131*b*.
impact, of ceramic materials, (10) 259*e*.
of Fe-graphite materials, (10) 246*e*.
of kaolin briquet, additive effect, (8) 195*c*.
law for concrete, (8) 187*g*.
loss of brittle ceramics, (10) 261*e*.
of materials, B (11) 284*a*.
mechanical, of firebricks, (2) 36*c*.
mechanical, of glass articles, P (2) 34*d*.
mortar, of CaS and alite, (4) 78*h*.
of plaster, effect of gypsum, (3) 53*j*.
of porcelain and oxide bodies, (10) 248*f*.
porosity-, of cellular concrete, (5) 104*d*.
of porous ceramic, polymer-impregnated, (4) 85*e*.
of porous materials, (5) 104*c*.
of portland cement clinker, (9) 214*f*; 215*a*.
of portland cement mortar, (4) 79*a*.
of portland cement paste, (4) 78*d*.
of powder aggregates, (10) 248*h*.
properties of Ni-base materials, (10) 260*e*.
of refractory-compound powders, (10) 259*j*.
relation to elastic modulus in BeO-SiC, (1) 25*g*.
shear, of concrete beams, (10) 241*h*.
of lightweight concrete, (6) 129*f*.
of pyrophyllite, (3) 75*d*.
of Na borosilicate glass-Al_2O_3 composite, (1) 3*d*.
splitting, of concrete, (10) 241*h*.
of strengthened glass, (3) 56*d*.
of S-glass fiber, (11) 269*j*.
tensile adhesive, in wall tiles, (7) 164*i*.
and compressive, of ceramics, (1) 17*h*.
of glasses, (5) 105*g*.
testing, of circular glass plates, (1) 3*f*.
testing of natural rocks, (6) 142*h*.
of TiO_2 and Al silicate under stresses, (8) 210*j*.
-vs-grain size, for ceramics, (6) 151*j*.
of wall ties, (9) 221*d*.
Strengthening, Al_2O_3, polycrystalline, (2) 49*h*.
by quenching, (5) 111*c*.
substrates, P (7) 170*d*.
bodies of vitreous material, P (10) 245*j*.
chemical, of glass articles, P (2) 33*g*.
concrete reinforced slabs, (6) 130*e*.
glass, P (1) 5*f*.
articles, P (9) 219*i*.
articles, chemically, P (4) 82*b*.
articles, photochromic, P (8) 193*a*.
in oil bath, P (5) 107*e*.
of thin dimension, P (8) 193*g*.
ion exchange, glass article, P (2) 35*c*.
ion exchange, of glasses, P (2) 34*i*.
metals by refractory fibers, (11) 271*h*.
precipitation, of MgO, (2) 49*a*.
Ni-Cr allov, (10) 247*j*.
vitreous materials, P (8) 204*a*; P (11) 270*f*.
Stresses, activation volume-, in UO_2, (5) 114*i*.
axial, in clad glass fibers, (1) 3*c*.
buildup in glass by uv radiation, (3) 55*e*.
distribution, around crack in materials, (10) 261*f*.
in brick wall, (9) 220*j*.
effect of end condition of concrete, (6) 128*b*.
of enamels, relation to properties, (8) 188*j*.
in float glass, (8) 191*i*.
in glass, effect of ultrasonic waves, (11) 269*i*.
gradient, ionic diffusion in, (1) 26*a*.
inherent, in concrete, evaluation, (6) 128*h*.
law for concrete, (8) 187*g*.
-measuring apparatus, X-ray, P (5) 116*h*.
measurement, diffraction line shift, (7) 173*e*.
model, for magnetic oxide films, (2) 49*i*.
profile, of strengthened glass, (3) 56*e*.
pulses, collision with fracture obstacles and dynamics, (6) 145*a*.
relaxation of B_2O_3 glass, (6) 132*j*.
residual, in quenched Al_2O_3, (3) 72*g*.
shear, calculation, nomogram for, (5) 116*a*.
in SiO_2 films, (2) 39*d*.
/strain factors in furnace life, (1) 19*b*.
stressing, catalyst supports for, P (5) 117*j*.
tensile, in Al_2O_3, (1) 25*i*.
thermal, effect on refractive index in clad fibers, (8) 190*d*.
in glass-to-metal seals, (7) 160*j*.
in vitreous china, (4) 85*f*.
in wall tiles, (4) 85*d*.
Strontium, -$BaNb_2O_6$, ir radiation in, (5) 123*a*.
$BaNb_2O_6$ plates, electrooptic effect in, (3) 74*f*.
fluoride and CaF_2 photochromic compositions, P (11) 274*e*.

Strontium *(continued)*
fluorides, crystalline miscibility in CdF_2, (10) 258*g*.
nitrate, ir and Raman spectra, (7) 178*a*.
nitriding, and SrN, (4) 99*b*.
orthothiogermanate, crystal structure, (4) 95*i*.
oxide, additive coloration, (5) 118*e*.
pyrophosphate, adhesive in screens, P (4) 91*a*.
pyrovanadate, β-, crystal structure, (8) 208*j*.
$Sr_xBa_{1-x}Nb_2O_6$, Raman scattering by, (5) 123*d*.
Sr_2GeS_4, structural evolution, (4) 95*i*.
$SrTiO_{3-x}$, superconductivity in, (5) 123*j*.
$SrZnP_2O_7:UO_2^{2+}$, fluorescence and energy transfer in, (2) 47*h*.
systems. See *Systems*.
titanate, attenuation of sound in, (6) 145*f*.
Cr^{3+} fluorescence in, (5) 125*j*.
$:Cr^{3+}$, optical line shifts in, (5) 119*j*.
crystals, attenuation in, (6) 148*e*.
effective masses in, (5) 120*e*.
elastic constants, (4) 98*b*.
fluorescence, (7) 177*g*.
force constants in, (4) 96*h*.
lattice absorption in, (6) 149*b*.
Ni-O vacancy pair in, (6) 150*d*.
nonlinear coloration in, (6) 150*c*.
110°K phase transition in, (5) 121*g*.
photoluminescence in, (5) 122*d*.
powders, high-purity, P (6) 139*g*.
reaction with Zr, (1) 24*c*.
spectroscopy, (5) 124*c*.
theory of polaron transitions, (5) 125*a*.
thermal conductivity, (3) 75*j*.
uranates, research, (1) 16*e*.
zirconate, creep behavior, high-temp., (4) 96*j*.

Structural clay products. See also *Brick; Tile*.
black cores in stoneware pipes, (11) 271*d*.
blast furnace slag in, (1) 6*a*.
composite, P (4) 83*i*.
drying, (4) 83*e*.
long hollow, extruding, P (9) 221*b*.
rationalization of drying, (7) 174*f*.
specific surface of Dutch clays, (4) 83*g*.

Structural clay products industry, air pollution problems, (9) 220*g*.
gas firing in, B (10) 263*e*.
quality control in, (4) 83*d*.
shuttle kiln in, (6) 134*a*.
strong markets, (11) 271*a*.

Structural materials. See *Aggregates; Brick; Building materials; Cement; Concrete; Enameled ware; Glass; Insulation, thermal; Masonry; Structural clay products*.

Structure, of alkaline earth aluminoborate glasses, (6) 132*g*.
analogy, of silicates and germanates, (7) 181*e*.
analysis, of silicate system, (9) 238*h*.
anion and cation defect, in Mg fluorogermanate, (10) 258*b*.
band, of ReO_3, (5) 118*i*.
of TiO, (5) 118*j*.
in V_2O_3, (5) 118*i*.
of basalt melts during cooling, (6) 151*j*.
of B oxide, vitreous and liquid, (3) 75*c*.
of C, deposited below 1600°C, (5) 115*b*.
effect of hydrocarbon pyrolysis, (8) 196*b*.
-SiC alloys, codeposited pyrolytic, (1) 25*a*.
of carbonate cements, (1) 2*c*.
of Cs borate glass and crystalline compounds, (7) 160*g*.
of chalcogenide glasses, (9) 218*g*.
of concrete hardened for 40 years, (8) 187*h*.
of crystals. See *Crystals* and specific types.
disperse, compactibility, (2) 48*i*.
effect on properties of cast stone, (8) 195*e*.
elasticity, and plasticity of matter, B (3) 76*h*.
electronic, of CaO, (6) 147*d*.
of EuO, EuS, EuSe, and GdS, (6) 150*h*.
in semiconducting alloys, (6) 147*d*.
of ferrites after sintering powders, (9) 223*h*.
of fireclay at high temps., (11) 271*g*.
formation in fireclay masses, (2) 50*b*.
of Ge oxides, (7) 178*e*.
of glass, (3) 57*c*; B (5) 126*b*.
fibers, (3) 57*i*.
inorganic, B (2) 52*e*.
of grain boundaries, with computer, (5) 118*i*.
of inorganic material, SEM study, (9) 231*f*.
internal, of C fibers, (5) 119*f*.
of Fe-graphite materials, (10) 246*e*.
of $FeO-P_2O_5$ glasses, (9) 218*i*.
of $55FeO-45P_2O_5$ glass, (8) 189*d*.
isotypes, of hematite, corundum, calcite, and quartz, (1) 25*j*.
layered, of plate glass, (7) 159*j*.
of $Pb_{3-x}(Ti,Ta)_2O_{7-y}$, (4) 98*i*.
of Li Al silicates, (11) 282*b*.
of Mn silicides, defect, (2) 50*a*.
of materials, electron microscopy, B (10) 263*g*.
micro-, of Al_2O_3, plasma-arc-sprayed, (1) 18*g*.
of $BaTiO_3$, doped and undoped, (1) 11*d*.
of CaF_2, during sintering, (2) 47*g*.
of Ca silicate hydrates, (4) 79*b*.
of C-TiC alloys, (10) 260*c*.
of cellular concrete, (4) 79*d*.
of cements pastes, (2) 31*b*; (4) 79*e*.
of chrome-magnesite refractories, (11) 271*d*.
of chrysotile asbestos, (9) 236*j*.
of crystallized glass, (5) 106*e*.
of fuel material, (3) 68*d*.
of gypsum pastes, (5) 103*d*.
in hematite, (3) 75*e*.
of kilchoanite, synthetic, (1) 23*c*.

Structure, micro- *(continued)*
of $MgO-Li_2O-Al_2O_3-SiO_2-TiO_2$ glass-ceramic, (7) 160*a*.
of periclase and C, (8) 195*a*.
of periclase-spinelide refractories, (7) 163*g*.
and pore, of clays, (5) 121*j*.
of portland cement, hydrating, (5) 103*g*.
of stoneware bodies, (6) 135*j*.
of supersulfated cement, (4) 79*e*.
of ThO_2, Y_2O_3-doped, (7) 179*g*.
of TiO_2 enamels, (1) 2*i*.
and ultra-, of $B_2O_3-BaO-Fe_2O_3$ glass, (11) 268*h*.
of V phosphate glasses, (4) 80*g*.
of mordenite, H_2 forms, (3) 73*a*.
of $MTiO_4$ and MTi_2O_6, (1) 25*i*.
of Ni in silicate glasses, (5) 106*d*.
of peridotite, alpine-type, (1) 20*i*.
phase, of $Li_xV_2O_5$ bronzes, (6) 149*i*.
of porcelain and oxide bodies, (10) 248*f*.
of porcelain, rapid firing effect, (7) 165*h*.
properties, of CoAs, (11) 282*g*.
of KCl, (5) 125*c*.
in system $BaCeO_3-Ba_2(CeTa)O_6$, (11) 282*g*.
of Re oxide, new, (10) 260*f*.
of RuO_2 thick films, (8) 199*g*.
of rutile surfaces, (3) 73*j*.
of semiconductors, amorphous, (6) 152*e*.
shear, based on MoO_3, (10) 259*c*.
shock-wave, in porous solids, (7) 180*c*.
of silicate glaze, by ir reflection, (5) 111*e*.
of silicate skeletons, in glasses, (2) 32*b*.
of silicates, B (11) 284*g*.
of silicates with octahedra chains, (1) 25*j*.
of SiO, (2) 50*b*.
of Ag β-Al_2O_3, (8) 210*i*.
of $NaNbO_3(T_2)$, (10) 261*f*.
of $Na_2O-MgO-SiO_2$ glass, (11) 269*i*.
sub-, of transition metal carbides, (10) 261*a*.
super, NaCl, new type, (10) 258*c*.
of system $PbO-B_2O_3-Fe_2O_3$, (6) 147*f*.
of $TeCl_4 \cdot 2TlCl$, $SeCl_4 \cdot 2TlCl$, and $FeCl_2 \cdot 2AlCl_3$, (6) 152*c*.
of Sn oxides, (7) 178*e*.
of Ti_nO_{2n-1} ($4 \leq n \leq 10$) phases, electron microscopic study, (3) 73*a*.
of trapped-hole center in MgO, (5) 124*i*.
of trapped-hole centers in borate glasses, (7) 158*j*.
of CaA, changes in, (6) 152*a*.
of CaS, Cr-doped, (7) 157*g*.
of ZrO_2 in $CaO-ZrO_2$ system, (4) 98*j*; (6) 152*c*.
of ZrO_2, change at high temps., (8) 208*a*.

Substrates, acoustic surface-wave beam diffraction on, (7) 166*c*.
Al_2O_3, orientation in, (11) 274*e*.
applying plurality of coatings to, P (6) 137*f*.
bonding metal pattern to, P (10) 251*a*.
$CaO-Al_2O_3-SiO_2$, for thin-film circuits, P (2) 39*e*.
cellulosic fibrous, carbonizing, P (3) 61*c*.
ceramic, decal metalization, P (2) 39*j*.
or glass film on, P (3) 65*e*.
for microcircuits, (9) 223*j*.
coating, with $B_2O_3-SiO_2$ glass, P (6) 133*b*.
with metal oxides, P (6) 138*j*.
by vapor deposition, P (1) 13*b*.
conductive coating on, P (11) 275*a*.
film on, by gas phase, P (7) 170*e*.
fluorescent high Al_2O_3 ceramic, (10) 249*d*.
forming crystals or wafers in, P (4) 88*h*.
glazed ceramic, camber measurements, (10) 249*b*.
graphite pallet and mask for, P (10) 250*f*.
growing semiconductor films on, P (9) 226*i*.
growth of IIB-VIA compounds on, P (9) 225*a*.
holder, apparatus for supporting, P (8) 200*c*.
insulating, coating, P (9) 226*d*.
insulating, thin films on, P (10) 251*a*.
metal plating, P (3) 66*c*.
metallic oxide film on, P (9) 226*d*.
microelectronic interconnection, P (1) 13*j*.
molding forms on, P (10) 251*i*.
nonconductive, Ni plating on, P (5) 112*j*.
nucleation on, (8) 199*j*.
photoconductive layers on, P (1) 13*e*.
preformed holes in, positional deviations, (7) 167*d*.
refractory, metal oxide coatings on, P (8) 193*c*.
removal of organic films from, P (9) 227*c*.
surface, applying film to, P (9) 226*c*.
temp. variations, P (3) 66*b*.
thin-film deposition on, P (7) 169*f*.
of thin magnetic films, treating, P (9) 227*a*.
TiC coatings on, P (11) 272*f*.
YIG films on, by CVD, (11) 274*i*.

Sulfates, alkaline-earth metal, P (9) 225*c*.
and bisulfate melts and glasses, (2) 32*f*.
control in NH_3 flue gas desulfurization, P (10) 257*j*.
double, crystallography, (9) 234*h*.
mortar resistance to, determination, (6) 129*d*.
removing from $MgCl_2$ brines, P (10) 257*g*.
resistance of hydrogarnets, (4) 79*b*.
systems. See *Systems*.

Sulfides, electrochemical activity, (5) 120*h*.
in Fe-Mn alloys, (6) 152*e*.
oxy-, Eu^{3+} in, fluorescence spectrum, (4) 96*j*.
sulfur, in slag glass, (8) 190*h*.

Sulfur, activity coeff. in Fe-Cr-S alloys, (6) 146*h*.
determination by combustion method, (7) 173*h*.
diffusion in CdTe, (4) 98*j*.
dioxide, apparatus for removing, P (2) 43*h*.
catalytic reduction in Al_2O_3, (11) 280*d*.

Sulfur, dioxide *(continued)*
monitoring, (10) 255*h*.
monitoring network, (9) 231*j*.
reactivity with calcined samples, (7) 181*h*.
removing from BF_3, P (3) 71*d*.
removing by CO reduction, (10) 256*c*.
removing from flue gases, (11) 279*i*.
removing from stack gases, (4) 92*b*; P (10) 255*d*.
solid oxides as sorbents of, (6) 143*a*.
electron microprobe analysis, (4) 93*e*.
liquid, electrical resistance, (3) 62*g*.
oxides, attack on refractories, (1) 8*a*.
problem in fuels, (5) 117*a*.
systems. See *Systems*.
trioxide, effect on cement hydration, (6) 129*i*.
effect on sintering cement clinker, (9) 214*h*.
for refining Be ores, P (7) 176*a*.
solubility in Na phosphate, (5) 123*c*.

Sulfuric acid, from SO_2 content in flue gases, (11) 279*i*.

Superconductivity, intercalation complexes, layered, (4) 96*j*.
in $SrTiO_{3-x}$, (5) 123*j*.
superconducting, bodies, hollow, P (5) 113*i*.
superconducting, Nb-Ti material, P (11) 275*c*.

Superconductors, P (10) 253*c*.
composite, P (7) 168*a*.
containing flux traps, P (10) 253*f*.
high-temp., first ternary system, (8) 209*g*.
materials, P (9) 226*e*.
materials, properties, (10) 249*g*.
physics and metallurgy, B (2) 51*i*.
tubular assembly, P (3) 65*g*.

Supersonics. See *Sonics*.

Surface, area of ceramic clays, (11) 281*i*.
measurement, (6) 130*d*.
measurements, industrial, (11) 277*j*.
of Ontario limestones and dolomites, (7) 181*e*.
in K fixation, (9) 236*d*.
coercivity in magnetic oxide platelets, (5) 125*d*.
Fermi, of ReO_3, (5) 118*i*; (6) 150*e*.
finish, of Al_2O_3 ceramics, (2) 29*h*.
finishing, and ceramic machining, B (10) 264*j*.
interface, stress distribution around crack perpendicular to, (10) 261*f*.
layers, in phase-separated glassware, (11) 269*b*.
nonconducting, preparation for electron microscopy, (7) 173*b*.
nuclei growth on, (6) 144*i*.
profile change measurement, P (2) 45*c*.
properties, of semiconductors, B (3) 76*j*.
properties, of CaS pastes, hydrated, (5) 103*j*.
raw material, effect on dye adsorption, (1) 19*h*.
solid, analyzing, P (6) 142*f*.
specific, area, of porous solids, (2) 44*g*.
areas of powders, measurement, (9) 230*f*.
of Ca silicate hydrates, (9) 213*j*.
of Dutch structural clays, (4) 83*g*.
of ferrite powders, (9) 223*i*.
of powders, measuring, P (6) 142*f*.
states, measuring, P (8) 206*a*.
treatment of glass-ceramics, P (9) 220*b*.
treatment, of porous bodies, P (1) 10*h*.

Suspensions. See also *Slips*.
classifying in liquid or solid, P (10) 255*g*.
clays. See *Clays*.
colloidal, of chrysotile asbestos, P (7) 164*c*.
liquid, classifying, P (3) 71*h*.
TiO_2 and alum mud, settling in H_2O, (5) 111*b*.
TiO_2 seed, P (4) 94*g*.

Swelling, effect on U_3Si, (6) 140*j*.
and gas release in UO_2, (5) 114*g*.
temp.-dependent, in U_3Si, (1) 16*f*.

Switches, analog, P (9) 225*h*.
SbSI-SnO_2 heterostructure, mode for, (3) 63*i*.
barrier layer, P (2) 39*c*.
coplanar semiconductor structure, P (3) 64*e*.
electronic, P (1) 12*a*; P (7) 168*g*.
electrooptic, using Y-plate of $LiNbO_3$, (3) 62*i*.
fast, P (10) 250*c*.
four-layer, P (9) 225*h*.
magnetic, P (9) 225*i*.
magnetosensitive semiconductor, P (2) 40*i*.
ovonic, photoconductivity in, (6) 137*a*.
with piezoelectric resonator, P (2) 42*h*.
reed, sealing with ir energy, P (8) 193*f*.
semiconductor, P (2) 39*i*; P (11) 275*h*.
barrier-free, P (2) 39*c*.
controllable, P (7) 168*c*.
element, P (8) 202*c*.
thermally tripped, P (8) 202*g*.

Switching, bistable, of ZnO thin film diodes, (3) 62*g*.
of chalcogenide glasses, (6) 132*a,d*.
in chalcogenide semiconductors, (6) 145*c*.
condenser element for ac, P (9) 228*d*.
device, dry reed, P (2) 34*i*.
device, piezoelectric, P (7) 170*c*.
element, memory and nonmemory, P (4) 88*c*.
energy-controlled, in system Te-As-Ge-Si, (6) 147*f*.
phenomena, in semiconductors, (6) 147*c*.
in semiconducting glass films, (6) 132*j*.
in semiconducting glasses, (6) 132*c*.
in semiconductors, amorphous, (6) 152*g*.
in Zr-ZrO_2-Au junctions, (6) 145*c*.

Symmetry, of crystals. See *Crystals*.

Systems. See also *Equilibrium studies; Phase diagrams*.
of alkali metal carbonates, (5) 124*j*.

Systems *(continued)*
alkali metal-O, (7) 176*e*.
alkali metal salt-V_2O_5, reactions in, (5) 121*e*.
Al-Al oxide-metal, electron tunneling in, (6) 148*g*.
Al-B, phase diagram, (5) 122*c*.
Al_2O_3-Al_4C_3, (3) 75*h*.
Al_2O_3-Cr_2O_3 and Al_2O_3-Cr_2O_3-Fe_2O_3, (2) 47*e*.
Al_2O_3-Cr_2O_3, electrical conductivity, (5) 125*e*.
Al_2O_3-Cr_2O_3, sintering and grain growth, (5) 125*h*.
Al_2O_3-Cr_2O_3, transfer processes in, (1) 26*d*.
Al_2O_3, Cr_2O_3, and Sm_2O_3, surface tension, density, and vol change on melting, (7) 181*b*.
$(1-x)Al_5LiO_8$-$xGeAlLiO_4$; $(1-x)Fe_5LiO_8$-x"$GeFeLiO_4$"; x"$Ge_5Li_6O_{12}$-$GeZn_2O_4$, (8) 211*a*.
Al_2O_3-P_2O_5-H_2O, phase composition, (9) 234*g*.
Al_2O_3-P_2O_5-H_2O, solidification products in, (9) 238*c*.
Al_2O_3-SiO_2, diffusion and reaction in, (11) 281*e*.
Al_2O_3-SiO_2, equilibria in, (1) 22*b*.
Al_2O_3-Na_2O, β and β'' Al_2O_3 in, (11) 282*a*.
Am-O, (1) 15*f*.
As-Se-Te, semiconductors in, conduction, (3) 62*e*.
As_2Se_3-Tl_2Se, (8) 211*d*.
Ba-$BaCl_2$, Ba-$BaBr_2$, and Sr-$SrCl_2$, densities of melts in, (11) 282*c*.
$BaCeO_3$-$Ba_2(CeTa)O_6$, properties, (11) 282*g*.
BaF_2-LaF_3, for electroslag melting, (4) 95*c*.
BaF_2-YF_3, phase relations in, (11) 281*j*.
BaO-B_2O_3-Nb_2O_5 and $BaNb_2O_6$-$SrNb_2O_6$, (10) 261*d*.
BaO-TiO_2 system KF-CoF_2 as model of, (1) 25*j*.
BaO-TiO_2-Al_2O_3, $BaO \cdot 4TiO_2 \cdot Al_2O_3$ identification in, (2) 48*f*.
binary, of simple fluorides, (6) 146*e*.
binary and ternary of I type, (8) 210*a*.
Bi-Pb-Te, (9) 239*d*.
Bi_2O_3-TeO_2, at 750°C, (6) 152*i*.
B-C, (5) 124*b*.
B-C-Si (11) 283*b*.
B_2O_3-PbO-Al_2O_3, decomposition in, (3) 75*a*.
B_2O_3-Tl_2O, (4) 99*g*.
BP-S, heterogeneous equilibria, (8) 209*f*.
Cd-Ge-As, phase diagram, (5) 122*c*.
CdSb-CdTe, (9) 239*f*.
$CdCl_2$-MCl, vapor pressure over molten salts in, (8) 211*f*.
CdF_2, CaF_2-CdF_2-PbF_2, and CdF_2-ZnF_2, phase equilibria in, (1) 23*e*.
$CdGe(As_xP_{1-x})_2$, kinetics of dissolution, (7) 178*b*.
$Ca_2Al_2SiO_7$-$CaLaAl_3O_7$, solid solution in, (8) 210*d*.
$CaAl_2Si_2O_8$-SiO_2-H_2O, *P-T* stability in, (1) 24*f*.
$CaCl_2$-MCl-MBr-$CaBr_2$ (M is Na, K, and Rb), enthalpies of mixing in, (11) 281*i*.
$CaCO_3$-$SrCO_3$-$BaCO_3$, $CaCO_3$-$SrCO_3$-$PbCO_3$, and $CaCO_3$-$BaCO_3$-$PbCO_3$, (9) 238*j*.
CaF_2-BaF_2, phase diagram, (8) 208*f*.
CaF_2+CaO+Al_2O_3, liquids in, electrical conductivity, (6) 147*f*.
CaF_2-CaO-SiO_2, activity in, (6) 144*j*.
CaF_2-LaF_3 for electroslag melting, (4) 95*c*.
$Ca(OH)_2$-(Ge,Sn,Pb,Ti,Zr,Mn)O_2-H_2O, binding properties, (9) 233*h*.
CaI_2-$CaCl_2$, CaI_2-CaF_2, and CaI_2-$MgCl_2$, (4) 97*a*.
Ca_3N_2-Ge_3N_4, (4) 99*j*.
CaO-Al_2O_3-Fe-Fe_2O_3, phase relations, (2) 50*e*.
CaO-Al_2O_3-SiO_2, Al_2O_3 in cement clinker, (1) 2*c*.
CaO-BaO-WO_3, phase equilibria in, (11) 281*j*.
CaO-2CaO SiO_2-CaF_2, (1) 25*h*.
CaO-Cr_2O_3-O, phase transformation in, (3) 75*b*.
CaO-IrO_2-Ir, phase relations in, (10) 260*h*.
CaO-Fe oxide-Ti oxide, phase relations, (1) 24*a*.
CaO-iron oxide-TiO_2, phase relations, (1) 23*i*.
CaO-MgO-Al_2O_3-SiO_2, phase equilibrium diagrams, (1) 8*b*.
CaO-MgO-B_2O_3-SiO_2, phase relations in, (1) 7*g*.
CaO-MgO-B_2O_3-SiO_2, (2) 48*e*.
CaO-MgO-SiO_2, effect of CaO solubility, (2) 49*c*.
CaO-MgO-TiO_2, phase equilibria in, (1) 25*c*.
CaO-Nd_2O_3-Al_2O_3, new phases in, (2) 48*c*.
CaO-P_2O_5-$CaSO_4$-H_2O, supersaturation, (7) 176*h*.
CaO-Pt, phase relations in, (9) 237*c*.
CaO-ZrO_2, ZrO_2 in, (6) 152*c*.
CaO-ZrO_2, ZrO_2 in, structure and thermomechanical properties, (4) 98*j*.
between 2CaO·SiO_2 and analogs, (4) 79*f*.
2CaO·SiO_2-3CaO·B_2O_3, study, (3) 75*g*.
of carbonates and tungstates of K and Na, (5) 124*i*.
CeO_2-ZrO_2, solid state phase relations, (4) 98*d*.
CeO_2-ZrO_2-Al_2O_3, solid state phase relations, (4) 98*f*.
CeO_2-ZrO_2-CaO, phase relations, (4) 95*e*.
CeO_2-ZrO_2-CoO, fluorite phase in, (11) 282*j*.
CeO_2-ZrO_2-MgO, phase relations, (4) 95*f*.
Cs_2SO_4-Cs_2WO_4, DTA studies, (1) 21*a*.
chloride and fluoride, BeO solubility in, (8) 210*e*.
chlorides, of Cs, Tl, and Pb, (5) 118*h*.
of Ga, Al, and K, (5) 124*d*.
of K, Sr, and Pb, (5) 124*e*.
clay-water. See *Clays*.
Cu^{2+}-Cl^-, Ni^{2+}-Cl^-, and Co^{2+}-Cl^-, adsorption spectrophotometry, (6) 144*j*.

Systems *(continued)*
disperse, rheological properties, (7) 180*g*.
Dy_2O_3-Nb_2O_5, study of Nb_2O_5 regions, (2) 50*d*.
of fluorides and chlorides of K, Ca, and Ba, (5) 123*a*.
of fluorides, iodides, and carbonates of Na and K, (5) 124*e*.
fusible, DTA, (6) 142*c*.
Gd_2O_3-Nb_2O_5, study of Nb_2O_5 regions, (2) 50*d*.
Ga-As-Te-Ge, semiconducting materials in, (6) 145*j*.
Ga-As-Zn and Ga-P-Zn, liquidus isotherms, (6) 149*g*.
Ga-In-As, interaction, (8) 209*b*.
Ga-In-As, liquidus isotherms in, (9) 236*d*.
GaAs, mass spectrometry, (5) 121*f*.
$GaCl_2$-$InCl_2$, (8) 211*e*.
$GaCl_3$-$AlCl_3$-RbCl, (5) 124*e*.
$GaCl_2$-$SrCl_2$, (8) 211*e*.
GaP-InP, solidus boundary in, (9) 238*d*.
glass. See *Glass*.
Hf-Te, nonmetal-rich region, (11) 281*g*.
HfO_2-Y_2O_3, (8) 211*f*.
H_2-H_2O flow, etching GaAs in, (9) 239*d*.
In,Mg,K‖Cl, (5) 124*f*.
of InCl and chlorides of Ca, Mn, and Te, (5) 118*j*.
InCl-TlCl-$AlCl_3$, thermal study, (8) 211*b*.
In_2S_3-NiS, interaction in, (2) 50*d*.
Fe-B, phase diagram, (10) 258*f*.
Fe-Mn-S-O, phase relations in, (6) 152*e*.
Fe-O-S, inclusion formation in, (6) 148*f*.
$FeCr_2O_4$-Fe_3O_4 ($Fe^{2+}Fe^{3+}Cr_{2-x}O_4$), (4) 95*j*.
$FeTi_2O_5$-Ti_3O_5, solid solution in, (3) 75*h*.
$LaAlO_3$-$CaTiO_3$, solid solutions in, (9) 235*d*.
La_2O_3-Yb_2O_3, high-temp., phase diagram, (10) 259*a*.
PbO-B_2O_3-Fe_2O_3, electrical conductivity and structure, (6) 147*f*.
PbSe-MnSe, (9) 239*f*.
PbS-CdS, subsolidus relations in, (4) 99*e*.
PbS-Cu_2S-FeS-Na_2S, (5) 124*g*.
$PbTiO_3$-$La_{2/3}TiO_3$, oxidation-reduction in, (3) 63*a*.
$Pb(Zn_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$, (8) 209*c*.
liquid metal-nonmetal, thermochemical properties, (6) 141*j*.
Li,K,Ba‖F,Cl, (8) 211*g*.
Li-V-W-O, crystal chemistry of phases in, (6) 145*h*.
$LiNbO_3$-$LiTaO_3$ solid solution, ^{93}Nb NMR, (7) 179*d*.
Li_2O-B_2O_3-GeO_2, (6) 150*h*.
MCl+$ZnCl_2$, electrical conductance, (6) 147*d*.
MF_2-TlF_2 (M=Ca, Sr), (4) 99*d*.
M'O_2-M"$_2O_5$, electrical conduction, (11) 281*h*.
Mg-Ti-Fe-O, crystal chemistry, (5) 119*b*.
Mg-Ti-Fe-O, solid solutions in, (1) 25*g*.
$MgAl_2O_4$-Al_2O_3, spinel ceramics in, (1) 10*g*.
MgF_2-LaF_3 for electroslag melting, (4) 95*c*.
MgO-Al_2O_3, solid-state spinel in, (5) 124*a*.
MgO-B_2O_3, phase relations in, (11) 282*b*.
MgO-CaO-SiO_2, solid solubility in, (1) 25*b*.
MgO-Fe_2O_3, diffusion and reactions in, (5) 119*c*.
MgO-ThO_2-B_2O_3, (2) 48*d*.
MgO-ZrO_2-SiO_2, phase equilibria, (1) 23*f*.
Mn-Ti-Fe-O, solid solutions in, (1) 25*g*.
metal-Al_2O_3-Si, photoemission measurements, (7) 178*a*.
Mo-Ti-C, phase equilibria in, (10) 260*g*.
Mo-W-B, (10) 261*c*.
Mo-W-O, Mo_8O_{14} and $Mo_{17}O_{47}$ structure, (4) 96*i*.
$NiFe_2O_4$-BaO-B_2O_3, crystal growth in, (8) 208*h*.
NiO-α-Fe_2O_3, quantitative phase analysis, (11) 277*f*.
NiO-Nb_2O_5, phase composition, (11) 281*i*.
Nb-C, vaporization, (4) 99*i*.
Nb-N-O, (6) 152*j*.
NbF_5-PbF_2, (10) 261*g*.
Nb_2O_5-MoO_3 and Ta_2O_5-MoO_3, phases in, (11) 281*d*.
N+Ta, absorption kinetics, (3) 72*c*.
Pu-C, volatilization in, (8) 203*b*.
Pu-Cr-N, phase behavior in, (6) 140*j*.
$PuMoO_4$—Li or Na molybdate, Scheelite structure phases in, (10) 260*g*.
$K‖CO_3$,SO_4,CrO_4, (8) 211*g*.
K,Cs‖Cl,I, (5) 124*f*.
K+Rb and Rb+Cs alloy, phase equilibria, (6) 151*f*.
K_3AlF_6-Li_3AlF_6, phase diagrams, (4) 99*c*.
$KClO_4$-$RbClO_4$-H_2O, $KBrO_3$-$RbBrO_3$-H_2O, and KIO_3-$CsIO_3$-H_2O, solubility in, (3) 75*h*.
KF-CoF_2 as model of system BaO-TiO_2, (1) 25*j*.
$KNbO_3$-KMF_3 (M=Mg,Mn), (2) 50*c*.
K_2O-ZrO_2-SiO_2, ternary compounds, (9) 239*b*.
PTOT, structures in, (7) 181*g*.
Re-B, phase diagram, (10) 260*f*.
Re-O, at high pressure, (10) 260*f*.
Rb_3AlF_6-Li_3AlF_6, phase diagrams, (4) 99*c*.
Rb_2BeF_4-Na_2BeF_4, (11) 283*d*.
$RbClO_4$-$CsClO_4$-H_2O, $RbBrO_3$-$CsBrO_3$-H_2O, and $RbIO_3$-$CsIO_3$-H_2O, solubility in, (3) 75*h*.
Sm-B, phase behavior in, (10) 260*f*.
Sm_2O_3-Nb_2O_5, study of Nb_2O_5 regions, (2) 50*d*.
silicate, B (8) 212*g*.
silicate, structural analysis, (9) 238*h*.
Si-O-N, (6) 151*e*.
Si-SiO_2, interface, (4) 99*c*.
SiO_2-Al_2O_3-CaO, quantitative analysis, (11) 278*h*.
SiO_2-Al_2O_3-CaO-MgO, melting points, (9) 233*j*.

Systems *(continued)*
SiO_2-$NaAlSi_3O_8$-Al_2O_3-H_2O, paragonite stability in, (5) 124*e*.
Ag_2WO_4-K_2WO_4, Ag_2WO_4-Cs_2WO_4, Ag_2SO_4-Cs_2SO_4, DTA studies, (1) 21*a*.
Na‖B_4O_7,PO_3,P_2O_7, (5) 124*f*.
Na-Cs alloy, phase equilibrium in, (5) 124*a*.
Na‖SO_4,PO_3,BO_2, (1) 23*c*.
Na_3AlF_6-SiO_2-Al, chemical reactions in, (7) 176*e*.
NaF-AlF_3, AlF_6Na_3-Al_2O_3, and AlF_6Na_3-CaF_2, (6) 146*h*.
NaF, pyrophosphate, and tetraborate, (5) 124*i*.
NaOH-KOH, NaCl-KCl, and NaOH-KOH-NaCl-KCl, solubility of Na and K in, (7) 177*c*.
$(Na_{0.88}Li_{0.12})NbO_3$+6 mol% Li_2O, X-ray and thermal expansion study, (1) 26*d*.
$NaNbO_3$-$BaTiO_3$-$BaNb_2O_6$, W bronze field in, (10) 261*e*.
Na_2O-CaO-Al_2O_3-SiO_2-H_2O, solid phases in, (8) 210*c*.
Na_2O-CaO-SiO_2-H_2O, (6) 150*f*.
Na_2O-NbO_2, phase equilibrium, (1) 23*i*.
Na_2O-K_2O-Al_2O_3-SiO_2-H_2O, solid phases in, (10) 261*b*.
Na_2O-ZrO_2-SiO_2, phase equilibria, (1) 23*g*.
$NaPO_3$-Fe_2O_3 and $NaPO_3$-Al_2O_3, chromatography of compounds in, (1) 21*c*.
Na_2SO_4-$Na_2B_4O_7$-$Na_4P_2O_7$, (1) 25*j*.
Sr-N, (4) 99*b*.
SrF_2-LaF_3, for electroslag melting, (4) 95*c*.
SrO-CdO-V_2O_5, phase equilibria in, (11) 281*j*.
SrO-TiO_2-ZrO_2, reactions in, (1) 24*c*.
$_xSrRuO_3$·$(1-x)LaRhO_3$, magnetic properties, (3) 74*f*.
Ta, Ti, B and Ta, Mo, B, phase equilibria in, (10) 260*h*.
$TaCl_5$-UCl_4-KCl, reactions in, (5) 123*j*.
Ta_2CrO_6-$TaCrO_4$, Jahn-Teller effect in, (10) 259*h*.
Ta_2VO_6-VO_2 and WV_2O_8-VO_2, (7) 177*f*.
Te-As-Ge-Si, switching process in, (6) 147*f*.
$TeCl_4$-TlCl, (8) 211*h*.
ternary, properties, calculation from binary data, (7) 176*j*.
$C_4A_3(SO_3)$ or CA-$Ca(OH)_2$-$CaSO_4$-R_2SO_4, hydration products in, (9) 214*a*.
tetrazolium-ZnO, photoresponse, (3) 72*e*.
$TlPO_3$-$Co(PO_3)_2$, $TlPO_3$-$Mg(PO_3)_2$, and $TlPO_3$-$Ca(PO_3)_2$, (8) 211*h*.
ThO_2-SrO and ThO_2-BaO, furnace to study, (7) 172*j*.
3$SnCl_2$+2Al=2$AlCl_3$+3Sn, (5) 124*g*.
SnI_2-MI (M=K,Rb,Cs), thermographic and X-ray study, (8) 211*d*.
Ti-Ni-B, Mo-Ni-B, and W-Ni-B, (10) 261*g*.
Ti-O, magnetic studies, (11) 281*e*.
Ti-TiO_2-metal, transient phenomena, (4) 99*i*.
TiO_2-Cr_2O_3, $Ti_2Cr_2O_7$ solid solubility in, (6) 151*h*.
TiO_2-SnO_2, reexamination, (7) 180*d*.
C_3A-$CaSO_4$-H_2O, hydration, (5) 103*i*.
C_3S-H_2O, He flow and density, (5) 103*h*.
W-Cr-B and W-Mo-B, phase equilibria in, (10) 260*g*.
WB-LaB_6, alloys of, (10) 259*e*.
U-C-O, phase relations at 1573°K, (1) 15*g*.
U-V-C, phase behavior, (8) 203*d*.
UC-W, phase reaction in, (1) 15*e*.
UC_2-C, C thermal diffusion in, (2) 43*e*.
UN-Mo and UN-W, at high temps., (7) 171*d*.
UO_3-ThO_2-O_2, (11) 276*e*.
V-Cr-B, Nb-Cr-B, and Mo-Cr-B, (10) 261*g*.
V-W-O, crystal chemistry of phases in, (6) 145*h*.
V-VO, (6) 153*a*.
VO_2-V_2O_5, melts in, thermodynamics, (6) 152*e*.
V_2O_5-MgO and V_2O_5-MPO_3, effect of acid-base properties on, (3) 72*f*.
V_2O_5-Na, V_2O_5 formation in, (8) 208*c*.
H_2O-B_2O_3-Tl_2O, (4) 99*g*.
Yb_2O_3-Nb_2O_5, study of Nb_2O_5 regions, (2) 50*d*.
Y_2O_3-Nb_2O_5, phase equilibria, (9) 237*b*.
Y_2O_3-Ta_2O_5, phase composition, (1) 23*b*.
$Zn(PO_3)_2$-ZnO, melts, surface tension, (9) 239*a*.
ZnS-Na_2S, (8) 211*h*.
Zr-lanthanide oxides, (6) 152*d*.
$ZrCl_4$-$AlCl_3$-$FeCl_3$-NaCl-KCl, (5) 118*j*.
ZrO_2, phase analysis in, (7) 179*a*.
ZrO_2-Ce_2O_3, phase studies, (11) 282*c*.
ZrO_2-MgO, liquidus curve measurements, (3) 74*e*.
ZrO_2-SiO_2-TiO_2, and $ZrSiO_4$-TiO_2, phase relations, in, (6) 150*g*.
ZrO_2-Y_2O_3, liquidus curve measurement, (3) 74*e*.

Tableware. See also *Dinnerware*.
porcelain, raw material for, (8) 198*c*.
Talc. See also *Steatite*.
beneficiation, P (11) 280*b*.
dehydroxylation, inhomogeneous, (4) 97*g*.
Tanks. See *Furnaces, glass*.
Tantalum, borides, magnesiothermic production, (3) 60*d*.
carbide, coiled-coil filament, P (7) 164*g*.
polycrystalline, (2) 48*c*.
wetting by liquid Cu and Ag, (4) 80*a*.
work function, (5) 125*f*.
carbides, external friction, (10) 259*d*.
oxide thin films on, (7) 179*i*.
pentachloride, reaction with chlorides of bivalent metals, (5) 123*i*.
phosphate, synthesis, (2) 50*b*.

Tantalum *(continued)*
powder, P (10) 257*g*.
reaction, with Al_2O_3 melt, (7) 163*j*.
with BN, AlN, and Si_3N_4, (2) 49*f*.
with SiO_2 melt, (7) 163*g*.
sulfide, new superconductor, (4) 97*h*.
systems. See *Systems*.
Ta_2C, eutectoid decomposition, (6) 148*a*.
Tape, pressure-fusible, for multilayer structures, (6) 136*j*.
Television tubes. See *Tubes*.
Television screens. See *Screens*.
Tellurium, -Cr dioxides, Fe-modified, P (5) 114*b*.
compounds with Zn and Ga, thin films, B (10) 264*i*.
diffusion in CdS and CdSe, (4) 93*j*.
dioxide, crystal, acoustic properties, (11) 273*d*.
dioxide, of low Fe content, P (4) 94*j*.
films, trigonal, growth on glass, (3) 56*i*.
I_2+Te solutions, electrical conductivity, (6) 147*f*.
single crystals, etching, (7) 176*d*.
systems. See *Systems*.
$TeCl_4$-$2TlCl$, structure, (6) 152*c*.
$TeCl_4$-$TiCl_4$ and $TeCl_4$-$SbCl_3$, phase diagrams, (8) 209*j*.
tetrachloride, reactions with chlorides of alkali metals and ammonium, (8) 210*a*.
Temperature, baths for electrical standards, (3) 70*f*.
coeff. of electroresistance of high-melting compounds, (10) 261*b*.
coeff., of Ni-Zn ferrites, (7) 167*b*.
control. See also *Controls*.
bath, in glass apparatus, P (5) 106*j*.
of chemical tempering, P (4) 83*a*.
of glass molds, P (2) 33*d*; P (4) 83*a*.
for laboratory furnaces, (2) 44*e*.
of rotary kiln, P (2) 45*c*.
of sample during X-ray, P (6) 142*a*.
with thermal conductance, (1) 18*b*.
time proportioning, P (1) 18*f*.
critical, on fusion of $NbCl_5$, (8) 208*h*.
curing, effect on $C_4A_3(SO_3)$ expansion, (4) 78*j*.
cycles, nonequilibrium, in adsorbates, (2) 48*g*.
dependence, of elastic moduli of ceramic materials, (9) 239*b*.
of elastic moduli of glasses, (8) 191*d*.
of EuO conductivity, (9) 239*a*.
of friction of ferrites, (3) 62*c*.
of hole velocity in *p*-GaAs, (5) 124*g*.
of optical absorption edge in SnO_2, (3) 75*h*.
of optical harmonic generation in quartz, (3) 75*i*.
of photocurrents in detectors, (6) 137*b*.
of susceptibility of antiferromagnetic oxides, (4) 81*c*.
of $YFeO_3$ susceptibility tensor, (5) 124*h*.
of Zn diffusion in GaAs, (4) 99*e*.
effect, on cement hardening, (8) 187*e*.
on liquid-state glasses, (7) 159*c*.
on $Mg(OH)_2$ carbonation, (7) 177*j*.
on properties of cast stone, (8) 195*e*.
on refractive index and optical path length of glass, (10) 243*d*.
on strength of porous ceramic, (4) 85*e*.
on work-hardening of LiF crystals, (6) 147*a*.
high-, analyzing of gaseous samples, P (3) 70*b*.
chemistry, advances, B (6) 153*f*; P (8) 212*a*.
data for ZrV_2O_7, (11) 283*d*.
devices, lead attachment to, P (9) 225*f*.
effect on gypsum hydration and crystallization, (7) 156*c*.
high-pressure techniques, B (7) 184*i*.
materials, ARPA-NBS research, (3) 70*j*.
measurement in hot glass, (3) 56*j*.
of melts, detecting, P (7) 174*c*.
of moving material, P (3) 70*d*.
Néel, of CoO, pressure effect, (5) 120*d*.
Néel, of magnetite, pressure effect, (6) 146*j*.
pressure-, apparatus, ultrahigh, P (6) 141*h*.
probes, resistance, sensor for, P (5) 116*g*.
regulator, (10) 255*e*.
safe usable for cement products, (10) 242*b*.
setting, effect on cement properties, (8) 186*j*.
superconducting, of NbN films, (3) 63*j*.
viscosity-, curve for glass, (11) 269*f*.
Temperature measuring instruments, P (1) 18*i*.
expendable immersion, P (9) 231*g*.
for gas stream, P (3) 70*g*.
for internal surface of steel furnace, P (9) 231*h*.
for material in rotary furnace, P (10) 256*a*.
for metal baths, P (6) 142*e*.
pyrometer, estimating errors, P (2) 45*b*.
for glass ribbon, (8) 190*d*.
turbine engine blade, P (3) 70*g*.
sensing, P (9) 231*d*.
sensors, comparison, (1) 18*a*.
remote radiation, P (4) 93*g*.
using microwave techniques, (9) 231*b*.
solid-state, P (11) 275*j*.
thermocouple, P (11) 278*j*.
calibration, (1) 19*f*.
connector construction, P (7) 174*a*.
in glassmaking, (10) 243*f*.
grounded circuits, (11) 279*c*.
guide, P (5) 116*h*.
holder, P (7) 174*b*.
input temp. sensing circuitry, P (7) 174*b*.
low temp., (10) 255*f*.
multijunction, P (9) 232*a*.
nonwelded junctions, P (1) 18*h*.
for nuclear environment, P (10) 254*b*.
Pt metal, (10) 255*i*.
Temp. measuring instr., thermocouple *(cont.)*
Pt-Rh vs Pt, P (10) 256*a*.
protected, P (6) 142*h*.
reference junctions, P (4) 93*e*.
regenerative sensor, P (7) 174*a*.
reinforced junction, P (3) 70*f*.
for surface temp., (3) 69*i*.
wire, Ag-28 at.% Au, (9) 231*a*.
thermometer, capacitive cryogenic, P (6) 137*g*.
circuit, Pt resistance, P (2) 45*d*.
glass, control device for, P (1) 5*f*.
high-temp., P (3) 70*b*.
metallic resistance, P (6) 142*f*.
radiation, P (2) 45*a*.
trimming method, P (5) 107*h*.
thermometry, in analysis of glasses, (8) 204*g*.
thermostat for ceramic top range, P (3) 64*b*.
by ultrasonic means, P (9) 231*j*.
Tempering, of glass. See *Glass*.
Tension, in glass fiber making, measuring, P (7) 161*g*.
specimens, thermal gradient in, P (2) 44*h*.
surface, of CaO-SiO_2 and CaO-SiO_2-Al_2O_3 slags, (8) 74*f*.
change on melting Al_2O_3 systems, Cr_2O_3, and Sm_2O_3, (7) 181*b*.
measuring, dipping cylinder method, (7) 173*a*.
of melts of $Zn(PO_3)_2$-ZnO system, (9) 239*a*.
tensile properties, of Cu-ThO_2, Au-ThO_2, Pt-ThO_2, and Au-Al_2O_3, Pt-Al_2O_3 alloys, (2) 38*e*.
tensioning, low-twist, of B filament, P (4) 84*c*.
Terbium, chloride, vapor pressure, (8) 210*b*.
fluorescence, in CaF_2, (9) 237*f*.
hydroxide, magnetic properties, (8) 209*j*.
phosphate, Sm^{3+} ion in, (3) 72*h*.
Tb^{3+} emission in YPO_4-YVO_4, (7) 181*c*.
Tb^{3+}, transition, in MPO_4 (M=Sc, Y, and Lu), (3) 73*a*.
Terminology. See *Nomenclature*.
Testing. See also *Analysis* and specific types.
ceramic materials, (7) 173*i*.
ceramic refractory materials, (7) 173*f*.
compression resistance, of pellets, P (2) 44*i*.
control, in whiteware mfg., (11) 272*i*.
glass flexural strength, (1) 3*f*.
industrial, of ceramics, B (10) 262*d*.
materials, flaw size indication in, P (6) 142*g*.
nondestructive, P (10) 256*b*.
nondestructive, ultrasonic device for, P (1) 18*e*.
plaster molds, in German laboratory, (5) 116*c*.
thermal conductivity, for refractories, (2) 44*g*.
work index, of cement raw materials, (4) 79*b*.
Thallium, borates, (4) 99*g*.
Fe fluoride, and devices using, P (2) 43*a*.
melts of salts of halides of, (5) 125*i*.
-ous fluoride, trimer and tetramer, (8) 209*d*.
-ous halide, phototropic articles, P (2) 35*a*.
-ous nitrate, vaporization, (8) 211*g*.
sulfohalides, unit cell, (2) 47*i*.
systems. See *Systems*.
Tl(I), spectroscopic probe in glass, (5) 106*h*.
TlP_3, crystal structure, (3) 72*h*.
Thermal analysis, apparatus for, P (9) 231*e*.
of $CaSO_4$ dihydrate and hemihydrate, (7) 181*c*.
of cement kiln samples, (8) 188*f*.
differential, (9) 231*b*.
apparatus for, P (11) 278*g*.
of basic Al sulfates, (10) 258*g*.
cell assembly, P (3) 70*a*.
in controlling solder-glass seals, (11) 274*c*.
curves, B (6) 153*i*.
for determination of crystalline quartz, (1) 17*h*.
of fusible systems, (6) 142*c*.
of glass fiber drawing mechanism, (7) 159*d*.
of marly clay, (1) 5*h*.
measurement of Al_2O_3 melting point, (5) 121*g*.
of montmorillonitic clays, (3) 71*c*.
of pyrophyllite diaspore minerals, (11) 283*a*.
furnace assembly for, P (4) 93*e*.
gravimetric, electronic microbalances in, (10) 255*f*.
of system InCl-TlCl-$AlCl_3$, (8) 211*b*.
of H_2O in cement, (5) 102*g*.
Thermal conductivity. See *Conductivity*.
Thermal decomposition. See *Decomposition*.
Thermal expansion. See *Expansion*.
Thermal properties, of bloating minerals, (6) 134*f*.
of natural rocks, (11) 283*a*.
of phosphates, cation effect, (5) 120*c*.
of Na silicate glasses at low temp., (9) 218*f*.
Thermal shock resistance. See *Shock resistance, thermal*.
Thermistors. See *Resistors, electrical*.
Thermochemistry. See *Thermodynamics*.
Thermocouples. See *Temperature measuring instruments*.
Thermodynamics, of adsorption of cement paste and concrete, (6) 130*a*.
for alkali fluorides, (6) 152*d*.
of Ca_3SiO_5 and $Ca_3Al_2O_6$ hydration, (7) 157*g*.
of crystals, B (11) 284*b*.
of ferromagnet, (6) 148*i*.
of GaAs vapor growth, (9) 239*c*.
of glasses, (2) 33*e*.
of gypsum, (5) 104*e*.
of high-temp. equilibria, (11) 283*a*.
of imperfect crystals, (11) 283*c*.
Thermodynamics *(continued)*
of liquidus surfaces of ternary systems, (6) 145*e*.
of LiCl in LiCl-$MgCl_2$, (11) 281*b*.
of melts in system VO_2-V_2O_5, (6) 152*e*.
properties, of $BaTiO_3$, Ti-rich, (1) 12*a*.
of BO^- and BO_2^-, (4) 96*f*.
chemical, (3) 70*b*.
of Cm_2O_3, (6) 148*c*.
of harmonic solids, (4) 98*c*.
of inorganic substances, (8) 211*c*.
of PbS, (8) 211*c*.
of liquid metal-nonmetal systems, (6) 141*j*.
of Mn silicides, (10) 261*d*.
of KCl, (5) 125*c*.
of refractory carbides, (8) 209*a*.
of silicates, (9) 238*f*.
of Na borates, (2) 50*c*.
of TiN, (10) 261*g*.
of UVC_2, (8) 209*d*.
of vapor species from Al_2O_3, (11) 281*c*.
reciprocating machine, P (8) 202*h*.
of refractory carbides, (10) 261*c*.
of Si sulfides and ZnS, (4) 99*h*.
of TiO_2 reactions with hydrosulfates of alkali metals, (2) 48*j*.
of vaporization of $NbCl_5$, (8) 211*f*.
Thermoelectric materials, antisublimation coating for, P (3) 64*d*.
Thermoelectricity, device, P (4) 91*c*.
devices, sintering, (7) 168*a*.
Thermography, duplication of heat radiation absorbent picture, P (7) 172*b*.
of systems SnI_2-MI (M=K,Rb,Cs), (8) 211*d*.
of thermal effects, (5) 116*g*.
Thermogravimetry, of ceramic clays, (6) 141*h*.
curves, B (6) 153*i*.
of limestones and dolomites, Ontario, (7) 181*e*.
of MgO in dolomitic limes, (11) 278*e*.
Thermoluminescence. See *Luminescence*.
Thermomechanical properties, of ZrO_2 in CaO-ZrO_2 system, (4) 98*j*; (6) 152*c*.
Thermometers. See *Temperature measuring instruments*.
Thermophysical properties. See *Physical properties*.
Thickness, of coating, controlling, P (9) 226*a*.
measuring apparatus and method, P (3) 70*c*.
measuring, by ultrasonics, P (1) 18*j*.
ratio of two spinel layers, (5) 125*d*.
of superficial layers on glass, (7) 159*g*.
Thin sections. See *Microscopy*.
Thoria. See *Thorium, oxide*.
Thorium, carbonate complexes, ir spectroscopy, (8) 211*a*.
dioxide, electrical conductivity, (7) 177*i*.
Eu^{3+} in, ESR spectrum, (6) 147*c*.
fluoride adsorption on, (9) 233*d*.
high-density, P (9) 228*f*.
and ThO_2-Y_2O_3, sintering with NiO, (11) 280*d*.
Y_2O_3-doped, transparent, (7) 179*g*.
in mineral deposits, P (2) 43*f*.
oxide, -base ceramics, P (2) 38*c*.
-rare earth ceramics, (5) 111*f*.
reduction by C, (7) 180*d*.
systems. See *Systems*.
$ThTi_2O_6$, properties, (1) 25*i*.
$Th(WO_4)_2$, decomposition temp., (3) 72*d*.
Thulium, oxide, heat source, P (1) 16*e*.
Thyristors. See *Transistors*.
Tile. See also *Pipe*.
P (9) 223*e*.
adhesion strength, (5) 110*g*.
advancing pallets for making, P (10) 248*i*.
assembling, P (8) 198*f*.
bodies, physical and mechanical behavior, (6) 135*j*.
and brick industry, in Canada, (9) 221*b*.
cast, low-temp. fluxes for, (8) 197*f*.
ceramic, dry-pressing, P (9) 223*c*.
fast-fire, P (7) 166*b*.
grouts, P (11) 273*b*.
chemically resistant, asbestos waste for, (8) 198*a*.
clay and concrete, B (6) 153*j*.
covering, on concrete seat, P (5) 111*g*.
decorative indented patterns on, P (4) 86*c*.
double, apparatus for splitting, P (11) 277*f*.
edge grinding machine, P (4) 86*b*.
electrooptical inspection, P (10) 248*f*.
firing setters for, P (8) 196*g*.
floor, by slip method, (8) 197*d*.
floor, wear resistance, (7) 165*g*.
frost resistance, (11) 271*a*.
glazed, depositing in magazines, P (2) 38*a*.
frost damage, (1) 6*b*.
muffle kiln for firing, P (5) 117*a*.
single-fired, P (4) 86*a*.
wear, optical measurements, (8) 198*c*.
glazing and decorating, (4) 92*f*.
heat exchange structure, P (4) 84*c*.
industry, automation in, (2) 35*d*.
laying, adhesion problems, (5) 110*d*.
-mortar-concrete, adhesive strength, (5) 110*g*.
mosaic, from clay and glass, (8) 190*j*.
or panels, P (11) 273*c*.
pantiles, stacking and setting down, P (11) 271*b*.
production in Italy, (5) 111*a*.
properties, effect of molding, (4) 83*f*.
roofing, conveyor, P (1) 6*c*.
frost resistance, (1) 17*i*; (4) 83*e*.
pressing, (4) 83*i*.
sludge bed, P (11) 271*c*.
spray dried bodies for, economical, (6) 136*c*.
terrazzo, NRDC study, (4) 100*a*.

Tile *(continued)*
wall, and floor, glazed and stoneware, Italian, (7) 165*b*.
majolica, dilatometric data, (7) 165*g*.
stress distribution in, (4) 85*d*.
tensile adhesive strength, (7) 164*i*.
H_2O absorption and frost resistance, (5) 108*f*.
Time, effects in hysteresis loop of (Pb,Sr)TiO_3, (3) 63*j*.
residence, distributions in mills, (5) 104*j*.
Tin, -ic oxide, crystals, electrical conductivity, (3) 72*f*.
crystals, electrical properties, (6) 147*g*.
crystals, properties, (3) 72*j*, 74*i*.
optical absorption edge in, (3) 75*h*.
Raman spectrum, (7) 179*j*.
-ous fluoride, (4) 97*f*.
-ous oxide, Sn_2O_2, Sn_3O_4, and Sn_4O_4, ir spectra, (7) 178*e*.
-ous silicate, for dental polishing, P (2) 29*f*.
oxide, crystals, in photoconductive layer, P (2) 34*j*.
oxide, etching method, P (9) 228*b*.
systems. See *Systems*.
tetrachloride, reactions with rutile, (11) 281*c*.
Titanates. See also *Dielectrics* and specific types.
ceramic elements and materials for, P (5) 113*h*.
Cr-Fe, shear structure compounds, (10) 260*j*.
mixed, thin layers by solid-solid reactions, (6) 136*i*.
Titania. See *Titanium, dioxide*.
Titanium, abrading, P (3) 53*g*.
carbide. See also *Cermets*.
P (8) 196*a*.
coatings on substrates, P (11) 272*f*.
crystals, deformation, recrystallization, strength, and fracture, (3) 72*e*.
deposition on WC substrate, P (5) 109*f*.
emissive power and electrical resistance, (8) 199*f*.
hard coatings, P (5) 109*j*.
impregnation with liquid steel, (10) 258*j*.
materials, binder for, P (4) 84*i*.
materials, heat treatment, (10) 246*h*.
-Ni compositions, P (10) 248*e*.
and Nb powders, sintering, (10) 260*c*.
nitrides, or borides, fibrous, P (8) 196*j*.
single-crystal growth, (9) 238*i*.
single crystal surfaces, (10) 259*i*.
sintering, (10) 261*a*.
stability, (3) 75*b*.
-VC structural materials, P (8) 196*a*.
carbonitride, P (2) 37*c*.
in cement, determination, (4) 78*g*.
centers, induced in borate glasses, (4) 81*g*.
chloride, raw, recovery of V from, P (3) 72*a*.
chlorides, thermal capacities, (4) 93*a*.
compounds of W-bronze type, (3) 75*i*.
diboride, thermal diffusion, (4) 97*e*.
dioxide. See also *Rutile*.
P (2) 46*c*; P (6) 144*d*; P (7) 175*f*.
ceramic, with low dielectric loss, (1) 11*h*.
coatings on glass bottles, (7) 160*j*.
composition, hot-pressing, P (5) 114*d*.
computer-controlled production, P (8) 205*j*.
concentrates, P (8) 196*j*.
effect on CeO_2 grain growth, (6) 147*a*.
effect on sintering Al_2O_3, (3) 72*i*.
fibrous, P (7) 175*e*.
film, P (4) 90*c*.
fine-particle-size, P (6) 144*b*.
in glass crystallization, (4) 80*j*.
interactions in, (6) 148*e*.
$^3Fe^{3+}$, exchange effects in, (6) 151*i*.
Fe_2O_3 and Fe_2TiO_5 mixtures, dielectric properties, (3) 62*d*.
microwave sound absorption in, (6) 150*h*.
offgrade, reclaiming, P (2) 46*f*.
O diffusion in, (9) 238*i*.
photoconductive, P (4) 94*e*.
photoconductive composition, P (10) 252*h*.
photoconductivity spectra, (3) 74*f*.
pigment-grade, P (8) 207*c*.
pigments. See *Pigments*.
reactions with hydrosulfates of alkali metals, (2) 48*j*.
recovery from hot gases, P (11) 279*i*.
seed suspensions, P (4) 94*g*.
solid reaction with $BaCO_3$, (6) 146*g*.
solubility in halide-phosphate melts, (8) 210*f*.
strength under stresses, (8) 210*j*.
suspensions, P (8) 207*i*.
suspensions, settling in H_2O, (5) 111*b*.
disilicides, interaction with graphite, (10) 259*c*.
fluoride, separation from UF_6, P (3) 68*i*.
hydroxide, changes during heating, (6) 145*i*.
monoxide, vacancies in, (3) 73*e*.
-Nb oxide, crystal lattice, (7) 178*b*.
nitride, -TiC hot-pressed, P (10) 247*i*.
-TiC, Ni–Mo-bonded, P (9) 222*b*.
vaporization and thermodynamic properties, (10) 261*g*.
and/or ZrN jewelry, P (9) 222*i*.
nitrides, reaction with graphite, (3) 60*h*.
oxide, band structure, physical properties, and stability, (5) 118*j*.
oxides, electrical properties, (6) 147*h*.
in electroslag processes, P (10) 257*j*.
optical spectra, (10) 260*d*.
reactions with rutile, ir study, (11) 281*c*.
systems. See *Systems*.
tetrachloride, combustion with O, P (10) 257*c*.
purification, P (2) 46*e*; P (4) 94*j*.
from titaniferous ore, P (4) 95*a*.

Titanium *(continued)*
titaniferous material, beneficiating, P (6) 143*i*.
or Ti alloy, for bone implants, P (6) 136*b*.
Ti^{3+} exolution rate from corundum, (3) 74*j*.
Ti^{4+} combined with Co^{2+} in rutile, (4) 97*j*.
TiC_{1-x}, physical properties, (3) 74*f*.
$Ti_2Cr_2O_7$ solid solubility in TiO_2–Cr_2O_3 system, (6) 151*h*.
Ti_nO_{2n-1} ($4 \leq n \leq 10$) phases, electron microscopy, (3) 73*a*.
Ti_2O_3, negative-magnetoresistance in, (5) 122*g*.
Titration. See also *Analysis*.
automatic, constant flow device, (1) 17*g*.
coulometric, of boric acid, (9) 231*d*.
potential, measurement, P (9) 232*a*.
Tobermorite, Al, low-temp. synthesis, (9) 214*h*.
in Ca silicate autoclaved materials, (5) 116*d*.
hydrothermal synthesis, (5) 117*i*.
Tools. See also *Drills*.
abrasive cutting, P (5) 101*f*.
abrasive jet machining, (5) 101*e*.
abrasive plumber's, P (5) 101*g*.
cutting. See also *Abrasives*.
abrasive element, P (4) 77*h*.
annular blades, P (5) 101*e*.
with B filament composite, P (3) 53*f*.
ceramic and cement, review, (3) 53*i*.
grinding, and polishing single-crystal workpieces, P (7) 172*f*.
in machining steel and cast Fe, (10) 246*e*.
for masonry, P (3) 69*a*.
sheet, P (8) 204*b*.
diamond bit, P (5) 101*f*.
diamond turning, wear, (6) 127*e*.
grinding. See *Grinding apparatus*.
hammer, hollow handle, with glass fibers, P (7) 161*g*.
hand, for sharpening cutting edges, P (3) 53*g*.
for impact-extruded articles, P (8) 204*c*.
Topaz, compositional variations in, (9) 233*j*.
Topography, equilibrium, of sputtered amorphous solids, (2) 47*d*.
surface, of Al_2O_3 substrates, (9) 224*g*.
X-ray, with chromatic-aberration correction, (7) 179*j*.
X-ray, of impurity platelet in diamond (10) 261*j*.
Trace elements. See *Elements*.
Tracers. See *Radioactive tracers*.
Transducers, apparatus and system, P (2) 43*c*.
composite surface-wave, P (10) 250*c*.
coupling to transmitter and receiver (U), P (2) 40*a*.
electroacoustic, P (11) 274*g*.
electroceramic sonar, P (8) 201*b*.
electromechanical, ceramic bodies for, P (11) 274*d*.
ferroelectric, semiconducting, P (2) 42*h*.
focused piezoelectric, P (10) 250*e*.
head, P (8) 202*i*.
heterojunction semiconductor, P (3) 65*c*.
high-frequency diode energy, P (11) 274*i*.
hybrid surface-wave, P (9) 225*d*.
magnetic, P (10) 251*e*.
heads, P (10) 251*c*.
with narrow sensing tip, P (9) 227*j*.
micro-, electrooptical, P (9) 225*g*.
mosaic acoustic, P (3) 66*c*.
piezoelectric, P (9) 227*g*.
controlling frequency, P (10) 251*i*.
elements, P (8) 202*c*.
insulating films for, P (4) 89*c*.
thin films for, P (7) 169*h*.
piezoresistive miniature pressure, P (3) 66*h*.
pressure-, P (10) 252*j*.
pressure, capacitance-type, P (4) 87*h*.
Se-Te, P (3) 67*i*.
semiconductor, P (11) 275*i*.
electromechanical, P (8) 202*i*.
pressure-electric, P (9) 227*h*.
strain, P (8) 202*b*.
stress, P (10) 253*a*.
sensing, for security device, P (1) 14*b*.
temp.-sensitive, P (7) 170*f*.
ultrasonic, ZnO films as, (3) 63*c*.
welded pressure, P (1) 15*b*.
ZnO film, for detection of elastic waves, (3) 63*a*.
Transfers. See *Decoration*.
Transformations, burst phenomenon in ZrO_2, (7) 178*b*.
in chalcogenide thin films, (6) 136*h*.
in glassy chalcogenides, (6) 152*d*.
high-pressure, in $MnSiO_3$, (9) 235*j*.
point, of enamels, relation to properties, (8) 188*j*.
polymorphic, of CaS, (4) 79*g*; (5) 104*c*.
thermal, of aluminosilicate minerals, (2) 47*c*.
during $H_2(HPO_3)$ reaction with chamotte, (8) 196*e*.
of kaolin, (7) 181*i*.
Transformers, ferroelectric, P (11) 274*g*.
piezoceramic, (11) 274*d*.
piezoelectric, P (8) 202*f*.
ceramic, P (3) 68*a*.
high-voltage, P (8) 200*h*.
Transistors, P (10) 251*h*, 252*i*.
alloy junction, P (3) 64*c*.
all-, logic, P (6) 137*f*.
bipolar-unipolar structure, P (8) 200*d*.
for C-60M system line repeaters, (11) 274*b*.
control, P (10) 252*a*.
double-diffused, P (1) 13*h*.
epitaxial, P (1) 12*b*.
field-effect, P (2) 41*e*; P (5) 112*d*; P (8) 200*e*, 201*b*; P (10) 251*f*.
blocking, P (8) 200*e*.

Transistors, field-effect *(continued)*
complementary, P (2) 41*f*.
doped-oxide, P (1) 12*h*.
glass-annealing process for, P (8) 200*g*.
low-noise, P (7) 169*b*.
Schottky-barrier, P (2) 42*g*.
self-aligned gate, P (10) 252*c*.
with semiconductor layer, P (1) 12*e*.
thin-film power, P (7) 170*g*.
floating gate, charging and discharging, P (8) 200*e*.
Ge, P (2) 41*j*.
Ge planar, electronic devices for, P (10) 252*a*.
hf, P (9) 225*c*.
with shallow emitters, P (1) 12*f*.
two-layer metalized, P (2) 43*a*.
high-speed, metal contacts to, P (10) 252*a*.
high-voltage structure, P (3) 65*d*.
high-voltage thin-film, P (9) 225*c*.
improved with Si_3N_4 seal, (11) 274*a*.
including gain-determining step, P (9) 226*b*.
IGFET, P (2) 40*c*,*d*; P (3) 65*e*; P (4) 88*g*, 89*a*; P (6) 138*b*; P (7) 168*h*; P (9) 228*a*.
complementary, P (10) 250*b*.
depletion-type, P (3) 64*f*.
with glass insulator, P (10) 250*j*.
integrated-circuit device, P (10) 250*i*.
shift register stage using, P (9) 227*i*.
integrated, P (3) 65*f*.
circuit lateral, P (8) 200*j*.
lateral, P (7) 169*a*.
interdigitated structures for, P (2) 40*e*.
inverse, with high current gain, P (8) 200*j*.
junction, P (3) 65*h*.
junction-type field-effect, P (6) 138*i*.
lateral, P (2) 41*f*; P (7) 169*a*.
mesa, nitride passivation, P (4) 89*f*.
metal-insulator, in $V_{2-x}Cr_xO_3$, (11) 281*e*.
metal-insulator-Si pairs, P (8) 200*g*.
MISFET, complementary, P (6) 137*i*.
MOS, high-voltage, P (4) 88*e*.
MOSFET, P (5) 112*h*.
decoder topology, P (7) 169*g*.
etched Schottky-barrier, (1) 11*e*.
self-registered, (11) 274*j*.
pedestal, P (10) 251*g*.
phosphorus glass passivated, P (2) 41*g*.
photo-, self-scanned array, P (3) 67*j*.
planar junction-gate field-effect, P (3) 66*i*.
with plateau emitter, P (9) 228*b*.
pnp power, high-speed, P (6) 137*e*.
power, P (2) 42*b*.
semiconductor unijunction device, P (3) 67*g*.
Si, detecting surface ions on, P (9) 226*d*.
Si, high-frequency, P (4) 89*i*.
structures, defect distribution in, (9) 233*f*.
surface barrier, P (2) 42*h*.
thin-film, P (4) 91*d*; P (9) 226*h*.
thyristor, with degenerate semiconduction, P (5) 114*c*.
thyristors, interdigitated structures for, P (2) 40*e*.
Transitions, in ferromagnetic semiconductors, (9) 236*e*.
metal-nonmetal, in magnetite, (5) 120*a*.
metal-semiconductor, in V_2O_3, (6) 145*g*.
Mott, in V_2O_3, (6) 150*i*.
orthorhombic-tetragonal, of WO_3 phase, (8) 211*j*.
phase. See *Phase*.
of polarons from large to small, theory, (5) 125*a*.
vibronic, of Eu^{3+} ions in $CaWO_4$, (3) 76*a*.
Transport, chemical, reaction, V_nO_{2n-1} growth by, (1) 11*a*.
electronic, in transition metal oxides, (9) 235*h*.
electronic, in ZrO_2, (9) 235*f*.
of Au Ge GaAs metal semiconductor system, (5) 112*d*.
ionic, in float glass, (8) 191*i*.
mass, role of defects in, (9) 235*b*.
phenomena in silicate glasses, (9) 217*a*.
in semiconducting alloys, (6) 147*d*.
Tricalcium. See *Calcium*.
Trituration. See *Crushing; Grinding*.
Tubes, arc, centering device, P (8) 57*h*.
arc, fused SiO_2, P (3) 58*d*.
camera, target structure for, P (2) 42*i*.
cathode-ray, P (2) 39*f*; P (3) 66*d*; P (5) 107*b*; P (6) 137*h*; P (8) 193*e*; P (10) 243*i*.
applying glass collet to, P (1) 4*c*.
Ba silicate glass for, P (4) 81*a*.
black enamel glass for, P (7) 161*i*.
character-display, P (10) 249*h*.
coating, P (7) 162*h*.
display, P (8) 192*b*.
envelope, P (9) 219*i*.
faceplate, P (9) 218*f*.
faceplate, securing planar member to, P (8) 193*g*.
forming techniques, P (9) 219*d*.
implosion-proof, P (6) 133*c*.
with inert barrier, P (8) 192*b*.
in-line plural-beam, P (4) 88*f*.
line scanning, P (8) 193*f*.
low-depth, P (11) 275*a*.
miniaturized, P (1) 13*j*.
phosphors for, P (9) 225*f*.
recording, P (2) 42*e*.
screening, P (10) 245*d*.
storage target for, P (2) 34*f*.
thin-window, P (3) 59*i*.
transducer for, P (3) 66*c*.
TV display, P (8) 193*a*.
TV display, glass for, P (9) 219*d*.
for ultrasonic uses, P (1) 15*b*.
using In alloy seal, P (4) 82*e*.

Tubes, cathode-ray *(continued)*
for X-ray protection, P (2) 34*h*.
cathode vacuum discharge, cold, P (8) 192*d*.
color cathode-ray, P (5) 107*c*.
screen for, P (10) 251*g*.
screening, P (1) 14*h*; P (4) 89*a*; P (10) 252*f*.
color, integrated shadow mask structure, P (1) 4*i*
kinescope, P (4) 89*i*.
penetration-type, P (1) 14*b*.
picture, P (2) 33*e*; P (9) 219*b*; P (10) 244*h*.
picture, deflecting device for, P (8) 200*h*.
picture, shadow mask, P (10) 244*h*.
TV, back etching mask for, P (10) 245*b*.
TV picture, P (3) 57*j*; P (8) 192*e*; P (10) 244*a*.
discharge gas-filled, P (5) 107*f*.
for ir emission stimulator, P (2) 40*b*.
for spectroscopic analysis, P (6) 142*c*.
display, implosion-free, P (1) 5*a*.
electric discharge, P (2) 40*d*.
electric gas discharge, P (9) 218*h*.
electron, beam collector structure for, P (10) 250*g*.
character-indicating, P (3) 57*i*.
devices, hot cathode, P (6) 140*c*.
electronic, tubular socket for, P (9) 218*i*.
filament-wound, P (4) 82*c*.
flanged, lining with glass, P (11) 267*e*.
fused metal oxide [SiO_2], P (3) 58*j*.
fusion sealing wire grid in, P (3) 59*d*.
gas discharge, P (11) 270*e*.
gas discharge display, P (8) 192*j*.
gas sampling, P (11) 278*h*.
Geiger, spherical halogen, P (6) 133*h*.
glass, P (1) 4*j*; P (8) 193*b*.
closed, with pellet in, P (7) 161*f*.
extrusion, P (9) 230*b*.
re-forming apparatus, P (3) 58*a*.
shaping ends, P (7) 162*a*.
wave propagation along, (8) 192*f*.
glow discharge starter, P (10) 244*d*.
image pickup and recording, P (10) 253*b*.
indicator, P (3) 58*d*.
laser, P (9) 226*h*.
laser, double-ended ion, P (2) 33*j*.
microwave, depressed collector for, P (10) 249*j*.
multibore, forming method, P (1) 4*i*.
multichannel photomultiplier, P (9) 219*e*.
neutron source, with coated target, P (5) 115*c*.
photographic recording, P (3) 59*b*.
planar capillary, for gas discharge, P (11) 270*f*.
plastic, fiber-glass-reinforced, P (4) 81*i*.
quartz, striation-free, P (1) 4*b*.
or rods, testing by ultrasonics, P (9) 231*e*.
roentgen, rotary anodes for, P (6) 135*e*.
screens. See also *Screens*.
shadow-mask, screens for, P (10) 245*c*.
storage, P (10) 253*d*.
storage, image-transducing, P (6) 138*b*.
TV camera, fiber-optical plate coupling screen to PbO target of, P (5) 112*d*.
TV, electrostatic coating, P (10) 244*e*.
melting particulate glass batch for, P (1) 4*b*.
nonglare coating for, P (10) 245*g*.
traveling-wave, P (5) 140*c*.
uniting with end fractures, P (3) 59*i*.
uniting with fusion barrier, P (3) 59*j*.
vidicon target plate, P (6) 140*d*.
Tungstates, isopoly-, ions, molecular weights, (6) 150*f*.
rare-earth normal, P (7) 170*f*.
refractory rare-earth, ceramics, (7) 180*e*.
vibronic transitions of Eu^{3+} in, (3) 76*a*.
Tungsten, barrier electrical connection, P (2) 43*a*.
borides, magnesiothermic production, (3) 60*d*.
bronze field in $NaNbO_3$-$BaTiO_3$-$BaNb_2O_6$ system, (10) 261*e*.
-bronze type compounds, (3) 75*i*.
carbide, Co-bonded, P (8) 196*j*.
-Co composition, P (10) 247*e*.
electrical resistivity, (6) 149*j*.
materials, binder for, P (4) 84*i*.
platelets, Co-bonded, P (6) 135*d*.
stability, (3) 75*b*.
Cr-W coating on, P (4) 80*a*.
disilicides, interaction with graphite, (10) 259*c*.
emissive properties, (8) 199*i*.
formation and desorption of oxide layers on, (11) 281*j*.
oxide bronzes, deposition and dissolution, (8) 208*i*.
oxides, optical spectra, (10) 260*d*.
porous layers, densifying, P (3) 68*d*.
reaction with SiO_2 melt, (7) 163*g*.
reactions with BN, AlN, and Si_3N_4, (2) 49*f*.
systems. See *Systems*.
trioxide, Nb_2O_5-doped, crystallographic shear in, (10) 258*j*.
trioxide, phase, thermal expansion and transition, (8) 211*j*.
-W oxide coating, depositing, P (9) 226*i*.
$W_2O_3(AsO_4)_2$, crystal structure, (3) 72*h*.
vapor-deposited for Si devices, (10) 249*b*.
Tunneling, resistance in *n*-GaAs Schottky barriers, (7) 179*i*.
Turbines, industrial gas, (2) 36*a*.
wheel, ceramic, P (9) 222*c*.
Tuyeres. See *Refractories*.
Twinning, of crystals. See *Crystals*.

Ultrasonics. See also *Sonics*.
apparatus for testing tubes or rods, P (9) 231*e*.
attenuation, in CdS, (5) 122*j*.
attenuation, in $KTaO_3$, (5) 125*a*.
behavior, of Cr_2O_3, (6) 152*h*.
behavior of hematite, (5) 125*a*.
device for nondestructive testing, P (1) 18*e*.
devices, with chalcogenide glasses, P (7) 168*g*.
image screen, P (1) 15*b*.
method of measuring temp., P (9) 231*j*.
propagation in $RbMnF_3$, (6) 152*h*.
study, of elasticity-porosity in Al_2O_3, (5) 125*b*.
thickness measuring system, P (1) 18*j*.
transmission medium, 0 temp. coeff., P (7) 163*b*.
treatment of plastic ceramic bodies, (8) 198*j*.
waves, effect on stresses in glasses, (11) 269*f*.
Urania. See *Uranium, oxide*.
Uranium, carbide, equations of state for, (5) 144*j*.
grain-boundary grooving, (7) 171*i*.
UO_2, and UN, elastic moduli and internal friction, (1) 15*d*.
vapor free melting, P (9) 228*j*.
(C,N), lattice parameter, (4) 91*g*.
diboride, enthalpy, (4) 91*f*.
dioxide, article, P (2) 43*e*.
deformation and fracture, (4) 91*g*.
crystals, dislocation glide in, (6) 140*i*.
fission gas bubbles in, (7) 171*a,f*.
fuel pellets, oxidation, (11) 276*c*.
gas bubble effect, (6) 140*j*.
gaseous fission products in, simulation, (8) 203*e*.
handling, P (10) 253*j*.
helices, for creep measurements, (3) 68*d*.
high temp. irradiation, (1) 15*h*.
particles, electron microscopy, (11) 278*a*.
plasticity, high-temp., (5) 114*i*.
point defects in, (6) 152*a*.
reaction with MoO_3 in NaF-LiF melt, (1) 24*f*.
reaction with Ni-Ti alloy, (7) 171*j*.
reactions with C, (6) 142*f*.
single crystals, deformation, (1) 15*d*.
sintering kinetics, (9) 228*h*.
stoichiometric, creep in, (5) 114*g*.
swelling and gas release in, (5) 114*g*.
thermal diffusion of O in, (7) 171*c*.
-W composite, microscopy and diffraction, (1) 16*d*.
$\cdot xH_2O$, proton relaxation in, (6) 151*h*.
hexafluoride, Np separation from, P (2) 43*f*.
hexafluoride, separation from TiFl and NbFl, P (3) 68*i*.
in mineral deposits, P (2) 43*f*.
mixing and settling process for, P (10) 254*a*.
-Mo oxide, "molecular" cermet, (1) 15*i*.
nitride, fuel, nonswelling, P (8) 203*e*.
ores, radiometric assay, (3) 68*f*.
oxide, pellets, carrier for, P (4) 91*f*.
oxides, X-ray diffractometry, (11) 276*e*.
parts, surface preparation, P (10) 254*b*.
-Pu carbide, fission-product inclusions in, (7) 171*a*.
-Pu oxides, sintered, (1) 16*a*.
Pu separation from, P (1) 16*d*.
porous, P (3) 68*f*.
separating from aqueous solution, P (10) 253*i*.
systems. See *Systems*.
trioxide, chemically reactive, P (1) 16*d*.
trioxide, crystallographic shear relations with CaF_2, La_2O_3, and NaCl, (9) 234*f*.
U^{4+} in CaF_2, ultrasonic paramagnetic resonance, (5) 125*a*.
UC-UC_2 phase boundaries, (4) 91*h*.
UN_{1+x}, cation self-diffusion in, (7) 171*b*.
UO_2^{2+} fluorescence in Na borate glass, (7) 159*b*.
U_3O_8 or UC_2, spheres, for porous fuel, P (5) 114*b*.
U_4O_9, phase limits, (1) 15*j*.
U_4O_9, superstructure, analysis, (10) 253*h*.
UP-US, in cryogenic sensing device, P (6) 140*j*.
U_3Si, effect of swelling, (6) 140*j*.
U_3Si fuel elements, irradiated, (1) 16*f*.
UVC_2, thermodynamic properties and crystal structure, (8) 203*d*.
viscosity, (4) 91*j*.

Vacancies, effects in solute segregation in solids, (9) 234*i*.
Vacuum, apparatus, for excluding C from Si body, P (1) 15*c*.
Vacuum tubes. See *Tubes*.
Valves, ceramic gate, P (2) 38*c*.
Vanadates, ortho-, of rare-earth metals, P (9) 233*b*.
peroxo-, crystal structure, (3) 74*e*.
Vanadium, borides, magnesiothermic production, (3) 60*d*.
bronze, oxygen, NaV_6O_{15}, formation in V_2O_5-Na compounds, (8) 208*c*.
carbide, di-, P (1) 9*b*.
carbide, electron scattering in, (7) 180*j*.
ESR, relaxation in, (3) 74*j*.
dioxide, electronic properties, (6) 147*d*.
fluoride bronze, new, (4) 96*j*.
oxide, and B, air firable, P (3) 64*c*.
oxides, attack on refractories, (1) 8*a*.
oxides, optical spectra, (10) 260*d*.
pentoxide, attack on refractories, (4) 84*e*.
attack on basic refractories, (10) 247*a*.
for treatment of Al_2O_3, P (3) 62*a*.
recovery from raw TiCl, P (3) 72*a*.
redox equilibrium, in V systems, (3) 72*f*.
Vanadium *(continued)*
structure in V_2O_5-Na phosphate glasses, (6) 131*j*.
suboxides, P (5) 118*b*; P (7) 175*f*.
systems. See *Systems*.
tetravalent, spectrophotometry, (4) 98*h*.
trioxide, metal-semiconductor transition in, (6) 145*g*
trioxide, Mott transition in, (6) 150*i*.
V(C,N) C-rich solutions, equilibrium, (4) 96*d*.
V_3C_7, crystal structure, (7) 176*h*.
$V_{2-x}Cr_xO_3$, metal-insulator transition in, (11) 281*e*.
$VN_{0.465}$, enthalpy and free energy of formation, (6) 147*h*.
V_nO_{2n-1}, crystal growth, (1) 11*a*.
V_2O_3 and V_3O_4 films, semiconductor-metal transition in, (3) 57*j*.
V_2O_5, band structure and lattice distortion in, (5) 118*i*.
reactions with Sb oxides, (6) 145*b*.
X-ray detection in Cr_2O_3-V_2O_5, (9) 239*f*.
V_4O_9, crystal structure, (1) 21*f*.
V_6C_5, superlattice based on, (10) 261*b*.
Vapor phase, effect on morphology of SiC crystals, (11) 281*a*.
reaction, for $Nd(OH)_3$ preparation, (8) 210*i*.
Vapor pressure, of chlorides of Y, Pr, Gd, Tb, and Dy, (8) 210*b*.
over molten salts in systems $CdCl_2$-MCl, (8) 211*f*.
of $NbCl_5$, (8) 211*f*.
of SnF_2, (4) 97*f*.
Vaporization, behavior of defect carbides, (4) 99*i*.
of CaO from ZrO_2 body, (5) 109*d*.
of Cs, (11) 283*b*.
of Cr_2O_3 over Al_2O_3-Cr_2O_3 solid solutions, (11) 283*b*.
during high temp. oxidation, P (11) 277*c*.
heat of, of SnF_2, (4) 97*f*.
of $LaCrO_3$ in vacuum, (6) 152*i*.
metal, apparatus for, P (4) 87*e*.
of $NbCl_5$, thermodynamics, (8) 211*f*.
rate of TiN, (10) 261*g*.
rates, of ZnO and CdS, (6) 152*j*.
of $TiNO_3$, (8) 211*g*.
of ZnO, effect of short wavelength light, (2) 47*b*.
Varistor. See *Resistors*.
Velocity, -electric field, of GaAs, (6) 150*h*.
Vermiculite, -amino acid complexes, (6) 153*a*.
dioctahedral, from muscovite, (6) 143*e*.
gelling in aminobutyric acid, (9) 235*f*.
kaolinite from, (6) 143*e*.
Vibration, effect on rheology of disperse systems, (7) 180*h*.
testing, inorganic materials, (9) 230*h*.
thickness, of piezoelectric plate, (3) 63*i*.
Vibrators, $LiTaO_3$ piezoelectric, P (6) 138*d*.
Viscometers, capillary, for molten salts, (7) 173*c*.
for high-mol-weight-substance solution, P (9) 232*a*.
sliding plate, stress calculation, (5) 116*a,b*.
Viscometry, data for alkali borate glasses, (3) 55*a*.
Viscosity, anomaly, in oxide mixtures, (7) 181*i*.
apparatus for determining, P (11) 278*f*.
of basalt melts during cooling, (6) 151*j*.
calculation, nomogram for, (5) 116*a*.
of cryolite-Al_2O_3 mixtures, (7) 182*a*.
of enamels, relation to properties, (8) 188*j*.
of glasses of system PbO-B_2O_3, (8) 192*e*.
of glasses of systems Na_2O-K_2O-SiO_2 and Li_2O-K_2O-SiO_2, (7) 161*c*.
measurements in glasses, (3) 56*g*.
of NaCl+$ZnCl_2$ melts, (6) 153*c*.
-temp. curve for glass, (11) 269*f*.
of U and Cr-U alloys, (4) 91*j*.
Vitreous materials, bodies, strengthening, P (10) 245*j*.
depositing on faceplate panel, P (10) 244*j*.
porous shapes, P (8) 204*a*.
reducible, P (4) 83*a*.
strengthening, P (8) 204*a*; P (11) 270*f*.
strengthening by coating method, P (4) 85*j*.
tempering, chemical and thermal, P (7) 161*j*.
Vitrification, of feldspathic and feldspathoid fluxes, (1) 26*a*.
of kaolinitic clays, (8) 209*g*.
Voltage, built-in, in MOS structures, (7) 166*e*.
Volatilization, behavior in Pu-C system, (3) 203*b*.
effect on acid-leaching in glass, (3) 55*d*.
of Pb glass, (2) 32*j*.
Volume, activation, -stress, in UO_2, (5) 114*i*.
change, on fusion of $NbCl_5$, (8) 209*h*.
change, on melting Al_2O_3 systems, Cr_2O_3, and Sm_2O_3, (7) 181*b*.
free, of glasses, (6) 131*j*.
molar, of $MgCl_2$-$CaCl_2$-alkali metal chloride melts, (5) 119*f*.
molar, partial, for glass, (6) 131*i*.
partial molal, of Ca montmorillonite, (9) 237*a*.

Walls, brick, rain penetration, (9) 220*i*.
Wastes, mineral, utilization, B (9) 240*e*.
molding sands, recovery of chromite and SiO_2, (1) 8*f*.
radioactive, glass coating for, (11) 268*f*.
radioactive, solidification, (10) 242*a*.
solid, disposal, (10) 254*d*.
solid, glass raw material from, (4) 92*b*.
Water. See also *Humidity; Moisture; Steam*.
absorption, test methods, (1) 18*c*.
absorption of tiles, (5) 108*f*.
adsorbed in hydrated CaA, (8) 187*h*.
adsorption, on cement pastes, (10) 242*c*.
by clays, (2) 47*a*.

Water, adsorption *(continued)*
on SiO_2, (7) 176*c*.
anomalous, (4) 95*d*.
attack on Na_2O-MgO-SiO_2 glasses, (11) 269*i*.
-cement system, relaxation and polarization, (3) 54*b*.
combining in hardened cement paste, (8) 187*j*.
content of fresh concrete, (7) 157*d*.
content of glass, (9) 217*j*.
cooling treatment, (9) 229*e*.
demineralized, corrosion of windows by, (11) 268*f*.
diffusion in concrete at 30°C, (5) 102*h*.
dissolved, in E-glass, (3) 54*j*.
effect on growth of cracks in glass, (3) 72*f*.
freezing point in porous glass, (7) 159*c*.
fresh, brine, and $Mg(OH)_2$, P (10) 257*g*.
frost damage to glazed tiles, (1) 6*b*.
interlayer and adsorbed, in cement, (5) 102*g*.
in La oxide, hydrated, (1) 23*d*.
in Pb borate glasses, (2) 32*e*.
PbO transformation induced by, (2) 48*d*.
loss and absorption of cement and concrete, (7) 156*f*.
in magnesite, (10) 255*c*.
poly-, (4) 98*g*.
-reducing admixture, (6) 130*b*.
effect on concrete, (6) 129*i*.
effect on steam-cured concrete, (6) 128*d*.
removal from $CaSO_4$, P (3) 54*d*.
removal from clays, (1) 20*a*.
-repellent shaped articles and coatings, P (9) 230*c*.
retention, effect on amber glass, (8) 189*f*.
solubility of compounds in, (5) 124*a*.
structure in lamellar ionic solutions, (3) 74*b*.
structure on SiO_2 surface, (6) 151*h*.
systems. See *Systems*.
treatment, new pollution standards, (5) 115*g*.
vapor, adsorption on clay minerals, (9) 236*j*.
adsorption on E-glass, (9) 216*b*.
adsorption on mordenite, (3) 73*j*.
effect on solid-state reaction of CaO and quartz, (10) 259*c*.
heats of adsorption on X-zeolites, (1) 22*b*.
for treating molten salt, P (8) 193*b*.
Water glass. See *Sodium, silicate*.
Waves, acoustic surface, light diffracted by, in quartz, (5) 121*j*.
bulk, converting to Rayleigh, P (7) 168*h*.
elastic, from cavities, scattering, (7) 177*f*.
detection with transducers, (3) 63*a*.
mixing on $LiNbO_3$, (7) 178*h*.
electromagnetic, reciprocity, (7) 180*c*.
finite-amplitude in composites, (7) 179*h*.
micro-, integrated system, P (2) 40*d*.
latching, Li ferrites for, (5) 111*h*.
measurement of GaAs velocity-electric field, (6) 150*h*.
method for tempering bricks, P (10) 248*c*.
sound absorption in TiO_2, (6) 150*h*.
plane, from plane ferrite surfaces, (4) 86*i*.
propagation along glass tubes, (8) 192*f*.
space-charge theory, (7) 178*d*.
spin, in $Ga_xFe_{2-x}O_4$, (5) 124*e*.
surface acoustic, at Au on $LiNbO_3$ boundaries, (5) 123*b*.
surface spin, in NiO, (6) 152*f*.
Weathering, of dolomite lime mortars, (5) 103*f*.
Weighing and weights. See also *Balances; Thermogravimetry*.
bulk, of portland cement clinker, (4) 79*d*.
change, revised, in ZrO_2, (2) 49*h*.
molecular, of isopolytungstate ions, (6) 150*f*.
system, fluent material, P (10) 254*j*.
Welding, device, ultrasonic, P (4) 91*b*.
diffusion, metal wire to graphite, (10) 249*a*.
electric, glass sheets, P (4) 81*g*.
electrodes. See *Electrodes*.
electroslag, guide tube for, P (3) 54*i*.
flux, P (4) 80*a*.
composition, P (8) 189*d*.
for light alloys, P (4) 80*c*.
reaction, of ceramics, (8) 199*g*.
SiO_2-clay tooling material for, P (4) 80*b*.
tubular glass rods, P (3) 57*g*.
Wetting, diamond and graphite, (10) 259*f*.
SiC crystals by metallic melts, (9) 239*c*.
of TaC by liquid Cu and Ag, (4) 80*a*.
Whiskers. See also *Crystals*.
Al_2O_3, P (8) 196*h*.
ceramic, furnace for, P (10) 256*f*.
growth on KBr single crystals, (7) 182*b*.
MgO, P (4) 84*d*.
Whiteware. See also *Art and artware; Bodies, ceramic; Bone china; Dielectrics; Dinnerware; Heating elements; Insulators, electrical; Porcelain; Pottery; Tile*.
ashtrays, smoker's P (7) 166*b*.
containers, Pb in, (7) 165*d*.
decorative ceramic ware, P (11) 273*c*.
industry, automatic batching, in W. Germany, (5) 110*h*.
automation in, (2) 37*h*.
environmental problems in, (3) 61*i*.
plant production, increase, (1) 9*j*.
mfg., control testing in, (11) 272*i*.
prosthetic joint, P (5) 111*f*.
silk screening, (4) 85*i*.
valve plates of mixing valve, liner for, P (8) 198*d*.
Willemite, films, structure on Si, (7) 168*d*.
Windows. See *Glass*.
Windshields. See *Glass*.
Wire, beam-lead, for semiconductor packages, P (11) 275*g*.
enameled, oven used in mfg., P (1) 17*c*.
grid, fusion sealing i:. tube, P (3) 59*d*.

Wire *(continued)*
metal, as reinforcing for furnace lining, (7) 163*g*.
metal, welding to graphite, (10) 249*a*.
micro-, casting in glass insulation, P (1) 4*i*; P (7) 162*e*.
micro-, glass-coated, glass for, P (2) 34*g*.
welding. See *Welding*.
Wollastonite, deposit in Japan, (6) 143*g*.
synthetic, in ceramic bodies, (1) 10*h*.
Wurtzite, structure, thermal stability, (3) 76*a*.
-type crystals, Raman effect in, (5) 120*i*.
Wustite, electrical properties, (9) 233*g*.
lattice parameter, high-temp. measurement, (4) 97*f*.

X rays, analysis, advances in, B (1) 26*e*; B (9) 239*i*.
fluorescent, (10) 255*d*.
of glass, (3) 57*c*.
of strain effects on Se, (11) 268*j*.
analyzer, collimator for, P (2) 44*i*.
camera, specimen alignment for, P (4) 93*g*.
characteristics of Ca_2SiO_4, (5) 104*d*.
collimator, with fiber optic light, P (4) 83*b*.
controlling temp. of sample during, P (6) 142*a*.
of crystal microstructure, P (4) 93*d*.
detection of Cr_2O_3 and V_2O_5 in mixtures, (9) 239*f*.
determination of calcite-dolomite, (1) 26*c*.
diffraction, of alkali titanate glasses, (2) 33*h*.
of α-Al_2O_3 ceramics, (11) 281*c*.
analysis, of CaO degree of burning, (5) 102*e*.
analysis of mineral phases, (1) 18*e*.
analysis of portland cement, (5) 104*f*.
apparatus, P (2) 45*c*.
of $BaTiO_3$, Ti-rich, (1) 12*a*.
of BeF_2 and alkali fluoberyllate glasses, (2) 33*j*.
of brick clays, (6) 141*i*.
of Ca aluminates, (7) 173*c*.
of $CrVO_4$ thermal expansion, (7) 181*d*.
data, for Ca_2SiO_4, (2) 48*g*.
equipment, safety standards, (10) 255*b*.
of glasses, (2) 33*h*.
for phase determination in cement, (5) 104*g*.
powder patterns, standard, (3) 70*c*.
of SiO_2-Al_2O_3-CaO system, (11) 278*h*.
of small diffusion zones, (5) 116*h*.
of Na borosilicate opalescence, (7) 160*e*.
of systems Ti-Ni-B, Mo-Ni-B, and W-Ni-B, (10) 261*g*.
of systems V-Cr-B, Nb-Cr-B, and Mo-Cr-B, (10) 261*h*.
of UO_2-W composite, (1) 16*d*.
diffractometer geometrical factors, effect on stress measurement, (7) 173*e*.
diffractometer, high temp., (3) 69*j*.
diffractometry, for detecting strains in Si, (10) 258*d*.
of high-Al_2O_3 glass, (3) 57*d*.
of thermal expansion, (7) 173*g*.
of U oxides, (11) 276*e*.
double crystal topography, of magnetic bubble domain garnets, (8) 199*j*.
emission analysis, of oxide films on Ta, (7) 179*i*.
films, noise in, (9) 231*h*.
fluorescence, to control glass material, (8) 192*c*.
to determine elements in silicate rocks, (9) 231*i*.
for spectrochemical analysis, B (9) 240*f*.
spectrometry, glass sample preparation for, (8) 205*h*.
use in silicate analysis, (9) 230*i*.
fluorescence analysis, P (3) 70*e*.
of cement raw mix, (9) 214*i*.
of glasses, (8) 191*c*.
matrix effects in, (7) 173*a*; (11) 278*a*.
of refractory raw materials, (8) 205*i*.
of Na_2O-CaO-SiO_2 glasses, (2) 32*j*.
of Na_2O-CaO-SiO_2 glass batch, (8) 205*c*.
inference patterns, obtaining, P (4) 93*f*.
intensities, measurement, (5) 116*g*.
K-absorption edge, of Nb, (6) 153*b*.
line broadening in agate, (3) 75*f*.
line broadening, of milling Al_2O_3 powder, (5) 125*g*.
line profile analysis of rutile, (11) 283*c*.
measurements, of particle orientation in clays, (6) 145*e*.
monochromatized, electron spectroscopy with, (8) 204*j*.
phase study of melts of salts of halides of metals and Tl, (5) 125*i*.
photography. See *Photography*.
powder camera, for microdiffraction, (9) 231*h*.
powder diffraction of Na sulfides, (11) 282*i*.
powder diffractometry, in mineralogy, (4) 92*j*.
quantitative determination, of montmorillonite, kaolinite, quartz, and alunite, (6) 142*d*.
radial distribution of high-Al_2O_3 glass, (5) 105*j*.
spectrometer. See *Spectrometers*.
spectrometric analysis, B (1) 28*e*.
stress-measuring apparatus, P (5) 116*h*.
study, of decomposition of ZrO_2-based solid solution, (8) 211*g*.
of ferrocyanides of In with K, Rb, and Cs, (8) 211*j*.
of phosphates and H phosphates of Pr, Sm, and Yb, (8) 211*i*.
of phosphates of Pr, Sm, and Yb, (8) 211*i*.
of $(Na_{0.85}Li_{0.15})NbO_3$+6 mol% Li_2O ceramic, (1) 26*d*.

X rays, study *(continued)*
of system Al_2O_3-Na_2O, (11) 282*a*.
of systems SnI_2-MI (M=K,Rb,Cs), (8) 211*d*.
on C_3A, (3) 76*a*.
of Y fluoride bronze, new, (4) 96*j*.
of Y oxytungstate and oxytungstates of lanthanides, (8) 211*j*.
TV microscope, P (2) 45*c*.
topography, of defects in transistor structures, (9) 233*f*.
tube, with thin Be windows, P (3) 66*h*.

Young's modulus. See *Elasticity*.
Yttria. See *Yttrium, oxide*.
Ytterbium, hydroxide, magnetic properties, (8) 209*j*.
phosphates and hydrogen phosphates, (8) 211*i*.
phosphates, X-ray study, (8) 211*i*.
Yb^{3+}, luminescence in phosphates and vanadates, (2) 47*i*.
Yttrium, Al, chemical lapping, P (4) 87*j*.
borides, emissive properties, (10) 260*j*.
chloride, reaction with chlorides of Rb, Ba, Nd, and Gd, (5) 123*i*.
chloride, vapor pressure, (8) 210*b*.
chromate, optical emission in, (5) 121*f*.
chromite, exciton absorption spectra, (3) 73*g*.
iodates, thermal stability, (8) 211*a*.
oxide, broad emission and excitation bands in, (2) 47*c*.
chlorination, (9) 232*g*.
point defects in, (7) 182*a*.
sintered, dielectric properties, (1) 11*b*.
oxysulfate, Bi-activated, P (4) 87*f*.
oxytungstate, X-ray study, (8) 211*j*.
phosphate, Sm^{3+} in, (3) 72*h*.
Tb^{3+} and Ce^{3+} transition in, (3) 73*a*.
YVO_4, Tb^{3+} emission in, (7) 181*c*.
purification, P (5) 118*c*.
recovery by leaching, P (6) 144*g*.
separation from lanthanide, P (2) 46*f*.
systems. See *Systems*.
vanadate, broad emission and excitation bands in, (2) 47*c*.
multiple activation, (2) 48*b*.
YPO_4, and $YAsO_4$, Gd^{3+} EPR in, (5) 120*i*.
$YAlO_3$, Nd^{3+} optical spectra in, (7) 179*i*.
$Y_3Al_5O_{12}$, optical absorption, (5) 122*i*.
$Y_3Al_5O_{12}$ synthesis, (10) 249*a*.
$YBaZrTiO_3$, resistivity, (3) 63*e*.
YF_3 to Y_2O_3, hydrolysis reaction from, (11) 282*i*.
$YFeO_3$, susceptibility tensor, (5) 124*h*.
$Y_3Fe_5O_{12}$, anisotropy and magnetostriction constants, (11) 281*f*.
Y_3OCl_7:Yb^{3+}·Er^{3+}, efficiency, (3) 72*g*.
Y_3OCl_7:Yb^{3+}·Er^{3+}, luminescence, (3) 72*h*.

Zeeman effect, in absorption spectrum of ZnS, (5) 125*j*.
of Cr^{3+} fluorescence in $SrTiO_3$, (5) 125*j*.
in $ErFeO_3$, (5) 120*e*.
of excitons in Cu_2O crystals, (6) 150*d*.
Zeolites, A, synthesis, P (8) 207*i*.
agglomerate, P (4) 95*b*.
aluminosilicate, use in dewaxing, P (11) 279*g*.
crystalline, P (8) 207*d*.
crystalline A, P (10) 257*f*.
desiccant bodies, P (3) 72*b*.
esters, P (11) 280*c*.
explosive fragmentation, P (3) 71*i*.
faujasite-type, stabilization, P (1) 20*a*.
high-temp. phases, (9) 236*a*.
hydrothermal reaction with lime, (9) 214*b*.
ir spectra, (6) 149*a*.
ion exchange, P (10) 257*f*.
metal halide containing, P (6) 144*a*.
K content in, decreasing, P (5) 117*g*.
K-M, rare gases in, (2) 50*e*.
rare earth-hydrogen exchanged, P (10) 257*i*.
small particle size Z-14, P (3) 71*d*.
Na A and Na X, crystals, gel growth, (7) 177*g*.
Na, W-Z, synthesis, P (6) 144*g*.
supersiliceous, P (5) 117*j*.
synthetic crystalline, P (10) 257*e*.
synthetic, ion-exchange equilibria, (1) 23*e*.
type A, Si-enriched, (8) 206*i*.
X-, heats of absorption of H_2O vapor on, (1) 22*b*.
X and Y, Cu-exchanged, P (6) 144*c*.
Zinc, blende materials, CdS films on, (6) 146*f*.
borate, of low hydration, P (6) 144*h*; P (10) 258*a*.
diffusion, in GaAs, (4) 99*e*.
diffusion into GaP, P (7) 170*i*.
Ge phosphide, in optical devices, P (10) 244*a*.
niobates, (9) 239*g*.
oxide, P (6) 144*d*.
ceramics, nonohmic properties, (3) 74*c*.
crystals, P (2) 40*c*.
deposition on sapphire, P (9) 225*a*.
effect on grain growth in Al_2O_3, (1) 21*c*.
effect on sintering cement clinker, (9) 214*h*.
exciton-donor complex in, (6) 148*a*.
films, *c*-axis orientation, (7) 166*g*.
films, as transducer, (3) 63*c*.
high-grade, P (6) 143*j*.
I_6 donor electron in, (7) 181*a*.
luminescent transitions, (6) 150*c*.
photoluminescence, (6) 150*c*.
reduction, with CO, (6) 149*h*.
single crystals, growth, (3) 73*e*.
sintering studies, (3) 75*e*.
thermally shocked, strength, (9) 238*g*.
vaporization, (2) 47*b*.
vaporization rates, (6) 152*j*.
whiskers, platelets, and dendrites, (7) 167*d*.

Zinc *(continued)*
selenide crystals, P (10) 249*e*.
selenide, ZnS, or ZnS/ZnSe, junctions in, P (9) 227*h*.
sulfide, absorption spectrum, (5) 125*j*.
α-, refractive index, (5) 122*g*.
α-, and ZnO, refractive index, (5) 122*g*.
devices, ohmic contact to, P (2) 41*i*.
single crystals, traps in, (6) 147*i*.
sublimation, (4) 99*c*.
sulfide ion diffusion in, (7) 180*h*.
and telluride, crystals, (7) 182*c*.
thermodynamics, (4) 99*h*.
systems. See *Systems*.
titanate, for coatings, P (1) 3*a*.
Zn^{2+}, ion-exchange equilibria of zeolite with, (1) 23*e*.
$Zn_xFe_{3-x}O_{4-x}F_x$, spinel-type, (2) 49*b*.
$ZnSiP_2$ and $ZnGeP_2$ single crystals, (7) 177*j*.
Zircon. See also *Refractories; Zirconium, silicate*.
ceramics, electrical resistance and porosity, (8) 199*i*.
colors, Pr-doped, (1) 2*j*.
corrosion by alkaline vapors, (5) 109*f*.
for pavers in glass tank bottom, (5) 106*j*.
review, (11) 279*e*.
thermal dissociation and reassociation, (7) 179*j*.
and uses, (8) 207*b*.
Zirconia. See *Zirconium, oxide*.
Zirconium, boride, thermal diffusion, (4) 97*e*.
carbide, compacts, density, (10) 247*b*.
enthalpy and thermal capacity, (10) 259*d*.
reaction with Si powders, (11) 260*d*.
stability, (3) 75*b*.

Zirconium *(continued)*
carbides, nitrides, or borides, fibrous, P (8) 196*j*.
compounds, P (11) 279*j*.
-corundum, shaped articles, P (10) 248*h*.
diboride-$MoSi_2$ mixtures, hot-pressing, (2) 48*f*.
diboride, plastic deformation, (1) 24*d*.
dioxide, (6) 143*h*.
blackening in, (2) 49*j*.
in $CaO-ZrO_2$ system, (4) 98*j*; (6) 152*c*.
conductive properties, in thermal probe preparation, (7) 172*i*.
crystalline transformation, (3) 72*c*.
crystals, growth and etching, (5) 121*b*.
cubic, stability, (7) 180*h*.
electrical conduction in, (9) 235*a*.
electrical properties, (10) 258*i*.
electronic transport in, (9) 235*f*.
and HfO_2 compositions, P (4) 85*b*.
phase transformations in, (11) 282*d*.
nucleating agent in glass-ceramics, (4) 81*a*.
O diffusion in, (9) 237*i*.
production from zircon, (8) 195*b*.
-rare earth ceramics, P (5) 111*f*.
reaction with Bi_2O_3, (5) 123*e*.
reaction with CeO_2, (8) 195*c*.
sintering, (5) 123*h*.
solid-state reaction with CaO, (9) 235*c*.
stabilized cubic, (7) 179*g*.
stabilizing with Nd_2O_3, (8) 195*j*.
structure, at high temps., (8) 208*a*.
thermal-shock and impact resistance, (8) 195*h*.
transformation, (6) 146*h*.
transformation, kinetics and burst phenomenon in, (7) 178*b*.

Zirconium, dioxide *(continued)*
weight change in, (2) 49*h*.
droplets, combustion in N_2/O_2 mixture, (8) 210*b*.
mask, for semiconductor, P (10) 253*f*.
nitride and/or TiN jewelry, P (9) 222*i*.
nitrides, reaction with graphite, (3) 60*h*.
oxide, and Al_2O_3 abrasive, P (1) 1*g*.
high-purity, P (4) 94*j*.
sintered stabilized, P (1) 9*e*.
provanadate transitions, (11) 283*d*.
reaction with $SrTiO_3$, (1) 24*c*.
reaction with transition metals and B, (10) 260*g*.
in refractories, (8) 195*a*.
sulfate and ZrO_2, from Na silicozirconate, P (6) 144*c*.
sulfates and other compounds, P (10) 257*d*.
systems. See *Systems*.
tetrachloride, P (9) 232*j*.
titanate, properties, (1) 25*i*.
titanate, thermal expansion, compressibility, and polymorphism in, (9) 239*c*.
ZrO_2-CeO_2, densification and electrical conductivity, (3) 72*e*.
Zone melting, in NH_4NO_3, (3) 71*e*.
crucible-free, crystalline rod, P (3) 64*b*; P (6) 138*a*; P (9) 225*b*; P (11) 274*e*.
device for, P (7) 168*d*.
for growing Si crystals, P (7) 169*i*.
monocrystalline rod, P (3) 66*d*.
rod displacement, P (2) 39*b*.
crystalline rods, P (8) 200*b*, 201*e*,*j*.
device for heater movement in, P (4) 92*b*.
test, distribution of components after, (5) 120*a*.



1969 Supplement
Phase Diagrams for Ceramists

This volume adds 2083 phase equilibrium diagrams to those in the basic volume, *Phase Diagrams for Ceramists*, published in 1964. Together the two books provide 4149 phase equilibrium diagrams, organized and indexed for convenient reference.

Indexes for the new volume are cumulative, covering all diagrams in both the 1964 and 1969 compilations. There are 8270 entries in the subject index, of which 3970 are new. In the index to authors there are 1459 names. Of these there are six prolific scientists credited with more than 100 diagrams each.

Most popular subjects in the combined index are: SiO_2 with 280 listings, and KCl with 241. Following closely are: NaCl with 221, Al_2O_3 with 189 and CaO with 161.

Diagrams are organized in seven sections:

(*a*) metal-oxygen systems
(*b*) metal oxide systems
(*c*) systems with oxygen containing radicals
(*d*) systems containing halides only
(*e*) systems containing halides and other substances
(*f*) systems containing cyanides, sulfides, etc.
(*g*) systems containing water.

Phase Diagrams for Ceramists is a cooperative project; compiled by the National Bureau of Standards; drafted, edited and published by the American Ceramic Society.

Authors of the *1969 Supplement* are the same that compiled the 1964 volume, Ernest M. Levin, Howard F. McMurdie, and Carl R. Robbins, all of NBS. The editor is Miss Margie K. Reser, technical editor on the staff of the American Ceramic Society.

The 1964 basic volume, with 2066 diagrams and 33-page introductory section, including glossary of terms, discussion of the phase rule, interpretation of diagrams, experimental methods and selected bibliography, is available at $18 to non-members, $12 to members of the Society. Add $2 for each copy to be mailed outside the United States.

Data on 1969 Supplement

2083 phase equilibrium diagrams (70% published since 1960)
625 pages
200 metal-oxygen systems
450 oxide systems
1220 salt systems
80 sulfide systems
130 water-containing systems
275 pressure systems, including hydrothermal
60 systems drawn from literature data
3970 new entries in subject index
8270 total entries in subject index which covers both the 1964 edition and 1969 supplement.
1459 entries in the author index, of which 600 are new, appearing only in the 1969 supplement.

$25 to members of the American Ceramic Society
$30 to non-members
$20 to student members
Ohio residents add 4% sales tax
Add $2 for overseas mailing and postage

Order from
The American Ceramic Society
65 Ceramic Drive
Columbus, Ohio 43214